NeoRdRp: A comprehensive dataset for identifying RNA-dependent RNA polymerase

of various RNA viruses from metatranscriptomic data

Shoichi Sakaguchi[1], Syun-ichi Urayama[2], Yoshihiro Takaki[3], Kensuke Hirosuna[4], Hong Wu[1],

Youichi Suzuki[1], Takuro Nunoura[5], Takashi Nakano[1*], So Nakagawa[6*]

[1]Department of Microbiology and Infection Control, Faculty of Medicine, Osaka Medical and

Pharmaceutical University

[2]Laboratory of Fungal Interaction and Molecular Biology (donated by IFO), Department of

Life and Environmental Sciences, University of Tsukuba

[3]Super-cuttingedge Grand and Advanced Research (SUGAR) Program, Japan Agency for

Marine-Earth Science and Technology (JAMSTEC)

[4]Medical School, Osaka Medical and Pharmaceutical University, Takatsuki, Japan

[5]Research Center for Bioscience and Nanoscience (CeBN), Japan Agency for Marine-Earth

Science and Technology (JAMSTEC)

[6]Department of Molecular Life Science, Tokai University School of Medicine

[*]Address correspondence to:

tnakano@ompu.ac.jp (TNakano); so@tokai.ac.jp (SN)

Keywords

RNA virome, RNA-dependent RNA polymerase, hidden Markov model, metatranscriptome

Running headline: NeoRdRp for RdRp identification

Abstract

RNA viruses are distributed throughout various environments, and most RNA viruses have recently been identified by metatranscriptome sequencing. However, due to the high nucleotide diversity of RNA viruses, it is still challenging to identify novel RNA viruses from metatranscriptome data. To overcome this issue, we created a dataset of RNA-dependent RNA polymerase (RdRp) domains that are essential for all RNA viruses belonging to *Orthornavirae*. Genes with RdRp domains from various RNA viruses were clustered based on their amino acid sequence similarity. For each cluster, a multiple sequence alignment was generated, and a hidden Markov model (HMM) profile was created if the number of sequences was greater than three. We further refined the 426 HMM profiles by detecting the RefSeq RNA virus sequences and subsequently combined the hit sequences with the RdRp domains. As a result, a total of 1,182 HMM profiles were generated from 12,502 RdRp domain sequences, and the dataset was named NeoRdRp. Almost all NeoRdRp HMM profiles successfully detected RdRp domains, specifically in the UniProt dataset. Furthermore, we compared the NeoRdRp dataset with two previously reported methods for RNA virus detection using metatranscriptome sequencing data. Our methods successfully identified most of the RNA viruses in the datasets; however, some RNA viruses were not detected, as in the cases of the other two methods. The NeoRdRp can be repeatedly improved by adding new RdRp sequences and is applicable as a system for detecting various RNA viruses from diverse metatranscriptome data.

Introduction

Currently, many RNA viruses have been identified by deep sequencing of RNA from diverse

environmental samples (i.e., metatranscriptome) (Shi et al., 2018; Sakaguchi et al., 2020;

Orba et al., 2021). Indeed, various metatranscriptomic analyses have revealed that RNA

viruses, similar to human infectious viruses, such as coronaviruses, orthomyxoviruses, and

filoviruses, are present even in non-mammalian species, including fishes (Shi et al., 2018).

However, identifying RNA virus-derived sequences from metatranscriptome data is

challenging because of the low abundance of viral RNA in sequencing reads and the high

nucleotide diversity among RNA viruses (Cobbin et al., 2021). Thus, we have developed a

method of double-stranded RNA (dsRNA) sequencing named "fragmented and primer ligated

dsRNA sequencing" (FLDS) to enrich the RNA virus sequences in the cellular transcriptome

(Urayama et al., 2016, 2018; Hirai et al., 2021). Long dsRNAs are rare in eukaryotic cells;

therefore, they are mainly derived from the genomes of dsRNA viruses or replicative

intermediates of single-strand RNA (ssRNA) viruses (Kumar and Carmichael, 1998).

Moreover, FLDS enables us to obtain entire dsRNA sequences, including both termi, and to

reconstruct multi-segmented genomes of RNA viruses based on terminal sequence similarity

(Urayama et al., 2016). Accordingly, FLDS can enrich potential RNA virus genomes even

though their sequences are dissimilar to known RNA viruses. However, it remains difficult to

conclude RNA viral genomes based on FLDS data if genes specific to RNA viruses were not

found.

Viruses that utilize RNA as a genetic material form a monophyletic group named

Riboviria based on taxonomy annotation by ICTV (International Committee on Taxonomy of

Viruses, https://talk.ictvonline.org/). *Orthornavirae* is a major kingdom of *Riboviria*

containing all the dsRNA and ssRNA viruses — but excluding retroviruses — which harbor

RNA-dependent RNA polymerase (RdRp). RdRp genes can be used as markers for most

RNA viruses; however, their nucleotide and amino acid sequences vary greatly, and some of

them have been identified as fusion genes with other protein motifs (Černý et al., 2014; Wolf

et al., 2018; Koonin et al., 2020, 2021). Indeed, it is often challenging to identify RNA virus

genes, including the RdRp gene, even in the cases of the potentially complete viral genome

sequences obtained by FLDS based on a similarity search using BLAST (Basic Local

Alignment Search Tool) with major amino acid databases (e.g., nr database or RefSeq

database) (Jia and Gong, 2019; Urayama et al., 2020).

In RdRp domain sequences, there are eight conserved amino acid motifs; notably, the

sixth motif containing three amino acid residues, GDD, is highly conserved (Koonin, 1991).

Based on these RdRp sequence motifs, Wolf and his colleagues inferred the phylogeny of

4,617 RNA viruses (Wolf et al., 2018). However, the accuracy of the multiple alignment of

all RdRp amino acid sequences was disputed due to their diversity (Holmes and Duchêne,

2019; Wolf et al., 2019). Therefore, in order to obtain reliable multiple alignments of RdRp

sequences, it is necessary to create multiple sequence alignments for each group defined by a

shared high sequence similarity.

This study collected RdRp domain sequences from 23,410 RNA viruses and clustered

them based on their similarity to build 1,182 hidden Markov model (HMM) profiles. Since an

HMM profile is based on a multiple sequence alignment, it can identify distantly related

sequences more efficiently than a pairwise-based search (Mistry et al., 2021). Several

bioinformatics approaches using HMM have been devised to identify more distantly related

viruses, such as VirSorter2 (Guo et al., 2021) and RVDB-prot (Goodacre et al., 2018; Bigot

et al., 2019). Note that since those datasets were based on various proteins in RNA and DNA

viruses (Goodacre et al., 2018; Bigot et al., 2019), the protein motifs identified by these

programs are not necessarily specific to RNA viruses. Furthermore, this study analyzed RdRp

sequences of marine RNA viruses obtained by FLDS and revealed that our method

successfully detected RdRp domains more efficiently than the two approaches mentioned

above (i.e., VirSorter2 and RVDB-prot). The RdRp construction bioinformatics pipeline and

constructed RdRp dataset, including annotation, are publicly available online

(https://github.com/shoichisakaguchi/NeoRdRp).

Materials and Methods

<u>Data sets</u>

A total of 4,620 amino acid sequences containing RdRp domains annotated by Wolf and his

colleagues (Wolf et al., 2018) were downloaded from the NCBI (National Center for

Biotechnology Information) GenBank database. Additionally, we obtained 18,790 amino acid

sequences of 4,239 RNA viruses from the NCBI Virus database

(https://www.ncbi.nlm.nih.gov/labs/virus/vssi/) on June 9, 2021. These datasets are referred

to as Wolf-RdRps and NCBI-RNA-virus in this study, respectively.

The UniProt Knowledgebase (UniProtKB) containing manually curated protein

sequences and functional information concerning 565,928 genes [UniProtKB Reviewed

(Swiss-Prot) 2021-05-11] (Boutet et al., 2016) was used to validate and annotate our dataset.

The gene ontology (GO) molecular function of RdRp genes was GO:0003968 (RNA-directed

5'-3' RNA polymerase activity). In the UniProtKB database, 1,027 out of 565,928 amino

acid sequences were categorized as GO:0003968; of these, 836 were validated as RdRp-

containing genes (Supplementary Table 1).

In addition, potential RNA virus genome sequences obtained from the marine

metatranscriptomic analysis by fragmented and primer ligated dsRNA sequencing (FLDS)

were used as a benchmark dataset (Urayama et al., 2018). This dataset contains 228 RdRp

domains in 1,143 potentially complete RNA virus genomes. For each genome, open reading

frames (ORFs) longer than 30 nucleotides (starting with any sense codon) were predicted

using ORFfinder version 0.4.3, with the following options: -ml 30 -s 2 (available at

https://www.ncbi.nlm.nih.gov/orffinder/).

<u>Clustering based on amino acid sequence similarity</u>

Amino acid sequences were clustered using the CD-HIT program version 4.7 (Li and Godzik,

2006; Fu et al., 2012) with the following criteria: a similarity threshold of 60% and word size

of 4. A multiple sequence alignment was generated using the L-INS-i program in MAFFT

version 7.450 (Katoh and Standley, 2013). To select regions with solid statistical evidence of

shared homology for each multiple sequence alignment by replacing an amino acid in the

uncertainty regions with a gap (-) using Divvier version 1.0, with the default parameters (Ali

et al., 2019). In the multiple sequence alignment, if five or more amino acid positions

followed by more than 25% of the sequences consisted of gaps, the region was defined as a

boundary between two different domains. Then, the multiple sequence alignment was split at

the boundary using our in-house script. Multiple alignments of amino acid sequences were

visualized using WebLogo version 3.7.8 with the following options: -c chemistry -U

probability (Crooks et al., 2004).

<u>Creation of Hidden Markov Model (HMM) profiles</u>

For each multiple sequence alignment, an HMM profile was built using hmmbuild, part of

the HMMER3 package version 3.1b2 (Eddy, 2011) with default parameters. All HMM

profiles were then compressed into an HMMER3 searchable database using hmmpress in the

HMMER3 package with default parameters.

<u>HMM and BLAST search</u>

All HMM searches with HMM profiles were carried out using the hmmsearch program from

the HMMER3 package with default parameters and three sequence threshold E-values: "-E

1E-10", "-E 1E-20" and "-E 1E-30". Two hits in a sequence with gaps of less than 500 amino

acid length were merged using BEDTools version 2.30.0 (Quinlan and Hall, 2010) with a

"merge -d 500" option (Supplementary Fig. 1). The BLASTp program from the BLAST+

software suite version 2.12.0 (Camacho et al., 2009) was used with "-evalue 1e-10," "-evalue

1e-20," and "-evalue 1e-30" options.

<u>VirSorter2 and RVDB-prot</u>

VirSorter2 (Guo et al., 2021) was used with the option "--include-groups RNA," targeting the

search group set to RNA viruses only. The HMM profiles obtained from Reference Viral

Protein DataBase (RVDB-prot) version 22.0 (Bigot et al., 2019) were used with the

hmmsearch program.

<u>Computer resource</u>

A workstation PC (CPU, Intel Core i9-7980XE 2.60 GHz; Memory, 128 GB; Storage 19 TB

SSD) with Linux OS (Ubuntu 18.04.6 LTS) was used for benchmarking each bioinformatics

program.

Results

<u>Constructing RdRp HMM profiles</u>

The schematic procedure for constructing the RdRp HMM profiles is illustrated in Fig. 1.

The details of datasets and software used for the analysis are described in Materials and

Methods. First, we obtained the amino acid sequences of 4,620 RdRp genes and those with

the RdRp domain selected by Wolf and his colleagues (named Wolf-RdRps) (Wolf et al.,

2018). Next, we clustered the 4,620 amino acid sequences based on their sequence

similarities and then obtained 3,190 clusters. Clusters containing more than three sequences

(262 clusters in total) were used for the HMM profile construction. For each cluster, the

amino acid sequences were aligned. Since genes including RdRp domain may contain

multiple other domains, unreliable regions in the multiple sequence alignments were replaced

with gaps. Then, in the multiple sequence alignment, if five or more amino acid positions

followed by more than 25% of the sequences consisted of gaps, the region was split there and

divided into two multiple alignments. Subsequently, a multiple sequence alignment

consisting of more than nine amino acids was defined as a domain. For each domain, an

HMM profile was created, and a total of 426 HMM profiles were obtained. The script for the

above-mentioned bioinformatics procedure is available at the website:

https://github.com/shoichisakaguchi/NeoRdRp.

Furthermore, we conducted comprehensive similarity searches using the 426 HMM

profiles with 18,790 amino acid sequences of 4,239 RefSeq RNA virus genomes downloaded

from NCBI Virus (named NCBI-RNA-Virus). A total of 7,463 viral amino acid sequences

were obtained through the HMM search. The obtained amino acid sequences were combined

with Wolf-RdRps, resulting in 12,502 amino acid sequences named "NeoRdRp-seq."

Applying the same procedure for HMM construction (1st round shown in Fig. 1), we

clustered the NeoRdRp-seq dataset based on amino acid sequence similarity, resulting in

1,092 clusters (including 8,516 sequences). Note that 2,753 clusters (including 3,986

sequences) containing fewer than three sequences for each were excluded from the HMM

profile construction. The 1,092 clusters were processed as the same procedures, and 1,182

domains were extracted. Fig. 2 shows an example of the domain clearly indicating the well-

conserved protein motifs, DxxxxD, GxxxTxxxN, and GDD (Koonin, 1991). For each

domain, an HMM profile was created, and the 1,182 HMM profiles in total were obtained,

which were named "NeoRdRp-HMM" and are available at

https://github.com/shoichisakaguchi/NeoRdRp.

<u>Evaluating NeoRdRp-HMM and NeoRdRp-seq</u>

To evaluate NeoRdRp-HMM and NeoRdRp-seq, the amino acid sequences and annotation

information obtained from the UniProtKB Reviewed database were used. The dataset

consisted of 565,928 amino acid sequences, including 836 genes with RdRp domains (see

Materials and Methods and Supplementary Table 1). With the 565,928 amino acid sequences

as queries, we conducted comprehensive searches using hmmsearch or BLASTp, targeting

NeoRdRp-HMM or NeoRdRp-seq, respectively, with three different threshold E-values: 1E-

10, 1E-20, and 1E-30. The resulting data are summarized in Supplementary Table 2, and the

recall and precision rates calculated from them are summarized in Table 1. For both methods

and datasets, the smaller the E-value, the fewer the number of true-positive and false-positive

hits there were. In general, NeoRdRp-seq identified more genes with RdRp domain with

more false-positive sequences than NeoRdRp-HMM. For example, with the E-value 1E-10

threshold, 813 and 824 out of 836 genes with RdRp domain, and 246 and 1,316 out of

564,418 non-RdRp genes were detected using the NeoRdRp-HMM and NeoRdRp-seq

datasets, respectively. Furthermore, our dataset could identify genes with RdRp domain from

various RNA viruses, whereas 12 genes with RdRp domain (1.4%) derived from nine

Birnaviridae, two Reoviridae, and one Paramyxoviridae were not identified.

We also annotated NeoRdRp-HMM profiles based on the UniProtKB annotation of

Gene Ontology (GO; molecular function) with an E-value 1E-10 threshold. Out of 1,182

HMM profiles, 1,012 were evaluated; each hit was scored 1 if "RNA-directed 5'-3' RNA

polymerase activity" (GO:0003968) was included, and 0 if excluded. We then calculated the

mean value of the scores for each NeoRdRp-HMM profile, as summarized in Supplementary

Table 3. The mean score of the profiles was 0.92, suggesting that most NeoRdRp-HMM

profiles annotated using the UniProtKB search were derived from the RdRp domain

sequences of RNA viruses. However, we also found that 13 HMM profiles (1.3%) had a

score of 0; RNA binding [GO:0003723], ATP binding [GO:0005524], helicase activity

[GO:0004386], mRNA methyltransferase activity [GO:0008174], and hydrolase activity

[GO:0016787] were shared among the seven HMM profiles. The results indicated that these

HMM profiles with a score of 0 detected proteins that interact with RNA but do not contain

RdRp domains.

Comparing RdRp identification

We benchmarked the ability of NeoRdRp-HMM and NeoRdRp-seq to identify RNA viruses

using potentially complete RNA virus genome and genome segment sequences obtained by

FLDS associated with marine RNA viromes (Urayama et al., 2018). The data comprised

1,143 nucleotide sequences. Among these, 112,108 open reading frames (ORFs) longer than

30 nucleotides (i.e., 10 amino acids) were obtained (see Materials and Methods),

including 228 sequences annotated as genes with RdRp domain. The data set of the translated

amino acid sequences was named FLDS-data.

Using the FLDS-data, we evaluated NeoRdRp-HMM and NeoRdRp-seq using

hmmsearch and BLASTp, respectively. First, NeoRdRp-HMM and NeoRdRp-seq were

compared with E-values of 1E-10, 1E-20, and 1E-30; 181, 138, and 123 genes encoding

RdRp domain were found by both methods, respectively (Supplementary Fig. 2).

Furthermore, with the 1E-10, 1E-20, and 1E-30 E-values, none, 5, and 2 RdRp domain

sequences were detected only by NeoRdRp-HMM, whereas 18, 27, and 21 RdRp domain

sequences were by NeoRdRp-seq, respectively. The difference in RdRp identification

between the two methods could be explained by the advantage of the HMM search in the

detection of diversified RdRp domain sequences and the lower coverage of the current HMM

models because of the requirement of at least three sequences to create a new reliable HMM

profile.

We then merged the results of the NeoRdRp-HMM and NeoRdRp-seq searches into

NeoRdRp. Since NeoRdRp-seq may detect large false-positive hits with a low E-value

threshold (Table 1), the threshold E-value of the BLASTp search with NeoRdRp-seq was

fixed at 1E-30 in this search. VirSorter2 (Guo et al., 2021) and hmmsearch with RVDB-prot

(Goodacre et al., 2018) were used for comparison. Note that since VirSorter2 only accepts

nucleotide sequences as an input file, the original 1,143 nucleotide sequences of the FLDS-

data were used for VirSorter2. First, with a threshold E-value 1E-10 of hmmsearch, we

analyzed the 228 genes with RdRp domain using the three methods and detected them as

follows: 68 by all three methods, 116 by NeoRdRp and RVDB-prot, one by NeoRdRp and

VirSorter2, three by RdRp-prot and VirSorter2, three only by NeoRdRp, 17 only by RVDB-

prot, and 20 were not detected by any methods (Fig. 3). Although all hits by NeoRdRp-HMM

were also identified by RVDB-prot (Supplementary Fig. 3), viral genomes detected only by

NeoRdRp were classified into the family *Flaviviridae, Reoviridae*, and unclassified ssRNA

positive-strand viruses based on HMM patterns and genomic structures. However, the viral

genomes that the three methods could not detect were recognized as members of *Reoviridae*

and *Megabirnaviridae* (Urayama et al., 2018).

We also found 13 possible RdRp-containing sequences in the FLDS-data that were

not annotated previously. According to the NeoRdRp-HMM annotation, 13 RdRp domain

sequences were similar to those of *Picovirnaviridae*, unclassified viruses, or unclassified

dsRNA viruses (Supplementary Table 4). The results suggested that our dataset is useful for

detecting RdRps in metatranscriptome data that have been overlooked with previously

published bioinformatic pipelines.

We also compared the computational time required to search for RNA viruses in

FLDS-data using the three methods (Table 2): hmmsearch using NeoRdRp-HMM and

BLASTp using NeoRdRp-seq took 1 min 2 sec and 2 min 56 sec, respectively (i.e., 3 min and

58 sec in total for the NeoRdRp search); hmmsearch using RVDB-prot took 7 min 11 sec;

and search using VirSorter took 11 min 45 sec. Furthermore, the database size required for

each analysis was 0.37 GB for NeoRdRp, 1.61 GB for RVDB-prot, and 11.3 GB for

VirSorter2 (Table 2). The results indicated that the NeoRdRp dataset required a smaller

computational capacity than the other methods tested.

Discussion

Nucleic acid contamination from DNA viruses, hosts, and environments is an issue when

analyzing RNA viromes. To overcome this issue, techniques to selectively extract and

sequence RNA virus-derived nucleic acids, such as the FLDS method (Urayama et al., 2016;

Hirai et al., 2021), have been developed. However, it is still challenging to eliminate all

contamination from the sequencing data. Thus, in this study, RdRp genes, which are the

hallmark of RNA viruses, were comprehensively obtained (NeoRdRp-seq), and HMM

profiles of RdRp domains were constructed based on amino acid similarity (NeoRdRp-

HMM) (Fig. 1). Using this dataset, we successfully obtained various genes encoding the

RdRp domain from the FLDS-data (Fig. 3), while those of some RNA viruses could not be

detected (Table 1 and Fig. 3). In addition, although NeoRdRp-seq could be utilized as a

complement to RdRp-HMM, a BLASTp search using NeoRdRp-seq generated a relatively

large number of false-positive hits (Table 1). This is because an RdRp domain is sometimes

encoded in a fusion gene, and NeoRdRp-seq includes non-RdRp domain sequences of such

fusion genes. To overcome this problem, repeating updates with additional RdRp sequences

is necessary. In principle, as the number of RdRp sequences increases, the number of clusters

used for HMM construction also increases, and subsequently, the detection power must

increase. We designed the pipeline used for the NeoRdRp-HMM to create enhanced HMM

profiles by incorporating newly detected RdRp sequences. The pipeline for HMM

construction is available on GitHub (https://github.com/shoichisakaguchi/NeoRdRp).

Therefore, users can modify NeoRdRp-HMM using their own sequences. Accordingly,

continuing to update NeoRdRp-HMM with successively identified RdRp sequences would

reduce undetected RdRp sequences and false-positive hits.

The NeoRdRp dataset was based only on genes containing RdRp domains. Our

approach has advantages in the accuracy of RNA virus identification from highly diversified

metatranscriptome data, particularly for the presence of known viruses is not expected.

Meanwhile, since the NeoRdRp cannot identify non-RdRp genes in RNA viruses, the

NeoRdRp dataset can be applied for RNA virus detection and annotation from

metatranscriptome data as the following research design; assemble of metatranscriptomic

data, subsequent ORF search for each contig, and RdRp domain identification of each ORF

using NeoRdRp-HMM. If more RNA virus sequences are required, further searches using

NeoRdRp-seq are expected, although it may produce more false-positive hits (Table 1 and

Supplementary Table S2) and the process is relatively computationally intensive (Table 2).

Based on the combination of these methods and their scores, we can identify contigs

containing RdRp domain, suggesting that they are derived from RNA viruses. Furthermore,

FLDS can identify multi-segmented genomes of RNA viruses based on terminal sequence

similarity (Urayama et al., 2016). Therefore, if one contig is found to contain an RdRp

domain, other contigs with a similar sequence on their either termini are strongly implied to

be derived from RNA viruses. Further, in these contigs, other viral genes could be detected

using other computational programs and datasets, including VirSorter2 and RVDB-prot.

In conclusion, the NeoRdRp can detect various RdRps with a high degree of accuracy

(Table 1 and Fig. 3), and the dataset is very compact compared to other methods for RNA

virome searches (Table 2). All sequence data, annotations, and bioinformatics pipelines are

available on GitHub (https://github.com/shoichisakaguchi/NeoRdRp). Furthermore, by

updating the NeoRdRp with new RdRp sequences, it will be possible to find more RdRp

sequences with higher accuracy levels from various metatranscriptome data, which may

become an essential technique for discovering unknown RNA viruses.

Acknowledgments

This work was supported by KAKENHI Grant-in-Aid for Scientific Research (C) 20K06775

(to S.S. and S.N.); Early-Career Scientists 20K15685 (to S.S.); Challenging Research

(Pioneering) 18H05368 (to S.U., Y.T., and T.Nunoura); and Scientific Research on

Innovative Areas 16H06429 (to S.U. and S.N.), 16K21723 (to S.U. and S.N.), 16H06437 (to

S.U.), 19H04843 (to S.N.); and by AMED under grant numbers JP19fm0208009 (to S.U.),

JP20wm0325004 (to S.U.), and JP21wm0325004 (to S.U. and S.N.). The computing

resources were partially supported by the NIG supercomputer at the ROIS National Institute

of Genetics, Japan, and SHIROKANE at the Human Genome Center, the Institute of Medical

Science, the University of Tokyo, Japan.

References

Ali, R. H., Bogusz, M., and Whelan, S. (2019). Identifying Clusters of High Confidence

Homologies in Multiple Sequence Alignments. Mol. Biol. Evol. 36, 2340–2351.

Bigot, T., Temmam, S., Pérot, P., and Eloit, M. (2019). RVDB-prot, a reference viral

protein database and its HMM profiles. F1000Res. 8, 530.

Boutet, E., Lieberherr, D., Tognolli, M., Schneider, M., Bansal, P., Bridge, A. J., et al.

(2016). UniProtKB/Swiss-Prot, the Manually Annotated Section of the UniProt

KnowledgeBase: How to Use the Entry View. Methods Mol. Biol. 1374, 23–54.

Černý, J., Černá Bolfíková, B., Valdés, J. J., Grubhoffer, L., and Růžek, D. (2014).

Evolution of tertiary structure of viral RNA dependent polymerases. PLoS One 9,

e96070.

Christiam, C., Coulouris, G., Avagyan, V., Ma, N., Papadopoulos, J., Bealer, K., and

Madden, T.L. (2009). BLAST+: Architecture and Applications. BMC Bioinformatics 10,

421.

Cobbin, J. C., Charon, J., Harvey, E., Holmes, E. C., and Mahar, J. E. (2021). Current

challenges to virus discovery by meta-transcriptomics. Curr. Opin. Virol. 51, 48–55.

Crooks, G. E., Hon, G., Chandonia, J.-M., and Brenner, S. E. (2004). WebLogo: a

sequence logo generator. Genome Res. 14, 1188–1190.

Eddy, S. R. (2011). Accelerated Profile HMM Searches. PLoS Comput. Biol. 7,

e1002195.

Fu, L., Niu, B., Zhu, Z., Wu, S., and Li, W. (2012). CD-HIT: accelerated for clustering

the next-generation sequencing data. Bioinformatics 28, 3150–3152.

Goodacre, N., Aljanahi, A., Nandakumar, S., Mikailov, M., and Khan, A. S. (2018). A

Reference Viral Database (RVDB) To Enhance Bioinformatics Analysis of High-

Throughput Sequencing for Novel Virus Detection. mSphere 3.

doi:10.1128/mSphereDirect.00069-18.

Guo, J., Bolduc, B., Zayed, A. A., Varsani, A., Dominguez-Huerta, G., Delmont, T. O., et

al. (2021). VirSorter2: a multi-classifier, expert-guided approach to detect diverse DNA

and RNA viruses. Microbiome 9, 37.

Hirai, M., Takaki, Y., Kondo, F., Horie, M., Urayama, S.-I., and Nunoura, T. (2021).

RNA Viral Metagenome Analysis of Subnanogram dsRNA Using Fragmented and

Primer Ligated dsRNA Sequencing (FLDS). Microbes Environ. 36.

doi:10.1264/jsme2.ME20152.

Holmes, E. C., and Duchêne, S. (2019). Can Sequence Phylogenies Safely Infer the

Origin of the Global Virome? MBio 10. doi:10.1128/mBio.00289-19.

Jia, H., and Gong, P. (2019). A Structure-Function Diversity Survey of the RNA-

Dependent RNA Polymerases From the Positive-Strand RNA Viruses. Front. Microbiol.

10, 1945.

Katoh, K., and Standley, D. M. (2013). MAFFT multiple sequence alignment software

version 7: improvements in performance and usability. Mol. Biol. Evol. 30, 772–780.

Koonin, E. V. (1991). The phylogeny of RNA-dependent RNA polymerases of positive-

strand RNA viruses. J. Gen. Virol. 72 (Pt 9), 2197–2206.

Koonin, E. V., Dolja, V. V., Krupovic, M., and Kuhn, J. H. (2021). Viruses defined by

the position of the virosphere within the replicator space. Microbiol. Mol. Biol. Rev.,

e0019320.

Koonin, E. V., Dolja, V. V., Krupovic, M., Varsani, A., Wolf, Y. I., Yutin, N., et al.

(2020). Global Organization and Proposed Megataxonomy of the Virus World.

Microbiol. Mol. Biol. Rev. 84. doi:10.1128/MMBR.00061-19.

Kumar, M., and Carmichael, G. G. (1998). Antisense RNA: function and fate of duplex

RNA in cells of higher eukaryotes. Microbiol. Mol. Biol. Rev. 62, 1415–1434.

Li, W., and Godzik, A. (2006). Cd-hit: a fast program for clustering and comparing large

sets of protein or nucleotide sequences. Bioinformatics 22, 1658–1659.

Mistry, J., Chuguransky, S., Williams, L., Qureshi, M., Salazar, G. A., Sonnhammer, E.

L. L., et al. (2021). Pfam: The protein families database in 2021. Nucleic Acids Res. 49,

D412–D419.

Orba, Y., Matsuno, K., Nakao, R., Kryukov, K., Saito, Y., Kawamori, F., et al. (2021).

Diverse mosquito-specific flaviviruses in the Bolivian Amazon basin. J. Gen. Virol. 102.

doi:10.1099/jgv.0.001518.

Quinlan, A. R., and Hall, I. M. (2010). BEDTools: a flexible suite of utilities for

comparing genomic features. Bioinformatics 26, 841–842.

Sakaguchi, S., Nakagawa, S., Mitsuhashi, S., Ogawa, M., Sugiyama, K., Tamukai, K., et

al. (2020). Molecular characterization of feline paramyxovirus in Japanese cat

populations. Arch. Virol. 165, 413–418.

Shi, M., Zhang, Y.-Z., and Holmes, E. C. (2018). Meta-transcriptomics and the

evolutionary biology of RNA viruses. Virus Res. 243, 83–90.

Urayama, S.-I., Takaki, Y., Hagiwara, D., and Nunoura, T. (2020). dsRNA-seq Reveals

Novel RNA Virus and Virus-Like Putative Complete Genome Sequences from

Hymeniacidon sp. Sponge. Microbes Environ. 35. doi:10.1264/jsme2.ME19132.

Urayama, S.-I., Takaki, Y., Nishi, S., Yoshida-Takashima, Y., Deguchi, S., Takai, K., et

al. (2018). Unveiling the RNA virosphere associated with marine microorganisms. Mol.

Ecol. Resour. 18, 1444–1455.

Urayama, S.-I., Takaki, Y., and Nunoura, T. (2016). FLDS: A Comprehensive dsRNA

Sequencing Method for Intracellular RNA Virus Surveillance. Microbes Environ. 31, 33–

40.

Wolf, Y. I., Kazlauskas, D., Iranzo, J., Lucía-Sanz, A., Kuhn, J. H., Krupovic, M., et al.

(2018). Origins and Evolution of the Global RNA Virome. MBio 9.

doi:10.1128/mBio.02329-18.

Wolf, Y. I., Kazlauskas, D., Iranzo, J., Lucía-Sanz, A., Kuhn, J. H., Krupovic, M., et al.

(2019). Reply to Holmes and Duchêne, "Can Sequence Phylogenies Safely Infer the

Origin of the Global Virome?": Deep Phylogenetic Analysis of RNA Viruses Is Highly

Challenging but Not Meaningless. MBio 10. doi:10.1128/mBio.00542-19.

Fig. 1. A schematic workflow of NeoRdRp-HMM construction

(1st Round, left) Amino acid sequences containing RdRp domains in the Wolf-RdRps data

were clustered based on similarity. For each cluster, a multiple sequence alignment was

constructed and processed to create HMM profiles. (RdRp search, middle) The HMM

profiles were used to detect the RdRp domain of amino acid sequences in the NCBI-RNA-

Virus data. (2nd Round, right) The detected RdRp domain sequences were merged with the

Wolf-RdRps data, which were clustered and processed to create HMM profiles for RdRp

detection. The dataset names used in this study are in bold. Yellow, NeoRdRp-seq; orange,

NeoRdRp-HMM.

Fig. 2. An example of a multiple sequence alignment of amino acid sequences including RdRp domain.

The multiple sequence alignment of the HMM profile of 1981.alnta.divvy_RDRP_0.25_923-1375 (including seven sequences) was visualized using Weblogo software. The height represents the probability at each site, and the width is proportional to the number of sequences. Underlines in red indicate the well-conserved DxxxxD, GxxxTxxxN, and GDD motifs in RdRp domain at positions 192–197, 258–266, and 303–305, respectively.

Fig. 3. Venn diagram of three different methods for identifying RNA viruses.

Annotated marine metatranscriptome data were searched using NeoRdRp (NeoRdRp-HMM and NeoRdRp-seq), RVDB-prot, and VirSorter2. The number in each region indicates the number of hits by the method(s); for example, three were found only in NeoRdRp. Purple, NeoRdRp (NeoRdRp-HMM and NeoRdRp-seq); green, RVDB-prot; yellow, VirSorter2.

439 **Table 1. Recall and precision rates of NeoRdRp-HMM or NeoRdRp-seq searches for**

440 **each E-value threshold.**

	E-value ≤ 1E-10		E-value ≤ 1E-20		E-value ≤ 1E-30	
	Recall (%)	Precision (%)	Recall (%)	Precision (%)	Recall (%)	Precision (%)
NeoRdRp-HMM	97.2	76.8	96.8	84.8	96.2	85.0
NeoRdRp-seq	98.6	38.5	98.2	47.7	98.1	48.4
NeoRdRp	98.6	37.9	98.2	47.7	98.1	48.4

442 **Table 2. Database size and processing time of three methods for searching for RNA**

443 **viruses in FLDS data.**

Data	Tool	Database Type	Database Size (GB)	Speed
NeoRdRp-HMM/ NeoRdRp-Seq	hmmsearch/ BLASTp	HMM/ blast	0.36/ 0.02	1 min 2 sec/ 2 min 56 sec
RVDB-prot	hmmsearch	HMM	1.61	7 min 11 sec
VirSorter2	VirSorter2	VS2	11.13	11 min 45 sec

Supplementary Figure 1. Defining an RdRp domain.

When the detected sequence distance was less than 500 amino acid length in the hmmsearch

results, we regarded them as a single region as a domain.

Supplementary Figure 2. Comparison of NeoRdRp-HMM and NeoRdRp-seq.

NeoRdRp-HMM and NeoRdRp-seq with an E-values of (a) 1E-10, (b) 1E-20, and (c) 1E-30

were compared. Pink, NeoRdRp-HMM; purple, NeoRdRp-seq.

Supplementary Figure 3. Comparison of NeoRdRp-HMM and RVDB-prot.

NeoRdRp-HMM and NeoRdRp-seq with E-values of (a) 1E-10, (b) 1E-20 and (c) 1E-30

were compared. Pink, NeoRdRp-HMM; purple, NeoRdRp-seq; green, RVDB-prot.

Supplementary Table 1. 836 RdRp genes in the UniProt KB database.

(provided as an Excel File)

Supplementary Table 2. NeoRdRp-HMM or NeoRdRp-seq searches for each E-value

threshold.

(provided as an Excel File)

Supplementary Table 3. Summary of the scores for each NeoRdRp-HMM profile.

(provided as an Excel File)

469 **Supplementary Table 4. Unannotated RdRps in metatranscriptome data detected by**

470 **NeoRdRp.**