Data and text mining

LinkExplorer: Predicting, explaining and exploring links in large biomedical knowledge graphs

Simon Ott [1,], Adriano Barbosa-Silva [1] and Matthias Samwald [1,*]

[1] Institute of Artificial Intelligence, Medical University of Vienna, Vienna, 1090, Austria

[*] To whom correspondence should be addressed.

Abstract

Summary: Machine learning algorithms for link prediction can be valuable tools for hypothesis generation. However, many current algorithms are black boxes or lack good user interfaces that could facilitate insight into why predictions are made. We present LinkExplorer, a software suite for predicting, explaining and exploring links in large biomedical knowledge graphs. LinkExplorer integrates our novel, rule-based link prediction engine SAFRAN, which was recently shown to outcompete other explainable algorithms and established black box algorithms. Here, we demonstrate highly competitive evaluation results of our algorithm on multiple large biomedical knowledge graphs, and release a web interface that allows for interactive and intuitive exploration of predicted links and their explanations.

Availability and Implementation: A publicly hosted instance, source code and further documentation can be found at https://github.com/OpenBioLink/Explorer.

Contact: matthias.samwald -at- meduniwien.ac.at

1 Introduction

Link prediction is a field in graph-based machine learning that aims to predict novel relationships between entities. When applied to biomedical knowledge graphs, link prediction can be a versatile and powerful method of hypothesis generation, e.g. for drug discovery (Abbas *et al.*, 2021). A vast array of machine learning link prediction algorithms emerged over the last decade. Most of these are black boxes such as embedding- or deep learning based algorithms, where the rationale for a prediction is difficult or impossible to explain. Explainability, however, is important for facilitating scientific insight, judging the plausibility of predictions and improving acceptance by end-users (Adadi and Berrada, 2018).

Previous work on explainable link prediction (Meilicke *et al.*, 2019) has limitations that decrease its utility for real-world applications involving large biomedical knowledge graphs, such as lacking scalability, limited predictive performance, or lack of end-user interfaces for viewing and understanding predictions and their explanations.

To address these issues, we release the LinkExplorer software suite for predicting, exploring and explaining links in large knowledge graphs. It integrates SAFRAN (Ott *et al.*, 2021), a novel, state-of-the-art rule-based link prediction algorithm that our group developed.

SAFRAN is highly scalable, outperforms other explainable link prediction methods on standard link prediction benchmarks, narrows the performance gap between explainable and black-box algorithms, and produces highly condensed and transparent explanations (Ott *et al.*, 2021). The LinkExplorer suite offers a web-based interface for navigating existing links between entities and relations together with predicted links and their explanations generated by SAFRAN, thereby enabling unprecedented insight into the predictions of a state-of-the-art link prediction algorithm. We also report highly competitive evaluation results of our explainable link prediction algorithm on several large-scale biomedical knowledge graphs.

2 Software architecture and performance

LinkExplorer was realized using a client-server architecture and is implemented in Javascript and HTML5. The client was created using the ReactJS framework and the server-sided Javascript components are served using NodeJS. The server is used to provide predictions and explanations which are retrieved from SQLite databases generated by SAFRAN. SAFRAN uses logical first-order Horn clauses learned by the rule miner AnyBURL (Meilicke *et al.*, 2019) and clusters them to provide

improved predictions and explanations. Thus predictions can be explained in terms of which rules and which instantiations triggered that prediction. A detailed description of the SAFRAN algorithm is available in (Ott *et al.*, 2021). A screenshot of LinkExplorer providing explanations for the prediction *cytochrome P450 family 2 subfamily C member 18 can be overexpressed in liver* is shown in Figure 1. Furthermore, metadata of entities and relations of benchmark datasets such as labels, descriptions and types of entities are accumulated as RDF* (Hartig and Thompson, 2019) graphs and are served via a SPARQL* endpoint. In addition to loading predictions and benchmark metadata hosted on the server, users can load local prediction files generated by SAFRAN and load custom benchmark metadata by specifying external SPARQL* endpoints.

Fig. 1. Structured view of rules that triggered a prediction.

We make a public LinkExplorer instance available that hosts three large biomedical knowledge graphs: OpenBioLink (Breit *et al.*, 2020), Hetionet (Himmelstein *et al.*, 2017) and PheKnowLator (Callahan *et al.*, 2020). Additionally, the instance contains two widely-used general-domain evaluation datasets: WN18RR (Dettmers *et al.*, 2018) and YAGO3-10 (Dettmers *et al.*, 2018). As there is no publicly available dataset split of Hetionet and PheKnowLator, they were randomly split using a 90-5-5 split ratio per relation. Prediction files were generated by SAFRAN using rules that were learned by AnyBURL for 1000 seconds using 22 threads of a machine with 24 physical (48 logical)Intel(R) Xeon(R) CPU E5-2650 v4 @ 2.20GHz cores and 264 GB of RAM. Table 1 shows a comparison of the performance of LinkExplorer/SAFRAN with AnyBURL and established black-box models RESCAL (Nickel *et al.*, 2011), TransE (Bordes *et al.*, 2013), DistMult (Yang *et al.*, 2015), ComplEx (Trouillon *et al.*, 2016), ConvE (Dettmers *et al.*, 2018), RotatE (Sun *et al.*, 2019) on the before mentioned biomedical datasets and ogbl-biokg (Hu *et al.*, 2020). For training and extensive hyperparameter optimization of the latent models we used the PyTorch-based LibKGE framework (Broscheit *et al.*, 2020) and use a similar hyperparameter search space as in (Ruffinelli *et al.*, 2020). Data on the conducted hyperparameter search can be found in the supplemental material.

LinkExplorer/SAFRAN consistently improves upon the already highly competitive explainable link prediction algorithm AnyBURL, and closely matches or outperforms black-box models.

Table 1. Comparison of the fully explainable algorithms SAFRAN and AnyBURL with several established latent models on the datasets OpenBioLink, PheKnowLator, Hetionet and ogbl-biokg. SAFRAN (denoted with *) is our approach. The best overall results are marked in bold and the best explainable results are underlined.

	OpenBioLink			PheKnowLator		
Model	MRR	h@1	h@10	MRR	h@1	h@10
RESCAL	**.320**	.212	**.544**	.330	.261	.454
TransE	.280	.175	.500	.330	.245	.468
DistMult	.300	.193	.521	.351	.263	.492
ComplEx	.319	.211	**.547**	.362	.274	**.505**
ConvE	.288	.186	.510	.290	.200	.441
RotatE	.286	.180	.511	.272	.173	.431
AnyBURL (Maximum)	.277	.192	.457	.393	.352	.466
AnyBURL (Noisy-OR)	.159	.098	.295	.367	.323	.449
SAFRAN*	<u>.306</u>	<u>**.214**</u>	<u>.501</u>	<u>**.418**</u>	<u>**.383**</u>	<u>.483</u>

	Hetionet			ogbl-biokg		
Model	MRR	h@1	h@10	MRR	h@1	h@10
RESCAL	.306	.229	.456	.370	.257	.598
TransE	.255	.190	.386	.237	.090	.511
DistMult	.292	.220	.432	**.378**	.261	**.610**
ComplEx	.297	.223	.441	.371	.252	.600
ConvE	.251	.180	.393	.326	.204	.568
RotatE	.242	.171	.383	.318	.200	.560
AnyBURL (Maximum)	.369	.318	.469	.358	.280	.511
AnyBURL (Noisy-OR)	.229	.171	.345	.228	.166	.346
SAFRAN*	<u>**.381**</u>	<u>**.327**</u>	<u>**.484**</u>	<u>.373</u>	<u>**.293**</u>	<u>.530</u>

3 Discussion and future work

LinkExplorer demonstrates that high predictive performance can be achieved while retaining a high level of model explainability and transparency, attributes that are very desirable for biomedical hypothesis generation. Future work should focus on conducting empirical user studies of explanation methods to quantify and understand their utility in real-world biomedical research settings.

Funding

This work received funding from netidee grant 5171 ('OpenBioLink').

References

Abbas, K., Abbasi, A., Dong, S., Niu, L., Yu, L., Chen, B., Cai, S.-M., and Hasan, Q. (2021). Application of network link prediction in drug discovery. *BMC Bioinformatics*, **22**(1), 187.

Adadi, A. and Berrada, M. (2018). Peeking inside the black-box: A survey on explainable artificial intelligence (xai). *IEEE Access*, **6**, 52138–52160.

Bordes, A., Usunier, N., Garcia-Duran, A., Weston, J., and Yakhnenko, O. (2013). Translating embeddings for modeling multi-relational data.

Breit, A., Ott, S., Agibetov, A., and Samwald, M. (2020). OpenBioLink: a benchmarking framework for large-scale biomedical link prediction. *Bioinformatics*, **36**(13), 4097–4098.

Broscheit, S., Ruffinelli, D., Kochsiek, A., Betz, P., and Gemulla, R. (2020). LibKGE - A knowledge graph embedding library for reproducible research. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pages 165–174.

Callahan, T. J., Tripodi, I. J., Hunter, L. E., and Baumgartner, W. A. (2020). A framework for automated construction of heterogeneous large-scale biomedical knowledge graphs. *bioRxiv*.

Dettmers, T., Minervini, P., Stenetorp, P., and Riedel, S. (2018). Convolutional 2d knowledge graph embeddings. In *Thirty-Second AAAI Conference on Artificial Intelligence*.

Hartig, O. and Thompson, B. (2019). Foundations of an alternative approach to reification in rdf.

Himmelstein, D. S., Lizee, A., Hessler, C., Brueggeman, L., Chen, S. L., Hadley, D., Green, A., Khankhanian, P., and Baranzini, S. E. (2017). Systematic integration of biomedical knowledge prioritizes drugs for repurposing. *eLife*, **6**, e26726.

Hu, W., Fey, M., Zitnik, M., Dong, Y., Ren, H., Liu, B., Catasta, M., and Leskovec, J. (2020). Open graph benchmark: Datasets for machine learning on graphs. In *Advances in Neural Information Processing Systems*, volume 33, pages 22118–22133. Curran Associates, Inc.

Meilicke, C., Chekol, M. W., Ruffinelli, D., and Stuckenschmidt, H. (2019). Anytime bottom-up rule learning for knowledge graph completion. In *Proceedings of the Twenty-Eighth International Joint Conference on Artificial Intelligence, IJCAI-19*, pages 3137–3143. International Joint Conferences on Artificial Intelligence Organization.

Nickel, M., Tresp, V., and Kriegel, H.-P. (2011). A three-way model for collective learning on multi-relational data. In *Proceedings of the 28th International Conference on International Conference on Machine Learning*, ICML'11, page 809–816, Madison, WI, USA. Omnipress.

Ott, S., Meilicke, C., and Samwald, M. (2021). SAFRAN: An interpretable, rule-based link prediction method outperforming embedding models. In *3rd Conference on Automated Knowledge Base Construction*.

Ruffinelli, D., Broscheit, S., and Gemulla, R. (2020). You CAN teach an old dog new tricks! on training knowledge graph embeddings. In *International Conference on Learning Representations*.

Sun, Z., Deng, Z.-H., Nie, J.-Y., and Tang, J. (2019). Rotate: Knowledge graph embedding by relational rotation in complex space. In *International Conference on Learning Representations*.

Trouillon, T., Welbl, J., Riedel, S., Gaussier, E., and Bouchard, G. (2016). Complex embeddings for simple link prediction. In M. F. Balcan and K. Q. Weinberger, editors, *Proceedings of The 33rd International Conference on Machine Learning*, volume 48 of *Proceedings of Machine Learning Research*, pages 2071–2080, New York, New York, USA. PMLR.

Yang, B., Yih, S. W.-t., He, X., Gao, J., and Deng, L. (2015). Embedding entities and relations for learning and inference in knowledge bases. In *Proceedings of the International Conference on Learning Representations (ICLR) 2015*.