MT-MAG: Accurate and interpretable machine learning for complete or partial taxonomic assignments of metagenome-assembled genomes

Wanxin Li[1,*], Lila Kari[1], Yaoliang Yu[1], Laura A. Hug[2]

1 School of Computer Science, University of Waterloo, Waterloo, Ontario, Canada
2 Department of Biology, University of Waterloo, Waterloo, Ontario, Canada

* wanxin.li@uwaterloo.ca

Abstract

We propose MT-MAG, a novel machine learning-based software tool for the complete or partial hierarchically-structured taxonomic classification of metagenome-assembled genomes (MAGs). MT-MAG is capable of classifying large and diverse metagenomic datasets: a total of 245.68 Gbp in the training sets, and 9.6 Gbp in the test sets analyzed in this study. MT-MAG is, to the best of our knowledge, the first machine learning method for taxonomic assignment of metagenomic data that offers a "partial classification" option. MT-MAG outputs complete or partial classification paths, and interpretable numerical classification confidences of its classifications, at all taxonomic ranks. To assess the performance of MT-MAG, we define a "weighted classification accuracy," with a weighting scheme reflecting the fact that partial classifications at different ranks are not equally informative. For the two benchmarking datasets analyzed (genomes from human gut microbiome species, and bacterial and archaeal genomes assembled from cow rumen metagenomic sequences), MT-MAG achieves an average of 80.13% in weighted classification accuracy. At the Species level, MT-MAG outperforms DeepMicrobes, the only other comparable software tool, by an average of 35.75% in weighted classification accuracy. In addition, MT-MAG is able to completely classify an average of 67.7% of the sequences at the Species level, compared with DeepMicrobes which only classifies 47.45%. Moreover, MT-MAG provides additional information for sequences that are not completely classified at the Species level, resulting in the partial or complete classification of 95.15%, of the genomes in the datasets analyzed. In particular, MT-MAG classifies, on average, 88.84% of the test sequences to the Phylum level, 88.39% to the Class level, 86.81% to the Order level, 81.17% to the Family level, and 71.13% to the Genus level.

Introduction

Metagenome assembled genomes (MAGs) are a technological innovation that has allowed detailed insights into environmental microbial communities, and has strengthened understanding of the uncultured majority of microorganisms ([1], [2]). Accurate taxonomic assignment for these environmentally-derived genomes is a necessary step for identifying populations, making connections across communities and environments, and anchoring hypotheses on metabolic function and roles in biogeochemical cycles ([3], [4]). To date, despite rapidly growing datasets and reference databases, the power of machine learning has not been effectively applied to this critical

task. Indeed, even though existing taxonomic assignment tools (e.g., CheckM [5], BERTax [6], GTDB-Tk [7]) have achieved good classification accuracies on benchmarked tasks, they are constrained by various limitations, as described in the following.

Alignment-based tools (e.g., GTDB-Tk [7]) require DNA sequences to be aligned to reference sequences to obtain sequence similarities [8]. In addition, alignment-based tools assume that homologous sequences are composed of a series of linearly arranged and more or less conserved sequence stretches, assumptions that may not always hold due to high mutation rates, frequent genetic recombination events, etc. [9]. Lastly, the utility of alignment-based tools is limited by their often prohibitive consumption of runtime and computational memory.

Genetic marker-based tools such as IDTAXA [3] and GTDB-Tk [7] rely on taxonomic markers (e.g., 16S ribosomal RNA genes, internal transcribed spacers) to identify microorganisms. The use of genetic marker-based tools is limited by the fact that partial genomes frequently lack major markers. The absence of major markers could be caused, e.g., by the genome not being sequenced to a sufficient depth to assemble well, resulting in markers of interest possibly missing from the assembly [10]. An additional reason could be that fragments carrying the markers do not bin with the rest of the genome, which is a frequent problem with 16S ribosomal RNA genes [11].

At the other end of the spectrum, alignment-free tools based on k-mer frequencies (e.g., DeepMicrobes [12], CLARK [13]) do not rely on alignment or genetic markers, and instead use k-mer frequencies as the input feature. However, existing k-mer-based tools are also limited by, e.g., the fact that they are only capable of taxonomic assignment at specific taxonomic levels (e.g., Genus, Species), and a lack of interpretability of their predicted taxonomic assignments.

To address these limitations we propose MT-MAG, a **m**achine learning-based **t**axonomic assignment tool for **m**etagenome-**a**ssembled **g**enomes. MT-MAG is an alignment-free and genetic marker-free tool, able to partially classify MAGs to the lowest taxonomic rank that it has confidence in, using a hierarchically-structured local classification approach. In addition, for a query genome, MT-MAG outputs not only a classification path, but also a numerical classification confidence of its prediction at each taxonomic rank. The main contributions of this paper are:

- **Partial Classification:** A novel feature of MT-MAG is that it outputs partial classifications for the sequences that it cannot confidently classify at the Species level. This results in an average of 95.15% of the genomes in the datasets analyzed being either partially or completely classified. In particular, MT-MAG completely classifies, on average, 88.84% of the test sequences to the Phylum level, 88.39% to the Class level, 86.81% to the Order level, 81.17% to the Family level, and 71.13% to the Genus level.

- **Interpretability:** MT-MAG outputs interpretable numerical classification confidences for its classifications, at all taxonomic ranks along the classification path. In addition, reliability diagrams are used to assess the quality of the training sets and determine the reliability of the MT-MAG classification confidences.

- **Weighted Classification Accuracy:** To assess the performance of MT-MAG, we introduce the "weighted classification accuracy," a performance metric defined as the weighted sum of the proportions of complete and partial classifications. To the best of our knowledge, this is the first metric that incorporates a weighting scheme which reflects the fact that partial classifications at different ranks are not equally informative.

- **Large Datasets:** MT-MAG is capable of classifying large and diverse metagenomic datasets. The two datasets analyzed in this paper are: genomes

from human gut microbiome species (training set 6.15 Gbp, test set 7.42 Gbp), and bacterial and archaeal genomes assembled from cow rumen metagenomic sequences (training set 239.53 Gbp, test set 2.18 Gbp).

- **Superior Performance:** MT-MAG achieves an average of 80.13% in weighted classification accuracy, for the datasets analyzed. In particular, at the Species level (the only comparable taxonomic rank with DeepMicrobes), MT-MAG outperforms DeepMicrobes by an average of 35.75% in weighted classification accuracy. In addition, MT-MAG is able to completely classify an average of 67.7% of the sequences at the Species level, compared to DeepMicrobes, which only classifies 47.45%.

Materials and Methods

Materials: Datasets and task description

Two different tasks were performed in the computational experiments of this study, called **Task 1** and **Task 2**. The dataset analyzed in Task 1 was selected for direct performance comparison purposes, as it was the dataset analyzed by DeepMicrobes [12]. More specifically, the MT-MAG training set in Task 1 was based on representative genomes from species in human gut microbiomes, and the test set comprised high-quality MAGs reconstructed from human gut microbiomes from a European Nucleotide Archive study [14]. The MT-MAG training set in Task 2 was based on representative and non-representative microbial genomes from GTDB r202, and the test set comprised 913 "draft" bacterial and archaeal genomes assembled from rumen metagenomic sequence data derived from 43 Scottish cattle [15].

The rationale behind the selection of DeepMicrobes for a benchmark comparison with MT-MAG is as follows. Like MT-MAG, DeepMicrobes is a machine learning-based alignment-free and genetic marker-free metagenomic taxonomic assignment tool that uses k-mer frequencies as input feature to predict taxonomic assignments of short reads at the Genus and Species level. DeepMicrobes has demonstrated better performance at the Species level classification, and better comparative accuracy in Species abundance estimation over other state-of-the-art tools, see [13, 16–20]. In addition, like MT-MAG, DeepMicrobes estimates classification confidences: The reads with classification confidences below a (constant) threshold are considered to be *unclassified reads*, while the rest are considered to be *classified reads*. Within the set of classified reads, the reads whose classified Species taxa are the same as their ground-truth Species taxa are considered to be *correctly classified reads*. Lastly, to the best of our knowledge, DeepMicrobes is the only other taxonomic assignment tool that enables probabilistic classification using machine learning classifiers and has attempted to classify large datasets (e.g., thousands of species), similar to MT-MAG's design goals.

As MT-MAG and DeepMicrobes have different requirements on their inputs, in that MT-MAG ideally requires the training sequences to be $> 10{,}000$ bp, while DeepMicrobes operates with short reads, the datasets were prepared separately for MT-MAG and DeepMicrobes.

We conclude these general remarks on the datasets used in this study with a discussion on the ground-truth labels that were used for both the training sets and test sets. We first note that the NCBI [21] labels are outdated, due to the lack of consensus on uncultivated taxa naming conventions [22]. In contrast, in GTDB a consistent naming scheme was achieved by naming uncultivated taxa as 'Genus name' sp1, 'Genus name' sp2, and so on [23]. Second, we note that GTDB provides a complete taxonomic hierarchy with no inconsistencies in naming, based on standardized phylogenetic distances used to define taxonomic ranks [24]. Third, we observe that the numerical

labels used by DeepMicrobes are not biologically meaningful, and cannot be extended to other datasets. In consequence, to obtain ground-truth labels for the training and test sets in this study, we opted for using the results of running GTDB-Tk [7], based on GTDB R06-RS202, April 27, 2021.

Task 1: Sparse training set

The dataset for Task 1 was specifically chosen so as to allow a direct comparison between the quantitative performance of MT-MAG and that of DeepMicrobes (see "Performance metrics"). Since the genomes that the training sets for Task 1 were based on comprise only 2.4 % of the GTDB at the Species level, in the remainder of the paper this task will be referred to as *Task 1 (sparse)*.

   We first note that we were unable to replicate the classification accuracies reported by DeepMicrobes, using the datasets and software provided in [12]. Absent the possibility to reproduce the results in [12] *ab initio*, and to give DeepMicrobes the best possible scenario for comparison, we opted for the alternative of using the already trained Species classification model reported in [12].

   The training set for the Species classification model provided by [12], consisted of reads extracted from 2,505 representative genomes of human gut microbial species. These genomes were identified previously by a large-scale assembling study of the species in human gut microbiomes, and are available at the FTP website `ftp://ftp.ebi.ac.uk/pub/databases/metagenomics/umgs_analyses`. This genome set comprised 1,952 MAGs, and 553 microbial gut Species-level genome representatives from the human-specific reference (HR) database. This 2,505 genome set was referred to in [12] as *"HGR."* Starting from HGR, DeepMicrobes [12] first assigned each species a numerical label from 0 to 2,504 (inclusive). Secondly, using the ART Illumina read simulator [25], 100,000 150 basepair (bp) paired-end reads were simulated from HiSeq 2500 error model with the mean fragment size of 200 and standard deviation of 50 bp per species. Thirdly, the simulated reads were trimmed from the $3'$ end to 75–150 bp in equal probability. Lastly, these trimmed simulated read sets with their numerical labels from 0 to 2504 (inclusive) were used as the input to DeepMicrobes. The total size of the training set of this Species classification model trained by DeepMicrobes is 56.03 Gbp.

   The test set of DeepMicrobes was prepared in [12] in a similar way to the training set, and it comprised twenty-thousand 75-150 bp trimmed paired-end 75-150 bp reads simulated using ART Illumina from 3,269 high-quality MAGs reconstructed from human gut microbiomes from a European Nucleotide Archive study titled "A new **g**enomic **b**lueprint of the **h**uman **g**ut **m**icrobiota" (GBHGM) [14]. The ground-truth taxonomic labels for the test set were derived by running GTDB-Tk. The total test set size for DeeMicrobes is 14.71 Gbp.

   The training set of MT-MAG was prepared as follows. Since MT-MAG uses an enhanced version of MLDSP as a subprocess (see "Methods: MT-MAG algorithm"), which achieves optimal performance when the input sequence length exceeds 10,000 bp, all contigs in HGR that were shorter than 5,000 bp were discarded. The remaining 14,358 contigs comprised the training set of MT-MAG, totalling 6.15 Gbp. The process by which MT-MAG handles the special case of imbalanced classes, and the special case of the input dataset being too large to be loaded in memory are described in Supplemental Information Section 1.3.

   The test set of MT-MAG comprised 3,269 full MAGs in GBHGM. The total size of the test set of MT-MAG is 7.42 Gbp.

   Finally, to compare the DeepMicrobes classification results with those of MT-MAG, we post-processed the numerical labels of the reads in the DeepMicrobes training set, as follows. Recall that the reads in the training set were simulated from real genomes in the HGR database. Post-processing the numerical label of a read in the training set

entailed using GTDB-Tk to obtain the GTDB ground-truth label of its originating genome, and this GTDB label was then associated to the numerical label of that read.

Task 2: Dense training set

The training sets used in Task 2 were based on genomes comprising 7.7% of GTDB taxonomy, hence this task will thereafter be referred to as *Task 2 (dense)*.

The training set of MT-MAG was prepared using GTDB R06-RS202. Note that the sizes of the genomes in GTDB are significantly larger than those of genomes in HGR. Most GTDB MAGs contain multiple contigs per genome. All contigs belonging to a given genome were pseudo-concatenated into a single sequence, by adding the symbol "O" between contigs, so as to avoid creating artificial k-mers at the junction of contigs. Then, 4 non-overlapping fragments of length 100,000 bp were selected from each such genome, using four random starts. The 4 obtained fragments belonging to the same genome were again pseudo-concatenated to form a *representative genomic fragment* for that genome. To ensure that we had a sufficient number of representative genomic fragments to perform cross-validation, the above sampling process was repeated 20 times for each genome, resulting in 20 separate representative genomic fragments with the same genome label. The total size of the training set of MT-MAG is 239.53 Gbp. The process by which MT-MAG handles the special case of imbalanced classes, and the special case of the input dataset being too large or too small, are described in Supplemental Information Section 1.3.

Regarding the preparation of the training set of DeepMicrobes, we note that the only way to enable the DeepMicrobes model to handle the training stage of Task 2 (dense) (training set comprising 49,871 species) is to increase the size of k-mer. However, according to our computational experiments, $k = 12$ is the largest value that can be handled by a 24Gb GPU memory. Thus, to make the benchmarking comparison with MT-MAG possible, we opted to include in the DeepMicrobes training set only reads belonging to the 601 Species present in its test set. Note that this design choice gives DeepMicrobes a significant advantage, since it now has to choose its predicted answers only from a small output space of 601 correct labels, while MT-MAG has to search for the correct answers in a large output space of 49,871 Species labels. Most likely, this advantage boosts the classification accuracy for DeepMicrobes by a large amount. Note also that, as a consequence of this design decision, the total size of the training set of DeepMicrobes is now significantly smaller than that of MT-MAG.

Following this design choice, the training set of DeepMicrobes was prepared from the representative and non-representative genomes of the afore-mentioned 601 species, in a similar way to the training set of DeepMicrobes in Task 1 (sparse). Approximately thirty-thousand 75-150 bp paired-end reads were simulated per species, and each species was assigned a numerical label between 0 and 600 (see Supplemental Information Section 1.4 for details).

The test set of MT-MAG comprised 913 full microbial genomes from metagenomic sequencing of cow rumen, which were derived from 43 Scottish cattle [15]. The total sequence length of the test set of MT-MAG is 2.18 Gbp.

The test set of DeepMicrobes (reads) was prepared from the 913 full microbial genomes [15], in a similar way to the test set of DeepMicrobes in Task 1 (sparse). In the end, 10,000 75-150bp trimmed simulated paired-end reads per MAG were generated as the input to DeepMicrobes. The total size of the test set of DeepMicrobes is 2.04 Gbp, and 18,143,340 reads were simulated.

Table 1 provides a summary of the total number of basepairs analyzed, number of FASTA files, and number of contigs or reads for training and test sets in Task 1 (sparse) and Task 2 (dense), for MT-MAG and DeepMicrobes.

Table 1. Summary of total number of basepairs analyzed, number of samples and number of contigs or reads for the training and test sets in Task 1 (sparse), and Task 2 (dense) for MT-MAG and DeepMicrobes.

Task ID	Dataset type	Tool	Total sequence length	# of FASTA files	# of contigs/reads
Task 1 (sparse)	Training	MT-MAG	6.15 Gbp	2,505	314,840
		DeepMicrobes	56.03 Gbp	5,010	498,086,752
	Test	MT-MAG	7.42 Gbp	3,269	245,564
		DeepMicrobes	14.71 Gbp	6,538	130,760,000
Task 2 (dense)	Training	MT-MAG	239.53 Gbp	635,248	2,540,992
		DeepMicrobes	4.02 Gbp	1,202	35,765,154
	Test	MT-MAG	2.18 Gbp	913	158,102
		DeepMicrobes	2.04 Gbp	1,826	18,143,340

Methods: MT-MAG algorithm

This section describes the hierarchically-structured local classification approach used by MT-MAG, the eMLDSP subprocess that is at the core of MT-MAG, and the two main phases of MT-MAG (training and classifying).

A hierarchically-structured local classification approach

Taxonomic assignment is a problem of hierarchical classification, whereby input items are grouped according to a hierarchy. A hierarchy can be formalized as a directed acyclic graph where every node can be reached by a unique path from the root node (see Figure 1). In machine learning, there are generally three types of approaches to hierarchical classification [26]. The simplest approach is *flat classification* where all parent nodes are ignored, and a single classifier is trained to classify each instance directly into a leaf node. The second approach is the so-called *big bang* classification where a single classifier is trained for all nodes in the hierarchy. The third approach is the *hierarchically-structured local classification*, whereby one multi-class classifier is trained for each parent-to-child relationship. This third approach is an iterative classifying process where instances classified to a child node are then further classified with the next-level classifier, where the child node is now the parent node for the next-level classifier.

Fig 1. A sample hierarchy (taxonomy) with three parent-to-child relationships. A parent node with all its children nodes forms a parent-to-child relationship. A parent node without a child node is called a leaf node. The level of a node is the length of path from that node to the root node. The part highlighted in red is a multi-child classification, while the part highlighted in cyan is a single-child classification.

In contrast with DeepMicrobes which uses flat classification, MT-MAG uses hierarchically-structured local classification, for reasons detailed below. First, in the case of flat classification, an erroneous classification of a DNA sequence directly at the

Species level is more likely, due to the very large number of classes at the Species level. This, in turn, results in a higher likelihood of placing the sequence into an erroneous higher-level taxonomic rank, e.g., Order. Such a serious misplacement is less likely to happen with hierarchically-structured local classification, whereby a sequence passes through multiple classifications, from higher to lower taxonomic ranks, thus providing multiple check-points for the identification of an incorrect classification. For example, an incorrect Order classification could be prevented if any of the classifications prior to and including this level are deemed "uncertain."

In addition, in the case of flat classification, if the classification confidence of a sequence into a Species taxon does not meet the required confidence level, this sequence is simply deemed "unclassified," with no further information being provided. In contrast, the hierarchically-structured local classification provides the option of partial classification and can output partial classification paths for such sequences, even if their Species level classification is uncertain.

Finally, flat classification requires significantly more computational time and memory resources, because it involves a single big classification task wherein all the training sequences are loaded into memory simultaneously. In contrast, a hierarchically-structured local classification approach involves multiple smaller classification tasks and, for each classification task, one only needs to load into memory the sequences pertaining to the specific parent taxon being classified at this step in the hierarchy. In particular, for classifications at higher taxonomic ranks, one can use, e.g., only representative genomes as opposed to all of the genomes available for that parent taxon.

The enhanced MLDSP (eMLDSP) subprocess

MT-MAG uses an enhanced version of MLDSP, an alignment-free software tool that combines supervised machine learning techniques with digital signal processing for ultrafast, accurate, and scalable genome classification at all taxonomic ranks [27].

The inputs to MLDSP are pseudo-concatenated DNA sequences, together with their ground-truth taxonomic labels. After selecting a value for the parameter k, each such input DNA sequence is converted into a numerical vector containing the counts of all of its k-mers, where a k-mer is defined as a DNA subsequence of length k that does not contain the symbol "O" (used during the pseudo-concatenation process), or the symbol "N" (representing an unidentified nucleotide). Each k-mer count vector is then converted into a k-mer frequency vector, via dividing its k-mer counts by the total length of the sequence (excluding "O"s and "N"s). These k-mer frequency vectors are the input to MLDSP.

MLDSP consists of two main steps: (a) *Pretraining*, whereby several different classifiers' performance is evaluated by 10-fold cross validation, and (b) *Classify*, whereby MLDSP first trains the classifiers using the entire training set *(Classify-Training)*, and then classifies new DNA sequences in the test set *(Classify-Classification)* (see Supplemental Information Section 2.1).

MT-MAG uses an enhanced version of MLDSP, called *eMLDSP* (enhanced MLDSP) as a subprocess. The eMLDSP subprocess augments MLDSP in several significant ways. First, it augments MLDSP by adding the capability to handle the special case where the parent taxon has only one child taxon, as well as by adding the new feature of computing classification confidences for its classifications. Second, it adds an stopping threshold picking algorithm, called "STP algorithm," which is at the core of the partial classification option feature of MT-MAG. Specifically, the STP algorithm provides an individual stopping threshold for each parent-child pair, at each taxonomic level, as opposed to the one-size-fits-all stopping threshold of DeepMicrobes at the Species level. Third, eMLDSP combines the hierarchically-structured local classification with the

Fig 2. *Overview of eMLDSP*, including the main steps that comprise eMLDSP (Pretraining) (lavender box), eMLDSP (Classify-Training) (blue box), and eMLDSP (Classify-Classification) (pink box). Ellipses represent computation steps. Rectangles represent inputs to, and outputs from, computation steps. The diamond represents a condition checking. Note that the training dataset consists of DNA sequences together with their taxonomic labels.

result of the STP algorithm to output "uncertain classification," if the classification confidence is below the stopping threshold. Figure 2 provides an overview of eMLDSP, including the main steps to accomplish eMLDSP (Pretraining), eMLDSP (Classify-Training) and eMLDSP (Classify-Classification).

The MLDSP implementation of the algorithms assumes that the input DNA sequences belong to multiple child taxa (*multi-child classification*). If this is the case, in the eMLDSP (Classify-Training) step, a QSVM classifier called *fully trained QSVM* is trained, using the entire training set. In the eMLDSP (Classify-Classification) step, eMLDSP computes classifications (taxonomic assignments) for the DNA sequences in the test set by using the fully trained QSVM, and the classification confidences of these classifications using Platt scaling [28]. In contrast with its precursor, eMLDSP then applies five-fold cross-validation to obtain classifications, and uses a softmax-max transformation to compute classification confidences, for the entire training set.

Note that, when classifying a sequence belonging to a parent taxon, a single numerical classification confidence is computed for this classification, namely the confidence of classifying the sequence into the most likely child taxon of that parent taxon. This classification confidence is computed as the maximum of the posterior likelihoods over all child taxa. These results are later used for determining the stopping

thresholds for each pair of parent and child taxon. ₃₀₀

The case where the training/test sequences belong to a single child taxon ₃₀₁
(*single-child classification*) is not addressed by MLDSP. In this case, in the eMLDSP ₃₀₂
(Classify-Training) step, a QSVM classifier called *novelty QSVM* is trained, that uses ₃₀₃
the entire training set, and sets a fraction (default 10%) of the training set as a second ₃₀₄
child-class (called outlier taxon). In the eMLDSP (Classify-Classification) step, ₃₀₅
eMLDSP computes classifications for the DNA sequences in the test set by classifying ₃₀₆
using the novelty QSVM, and computes the classification confidences of these ₃₀₇
classifications by utilizing a normalizing logit transformation. The eMLDSP ₃₀₈
(Pretraining) step is not applicable here, since there is no need for picking stopping ₃₀₉
thresholds in the case of single-child classifications. ₃₁₀

The MT-MAG training phase and classifying phase ₃₁₁

MT-MAG comprises two phases, training and classifying, as described below (see ₃₁₂
Supplemental Information Section 2.3 and Section 2.4 for details of the two phases, and ₃₁₃
an additional optimization step that combines the two phases into a hybrid approach). ₃₁₄

The **MT-MAG training phase** (of the training set comprising contigs in the case of ₃₁₅
Task 1 (sparse), respectively representative genomic fragments in the case of Task 2 ₃₁₆
(dense), together with their ground-truth labels) comprises multiple training processes: ₃₁₇
For each parent taxon, after preparing the training set (discarding short sequences, ₃₁₈
handling imbalances in the dataset, etc.), two situations can occur, depending on the ₃₁₉
number of child taxa: ₃₂₀

- *Multi-child classification.* In contrast to DeepMicrobes which uses a single ₃₂₁
  stopping threshold, MT-MAG has multiple stopping thresholds, one for each ₃₂₂
  parent-child pair. ₃₂₃

  Concretely, MT-MAG determines a stopping threshold for every parent-child pair, ₃₂₄
  based on the confidences calculated by eMLDSP (Pretraining) with the training ₃₂₅
  set as input. MT-MAG selects the stopping threshold from a list of candidate ₃₂₆
  stopping thresholds, and searches for the stopping threshold T which results in ₃₂₇
  the fewest number of contigs (resp. representative genomic fragments) with ₃₂₈
  classification confidences lower than T, while at the same time resulting in the ₃₂₉
  classification accuracies of the other contigs (resp. representative genomic ₃₃₀
  fragments) being higher than the value of a user-specified accuracy parameter. ₃₃₁

  More specifically, a stopping threshold is the result of subtracting a "variability" ₃₃₂
  parameter from the maximum of *(a)* the minimum of the candidate thresholds ₃₃₃
  (numbers between 0 and 1) that result in a "constrained accuracy" being greater ₃₃₄
  than the value of a user-specified parameter (default: 90%), and *(b)* the average of ₃₃₅
  classification confidences for the contigs (resp. representative genomic fragments) ₃₃₆
  with correct eMLDSP (Pretraining) classifications. ₃₃₇

  Subsequently, a QSVM classifier (the fully trained QSVM) is trained with the ₃₃₈
  entire training set of this parent taxon, as part of the eMLDSP (Classify-Training) ₃₃₉
  step. ₃₄₀

- *Single-child classification.* A QSVM classifier called *novelty QSVM* is trained in ₃₄₁
  the eMLDSP (Classify-Training) step. The novelty QSVM sets a fraction of the ₃₄₂
  contigs (resp. representative genomic fragments) in the training set as a second ₃₄₃
  child-class, called *outlier taxon.* The default fraction is set to 10%. ₃₄₄

The **MT-MAG classifying phase** (of the test set comprising test genomes with known ₃₄₅
ground-truth labels, or unknown genomes) proceeds as follows. When, in the process of ₃₄₆

hierarchically-structured local classification, MT-MAG has classified a test/unknown genome into a parent taxon, and attempts to classify it further into one of its child taxa, two possibilities can occur:

- *Multi-child classification.* If the parent taxon has multiple child taxa, then the fully trained QSVM is used to classify the test/unknown genome into one of the child taxa, and this result is also used to compute a classification confidence as part of the eMLDSP (Classify-Classification) step. If this classification confidence is below the stopping threshold for this parent-child pair, then this classification is considered uncertain, and no further attempts are made to classify this test/unknown genome from the child taxon into its own child taxa.

- *Single-child classification.* If the parent taxon has a single child taxon, then the novelty QSVM is used to classify the test/unknown genome into either the child taxon or the outlier taxon as part of the eMLDSP (Classify-Classification) step, and the result is used to compute a classification confidence. If the output is the outlier taxon, then this classification is considered uncertain and no further classifications are attempted.

Given a test/unknown genome, the output of MT-MAG is either *(i)* a complete classification path down to the Species level, if all the intermediate classification confidences are greater than or equal to the stopping thresholds, or *(ii)* a partial classification path, down to the lowest taxonomic rank with a high enough classification confidence. In either case, the output of MT-MAG also includes the classification confidence for each taxon along the classification path.

Figure 3 illustrates the MT-MAG training phase and classifying phase for classifying two genomes belonging to a given parent taxon, into one of its two child taxa (multi-child classification). See the Supplemental Information Section 2.2 for a similar illustration of the single-child classification scenario.

MT-MAG multi-child classification pipeline

Fig 3. *MT-MAG pipeline for classifying two genomes, genome a and genome b, from the parent taxon Genus* Prevotella *into its two child taxa, Species* Prevotella sp900290275, *and Species* Prevotella stercorea *(multi-child classification).* Blue ellipses represent computation steps. Gray rectangles represent inputs to, and outputs from, computation steps. In the MT-MAG training phase (yellow box), the training set is prepared and given as the input to eMLDSP (Pretraining). The classifications and classification confidences outputted in eMLDSP (Pretraining) for the training set from all folds are used for determining the stopping thresholds for every child taxon of this parent taxon. Furthermore, in eMLDSP (Classify-Training), a fully trained QSVM is trained by using the entire training data. In the MT-MAG classifying phase (violet box), the test set is given as the input to eMLDSP (Classify-Classification), together with the fully trained SVM from the training phase. eMLDSP (Classify-Classification) outputs a classification and a classification confidence for each genome in the test set. Then, the classification confidence from eMLDSP (Classify-Classification) to classify a genome from the parent taxon into a child taxon is compared with the stopping threshold of that parent taxon and child taxon pair. If the classification confidence is lower than its stopping threshold, then the output is "uncertain classification" and further classification into children of this child taxon will not be attempted.

Results

In this section, we first describe the performance metrics used for measuring the 374
performance of MT-MAG, and for comparing it with DeepMicrobes. Second, we present 375
a detailed analysis of the novel features of MT-MAG: *(i)* the capability to classify a 376
DNA sequence at all taxonomic ranks, *(ii)* the capability to output an interpretable 377
classification confidence for the classification at each taxonomic rank along the 378
classification path, and *(iii)* the capability to output a "partial classification" path when 379
the classification confidence of a classification does not meet a given threshold. Third, 380
since DeepMicrobes is able to classify only at the Species level, we summarize the 381
results of a comparative analysis of the performance of MT-MAG with that of 382
DeepMicrobes at the Species level. Note that, in the comparative analysis, some 383
genomes were excluded from the test sets as follows: the genomes for which the GTDB 384
taxon is "unnamed species" were excluded in both Task 1 and Task 2, and the genomes 385
for which the ground-truth GTDB species did not exist in the training set were 386
excluded in Task 1 (see Supplemental Information Section 3.2). 387

Performance metrics 388

In this section, we define the terminology and the performance metrics used to discuss 389
and assess the performance of MT-MAG's classification of test genomes. 390

A classification of a genome x from taxonomic rank tr_1 to taxonomic rank tr_2, is 391
called *a classification at* tr_2. Given a taxonomic rank tr, we call the classification of x a 392
complete classification at tr, if the classification confidences of classifying x at all 393
taxonomic levels higher than and including tr, are greater than or equal to the 394
respective stopping thresholds. The classification of x is called an *uncertain* 395
classification at tr if the confidence of the classification at tr is strictly less than the 396
stopping threshold of this parent-child pair, and the confidences of the classifications at 397
ranks higher than tr are greater than or equal to their corresponding stopping 398
thresholds. If the classification is uncertain a rank higher than tr, we call it an 399
unattempted classification at tr. At the end of the MT-MAG classifying phase for an 400
input genome x, if the classification of x is uncertain at any taxonomic rank lower than 401
the first non-root rank, then we say that x is *partially classified*. On the other hand, if 402
the output of the classifying phase is that x is completely classified at the lowest 403
taxonomic rank (herein Species), then we say that x is *completely classified.* 404

We note that for a given test genome, the output of its classification at rank tr can 405
be only one of the following: complete classification at tr (if classifications all the way 406
down to tr exceed their thresholds), uncertain classification at tr (if classifications at all 407
higher ranks exceed their thresholds, but the classification at tr is below the threshold), 408
or unattempted classification at tr (if the classification at any rank higher than the one 409
right above tr is below the threshold). 410

Finally, we say that a classification of x is a *correct classification down to* tr if it is a 411
complete classification at tr, and a correct classification at all taxonomic ranks higher 412
than, and including, tr. By definition, all genomes have correct classifications down to 413
the root. 414

As an example, in Figure 4, the classification of genome x is a complete classification 415
at rank 1, an uncertain classification at rank 2, and an unattempted classification at 416
rank 3. In addition, if the ground-truth taxon of genome x at rank 1 is "rank 1 group 1", 417
then the classification of genome x is a correct classification at rank 1, as well as a 418
correct classification down to rank 1. Note that, for each classification of a parent taxon, 419
the number of stopping thresholds equals the number of that parent's child taxa. In 420
contrast, each such classification has associated with it a single classification confidence, 421
that of classifying the genome into a single, "best-guess," child taxon. 422

Fig 4. Example of the classification path for a genome x. The pre-calculated stopping thresholds are listed under the corresponding taxon labels. The classification confidences are listed inside blue-bordered rectangles. MT-MAG classifies x from root into "rank 1 group 1" with confidence 0.99, which is greater than the stopping threshold for "rank 1 group 1" (0.94), so MT-MAG continues its classification for x. In the next iteration MT-MAG classifies x from "rank 1 group 1" into "rank 2 group 2" with confidence 0.90, but since this is below the stopping threshold of the parent into its child "rank 2 group 2" (0.92), this classification is deemed "uncertain" and MT-MAG does not attempt further classifications. The path in cyan indicates complete classification(s), the path in yellow indicates uncertain classification(s), and the part in red indicates unattempted classifications.

With this terminology, for a given taxonomic rank tr, we define the following performance metrics (the subscript g indicates that these metrics refer to genomes):

- $CA_g(tr)$ (constrained accuracy): the proportion of the test genomes with correct classifications down to tr, to the test genomes with complete classifications at tr.

- $AA_g(tr)$ (absolute accuracy): the proportion of the test genomes with correct classifications down to tr, to all test genomes.

- $WA_g(tr)$ (weighted classification accuracy): the weighted sum of the proportions of the test genomes with correct classifications down to tr to all test genomes, the test genomes with uncertain classifications at tr to all test genomes, and the test genomes with unattempted classifications at tr to all test genomes. (Hereafter, *weighted classification accuracy* will sometimes be called just *weighted accuracy*.)

The weights are assigned as follows. Consider a list of increasingly lower taxonomic ranks $tr_0, tr_1, ..., tr_i$, where tr_0 is the root, and tr_i is tr. To calculate $WA_g(tr)$, the weight for a test genome with a correct classification down to $tr_i = tr$ (complete classification at tr_i, *and* a correct classification at tr_i) is 1. Otherwise, the weight of the test genome is j/i, where $0 \leq j < i$, if it has a correct classification down to tr_j, but does not have a correct classification down to tr_{j+1} (the latter condition avoids double counting). The underlying assumption is that

the test genomes are always assumed to belong to the root, and note that genomes that do not have correct classifications down to any taxonomic rank below the root are given weight 0.

This weighting scheme reflects the fact that partial classifications at different ranks are not equally informative. For example, a correct classification of a test genome down to the Phylum level is less informative than a correct classification of a test genome down to the Genus level.

- $CR_g(tr)$ (complete classification rate): the proportion of the test genomes with complete classifications at tr, to all test genomes.

The three accuracies $CA_g(tr), AA_g(tr)$ and $WA_g(tr)$ are numbers between 0 and 1, with $CA_g(tr) \geq AA_g(tr)$, and where higher values indicate better performance. The complete classification rate $CR_g(tr)$ is a number between 0 and 1, and a higher value indicates a higher proportion of genomes that are completely classified at tr. See Supplemental Information Section 3.3 for the formal definitions of these performance metrics.

MT-MAG novel features

Classifications at all taxonomic ranks

In contrast with DeepMicrobes which only classifies reads at the Species level, a significant feature of MT-MAG is its capability to classify genomes at all taxonomic ranks. Table 2 provides a summary of MT-MAG's performance metrics, at all taxonomic ranks, for both Task 1 (sparse) and Task 2 (dense). Table 3 provides a summary of the percentages of the test sequences completely classified by MT-MAG vs. classified by DeepMicrobes, at all taxonomic ranks.

Table 2. Summary of MT-MAG performance metrics at all taxonomic ranks, for Task 1 (sparse) and Task 2 (dense): constrained accuracy $CA_g(tr)$, absolute accuracy $AA_g(tr)$, weighted accuracy $WA_g(tr)$, and complete classification rate $CR_g(tr)$ (higher is better).

Task ID	Taxonomic Rank	$CA_g(tr)(\%)$	$AA_g(tr)(\%)$	$WA_g(tr)(\%)$	$CR_g(tr)(\%)$
Task 1 (sparse)	Phylum	100.00	93.80	93.80	93.80
	Class	100.00	93.80	93.80	93.80
	Order	99.56	91.99	92.59	92.40
	Family	100.00	82.67	87.93	82.67
	Genus	99.39	71.53	84.22	71.96
	Species	81.53	57.60	81.90	70.65
	Average	96.75	81.90	89.04	84.21
Task 2 (dense)	Domain	99.66	96.13	96.13	96.46
	Phylum	97.50	83.82	89.83	83.87
	Class	97.74	81.10	83.35	82.98
	Order	97.96	79.56	82.46	81.22
	Family	98.06	78.12	81.85	79.67
	Genus	96.70	67.96	78.94	70.28
	Species	98.63	63.87	78.36	64.75
	Average	98.03	78.36	83.56	79.89

In Task 1 (sparse) MT-MAG achieves an excellent performance at all taxonomic ranks from Phylum to Genus, with a slight drop in performance at the Species level (see

Table 3. Summary of percentages of test sequences completely classified by MT-MAG (quantified as $CR_g(tr)$) vs. classified by DeepMicrobes (quantified as CR_r), at all taxonomic ranks. A higher $CR_g(tr)$ (respectively CR_r) is better, as it signifies that a higher proportion of genomes (resp. reads) have been completely classified (resp. classified). Dash denotes not applicable.

Task ID	Taxonomic Rank	MT-MAG $CR_g(tr)(\%)$	DeepMicrobes $CR_r(\%)$
Task 1 (sparse)	Phylum	93.80	—
	Class	93.80	—
	Order	92.40	—
	Family	82.67	—
	Genus	71.96	—
	Species	70.65	45.02
Task 2 (dense)	Domain	96.46	—
	Phylum	83.87	—
	Class	82.98	—
	Order	81.22	—
	Family	79.67	—
	Genus	70.28	—
	Species	64.75	49.88

Table 2). Specifically, the MT-MAG constrained accuracies $CA_g(tr)$ are above 99% at all taxonomic ranks, except at the Species level $CA_g(Species)$, where they drop to 81.53%. The increase in the number of incorrect classifications at the Species level explains, in part, the 13.26% drop in weighted accuracy $WA_g(tr)$ from the Genus to the Species level. In addition, due to its partial classification capability, MT-MAG is able to completely classify 93.80% of the test genomes to the Phylum and Class levels, 92.40% to the Order level, 82.67% to the Family level, and 71.96% to the Genus level, with 70.65% of the test genomes being completely classified to the Species level (see Table 3). In contrast, in Task 1, DeepMicrobes classifies only 45.02% of the test reads at the Species level, and it does not assess other taxonomic levels.

In Task 2 (dense) MT-MAG has an excellent performance all around, with constrained accuracies $CA_g(tr)$ above 96% at all taxonomic ranks (see Table 2). In addition, due to its partial classification capability, MT-MAG completely classifies 83.87% of the test genomes to the Phylum level, 82.98% to the Class level, 81.22% to the Order level, 79.67% to the Family level, and 70.29% to the Genus level, with 64.75% of the test genomes being completely classified to the Species level (see Table 3). In contrast, in Task 2, DeepMicrobes only classifies 49.88% of the test reads to the Species level, and does not assess other taxonomic levels.

Overall, for the two benchmarking datasets, MT-MAG completely classifies an average of 67.7% of the test sequences (to the Species level). In addition, MT-MAG provides partial classifications for most of the remaining sequences. This results in 93.80% of genomes analyzed in Task 1 (sparse) and 96.46% of genomes analyzed in Task 2 (dense) being partially classified or completely classified. In particular, due to its partial classification capability, MT-MAG completely classifies on average 88.84% of the test sequences to the Phylum level, 88.39% to the Class level, 86.81% to the Order level, 81.17% to the Family level, and 71.13% to the Genus level.

Numerical classification confidences

In addition to the final classification path, MT-MAG also outputs numerical classification confidences along the classification path, indicating how confident MT-MAG is in the classification, at each taxonomic rank. For example, the final classification path for genome x, illustrated in Figure 4 is interpreted as MT-MAG

being 99% confident in classifying x from "root" to "rank 1 group 1," and 90% confident 497
in classifying x from "rank 1 group 1" to "rank 2 group 2." However, since the 498
confidence of the latter classification is strictly less than the pre-calculated stopping 499
threshold of 92%, this classification is deemed "uncertain" and no further classifications 500
are attempted for genome x. 501

As an example of a complete classification down to the Species level, in Task 2 502
(dense) the final classification path for genome hRUG888 is "Domain Bacteria 503
(confidence 97%) → Phylum Bacteroidota (confidence 97%) → Class Bacteroidia 504
(confidence 100%) → Order Bacteroidales (confidence 100%) → Family Muribaculaceae 505
(confidence 99%) → Genus *Sodaliphilus* (confidence 99%) → Species *Sodaliphilus* 506
sp900314215 (confidence 99%)." As an example of a partial classification path, the final 507
classification path for genome RUG412 is "Domain Bacteria (confidence 93%) → 508
Phylum Bacteroidota (confidence 100%) → Class Bacteroidia (confidence 100%) → 509
Order Bacteroidales (confidence 100%) → Family Muribaculaceae (confidence 98%) → 510
Genus *Sodaliphilus* (confidence 99%) → Species *Sodaliphilus* sp900318645 (uncertain)." 511
The last output means that MT-MAG is uncertain regarding its classification of 512
RUG412 from Genus *Sodaliphilus* into Species *Sodaliphilus* sp900318645. 513

Determining the reliability of the MT-MAG classification confidences 514

The selection of training sets is important for MT-MAG, since the composition of the 515
training sets affects both *(i)* the parameters of the classifier that is trained on the 516
training set and then used to classify unknown genomes, and *(ii)* the computation of 517
stopping thresholds used to stop classifications once they become uncertain. A tool that 518
can be used to determine whether the training sets are well selected and whether the 519
MT-MAG classification confidences are reliable estimates is the so-called *reliability* 520
diagram [29]. 521

Reliability diagrams plot the observed frequency of an event against the predicted 522
probability of that event (see Figure 5 for an example). In the case of taxonomic 523
classification, the event is a match between the ground-truth and the class assignment 524
predicted by the classifier under consideration. In a reliability diagram, the step-wise 525
lines (red in Figure 5) represent the reliability curves, that is, the observed frequency of 526
the event against the predicted probability of that event. The diagonal indicates a 527
perfect match between the observed frequency and predicted probability. A curve that 528
is closer to the diagonal (more specifically, where the total area formed by the curves 529
and the diagonal is smaller) indicates a better selected training set and a more reliable 530
classifier. Usually, a reliability diagram of a classification is accompanied by a *reliability* 531
score, which is a number greater or equal to zero (the smaller the number, the better 532
the reliability, with 0 being the best reliability score). 533

In the case of MT-MAG, the predicted probability is the classification confidence, 534
and a reliability diagram is an indicator of the suitability of the training set and of the 535
reliability of the classification confidences computed by MT-MAG. Consider for example 536
the scenario whereby MT-MAG classifies a training DNA fragment to be Domain 537
Bacteria with classification confidence 0.90. If the classification confidence matches the 538
observed frequency, then out of all the training DNA fragments classified by MT-MAG 539
as Domain Bacteria with classification confidence 0.90, we would expect roughly 90% to 540
have their ground-truth taxa to be Domain Bacteria. In the reliability diagram, this 541
match will be indicated by a point on the reliability curve that falls on or near the 542
diagonal. If the classification confidences do not match the observed frequencies, this 543
will also be observed on the reliability diagram, and could be an indicator that the 544
training set is imbalanced at some parent-to-child classification (some of the child taxa 545
have too few or too many training DNA fragments compared to the others) [30]. Note 546
that for analyzing MT-MAG, we actually used an extended version of reliability 547

diagrams, called *stable reliability diagrams* [31] (see Supplemental Information Section 3.4).

Figure 5 displays the reliability diagrams and reliability scores of two parent-to-child classifications for Task 2 (dense): (a) the parent taxon GTDB root into its two child taxa, Domain Bacteria and Domain Archaea, and (b) the parent taxon Family Campylobacteraceae into its five child taxa, Genus *Campylobacter*, Genus *Campylobacter_A*, Genus *Campylobacter_B*, Genus *Campylobacter_D*, and Genus *Campylobacter_E*. If we compare the two reliability diagrams, we first observe that the reliability curve for the classification of Family Campylobacteraceae deviates more from the diagonal than that for the classification of the GTDB root. Secondly, we observe that the 0.001 reliability score of the classification of the GTDB root is smaller than the 0.005 reliability score of the classification of Family Campylobacteraceae. Together, these indicators suggest that the training set of the GTDB root into its Domains is better selected, and its classification confidences are higher, than those of Family Campylobacteraceae into its five genera. Thus, for test/unknown genomes, we can expect more accurate classifications of the GTDB root to its child taxa than from Family Campylobacteraceae to its child taxa.

(a) Reliability diagrams for the classification of the GTDB root into Domains Bacteria and Archaea. Reliability score is 0.001.

(b) Reliability diagram for the classification the Family Campylobacteraceae into genera. Reliability score is 0.005.

Fig 5. Reliability diagrams and reliability scores (smaller is better) for the classification of *(a)* the GTDB root to its child taxa Domain Archaea and Domain Bacteria, and *(b)* Family Campylobacteraceae to its five child taxa (i.e., Genus *Campylobacter*, Genus *Campylobacter_A*, Genus *Campylobacter_B*, Genus *Campylobacter_D*, Genus *Campylobacter_E*). The larger deviation of the reliability curve (red) from the diagonal in *(b)*, and the larger reliability score of *(b)*, both indicate a lower reliability of the classification of Family Campylobacteraceae *(b)* than that of the GTDB root *(a)*.

Species level comparison of MT-MAG with DeepMicrobes

In this section, we compare the performance of MT-MAG against the performance of DeepMicrobes at the Species level, the only taxonomic rank at which DeepMicrobes classifies. The performance metrics we define here are used to assess the quality of DeepMicrobes's classification, and are defined analogously to the performance metrics for MT-MAG. The subscript r indicates that these metrics refer to reads, and the exact

definitions of the terms used can be found in , "Materials: Datasets and task description". These performance metrics are:

- CA_r (constrained accuracy): the proportion of correctly classified test reads, to classified test reads.

- AA_r (absolute accuracy): the proportion of correctly classified reads, to all test reads.

- WA_r (weighted classification accuracy): the proportion of correctly classified reads. Note that in this case WA_r coincides with AA_r, since DeepMicrobes does not provide any classification at ranks other than Species. (hereafter, *weighted classification accuracy* will sometimes simply be called *weighted accuracy*.)

- CR_r (classified rate): the proportion of classified test reads to all test reads. Note the difference in the definition between $CR_g(tr)$ for MT-MAG (complete classification rate for genomes, at rank tr), and CR_r (classified rate for reads, at the Species level) for DeepMicrobes.

The three accuracies CA_r, AA_r and WA_r are numbers between 0 and 1, with $CA_r \geq AA_r$, and where higher values indicate better performance. The classified rate CR_r is a number between 0 and 1, and a higher value indicates a higher proportion of classified reads, at the Species level (for exact definitions, see Supplemental Information Section 3.3).

Since DeepMicrobes only makes classifications at the Species level, to compare its performance with that of MT-MAG, we set the parameter tr (taxonomic rank) to Species in MT-MAG, and proceeded to compare CA_r with $CA_g(\text{Species})$, AA_r with $AA_g(\text{Species})$, WA_r with $WA_g(\text{Species})$, and CR_r with $CR_g(\text{Species})$.

Of all the metrics we defined, we posit that the most informative metric for comparing MT-MAG with DeepMicrobes is the *weighted (classification) accuracy* at the Species level. Indeed, in the case of MT-MAG, $WA_g(\text{Species})$ combines, into a single numerical indicator, the information on the proportion of genomes that MT-MAG correctly classifies together with that of genomes that it partially classifies. In the case of DeepMicrobes, WA_r combines the information on the proportion of reads that it correctly classifies together with that of reads that it is unable to classify. In addition to this main comparison performance metric, and for a more nuanced discussion, in the following we also compare the other performance metrics, namely CA_r with $CA_g(\text{Species})$, AA_r with $AA_g(\text{Species})$, and CR_r with $CR_g(\text{Species})$.

Table 4 summarizes the MT-MAG and DeepMicrobes constrained accuracies, absolute accuracies, and *weighted accuracies*, as well as the complete classification rates of MT-MAG, respectively the classified rates of DeepMicrobes.

For Task 1 (sparse), as seen in Table 4, MT-MAG demonstrates significantly better overall performance than DeepMicrobes, with the weighted accuracy of MT-MAG being 39.96% higher than that of DeepMicrobes. Regarding other performance metrics, the constrained accuracy of DeepMicrobes 11.61% higher than that of MT-MAG, the absolute accuracy for MT-MAG is 15.66% higher than that of DeepMicrobes, and the complete classification rate of MT-MAG is 25.63% higher than the classified rate of DeepMicrobes. The latter indicates that MT-MAG completely classifies significantly more sequences than DeepMicrobes, though DeepMicrobes demonstrates a slightly higher constrained classification accuracy for the classified sequences.

For Task 2 (dense), as seen in Table 4, MT-MAG demonstrates significantly better overall performance than DeepMicrobes, with the weighted accuracy of MT-MAG being 31.54% higher than that of DeepMicrobes. Comparing the other performance metrics, the constrained accuracy of MT-MAG is 4.76% higher than that of DeepMicrobes, the

Table 4. Summary of MT-MAG and DeepMicrobes accuracy statistics, as well as the complete classification rates of MT-MAG and the classified rates of DeepMicrobes. The inputs are genomes in the case of MT-MAG, and reads in the case of DeepMicrobes. A higher value indicates better performance (in boldface).
The metric that best captures the performance of the methods is the weighted accuracy (in blue), since this metric combines information about sequences that have been completely classified with information about the sequences that have not been completely classified to the Species level.

Task ID	Metric	MT-MAG(%)	DeepMicrobes(%)
Task 1 (sparse)	CA_g(Species)$/CA_r$	81.53	**93.14**
	AA_g(Species)$/AA_r$	**57.60**	41.94
	WA_g(Species)$/WA_r$	**81.90**	41.94
	CR_g(Species)$/CR_r$	**70.65**	45.02
Task 2 (dense)	CA_g(Species)$/CA_r$	**98.63**	93.87
	AA_g(Species)$/AA_r$	**63.87**	46.82
	WA_g(Species)$/WA_r$	**78.36**	46.82
	CR_g(Species)$/CR_r$	**64.75**	49.88

absolute accuracy for MT-MAG is 17.05% higher than that of DeepMicrobes, and the complete classification rate of MT-MAG is 14.87% higher than the classified rate of DeepMicrobes. This indicates that MT-MAG not only completely classifies significantly more sequences than DeepMicrobes, but also demonstrates a slightly higher MT-MAG classification accuracy for the completely classified sequences.

Overall, for Task 1 (sparse) and Task 2 (dense), MT-MAG outperforms DeepMicrobes by an average of 35.75% in weighted accuracy. In addition, MT-MAG is able to completely classify an average of 67.7% of the sequences at the Species level, the only comparable taxonomic rank of DeepMicrobes, which only classifies 47.45%.

Discussion

We proposed MT-MAG, a novel machine learning-based taxonomic assignment tool for metagenome-assembled genomes. This is, to the best of our knowledge, the first machine learning method for taxonomic assignment of metagenomic data that has a partial classification option, and outputs a partial classification path in cases where it does not have enough confidence for a complete classification to the lowest taxonomic rank. In addition, MT-MAG outputs interpretable numerical classification confidences of its classifications, at each taxonomic rank. Reliability diagrams confirmed the quality of the training sets and the overall reliability of the MT-MAG classification confidences.

To assess the performance of MT-MAG, we defined a "weighted accuracy," with a weighting scheme reflecting the fact that partial classifications at different ranks are not equally informative. Compared with DeepMicrobes (the only other machine learning tool for taxonomic assignment of metagenomic data, with confidence scores), for the two datasets analyzed (genomes from human gut microbiome species, respectively bacterial and archaeal genomes assembled from cow rumen metagenomic sequences), MT-MAG outperforms DeepMicrobes by an average of 35.75% in weighted accuracy. In addition, MT-MAG is able to completely classify an average of 67.7% of the sequences at the Species level, the only comparable taxonomic rank of DeepMicrobes, which only classifies 47.45%. Moreover, a novel feature of MT-MAG is that it provides additional information for the sequences that are not completely classified at the Species level. This results in 95.15% of the genomes analyzed being either partially classified or completely classified, averaged over the two datasets analyzed. In particular, due to its

partial classification capability, MT-MAG completely classifies, on average, 88.84% of the test genomes to the Phylum level, 88.39% to the Class level, 86.81% to the Order level, 81.17% to the Family level, and 71.13% to the Genus level.

Limitations of MT-MAG include the fact that, being a supervised machine learning classification algorithm, its performance relies on the availability of ground-truth taxonomic labels for the DNA sequences in the training set. In addition, any incorrect or unstable ground-truth labels in the training set may cause erroneous future classifications. This limitation could be addressed, e.g., by extending the supervised machine learning approach to semi-supervised machine learning (where some, but not all, information about the training set is available), or even to unsupervised machine learning (where the training process does not require any ground-truth taxonomic labels, see, e.g., [32]).

Second, even though MT-MAG significantly outperforms DeepMicrobes in Task 1 (sparse training set) and Task 2 (dense training set) in weighted accuracy, there is still room for improvement in accuracies and complete classification rates. An analysis of the Task 1 (sparse) training set suggests two possible reasons contributing to incorrect classifications. One reason is the fact that the training set was the HGR database, which constitutes a very small subset of the GTDB taxonomy, in terms of both the number of representative genomes and of coverage of the GTDB taxonomy. This could be addressed by requiring a specific level of coverage for known taxa, to ensure that feature characteristics are reasonably well-represented. Another reason is the fact that, due to computational requirements of MLDSP, the training set had to exclude any contigs shorter than 5,000 bp, and this selection process resulted in the removal of 93% of the available basepairs. This could be addressed by finding ways to relax the selection criteria for the training set, to allow more sequences to participate in the training process without compromising the classification performance.

Third, the interpretability of classification could be further enhanced by exploring the last layer of the classifier. For example, the process of computing classification confidences could be used to identify pairs of child taxa that are difficult to distinguish from each other, which could potentially be biologically relevant. In addition, while single-child cases are few in the case of real DNA datasets, we note that their classification confidences are computed via a transformation of the distances between a test sequence and decision boundaries in the feature space into a valid probability distribution. To enhance the interpretability of these single-child class confidences, one could consider applying more interpretable training process and transformations such as those proposed in [33, 34].

Fourth, the classification accuracy and computational efficiency of MT-MAG could be further improved by taking advantage of user-provided information, so that the computation does not always start from the root of the taxonomy. For example, if the user already knows that an input genome belongs to Class Bacteroidia, then MT-MAG could bypass the higher taxonomic ranks and start its training and classifying phases at the Class-to-Order level directly.

Fifth, when defining the weighted accuracy for a classification at given taxonomic rank tr (i.e., $WA_g(tr_i)$), the weights used in this computation can be further refined, to reflect the dataset analyzed. Recall that the intent of defining a weighted classification accuracy was to account for the fact that partial classifications of a genome at different ranks are not equally informative. For example, a partial classification of a genome down to the Genus level is intuitively more informative than a partial classification to, say, the Phylum level, and this is quantified as follows in the definition of weighted accuracy. The root is assigned weight 0, the last taxonomic rank with a correct classification is assigned weight 1, and intermediate taxonomic ranks are assigned weights that increase in *equal* fractional increments, from the root to the last correctly

classified rank. However, this assumption of equal increments at each intermediate rank could be inadequate if, e.g., some of the intermediate taxonomic ranks are missing from the path. In such cases, the individual weights of taxonomic ranks could be defined as being different, with each weight corresponding to the amount of information that a classification at that rank contributes.

Lastly, even though MT-MAG achieves superior performance on the datasets analyzed in this paper, it would be desirable to obtain mathematical proofs of the optimality of the classifier, such as the Bayes optimality proofs in [35].

Acknowledgments

We thank DeepMicrobes's co-author Qiaoxing Liang for the assistance with DeepMicrobes, Dr. Gurjit Randhawa for the guidance on MLDSP, Fatemeh Alipour and Pablo Millan Arias for replicating the results and proofreading the manuscript. Resources used in preparing this research were provided, in part, by the Province of Ontario, the Government of Canada through CIFAR, and companies sponsoring the Vector Institute.

References

1. Sharon I, Banfield JF. Genomes from metagenomics. Science. 2013;342(6162):1057-8. doi:10.1126/science.1247023.

2. Parks DH, Rinke C, Chuvochina M, Chaumeil PA, Woodcroft BJ, Evans PN, Hugenholtz P, Tyson GW. Recovery of nearly 8,000 metagenome-assembled genomes substantially expands the tree of life. Nature Microbiology. 2017;2(11):1533-42. doi:10.1038/s41564-017-0012-7.

3. Murali A, Bhargava A, Wright ES. IDTAXA: A novel approach for accurate taxonomic assignment of microbiome sequences. Microbiome. 2018;6(1):1-4. doi:10.1186/s40168-018-0521-5.

4. Frioux C, Singh D, Korcsmaros T, Hildebrand F. From bag-of-genes to bag-of-genomes: metabolic modelling of communities in the era of metagenome-assembled genomes. Computational and Structural Biotechnology Journal. 2020;18:1722-34. doi:10.1016/j.csbj.2020.06.028.

5. Parks DH, Imelfort M, Skennerton CT, Hugenholtz P, Tyson GW. CheckM: assessing the quality of microbial genomes recovered from isolates, single cells, and metagenomes. Genome Research. 2015;25(7):1043-55. doi:10.1101/gr.186072.114.

6. Mock F, Kretschmer F, Kriese A, Böcker S, Marz M. BERTax: taxonomic assignment of DNA sequences with deep neural networks. BioRxiv. 2021. doi:10.1101/2021.07.09.451778.

7. Chaumeil PA, Mussig AJ, Hugenholtz P, Parks DH. GTDB-Tk: a toolkit to classify genomes with the Genome Taxonomy Database. Bioinformatics. 2019;36(6):1925–1927. doi:10.1093/bioinformatics/btz848.

8. Eisenhofer R, Weyrich LS. Assessing alignment-based taxonomic classification of ancient microbial DNA. PeerJ. 2019;7:e6594. doi:10.7717/peerj.6594.

9. Zielezinski A, Vinga S, Almeida J, Karlowski WM. Alignment-free sequence comparison: benefits, applications, and tools. Genome Biology. 2017;18(1):1-7. doi:10.1186/s13059-017-1319-7.

10. Segata N, Waldron L, Ballarini A, Narasimhan V, Jousson O, Huttenhower C. Metagenomic microbial community profiling using unique clade-specific marker genes. Nature Methods. 2012;9(8):811-4. doi:10.1038/nmeth.2066.

11. Zhou F, Olman V, Xu Y. Barcodes for genomes and applications. BMC Bioinformatics. 2008;9(1):1-1. doi:10.1186/1471-2105-9-546.

12. Liang Q, Bible PW, Liu Y, Zou B, Wei L. DeepMicrobes: taxonomic classification for metagenomics with deep learning. NAR Genomics and Bioinformatics. 2020;2(1):lqaa009. doi:10.1093/nargab/lqaa009.

13. Ounit R, Wanamaker S, Close TJ, Lonardi S. CLARK: fast and accurate classification of metagenomic and genomic sequences using discriminative k-mers. BMC Genomics. 2015;16(1):1-3. doi:10.1186/s12864-015-1419-2.

14. Almeida A, Mitchell AL, Boland M, Forster SC, Gloor GB, Tarkowska A, Lawley TD, Finn RD. A new genomic blueprint of the human gut microbiota. Nature. 2019;568(7753):499-504. doi:10.1038/s41586-019-0965-1.

15. Stewart RD, Auffret MD, Warr A, Wiser AH, Press MO, Langford KW, Liachko I, Snelling TJ, Dewhurst RJ, Walker AW, Roehe R. Assembly of 913 microbial genomes from metagenomic sequencing of the cow rumen. Nature Communications. 2018;9(1):1-1. doi:10.1038/s41467-018-03317-6.

16. Wood DE, Salzberg SL. Kraken: ultrafast metagenomic sequence classification using exact alignments. Genome Biology. 2014;15(3):1-2. doi:10.1186/gb-2014-15-3-r46.

17. Kim D, Song L, Breitwieser FP, Salzberg SL. Centrifuge: rapid and sensitive classification of metagenomic sequences. Genome Research. 2016;26(12):1721-9. doi:10.1101/gr.210641.116.

18. Ounit R, Lonardi S. Higher classification sensitivity of short metagenomic reads with CLARK-S. Bioinformatics. 2016;32(24):3823-5. doi:10.1093/bioinformatics/btw542.

19. Huson DH, Beier S, Flade I, Górska A, El-Hadidi M, Mitra S, Ruscheweyh HJ, Tappu R. MEGAN community edition-interactive exploration and analysis of large-scale microbiome sequencing data. PLoS Computational Biology. 2016;12(6):e1004957. doi:10.1371/journal.pcbi.1004957.

20. Menzel P, Ng KL, Krogh A. Fast and sensitive taxonomic assignment for metagenomics with Kaiju. Nature Communications. 2016;7(1):1-9. doi:10.1038/ncomms11257.

21. Federhen S. The NCBI taxonomy database. Nucleic Acids Research. 2012;40(D1):D136-43. doi:10.1093/nar/gkr1178.

22. Murray AE, Freudenstein J, Gribaldo S, Hatzenpichler R, Hugenholtz P, Kämpfer P, Konstantinidis KT, Lane CE, Papke RT, Parks DH, Rossello-Mora R. Roadmap for naming uncultivated Archaea and Bacteria. Nature Microbiology. 2020;5(8):987-94. doi:10.1038/s41564-020-0733-x.

23. Parks DH, Chuvochina M, Waite DW, Rinke C, Skarshewski A, Chaumeil PA, Hugenholtz P. A standardized bacterial taxonomy based on genome phylogeny substantially revises the tree of life. Nature Biotechnology. 2018;36(10):996-1004. doi:10.1038/nbt.4229.

24. Parks DH, Chuvochina M, Chaumeil PA, Rinke C, Mussig AJ, Hugenholtz P. A complete Domain-to-Species taxonomy for Bacteria and Archaea. Nature Biotechnology. 2020;38(9):1079-86. doi:10.1038/s41587-020-0501-8.

25. Huang W, Li L, Myers JR, Marth GT. ART: a next-generation sequencing read simulator. Bioinformatics. 2012;28(4):593-4. doi:0.1093/bioinformatics/btr708.

26. Babbar R, Partalas I, Gaussier E, Amini MR. On flat versus hierarchical classification in large-scale taxonomies. In: Annual Conference on Neural Information Processing Systems; 2013; p. 1824-1832.

27. Randhawa GS, Hill KA, Kari L. ML-DSP: machine learning with digital signal processing for ultrafast, accurate, and scalable genome classification at all taxonomic ranks. BMC Genomics. 2019;20(1):267. doi:10.1186/s12864-019-5571-y.

28. Platt J. Probabilistic outputs for support vector machines and comparisons to regularized likelihood methods. Advances in Large Margin Classifiers. 1999;26;10(3):61-74.

29. Hartmann HC, Pagano TC, Sorooshian S, Bales R. Confidence builders: evaluating seasonal climate forecasts from user perspectives. Bulletin of the American Meteorological Society. 2002;83(5):683-98. doi:10.1175/1520-0477(2002)083<0683:CBESCF>2.3.CO;2.

30. Wallace BC, Dahabreh IJ. Class probability estimates are unreliable for imbalanced data (and how to fix them). In: IEEE International Conference on Data Mining; 2012; p. 695-704. doi:10.1109/ICDM.2012.115.

31. Dimitriadis T, Gneiting T, Jordan AI. Stable reliability diagrams for probabilistic classifiers. Proceedings of the National Academy of Sciences; 2021;118(8). doi:10.1073/pnas.2016191118.

32. Arias PM, Alipour F, Hill K, Kari L. DeLUCS - deep learning for unsupervised clustering of DNA sequences. PLoS ONE; 2022; 17(1): e0261531. doi:10.1371/journal.pone.0261531.

33. Gao J, Tan P N. Converting output scores from outlier detection algorithms into probability estimates International Conference on Data Mining (ICDM'06). 2006; p. 212-221. doi:10.1109/ICDM.2006.43

34. Perini L, Vercruyssen V, Davis J. Quantifying the confidence of anomaly detectors in their example-wise predictions. Joint European Conference on Machine Learning and Knowledge Discovery in Databases. 2020; p. 1824-1832.

35. Ramaswamy H, Tewari A, Agarwal S. Convex calibrated surrogates for hierarchical classification. In: Proceedings of Machine Learning Research; 2015; p. 1852-1860.

36. Zheng Z, Cai Y, Li Y. Oversampling method for imbalanced classification. Computing and Informatics. 2015; 34(5): 1017-37.

37. Tax DM. One-class classification: Concept learning in the absence of counter-examples. PhD thesis. Technische Universiteit Delft (The Netherlands). 2002.