1   **Title:** BOLD cofluctuation 'events' are predicted from static functional connectivity
2   **Authors:** Zach Ladwig[1], Benjamin A. Seitzman[4], Ally Dworetsky[2], Yuhua Yu[2], Babatunde
3   Adeyemo[6], Derek M. Smith[10,11], Steven E. Petersen[5-9], Caterina Gratton[1-3]
4
Affiliations:
Departments of Interdepartmental Neuroscience Program[1], Psychology[2], Neurology[3] –
Northwestern University
Departments of Radiation Oncology[4], Radiology[5], Neurology[6], Psychological and Brain
Sciences[7], Neuroscience[8], and Biomedical Engineering[9] – Washington University St. Louis
School of Medicine
Department of Neurology[10], Division of Cognitive Neurology/Neuropsychology[11] – The Johns
Hopkins University School of Medicine
13
14   **Corresponding Author:** Caterina Gratton (caterina.gratton@northwestern.edu)
15

ABSTRACT

Recent work identified single time points ("events") of high regional cofluctuation in functional Magnetic Resonance Imaging (fMRI) which contain more large-scale brain network information than other, low cofluctuation time points. This suggested that events might be a discrete, temporally sparse signal which drives functional connectivity (FC) over the timeseries. However, a different, not yet explored possibility is that network information differences between time points are driven by sampling variability on a constant, static, noisy signal. Using a combination of real and simulated data, we examined the relationship between cofluctuation and network structure and asked if this relationship was unique, or if it could arise from sampling variability alone. First, we show that events are not discrete – there is a gradually increasing relationship between network structure and cofluctuation; ~50% of samples show very strong network structure. Second, using simulations we show that this relationship is predicted from sampling variability on static FC. Finally, we show that randomly selected points can capture network structure about as well as events, largely because of their temporal spacing. Together, these results suggest that, while events exhibit particularly strong representations of static FC, there is little evidence that events are unique timepoints that drive FC structure. Instead, a parsimonious explanation for the data is that events arise from a single static, but noisy, FC structure.

KEYWORDS

Resting-state fMRI, cofluctuations, events, simulations, RSFC, networks

HIGHLIGHTS

- Past results suggested high cofluctuation BOLD "events" drive fMRI functional connectivity, FC
- Here, events were examined in both real fMRI data and a stationary null model to test this model
- In real data, >50% of BOLD timepoints show high modularity and similarity to time-averaged FC
- Stationary null models identified events with similar behavior to real data
- Events may not be a transient driver of static FC, but rather an expected outcome of it.

INTRODUCTION

The human brain is organized in large-scale systems, or 'networks,' with coordinated functions such as the visual network, somatomotor network, and default mode network. In humans, these networks can be identified by grouping regions of the brain that have highly correlated spontaneous BOLD fMRI signals - regions with high "functional connectivity (FC)" (Biswal et al., 1995; Power et al., 2011; Yeo et al., 2011). These FC networks have been shown to have a canonical spatial layout (most people have the same networks represented in the same locations), with stable patterns of individual variation (each person's network topography is slightly different from the canonical layout and consistent within themselves across time (Gordon et al., 2017; Gratton et al., 2018; Laumann et al., 2015; Seitzman et al., 2019). At both the individual and group level, functional network topology accurately predicts which regions of the brain will be activated during specific tasks (Braga et al., 2020; Gordon et al., 2017; Smith et al., 2009; Tavor et al., 2016) and variations in network topology are related to individual differences in behavior outside of the scanner (Bijsterbosch et al., 2018; Kong et al., 2019; Smith et al., 2015; van den Heuvel et al., 2009). Further, FC measured by fMRI has identified functional systems in other species which are consistent with circuit architecture measured through anatomical tracing (Du & Buckner, 2021; Margulies et al., 2009; Vincent et al., 2007).

However, analysis of spontaneous fMRI data is not straightforward. Unlike in task-fMRI, there is no predefined temporal structure that can be used to separate relevant signals from artifactual signals. Instead, typical analyses of spontaneous (resting-state) fMRI remove physiological artifacts (motion, respiration, cardiac rhythms, etc.) and assume the residual signal is the neural signal of interest (Power et al., 2020). It is typically presumed that this signal is equally present at all moments and FC is calculated using all available data over long periods. However, recent work suggested that rather than being constantly present, FC information might be inordinately present at particular time points called "events" (Esfahlani et al., 2020). Esfahlani and colleagues found that "events," time points with the highest BOLD signal cofluctuation, reproduce static functional connectivity patterns better than the same number of "non-events," time points with the lowest BOLD signal cofluctuation, and require relatively few timepoints to reproduce them well. The authors concluded that rather than functional network structure being present at all timepoints, it is driven by events – a discrete and temporally sparse phenomena (Esfahlani et al., 2020). This idea has deep implications for the field: a thorough analysis of events across brain organizational levels (e.g., from systems to cellular recordings) could reveal information about the physiological mechanisms of FC and new analysis methods focused on events could improve the clinical utility of fMRI (Esfahlani et al., 2021; Greenwell et al., 2021). The idea that brain network information can be identified in a reduced data set is not new. Previous approaches such as co-activation patterns (CAPS) and point-process analysis (PPA) have been used to identify a small number of points which can capture functional network information (Liu & Duyn, 2013; Tagliazucchi et al., 2012). In this work, we consider events methods because they do not require the specification of a seed region or threshold for high-amplitude activity (Esfahlani et al., 2020).

However, there are alternative interpretations of these findings which have not yet been explored. First, it is possible that differences between "events" and "non-events" are driven by contamination in "non-events" (motion, respiration, etc.) rather than by a unique signal present during "events." Second, it has been shown that random sampling variability in BOLD data is high and alone can create the appearance of discrete states in stationary FC simulations (Hlinka & Hadrava, 2015; Laumann et al., 2017). This principle may apply here too – sampling variability could make a subset of single points look extreme, even if they are drawn from a continuous distribution around a static FC matrix (note that if this were the case, events methodology may still be a useful way to rapidly and accurately reproduce static FC structure, but this outcome would suggest that a deep focus on events physiology relative to other timepoints has less utility). Recent work has provided a mathematical basis for how this could

be the case. (Novelli & Razi, 2022). In this paper, we ask (1) if events are unique points which
drive FC, (2) if non-events are unique points with high contamination, or (3) if events and non-
events are an expected consequence of static FC and sampling variability.
To answer these questions, we conduct a series of analyses on real and simulated data.
First, we use real data from the Midnight Scan Club dataset to test how unique events and non-
events are by examining whether their properties differ markedly from intermediate timepoints.
Second, we create models of simulated static BOLD data to see if sampling variability on a
static signal is sufficient to explain event behavior. Finally, we examine why events are able to
recreate static FC structure with so few time points.
107
108   **MATERIALS AND METHODS**
109
110   ***Overview and Dataset***
111   The goal of this project was to investigate if high cofluctuation moments in resting state fMRI
112   BOLD signals are discrete events that drive functional connectivity. We used a combination of
113   real and simulated data for these analyses.
114
The publicly available Midnight Scan Club (MSC) dataset was used as our real sample dataset.
The MSC dataset contains fMRI data from 10 highly sampled individuals (5 females, ages 24-
34). The data for each subject was collected across 10 fMRI sessions within 7 weeks. Across
these sessions, the MSC dataset includes 5 hours of resting state fMRI; this resting-state data is
the focus of our analyses. One participant (MSC08) has been excluded from these analyses
because of head motion and drowsiness during rest. For single session-analysis and
simulations, sessions with less than 333 usable timepoints (6/90 sessions) were excluded. All
data collection was approved by the Washington University Internal Review Board and written
informed consent was received from all participants. The dataset and processing have been
previously described in detail (Gordon et al., 2017). A summary of relevant details is provided
below.
126
MRI Acquisition
MRI data were acquired on a Siemens 3T Magnetom Tim Trio with a 12-channel head coil. T1-
weighted (sagittal, 224 slices, 0.8 mm isotropic resolution, TE = 3.74ms, TR = 2.4s, TI = 1.0s,
flip angle = 8 degrees), T2-weighted (sagittal, 224 slices, 0.8 mm isotropic resolution, TE =
479ms, TR = 3.2s) and functional (gradient-echo EPI sequence, TE = 27ms, TR = 2.2 s, flip
angle = 90, voxels =isotropic $4mm^3$, 36 axial slices) MRI images were collected. Thirty minutes
of resting-state fMRI were collected at the start of each session.
134
135   ***Preprocessing***
136   Data processing for the MSC dataset is explained in detail elsewhere (Gordon et al., 2017).
137   Relevant details for this project are shared below.
138
139   Structural MRI Processing: For each participant, T1 images were averaged together and used
140   to generate a cortical surface in Freesurfer (Dale et al., 1999). These surfaces were hand-edited
141   and registered into fs_LR_32k surface space (Glasser et al., 2013).
142
Functional MRI Processing: Slice time correction, motion correction, and intensity normalization
to mode 1000 were all completed in the volume. The functional data was then registered to the
T2 image (which was registered to the T1 image registered to template space), resampled to
3mm isotropic resolution and distortion corrected (Gordon et al., 2017). All alignments were
applied in a single step.

<u>Functional Connectivity Processing</u>: Described in detail elsewhere (Power et al., 2014),
preprocessing steps were taken to reduce the effect of artifacts on functional network analysis.
This included the regression of nuisance signals (white matter, ventricles, global signal, motion
and derivative and expansion terms), scrubbing of high motion frames (FD > 0.2 mm), and
bandpass filtering (0.009 Hz to 0.08 Hz). For two subjects (MSC03 and MSC10), motion
parameters were low pass filtered before censoring to address respiratory activity in the motion
traces (Fair et al., 2020; Gordon et al., 2017). Functional data was then registered to the surface
and spatially smoothed (FWHM = 6 mm, sigma = 2.55) (Marcus et al., 2011).
156

Network and region definition

All analyses were done on parcellated timeseries extracted using a group-level map of 333
cortical parcels (Gordon et al., 2016). These 333 parcels can be split into 12 functional systems:
somatomotor (SM), somatomotor lateral (SM-lat), visual (Vis), auditory (Aud), cingulo-opercular
(CO), salience (Sal), frontoparietal (FP), dorsal attention (DAN), ventral attention (VAN), default
mode (DMN), parietal memory (PMN), and retrosplenial (RSP). These systems are used to
group parcels in the visualization of FC matrices.
164

Comparisons between events and static functional connectivity in real data

Our first goal was to compare the network structure present in events, non-events, and
intermediate bins. We followed the approach used in Esfahlani et al., 2020, calculating the RSS
(root-sum-square) cofluctuation for each timepoint and binning timepoints by their RSS
cofluctuation value. We compared the network structure present in each bin by creating FC
matrices for each bin and calculating the similarity between bin FC and whole session FC and
the modularity of bin FC. These measures are defined below.
172

<u>Cofluctuation Time Series and Events</u>: The method for calculating cofluctuation and identifying
events has been fully described elsewhere (Esfahlani et al 2020). It was followed exactly and is
summarized here. The original fMRI BOLD timeseries was z-scored per parcel. For each edge
(a unique pair of parcels), the z-scored values at each timepoint were multiplied, resulting in an
edges X timepoints matrix. As described elsewhere, this timeseries (also called the edge-time-
series), represents the exact contribution of each timepoint to static FC (Esfahlani et al., 2020).
For each time point, the RSS (root-sum-square) across parcels was calculated, resulting a 1 X
timepoints matrix containing the RSS cofluctuation value at each timepoint. Timepoints were
binned based on RSS cofluctuation value in 5% bins, with the 5% of points with highest
cofluctuation in bin one, the next 5% of points in bin two and so on.
183

<u>Functional Connectivity (FC):</u> For each session and subject, functional connectivity matrices
were calculated using either the timepoints from the full session ('static' FC matrices) or from
the timepoints in each bin (cofluctuation bin FC matrices). In all cases, FC was calculated by the
product moment correlation between each pair of parcel timeseries, resulting in a 333X333
functional network matrix. Parcels were grouped by functional system for visualization. Edges
within the diagonal blocks represent within-system correlations, and edges in the off-diagonal
blocks represent between-system correlations.
191

192   <u>Similarity</u>: Similarity between each bin's FC and whole-session 'static' FC was calculated by
193   vectorizing both matrices and taking the correlation between them.
194

<u>Modularity</u>: Modularity was calculated for each bin as measure of network structure. Modularity
maximization is a strategy used to arrange nodes into communities in which there are more
edges within communities than expected by random chance. Each matrix was thresholded for
sparseness, keeping only the top 5% of weighted edges (5% edge density). Then, all remaining

edge weights were set to 1, making the graph unweighted. Newman's spectral optimization was
used to identify the optimal network structure. This structure was then quantified using
Newman's modularity statistic, Q, which measures the fraction of within-network edges minus
the expected value of within-network edges in a network with the same communities but random
connections (Newman & Girvan, 2004). Larger values of modularity reflect stronger community
structure than expected by chance.
205
206 ***Comparisons between events and static functional connectivity in simulated data***
207 Our second goal was to test whether the relationship between network structure and
208 cofluctuation found in real data could be explained by sampling variability in a stationary model.
209 To examine this, we created simulated data with the same dimensionality and static covariance
210 structure as BOLD data but sampled from a random Gaussian distribution.
211
Simulated BOLD Data: For each subject and session, data was sampled from a Gaussian
distribution in the dimensionality of the real data from that session. Separately, a static FC
matrix was calculated from the full 30 minutes of real data. The random timeseries were
projected on to the eigenvectors derived from the static FC matrix, resulting in data matched in
dimensionality and covariance structure with real BOLD data but stationary by construction. This
strategy is largely adapted from prior simulation work (Laumann et al., 2017). We then did the
same analysis in the simulation data as was described above for real data – calculating
cofluctuation, binning frames by cofluctuation, and comparing the network structure present in
each bin with two measures (similarity to static FC and modularity).
221
Simulated Toy Model: To aid in our second goal, we did a supplementary analysis investigating
the relationship between network structure and cofluctuation in a very simple non-BOLD-like
data set. The data set comprised of 4 nodes total – 2 anti-correlated networks with two nodes
each. Network A was defined by the simple sine(x) wave, and both network A nodes were given
that signal. Network B was defined by sine(x + π/2) and both network B nodes were given that
signal. Normally distributed random noise of half the magnitude as the real signal was added to
all four nodes. Then, cofluctuation was calculated for each timepoint, timepoints were binned by
cofluctuation, and similarity with time-averaged FC calculated for each bin.
230
PCA Analysis: To test whether simulated data would replicate the result that high amplitude
cofluctuations show a particular mode of brain activity characterized by counter-fluctuations in
traditionally task-positive and task-negative areas of the brain, we replicated the analysis from
Esfahlani et al. 2020 in both real and simulated data. For each subject and session, we
calculated a mean activity pattern for high and low cofluctuation time points (top 5% and bottom
5%). We correlated these mean activity patterns, and took the first principal component from
that correlation matrix. We compared the coefficients for the high versus low points, and then
mapped the coefficient scores from PC1 on to the surface of the brain.
239
240 ***Temporal Spacing Analysis***
241 Our third goal was to compare the effects of different sampling methods on the network
242 structure present in the sampled points. We specifically wanted to investigate the effect of
243 temporal spacing on network structure.
244
Comparison of Sampling Methods
For each subject and session, we examined the network structure present in four groups of time
points: high cofluctuation points (selected as the top 5% of points with highest RSS
cofluctuation), low cofluctuation points (selected as the bottom 5% of points with the lowest RSS
cofluctuation), consecutive points (5% of points selected consecutively beginning at a random

point of the session and wrapping around when needed), and random points (5% of points
selected randomly from the session). For consecutive samples, 100 iterations were done for
each session to not bias the result by starting location. We further tested this by varying the
number of time points selected rather than choosing 5% of time points. The number of time
points was varied from 1 to 100.
255
Circular Offset Analysis
In a supplemental analysis, we examined the relationship between cofluctuation and network
structure after removing temporal spacing effects. To do this, we binned time points by
cofluctuation and then circularly shifted them by 1-10 points in both directions to maintain the
temporal spacing found in the original binning while varying their cofluctuation values. However,
because we previously scrubbed high motion points from this data set, it was not possible to
select 5% of time points (as in other binned analyses) and shift them without running into
scrubbed points. To address this issue, we randomly sampled only 5 points per bin and used
fewer bins (95-100, 85-90, 70-75, 45-50, 20-25, 0-5). This resulted in a smaller number of
analyzed sessions with lower peak similarities for this analysis. To reduce bias from random
sampling, we did 100 iterations and averaged the results.
267
Dataset and Code Availability
MSC data has been made publicly available
(https://openneuro.org/datasets/ds000224/versions/1.0.3). The parcellated timeseries used for
these analyses is available here (https://github.com/GrattonLab/MSC_ROI_data).The code for
the analyses in this paper is available at
(https://github.com/GrattonLab/Ladwig_2022_Events_Static_FC) which will made public upon
publication.
275
276   **RESULTS**
277
Overview:
Previous work showed that moments with high amplitude cofluctuations in BOLD, or "events",
estimate static functional connectivity patterns better than low cofluctuation moments, and can
do so with relatively few timepoints (Esfahlani et al., 2020). This suggested that (1) high
cofluctuation events may be unique, transient phenomena which drive the large-scale network
organization that we observe over long timeseries (Esfahlani et al., 2020). But there are
alternate interpretations of this result: (2) differences between low and high cofluctuation could
be driven by low cofluctuation timepoints exhibiting more BOLD artifacts (e.g., motion or
respiration) that disrupt functional connectivity measures or (3) events may arise as a
consequence of sampling from a continuous distribution, where some moments will, by chance,
exhibit higher cofluctuation than others.
289
290   In this work, we test these three hypotheses. We test how network structure changes over a
291   range of cofluctuation amplitudes, ask if this relationship is present in stationary simulated data,
292   and analyze why events can recreate static correlation structure with so few time points.
293
1. Network structure is continuously related to cofluctuation
First, we examined the relationship between BOLD cofluctuation and network structure across a
range of cofluctuation amplitudes. Our hypotheses are visualized in **Fig. 1A.** If events are
specialized discrete timepoints that drive network structure, then they should especially well
represent network structure (purple) relative to other points. If low cofluctuation points are
discrete timepoints more contaminated by artifacts, they should especially poorly represent
network structure (yellow). If BOLD cofluctuations exhibit random variation as would be

expected from sampling variation, then there should be a continuous relationship between
cofluctuation amplitude and network structure (green).
303
For each participant and resting state session (30 minutes), we calculated BOLD cofluctuation
amplitude at each timepoint (after standard preprocessing and denoising to improve alignment
and remove artifacts, including those associated with motion, see *Methods*). In Esfahlani et al.,
2020, events were defined as the top 5% of timepoints ranked by cofluctuation. We extended
this, grouping timepoints in each session into discrete 5% bins based on their cofluctuation (**Fig.
1B**). For each bin, we calculated an FC matrix using Pearson's correlation **(Fig. 1C)** and
computed measures of network structure as in Esfahlani et al. 2020. **(Fig. 1D-E).**
311
We reproduced both results from Esfahlani et al., 2020 showing that compared to FC from the
lowest cofluctuation bin ("non-events"), FC from events is more similar to whole-session FC
(r_{events} = 0.792, r_{lowest} = 0.514, $t(89)$ = 42.2, p = 1.2e-60) and more modular (q_{events} = 0.562, q_{lowest}
= 0.478, $t(89)$ = 12.3 p = 6.0e-21) **(Fig. 1D, E).** However, when we examined the relationship
across intermediate bins, we found that both metrics increased gradually with cofluctuation, not
discretely for events. The increase was especially gradual at high values of cofluctuation. In
fact, the top bin (events) was not substantially different than the 70th percentile bin (r_{events} =
0.792 vs. r_{70} = 0.797, r_{diff}=-0.005, $t(89)$ = 0.48, p = 0.31; modularity: q_{events} = 0.562 vs. q_{70} =
0.561, qdiff=-0.001, $t(89)$ = 0.15, p = 0.45) and only slightly different than the 50th percentile bin
(r_{50} = 0.740, q_{50} = 0.546, r_{diff}=0.052, q_{diff} = 0.016). Low cofluctuation points, while substantially
different from events, were not obviously discrete when compared with the 10th and 20th
percentile bins (r_{lowest} = 0.514, q_{lowest} = 0.478, r_{10} = 0.579, q_{10} = 0.499, r_{20} = 0.637, q_{20} = 0.515).
Notably, many sets of points explicitly excluding events still recapitulated network structure well.
These relationships were consistent in all 9 subjects (lines in **Fig. 1D-E**, separated by session in
Fig. S1), suggesting that neither high nor low cofluctuation points are discrete, specialized,
timepoints that drive network structure (or the lack thereof). Rather, network structure appears
to be present in all bins, with variability that is positively correlated with the cofluctuation
amplitude of a given time point. These results do not suggest that there are a small number of
time points which drive functional connectivity.
331
332 As an additional check, we re-analyzed the data omitting the low-pass filter (< 0.08 Hz)
333 commonly applied in rsFC analysis. Low-pass filters temporally smooth data and we were
334 concerned it may blunt the temporally discrete properties of events. We re-analyzed a single
335 subject (MSC06) omitting the low-pass filter. As in the original analysis, it appears that network
336 structure exists in all cofluctuation bins even in the absence of low-pass filtering (**Fig. S2**).

337
Figure 1: Network structure varies continuously with BOLD cofluctuation. (A) Previous literature
showed that high cofluctuation events contain stronger network structure than low cofluctuation
points (gray dots). We posited three hypotheses: (1) high cofluctuation points are discrete
phenomena which drive network structure (purple), (2) low cofluctuation points are discrete
artifacts which do not contain network structure (yellow), or (3) there is a continuous gradual
relationship between cofluctuation magnitude and network structure as would be expected from
sampling variability (green). (B) To test these hypotheses, we binned time points into 5
percentile bins of increasing cofluctuation. See example histogram here from MSC05 session 4.
(C) For each bin, we calculated an FC matrix (examples here from MSC02 session 5) and
calculated two measures of network structure – similarity to static FC and modularity. (D)
Similarity to static FC increased gradually with cofluctuation for all subjects (black line = mean,
colored lines = subjects, error bars represent SEM for the group). (E) Modularity increased
gradually with cofluctuation as well. These results suggest that neither high nor low cofluctuation
time points are discrete, unique entities.
352
2. Stationary simulations produce similar behavior to BOLD events and non-events
Above, we found that there was a consistent and gradual relationship between BOLD
cofluctuation amplitude and network structure. Next, we asked, what drives this relationship?
One possible explanation is sampling variability: with noisy data, some timepoints will have

higher similarity to the session average, while others will have lower similarity, simply by
chance. Here, we tested whether sampling variability could account for event behavior by
creating and analyzing a simulated BOLD dataset with stationary covariance structure. In this
simulated dataset, as in the real data in the previous section, we identified points of high and
low cofluctuation and compared their relationship to network structure.
362
363 The procedure to generate simulated data is shown in **Fig. 2A**. For each subject and session,
364 data was generated by sampling from a Gaussian distribution in the dimensionality of real data.
365 This data was then projected on to the eigenvectors of the static correlation structure from the
366 real BOLD data for that subject and session, resulting in random Gaussian data with stationary
367 correlation structure matching real data (see *Methods*).
368
The analysis from **Figure 1** was repeated on the simulated data. We calculated cofluctuation for
each time point, binned time points by cofluctuation, computed FC matrices for each bin, and
compared the network structure properties across bins. We found that the relationship between
network structure and cofluctuation in simulated data was remarkably similar to the one found in
real data. Similarity to static FC (**Fig. 2B**) and modularity (**Fig. 2C**) both showed gradually
increasing relationships with cofluctuation in the simulated data, just as in real data. Visually, the
network structure present in each bin was remarkably similar between simulated and real data
(**Fig. 2D**). These results were consistent within individuals and sessions (**Fig. S3**). Further, we
confirmed that the particular task-positive versus task-negative activity pattern associated with
high amplitude cofluctuations in Esfahlani et al. 2020 was present in the simulation data as well,
suggesting that this pattern, too, is sufficiently explained by static FC (**Fig. S4**). These results
suggest that the difference between high and low cofluctuation moments and their relationship
to network structure can be explained by sampling variability alone.
382
Next, we extended this simulation analysis to non-BOLD-like data by creating an extremely
simple toy model made of correlated sine waves and noise **(Fig. 3A)**. Even such a basic model
of correlated data shows points of high and low cofluctuation amplitude and a gradually
increasing relationship between cofluctuation amplitude and network structure, similar to what is
seen in BOLD and the stationary simulation. (**Fig. 3B, 3C, 3D, 3E**) This provides evidence that
these properties may be the general statistical behavior of correlated timeseries and not specific
to BOLD or BOLD-like data.

390
Figure 2: Sampling variability alone can produce event-like behavior. (A) For each subject and
session, we generated a dimensionality-matched timeseries sampled from a Gaussian
distribution. This time series was projected onto the eigenvectors of static FC calculated from
that session. This yielded a simulated random Gaussian data set with BOLD-matched
dimensionality and covariance structure. (B, C) Using the same analysis methods as in **Fig. 1**,
we found that the relationship between network structure and cofluctuation in simulated data
was remarkably similar to the one found in real data. Both (B) similarity with session FC and (C)
modularity increased gradually just as they did in real data. (D) Visually, the FC matrices made
from specific cofluctuation bins look similar between simulated and real data. The data shown is
an example from a single session: MSC02 Session 5. These results suggest the relationship
between network structure and cofluctuation amplitude can be explained by sampling variability
and static FC.

Figure 3: The relationship between network structure and cofluctuation is present in extremely simple non-BOLD-like models. We created a 2 network, 4 node model from sine waves and tested the relationship between network structure and cofluctuation. (A) Network A is made of two nodes, each with the sine(t) wave. Network B is made of two nodes, each with sine(t+π/2) wave. Random noise was added to all four nodes. (B) Over the time course, there is moderately high magnitude (r = 0.7) correlation between in-network nodes. (C) As in real data, there were points of high and low cofluctuation so it was possible to bin time points the same way as was done in real and BOLD-simulated data. (D) A similar relationship exists between cofluctuation and network structure where higher cofluctuation bins are better able to reproduce network structure from the overall time course. Error bars here represent SEM over 1000 iterations of the model. (E) This relationship is visually obvious in correlation matrices. In high cofluctuation bins, the two antagonistic networks are strongly present, and in low bins there is little or no relationship between nodes.

3. **Randomly selected timepoints can also reproduce network structure**

One particularly notable property of events is their ability to recapitulate network structure with a small number of timepoints. As shown in **Fig. 1** and Esfahlani et al., 2020, 5% of time points in a 30-minute resting state session (approximately 1.5 min. of total data) show high similarity with the static FC calculated from the whole session (r = 0.792). In contrast, past work (Anderson et al., 2011; Gordon et al., 2017; Laumann et al., 2015; Noble et al., 2017) suggests that large amounts (> 30 min.) of resting state fMRI data collection are required to achieve high reliability. This discrepancy appears to bolster the suggestion that events are discrete transient phenomena which drive static functional connectivity.

However, in the previous sections, we showed that events are not unique in their ability to reproduce static FC (**Fig. 1D**). Many other points can recreate static FC. The 70[th] percentile points were correlated with static FC at r = 0.797 and the 50[th] percentile points are correlated at

431 r = 0.740. These results raise the question: is the ability for a few points to recreate session FC
432 driven by cofluctuation or something else?
433
We hypothesized that this apparent discrepancy was related to how the events methodology
samples time points. One reason that substantial data is required for reliable FC measures is
because BOLD data is autocorrelated – each time point shares information with the time points
around it. In contrast, the events methodology is not constrained to select temporally adjacent
points. Looking at a sample timeseries, it is obvious that events are more spread out than
consecutive points **(Fig. 4A).** This is confirmed by looking at the histogram of the distance
between events **(Fig. 4B).**
441
To test the effect of temporal spacing on network structure, we compared 5% of points (a)
sampled consecutively (starting from a random section of the scan), (b) sampled randomly
across the whole scan, (c) sampled from the highest cofluctuation points (events), and (d)
sampled from the lowest cofluctuation moments. **Fig. 4C** shows the outcome of sampling
timepoints in these different ways: randomly sampled points are similarly correlated with the
static session FC structure as events (r_{random} = 0.78, r_{events} = 0.79, $t(89)$ = 1.7, p = 0.045).
Random points show substantially higher similarity to static session FC than either low
cofluctuation points (r_{low} = 0.50 $t(89)$ = 43.0 p = $1.3e^{-60}$), or consecutively sampled time points
($r_{consecutive}$=0.58, $t(89)$ = 35.2 p = $2.42e^{-54}$). These results are consistent over a range of bin sizes
(**Fig. 4D**), suggesting that random temporal spacing is sufficient to estimate FC well.
452
We note that the similarity between random sampling and event timepoints in reproducing static
network FC is not immediately intuitive. One might reasonably expect that randomly selected
points would fall somewhere between low and high cofluctuation points, rather than be similar to
high cofluctuation points as was seen **(Fig. 4C)**. We hypothesize this unexpected result is
because of temporal spacing – randomly selected points are more evenly spread out **(Fig. 4B)**,
and thus better sample the underlying data, than either high or low cofluctuation points. We also
examined spacing within each of the cofluctuation bins **(Fig. S5)**, finding that while all appear
more spaced than consecutive points and less spaced than random samples, the extreme bins
(100^{th} and 5^{th} bins) appear less spaced than the others, providing a possible explanation for why
the 100^{th} bin is slightly less similar to static FC than the 90^{th} bin in real data **(Fig. 1D).** Similarity
to static FC appears to be affected by two factors – cofluctuation magnitude and temporal
spacing.
465
To disambiguate the effects of cofluctuation magnitude and temporal spacing, we circularly
shifted the cofluctuation-binned time points (see *Methods*) to keep temporal spacing constant
and vary cofluctuation. We found that after accounting for temporal spacing, there remained a
graded hierarchy where higher cofluctuation points contained more network structure than lower
cofluctuation time points (**Fig. S6**). The simulation results in the previous section suggest that
this is expected and can be parsimoniously explained by sampling variability. To further
investigate the impact of temporal spacing, we tested all possible spacing distances for a set
number of sampled points and find that ~10 seconds between samples is sufficient to achieve
most of the benefit of temporal spacing in terms of estimating static FC **(Fig. S7).** Jointly, these
findings suggest that the ability to recreate network structure with a few time points is a function
of both temporal spacing (as shown here) and sampling variability (as shown in the previous
section).

Figure 4: Effects of temporal spacing on estimating FC. (A) Events (red dots) are more temporally spaced than consecutive points, shown here for MSC02 session 6. (B) Histograms of distance between sampled points using consecutive, random, or cofluctuation-based sampling, aggregated over all subjects and sessions. (C) Randomly sampled points are as similar to static session FC as are events; both match static session FC much better than consecutive or low cofluctuation points. (D) These relationships hold over a range of bin sizes. These results suggest that temporal spacing is an important factor in estimating FC well.

DISCUSSION

In this study, we asked if "events", time points with high BOLD cofluctuation, are discrete, transient events that drive functional connectivity. We found that events are not discrete phenomena driving FC. When they are removed, static FC structure is still present. Further, there is a gradual positive relationship between network structure and cofluctuation amplitude, with relatively similar behavior for the top 50% of timepoints, including events. Next, we asked if this gradual relationship between network structure and cofluctuation could be explained by sampling variability on static FC. We created a simulated data set matched to BOLD in dimensionality and covariance structure. Our model produced the same gradual positive relationship seen in real data, including the existence of extreme points like events, suggesting that event behavior can be explained by sampling variability alone. Finally, we analyzed why events are able to recreate static FC with so few points. We found that small numbers of randomly sampled timepoints are also able to reproduce static network structure well,

501 suggesting that both sampling variability and temporal spacing are important factors in
502 estimating FC. Taken together, these results support the idea that while events are an
503 especially good representation of the network structure present in static FC, there is not
504 evidence that they are unique points driving it.
505
Should events be used to study the neural underpinnings of functional connectivity?
Although there is a large literature linking fMRI BOLD signal to neural activity (Heeger et al.,
2000; Logothetis et al., 2001), the physiological mechanism of FC itself is incompletely
understood. Past work suggests that BOLD FC is constrained by structural connections (Honey
et al., 2009; Johnston et al., 2008; Vincent et al., 2007) and is related to correlations in neural
activity (Nir et al., 2008; Shmuel & Leopold, 2008; Vincent et al., 2007) but the underlying
drivers of these spontaneous activity correlations remain relatively unknown. Because events
contain similar functional connectivity patterns to static functional connectivity, it was suggested
that these specific moments are responsible for functional connectivity measured over the
timeseries (Esfahlani et al., 2020). From a research perspective, this would make them an
excellent temporal target for investigating the neural mechanism of FC.
517
In this work, we show that while events do match static FC well, they are not discrete markers
for it. When they are discarded, static FC structure is still strongly present in the remaining time
points. Further, there is a gradual and increasing relationship between cofluctuation amplitude
and FC where many points (at least 50%) have a strong relationship with static FC. These
results suggest that events by themselves do not (mechanistically)[1] drive FC and it is unlikely
there is a unique physiological event happening at high cofluctuation points which is creating the
FC matrix. Given these observations, we consider it unlikely that investigating the unique
temporal physiological activity coincident with events would glean additional new information
about the physiologic origins of FC, beyond what might be seen at other timepoints as well.
However, as events show a very strong relationship to FC structure, it is possible that their
study may prove useful for denoising and analysis, to provide a higher signal to noise ratio for
investigations of simultaneous BOLD and direct neural recordings.
530
Relationship between events and static vs. dynamic functional connectivity
The results of this work show that events can be predicted by static functional connectivity and
sampling variability. However, the interpretation of these results and on the practical application
of events may depend on one's perspective about the temporal nature of FC. As has been
summarized elsewhere (Lurie et al., 2020), there are two dominant perspectives on this topic.
One perspective posits that functional connectivity exhibits meaningful temporal dynamics on a
moment to moment basis which could represent differences in neural interactions related to
ongoing cognition and task processing (Calhoun et al., 2014; R. M. Hutchison et al., 2013; Lurie
et al., 2020). This view is supported by the fact that states can be found in resting-state FC data
at second and minute time scales using sliding windows or instantaneous coactivation patterns
(Allen et al., 2014; Chang & Glover, 2010; Petridou et al., 2013; Shakil et al., 2016), and that
changes in state properties have been linked to task behavior, ongoing cognition, and arousal
(Chang et al., 2016; Gonzalez-Castillo et al., 2015; M. R. Hutchison et al., 2013; Kucyi & Davis,
2014; Kupis et al., 2021; Sadaghiani et al., 2015; Tagliazucchi & Laufs, 2014) as well as more
stable measures of cognitive/behavioral traits and psychiatric disease (Damaraju et al., 2014; de
Lacy et al., 2017; Liégeois et al., 2019; Rashid et al., 2016). From this perspective, static FC is
less significant than its constituent parts.

---

[1] Events do not appear to drive FC in a unique way but do contribute the most to FC estimates as a mathematical necessity of their definition and relationship with correlation.

The second perspective posits FC is temporally stable and primarily reflects a history of co-
activation between regions (Laumann & Snyder, 2021). This is supported by evidence that
functional connectivity patterns are consistent within people over sessions (Finn et al., 2015;
Gratton et al., 2018; Laumann et al., 2015; Miranda-Dominguez et al., 2014; Mueller et al.,
2013; Poldrack et al., 2015), only slightly altered during tasks (Cole et al., 2014; Gratton et al.,
2016, 2018; Krienen et al., 2014), and present in anesthesia (Mhuircheartaigh et al., 2010;
Palanca et al., 2015) and slow wave sleep (Mitra et al., 2015; Sämann et al., 2011). This
perspective emphasizes that resting state FC patterns are only a weak marker of ongoing
cognition, and are instead more related to stable neuroanatomical constraints (Barttfeld et al.,
2015; Honey et al., 2009; Lu et al., 2011), homeostatic processes (Laumann & Snyder, 2021),
and learning related adaptations (Fair et al., 2007; Guerra-Carrillo et al., 2014; Lewis et al.,
2009; Newbold et al., 2020; Tambini et al., 2010; Voss et al., 2012). This perspective collides
with the previous one in that it suggests that the dynamic states found during rest[2] may be
explained by sampling variability, motion artifacts, and arousal (Hindriks et al., 2016; Hlinka &
Hadrava, 2015; Laumann et al., 2017; Liégeois et al., 2017) rather than current cognitive
content or information processing. From this second perspective, the focus of resting state
analysis is on finding a clean and reliable static FC measure that may be informative about brain
organization.
566
The information held in events, then, largely depends on which perspective one takes. From a
dynamic FC states perspective, events may help identify states and characterize their properties
in a more temporally specific way. Indeed, events have been used to identify states within
resting state fMRI (Sporns et al., 2021), states that differentiate people (Jo et al., 2021) and
states related to variation in hormone concentrations within individuals across days (Greenwell
et al., 2021). However, from a static FC perspective, events may instead reflect moments of
randomly good representation of the static FC structure. From this view, the previous results
could be interpreted as occurring because events are particularly good timepoints for identifying
stable differences between people and stable static network structure that is relevant to
hormonal neurobiology.
577
Consistent with our findings, Novelli and Razi recently showed that many of the results of edge
functional connectivity (eFC), including the presence of high amplitude cofluctuations, can be
derived from static FC alone (Novelli & Razi, 2022). We showed in this current work that
presence of events and the gradual relationship between cofluctuation and static FC is
predictable from static FC too. While a more extended discussion of dynamic FC is outside the
scope of this work, the results shown suggest that static FC and sampling variability are
sufficient to explain the properties of high cofluctuation timepoints during rest reported so far.
This work alone does not eliminate the possibility of multiple diverse states within resting state
FC. Other modeling work has shown that events arise from biophysical models built on
structural connectivity and simulated spontaneous BOLD signal dynamics (Pope et al., 2021).
Indeed, it may be useful to use other simulations which include the time-varying components to
see the effect of that property on events. However, the present work provides a parsimonious
explanation for how events could arise from a stationary but noisy signal. We echo Novelli and
Razi in our interest in future explorations of edge FC features which cannot be explained by
static FC (Novelli & Razi, 2022).
593
594 Further, while we focused specifically on the events methodology in this paper, there is not an
595 obvious reason why the results would not extend to other methods to identify single critical

---

[2] Significant differences in dynamic FC states are seen during tasks, but they tend to be relatively small (Cole et al.,
2014; Gratton et al., 2018; Krienen et al., 2014; Laumann et al., 2017).

596 points like CAPS (co-activation patterns) and PPA (point-process analysis) among other similar
597 techniques. That is, we suspect that a stationary null model of BOLD would also predict the brief
598 instances of spontaneous brain activity reported using CAPS and PPA methodology (Liu &
599 Duyn, 2013; Tagliazucchi et al., 2012) Indeed, recent work has shown evidence for this in both
600 cases (Cifre et al., 2017; Matsui et al., 2021).
601
Finally, there is the question of the relationship between events and task-states. Previously, it
was shown that events temporally synchronize across subjects during a movie watching task
(Esfahlani et al., 2020). We did not explore the relationship between events and tasks in this
paper, but given that arousal and tasks can create modulations in BOLD evoked signals and
(more subtly) in BOLD functional connectivity patterns, we consider it possible that tasks and
imposed states could change the prevalence and structure of events (Betti et al., 2013; Betzel et
al., 2020; Cole et al., 2014; Gratton et al., 2016, 2018; Krienen et al., 2014; Laumann et al.,
2017; Tagliazucchi & Laufs, 2014). Indeed, in the previous results it was shown that events
during movies were driven by visual and attention networks rather than default and control
networks shown during rest, supporting the idea that they are associated with the shared visual
stimulus. However, more work is needed to fully explore these relationships and how they are
separately associated with evoked signals in each region and cofluctuations.
614
Practical considerations for fMRI functional connectivity analysis
Beyond fundamental neurophysiological concerns related to FC, events could be useful for a
range of practical applications in FC analysis. First, we wondered if events could be used to
define a filter for data points particularly suited to FC analysis. And second, given that events
are good at recapitulating static FC, we wondered if it would be possible to reduce data
collection by inducing more event-like time points.
621
Traditionally, resting state FC analyses try to isolate relevant signal by identifying and extracting
known artifacts (motion, respiration, etc.) and presuming the residual data is all equally useful
(Power et al., 2020). Esfahlani and colleagues' result was particularly exciting because it
suggested that, after addressing artifacts, the remaining data varied in utility for defining FC
structure, with events providing a means to isolate the particularly useful components (Esfahlani
et al., 2020). Although in this paper we showed that events can be explained as a consequence
of sampling variability on static FC, this does not rule out that they may be a useful analytical
tool. In fact, recent work has shown that ETS (edge-time-series) are better at identifying
individuals than static FC (Jo et al., 2021). The strategy of seeking out points with maximal
network information as a 'denoising' strategy is a paradigm shift in fMRI FC analysis and could
be an exciting avenue of future study.
633
The second question is whether the fact that events can recapitulate FC with few timepoints
suggests that FC may be effectively measured through much shorter data collection regimes. It
has become evident in recent years that it is possible to study functional brain organization at
the individual level if enough data is collected (Braga & Buckner, 2017; Gordon et al., 2017;
Laumann et al., 2015; Noble et al., 2017), with most papers suggesting more than 30 minutes of
high quality resting-state data is needed to measure static cortical FC reliably. This has
motivated significant ongoing efforts to collect large amounts of individual 'precision' data
(Fedorenko, 2021; Gratton & Braga, 2021; Naselaris et al., 2021; Pritschet et al., 2021) which
have led to novel findings, but are costly and time-intensive, and may be difficult to acquire in
clinical or pediatric populations. We wondered if, because events contain more network
structure information than other time points, one could decrease data collection by increasing
the rate of events and focusing analysis solely on those moments. The results in this manuscript
suggest that event correspondence to static FC can be explained by sampling variability and

temporal spacing - suggesting it would be difficult to ensure a high proportion of events in a
short amount of data collection time. However, the results do suggest that given a sample of
data, network structure could be maximized by selecting points which have high cofluctuation
and are well temporally spaced (at least 10 seconds apart). Future work could explore this. In
line with this, more recent publications from Betzel and colleagues have adopted an event-
selection strategy which takes temporal spacing into account (Betzel et al., 2022). Beyond
sampling methods, we are optimistic about new strategies for decreasing data collection needs
such as new MRI techniques (Lynch et al., 2020), new parcellation strategies (Kong et al.,
2019), and novel efforts to reduce artifacts (Power et al., 2020) to address these continued
issues in fMRI data collection.
657
Limitations
We will close by noting some limitations in this work and opportunities for future research. First.
we used a dataset collected from a small number of individuals. However, we showed that the
results were very similar across each participant and sessions within participants (**Fig. S1**),
suggesting robustness in these results. Second, when simulating BOLD data, we used a very
simple model which accounted only for spatial correlation and included no BOLD-like temporal
features (e.g., autocorrelation, matched spectral structure) (Cordes et al., 2001; He et al., 2010;
Liégeois et al., 2021; Zarahn et al., 1997). However, this simple model still was able to produce
event-like behavior, as was an even simpler toy model from sine-waves (**Fig. 3**). That even such
simple models showed event-like behavior suggests that events arise based on simple
properties of the BOLD timeseries. Third, as discussed, we focused on resting-state fMRI data
in this manuscript, rather than data from task sessions. However, given the synchronization of
events during movie-watching, we are curious about the relationship between events and tasks,
and hope to explore this in future work.
672
Conclusions
In this work, we investigated high cofluctuation BOLD events and found evidence suggesting
that, rather than events behaving as unique discrete timepoints that drive functional
connectivity, events may arise as an expected byproduct of a static functional network structure.
Event recapitulation of network structure was not unique, but varied continuously across
timepoints in real data, and was present in data from which events had been excluded.
Simulations demonstrated similar responses from stationary signals. Finally, one of the primary
interesting properties of events – that they can recreate static FC with a few points – is not
unique and is driven in part by sampling rate. These results suggest that events are
parsimoniously explained as a consequence of a highly correlated, modular, noisy signal
(BOLD) and therefore might be better suited as methods for identifying good representations of
static network structure than as a tool to investigate the mechanistic sources of functional
connectivity.
686

ACKNOWLEDGEMENTS
Funding was provided by NIH grant R01MH118370 (CG), NSF CAREER2048066 (CG), the
Washington University Intellectual and Developmental Disabilities Research Center Engelhardt
Family Foundation Innovation Fund (BAS) and NIH T32NS047987 (DMS). This research was
supported in part through the computational resources and staff contributions provided for the
Quest high performance computing facility at Northwestern University which is jointly supported
by the Office of the Provost, the Office for Research, and Northwestern University Information
Technology.

695
696   **DECLARATIONS OF COMPETING INTERESTS**
697   None

CITATION DIVERSITY STATEMENT

Recent work in several fields of science has identified a bias in citation practices such that papers from women and other minority scholars are under-cited relative to the number of such papers in the field (Bertolero et al., 2020; Caplar et al., 2017; Chatterjee & Werner, 2021; Dion et al., 2018; Dworkin et al., 2020; Fulvio et al., 2021; Maliniak et al., 2013; Mitchell et al., 2013; Wang et al., 2021). Here we sought to proactively consider choosing references that reflect the diversity of the field in thought, form of contribution, gender, race, ethnicity, and other factors. First, we obtained the predicted gender of the first and last author of each reference by using databases that store the probability of a first name being carried by a woman (Dworkin et al., 2020; Zhou et al., 2020). By this measure (and excluding self-citations to the first and last authors of our current paper), our references contain 8.03% woman(first)/woman(last), 10.87% man/woman, 19.14% woman/man, and 61.96% man/man. This method is limited in that a) names, pronouns, and social media profiles used to construct the databases may not, in every case, be indicative of gender identity and b) it cannot account for intersex, non-binary, or transgender people. Second, we obtained predicted racial/ethnic category of the first and last author of each reference by databases that store the probability of a first and last name being carried by an author of color (Ambekar et al., 2009; Sood & Laohaprapanon, 2018). By this measure (and excluding self-citations), our references contain 11.74% author of color (first)/author of color(last), 13.99% white author/author of color, 27.03% author of color/white author, and 47.24% white author/white author. This method is limited in that a) names and Florida Voter Data to make the predictions may not be indicative of racial/ethnic identity, and b) it cannot account for Indigenous and mixed-race authors, or those who may face differential biases due to the ambiguous racialization or ethnicization of their names. We look forward to future work that could help us to better understand how to support equitable practices in science.

REFERENCES

Allen, E. A., Damaraju, E., Plis, S. M., Erhardt, E. B., Eichele, T., & Calhoun, V. D. (2014).

Tracking whole-brain connectivity dynamics in the resting state. *Cerebral Cortex (New York, N.Y.: 1991)*, *24*(3), 663–676. https://doi.org/10.1093/cercor/bhs352

Ambekar, A., Ward, C., Mohammed, J., Male, S., & Skiena, S. (2009). Name-ethnicity classification from open sources. *Proceedings of the 15th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, 49–58. https://doi.org/10.1145/1557019.1557032

Anderson, J. S., Ferguson, M. A., Lopez-Larson, M., & Yurgelun-Todd, D. (2011). Reproducibility of single-subject functional connectivity measurements. *AJNR. American Journal of Neuroradiology*, *32*(3), 548–555. https://doi.org/10.3174/ajnr.A2330

Barttfeld, P., Uhrig, L., Sitt, J. D., Sigman, M., Jarraya, B., & Dehaene, S. (2015). Signature of consciousness in the dynamics of resting-state brain activity. *Proceedings of the National Academy of Sciences of the United States of America*, *112*(3), 887–892. https://doi.org/10.1073/pnas.1418031112

Bertolero, M., Dworkin, J., David, S., Lloreda, C. L., Srivastava, P., Stiso, J., Zhou, D., Dzirasa, K., Fair, D., Kaczkurkin, A., Marlin, B. J., Shohamy, D., Uddin, L., Zurn, P., & Bassett, D. (2020). *Racial and ethnic imbalance in neuroscience reference lists and intersections with gende*. https://doi.org/10.1101/2020.10.12.336230

Betti, V., Della Penna, S., de Pasquale, F., Mantini, D., Marzetti, L., Romani, G. L., & Corbetta, M. (2013). Natural Scenes Viewing Alters the Dynamics of Functional Connectivity in the Human Brain. *Neuron*, *79*(4), 782–797. https://doi.org/10.1016/j.neuron.2013.06.022

Betzel, R. F., Byrge, L., Esfahlani, F. Z., & Kennedy, D. P. (2020). Temporal fluctuations in the brain's modular architecture during movie-watching. *NeuroImage*, *213*, 116687. https://doi.org/10.1016/j.neuroimage.2020.116687

Betzel, R. F., Cutts, S. A., Greenwell, S., Faskowitz, J., & Sporns, O. (2022). Individualized

event structure drives individual differences in whole-brain functional connectivity.

NeuroImage, *252*, 118993. https://doi.org/10.1016/j.neuroimage.2022.118993

Bijsterbosch, J. D., Woolrich, M. W., Glasser, M. F., Robinson, E. C., Beckmann, C. F., Van

Essen, D. C., Harrison, S. J., & Smith, S. M. (2018). The relationship between spatial

configuration and functional connectivity of brain regions. *ELife*, *7*, e32992.

https://doi.org/10.7554/eLife.32992

Biswal, B., Yetkin, F. Z., Haughton, V. M., & Hyde, J. S. (1995). Functional connectivity in the

motor cortex of resting human brain using echo-planar MRI. *Magnetic Resonance in*

Medicine, *34*(4), 537–541. https://doi.org/10.1002/mrm.1910340409

Braga, R. M., & Buckner, R. L. (2017). Parallel Interdigitated Distributed Networks within the

Individual Estimated by Intrinsic Functional Connectivity. *Neuron*, *95*(2), 457-471.e5.

https://doi.org/10.1016/j.neuron.2017.06.038

Braga, R. M., DiNicola, L. M., Becker, H. C., & Buckner, R. L. (2020). Situating the left-

lateralized language network in the broader organization of multiple specialized large-

scale distributed networks. *Journal of Neurophysiology*, *124*(5), 1415–1448.

https://doi.org/10.1152/jn.00753.2019

Calhoun, V. D., Miller, R., Pearlson, G., & Adalı, T. (2014). The chronnectome: Time-varying

connectivity networks as the next frontier in fMRI data discovery. *Neuron*, *84*(2), 262–

274. https://doi.org/10.1016/j.neuron.2014.10.015

Caplar, N., Tacchella, S., & Birrer, S. (2017). Quantitative evaluation of gender bias in

astronomical publications from citation counts. *Nature Astronomy*, *1*(6), 0141.

https://doi.org/10.1038/s41550-017-0141

Chang, C., & Glover, G. H. (2010). Time–frequency dynamics of resting-state brain connectivity

measured with fMRI. *NeuroImage*, *50*(1), 81–98.

https://doi.org/10.1016/j.neuroimage.2009.12.011

Chang, C., Leopold, D. A., Schölvinck, M. L., Mandelkow, H., Picchioni, D., Liu, X., Ye, F. Q.,

Turchi, J. N., & Duyn, J. H. (2016). Tracking brain arousal fluctuations with fMRI.

Proceedings of the National Academy of Sciences, *113*(16), 4518–4523.

https://doi.org/10.1073/pnas.1520613113

Chatterjee, P., & Werner, R. M. (2021). Gender Disparity in Citations in High-Impact Journal

Articles. *JAMA Network Open*, *4*(7), e2114509.

https://doi.org/10.1001/jamanetworkopen.2021.14509

Cifre, I., Zarepour, M., Horovitz, S. G., Cannas, S., & Chialvo, D. R. (2017). On why a few points

suffice to describe spatiotemporal large-scale brain dynamics. *ArXiv:1707.00759 [q-Bio]*.

http://arxiv.org/abs/1707.00759

Cole, M. W., Bassett, D. S., Power, J. D., Braver, T. S., & Petersen, S. E. (2014). Intrinsic and

task-evoked network architectures of the human brain. *Neuron*, *83*(1), 238–251.

https://doi.org/10.1016/j.neuron.2014.05.014

Cordes, D., Haughton, V. M., Arfanakis, K., Carew, J. D., Turski, P. A., Moritz, C. H., Quigley,

M. A., & Meyerand, E. (2001). Frequencies contributing to functional connectivity in the

cerebral cortex in "resting-state" data. *AJNR. American Journal of Neuroradiology*, *22*(7),

1326–1333.

Dale, A. M., Fischl, B., & Sereno, M. I. (1999). Cortical Surface-Based Analysis: I. Segmentation

and Surface Reconstruction. *NeuroImage*, *9*(2), 179–194.

https://doi.org/10.1006/nimg.1998.0395

Damaraju, E., Allen, E. A., Belger, A., Ford, J. M., McEwen, S., Mathalon, D. H., Mueller, B. A.,

Pearlson, G. D., Potkin, S. G., Preda, A., Turner, J. A., Vaidya, J. G., van Erp, T. G., &

Calhoun, V. D. (2014). Dynamic functional connectivity analysis reveals transient states

of dysconnectivity in schizophrenia. *NeuroImage: Clinical*, *5*, 298–308.

https://doi.org/10.1016/j.nicl.2014.07.003

de Lacy, N., Doherty, D., King, B. H., Rachakonda, S., & Calhoun, V. D. (2017). Disruption to control network function correlates with altered dynamic connectivity in the wider autism spectrum. *NeuroImage. Clinical*, *15*, 513–524. https://doi.org/10.1016/j.nicl.2017.05.024

Dion, M. L., Sumner, J. L., & Mitchell, S. M. L. (2018). Gendered Citation Patterns across Political Science and Social Science Methodology Fields. *Political Analysis*, *26*(3), 312–327. https://doi.org/10.1017/pan.2018.12

Du, J., & Buckner, R. L. (2021). Precision estimates of macroscale network organization in the human and their relation to anatomical connectivity in the marmoset monkey. *Current Opinion in Behavioral Sciences*, *40*, 144–152. https://doi.org/10.1016/j.cobeha.2021.04.010

Dworkin, J. D., Linn, K. A., Teich, E. G., Zurn, P., Shinohara, R. T., & Bassett, D. S. (2020). The extent and drivers of gender imbalance in neuroscience reference lists. *Nature Neuroscience*, *23*(8), 918–926. https://doi.org/10.1038/s41593-020-0658-y

Esfahlani, F. Z., Byrge, L., Tanner, J., Sporns, O., Kennedy, D. P., & Betzel, R. F. (2021). *Edge-centric analysis of time-varying functional brain networks with applications in autism spectrum disorder* (p. 2021.07.01.450812). https://doi.org/10.1101/2021.07.01.450812

Esfahlani, F. Z., Jo, Y., Faskowitz, J., Byrge, L., Kennedy, D. P., Sporns, O., & Betzel, R. F. (2020). High-amplitude cofluctuations in cortical activity drive functional connectivity. *Proceedings of the National Academy of Sciences of the United States of America*, *117*(45), 28393–28401. https://doi.org/10.1073/pnas.2005531117

Fair, D. A., Dosenbach, N. U. F., Church, J. A., Cohen, A. L., Brahmbhatt, S., Miezin, F. M., Barch, D. M., Raichle, M. E., Petersen, S. E., & Schlaggar, B. L. (2007). Development of distinct control networks through segregation and integration. *Proceedings of the National Academy of Sciences*, *104*(33), 13507–13512. https://doi.org/10.1073/pnas.0705843104

Fair, D. A., Miranda-Dominguez, O., Snyder, A. Z., Perrone, A., Earl, E. A., Van, A. N., Koller, J.

M., Feczko, E., Tisdall, M. D., van der Kouwe, A., Klein, R. L., Mirro, A. E., Hampton, J.

M., Adeyemo, B., Laumann, T. O., Gratton, C., Greene, D. J., Schlaggar, B. L., Hagler,

D. J., … Dosenbach, N. U. F. (2020). Correction of respiratory artifacts in MRI head

motion estimates. *NeuroImage*, *208*, 116400.

https://doi.org/10.1016/j.neuroimage.2019.116400

Fedorenko, E. (2021). The early origins and the growing popularity of the individual-subject

analytic approach in human neuroscience. *Current Opinion in Behavioral Sciences*, *40*,

105–112. https://doi.org/10.1016/j.cobeha.2021.02.023

Finn, E. S., Shen, X., Scheinost, D., Rosenberg, M. D., Huang, J., Chun, M. M., Papademetris,

X., & Constable, R. T. (2015). Functional connectome fingerprinting: Identifying

individuals using patterns of brain connectivity. *Nature Neuroscience*, *18*(11), 1664–

1671. https://doi.org/10.1038/nn.4135

Fulvio, J. M., Akinnola, I., & Postle, B. R. (2021). Gender (Im)balance in Citation Practices in

Cognitive Neuroscience. *Journal of Cognitive Neuroscience*, *33*(1), 3–7.

https://doi.org/10.1162/jocn_a_01643

Glasser, M. F., Sotiropoulos, S. N., Wilson, J. A., Coalson, T. S., Fischl, B., Andersson, J. L.,

Xu, J., Jbabdi, S., Webster, M., Polimeni, J. R., Van Essen, D. C., & Jenkinson, M.

(2013). The minimal preprocessing pipelines for the Human Connectome Project.

NeuroImage, *80*, 105–124. https://doi.org/10.1016/j.neuroimage.2013.04.127

Gonzalez-Castillo, J., Hoy, C. W., Handwerker, D. A., Robinson, M. E., Buchanan, L. C., Saad,

Z. S., & Bandettini, P. A. (2015). Tracking ongoing cognition in individuals using brief,

whole-brain functional connectivity patterns. *Proceedings of the National Academy of*

Sciences, *112*(28), 8762–8767. https://doi.org/10.1073/pnas.1501242112

Gordon, E. M., Laumann, T. O., Adeyemo, B., Huckins, J. F., Kelley, W. M., & Petersen, S. E.

(2016). Generation and Evaluation of a Cortical Area Parcellation from Resting-State

Correlations. *Cerebral Cortex (New York, N.Y.: 1991)*, *26*(1), 288–303.

https://doi.org/10.1093/cercor/bhu239

Gordon, E. M., Laumann, T. O., Gilmore, A. W., Newbold, D. J., Greene, D. J., Berg, J. J.,

Ortega, M., Hoyt-Drazen, C., Gratton, C., Sun, H., Hampton, J. M., Coalson, R. S.,

Nguyen, A. L., McDermott, K. B., Shimony, J. S., Snyder, A. Z., Schlaggar, B. L.,

Petersen, S. E., Nelson, S. M., & Dosenbach, N. U. F. (2017). Precision Functional

Mapping of Individual Human Brains. *Neuron*, *95*(4), 791-807.e7.

https://doi.org/10.1016/j.neuron.2017.07.011

Gratton, C., & Braga, R. M. (2021). Editorial overview: Deep imaging of the individual brain:

past, practice, and promise. *Current Opinion in Behavioral Sciences*, *40*, iii–vi.

https://doi.org/10.1016/j.cobeha.2021.06.011

Gratton, C., Laumann, T. O., Gordon, E. M., Adeyemo, B., & Petersen, S. E. (2016). Evidence

for Two Independent Factors that Modify Brain Networks to Meet Task Goals. *Cell*

Reports, *17*(5), 1276–1288. https://doi.org/10.1016/j.celrep.2016.10.002

Gratton, C., Laumann, T. O., Nielsen, A. N., Greene, D. J., Gordon, E. M., Gilmore, A. W.,

Nelson, S. M., Coalson, R. S., Snyder, A. Z., Schlaggar, B. L., Dosenbach, N. U. F., &

Petersen, S. E. (2018). Functional Brain Networks Are Dominated by Stable Group and

Individual Factors, Not Cognitive or Daily Variation. *Neuron*, *98*(2), 439-452.e5.

https://doi.org/10.1016/j.neuron.2018.03.035

Greenwell, S., Faskowitz, J., Pritschet, L., Santander, T., Jacobs, E. G., & Betzel, R. F. (2021).

High-amplitude network co-fluctuations linked to variation in hormone concentrations

over menstrual cycle (p. 2021.07.29.453892). https://doi.org/10.1101/2021.07.29.453892

Guerra-Carrillo, B., Mackey, A. P., & Bunge, S. A. (2014). Resting-State fMRI: A Window into

Human Brain Plasticity. *The Neuroscientist*, *20*(5), 522–533.

https://doi.org/10.1177/1073858414524442

He, B. J., Zempel, J. M., Snyder, A. Z., & Raichle, M. E. (2010). The temporal structures and

functional significance of scale-free brain activity. *Neuron*, *66*(3), 353–369.

https://doi.org/10.1016/j.neuron.2010.04.020

Heeger, D. J., Huk, A. C., Geisler, W. S., & Albrecht, D. G. (2000). Spikes versus BOLD: What

does neuroimaging tell us about neuronal activity? *Nature Neuroscience*, *3*(7), 631–633.

https://doi.org/10.1038/76572

Hindriks, R., Adhikari, M. H., Murayama, Y., Ganzetti, M., Mantini, D., Logothetis, N. K., & Deco,

G. (2016). Can sliding-window correlations reveal dynamic functional connectivity in

resting-state fMRI? *NeuroImage*, *127*, 242–256.

https://doi.org/10.1016/j.neuroimage.2015.11.055

Hlinka, J., & Hadrava, M. (2015). On the danger of detecting network states in white noise.

Frontiers in Computational Neuroscience, *9*, 11.

https://doi.org/10.3389/fncom.2015.00011

Honey, C. J., Sporns, O., Cammoun, L., Gigandet, X., Thiran, J. P., Meuli, R., & Hagmann, P.

(2009). Predicting human resting-state functional connectivity from structural

connectivity. *Proceedings of the National Academy of Sciences*, *106*(6), 2035–2040.

https://doi.org/10.1073/pnas.0811168106

Hutchison, M. R., Womelsdorf, T., Gati, J. S., Everling, S., & Menon, R. S. (2013). Resting-state

networks show dynamic functional connectivity in awake humans and anesthetized

macaques. *Human Brain Mapping*, *34*(9), 2154–2177.

https://doi.org/10.1002/hbm.22058

Hutchison, R. M., Womelsdorf, T., Allen, E. A., Bandettini, P. A., Calhoun, V. D., Corbetta, M.,

Della Penna, S., Duyn, J. H., Glover, G. H., Gonzalez-Castillo, J., Handwerker, D. A.,

Keilholz, S., Kiviniemi, V., Leopold, D. A., de Pasquale, F., Sporns, O., Walter, M., &

Chang, C. (2013). Dynamic functional connectivity: Promise, issues, and interpretations.

NeuroImage, *80*, 360–378. https://doi.org/10.1016/j.neuroimage.2013.05.079

Jo, Y., Faskowitz, J., Esfahlani, F. Z., Sporns, O., & Betzel, R. F. (2021). Subject identification

using edge-centric functional connectivity. *NeuroImage*, *238*, 118204.

https://doi.org/10.1016/j.neuroimage.2021.118204

Johnston, J. M., Vaishnavi, S. N., Smyth, M. D., Zhang, D., He, B. J., Zempel, J. M., Shimony, J.

S., Snyder, A. Z., & Raichle, M. E. (2008). Loss of Resting Interhemispheric Functional

Connectivity after Complete Section of the Corpus Callosum. *Journal of Neuroscience*,

28(25), 6453–6458. https://doi.org/10.1523/JNEUROSCI.0573-08.2008

Kong, R., Li, J., Orban, C., Sabuncu, M. R., Liu, H., Schaefer, A., Sun, N., Zuo, X.-N., Holmes,

A. J., Eickhoff, S. B., & Yeo, B. T. T. (2019). Spatial Topography of Individual-Specific

Cortical Networks Predicts Human Cognition, Personality, and Emotion. *Cerebral Cortex*

(New York, N.Y.: 1991), *29*(6), 2533–2551. https://doi.org/10.1093/cercor/bhy123

Krienen, F. M., Yeo, B. T. T., & Buckner, R. L. (2014). Reconfigurable task-dependent functional

coupling modes cluster around a core functional architecture. *Philosophical Transactions*

of the Royal Society of London. Series B, Biological Sciences, *369*(1653), 20130526.

https://doi.org/10.1098/rstb.2013.0526

Kucyi, A., & Davis, K. D. (2014). Dynamic functional connectivity of the default mode network

tracks daydreaming. *NeuroImage*, *100*, 471–480.

https://doi.org/10.1016/j.neuroimage.2014.06.044

Kupis, L., Goodman, Z. T., Kornfeld, S., Hoang, S., Romero, C., Dirks, B., Dehoney, J., Chang,

C., Spreng, R. N., Nomi, J. S., & Uddin, L. Q. (2021). Brain Dynamics Underlying

Cognitive Flexibility Across the Lifespan. *Cerebral Cortex*, *31*(11), 5263–5274.

https://doi.org/10.1093/cercor/bhab156

Laumann, T. O., Gordon, E. M., Adeyemo, B., Snyder, A. Z., Joo, S. J., Chen, M.-Y., Gilmore,

A. W., McDermott, K. B., Nelson, S. M., Dosenbach, N. U. F., Schlaggar, B. L., Mumford,

J. A., Poldrack, R. A., & Petersen, S. E. (2015). Functional System and Areal

Organization of a Highly Sampled Individual Human Brain. *Neuron*, *87*(3), 657–670.

https://doi.org/10.1016/j.neuron.2015.06.037

Laumann, T. O., & Snyder, A. Z. (2021). Brain activity is not only for thinking. *Current Opinion in*

Behavioral Sciences, *40*, 130–136. https://doi.org/10.1016/j.cobeha.2021.04.002

Laumann, T. O., Snyder, A. Z., Mitra, A., Gordon, E. M., Gratton, C., Adeyemo, B., Gilmore, A.

W., Nelson, S. M., Berg, J. J., Greene, D. J., McCarthy, J. E., Tagliazucchi, E., Laufs, H.,

Schlaggar, B. L., Dosenbach, N. U. F., & Petersen, S. E. (2017). On the Stability of

BOLD fMRI Correlations. *Cerebral Cortex (New York, N.Y.: 1991)*, *27*(10), 4719–4732.

https://doi.org/10.1093/cercor/bhw265

Lewis, C. M., Baldassarre, A., Committeri, G., Romani, G. L., & Corbetta, M. (2009). Learning

sculpts the spontaneous activity of the resting human brain. *Proceedings of the National*

Academy of Sciences, *106*(41), 17558–17563. https://doi.org/10.1073/pnas.0902455106

Liégeois, R., Laumann, T. O., Snyder, A. Z., Zhou, J., & Yeo, B. T. T. (2017). Interpreting

temporal fluctuations in resting-state functional connectivity MRI. *NeuroImage*, *163*,

437–455. https://doi.org/10.1016/j.neuroimage.2017.09.012

Liégeois, R., Li, J., Kong, R., Orban, C., Van De Ville, D., Ge, T., Sabuncu, M. R., & Yeo, B. T.

T. (2019). Resting brain dynamics at different timescales capture distinct aspects of

human behavior. *Nature Communications*, *10*(1), 2317. https://doi.org/10.1038/s41467-

019-10317-7

Liégeois, R., Yeo, B. T. T., & Van De Ville, D. (2021). Interpreting null models of resting-state

functional MRI dynamics: Not throwing the model out with the hypothesis. *NeuroImage*,

243, 118518. https://doi.org/10.1016/j.neuroimage.2021.118518

Liu, X., & Duyn, J. H. (2013). Time-varying functional network information extracted from brief

instances of spontaneous brain activity. *Proceedings of the National Academy of*

Sciences of the United States of America, *110*(11), 4392–4397.

https://doi.org/10.1073/pnas.1216856110

Logothetis, N. K., Pauls, J., Augath, M., Trinath, T., & Oeltermann, A. (2001).

Neurophysiological investigation of the basis of the fMRI signal. *Nature*, *412*(6843), 150–

157. https://doi.org/10.1038/35084005

Lu, J., Liu, H., Zhang, M., Wang, D., Cao, Y., Ma, Q., Rong, D., Wang, X., Buckner, R. L., & Li,

K. (2011). Focal Pontine Lesions Provide Evidence That Intrinsic Functional Connectivity

Reflects Polysynaptic Anatomical Pathways. *Journal of Neuroscience*, *31*(42), 15065–

15071. https://doi.org/10.1523/JNEUROSCI.2364-11.2011

Lurie, D. J., Kessler, D., Bassett, D. S., Betzel, R. F., Breakspear, M., Kheilholz, S., Kucyi, A.,

Liégeois, R., Lindquist, M. A., McIntosh, A. R., Poldrack, R. A., Shine, J. M., Thompson,

W. H., Bielczyk, N. Z., Douw, L., Kraft, D., Miller, R. L., Muthuraman, M., Pasquini, L., …

Calhoun, V. D. (2020). Questions and controversies in the study of time-varying

functional connectivity in resting fMRI. *Network Neuroscience (Cambridge, Mass.)*, *4*(1),

30–69. https://doi.org/10.1162/netn_a_00116

Lynch, C. J., Power, J. D., Scult, M. A., Dubin, M., Gunning, F. M., & Liston, C. (2020). Rapid

Precision Functional Mapping of Individuals Using Multi-Echo fMRI. *Cell Reports*, *33*(12),

108540. https://doi.org/10.1016/j.celrep.2020.108540

Maliniak, D., Powers, R., & Walter, B. F. (2013). The Gender Citation Gap in International

Relations. *International Organization*, *67*(4), 889–922.

https://doi.org/10.1017/S0020818313000209

Marcus, D. S., Harwell, J., Olsen, T., Hodge, M., Glasser, M. F., Prior, F., Jenkinson, M.,

Laumann, T., Curtiss, S. W., & Van Essen, D. C. (2011). Informatics and data mining

tools and strategies for the human connectome project. *Frontiers in Neuroinformatics*, *5*.

Scopus. https://doi.org/10.3389/fninf.2011.00004

Margulies, D. S., Vincent, J. L., Kelly, C., Lohmann, G., Uddin, L. Q., Biswal, B. B., Villringer, A.,

Castellanos, F. X., Milham, M. P., & Petrides, M. (2009). Precuneus shares intrinsic

functional architecture in humans and monkeys. *Proceedings of the National Academy*

of Sciences, *106*(47), 20069–20074. https://doi.org/10.1073/pnas.0905314106

Matsui, T., Pham, T. Q., Jimura, K., & Chikazoe, J. (2021). *On co-activation pattern analysis*

and non-stationarity of resting brain activity (p. 2021.08.30.458155).

https://doi.org/10.1101/2021.08.30.458155

Mhuircheartaigh, R. N., Rosenorn-Lanng, D., Wise, R., Jbabdi, S., Rogers, R., & Tracey, I.

(2010). Cortical and subcortical connectivity changes during decreasing levels of

consciousness in humans: A functional magnetic resonance imaging study using

propofol. *The Journal of Neuroscience: The Official Journal of the Society for*

Neuroscience, *30*(27), 9095–9102. https://doi.org/10.1523/JNEUROSCI.5516-09.2010

Miranda-Dominguez, O., Mills, B. D., Carpenter, S. D., Grant, K. A., Kroenke, C. D., Nigg, J. T.,

& Fair, D. A. (2014). Connectotyping: Model based fingerprinting of the functional

connectome. *PloS One*, *9*(11), e111048. https://doi.org/10.1371/journal.pone.0111048

Mitchell, S. M., Lange, S., & Brus, H. (2013). Gendered Citation Patterns in International

Relations Journals. *International Studies Perspectives*, *14*(4), 485–492.

https://doi.org/10.1111/insp.12026

Mitra, A., Snyder, A. Z., Tagliazucchi, E., Laufs, H., & Raichle, M. E. (2015). Propagated infra-

slow intrinsic brain activity reorganizes across wake and slow wave sleep. *ELife*, *4*,

e10781. https://doi.org/10.7554/eLife.10781

Mueller, S., Wang, D., Fox, M. D., Yeo, B. T. T., Sepulcre, J., Sabuncu, M. R., Shafee, R., Lu,

J., & Liu, H. (2013). Individual variability in functional connectivity architecture of the

human brain. *Neuron*, *77*(3), 586–595. https://doi.org/10.1016/j.neuron.2012.12.028

Naselaris, T., Allen, E., & Kay, K. (2021). Extensive sampling for complete models of individual

brains. *Current Opinion in Behavioral Sciences*, *40*, 45–51.

https://doi.org/10.1016/j.cobeha.2020.12.008

Newbold, D. J., Laumann, T. O., Hoyt, C. R., Hampton, J. M., Montez, D. F., Raut, R. V.,

      Ortega, M., Mitra, A., Nielsen, A. N., Miller, D. B., Adeyemo, B., Nguyen, A. L.,

      Scheidter, K. M., Tanenbaum, A. B., Van, A. N., Marek, S., Schlaggar, B. L., Carter, A.

      R., Greene, D. J., … Dosenbach, N. U. F. (2020). Plasticity and Spontaneous Activity

      Pulses in Disused Human Brain Circuits. *Neuron*, *107*(3), 580-589.e6.

      https://doi.org/10.1016/j.neuron.2020.05.007

Newman, M., & Girvan, M. (2004). Finding and evaluating community structure in networks.

      Physical Review E, *69*(2), 026113. https://doi.org/10.1103/PhysRevE.69.026113

Nir, Y., Mukamel, R., Dinstein, I., Privman, E., Harel, M., Fisch, L., Gelbard-Sagiv, H.,

      Kipervasser, S., Andelman, F., Neufeld, M. Y., Kramer, U., Arieli, A., Fried, I., & Malach,

      R. (2008). Interhemispheric correlations of slow spontaneous neuronal fluctuations

      revealed in human sensory cortex. *Nature Neuroscience*, *11*(9), 1100–1108.

      https://doi.org/10.1038/nn.2177

Noble, S., Spann, M. N., Tokoglu, F., Shen, X., Constable, R. T., & Scheinost, D. (2017).

      Influences on the Test-Retest Reliability of Functional Connectivity MRI and its

      Relationship with Behavioral Utility. *Cerebral Cortex (New York, N.Y.: 1991)*, *27*(11),

      5415–5429. https://doi.org/10.1093/cercor/bhx230

Novelli, L., & Razi, A. (2022). A mathematical perspective on edge-centric brain functional

      connectivity. *Nature Communications*, *13*(1), 2693. https://doi.org/10.1038/s41467-022-

      29775-7

Palanca, B. J. A., Mitra, A., Larson-Prior, L., Snyder, A. Z., Avidan, M. S., & Raichle, M. E.

      (2015). Resting-state Functional Magnetic Resonance Imaging Correlates of

      Sevoflurane-induced Unconsciousness. *Anesthesiology*, *123*(2), 346–356.

      https://doi.org/10.1097/ALN.0000000000000731

Petridou, N., Gaudes, C. C., Dryden, I. L., Francis, S. T., & Gowland, P. A. (2013). Periods of

      rest in fMRI contain individual spontaneous events which are related to slowly fluctuating

spontaneous activity. *Human Brain Mapping*, *34*(6), 1319–1329.

https://doi.org/10.1002/hbm.21513

Poldrack, R. A., Laumann, T. O., Koyejo, O., Gregory, B., Hover, A., Chen, M.-Y., Gorgolewski,

K. J., Luci, J., Joo, S. J., Boyd, R. L., Hunicke-Smith, S., Simpson, Z. B., Caven, T.,

Sochat, V., Shine, J. M., Gordon, E., Snyder, A. Z., Adeyemo, B., Petersen, S. E., …

Mumford, J. A. (2015). Long-term neural and physiological phenotyping of a single

human. *Nature Communications*, *6*, 8885. https://doi.org/10.1038/ncomms9885

Pope, M., Fukushima, M., Betzel, R. F., & Sporns, O. (2021). Modular origins of high-amplitude

cofluctuations in fine-scale functional connectivity dynamics. *Proceedings of the National*

Academy of Sciences, *118*(46), e2109380118. https://doi.org/10.1073/pnas.2109380118

Power, J. D., Cohen, A. L., Nelson, S. M., Wig, G. S., Barnes, K. A., Church, J. A., Vogel, A. C.,

Laumann, T. O., Miezin, F. M., Schlaggar, B. L., & Petersen, S. E. (2011). Functional

network organization of the human brain. *Neuron*, *72*(4), 665–678.

https://doi.org/10.1016/j.neuron.2011.09.006

Power, J. D., Lynch, C. J., Adeyemo, B., & Petersen, S. E. (2020). A Critical, Event-Related

Appraisal of Denoising in Resting-State fMRI Studies. *Cerebral Cortex (New York, N.Y.:*

1991), *30*(10), 5544–5559. https://doi.org/10.1093/cercor/bhaa139

Power, J. D., Mitra, A., Laumann, T. O., Snyder, A. Z., Schlaggar, B. L., & Petersen, S. E.

(2014). Methods to detect, characterize, and remove motion artifact in resting state fMRI.

NeuroImage, *84*, 320–341. https://doi.org/10.1016/j.neuroimage.2013.08.048

Pritschet, L., Taylor, C. M., Santander, T., & Jacobs, E. G. (2021). Applying dense-sampling

methods to reveal dynamic endocrine modulation of the nervous system. *Current*

Opinion in Behavioral Sciences, *40*, 72–78. https://doi.org/10.1016/j.cobeha.2021.01.012

Rashid, B., Arbabshirani, M. R., Damaraju, E., Cetin, M. S., Miller, R., Pearlson, G. D., &

Calhoun, V. D. (2016). Classification of schizophrenia and bipolar patients using static

and dynamic resting-state fMRI brain connectivity. *NeuroImage*, *134*, 645–657.

https://doi.org/10.1016/j.neuroimage.2016.04.051

Sadaghiani, S., Poline, J.-B., Kleinschmidt, A., & D'Esposito, M. (2015). Ongoing dynamics in

large-scale functional connectivity predict perception. *Proceedings of the National*

Academy of Sciences, *112*(27), 8463–8468. https://doi.org/10.1073/pnas.1420687112

Sämann, P. G., Wehrle, R., Hoehn, D., Spoormaker, V. I., Peters, H., Tully, C., Holsboer, F., &

Czisch, M. (2011). Development of the brain's default mode network from wakefulness

to slow wave sleep. *Cerebral Cortex (New York, N.Y.: 1991)*, *21*(9), 2082–2093.

https://doi.org/10.1093/cercor/bhq295

Seitzman, B. A., Gratton, C., Laumann, T. O., Gordon, E. M., Adeyemo, B., Dworetsky, A.,

Kraus, B. T., Gilmore, A. W., Berg, J. J., Ortega, M., Nguyen, A., Greene, D. J.,

McDermott, K. B., Nelson, S. M., Lessov-Schlaggar, C. N., Schlaggar, B. L., Dosenbach,

N. U. F., & Petersen, S. E. (2019). Trait-like variants in human functional brain networks.

Proceedings of the National Academy of Sciences, *116*(45), 22851–22861.

https://doi.org/10.1073/pnas.1902932116

Shakil, S., Lee, C.-H., & Keilholz, S. D. (2016). Evaluation of sliding window correlation

performance for characterizing dynamic functional connectivity and brain states.

NeuroImage, *133*, 111–128. https://doi.org/10.1016/j.neuroimage.2016.02.074

Shmuel, A., & Leopold, D. A. (2008). Neuronal correlates of spontaneous fluctuations in fMRI

signals in monkey visual cortex: Implications for functional connectivity at rest. *Human*

Brain Mapping, *29*(7), 751–761. https://doi.org/10.1002/hbm.20580

Smith, S. M., Fox, P. T., Miller, K. L., Glahn, D. C., Fox, P. M., Mackay, C. E., Filippini, N.,

Watkins, K. E., Toro, R., Laird, A. R., & Beckmann, C. F. (2009). Correspondence of the

brain's functional architecture during activation and rest. *Proceedings of the National*

Academy of Sciences, *106*(31), 13040–13045. https://doi.org/10.1073/pnas.0905267106

Smith, S. M., Nichols, T. E., Vidaurre, D., Winkler, A. M., Behrens, T. E. J., Glasser, M. F.,

Ugurbil, K., Barch, D. M., Van Essen, D. C., & Miller, K. L. (2015). A positive-negative

mode of population covariation links brain connectivity, demographics and behavior.

Nature Neuroscience, *18*(11), 1565–1567. https://doi.org/10.1038/nn.4125

Sood, G., & Laohaprapanon, S. (2018). Predicting Race and Ethnicity From the Sequence of

Characters in a Name. *ArXiv:1805.02109 [Stat]*. http://arxiv.org/abs/1805.02109

Sporns, O., Faskowitz, J., Teixeira, A. S., Cutts, S. A., & Betzel, R. F. (2021). Dynamic

expression of brain functional systems disclosed by fine-scale analysis of edge time

series. *Network Neuroscience (Cambridge, Mass.)*, *5*(2), 405–433.

https://doi.org/10.1162/netn_a_00182

Tagliazucchi, E., Balenzuela, P., Fraiman, D., & Chialvo, D. R. (2012). Criticality in large-scale

brain FMRI dynamics unveiled by a novel point process analysis. *Frontiers in*

Physiology, *3*, 15. https://doi.org/10.3389/fphys.2012.00015

Tagliazucchi, E., & Laufs, H. (2014). Decoding wakefulness levels from typical fMRI resting-

state data reveals reliable drifts between wakefulness and sleep. *Neuron*, *82*(3), 695–

708. https://doi.org/10.1016/j.neuron.2014.03.020

Tambini, A., Ketz, N., & Davachi, L. (2010). Enhanced Brain Correlations during Rest Are

Related to Memory for Recent Experiences. *Neuron*, *65*(2), 280–290.

https://doi.org/10.1016/j.neuron.2010.01.001

Tavor, I., Jones, O. P., Mars, R. B., Smith, S. M., Behrens, T. E., & Jbabdi, S. (2016). Task-free

MRI predicts individual differences in brain activity during task performance. *Science*,

352(6282), 216–220. https://doi.org/10.1126/science.aad8127

van den Heuvel, M. P., Stam, C. J., Kahn, R. S., & Hulshoff Pol, H. E. (2009). Efficiency of

functional brain networks and intellectual performance. *The Journal of Neuroscience:*

The Official Journal of the Society for Neuroscience, *29*(23), 7619–7624.

https://doi.org/10.1523/JNEUROSCI.1443-09.2009

Vincent, J.-L., Patel, G. H., Fox, M. D., Snyder, A. Z., Baker, J. T., Van Essen, D. C., Zempel, J.

M., Snyder, L. H., Corbetta, M., & Raichle, M. E. (2007). Intrinsic functional architecture

in the anaesthetized monkey brain. *Nature*, *447*(7140), 83–86.

https://doi.org/10.1038/nature05758

Voss, M. W., Prakash, R. S., Erickson, K. I., Boot, W. R., Basak, C., Neider, M. B., Simons, D.

J., Fabiani, M., Gratton, G., & Kramer, A. F. (2012). Effects of training strategies

implemented in a complex videogame on functional connectivity of attentional networks.

NeuroImage, *59*(1), 138–148. https://doi.org/10.1016/j.neuroimage.2011.03.052

Wang, X., Dworkin, J. D., Zhou, D., Stiso, J., Falk, E. B., Bassett, D. S., Zurn, P., & Lydon-

Staley, D. M. (2021). Gendered citation practices in the field of communication. *Annals*

of the International Communication Association, *45*(2), 134–153.

https://doi.org/10.1080/23808985.2021.1960180

Yeo, B. T., Krienen, F. M., Sepulcre, J., Sabuncu, M. R., Lashkari, D., Hollinshead, M., Roffman,

J. L., Smoller, J. W., Zöllei, L., Polimeni, J. R., Fischl, B., Liu, H., & Buckner, R. L.

(2011). The organization of the human cerebral cortex estimated by intrinsic functional

connectivity. *Journal of Neurophysiology*, *106*(3), 1125–1165.

https://doi.org/10.1152/jn.00338.2011

Zarahn, E., Aguirre, G. K., & D'Esposito, M. (1997). Empirical analyses of BOLD fMRI statistics.

I. Spatially unsmoothed data collected under null-hypothesis conditions. *NeuroImage*,

5(3), 179–197. https://doi.org/10.1006/nimg.1997.0263

Zhou, D., Cornblath, E. J., Stiso, J., Teich, E. G., Dworkin, J. D., Blevins, A. S., & Bassett, D. S.

(2020). *Gender Diversity Statement and Code Notebook v1.0*. Zenodo.

https://doi.org/10.5281/zenodo.3672110

 SUPPLEMENTAL INFORMATION

1129
1130 **Figure S1, related to Figure 1:** Individual subject results for Figure 1 analyses. In all subjects
1131 and sessions, the relationships present between cofluctuation and correlation with time-
1132 averaged FC (A) and modularity (B) are continuous, positive, and gradual. It suggests that in all
1133 cases, neither high or low cofluctuation time points are discrete. Boxplots show the median, 25[th]
1134 and 75[th] percentile values per subject calculated across sessions.

1135
Figure S2, related to Figure 1: Re-analysis of MSC06 data without a lowpass filter. The
general pattern of increasing network structure with cofluctuation is still present in non-low-pass-
filtered data across 10 sessions in one subject. This is reflected in correlation with static FC (A)
and modularity (B). Notably, there is an overall decrease in network structure across all bins
versus filtered data. This is to be expected, as high frequencies of BOLD contain noise (e.g.,
respiratory and cardiac) that may obscure network structure.

1142

Figure S3, related to Figure 2: Individual subject results for simulation analysis. In all subjects,
the relationships present between cofluctuation amplitude and correlation with time-averaged
FC (A) and modularity (B) are continuous, positive, and extremely similar to the relationships
present in real data. This suggests sampling variability in static FC is sufficient to explain the
presence of high and low cofluctuation points in real data.

Figure S4, related to Figure 2: As in Esfahlani et al 2020, we find that the first principal component extracted from high and low amplitude cofluctuations corresponded to an activity pattern with shared fluctuations between default-mode and control areas and anti-correlated with fluctuations in sensorimotor and attention areas (A). We find these patterns are nearly identical in simulated data (B), suggesting that static FC is sufficient to explain this result.

Distance Between Adjacent Sampled Points

Figure S5, Related to Figure 4: Temporal spacing histograms as in **Fig. 4B** but for 11 cofluctuation bins. Temporal spacing for all bins appears more spaced than consecutive and less spaced than random. It appears less spaced for the most extreme (100[th] and 5[th]) bins than for other bins.

1159
Figure S6, Related to Figure 4: After accounting for spacing, there remains a graded hierarchy
of network structure with cofluctuation. We completed a circular shifting analysis (see *Methods*)
where time points are binned by cofluctuation and then circularly offset. Due to scrubbing, it was
not possible to select as many time points per bin (typically all time points, 5% of total time
points) without running into scrubbed points while circularly shifting the values. To address this
issue, we randomly sampled only 5 eligible points per bin and used fewer bins (95-100, 85-90,
70-75, 45-50, 20-25, 0-5). This resulted in a smaller number of sessions (53/90) which
contained full data for all bin and shift combinations. Because we used only five points,
correlation values (maximum = 0.45 in group data) were much lower than when we calculate
similarity with session FC using 5% of available points. We completed 100 iterations of this
analysis and averaged the results to reduce single trial bias of the random selection of 5 eligible
points. Higher cofluctuation bins have stronger correlation with time averaged FC compared to
their offset counterparts and lower cofluctuation bins have weaker correlation. This suggests
that while temporal spacing does in part drive the similarity of events to static network structure,
there is a relationship between cofluctuation and network structure. **Fig. 2** suggests this is
parsimoniously explained by sampling variability.

1176
Figure S7, Related to Figure 4: Given a fixed number of sampled points, increasing temporal
spacing between samples increases the similarity with static FC. We sampled 5% of time points
for each session in each subject and correlated it with static FC. We iterated over sampling
spacing from sampling consecutive points (0 points between samples) to the maximum possible
spacing (total # time points / # sampled points). We find that ~10 seconds (4-5 TRs here)
between samples appears adequate to achieve most of the benefit of spaced sampling.