Rabbit hindlimb kinematics and ground contact pressure during the stance phase of hopping gait

Patrick Hall [Corresp., 1] , Caleb Stubbs [1] , David E Anderson [2] , Cheryl B Greenacre [3] , Dustin L Crouch [1]

[1] Mechanical, Aerospace, and Biomedical Engineering, University of Tennessee - Knoxville, Knoxville, Tennessee, United States

[2] Department of Large Animal Sciences, University of Tennessee - Knoxville, Knoxville, Tennessee, United States

[3] Department of Small Animal Sciences, University of Tennessee - Knoxville, Knoxville, Tennessee, United States

Corresponding Author: Patrick Hall
Email address: phall8@vols.utk.edu

Though the rabbit is a common animal model in musculoskeletal research, there is very limited data reported on healthy rabbit biomechanics. Our objective was to quantify the normative hindlimb biomechanics of six New Zealand White rabbits (3 male, 3 female) during the stance phase of hopping gait. We measured biomechanics by synchronously recording sagittal plane motion and ground contact pressure using a video camera and pressure mat, respectively. Both foot angle (i.e. angle between foot and ground) and ankle angle curves were unimodal. The peak ankle dorsiflexion angle was 65.9°±12.7° and occurred at 39% stance, while the peak ankle plantarflexion angle was 136.9°±7.8° at toe-off. Minimum and maximum foot angles were 16.6°±6.4° at 12% stance and 125.4°±4.0° at toe-off, respectively. During stance, the knee joint center gradually progressed 4.7 cm downward and 18.1 cm forward, on average. The maximum vertical ground reaction force and contact area, both averaged across rabbits, were 42.5 ± 11.4 %BW and 7.5 ± 1.8 cm^2, respectively. Our study confirmed that rabbits exhibit a plantigrade gait pattern, similar to humans. Future studies can reference our data to quantify the extent to which orthopedic interventions affect rabbit biomechanics.

Rabbit Hindlimb Kinematics and Ground Contact Pressure During the Stance Phase of Hopping

Gait

Authors: Patrick T. Hall[1], Caleb Stubbs[1], David E. Anderson[2], Cheryl B. Greenacre[3], Dustin L.
Crouch[1]

[1]University of Tennessee, Knoxville – Department of Mechanical, Aerospace, and Biomedical
Engineering

[2]University of Tennessee, Knoxville – Department of Large Animal Sciences

[3]University of Tennessee, Knoxville – Department of Small Animal Sciences

Corresponding author contact:

Phone: (919) 670-4234

Email: dcrouch3@utk.edu

Keywords: Rabbit, Biomechanics, Noninvasive, Stance

Word Count: 2837

Abstract

Though the rabbit is a common animal model in musculoskeletal research, there is very

limited data reported on healthy rabbit biomechanics. Our objective was to quantify the

normative hindlimb biomechanics of six New Zealand White rabbits (3 male, 3 female) during

the stance phase of hopping gait. We measured biomechanics by synchronously recording

sagittal plane motion and ground contact pressure using a video camera and pressure mat,

respectively. Both foot angle (i.e., angle between foot and ground) and ankle angle curves were

unimodal. The peak ankle dorsiflexion angle was 65.9°±12.7° and occurred at 39% stance,

while the peak ankle plantarflexion angle was 136.9°±7.8° at toe-off. Minimum and maximum

foot angles were 16.6°±6.4° at 12% stance and 125.4°±4.0° at toe-off, respectively. During

stance, the knee joint center gradually progressed 4.7 cm downward and 18.1 cm forward, on

average. The maximum vertical ground reaction force and contact area, both averaged across

rabbits, were 42.5 ± 11.4 %BW and 7.5 ± 1.8 cm^2, respectively. Our study confirmed that rabbits

exhibit a plantigrade gait pattern, similar to humans. Future studies can reference our data to

quantify the extent to which orthopedic interventions affect rabbit biomechanics.

Introduction

The rabbit is a common animal model in musculoskeletal research to, for example, test new potential clinical interventions or study the response of tissues to mechanical stimuli. Some interventions would be expected to affect the motor function of the hindlimb ankle and foot. Examples of such interventions include tenotomy of ankle dorsiflexor muscles (Abrams et al. 2000) or the Achilles tendon (Nagasawa et al. 2008; Reddy et al. 1998), immobilization of the knee and/or ankle joint (Gossman et al. 1986; Ponten & Friden 2008; Sjostrom et al. 1979), and release of tendon retinacula to manipulate muscle-tendon moment arms (Koh & Herzog 1998b; Reddy & Gupta 2007). Recently, we adopted a rabbit model to test the feasibility of a new type of ankle-foot prosthesis (Hall et al. 2021). For these interventions, quantifying their effect on motor function will be valuable, if not essential, for achieving clinical translation.

One way to quantify motor function is by measuring biomechanical variables, such as kinematics and ground reaction forces. The effect of an intervention could be determined by comparing biomechanical data between animals that did and did not receive the intervention. Unfortunately, the hindlimb biomechanics of healthy rabbits has not been well characterized. We are aware of only one previous study in which multi-sample data were limited to knee and ankle joint moments during hopping gait (Gushue et al. 2005). A more comprehensive dataset on normative rabbit hindlimb biomechanics in the literature would (1) make it easier for researchers to determine the effects of experimental interventions on motor function, (2) reduce the number of healthy animals used as experimental controls, and (3) increase basic understanding about animal locomotion.

Two common measures of hindlimb biomechanics that have not been reported for a multi-sample rabbit cohort are joint kinematics and ground contact pressure. These variables, in some respects, are similar between the rabbit hindlimb and human lower extremity. For example, the rabbit hindlimb (Bensley 1910; Kimura 1996), like the human lower extremity

(Grasso et al. 1998), is considered to exhibit a plantigrade kinematic gait pattern in which most

or all of the plantar surface of the foot contacts the ground during the stance phase. This differs

from other common animal models that exhibit either a digitigrade (e.g., cats, dogs) (Barbeau &

Rossignol 1987) or unguligrade (e.g. pigs and goats) (Polly 2007) gait pattern. Likewise, the net

vertical ground reaction force (i.e., the integral of ground contact pressure across the contact

area) during stance phase has a bimodal pattern in both rabbits (Gushue et al. 2005), and

humans (Wannop et al. 2012). Thus, in interventional studies, joint kinematics and ground

contact pressure results from rabbits may be more translateable to humans than those from

other common animal models.

The goal of our study was to quantify hindlimb ankle and foot kinematics and ground

contact pressures during the stance phase of hopping gait in healthy rabbits (i.e., rabbits that

have not received an experimental intervention). Summary results are presented below, and the

raw data are available online as supplementary data. The new biomechanics data will serve as

a valuable reference for interventional studies involving rabbits and improve our basic

understanding about rabbit locomotion.

87 **Materials & Methods**

All animal procedures were approved by the University of Tennessee, Knoxville

Institutional Animal Care and Use Committee (protocol #2637). We used a cross-sectional study

design, measuring biomechanics in one test session from both hindlimbs of six (3 male, 3

female) healthy, standard laboratory New Zealand White (NZW) rabbits (Charles River

Laboratories, Wilmington, MA). At the time of testing, the rabbits were 16 weeks old and

weighed 2.7 ± 0.33 kg. Each rabbit was one experimental unit. Since this was not a clinical trial,

there were no separate groups (i.e., control), no inclusion criteria, and no power analysis to

compute sample size. Rabbits were housed individually in adjacent crates, fed ad libitum with a

standard laboratory diet and Timothy hay, and given daily enrichment and positive human

interaction. After this study, the rabbits were subsequently used in another study to test a novel

orthopedic implant (Hall et al. 2021).

The setup for our locomotor measurement system included several components (Fig. 1,

1-3). A pressure mat (Very High Resolution Walkway 4, Tekscan, Inc., South Boston, MA) was

used to record pressure data at 60 Hz. We taped 320-grit sandpaper to the top of the smooth

pressure-sensing area to prevent the rabbits from slipping. We placed a 3-kg weight on the

sandpaper-covered mat and calibrated the mat through the Tekscan software calibration

program. The mat was placed inside a clear acrylic tunnel to guide the rabbits across the

pressure mat. The mat width (11.2 cm) permitted only unilateral pressure measurements;

therefore, to record data for both hindlimbs, we laterally offset the mat in the tunnel and had the

rabbit hop across the mat in both directions, as described below. A camera (1080P HD

Webcam, SVPRO), placed three feet away from the clear acrylic panel, captured video at 60

Hz. Video and pressure mat data were synchronized using the Tekscan Walkway software

(Tekscan, South Boston, MA).

During a two-week acclimation period prior to testing, rabbits were trained to hop

through the acrylic tunnel when given negative reinforcement (i.e., prodding). Then, at the

beginning of the test session, we shaved both hindlimbs and marked the metatarsophalangeal

(MTP), ankle, and knee joint centers on the lateral side of each hindlimb with black ink (Fig. 1,

4) to facilitate calculation of joint kinematics from the videos. After marking, we placed the rabbit

into a pen with the acrylic tunnel and pressure mat. Each trial began when the rabbit entered the

tunnel. A trial was deemed successful if the rabbit continued the hopping motion through the

entire length of the tunnel without stopping. The rabbits completed 5 trials of hopping through

the tunnel in each direction while we synchronously recorded pressure and video data for each

trial. The direction of hopping is a potential confounder, which we address as a limitation in the

Discussion section.

Data from all rabbits were included in the analysis. We calculated joint angles from the

video frames corresponding to stance phase using a custom script in MATLAB (Mathworks,

Natick, MA). The program used a bottom-hat morphology filter to distinguish the black ink marks

and calculate the centroid of each marker position (Fig. 2). Then, frame-by-frame, we visually

verified the marker centroids and, if the centroid location appeared inaccurate, corrected the

location by manually approximating the centroid from the still frame. This method assumed that

the sagittal plane orientation of the foot and shank was aligned with the line segments

connecting the centroids; this was a reasonable assumption given the arrangement of the

camera with respect to the acrylic tunnel. Finally, we calculated the angle between the foot

segment and ground (i.e., foot angle) and between the foot and shank segments (i.e., ankle

angle) throughout stance (Fig. 2). Since the camera was approximately level with the ground,

we defined the ground as the horizontal line that intersected the MTP joint. Ankle angles >90°

and <90° corresponded to plantarflexion and dorsiflexion, respectively.

Evaluating joint angles separately for each joint provides an incomplete picture of rabbit

hindlimb kinematics. This is because the hindlimb is a kinematic chain, so the positions and

orientations of proximal limb segments depend on those of distal limb segments. Therefore, we

calculated the knee joint center position in the sagittal plane from the foot and ankle angles. To

permit comparison among rabbits of different sizes, we applied the joint angles to a generic

planar kinematic model of the rabbit hindlimb (Fig. 3, A). The foot (ankle to MTP joint) and

shank (knee to ankle) segments of the model were 6.7 cm and 10.0 cm, respectively, to

approximate the anatomical lengths of the two segments in our rabbits. For each rabbit, we

computed the time-series "trajectory" of knee joint position throughout stance for each trial.

Ground contact pressure data were processed using the Tekscan Walkway software.

Each hind foot was isolated by drawing a strike box around the foot contact location, as

indicated by the pressure data (Fig. 4). From the pressure data in the strike box and for each

time point, we computed (1) average pressure, (2) contact area, and (3) net vertical ground

reaction force (vGRF). The contact area was calculated as the total geometric area within the

strike box for which the pressure was greater than zero. The vGRF was calculated as the

product of foot contact area and the average pressure across the contact area; vGRF data were

expressed as a percentage of body weight (%BW). We also computed the total contact area

over the entire stance phase. The duration of the stance phase for each limb was computed as

the length of time for which pressure was greater than zero within the limb's strike box.

In each trial, the data were calculated separately for each side (i.e., right and left). Since

the sides were measured independently, each side was considered as an independent sample

in calculations of the mean and standard deviation (i.e., n=12).

157   Results

At foot strike, the ankle angle exhibited a similar pattern to that of humans (Li & Hsiao-

Wecksler 2013), with the ankle becoming increasingly dorsiflexed for the first 39% of stance,

commonly referred to as "loading response"; for the remaining 61% of stance, considered the

"forward propulsion" sub-phase, the ankle became increasingly plantarflexed (Fig. 4). The peak

ankle dorsiflexion angle was 65.9°±12.7°, while the ankle was plantarflexed at both foot strike

(101.2°±13.7°) and toe-off (136.9°±7.8°). The foot maintained a positive angle throughout

stance, starting at 21.1°±7.3°, then decreasing to a minimum foot ankle of 16.6°±6.4° at 12%

stance. Thereafter, the foot ankle gradually increased up to 125.4°±4.0° at toe-off, indicating

that the foot rotated beyond a vertical orientation (90°). The standard deviation of the foot and

ankle angles, averaged over the stance phase, was 7.7° and 12.7° degrees, respectively.

Despite both foot and ankle angles exhibiting a unimodal curve, the knee joint center

trajectory was nearly linear (Fig. 5). During stance, the knee joint center gradually progressed

4.7 cm downward and 18.1 cm forward, on average. The standard deviation of the knee joint

center position, averaged across the stance phase, was 2.1 cm.

The maximum vGRF was 42.5±11.4 %BW, and the maximum contact area was 7.5±1.8

cm^2 (Fig. 6). Both vGRF and contact area exhibited similar bimodal trends during stance, with

the first peak occurring at approximately 25% of stance and the second occurring at

approximately 75% of stance. In fact, vGRF and contact area were strongly correlated, with a

Pearson's correlation coefficient of 0.986. Because of the correlation between vGRF and

contact area, the foot experienced a nearly constant average pressure of about 0.15 kg/cm^2

through the middle 80% of stance.

The spatial distribution of ground contact pressure indicated that, relative to the foot, the

contact area progressed from the caudal to cranial aspect of the plantar surface during stance

(Fig. 7). At foot strike, the heel and midfoot regions of the plantar surface were the first to

contact the ground. By about 25% stance, the contact area in these regions increased and

expanded toward the cranial aspect (i.e., forefoot) of the plantar surface. By about 65% of

stance, the contact area shifted entirely to the forefoot region.

The stance phase duration, averaged across all trials and sides, was 0.50±0.27 seconds

but had a right-skewed distribution; the median duration was 0.40 seconds.

Discussion

Our kinematic and pressure data confirmed that rabbits exhibit a plantigrade gait pattern,

loading the heel first (Fig. 5). Humans also have a plantigrade walking pattern and land with

their heel first (Grasso et al. 1998). However, there are differences in kinematics between

rabbits and humans. For example, foot angle during stance is more negative during human

walking (Grasso et al. 1998) than rabbit hopping (Fig. 5). Such differences must be considered

when attempting to translate results from animal models to humans.

The time-series vGRF data exhibited a bimodal pattern that is consistent with vGRF data

reported for one rabbit (Gushue et al. 2005) and for humans during walking (Wannop et al.

2012). We expect that, as with humans, the maximum vGRF that occurs at approximately 25%

of stance corresponds to the loading response triggered by the need to support body weight

during landing (Winiarski & Rutkowska-Kucharska 2009). As in humans (Grasso et al. 1998),

the second mode at approximately 75% of stance presumably corresponds to forward

propulsion, though we could not confirm this since the pressure mat cannot record horizontal

ground reaction forces.

Contact area was strongly correlated with vGRF magnitude, with a correlation coefficient

of 0.986 across all trials. The correlation explains why the average pressure was nearly

constant throughout stance phase. Maintaining a constant ground-paw pressure may be a

locomotor strategy employed by the rabbit's sensorimotor system. However, as seen in our prior

study (Hall et al. 2021), orthopedic interventions can alter the pressure between the hindlimb

and ground.

We computed the sagittal-plane position of the knee joint center, which gives an

indication of how the joint is moving in the global coordinate system. In contrast, joint angles

represent the orientation of one local coordinate frame to another, where both frames are

aligned with a limb segment. Thus, joint center position data provide important context to joint

angle data by showing how local joint-level changes may affect global limb or body position.

Joint center positions may even better reflect task goals than joint angles. For example, a

previous study found that rats with peripheral nerve injury recovered joint position kinematics

even as individual joint angles remained altered (Chang et al. 2018).

We chose an approach to measure rabbit hindlimb biomechanics that is practical for

longitudinal interventional studies in rabbits. For example, we used a markerless video-based

motion capture method to quantify hindlimb kinematics. This differs from the state-of-the-art

method that involves tracking reflective markers using multiple infrared cameras. Reflective

markers are typically placed on a subject's skin using adhesive tape, but this method is

unreliable in rabbits, in our experience. This possibly explains why the previous rabbit

biomechanics study (Gushue et al. 2005) attached reflective markers using transdermal bone

pins which, though reliable, are relatively difficult to implement and may interfere with movement

either mechanically or by causing discomfort. Bi-plane fluoroscopy can acquire detailed

kinematic data (Koh & Herzog 1998a; Tinga et al. 2018) but poses a radiation safety risk to the

animals and researchers in longitudinal studies. Finally, both infrared- and fluoroscopy-based

methods require relatively expensive equipment that must remain stationary during testing and,

thus, are not as accessible, portable, or mobile as video-based methods.

Pressure mats are also more practical for measuring ground contact forces in

quadrupedal animal models than the alternative, force plates. Force plates measure the

resultant forces along 6 degrees of freedom, which requires that only one limb contacts the

plate at a time to distinguish forces among limbs (Gushue et al. 2005; Jarrell et al. 2018).

Pressure mats, which measure vertical pressure and contact area, are more convenient to use

with quadrupedal animals since individual limbs can be distinguished even if multiple limbs

contact the mat simultaneously (de Carvalho et al. 2009; Sheldon et al. 2019; Steiner et al.

2019).

Our study was limited in several ways. First, because our pressure mat was relatively

narrow (11.2 cm), we only measured kinematic and pressure data for one hindlimb at a time. In

future studies we plan to use a wider pressure mat and two cameras (one on each side) to

capture biomechanics data from both hindlimbs simultaneously; this data will allow us to

quantify temporal relationships between sides. Second, the sample frequency (60 Hz) of our

motion capture setup allowed us to capture stance phase only; in future studies we will use

cameras with a higher sample frequency to also capture the high-frequency kinematics of the

swing phase. Third, the kinematics we computed with our custom MATLAB script were limited to

the sagittal plane. The more-advanced open-source software DeepLabCut (Mathis et al. 2018a;

Mathis et al. 2018b) uses machine learning to track anatomical features automatically and

calculate 3-D kinematics from markerless motion capture videos; we plan to use such software

in future studies. Fourth, we tracked the motion of marked points on the skin, which are more

convenient than the bone pins used in the previous rabbit biomechanics study (Gushue et al.

2005) but can move relative to underlying bony landmarks.

Conclusions

In conclusion, we have reported select hindlimb kinematics and ground contact

pressures from healthy New Zealand white rabbits. Our results showed that rabbits exhibit a

plantigrade gait pattern as described in previous literature. Hindlimb ankle kinematics during

stance were unimodal, similar to humans. Vertical ground reaction force (vGRF) and contact

area were highly correlated, resulting in relatively constant pressure during stance. Our results

add substantially to the limited existing data on rabbit hindlimb biomechanics and can be used

as an experimental control to quantify the effect experimental interventions. Additionally,

knowledge of rabbit hindlimb biomechanics can inform the design and development of

orthopedic interventions to improve functional outcomes of patients.

Conflict of Interest Statement

The authors have no conflicts of interest to report.

Acknowledgments

The authors thank Dr. Bryce Burton, Dr. Kelsey Finnie, Dr. Lori Cole, and Chris Carter

for veterinary care provided for the rabbits in this study, and the Office of Laboratory Animal

Care and Animal Housing Facility staffs at the University of Tennessee, Knoxville for animal

care assistance. Thanks to Dr. Katrina Easton for providing constructive feedback on the

manuscript. Research reported in this publication was supported by (1) the Eunice Kennedy

Shiver National Institute of Child Health & Human Development of the National Institutes of

Health under Award Number K12HD073945, (2) NSF CAREER Award #1944001, (3) a seed

grant from the University of Tennessee Office of Research and Engagement, and (4) the

University of Tennessee Department of Mechanical, Aerospace and Biomedical Engineering

start-up funds. The authors have no conflicts of interest to disclose.

References

Abrams RA, Tsai AM, Watson B, Jamali A, and Lieber RL. 2000. Skeletal muscle recovery after tenotomy
and 7-day delayed muscle length restoration. *Muscle Nerve* 23:707-714.
Barbeau H, and Rossignol S. 1987. Recovery of locomotion after chronic spinalization in the adult cat.
Brain research 412:84-95.
Bensley BA. 1910. *Practical anatomy of the rabbit*: The University Press.
Chang YH, Housley SN, Hart KS, Nardelli P, Nichols RT, Maas H, and Cope TC. 2018. Progressive
adaptation of whole-limb kinematics after peripheral nerve injury. *Biol Open* 7.
10.1242/bio.028852
de Carvalho VC, de Alencar Nääs I, Neto MM, and de Souza SRL. 2009. Measurement of pig claw
pressure distribution. *biosystems engineering* 103:357-363.
Fiker R, Kim LH, Molina LA, Chomiak T, and Whelan PJ. 2020. Visual Deep Lab Cut: A user-friendly
approach to gait analysis. *Journal of Neuroscience Methods*:108775.
Gossman MR, Rose SJ, Sahrmann SA, and Katholi CR. 1986. Length and circumference measurements in
one-joint and multijoint muscles in rabbits after immobilization. *Phys Ther* 66:516-520.
10.1093/ptj/66.4.516
Grasso R, Bianchi L, and Lacquaniti F. 1998. Motor patterns for human gait: backward versus forward
locomotion. *Journal of neurophysiology* 80:1868-1885.
Gushue DL, Houck J, and Lerner AL. 2005. Rabbit knee joint biomechanics: Motion analysis and modeling
of forces during hopping. *Journal of orthopaedic research* 23:735-742.
10.1016/j.orthres.2005.01.005

Hall PT, Bratcher SZ, Stubbs C, Rifkin RE, Grzeskowiak RM, Burton BJ, Greenacre CB, Stephenson SM,
Anderson DE, and Crouch DL. 2021. Fully Implanted Prostheses for Musculoskeletal Limb
Reconstruction After Amputation: An In Vivo Feasibility Study. *Annals of Biomedical Engineering*
49:1012-1021. 10.1007/s10439-020-02645-3
Jarrell JR, Farrell BJ, Kistenberg RS, Dalton IV JF, Pitkin M, and Prilutsky BI. 2018. Kinetics of individual
limbs during level and slope walking with a unilateral transtibial bone-anchored prosthesis in the
cat. *Journal of Biomechanics* 76:74-83.
Kadaba MP, Ramakrishnan HK, and Wooten ME. 1990. Measurement of lower extremity kinematics
during level walking. *Journal of Orthopaedic Research* 8:383-392.
Kimura T. 1996. Correlation between the morphology of the feet and muscle fiber composition in the
anterior tibial muscle. *Anthropological Science* 104:1-14.
Koh TJ, and Herzog W. 1998a. Excursion is important in regulating sarcomere number in the growing
rabbit tibialis anterior. *The Journal of physiology* 508:267-280.
Koh TJ, and Herzog W. 1998b. Increasing the moment arm of the tibialis anterior induces structural and
functional adaptation: implications for tendon transfer. *J Biomech* 31:593-599. 10.1016/s0021-
9290(98)00052-9
Li Y, and Hsiao-Wecksler E. 2013. Gait mode recognition and control for a portable-powered ankle-foot
orthosis. *IEEE International Conference on Rehabilitation Robotics : [proceedings]* 2013:1-8.
10.1109/ICORR.2013.6650373
Mathis A, Mamidanna P, Abe T, Cury KM, Murthy VN, Mathis MW, and Bethge M. 2018a. Markerless
tracking of user-defined features with deep learning. *arXiv preprint arXiv:180403142*.
Mathis A, Mamidanna P, Cury KM, Abe T, Murthy VN, Mathis MW, and Bethge M. 2018b. DeepLabCut:
markerless pose estimation of user-defined body parts with deep learning. *Nature neuroscience*
21:1281-1289.
Nagasawa K, Noguchi M, Ikoma K, and Kubo T. 2008. Static and dynamic biomechanical properties of the
regenerating rabbit Achilles tendon. *Clin Biomech (Bristol, Avon)* 23:832-838.
10.1016/j.clinbiomech.2008.02.002
Pataky TC. 2010. Generalized n-dimensional biomechanical field analysis using statistical parametric
mapping. *Journal of Biomechanics* 43:1976-1982.
Polly PD. 2007. Limbs in mammalian evolution. *Fins into limbs: evolution, development and
transformation*:245-268.
Ponten E, and Friden J. 2008. Immobilization of the rabbit tibialis anterior muscle in a lengthened
position causes addition of sarcomeres in series and extra-cellular matrix proliferation. *J
Biomech* 41:1801-1804. 10.1016/j.jbiomech.2008.03.006
Reddy GK, Stehno-Bittel L, and Enwemeka CS. 1998. Laser photostimulation of collagen production in
healing rabbit Achilles tendons. *Lasers Surg Med* 22:281-287. 10.1002/(sici)1096-
9101(1998)22:5<281::aid-lsm4>3.0.co;2-l
Reddy NP, and Gupta V. 2007. Toward direct biocontrol using surface EMG signals: control of finger and
wrist joint models. *Medical Engineering & Physics* 29:398-403.
10.1016/j.medengphy.2005.10.016
Sheldon JD, Adkesson MJ, Allender MC, Bailey RS, Langan JN, and Chinnadurai SK. 2019. Evaluation of a
pressure sensitive walkway for objective gait analysis in normal and arthritic domestic ducks
(Cairina moschata domestica). *PloS one* 14:e0220468.
Sjostrom M, Wahlby L, and Fugl-Meyer A. 1979. Achilles tendon injury. 3. Structure of rabbit soleus
muscles after immobilization at different positions. *Acta Chir Scand* 145:509-521.
Steiner R, Dhar M, Stephenson SM, Newby S, Bow A, Pedersen A, and Anderson DE. 2019. Biometric
Data Comparison Between Lewis and Sprague Dawley Rats. *Frontiers in Veterinary Science* 6.
10.3389/fvets.2019.00469

Tinga S, Kim SE, Banks SA, Jones SC, Park BH, Pozzi A, and Lewis DD. 2018. Femorotibial kinematics in
dogs with cranial cruciate ligament insufficiency: a three-dimensional in-vivo fluoroscopic
analysis during walking. *BMC veterinary research* 14:1-9.
Wannop J, Worobets JT, and Stefanyshyn D. 2012. Normalization of ground reaction forces, joint
moments, and free moments in human locomotion. *Journal of Applied Biomechanics* 28 6:665-
676.
Winiarski S, and Rutkowska-Kucharska A. 2009. Estimated ground reaction force in normal and
pathological gait. *Acta of Bioengineering & Biomechanics* 11.

List of Illustrations

Figure 1. Testing setup used to collect motion capture data. (1) Tekscan Very HR Walkway

4 for measuring pressure data. **(2)** Acrylic tunnel for guiding rabbits across pressure mat. **(3)** 60

Hz Camera for recording sagittal plane kinematics. **(4)** Black ink marks at approximate joint

centers based on bony landmarks.

Figure 2. Motion capture analysis from sagittal plane videos for calculating hindlimb

kinematics. A frame-by-frame top-hat morphology permitted detection of joint markers. Vectors

representing limb segments (orange lines) were drawn between the centroids of the joint

markers. Using the dot product and the segment vectors, we calculated the ankle angle (yellow)

and foot angle (i.e., the angle between the foot and ground) (blue). We considered the ground

(dashed blue) to be a horizontal line that intersected the MTP joint.

Figure 3. Example of strike box used to isolate a single foot from ground contact

pressure data using Tekscan Walkway software.

Figure 4. Joint kinematics of the rabbit hindlimb during stance phase. Mean and ±1

standard deviation represented by black line and grey shaded region, respectively. Both foot

angle (top) and ankle angle (bottom) exhibited a unimodal curve. Consistent with human gait,

we divided rabbit stance into "loading response" and "propulsion" sub-phases at the maximum

ankle dorsiflexion (i.e., smallest value) angle.

Figure 5. Knee joint center position during stance phase. Mean and ±1 standard deviation

represented by black line and grey shaded region, respectively. The knee joint gradually

progressed forward and downward due to the combination of foot and ankle joint angles.

Figure 6. Characteristics of ground contact of one hindlimb during stance phase. Mean

and ±1 standard deviation represented by black line and grey shaded region, respectively.

(Top) Vertical ground reaction force (vGRF) expressed as a percentage of body weight. vGRF

had a bimodal pattern, with peaks at approximately 25% and 75% of stance. **(Middle)** Ground

contact area, computed as the total surface area for which measured pressure was greater than

zero. Similar to vGRF, contact area had a bimodal pattern. vGRF and contact area were

strongly correlated (Pearson's r= 0.986). **(Bottom)** Average ground contact pressure. Given the

correlation between vGRF and contact area, pressure was nearly constant over the middle 80%

of stance.

Figure 7. Ground contact area (left) and pressure distribution from a representative trial

(right) during stance phase. Mean and ±1 standard deviation represented by black line and

grey shaded region, respectively. Ground contact pressure generally progressed from the

caudal to cranial direction of the foot during stance.

Figure 1

Testing setup used to collect motion capture data

(1) Tekscan Very HR Walkway 4 for measuring pressure data. **(2)** Acrylic tunnel for guiding rabbits across pressure mat. **(3)** 60 Hz Camera for recording sagittal plane kinematics. **(4)** Black ink marks at approximate joint centers based on bony landmarks.

Figure 2

Motion capture analysis from sagittal plane videos for calculating hindlimb kinematics.

A frame-by-frame top-hat morphology permitted detection of joint markers. Vectors representing limb segments (orange lines) were drawn between the centroids of the joint markers. Using the dot product and the segment vectors, we calculated the ankle angle (yellow) and foot angle (i.e., the angle between the foot and ground) (blue). We considered the ground (dashed blue) to be a horizontal line that intersected the MTP joint.

Figure 3

Example of strike box used to isolate a single foot from ground contact pressure data using Tekscan Walkway software.

Figure 4

Joint kinematics of the rabbit hindlimb during stance phase.

Mean and ±1 standard deviation represented by black line and grey shaded region, respectively. Both foot angle (top) and ankle angle (bottom) exhibited a unimodal curve. Consistent with human gait, we divided rabbit stance into "loading response" and "propulsion" sub-phases at the maximum ankle dorsiflexion (i.e., smallest value) angle.

Figure 5

Knee joint center position during stance phase.

Mean and ±1 standard deviation represented by black line and grey shaded region, respectively. The knee joint gradually progressed forward and downward due to the combination of foot and ankle joint angles.

Figure 6

Characteristics of ground contact of one hindlimb during stance phase.

Mean and ±1 standard deviation represented by black line and grey shaded region, respectively. **(Top)** Vertical ground reaction force (vGRF) expressed as a percentage of body weight. vGRF had a bimodal pattern, with peaks at approximately 25% and 75% of stance. **(Middle)** Ground contact area, computed as the total surface area for which measured pressure was greater than zero. Similar to vGRF, contact area had a bimodal pattern. vGRF and contact area were strongly correlated (Pearson's r= 0.986). **(Bottom)** Average ground contact pressure. Given the correlation between vGRF and contact area, pressure was nearly constant over the middle 80% of stance.

Figure 7

Ground contact area (left) and pressure distribution from a representative trial (right) during stance phase.

Mean and ±1 standard deviation represented by black line and grey shaded region, respectively. Ground contact pressure generally progressed from the caudal to cranial direction of the foot during stance.