Brain strain rate response: addressing computational ambiguity and experimental data for model validation

Zhou Zhou,[1*] Xiaogai Li, [1] Yuzhe Liu,[2,3] Warren N. Hardy,[4] Svein Kleiven[1]

[1] Neuronic Engineering, KTH Royal Institute of Technology, Stockholm, 14152, Sweden.

[2] Department of Bioengineering, Stanford University, Stanford, CA, 94305, USA.

[3] School of Biological Science and Medical Engineering, Beihang University, Beijing 100083, China.

[4] Virginia Tech-Wake Forest Center for Injury Biomechanics, Blacksburg, VA, 24061, USA.

Corresponding email: zhouz@kth.se

Abstract

Traumatic brain injury (TBI) is an alarming global public health issue with high morbidity and mortality rates. Although the causal link between external insults and consequent brain injury remains largely elusive, both strain and strain rate are generally recognized as crucial factors for TBI onsets. With respect to the flourishment of strain-based investigation, ambiguity and inconsistency are noted in the scheme for strain rate calculation within the TBI research community. Furthermore, there is no experimental data that can be used to validate the strain rate responses of finite element (FE) models of the human brain. Thus, the current work presented a theoretical clarification of two commonly used strain rate computational schemes: the strain rate was either calculated as the time derivative of strain or derived from the rate of deformation tensor. To further substantiate the theoretical disparity, these two schemes were respectively implemented to estimate the strain rate responses from a previous-published cadaveric experiment and an FE head model secondary to a concussive impact. The results clearly showed scheme-dependent responses, both in the experimentally determined principal strain rate and FE model-derived principal and tract-oriented strain rates. The results highlight that cross-scheme comparison of strain rate responses is inappropriate, and the utilized strain rate computational scheme needs to be reported in future studies. The newly calculated experimental strain rate curves in the supplementary material can be used for strain rate validation of FE head models.

Keywords

1 Introduction

Traumatic brain injury (TBI), defined as an alteration in brain function or other evidence of brain pathology caused by an external force [1], is a major global public health threat. In the United States, around 61000 people died from TBI-induced injuries in 2019 [2], and in the European Union, there were approximately 82000 TBI-associated deaths in 2012 [3]. Despite collective efforts from the scientific community, clinical services, and policymakers to prevent the occurrence and mitigate the detriment of TBI, no clear improvement has been noted over the past two decades [4]. Efforts to better decipher brain injury pathogenesis and develop more effective head protective strategies are vital to resolve this concerning epidemic.

Although the mechanobiological pathway from external insult, localized tissue responses, and resultant brain injury remains to be better explored, it has been generally understood that both strain and strain rate are crucial factors for TBI onsets [5]. For example, through relating controlled mechanical inputs to neuromorphological changes in a three-dimensional (3D) *in vitro* compression model, Bar-Kochba et al. [6] found that the localization of neurite blebbing correlated with shear strain along the axial direction of neurons, while neurite swelling was highly loading-rate dependent. Montanino et al. [7] utilized a composite finite element (FE) model of a single axon to predict the responses of axonal subcomponents secondary to tensile elongation, revealing a dependency of axolemma deformation on both the magnitude and the rate of imposed loadings. Hajiaghamemar and Margulies [8] found FE model-derived strain and strain rate along the fiber tracts spatially aligned with the pattern of histology-identified axonal injury in the pig brains after rapid head rotations. These experimental and computational findings collectively underscored the importance of monitoring both the strain and strain rate during head impacts.

Various strain-based metrics have been proposed for TBI analyses , such as maximum principal strain (MPS) [9-16], cumulative strain damage measure (CSDM) quantifying the volume fraction of brain experiencing strain levels over a pre-defined threshold [17, 18],

maximum tract-oriented strain (MTOS) measuring the stretch along axonal fiber tract [19-21].

Strain-based measurements have been experimentally quantified by Hardy et al. [22] (recently

reanalysed by Zhou et al. [23]) based on MPS (0.07-0.22) in cadaveric experiments with

loading conditions close to traumatic levels, and by Knutsen et al. [24] based on MPS (0.02-

0.05) and MTOS (0.005-0.03) in voluntary loading scenarios. These strain-based metrics were

also used to establish kinematic-based brain injury risk functions with the aid of FE head

models. For example, the Brain Injury Criteria (BrIC) [25] was proposed based on the

dependency of MPS and CSDM on the angular velocity observed from two FE models of

human brain [17, 26]. Discussions are ongoing to potentially adopt this newly proposed BrIC

into the New Car Assessment Program in the vehicle safety standards [27].

Compared with the large body of strain-based studies, there are relatively fewer

investigations on brain strain rate. It is ubiquitous in the literature that the strain rate values are

directly reported without any clarification on how they are calculated [9, 28-33]. Even when

limiting to the handful of studies with the strain rate computational schemes elaborated,

alarming inconsistency existed. As typical practices, the strain rate is either cacluated from the

rate of deformation tensor [34, 35] or computed as the time derivative of strain [36, 37].

However, little knowledge exists on how the computational schemes affect the resultant strain

rate values.

Today, there is no existing experimental brain strain rate dataset with loading

conditions close to traumatic levels and hence the accuracy of the FE model-derived strain

rate response remains unknow. Commonly, the FE model of human brain is validated against

the brain-skull relative motion and/or brain strain and then directly used for strain rate prediction.

As highlighted by Zhou et al. [38] and Zhao and Ji [39], if the model is evaluated against an

experimental parameter that is not the parameter of interest itself, it is suspected that numerical

error might be introduced and propagated through the chain of calculation from the evaluated

parameter to the parameter of interest (e.g., the relationship between brain motion/strain and

brain strain rate). For an FE model with intended usage of strain rate prediction, a direct

evaluation of brain strain rate response is thus preferred.

The current study endeavoured to address the ambiguity relevant to the calculation of

brain strain rate and provide experimental data for strain rate evaluation of FE models of the

human brain. Thus, a theoretical clarification of two commonly used strain rate computational

schemes was presented, in which the strain rates were computed as the time derivatives of

strains of interest (referred to as scheme 1), and components of interest of the rate of

deformation tensor (referred to as scheme 2), respectively. These two schemes were then

implemented to calculate the experimental principal strain rate and computational principal and

tract-oriented strain rates, through which the distinction between these two schemes was

substantiated. The newly calculated experimental strain rate curves can be served as a

reference to evaluate the strain rate responses of FE models.

2 Methods

2.1 Theoretical clarification

This section presents a continuum mechanical description of the two strain rate

computational schemes (i.e., scheme 1 and scheme 2), in which the calculation of two specific

strain rates are elaborated (i.e., the first principal strain rate and the tract-oriented strain rate).

Two strain rates in combination with two computation schemes thus yields 4 types of strain

rates, all of which are used as response variables in TBI studies. The mathematical symbols

used throughout the text are clarified below: $\dot{\text{MPSR}}$ and $\hat{\text{MPSR}}$ represent the maximum first

principal strain rates computed by scheme 1 and scheme 2, respectively; $\dot{\text{MTOSR}}$ and

$\hat{\text{MTOSR}}$ namely denote the maximum tract-oriented strain rates following scheme 1 and

scheme 2.

As is the common context of these two schemes, the motion $\varphi(\mathbf{X},t)$ maps the position

vector of every point in the brain in the undeformed configuration ($\mathbf{X}$) (i.e., $\mathbf{X}=\{X_1 \quad X_2 \quad X_3\}$)

to its deformed configuration ($\mathbf{x}$) at time t (i.e., $\mathbf{x}(t)=\{x_1(t) \quad x_2(t) \quad x_3(t)\}$). The temporal

derivative of $\varphi(\mathbf{X},t)$ at fixed position $\mathbf{X}$ represents the velocity, writing as

$\mathbf{v}(\mathbf{X},t)=\{v_1(t) \quad v_2(t) \quad v_3(t)\}$.

2.1.1 Scheme 1: Time derivative of strain

103   Scheme 1 calculates the strain rates as the time derivatives of the first eigenvalue or

104   the component of interest of the strain tensor $\mathbf{E}(t)$. Given that $\varphi(\mathbf{X},t)$ consists of both

105   deformation and rigid-body motion, the deformation gradient $\mathbf{F}(t)$ is introduced, isolating the

106   deformation through mapping line elements ($d\mathbf{X}$) in the reference configuration into its

107   counterpart ($d\mathbf{x}$) in the current configuration.

108
$$\mathbf{F}(t)=\frac{\partial \varphi(\mathbf{X},t)}{\partial \mathbf{X}}=\begin{bmatrix} \dfrac{\partial x_1(t)}{\partial X_1} & \dfrac{\partial x_1(t)}{\partial X_2} & \dfrac{\partial x_1(t)}{\partial X_3} \\ \dfrac{\partial x_2(t)}{\partial X_1} & \dfrac{\partial x_2(t)}{\partial X_2} & \dfrac{\partial x_2(t)}{\partial X_3} \\ \dfrac{\partial x_3(t)}{\partial X_1} & \dfrac{\partial x_3(t)}{\partial X_2} & \dfrac{\partial x_3(t)}{\partial X_3} \end{bmatrix} \tag{1}$$

109   The Green-Lagrange strain tensor is then calculated as

110
$$\mathbf{E}(t)=\frac{1}{2}(\mathbf{F}^{\mathrm{T}}(t)\mathbf{F}(t)-\mathbf{I}) \tag{2}$$

111   where the superscript T represents the transpose operation and $\mathbf{I}$ is the identify tensor.

112   The first principal strain ($\mathrm{PS}(t)$) is computed as the maximum eigenvalue of $\mathbf{E}(t)$ and

113   the tract-oriented strain ($\mathrm{TOS}(t)$) is obtained by projecting $\mathbf{E}(t)$ along the real-time fiber

114   orientation ($\mathbf{a}(t)$) (equation 3) [40]:

115
$$\mathrm{TOS}(t)=\mathbf{a}^{\mathrm{T}}(t)\cdot\mathbf{E}(t)\cdot\mathbf{a}(t) \tag{3}$$

116   Resultantly, the first principal strain rate ($\dot{\text{PSR}}(t)$) and tract-oriented strain rate ($\dot{\text{TOSR}}(t)$)

117   were computed as the derivative of $\text{PS}(t)$ and $\text{TOS}(t)$ with respect to time (equations 4 and

118   5), respectively. Of note, a five-point stencil neural network derivative function was used for all

119   the derivative operations, same as the approach used in previous studies [41-43].

120
$$\dot{\text{PSR}}(t) = \frac{\partial \text{PS}(t)}{\partial t} \tag{4}$$

121
$$\dot{\text{TOSR}}(t) = \frac{\partial \text{TOS}(t)}{\partial t} \tag{5}$$

The maximum value of $\dot{\text{PSR}}(t)$ and $\dot{\text{TOSR}}(t)$ across the simulated time domain was identified

(i.e., $\dot{\text{MPSR}}$ and $\dot{\text{MTOSR}}$, respectively). Scheme 1 has been used to calculate the maximum

principal strain rate in the brain [8, 19, 36, 41-49] and maximum tract-oriented strain rate in the

white matter (WM) [8, 19, 41, 42, 44-46, 48].

2.1.2 Scheme 2: Rate of deformation tensor

Scheme 2 calculates strain rate as the first eigenvalue or the component of interest of

the rate of deformation tensor $\mathbf{d}(t)$. Of note, the rate of deformation tensor is synonymous with

rate of strain tensor [50]. In contrast with the deformation gradient $\mathbf{F}(t)$ based on displacement

field, velocity gradient $\mathbf{l}(t)$ is derived from velocity field $\mathbf{v}(\mathbf{X}, t)$ by taking its spatial gradient

according to equation 6:

132
$$\mathbf{l}(t) = \frac{\partial \mathbf{v}(\mathbf{X}, t)}{\partial \mathbf{x}} = \begin{bmatrix} \dfrac{\partial v_1(t)}{\partial x_1} & \dfrac{\partial v_1(t)}{\partial x_2} & \dfrac{\partial v_1(t)}{\partial x_3} \\ \dfrac{\partial v_2(t)}{\partial x_1} & \dfrac{\partial v_2(t)}{\partial x_2} & \dfrac{\partial v_2(t)}{\partial x_3} \\ \dfrac{\partial v_3(t)}{\partial x_1} & \dfrac{\partial v_3(t)}{\partial x_2} & \dfrac{\partial v_3(t)}{\partial x_3} \end{bmatrix} \tag{6}$$

133   The symmetrical part of $\mathbf{l}(t)$ is defined as the rate of deformation tensor $\mathbf{d}(t)$:

$$\mathbf{d}(t) = \frac{1}{2}(\mathbf{l}(t) + \mathbf{l}^{\mathrm{T}}(t)) \qquad (7)$$

The first principal strain rate ($\hat{\mathrm{PSR}}(t)$) and tract-oriented strain rate ($\hat{\mathrm{TOSR}}(t)$) were respectively computed as the maximum eigenvalue of $\mathbf{d}(t)$ and the projection of $\mathbf{d}(t)$ along the real-time fiber orientation ($\mathbf{a}(t)$) (equation 8).

$$\hat{\mathrm{TOSR}}(t) = \mathbf{a}^{\mathrm{T}}(t) \cdot \mathbf{d}(t) \cdot \mathbf{a}(t) \qquad (8)$$

The time-accumulated peaks of $\hat{\mathrm{PSR}}(t)$ and $\hat{\mathrm{TOSR}}(t)$ were determined and labelled as $\hat{\mathrm{MPSR}}$ and $\hat{\mathrm{MTOSR}}$, respectively. Scheme 2 has been previously used to extract the strain rate in the brain [35, 51] and other biological tissues (e.g., leg muscles [52-55], myocardium [56-58]).

While collectively considering these two schemes, it is worth mentioning that the material time derivative of the Green-Lagrange strain tensor (i.e., $\mathbf{E}$ in scheme 1) is the pull-back of the rate of deformation tensor (i.e., $\mathbf{d}$ in scheme 2) (equation 9) [50, 59]. $\dot{\mathbf{E}}$ in equation 9 is termed as material strain rate tensor in the literature [50] and, to the best of the authors' knowledge, has also been used to inform the computation of brain strain rate in two studies from one research group [60, 61]. Given its relatively limited usage within the TBI community, this scheme is thus not incorporated in the current study.

$$\dot{\mathbf{E}} = \mathbf{F}^{\mathrm{T}} \cdot \mathbf{d} \cdot \mathbf{F} \qquad (9)$$

2.2 Experimental strain rate

To substantiate the disparity between scheme 1 and scheme 2 and provide experimental data for strain rate evaluation of FE brain model, we computed the principal strain rates in cadaveric brains using both schemes. In Hardy et al. [22], thirty-five impacts were conducted on eight inverted and perfused head-neck complexes of post-mortem human

subjects, in which the motion of the radiopaque neutral density targets (NDTs) implanted within the cadaveric brain was measured using a high-speed, bi-planar X-ray system with a temporal resolution of 1 ms. To expedite the estimation of local responses, Hardy et al. [22] deployed 7 NDTs in a cluster configuration with the center target being 10 mm from the remaing six counterparts, roughly occupying 1.5 ml of tissue. As represented by C1 and C2 in Figure 1A, two NDT clusters were implanted within each cadaveric brain.

Following the selection criteria proposed by Zhou et al. [38], 15 NDT clusters from 14 impacts with both impact kinematics and motions of all 7 associated NDTs recorded over 40 ms were chosen to calculate the principal strain rates. As illustrated by a representative cluster in Figure 1B, FE nodes were generated based on the NDT starting positions. Based on the NDT deploying characteristics in Hardy et al. [22], 8 tetrahedron elements were developed for each cluster by connecting each NDT to its neighbouring counterparts [23]. The tracked motions were used to excite the tetrahedron model, which was solved by the LS-DYNA software (Livermore Software Technology Corporation, LSTC). From the completed simulation, the first principal strain rates were respectively extracted as the time derivatives of the first principal strain (i.e., $\dot{\mathrm{PSR}}(t)$ for the scheme 1) and maximum eigenvalue of the rate of deformation tensor (i.e., $\hat{\mathrm{PSR}}(t)$ for scheme 2). The strain rates of all available tetrahedron elements were averaged to provide a general estimation of the strain rate within the volume occupied by the NDT cluster. The maximum values of $\dot{\mathrm{PSR}}(t)$ and $\hat{\mathrm{PSR}}(t)$ were identified (i.e., $\dot{\mathrm{MPSR}}$ and $\hat{\mathrm{MPSR}}$). Due to the unavailability of fiber orientation information of these cadavers, it is infeasible to compute tract-oriented strain rate from this experimental data.

Figure 1. (A) Representative sketch of NDT cluster implanting schemes. For a given head, two NDT clusters were implanted as cluster 1 (C1) and cluster 2 (C2). (B) Strain-rate estimation with the NDTs as black spheres while tetrahedron elements in grey and mesh line in black. To visualize the center NDT, all tetrahedron elements are shown in translucency.

2.3 Computational strain rate

2.3.1 The ADAPT model

We next implemented scheme 1 and scheme 2 to calculate the principal strain rate and tract-oriented strain rate from an anatomically detailed head model (i.e., the ADAPT model in Figure 2). The ADAPT model was developed previously at KTH Royal Institute of Technology in Stockholm using the LS-DYNA software [62]. The model includes the brain, skull, meninges (i.e., dura mater, pia mater, falx, and tentorium), subarachnoid cerebrospinal fluid (CSF), ventricle, and sinuses (i.e., superior sagittal sinus and transverse sinus). As is the structure of interest in the current study, the brain was further grouped with explicit representations of various components, including four lobes of the cerebral gray matter (GM) (Figure 2A), cerebellar GM, cerebral WM, cerebellar WM, and brainstem (Figure 2B). The element numbers of brain and WM are 1513198 and 213321, respectively. A second-order Ogden hyperelastic constitutive model combined with six-order Prony series was employed to describe the nonlinearity and viscoelasticity of brain material [63]. The biofidelity of the model has been evaluated against experimental data of intracranial pressure [64], brain-skull relative displacement [22], and brain strain [23]. The strain rate responses of the model were additionally evaluated by the newly calculated experimental strain rate data in Appendix.

To extract tract-related responses, it is imperative to monitor the real-time direction of fiber tracts during the impact [40]. Thus, the primary orientation of the WM fiber tracts was extracted from the ICBM DTI-81 atlas [65] and then embedded within the WM elements in the form of truss elements [40]. Through this, potential variation in fiber orientation during the impacts was reflected by the temporal direction of the truss element, which was updated at each solution cycle of the time-marching simulation. These temporally dynamic fiber orientation informed the computation of tract-oriented strain rate.

206
Figure 2. Finite element model of the human head with embedded truss elements representing te white
mater fiber tracts. (A) Finite element model of the human head with the skull open to expose the
subarachnoid cerebrospinal fluid (CSF) and brain. A skull-fixed coordinate system and corresponding
axes are illustrated with the origin at the head's centre of gravity. (B) Brain components of cerebral white
matter (WM), cerebellar WM, brainstem, pia mater, falx, tentorium, superior sagittal sinus, and
transverse sinus. (C) Brain with fiber tracts.

2.3.2 Impact simulation

The ADAPT model was employed to simulate a concussive impact, through which both

the maximum principal strain rates and maximum tract-oriented strain rates were computed

using scheme 1 and scheme 2. The impact loading was measured by instrumented

mouthguard from a collegiate American football player with self-reported post-concussive

symptoms [66]. Both translational and rotational acceleration profiles (Figure 3) were applied

to a node located at the head's centre of gravity and constrained to the rigidly modelled skull.

The model responses were output at every 0.1 msec, the same as the output interval in [41].

Figure 3. Head model loading conditions for one concussive impact with the kinematics measured from
instrumented mouthguard. Note the X, Y, and Z axes are the same as those in the skull-fixed coordinate
system in Figure 2A.

Once the simulation was complete, the strain tensor and rate of deformation tensor of

all brain elements and the temporal orientation of the truss elements embedded within the WM

elements were obtained. For each brain element, the first principal strain rates were calculated

as the time derivatives of the first principal strain (i.e., scheme 1) and the first eigenvalue of

the rate of deformation tensor (i.e., scheme 2) with their maximum values across the whole

impact reported (i.e., $\dot{\overline{MPSR}}$ and $\hat{\overline{MPSR}}$). The tract-oriented strain rates were additionally

computed for all WM elements. In scheme 1, the strain tensor of each WM element was

iteratively resolved along the temporal direction of its embedded truss element (i.e., equation

3) with the outcome being discretely differentiated between time points to obtain the tract-

oriented strain rate (i.e., equation 5). In scheme 2, the rate of deformation tensor of each WM

element was projected along the real-time direction of its embedded truss element (i.e.,

equation 8). For both schemes, the maximum values of the tract-oriented strain rates across

the whole impact were reported, i.e., $\dot{\overline{MTOSR}}$ and $\hat{\overline{MTOSR}}$.

2.3.3 Data analysis of computational strain rate responses

To quantify the cross-scheme disparity, relative differences in strain rate peaks

computed by scheme 1 and scheme 2 were computed for all brain elements based on the

principal measures and for all WM elements based on the tract-oriented measures,

respectively. To test whether cross-scheme strain rate results were readily translatable, linear

regression analyses were conducted between $\dot{\overline{MPSR}}$ and $\hat{\overline{MPSR}}$, and between $\dot{\overline{MTOSR}}$

and $\hat{\overline{MTOSR}}$, respectively. In addition to the correlation coefficient (r), the root-mean-square

error normalized by the mean value of strain rate peaks calculated by scheme 1 (i.e., NRMSE)

was reported. The threshold for significance was $p<0.05$.

3 Results

3.1 Experimental principal strain rates

Experimental principal strain rates computed by both schemes for all 15 clusters are

depicted in Figure 4. Using scheme 1, the time history curves of the principal strain rate were

generally biphasic with both positive and negative phases. When switching to scheme 2, the

strain rate curves were monophasic with purely positive values. The strain rate responses of

all 15 clusters attained the peak values within the pulse durations except for C241-T5 C2 and

C393-T1 C1 solved by scheme 2. The strain rate peaks along with experimental kinematic

peaks are summarized in Table 1. The maximum values ranged from 9.3 s^{-1} (C241-T6 C2) to

25.8 s^{-1} (C380-T4 C1) in scheme 1 and spanned from 15.6 s^{-1} (C380-T2 C1) to 35.6 s^{-1} (C064-

T1 C1) in scheme 2. Note that the experimental principal strain rate-time history curves in

Figure 4 are available in the supplentary materials.

259
Figure 4. Comparison of experimental principal strain rates computed as time derivate of first principal

strain ($\overset{\bullet}{\mathrm{PSR}}(t)$ in scheme 1) and first eigenvalue of the rate of deformation tensor ($\overset{\wedge}{\mathrm{PSR}}(t)$ in scheme

2).

Table 1. Summary of test configurations of 14 impacts and strain rate responses of 15 NDT clusters.
Note that the loading peaks are calculated based on the resultant kinematics and the superscript *****
indicates the strain rate does not reach the peak value within the available time duration.

Specimen and test	Impact configuration		Loading peaks			Cluster	Maximum principal strain rate (s⁻¹)	
	Plane	Location	Linear acceleration (g)	Angular acceleration (krad/s²)	Angular velocity (rad/s)		Scheme 1	Scheme 2

C288	T3	Sagittal	Occipital	236	26.6	30.3	C1	18.5	31.4
							C2	21.0	20.0
C241	T5	Sagittal	Occipital	194	10.5	16.0	C2	15.8	17.9[*]
	T6	Sagittal	Occipital	127	6.6	18.5	C2	9.4	16.6
C064	T1	Sagittal	Occipital	101	5.0	10.0	C1	18.1	35.6
C380	T1	Coronal	Temporal	87	7.2	30.0	C1	13.3	19.6
	T2	Horizontal	Parietal	66	5.7	24.1	C1	17.7	15.6
	T3	Coronal	Temporal	78	6.6	22.4	C1	16.2	20.2
	T4	Coronal	Temporal	196	19.2	37.7	C1	25.0	21.0
	T5	Horizontal	Parietal	77	7.0	25.3	C1	15.3	15.8
	T6	Coronal	Temporal	147	13.7	31.8	C1	23.5	25.4
C393	T1	Coronal	Temporal	91	6.7	20.5	C1	12.5	25.4[*]
	T2	Coronal	Temporal	43	4.0	24.5	C1	23.7	25.8
	T3	Coronal	Temporal	159	12.2	26.8	C1	24.5	21.7
	T4	Coronal	Temporal	180	12.5	28.5	C1	25.1	24.4

3.2 Computational principal and tract-oriented strain rates

Figure 5A-F visually compares the maximum principal and tract-oriented strain rates at a representative horizontal cut-section. For the maximum principal strain rate (Figure 5A-C), although both schemes predicted high strain rate peaks (i.e., peaks over or approaching 40 s^{-1}) at the cortical region, substantial differences (i.e., differences over 10 s^{-1} or less than -10 s^{-1}) between $\dot{\mathrm{MPSR}}$ and $\hat{\mathrm{MPSR}}$ were noted in the left frontal lobe, right occipital lobe, and paraventricular region. For example, $\dot{\mathrm{MPSR}}$ was larger than $\hat{\mathrm{MPSR}}$ in the left temporal lobe (solid arrow in Figure 5C), while a reverse trend was noted in the left frontal cortex (dash arrow in Figure 5C). When switching to maximum tract-oriented strain rate (Figure 5D-F), $\dot{\mathrm{MTOSR}}$ and $\hat{\mathrm{MTOSR}}$ differed in magnitude and spatial distribution. In particular, scheme 1 revealed substantially larger tract-oriented strain rate peaks than scheme 2 across the whole WM in the frontal region (solid arrows in Figure 5F), while $\dot{\mathrm{MTOSR}}$ was relatively smaller than $\hat{\mathrm{MTOSR}}$ in the external capsules (dash arrows in Figure 5F).

These visible differences were further quantified by linear regression analysis between two schemes (Figure 5G-H). Although a significant correlation ($p<0.001$) was attained for both

types of strain rates, the correlation coefficients (r) were 0.82 for maximum principal strain rate

and 0.77 for maximum tract-oriented strain rate. Across the whole brain elements

(N=1513198), a NRMSE value of 16.69% was computed between $\dot{\mathrm{MPSR}}$ and $\hat{\dot{\mathrm{MPSR}}}$, while

across the whole WM elements (N=213321), a NRMSE value of 27.35% was calculated

between $\dot{\mathrm{MTOSR}}$ and $\hat{\dot{\mathrm{MTOSR}}}$.

Figure 5. Comparison of time-accumulated maximum principal strain rate and tract-oriented strain rate

by both schemes. Upper row: Horizontal cross-sections of $\dot{\mathrm{MPSR}}$ (A), $\hat{\dot{\mathrm{MPSR}}}$ (B), and their relative

difference (C). Middle row: Horizontal cross-sections of $\dot{\mathrm{MTOSR}}$ (D), $\hat{\dot{\mathrm{MTOSR}}}$ (E), and their relative

difference (F). Lower row: Linear regression plots for element-wise maximum principal strain rate in the whole brain (G) and element-wise maximum tract-oriented strain in WM region (H), respectively.

4 Discussion

The current study addressed the ambiguity of brain strain rate computation by presenting a theoretical clarification of two alternative schemes, in which the strain rate was either computed as the time derivative of strain or derived from the rate of deformation tensor. This theoretical disparity was further substantiated by discordant cross-scheme responses in experimental principal strain rate, and computational principal and tract-oriented strain rates. It was thus verified that strain rates were dependent on the specific computational schemes, underscoring that cross-scheme comparison of strain rate results was inappropriate. The newly calculated experimental strain rate curves in the supplementary material, especially those with the peak values attained within the pulse durations, can be used to evaluate the strain rate response of FE models of human head, as exemplified for the ADAPT model in Appendix.

Many experimental models of TBI have reported a strain rate dependency of morphological or functional alterations of experimental tissues secondary to mechanical insults with precisely controlled loading parameters [67-69], while several computational studies have also reported strain rate as an appropriate predictor for brain injury [8, 19, 31, 36, 41]. However, most TBI studies didn't report details of strain rate calculation, making an appropriate interpretation of strain rate results impossible. For the handful of investigations with the strain rate calculation procedures elaborated, disparate inconsistency was noted in the computational scheme, posing inevitable challenges while comparing strain rate-related findings across studies. Our work demonstrated cross-scheme disparities in the resultant strain rate responses from the theoretical perspective as well as experimental and computational substantiation. These disparities highlighted that cross-scheme comparison of strain rate results is invalid. For example, the strain rate thresholds established by Patton et al. [70] using scheme 2 were not comparable with the strain rate results derived by scheme 1 in the study by Hernandez and Camarillo [45], even though both studies used the exact same FE model

[63]. We recommended that, if applicable, clarifying the strain rate computational details be

regarded as standard content in future studies.

As both schemes are in use for strain rate computation and no consensus has been

reached within the research community, we thus computed the experimental strain rates from

the cadaveric tests reported earlier [22] using both schemes. The newly calculated strain rate

responses are compared with values reported in other studies (Table 1). When computing the

strain rate as the time derivate of strain (i.e., scheme 1), Sullivan et al. [19] estimated the strain

rate in six horizontally dissected piglet brains during rapid rotational events, in which the

imposed angular velocities were one order of magnitude larger than those in Hardy et al. [22].

Consequently, the reported strain rates in Sullivan et al. [19] largely surpassed the current

experimental results. When switching to scheme 2, Reese et al. [51] reconstructed the velocity

gradient from phase-contrast magnetic resonance imaging due to the vascular pulsatile and

then computed 3D strain-rate tensor of brain parenchyma. This pulsatile-induced strain rate

was two orders of magnitude smaller than the current experimental strain rates calculated by

scheme 2.

Table 2. Comparison of brain strain rates from existing studies. Note that the strain rate in Feng et al.
[71] was estimated from Figure 10 in the original article using scheme 1, while the computational scheme
for strain rate in Reese et al. [51] was clarified in the caption of Figure 2 in the original article,
corresponding to scheme 2 in the current study.

Scheme	Approach	Study	Loading conditions	Strain rate (s^{-1})
Scheme 1: Time derivative of strain	Volunteer test	Feng et al. [71]	Linear acceleration: 1.5 g Angular acceleration: 120-140 rad/s^2	Peak principal strain rate: ~1.2-2.7
	Animal test	Sullivan et al. [19]	Angular velocity: 121 ± 3.22 rad/s	Mean principal strain rate: 150-189
	PMHS test	Current study	Linear acceleration: 43-236 g Angular acceleration: 4.0-26.6 krad/s^2 Angular velocity: 10-37.7 rad/s	Peak principal strain rate: 9.3-25.8
	Concussive simulation	Current study	Linear acceleration: 84 g Angular acceleration: 6.2 krad/s^2 Angular velocity: 18.8 rad/s	Element-wise maximum principal strain rate: 9.7-143.6 Element-wise maximum tract-oriented strain rate: 5.3-114.2
Scheme 2: Rate of deformation tensor	Volunteer test	Reese et al. [51]	Vascular pulsatility	Principal strain rate: 0.1
	PMHS test	Current study	Linear acceleration: 43-236 g Angular acceleration: 4.0-26.6 krad/s^2 Angular velocity: 10-37.7 rad/s	Peak principal strain rate: 15.6-35.6

		Linear acceleration: 84 g	Element-wise maximum principal strain rate: 14.6-119.2
Concussive simulation	Current study	Angular acceleration: 6.2 krad/s^2	
		Angular velocity: 18.8 rad/s	Element-wise maximum tract-oriented strain rate: 3.2-63.2

The reliability of FE model-predicted responses can be partially guaranteed only if the

computational variables are validated against relevant experimental data. It has been long

recognized that an FE head model validated against experimental pressure does not

necessarily guarantee an acceptable predictability of the brain displacement or deformation

[72-74]. More recently, several independent research groups advocated that a model to be

used for strain prediction should be evaluated against the experimental brain strain, and not

just the brain-skull relative motion [23, 38, 39]. When it comes to strain rate, there is only one

FE model of piglet brain [19], to the best of the authors' knowledge, having the strain rate peaks

(instead of the whole strain rate curves) evaluated. As is the typical practice, FE head models

validated against brain-skull relative motion and/or brain deformation are directly used for

strain rate prediction. Although the strain rate can be derived from strain or displacement field

via a chain of calculation (as detailed in section 2.1), a direct evaluation of FE-derived strain

rate responses is preferred if the model is intended to be used for strain rate prediction. This

is partially supported by the incongruent strain and strain rate validation performances of the

FE model of piglet brain [19], in which the computational strain rate peaks exhibited superior

correlation with their experimentally determined counterparts than that between the

experimental and computational strain peaks. Note that, in the study by Sullivan et al. [19], the

strain rate was computed as the time derivative of strain (i.e., scheme 1 in the current study).

Several recent studies based on FE models of piglet brain [8, 19, 41] have reported

that the maximum tract-oriented strain rate exhibited superior injury predictability over

maximum principal strain rate, while the majority of the existing FE investigations on human

brain remain to solely scrutinize the maximum principal strain rate. We thus examined the

relationship between the prevalently used principal strain rate and the recently advocated tract-

oriented strain rate across all WM elements in the ADAPT model. As quantitatively illustrated

in Figure 6, no consistent scaling from maximum principal strain rate to its tract-aligned

counterpart was noted regardless of the computational scheme. This supports the potential

incorporation of tract-oriented strain rate as an independent injury metric in future studies of

human brain injury.

365
Figure 6. Element-wise comparisons of maximum principal strain rates and tract-related strain rates
computed by scheme 1 (A) and scheme 2 (B) based on results of WM elements.

In addition to the strain rate, inconsistency is also noted in strain type in the literature.

Even when limiting to TBI-related studies, the adopted strain type includes Green-Lagrange

strain [40, 75-78], logarithmic strain (alternatively termed as true strain and natural strain) [79-

81], engineering strain [82, 83], incremental strain [22], etc. For a detailed comparison of

different strain types, readers are suggested to refer on one study by Karimi and Navidbakhsh

[84] or continuum mechanics-related textbooks (e.g., chapter 3 in [85]). It is recommended that

the strain type should also be clarified in future studies.

4.1 Limitation and future work

Several limitations in this study should be noted, which require further investigation.

First, although our results clearly demonstrated cross-scheme disparities, we have no

recommendation on which scheme is superior. This can be alternatively done by evaluating

the injury predictability of these strain rate-based metrics computed by these two schemes.

For the time being, choices may be prioritized differently depending on the intended purpose,

but we strongly recommended that the exact strain rate computational schemes be clearly

stated. Secondly, the cadaveric experiments analysed in this study were not without errors, as

was acknowledged in the original studies [22, 86] and exhaustively evaluated in one recent

study [38]. Moreover, the principal strain rate responses estimated from the experimental data

and the ADAPT model exhibited certain deviations (Appendix), although this is the first FE human brain model performing strain rate evaluation. Even so, we'd like to highlight that the main advocation of the current work, i.e., cross-scheme comparison of the strain rate results was not valid, is theoretically supported by the content presented in the "Theoretical clarification" section in the current study. Such a advocation should not be disapproved by these experimental and computational substantiations with certain deficits. Nevertheless, we acknowledge that further demonstration of cross-scheme disparity is deemed necessary by employing other experimental data and better validated FE models.

5 Conclusion

Given the ambiguity and inconsistency of strain rate computational schemes in existing brain injury studies, the current work presented a theoretical clarification of two rival schemes: strain rates computed as the time derivative of strain and derived from the rate of deformation tensor. Both schemes were employed to calculate experimental principal strain rate and computational principal and tract-oriented strain rates, exhibiting highly scheme-dependent responses. Our work underscores that cross-scheme comparison of strain rate should be avoided and the exact strain rate computational scheme needs to be clarified in future studies. The newly calculated experimental strain rate data in the supplementary material can be used to validate the strain rate response of FE models of human head.

Acknowledgment

This research has received funding from KTH Royal Institute of Technology (Stockholm, Sweden) and the Swedish Research Council (VR-2020-04496 and VR-2020-04724). The content of this article is solely the responsibility of the authors and does not necessarily represent the official views of funding agencies. The simulations were enabled by resources in projects [NAISS 2023/5-17, SNIC 2022/5-645, SNIC 2022/5-475, SNIC 2021/5-406 and SNIC 2021/5-459] provided by the Swedish National Infrastructure for Computing (SNIC) at the center for High Performance Computing (PDC), partially funded by the Swedish Research

Council through grant agreement no. VR-2020-04496 and VR-2020-04724. The authors thank for the two anonymous reviewers and Professor Antoine Jerusalem for the stimulating comments and valuable suggestions that substantially improved this paper. We also acknowledge Dr. Michel Destrade and Dr. Valentina Balbi from University of Galway, Dr. David B MacManus from University College Dublin, Dr. Xiancheng Yu from Imperial College London, Dr. Haojie Mao from Western University, Dr. Rika Wright Carlsen from Robert Morris University, Dr. Declan Patton from Children's Hospital of Philadelphia, and Dr. T Christian Gasser from KTH Royal Institute of Technology for the helpful discussion on strain rate computation.

Author contributions

Zhou Zhou: Conception and study design, Theoretical investigation, Finite element simulation, Data processing, Visualization; Writing – review & editing; **Xiaogai Li:** Conception and study design, Methodology, Review & editing; **Yuzhe Liu:** Theoretical investigation, Review & editing; **Warren Hardy:** Experimental data resources; **Svein Kleiven:** Conception and study design, Methodology, Review & editing.

Conflict of Interest

The authors declare that they have no conflict of interest.

References

[1] Menon DK, Schwab K, Wright DW, Maas AI. Position statement: definition of traumatic brain injury. Archives of physical medicine and rehabilitation 2010;91:1637-40.
[2] CDC. Centers for Disease Control and Prevention, National Center for Health Statistics: Mortality data on CDC WONDER. Available at: https://wondercdcgov/mcdhtml 2020.
[3] Majdan M, Plancikova D, Brazinova A, Rusnak M, Nieboer D, Feigin V, Maas A. Epidemiology of traumatic brain injuries in Europe: a cross-sectional analysis. The Lancet Public Health 2016;1:e76-e83.
[4] Roozenbeek B, Maas AI, Menon DK. Changing patterns in the epidemiology of traumatic brain injury. Nature Reviews Neurology 2013;9:231-6.
[5] Bayly PV, Clayton EH, Genin GM. Quantitative imaging methods for the development and validation of brain biomechanics models. Annual review of biomedical engineering 2012;14:369-96.

[6] Bar-Kochba E, Scimone MT, Estrada JB, Franck C. Strain and rate-dependent neuronal injury in a 3D in vitro compression model of traumatic brain injury. Scientific Reports 2016;6:1-11.

[7] Montanino A, Saeedimasine M, Villa A, Kleiven S. Axons Embedded in a Tissue May Withstand Larger Deformations Than Isolated Axons Before Mechanoporation Occurs. Journal of Biomechanical Engineering 2019;141.

[8] Hajiaghamemar M, Margulies SS. Multi-scale white matter tract embedded brain finite element model predicts the location of traumatic diffuse axonal injury. Journal of Neurotrauma 2021;38:144-57.

[9] Kleiven S. Predictors for traumatic brain injuries evaluated through accident reconstructions. Stapp car crash J 2007;51:81-114.

[10] Bian K, Mao H. Mechanisms and variances of rotation-induced brain injury: a parametric investigation between head kinematics and brain strain. Biomechanics and modeling in mechanobiology 2020;19:2323-41.

[11] Zhou Z, Li X, Kleiven S. Fluid–structure interaction simulation of the brain–skull interface for acute subdural haematoma prediction. Biomechanics and modeling in mechanobiology 2019;18:155-73.

[12] Ho J, Zhou Z, Li X, Kleiven S. The peculiar properties of the falx and tentorium in brain injury biomechanics. Journal of biomechanics 2017;60:243-7.

[13] Zhou Z, Li X, Kleiven S. Biomechanics of periventricular injury. Journal of neurotrauma 2020.

[14] Zhou Z, Li X, Kleiven S. Biomechanics of acute subdural hematoma in the elderly: a fluid-structure interaction study. Journal of neurotrauma 2019;36:2099-108.

[15] Zhan X, Li Y, Liu Y, Domel AG, Alizadeh HV, Zhou Z, Cecchi NJ, Raymond SJ, Tiernan S, Ruan J. Predictive factors of kinematics in traumatic brain injury from head impacts based on statistical interpretation. Annals of biomedical engineering 2021;49:2901-13.

[16] Cecchi NJ, Domel AG, Liu Y, Rice E, Lu R, Zhan X, Zhou Z, Raymond SJ, Sami S, Singh H. Identifying factors associated with head impact kinematics and brain strain in high school American football via instrumented mouthguards. Annals of Biomedical Engineering 2021;49:2814-26.

[17] Takhounts EG, Ridella SA, Hasija V, Tannous RE, Campbell JQ, Malone D, Danelson K, Stitzel J, Rowson S, Duma S. Investigation of Traumatic Brain Injuries Using the Next Generation of Simulated Injury Monitor (SIMon) Finite Element Head Model. Stapp car crash journal 2008;52:1-31.

[18] Weaver AA, Danelson KA, Stitzel JD. Modeling brain injury response for rotational velocities of varying directions and magnitudes. Annals of biomedical engineering 2012;40:2005-18.

[19] Sullivan S, Eucker SA, Gabrieli D, Bradfield C, Coats B, Maltese MR, Lee J, Smith C, Margulies SS. White matter tract-oriented deformation predicts traumatic axonal brain injury and reveals rotational direction-specific vulnerabilities. Biomechanics and modeling in mechanobiology 2015;14:877-96.

[20] Zhou Z, Li X, Liu Y, Fahlstedt M, Georgiadis M, Zhan X, Raymond SJ, Grant G, Kleiven S, Camarillo D. Toward a comprehensive delineation of white matter tract-related deformation. Journal of Neurotrauma 2021;38:3260-78.

[21] Montanino A, Li X, Zhou Z, Zeineh M, Camarillo D, Kleiven S. Subject-specific multiscale analysis of concussion: from macroscopic loads to molecular-level damage. Brain multiphysics 2021;2:100027.

[22] Hardy WN, Mason MJ, Foster CD, Shah CS, Kopacz JM, Yang KH, King AI, Bishop J, Bey M, Anderst W. A Study of the Response of the Human Cadaver Head to Impact. Stapp Car Crash J 2007;51:17-80.

[23] Zhou Z, Li X, Kleiven S, Hardy WN. Brain strain from motion of sparse markers. Stapp car crash journal 2019;63:1-27.

[24] Knutsen AK, Gomez AD, Gangolli M, Wang W-T, Chan D, Lu Y-C, Christoforou E, Prince JL, Bayly PV, Butman JA. In vivo estimates of axonal stretch and 3D brain deformation during mild head impact. Brain multiphysics 2020;1:100015.

[25] Takhounts EG, Craig MJ, Moorhouse K, McFadden J, Hasija V. Development of Brain
Injury Criteria (BrIC). Stapp car crash journal 2013;57:243-66.

[26] Mao H, Zhang L, Jiang B, Genthikatti VV, Jin X, Zhu F, Makwana R, Gill A, Jandir G, Singh
A. Development of a finite element human head model partially validated with thirty five
experimental cases. Journal of biomechanical engineering 2013;135:111002.

[27] Laituri T, Henry S, Pline K, Li G, Frankstein M, Weerappuli P. New Risk Curves for
NHTSA's Brain Injury Criterion (BrIC): Derivations and Assessments. Stapp car Crash Journal
2016;60:301-62.

[28] Liu Y, Domel AG, Cecchi NJ, Rice E, Callan AA, Raymond SJ, Zhou Z, Zhan X, Li Y,
Zeineh MM, Grant GA, Camarillo DB. Time Window of Head Impact Kinematics Measurement
for Calculation of Brain Strain and Strain Rate in American Football. Annals of Biomedical
Engineering 2021;49:2791-804.

[29] Beckwith JG, Zhao W, Ji S, Ajamil AG, Bolander RP, Chu JJ, McAllister TW, Crisco JJ,
Duma SM, Rowson S. Estimated brain tissue response following impacts associated with and
without diagnosed concussion. Annals of biomedical engineering 2018;46:819-30.

[30] Post A, Kendall M, Koncan D, Cournoyer J, Hoshizaki TB, Gilchrist MD, Brien S, Cusimano
MD, Marshall S. Characterization of persistent concussive syndrome using injury
reconstruction and finite element modelling. Journal of the mechanical behavior of biomedical
materials 2015;41:325-35.

[31] McAllister TW, Ford JC, Ji S, Beckwith JG, Flashman LA, Paulsen K, Greenwald RM.
Maximum principal strain and strain rate associated with concussion diagnosis correlates with
changes in corpus callosum white matter indices. Annals of biomedical engineering
2012;40:127-40.

[32] Mao H, Zhang L, Yang K, King A. Application of a finite element model of the brain to study
traumatic brain injury mechanisms in the rat. Stapp car Crash Journal 2006;50:583-600.

[33] Viano DC, Casson IR, Pellman EJ, Zhang L, King AI, Yang KH. Concussion in professional
football: brain responses by finite element analysis: part 9. Neurosurgery 2005;57:891-916.

[34] Rashid B, Destrade M, Gilchrist MD. Influence of preservation temperature on the
measured mechanical properties of brain tissue. Journal of biomechanics 2013;46:1276-81.

[35] Zhou Z, Li X, Domel AG, Dennis EL, Georgiadis M, Liu Y, Raymond SJ, Grant G, Kleiven
S, Camarillo D, Zeineh M. The Presence of the Temporal Horn Exacerbates the Vulnerability
of Hippocampus during Head Impacts Frontiers in bioengineering and biotechnology 2022;10.

[36] King AI, Yang KH, Zhang L, Hardy W, Viano DC. Is head injury caused by linear or angular
acceleration. IRCOBI conference: Lisbon, Portugal; 2003.

[37] LaPlaca MC, LEE VM-Y, THIBAULT LE. An in vitro model of traumatic neuronal injury:
loading rate-dependent changes in acute cytosolic calcium and lactate dehydrogenase
release. Journal of neurotrauma 1997;14:355-68.

[38] Zhou Z, Li X, Kleiven S, Shah CS, Hardy WN. A Reanalysis of Experimental Brain Strain
Data: Implication for Finite Element Head Model Validation. Stapp car crash journal
2018;62:293-318.

[39] Zhao W, Ji S. Displacement-and strain-based discrimination of head injury models across
a wide range of blunt conditions. Annals of biomedical engineering 2020;48:1661-77.

[40] Zhou Z, Domel AG, Li X, Grant G, Kleiven S, Camarillo D, Zeineh M. White matter tract-
oriented deformation is dependent on real-time axonal fiber orientation. Journal of
neurotrauma 2021;38:1730-45.

[41] Hajiaghamemar M, Wu T, Panzer MB, Margulies SS. Embedded axonal fiber tracts
improve finite element model predictions of traumatic brain injury. Biomechanics and modeling
in mechanobiology 2020;19:1109-30.

[42] Hernandez F, Giordano C, Goubran M, Parivash S, Grant G, Zeineh M, Camarillo D.
Lateral impacts correlate with falx cerebri displacement and corpus callosum trauma in sports-
related concussions. Biomechanics and modeling in mechanobiology 2019;18:631-49.

[43] Miller LE, Urban JE, Davenport EM, Powers AK, Whitlow CT, Maldjian JA, Stitzel JD. Brain
strain: computational model-based metrics for head impact exposure and injury correlation.
Annals of biomedical engineering 2021;49:1083-96.

[44] Hajiaghamemar M, Seidi M, Margulies SS. Head rotational kinematics, tissue deformations, and their relationships to the acute traumatic axonal injury. Journal of biomechanical engineering 2020;142:031006.

[45] Hernandez F, Camarillo DB. Voluntary head rotational velocity and implications for brain injury risk metrics. Journal of neurotrauma 2019;36:1125-35.

[46] Sahoo D, Deck C, Willinger R. Brain injury tolerance limit based on computation of axonal strain. Accident Analysis & Prevention 2016;92:53-70.

[47] Vogel EW, Panzer MB, Morales FN, Varghese N, Bass CR, Meaney DF, Morrison B. Direct observation of low strain, high rate deformation of cultured brain tissue during primary blast. Annals of biomedical engineering 2020;48:1196-206.

[48] Wu T, Hajiaghamemar M, Giudice JS, Alshareef A, Margulies SS, Panzer MB. Evaluation of tissue-level brain injury metrics using species-specific simulations. Journal of neurotrauma 2021.

[49] Zhang L, Yang KH, King AI, Viano DC. A new biomechanical predictor for mild traumatic brain injury–A preliminary finding. Proc 2003 Summer Bioengineering Conference2003. p. 137-8.

[50] Holzapfel AG. Nonlinear solid mechanics: A continuum approach for engineering: Wiley, Chichester; 2000.

[51] Reese TG, Feinberg DA, Dou J, Wedeen VJ. Phase contrast MRI of myocardial 3D strain by encoding contiguous slices in a single shot. Magnetic Resonance in Medicine: An Official Journal of the International Society for Magnetic Resonance in Medicine 2002;47:665-76.

[52] Malis V, Sinha U, Sinha S. 3D Muscle Deformation Mapping at Submaximal Isometric Contractions: Applications to Aging Muscle. Frontiers in physiology 2020;11:1563.

[53] Mazzoli V, Gottwald LM, Peper ES, Froeling M, Coolen BF, Verdonschot N, Sprengers AM, van Ooij P, Strijkers GJ, Nederveen AJ. Accelerated 4 D phase contrast MRI in skeletal muscle contraction. Magnetic resonance in medicine 2018;80:1799-811.

[54] Sinha U, Malis V, Chen J-S, Csapo R, Kinugasa R, Narici MV, Sinha S. Role of the Extracellular Matrix in Loss of Muscle Force With Age and Unloading Using Magnetic Resonance Imaging, Biochemical Analysis, and Computational Models. Frontiers in Physiology 2020;11:626.

[55] Sinha U, Malis V, Csapo R, Narici M, Sinha S. Shear strain rate from phase contrast velocity encoded MRI: application to study effects of aging in the medial gastrocnemius muscle. Journal of Magnetic Resonance Imaging 2018;48:1351-7.

[56] Wedeen VJ. Magnetic resonance imaging of myocardial kinematics. Technique to detect, localize, and quantify the strain rates of the active human myocardium. Magnetic resonance in medicine 1992;27:52-67.

[57] Robson MD, Constable RT. Three‐dimensional strain‐rate imaging. Magnetic resonance in medicine 1996;36:537-46.

[58] Dou J, Tseng WYI, Reese TG, Wedeen VJ. Combined diffusion and strain MRI reveals structure and function of human myocardial laminar sheets in vivo. Magnetic Resonance in Medicine: An Official Journal of the International Society for Magnetic Resonance in Medicine 2003;50:107-13.

[59] de Rooij R, Kuhl E. Constitutive modeling of brain tissue: current perspectives. Applied Mechanics Reviews 2016;68.

[60] Ghajari M, Hellyer PJ, Sharp DJ. Computational modelling of traumatic brain injury predicts the location of chronic traumatic encephalopathy pathology. Brain 2017;140:333-43.

[61] Donat CK, Yanez Lopez M, Sastre M, Baxan N, Goldfinger M, Seeamber R, Müller F, Davies P, Hellyer P, Siegkas P. From biomechanics to pathology: predicting axonal injury from patterns of strain after traumatic brain injury. Brain 2021;144:70-91.

[62] Li X, Zhou Z, Kleiven S. An anatomically detailed and personalizable head injury model: Significance of brain and white matter tract morphological variability on strain. Biomechanics and modeling in mechanobiology 2021;20:403-31.

[63] Kleiven S. Predictors for traumatic brain injuries evaluated through accident reconstructions. Stapp car crash journal 2007;51:81-114.

[64] Nahum AM, Smith R, Ward CC. Intracranial pressure dynamics during head impact. Proceedings of the 21st Stapp Car Crash Conference. Warrendale, PA, USA: SAE Technical Paper; 1977. p. 337-66.

[65] Mori S, Oishi K, Jiang H, Jiang L, Li X, Akhter K, Hua K, Faria AV, Mahmood A, Woods R. Stereotaxic white matter atlas based on diffusion tensor imaging in an ICBM template. Neuroimage 2008;40:570-82.

[66] Hernandez F, Wu LC, Yip MC, Laksari K, Hoffman AR, Lopez JR, Grant GA, Kleiven S, Camarillo DB. Six degree-of-freedom measurements of human mild traumatic brain injury. Annals of biomedical engineering 2015;43:1918-34.

[67] Wu Y-H, Rosset S, Lee T-r, Dragunow M, Park T, Shim V. In vitro models of traumatic brain injury: A systematic review. Journal of Neurotrauma 2021;38:2336-72.

[68] Morrison III B, Elkin BS, Dollé J-P, Yarmush ML. In vitro models of traumatic brain injury. Annual review of biomedical engineering 2011;13:91-126.

[69] Montanino A. Definition of axonal injury tolerances across scales: A computational multiscale approach: Kungliga Tekniska högskolan; 2020.

[70] Patton DA, McIntosh AS, Kleiven S. The biomechanical determinants of concussion: finite element simulations to investigate tissue-level predictors of injury during sporting impacts to the unprotected head. Journal of applied biomechanics 2015;31:264-8.

[71] Feng Y, Abney TM, Okamoto RJ, Pless RB, Genin GM, Bayly PV. Relative brain displacement and deformation during constrained mild frontal head impact. Journal of the Royal Society Interface 2010;7:1677-88.

[72] Bradshaw D, Morfrey C. Pressure and shear responses in brain injury models. Proceedings: International Technical Conference on the Enhanced Safety of Vehicles: National Highway Traffic Safety Administration; 2001. p. 10 p.- p.

[73] Kleiven S, Hardy W. Correlation of an FE Model of the Human Head with Local Brain Motion--Consequences for Injury Prediction. Stapp car Crash Journal 2002;46:123-44.

[74] Zhao W, Ruan S, Ji S. Brain pressure responses in translational head impact: a dimensional analysis and a further computational study. Biomechanics and modeling in mechanobiology 2015;14:753-66.

[75] Fahlstedt M, Abayazid F, Panzer MB, Trotta A, Zhao W, Ghajari M, Gilchrist MD, Ji S, Kleiven S, Li X. Ranking and rating bicycle helmet safety performance in oblique impacts using eight different brain injury models. Annals of biomedical engineering 2021;49:1097-109.

[76] Zhou Z, Wang T, Jörgens D, Li X. Fiber orientation downsampling compromises the computation of white matter tract-related deformation. Journal of the Mechanical Behavior of Biomedical Materials 2022;132:105294.

[77] Morrison III B, Cater HL, Wang CC, Thomas FC. A tissue level tolerance criterion for living brain developed with an in vitro model of traumatic mechanical loading. Stapp car crash journal 2003;47:93.

[78] Morrison III B, Cater H, Wang C, Thomas F, Hung C, Ateshian G, Sundstrom L. A tissue level tolerance criterion for living brain developed with an in vitro model of traumatic mechanical loading. Stapp Car Crash Journal 2003;47:93-105.

[79] DiMasi F, Eppinger RH, Bandak F. Computational Analysis of Head Impact Response Under Car Crash Loadings. Proceedings: Stapp Car Crash Conference: Society of Automotive Engineers SAE; 1995. p. 425-38.

[80] Shreiber DI, Bain A, Meaney D. In Vivo Thresholds for Mechanical Injury to the Blood-Brain Barrier. Proceedings: Stapp Car Crash Conference: Society of Automotive Engineers SAE; 1997. p. 277-91.

[81] Zhou R, Li Y, Cavanaugh JM, Zhang L. Investigate the variations of the head and brain response in a rodent head impact acceleration model by finite element modeling. Frontiers in bioengineering and biotechnology 2020;8:172.

[82] Jin X, Zhu F, Mao H, Shen M, Yang KH. A comprehensive experimental study on material properties of human brain tissue. Journal of biomechanics 2013;46:2795-801.

[83] Laksari K, Shafieian M, Darvish K. Constitutive model for brain tissue under finite compression. Journal of biomechanics 2012;45:642-6.

[84] Karimi A, Navidbakhsh M. An experimental study on the mechanical properties of rat brain
tissue using different stress–strain definitions. Journal of Materials Science: Materials in
Medicine 2014;25:1623-30.
[85] Gasser TC. Vascular Biomechanics. Springer; 2021. p. 91-165.
[86] Hardy WN, Foster CD, Mason MJ, Yang KH, King AI, Tashman S. Investigation of head
injury mechanisms using neutral density technology and high-speed biplanar X-ray. Stapp car
crash journal 2001;45:337-68.
[87] Gehre C, Gades H, Wernicke P. Objective rating of signals using test and simulation
responses. 21st International Technical Conference on the Enhanced Safety of Vehicles
Conference (ESV)2009. p. 09-0407.

Appendix: Strain rate evaluation of finite element head model

Strain rate responses of the ADAPT model were validated against the newly calculated

experimental results. Three representative impacts were selected, including C1 in C288T3

(sagittal impact), C1 in C380T2 (horizontal impact), and C1 in C380T4 (coronal impact). To

better reflect the cranial geometry of experimental specimens, the model was scaled to match

the reported anthropometric measurements of the cadaveric heads. The nodes nearest to the

initial position of the experimental NDT markers were identified and further informed the

formulation of the eight tetrahedral elements representing the tissue encased by the

experimental NDT cluster. Following the same approach of computing experimental strain rate,

the 3D motion of the identified nodes with respect to the skull was acquired from the whole

head model simulation and further exercised the tetrahedral elements, through which the first

principal strain rate of each element was respectively extracted as the time derivatives of the

first principal strain (i.e., $\dot{\mathrm{PSR}}(t)$ for the scheme 1) and maximum eigenvalue of the rate of

deformation tensor (i.e., $\hat{\mathrm{PSR}}(t)$ for the scheme 2). For each cluster, the strain rates from all

eight elements were averaged.

The correlation between the computationally predicted strain rate responses and

experimentally determined measurements was quantitatively evaluated by the cross-

correlation method in CORA (correlation and analysis) with technical details available in [87].

Briefly, the cross-correlation method in CORA scored the level of correlation between a pair of

time history curves by equally weighting their similarities in shape, size, and phase. The CORA

score ranges from 0 (no correlation) to 1 (perfect match). The exact setting of relevant

parameters for CORA implementation and biofidelity classification based on CORA scores are

respectively presented in Table A1 and Table A2.

Table A1. Parameter setting for the cross-correlation in CORA.

Parameter	Value	Parameter	Value
A_THRES	0.030	INT_MIN	0.70
B_THRES	0.075	K_V	3
A_VAL	0.010	K_P	1
B_DELTA_END	0.200	K_G	1
T_MIN / T_MAX (ms)	0/40	G_V	0.333
D_MIN	0.01	G_P	0.333
D_MAX	0.25	G_G	0.333

694 Table A2. Biofidelity rate and corresponding range of CORA score defined by ISO/TR 9790.

Biofidelity rating	CORA score
Excellent	0.86-1.00
Good	0.65-0.86
Fair	0.44-0.65
Margin	0.26-0.44
Unacceptable	0-0.26

Figure A1 illustrates the comparison of model-predicted strain rate curves against the

experiment-derived results for both schemes. The CORA score ranged from 0.65 to 0.71 for

scheme 1 and from 0.64 to 0.94 for scheme 2. According to the biofidelity classification based

on CORA scores (Table A2), the strain rate response of the ADAPT model can be rated as

"good" for scheme 1, and "good" to "excellent" for scheme 2.

Figure A1. Comparison of experimental and simulated strain rates computed by scheme 1 (upper row)
and scheme 2 (low row).