Speech understanding oppositely affects acoustic and linguistic neural tracking in a speech rate manipulation paradigm.

Abbreviated title: Untangling acoustic and linguistic neural tracking

Eline Verschueren [a,*,△] **& Marlies Gillis** [a,△]**, Lien Decruy** [b]**, Jonas Vanthornhout** [a] **and Tom Francart** [a]

[a]*:Research Group Experimental Oto-rhino-laryngology (ExpORL), Department of Neurosciences, KU Leuven - University of Leuven, 3000 Leuven, Belgium*

[b]*:Institute for Systems Research, University of Maryland, College Park, MD 20742, USA*

△*: shared first authorship*

Correspondence*:
Eline Verschueren
Herestraat 49, bus 721, 3000 Leuven, Belgium
eline.verschueren@kuleuven.be

Word Counts: Abstract (225), Introduction (626), Discussion (1278)

Funding: The presented study received funding from the European Research Council

(ERC) under the European Union's Horizon 2020 research and innovation programme (Tom

Francart; grant agreement No. 637424). Research of Eline Verschueren (PhD grant: SB

1S86118N), Marlies Gillis (PhD grant: SB 1SA0620N) and Jonas Vanthornout (postdoctoral

grant: 1290821N) was funded by the Research Foundation Flanders (FWO).

Acknowledgment: The authors would like to thank Sofie Keunen and Elise Verwaerde for

their help in data acquisition.

ABSTRACT

When listening to continuous speech, the human brain can track features of the presented speech signal. It has been shown that neural tracking of acoustic features is a prerequisite for speech understanding and can predict speech understanding in controlled circumstances. However, the brain also tracks linguistic features of speech, which may be more directly related to speech understanding. We investigated acoustic and linguistic speech processing as a function of varying speech understanding by manipulating the speech rate. In this paradigm, acoustic and linguistic speech processing are affected simultaneously but in opposite directions: When the speech rate increases, more acoustic information per second is present. In contrast, the tracking of linguistic information becomes more challenging when speech is less intelligible at higher speech rates. We measured the EEG of 18 participants (4 male) who listened to speech at various speech rates. As expected and confirmed by the behavioral results, speech understanding decreased with increasing speech rate. Accordingly, linguistic neural tracking decreased with increasing speech rate, but acoustic neural tracking increased. This indicates that neural tracking of linguistic representations can capture the gradual effect of decreasing speech understanding. In addition, increased acoustic neural tracking does not necessarily imply better speech understanding. This suggests that, although more challenging to measure due to the low signal-to-noise ratio, linguistic neural tracking may be a more direct predictor of speech understanding.

Keywords: neural coding, natural speech, speech rate, EEG, acoustic hearing, linguistic representations

Significance statement: An increasingly popular method to investigate neural speech processing is to measure neural tracking. Although much research has been done on how the brain tracks acoustic speech features, linguistic speech features have received less attention. In this study, we disentangled acoustic and linguistic characteristics of neural speech tracking via manipulating the speech rate. A proper way of objectively measuring auditory and language processing paves the way towards clinical applications: An objective measure of speech understanding would allow for behavioral-free evaluation of speech understanding, which allows to evaluate hearing loss and adjust hearing aids based on brain responses. This objective measure would benefit populations from whom obtaining behavioral measures may be complex, such as young children or people with cognitive impairments.

1 INTRODUCTION

Understanding speech relies on the integration of different acoustic and linguistic properties

of the speech signal. The acoustic properties are mainly related to sound perception,

while the linguistic properties are linked to the content and understanding of speech. When

listening to continuous speech, our brain can track both the acoustic and linguistic properties

of the presented speech signal.

Neural tracking of acoustic properties of natural speech has been the subject of many

studies. Particular emphasis has been placed on recovering the temporal envelope, i.e., the

slow modulations of the speech signal, from the brain responses, so-called neural envelope

tracking. The temporal envelope is essential for speech understanding (Shannon et al.,

1995), and neural envelope tracking can be linked to speech intelligibility (e.g. Ding and

Simon, 2013; Vanthornhout et al., 2018; Lesenfants et al., 2019; Iotzov and Parra, 2019;

Verschueren et al., 2020). However, only taking acoustic speech properties into account to

investigate neural speech tracking would underestimate the complexity of the human brain,

where linguistic properties also play an essential part, as reviewed in detail by Brodbeck

and Simon (2020).

In addition to acoustic properties, there is growing interest in retrieving linguistic

properties from brain responses to speech. Broderick et al. (2018) used semantic

dissimilarity to quantify the meaning carried by words based on their preceding context.

They report that the brain responds in a time-locked way to the semantic context of each

content word. Additionally, neural tracking is also observed to linguistic properties derived

from the probability of a given word or phoneme, i.e., word or phoneme surprisal (Brodbeck

et al., 2018; Weissbart et al., 2019; Koskinen et al., 2020). Recently Gillis et al. (2021b)

combined several linguistic neural tracking measures and evaluated the potential of each

measure as a neural marker of speech intelligibility. After controlling for acoustic properties,

phoneme surprisal, cohort entropy, word surprisal, and word frequency were significantly

tracked. These results show the potential of linguistic representations as a neural marker of

speech intelligibility. In addition, this underlines the importance of controlling for acoustic
features when investigating linguistic neural processing, as acoustic and linguistic features
are often correlated (Brodbeck and Simon, 2020).

We investigated whether neural speech processing can capture the effect of gradually
decreasing speech understanding by manipulating the speech rate. In this study, we focused
on acoustic and linguistic speech processing. By changing the speech rate, we manipulate
acoustic and linguistic speech processing simultaneously but in opposite directions: When
increasing the speech rate, more phonemes, words, and sentences, and thus more acoustic
information per second is present. In contrast, linguistic tracking decreases because it
becomes more challenging to identify the individual phonemes or words at high speech rates,
causing decreased speech understanding. We hypothesize that neural tracking of acoustic
features will increase with increasing speech rate because more acoustic information will
be present. However, linguistic speech tracking will decrease with increasing speech rate
because of decreasing speech understanding. The effect of speech rate on neural responses
to speech has already been investigated. However, all these studies only investigated brain
responses to the acoustic properties of the speech signal (Ahissar et al., 2001; Nourski et al.,
2009; Hertrich et al., 2012; Müller et al., 2019; Casas et al., 2021). It is challenging to
extrapolate these findings to what would happen at a linguistic level as acoustic aspects of
the speech dominate the neural responses to speech. No study, to our knowledge, reported
on how speech rate affects linguistic speech processing and the potential interaction between
both. In addition, no consensus has been reached on the effect of speech rate on acoustic
neural tracking. For example, Nourski et al. (2009) reported that phase-locked responses
decrease with increasing speech rate, similar to Ahissar et al. (2001) and Hertrich et al.
(2012). However, in the same data, Nourski et al. (2009) also reported that time-locked
responses to the envelope (70-250 Hz) could still be found at very high speech rates where
speech is no longer understood.

We investigated how linguistic and acoustic speech tracking are affected when
speech understanding gradually decreases. Analyzing neural speech tracking to different
characteristics of the presented speech allows us to identify neural patterns associated with
speech understanding.

2   MATERIAL AND METHODS

2.1   Participants

101   Eighteen participants aged between 19 and 24 years (4 men and 14 women) took part in the
102   experiment after having provided informed consent. Participants had Dutch as their mother
103   tongue and were all normal-hearing, confirmed with pure tone audiometry (thresholds $\leq$
104   25 dB HL at all octave frequencies from 125 Hz to 8 kHz). The study was approved by the
105   Medical Ethics Committee UZ Leuven / Research (KU Leuven) with reference S57102.

2.2   Speech material

The story presented during the EEG measurement was 'A casual vacancy' by J.K. Rowling,
narrated in Dutch by Nelleke Noordervliet. The story was manually cut into 12 blocks
of varying length selected from the following list: 4 min, 5 min, 8.5 min, 12.5 min, 18
min, and 23 min. After cutting the story, the story was time-compressed with the Pitch
Synchronous Overlap and Add algorithm (PSOLA) from PRAAT (Boursma and Weenink,
2018) to manipulate the speech rate. This algorithm compresses the speech by dividing the
speech into small overlapping segments and then repeating or deleting segments to decrease
or increase the speech rate, thereby preserving the pitch. However, this manipulation
is not exactly comparable with fast natural speech where vowels and silences become
shorter, while some consonants (like, e.g, 't') cannot be shortened. Using this algorithm all
phonemes are merging similarly and the formant transitions are probably not completely
realistic anymore. Six different compression ratio's (CR) were used: 1.4, 1.0, 0.6, 0.4, 0.28,
0.22 with corresponding speech rates varying from $\approx$ 2.6 syllables/second (CR=1.4) to

$\approx$ 16.2 syllables/second (CR=0.22). An example audio fragment for every speech rate is
added as supplementary material. The fastest CR (CR=0.22) was applied to the longest
part (23 min), the one but fastest CR (CR=0.28) to the one but longest part (18 min),
and so on. This way, all story parts were compressed or expanded to $\approx$ 5 minutes. These
blocks had slightly different lengths because word and sentence boundaries were taken
into account while cutting the story, which is important for the linguistic analysis. Every
speech rate was presented twice to obtain 10 minutes of speech at the same rate. The
story was presented in chronological order and no part of the story was presented twice
to the same participant. Although the linguistic measures only go back up to 4 words,
and higher top-down processing has limited impact on the linguistic measures we used,
we presented all speech rates in random order per participant. This way the effect of the
level of understanding of previous parts, which could influence linguistic processing, was
minimized. For each stimulus block, we determined the number of syllables using the
forced aligner of the speech alignment component of the reading tutor (Duchateau et al.,
2009) and CELEX database (Baayen et al., 1996). The number of syllables uttered for each
speech block was then divided by the duration of the speech block in seconds to obtain the
speech rate.

After each part of the story, content questions were asked to maximize the participants'
attention and motivation. In addition, speech intelligibility was measured after each block
by asking the participants to rate their speech understanding on a scale from 0 to 100%
following the question 'Which percentage of the story did you understand?'. A short
summary of the story was shown in the beginning of the experiment to enhance intelligibility
as some participants started with more difficult speech rates.

2.3 Experimental setup

2.3.1 EEG recording

EEG was recorded with a 64-channel BioSemi ActiveTwo EEG recording system at a sample rate of 8192 Hz. Participants sat in a comfortable chair and were asked to move as little as possible during the EEG recordings. All stimuli were presented bilaterally using APEX 4 (Francart et al., 2008), an RME Multiface II sound card (Haimhausen, Germany), and Etymotic ER-3A insert phones (Illinois, USA). The setup was calibrated using a 2 cm^3 coupler of the artificial ear (Brüel $\&$ Kjær 4152, Denmark). Recordings were made in a soundproof and electromagnetically shielded room.

2.4 Signal processing

2.4.1 EEG processing

We processed the EEG in 5 consecutive steps. Firstly, we drift-corrected the EEG signals by applying a first-order highpass Butterworth filter with a cutoff frequency of 0.5 Hz in the forward and backward direction. Then, we reduced the sampling frequency of the EEG from 8192 Hz to 256 Hz to reduce computation time. Artifacts related to eyeblinks were removed with a multichannel Wiener filter (Somers et al., 2018). Subsequently, we referenced the EEG signals to the common average signal. The major advantage of common average referencing is that topography patterns are not biased relative to the chosen channel. No particular accentuation of certain channels allows us to investigate the contribution of neural processes related to language processing evoked by spatially different neural sources. Lastly, we removed the power line frequency of 50 Hz by using a second-order IRR notch filter at this frequency with a quality factor of 35 to determine the filter's bandwidth at the -3dB.

 ### 2.4.2   Stimuli Representations

This study aims to investigate acoustic and linguistic neural tracking at different speech

rates. To examine acoustic tracking, we estimated neural tracking based solely on acoustic

representations of the stimulus, namely the spectrogram and acoustic edges. To investigate

linguistic neural tracking, we created two models: a model to control speech acoustics,

which consisted of acoustic and lexical segmentation representations, and a model that

included linguistic representations on top of these acoustic and lexical segmentation

representations. All speech representations used in the analysis are visualized in Figure 1.

Figure 1. Speech representations at acoustic, lexical and linguistic level We visualized the speech representations used in this study for all three levels: acoustic (averaged across frequency bands; top box; blue), lexical (middle box; orange), and linguistic (bottom box; red) for the lowest speech rate (SR = 2.6 syllables/sec, left) and highest speech rate (SR = 16.2 syllables/sec; right) for the first 10 seconds of the speech material. This is the first sentence of the audio book. Note: Barry Fairbrother (second and third word) is a proper name and therefore not included in the corpus used for the linguistic features.

The spectrogram representations were calculated based on the low-pass filtered speech
stimulus (zero-phase low-pass FIR filter with a hamming window of 159 samples). We
low-pass filtered the stimulus at a cut-off frequency of 4 kHz as the insert earphones also
low-pass filter at this frequency. Subsequently, we calculated the spectrogram representation
from this filtered stimulus using the Gammatone Filterbank Toolkit (Heeris, 2014, center
frequencies between 70 and 4000 Hz with 256 filter channels and an integration window of
0.01 second). By using a Gammatone Filterbank, the estimated filter outputs are closer to
the human auditory response: the higher the frequency, the wider the filter (Slaney, 1998).
We combined the filter outputs by averaging them into eight frequency bands with center
frequencies of 124 Hz, 262 Hz, 455 Hz, 723 Hz, 1098 Hz, 1618 Hz, 2343 Hz, and 3352 Hz.
To calculate the acoustic edges representations, we took the derivative of the spectrogram's
response in each frequency band and mapped all its negative values to 0. Lastly, we reduced
the sampling frequency of these representations to the same sampling frequency as the
EEG, namely 256 Hz.

To determine linguistic neural tracking, we carefully controlled for neural responses
related to acoustic and lexical characteristics of the speech. As pointed out by Brodbeck and
Simon (2020); Gillis et al. (2021b), it is important to control for these characteristics
when investigating linguistic neural tracking, as otherwise spurious linguistic neural
tracking can be observed due to the high correlation between linguistic and acoustic
representations. To evaluate linguistic neural tracking, we determined the added value of
linguistic representations by subtracting the performance of the model containing acoustic
and lexical segmentation characteristics of the speech from the performance of the model
that included the same representations together with the linguistic representations. We used
four linguistic representations: phoneme surprisal, cohort entropy, word surprisal, and word
frequency, which according to Gillis et al. (2021b), have an added value over and beyond
acoustic representations.

All linguistic representations are one-dimensional arrays with impulses at the onsets
of phonemes or words. The amplitude of an impulse represents the amount of linguistic
information conveyed by the phoneme or word. To obtain the timing of the phonemes
and words, we used the forced aligner of the speech alignment component of the reading
tutor (Duchateau et al., 2009). Similar to linguistic representations, lexical segmentation
representations are one-dimensional arrays. However, the impulses' amplitudes are one and
thus independent of the amount of linguistic information.

Phoneme surprisal and cohort entropy are two linguistic representations that describe
the linguistic information of a phoneme. Phoneme surprisal is thought to be a measure of
phoneme prediction error as it represents how surprising a phoneme is given the previously
uttered phonemes. This surprisal measure reflects to what extent the upcoming phoneme can
be predicted, which is intrinsically related to the information contributed by the phoneme.
The more likely a specific phoneme is, the lower its surprisal value, and the less information
is gained (and vice versa). It is calculated as the negative logarithm of the inverse conditional
probability of the phoneme given the preceding phonemes of the word. Another linguistic
representation at the phoneme level is cohort entropy derived from the cohort of words
congruent with the already uttered phonemes. Cohort entropy is a measure of uncertainty:
higher cohort entropy implies that the active cohort consists of a larger number of words
with a high word frequency. It is calculated as the Shannon entropy of this active cohort of
words. Both measures have a similar trend: phoneme surprisal and cohort entropy decrease
when more phonemes of the word are pronounced because the prediction of the upcoming
word can be made with a higher precision.

To calculate both representations, we used a custom pronunciation dictionary that maps a
word to its phoneme representation. This dictionary was created by manual and grapheme-to-
phoneme conversion and contained the segmentation of 9157 words. The word probabilities
were derived from the SUBTLEX-NL database (Keuleers et al., 2010). The linguistic
information of the initial phoneme was not modeled in these representations. More details

regarding phoneme surprisal and cohort entropy, as well as the mathematical determinations,
can be found in Brodbeck et al. (2018).

The linguistic information conveyed by a word is described by word surprisal and word
frequency. Similarly as phoneme surprisal, word surprisal reflects to what extent the
upcoming word can be predicted based on the information contributed by that word. We
used a 5-gram model to determine the negative logarithm of the conditional probability
of the word given the preceding words. Therefore, a word's surprisal is estimated given
its four preceding words. Word frequency was derived from the same 5-gram model but
without including previous words, describing the word's unigram probability. This measure
reflects the probability of the word, independent of its context.

Notice that these linguistic representations rely on the statistical probabilities in language.
Gwilliams and Davis (2022) reviewed in detail how listeners rely on this type of internal
language model that allows them to predict the upcoming word or phoneme.

240 2.4.3   Determination of Neural Tracking

To determine neural tracking, we used a forward modeling approach, estimating how the
brain responds to specific speech characteristics. The temporal response function (TRF)
describes the relationship between the presented stimulus and measured EEG. It also
allows us to predict the EEG responses associated with the speech stimulus. By correlating
the predicted EEG responses with the measured EEG responses, we obtain a prediction
accuracy per EEG channel. This prediction accuracy is a measure of neural tracking.

We used the boosting algorithm (David et al., 2007) implemented by the Eelbrain Toolbox
(Brodbeck, 2020) to estimate the TRF and obtain the prediction accuracy. The boosting
algorithm estimates the TRF in a sparse and iterative way. It requires a training partition to
estimate the TRF and a validation partition to evaluate the TRF. The boosting algorithm
aims to find the optimal solution by evaluating the effect of incremental changes in the TRF.
The incremental change which yields the highest prediction accuracy on the validation set,

is kept. Incremental changes are made until no further improvement can be found on the
validation set.

We used an integration window of -100 to 600 ms, i.e., the neural response is estimated
ranging from 100 ms before activation of the stimulus characteristic to 600 ms after its
activation. We use a broad integration window to ensure that the model captures the brain
responses to the linguistic representations, which occur at longer latencies. As each speech
rate condition was presented twice, we estimated the TRF on the concatenation of these
two blocks per speech rate, i.e., ten minutes of data. Before the TRF estimation, the data is
normalized by dividing by the Euclidean norm per channel. We applied this normalization
for the stimulus and EEG data individually. Then the boosting algorithm estimates the
associated response behavior using a fixed step size of 0.005. We derived the TRF and
prediction accuracy per channel using a cross-validation scheme: the TRF was estimated
and validated on partitions unseen during testing of the TRF to obtain the prediction
accuracy. More specifically, we used 10-fold cross-validation, implying the data was split
into ten equally long folds, of which eight folds are used for estimating the TRF, one fold for
validation, and one fold for testing. The obtained TRFs and prediction accuracies are then
averaged across the different folds. Note that the validation fold is required to determine
the stopping criterion: we used an early stopping based on the ℓ_2-norm, i.e., estimation
of the TRF is stopped when the Euclidian distance between the actual and predicted EEG
data on the validation partition stops decreasing. The resulting TRFs are sparse. Therefore,
to account for the inter-subject variability and obtain a meaningful average TRF response
across subjects, we smoothed the TRFs across time by convolving the estimated response
with a hamming window of 50 ms in the time dimension.

To determine the acoustic tracking of the speech, we purely used acoustic representations.
Therefore, we determined the prediction accuracy and TRFs based on the spectrogram
and acoustic edges. Regarding the linguistic tracking of speech, we investigated the added
value of these linguistic representations. To determine the added value, we subtracted

the prediction accuracies of two different models. Firstly, we estimated a baseline model
consisting of acoustic and lexical segmentation representations. Secondly, we estimated
a combined model which included linguistic representations on top of the acoustic and
lexical segmentation representations. By subtracting the prediction accuracy obtained with
the baseline model from the prediction accuracy of the combined model, we can examine
the added value of the linguistic representations after controlling for the acoustic and lexical
segmentation representations. Please note that we did not include lexical features in the
acoustic or linguistic model because the neural response to a phoneme or word onset does
not reflect purely acoustic nor linguistic processing (Sanders and Neville, 2003).

We used two predetermined channel selections to investigate the effect of acoustic and
linguistic tracking. The neural responses to acoustics are significantly different from those
to linguistic content and therefore require a different channel selection. We used a frontal
channel selection for acoustic neural tracking based on Lesenfants et al. (2019) and a central
channel selection for linguistic neural tracking as reported by Gillis et al. (2021b).

Table 1. Time windows selected per speech representation to determine the peak characteristics

Speech representation	Time window(s)	Channel selection
Spectrogram Acoustic edges	0 to 90 ms, 110 to 200 ms	frontocentral
Phoneme surprisal Cohort entropy	200 to 300 ms	central
Word surprisal Word frequency	350 to 450 ms	central

These channel selections were used to visualize the TRFs and to determine associated peak
latency and amplitudes. To determine the peak characteristics, we set a preset time window
based on the TRF averaged across subjects (see Table 1). Within this time window, we
normalized the TRF per channel by dividing the TRF by its ℓ_2-norm over time to decrease

across subject variability and averaged the TRF across the channel selection. Depending
on a positive or negative peak, we determined the maximal or minimal amplitude and its
corresponding latency to obtain the peak amplitude and latency. If the peak latency was the
same as the beginning of the window, indicating the end of the previous peak, we discarded
the peak from the analysis (see Table 2).

Table 2. Number of peaks detected per speech representation per speech rate with n_{max} = 18 (= amount of participants).

	2.6 syll/sec	3.6 syll/sec	6.2 syll/sec	9.0 syll/sec	12.9 syll/sec	16.2 syll/sec
Spectrogram - peak 1	n = 15	n = 17	n = 18	n = 18	n = 18	n = 18
Spectrogram - peak 2	n = 14	n = 16	n = 18	n = 15	n = 13	n = 11
Acoustic edges - peak 1	n = 17	n = 17	n = 18	n = 18	n = 18	n = 18
Acoustic edges - peak 2	n = 18	n = 17	n = 16	n = 10	n = 8	n = 8
Phoneme surprisal	n = 17	n = 18	n = 17	n = 16	n = 15	n = 18
Cohort entropy	n = 17	n = 16	n = 16	n = 15	n = 18	n = 17
Word surprisal	n = 15	n = 16	n = 15	n = 18	n = 16	n = 17
Word frequency	n = 16	n = 15	n = 13	n = 14	n = 15	n = 17

2.5 Statistics

Statistical analysis was performed using MATLAB (version R2018a) and R (version 3.4.4)
software. The significance level was set at α=0.05 unless otherwise stated.

To evaluate the subjectively rated speech understanding results we calculated the
correlation between speech rate and rated speech understanding using a Spearman rank
correlation. In addition, we fitted a sigmoid function on the data to address the relation
between rated speech understanding and speech rate using the minpack.lm package (Elzhov
et al., 2016) in R. For further statistical analysis, we selected speech rate (and not
subjectively rated speech understanding) as a main predictor. We opted for this because
(1) it is impossible to obtain reliable speech understanding scores from a continuous

story. In clinical practice participants are asked to repeat sentences or words to calculate a percentage correct. Asking someone to repeat an entire discourse and scoring it is not feasible (Decruy et al., 2018; MacPherson and Akeroyd, 2014). (2) A subjective rating is very idiosyncratic. This results in a high inter-subject variability: some participants will rate their speech understanding more optimistically than others for the same underlying level of understanding. (3) Third, we investigated a homogeneous group of participants' neural responses: all normal-hearing participants between 19 and 24 years old. Therefore we do not expect large differences in speech understanding between participants at a particular speech rate.

To determine whether the topographies or the TRFs were significantly different from zero, we performed non-parametric permutation tests (Maris and Oostenveld, 2007). For the analysis of the acoustic TRFs, we limited the window of interest to the time region between 0 and 200 ms. As speech is more difficult to understand, the latency of the neural responses to acoustic representation increases (Mirkovic et al., 2019; Verschueren et al., 2021; Gillis et al., 2021a). These effects are most prominent in a time region of 0 to 200 ms (Verschueren et al., 2020; Mirkovic et al., 2019; Kraus et al., 2020), explaining the rationale to limit the time window of interest. However, no time window of interest was set to determine the significance of the linguistic TRFs. We are not aware of any studies that assess the effect of linguistic tracking when speech comprehension becomes challenging. Therefore we chose not to specify a time window of interest when investigating the neural responses to linguistic representations. As observed in previous literature, linguistic TRFs are associated with negative responses in central areas. Therefore, we applied this test in a one-sided fashion, i.e., we determined where the TRF was significantly negative.

To asses the relationship between speech rate, neural speech tracking and speech understanding, we created a linear mixed effect (LME) model using the LME4 package (Bates et al., 2015) in R with the following general formula:

$$neuralMeasure \sim rate(+rate^2)(+understanding) + random = participant$$

where "neuralMeasure" refers to neural speech tracking, TRF amplitude or TRF latency,

depending on the model being investigated and "rate" refers to the speech rate the speech

was presented at. Speech rate was also added as a quadratic effect, "rate^2", as we do not

expect neural speech tracking will decrease or increase linearly indefinitely with increasing

speech rate. Lastly, "understanding", referring to rated speech understanding, was added to

the model to investigate whether speech understanding is able to explain additional variance

on top of speech rate. An additional random intercept per participant was included in the

model to account for the multiple observations per participant. "Rate^2" and "understanding"

are added between brackets to the general formula because these factors were only included

if they benefited the model. We controlled this by calculating the Akaike Information

Criterion (AIC) for the model with and without "Rate^2" and "understanding". The model

with the lowest AIC was selected and its residuals plot was analyzed to assess the normality

assumption of the LME residuals. Unstandardized regression coefficients (beta) with 95%

confidence intervals and p-value of the factors included in the model are reported in the

results section.

3 RESULTS

3.1 Effect of speech rate on speech understanding

Figure 2 shows that when speech rate increases, rated speech understanding decreases

(r=-0.91, p<0.001, Spearman rank correlation). To model the data, we fitted a sigmoid

function between speech understanding and speech rate. The function shows a plateau

until 6 syllables/sec (=±1.5 times the rate of normal speech). When the speech rate further

increases, speech understanding drops. Because speech understanding and speech rate

are highly correlated, selecting the one or the other for the analysis should not matter too

much. We select speech rate for further analysis in function of neural speech tracking.

As mentioned above, speech rate is more reliable than the subjectively rated speech

understanding scores since it is objectively derived from the acoustic stimulus.

Figure 2. Rated speech understanding in function of speech rate. The dots show speech understanding per participant for every participant specific speech rate. The boxplots show the participants' results for the averaged speech rates (based on compression ratio). The red line is the sigmoid function fitted on the data over participant.

3.2 Effect of speech rate on neural processing of speech

To obtain the results in this section, we created two models: an acoustic model and a linguistic model as explained in detail in section 2.4.3.

3.2.1 Acoustic neural tracking

First, we investigated the acoustic model containing acoustic edges and the spectrogram. Figure 3.A shows how accurately the acoustic model can predict the speech signal for every electrode used. To better quantify this result, we selected the frontocentral channels based on Lesenfants et al. (2019) (channels are highlighted in red in the inset of figure 3.B) and averaged them per subject. This resulted in one neural tracking value per speech rate per subject. Neural tracking of this frontocentral channel selection increased with increasing speech rate ($p<0.001$, $b=7.61\text{x}10^{-3}$, $CI(95\%)$: $\pm1.59\text{x}10^{-3}$, LME, table 3). However,

376 as visualized on the right in figure 3.A this increase is not monotonous, but quadratic

377 ($p<0.001$, b=-3.28x10^{-4}, CI(95%): ± 8.41x10^{-5}, LME, table 3). Finally, adding speech

378 understanding as an extra predictor to the model does not improve the model (AIC$_{SR}$ =

379 -623, AIC$_{SR + understanding}$ = -605).

Table 3. Linear Mixed Effect Model of prediction accuracies and amplitude and latency of the TRF peaks in function of speech rate for the acoustic model

Acoustic model			Rate			Rate^2		
			β	CI(95%)	p	β	CI(95%)	p
Prediction accuarcy			7.61x10^{-3}	± 1.59x10^{-3}	<0.001	-3.28x10^{-4}	± 8.41x10^{-5}	<0.001
Spectrogram	p1	ampl	3.95x10^{-2}	± 8.00x10^{-3}	<0.001	-1.45x10^{-3}	± 4.20x10^{-4}	<0.001
		lat	1.02x10^{-3}	± 5.35x10^{-4}	<0.001	does not improve AIC		
	p2	ampl	-6.64x10^{-3}	± 1.77x10^{-3}	<0.001	does not improve AIC		
		lat	-9.81x10^{-5}	± 7.55x10^{-4}	NS	does not improve AIC		
Acoustic edges	p1	ampl	2.33x10^{-2}	± 1.05x10^{-2}	<0.001	-1.33x10^{-3}	± 5.54x10^{-4}	<0.001
		lat	1.05x10^{-3}	± 4.58x10^{-4}	<0.001	does not improve AIC		
	p2	ampl	-3.92x10^{-3}	± 1.83x10^{-3}	<0.001	does not improve AIC		
		lat	2.37x10^{-3}	± 2.84x10^{-3}	NS	does not improve AIC		

Every line represents a different model. NS = not significant, ampl = TRF amplitude, lat = TRF latency, p1 = peak 1, p2 = peak 2

To better understand the obtained quadratic tendency of neural tracking as a function of

speech rate, we analyzed the acoustic features separately using TRFs. Figure 3.B visualizes

the averaged TRF of the frontocentral channels for the spectrogram (left panel) and for the

acoustic edges (right panel). For both speech features, two significant positive peaks appear

around 70 and 150 ms (horizontal bars show the TRF parts significantly different from zero).

The topographies of these peaks are shown underneath the TRFs. More detailed analysis

on both peaks is done by calculating the maximum value for every participant per speech

rate between 0 and 90 ms (= peak value 1) and between 110 and 200 ms (= peak value 2).

We investigated the amplitude and the latency of these peak values as a function of speech

rate as shown in Figure 4. With increasing speech rate the amplitude of peak 1 increases,

saturates and decreases again for the spectrogram feature (SR: p<0.001, b=3.95x10^{-2},

CI(95%): ±8.00x10^{-3}; SR^2: p<0.001, b=-1.45x10^{-3}, CI(95%): ±4.20x10^{-4}; LME; table

3) and acoustic edges (SR: p<0.001, b=2.33x10^{-2}, CI(95%): ±1.05x10^{-2}; SR^2: p<0.001,

b=-1.33x10^{-3}, CI(95%): ±5.54x10^{-4}; LME; table 3). In contrast, the amplitude of peak

2 decreases with increasing speech rate (spectrogram: p<0.001, b=-6.64x10^{-3}, CI(95%):

±1.77x10^{-3}; acoustic edges: p<0.001, b=-3.92x10^{-3}, CI(95%): ±1.83x10^{-3}; LME; table

3). Interestingly, the second peak for the acoustic edges even disappears when the speech

rate is 9 syllables/sec or higher and speech understanding drops below 80% (Figure 3.B,

horizontal bars show the TRF parts significantly different from zero). For the latency

analysis of peak 2 for acoustic edges, we thus only include the latency of the peaks in the 3

easiest speech rate conditions, as no peaks (and latencies) can be found anymore at higher

speech rates. The latency of peak 1, for both speech features, increases with increasing

speech rate (spectrogram: p<0.001, b=1.02x10^{-3}, CI(95%): ±5.35x10^{-4}; acoustic edges:

p<0.001, b=1.05x10^{-3}, CI(95%): ±4.58x10^{-4}; LME; table 3), while the latency of peak

2 shows no significant relation with speech rate (spectrogram: p=0.80, b=-9.81x10^{-5},

CI(95%): ±7.55x10^{-4}; acoustic edges: p=0.11, b=2.37x10^{-3}, CI(95%): ±2.84x10^{-3};

LME; table 3).

407 3.2.2 Linguistic neural tracking

Next to acoustic neural tracking, we also investigated the effect of speech rate on linguistic

neural tracking (see section 2.4.3 for more details). Figure 5.A (left panel) shows how

accurately the linguistic model can predict the speech signal over subjects per speech rate per

channel. The channels in the cluster which drives the topography from 0 are annotated with

grey markers. The higher the speech rate, the fewer channels have significant neural tracking.

To quantify this, we averaged the prediction accuracy over a central channel selection based

on Gillis et al. (2021b) (channels are highlighted in red in the inset of figure 5.B), resulting

in one neural tracking value per speech rate per subject. As shown in figure 5.A (right),

neural tracking significantly drops monotonically with increasing speech rate (p=0.008,

b=-4.59x10^{-5}, CI(95%):±3.31x10^{-5}, LME, table 4). Interestingly, this is the opposite

trend from the acoustic model in section 3.2.1. Finally, adding speech understanding as

a predictor does not improve the linguistic model (AIC$_{SR}$ = -1175, AIC$_{SR + understanding}$ =

-1151).

To thoroughly investigate the neural responses to the linguistic features, we examined the

TRFs of the central channel selection. Figure 5.B visualizes the averaged normalized TRF

in the central channel selection for the different linguistic features per speech rate. The grey

zone is where, based on Gillis et al. (2021b), we would expect a neural response. Significant

responses can be found in the lower speech rates when speech can still be understood for

all features. In the higher speech rates, where speech understanding is worse or absent,

the linguistic neural response also disappears (Figure 5.B, horizontal bars show the TRF

parts significantly different from zero). The topographies of these responses are shown

in Figure 5.B underneath the TRFs. Interestingly, the topographies switch from central

negativity when speech is understood to frontal negativity when speech understanding is

worse or absent. To investigate whether the amplitude or latency of these peaks is related to

speech rate, we calculated the minimum value for every participant within the grey zone

(= peak value). For all linguistic features the peak amplitude shrinks significantly with

increasing speech rate as shown in Figure 6 (Phoneme surprisal: p<0.001, b=6.81x10^{-3},

CI(95%): ±2.82x10^{-3}; Cohort entropy: p=0.008, b=4.21x10^{-3}, CI(95%): ±3.07x10^{-3};

Word surprisal: p<0.001, b=6.46x10^{-3}, CI(95%): ±3.09x10^{-3}; Word Frequency: p<0.001,

b=6.44x10^{-3}, CI(95%): ±3.00x10^{-3}; LME; table 4). In other words, when speech becomes

faster and more difficult to understand, the peak amplitude of the linguistic features

decreases until it finally disappears when the speech rate is 9.0 or 12.9 syllables/sec,

or higher, and speech understanding is dropping below 90%. Similar to the analysis of the

second peak for acoustic features, we only include the latency of significant peaks. Phoneme

surprisal shows a significant increase of peak latency with increasing speech rate (p=0.015,

b=5.47x10^{-3}, CI(95%): ±4.20x10^{-3}; LME; table 4). Cohort entropy, word surprisal and

word frequency, on the other hand, reveal no significant effect of speech rate on peak latency

(Cohort entropy: p=0.18, b=$3.59\text{x}10^{-3}$, CI(95%): $\pm5.11\text{x}10^{-3}$; Word surprisal: p=0.23,

b=$-3.33\text{x}10^{-3}$, CI(95%): $\pm5.38\text{x}10^{-3}$; Word frequency: p=0.95, b=$-1.09\text{x}10^{-4}$, CI(95%):

$\pm3.06\text{x}10^{-3}$; LME; table 4).

Table 4. Linear Mixed Effect Model of prediction accuracy and amplitude and latency of the TRF peaks in function of speech rate for the linguistic model

Linguistic model		rate			rate^2		
		β	CI(95%)	p	β	CI(95%)	p
Prediction accuarcy		$-4.59\text{x}10^{-5}$	$\pm3.31\text{x}10^{-5}$	0.0081	does not improve AIC		
Phoneme surprisal	ampl	$6.81\text{x}10^{-3}$	$\pm2.82\text{x}10^{-3}$	<0.001	does not improve AIC		
	lat	$5.47\text{x}10^{-3}$	$\pm4.20\text{x}10^{-3}$	0.015	does not improve AIC		
Cohort entropy	ampl	$4.21\text{x}10^{-3}$	$\pm3.07\text{x}10^{-3}$	0.008	does not improve AIC		
	lat	$3.59\text{x}10^{-3}$	$\pm5.11\text{x}10^{-3}$	NS	does not improve AIC		
Word surprisal	ampl	$6.46\text{x}10^{-3}$	$\pm3.09\text{x}10^{-3}$	<0.001	does not improve AIC		
	lat	$-3.33\text{x}10^{-3}$	$\pm5.38\text{x}10^{-3}$	NS	does not improve AIC		
Word frequency	ampl	$6.44\text{x}10^{-3}$	$\pm3.00\text{x}10^{-3}$	<0.001	does not improve AIC		
	lat	$-1.09\text{x}10^{-4}$	$\pm3.06\text{x}10^{-3}$	NS	does not improve AIC		

Every line represents a different model. NS = not significant, ampl = TRF amplitude, lat = TRF latency

4 DISCUSSION

448 We aimed to investigate whether neural speech processing can capture the effect of gradually

449 decreasing speech understanding by manipulating the speech rate. With increasing speech

450 rate, we found that neural tracking of the acoustic features increased, while neural tracking

451 of the linguistic features decreased.

4.1 Effect of speech rate on acoustic neural processing of speech

We hypothesized that neural tracking of acoustic features would increase with increasing

speech rate because more acoustic information is present. We found an increase of acoustic

neural tracking with increasing speech rate and thus decreasing speech understanding,

confirming our hypothesis. When speech becomes faster, the model is better at predicting
acoustic speech features.

This increase of acoustic neural tracking with increasing speech rate, and thus decreasing
speech understanding, seems discrepant with previous research trying to link acoustic
neural tracking to speech understanding using, for example, speech-in-noise paradigms
(Vanthornhout et al., 2018; Verschueren et al., 2020; Ding and Simon, 2013; Iotzov and
Parra, 2019; Etard and Reichenbach, 2019). The experimental paradigm could explain this
discrepancy. Previous studies used, for example, noise to manipulate speech understanding.
In those cases, decreased neural tracking was accompanied by a decrease in speech
understanding and an acoustically degraded speech signal. Because speech understanding
and signal-to-noise ratio are highly correlated, it is challenging to unravel to what extent
the decreased neural tracking is driven by decreased speech understanding or the signal-
to-noise ratio used to vary speech understanding. In this study, we manipulated speech
understanding by speeding up the speech signal and preserving its signal-to-noise ratio, in
contrast to the speech in noise studies. We hypothesize that the brain mainly responds to
acoustic boundaries, i.e. onsets of sounds, which are more prominent in the faster speech
presented in this study, explaining the increasing tendency. In addition, because the speech
is sped up, the duration of the silences in between words or sentences inherently decreases,
which increases the amount of speech data allowing the model to improve its estimate of
the TRF and obtain higher prediction accuracies. However, this increase of acoustic neural
tracking and speech rate is not linear: it saturates, and decreases again at very high speech
rates. This may be due to the stimulus characteristics. When increasing the speech rate, the
spectrogram and acoustic edges contain more and more peaks. Possibly, at very high speech
rates, these peaks occur so fast after each other making it difficult for the brain to perceive
them still (see Figure 1), similar to speech in noise studies where the amount of noise can
mask acoustic boundaries. Therefore, it is difficult to attribute this decrease in acoustic
neural tracking at very high speech rates (or low signal-to-noise ratios): a decrease in speech
understanding or a decrease in neural detection of acoustic boundaries, or a combination

of both? A different hypothesis is related to the motor cortex. When participants listen to
the speech, they tend to mimic the speech in their brain, activating neural activity in motor
areas (Casas et al., 2021). However, most speakers cannot produce speech as fast as 16.2
syllables/sec. Hence, the corresponding mouth movements are unnatural, which implies
that the listener cannot mimic the speech in their brain anymore, decreasing the related
responses in the motor areas and thus brain responses to the acoustic speech features in
general.

To better understand the observed quadratic tendency of acoustic neural tracking with
increasing speech rate, we investigated the TRFs of the speech features separately. Two
significant peaks with opposite behavior could be observed for both acoustic features. The
first peak is the largest. With increasing speech rate the amplitude of peak 1 increases,
saturates and decreases again at very high speech rates. This is similar to the previously
discussed neural acoustic tracking results. On the other hand, the second peak amplitude
decreases with increasing speech rate. This discrepancy is intriguing as it suggests that
both peaks have different underlying brain processes as confirmed by literature (Picton,
2011; Brodbeck and Simon, 2020). Peak 1 occurs relatively fast, around 50 ms, and is
probably mainly related to the acoustics of the incoming speech and thus benefits from an
increased speech rate. Peak 2, on the other hand, occurs somewhat later, around 150 ms, and
could, in addition to the acoustics, be influenced by top-down processing related to speech
understanding and attention (Ding and Simon, 2012; Vanthornhout et al., 2019). Besides the
amplitude, we also investigated the latencies. The latency of the first peak increases with
increasing speech rate. Increased latencies are often observed in more complex conditions
with a higher task demand, like for example lower stimulus intensity, vocoded speech
or speech in noise (Mirkovic et al., 2019; Verschueren et al., 2021; Kraus et al., 2020).
The latency of the neural responses can also be related to neural processing efficiency
(Bidelman et al., 2019; Gillis et al., 2021a). In more detail, a larger latency indicates
that more processing time is required to process the same speech characteristics, showing
reduced neural processing efficiency. More words and phonemes need to be processed as

the speech rate increases, resulting in a more challenging condition to process the incoming
speech.

4.2   Effect of speech rate on linguistic neural processing of speech

When speech becomes faster, speech understanding drops. Interestingly, this same decrease
can be observed in linguistic neural tracking, in contrast to acoustic neural tracking (section
4.1). It is interesting to note that the pattern between speech rate and acoustic and linguistic
neural tracking differs. Linguistic neural tracking seems linearly related to speech rate,
while acoustic neural tracking shows non-linearity: it increases, stagnates and eventually
slightly decreases for the highest speech rates. To the best of our knowledge, this is the
first study that evaluates linguistic neural tracking when manipulating the level of speech
understanding as a gradual effect. The studies of Brodbeck et al. (2018) and Broderick et al.
(2018) using a two-talker paradigm are most comparable. They compared two conditions,
i.e., intelligible and attended speech versus unintelligible and ignored speech, but not the
spectrum in between. Nevertheless, their findings converge with our results and support our
hypothesis of linguistic neural tracking as a neural marker of speech understanding. When
the speech is not understood or ignored, the brain does not track the linguistic aspects of
the speech, while for intelligible speech linguistic tracking is present.

To better understand the observed decrease of linguistic neural tracking with increasing
speech rate, we investigated the TRFs of the speech representations separately. We observed
a characteristic negative peak for each linguistic representation as observed in previous
literature (e.g. Brodbeck et al., 2018; Gillis et al., 2021b; Weissbart et al., 2019). Although
the responses are very small, they are significantly different from zero and the TRF patterns
converge with the patterns observed in previous literature. For the phoneme-related features,
phoneme surprisal and cohort entropy, this peak occurs around 250 ms. For the word-related
features, word surprisal and word frequency, this peak occurs somewhat later, around 350
ms. The difference in timescale between both feature groups could be linked to the different

speech processing stages (phonemes versus words) they represent (Van Canneyt et al., 2021). Regarding the topographies of these peaks, the understandable speech conditions are associated with a typical topography, similar to the classical N400 responses characterized by central negative channels. As speech becomes less understandable, i.e., the speech rate increases, the associated topography disappears.

For all speech features, the amplitude of this negative peak decreases with increasing speech rate until it disappears at speech rates as high as 9.0 tot 12.9 syllables/sec. Gillis et al. (2021b) already showed that these linguistic representations have an added value above and beyond acoustic and lexical representations. However, the authors did not compare intelligible to unintelligible speech. Here, we elegantly showed that as the speech becomes less understandable but remains audible and acoustically intact (in contrast to speech in noise studies or vocoder studies), the characteristic negative peak decreases and finally disappears. Altogether, our results suggest that these characteristic negative peaks to linguistic representations could be neural correlates of speech understanding.

4.3 Conclusion

Using a speech rate paradigm, we map how the level of speech understanding affects acoustic and linguistic neural speech processing. When speech rate increases, acoustic neural tracking increases, although speech understanding drops. However, the amplitude of the later acoustic neural response decreases with increasing speech rate, suggesting influence of top-down processing related to speech understanding and attention. In contrast, linguistic neural tracking decreases with increasing speech rate and even disappears when speech is no longer understood. Altogether, this suggests that linguistic neural tracking could possibly be a more direct predictor of speech understanding compared to acoustic neural tracking.

Figure 3. Effect of speech rate on acoustic tracking Panel A: visualization of the average prediction accuracy across participants for each speech rate. The annotated grey channels indicate the cluster which drives the significant difference from 0. How acoustic tracking, averaged across frontocentral channels, changes according to the speech rate is shown on the right. Panel B: Normalized TRFs of the spectrogram and acoustic edges. The bold horizontal lines indicate where the TRFs are significantly different from 0 (the same color as the TRF of the considered speech rate). The topographies below show the associated peak topographies in the TRF.

Figure 4. Effect of speech rate on the amplitude and latency of acoustic representation Each row shows the effect of speech rate on latency (left plot) and the amplitude (right plot) of the neural response to spectrogram (top row) and acoustic edges (bottom row) for respectively the first and second identified peak as indicated on Figure 3. The blue line shows the model's prediction for each speech rate; the shaded area indicates the confidence interval of the model's prediction. The non-significant models are shown in grey. Remark that we only include the latency of significant peaks for the latency analysis.

A) Linguistic neural tracking

B) Temporal Response Function

Figure 5. Effect of speech rate on linguistic tracking Panel A: visualization of the added value of linguistic representations across participants for each speech rate. The annotated grey channels indicate the cluster which drives the significant difference from 0. How linguistic tracking, averaged across central channels, changes according to the speech rate is shown on the right. Panel B: The associated normalized TRFs for the linguistic representations. The bold horizontal lines indicate where the TRFs are significantly different from 0 (the same color as the TRF of the considered speech rate). The topographies below indicate the associated peak topographies to the TRF in the grey shaded area. The horizontal arrow underneath the topographies indicates the increasing speech rate.

Figure 6. Effect of speech rate on the amplitude and latency of linguistic representation Each row shows the effect of speech rate on latency (left plot) and the amplitude (right plot) of the neural response to phoneme surprisal (top row), cohort entropy (second row), word surprisal (third row) and word frequency (bottom row). The blue line shows the model's prediction for each speech rate; the shaded area indicates the confidence interval of the model's prediction. The non-significant models are shown in grey. Remark that we only include the latency of significant peaks for the latency analysis.

REFERENCES

Ahissar, E., Nagarajan, S., Ahissar, M., Protopapas, A., Mahncke, H., and Merzenich, M. M. (2001). Speech comprehension is correlated with temporal response patterns recorded from auditory cortex. *Proceedings of the National Academy of Sciences of the United States of America* 98, 13367–72. doi:10.1073/pnas.201400998

Baayen, R. H., Piepenbrock, R., and Gulikers, L. (1996). The celex lexical database (cd-rom)

Bates, D., Mächler, M., Bolker, B., and Walker, S. (2015). Fitting linear mixed-effects models using lme4. *Journal of Statistical Software* 67, 1–48. doi:10.18637/jss.v067.i01

Bidelman, G. M., Price, C. N., Shen, D., Arnott, S. R., and Alain, C. (2019). Afferent-efferent connectivity between auditory brainstem and cortex accounts for poorer speech-in-noise comprehension in older adults. *Hearing research* 382, 107795

Boursma, P. and Weenink, D. (2018). Praat: doing phonetics by computer [computer program]. *version 6.0.37, retrieved 3 Februari 2018 from http://www.praat.org/*

[Dataset] Brodbeck, C. (2020). Eelbrain 0.34. `http://doi.org/10.5281/zenodo.3923991`

Brodbeck, C., Hong, L. E., and Simon, J. Z. (2018). Rapid transformation from auditory to linguistic representations of continuous speech. *Current Biology* 28, 3976–3983

Brodbeck, C. and Simon, J. Z. (2020). Continuous speech processing. *Current Opinion in Physiology* 18, 25–31. doi:10.1016/j.cophys.2020.07.014

Broderick, M. P., Anderson, A. J., Liberto, G. M. D., Crosse, M. J., and Lalor, E. C. (2018). Electrophysiological Correlates of Semantic Dissimilarity Reflect the Comprehension of Natural , Report Electrophysiological Correlates of Semantic Dissimilarity Reflect the Comprehension of Natural , Narrative Speech. *Current Biology* 28, 803–809. doi:10.1016/j.cub.2018.01.080

Casas, A. S. H., Lajnef, T., Pascarella, A., Guiraud-vinatea, H., Laaksonen, H., Bayle, D., et al. (2021). Neural oscillations track natural but not artificial fast speech: Novel

insights from speech-brain coupling using meg. *NeuroImage* 244, 118577

David, S. V., Mesgarani, N., and Shamma, S. A. (2007). Estimating sparse spectro-temporal receptive fields with natural stimuli. *Network: Computation in Neural Systems* 18, 191–212. doi:10.1080/09548980701609235

Decruy, L., Das, N., Verschueren, E., and Francart, T. (2018). The self-assessed Békesy procedure: validation of a method to measure intelligibility of connected discourse. *Trends in Hearing* 22, 1–13. doi:10.1177/2331216518802702

Ding, N. and Simon, J. Z. (2012). Emergence of neural encoding of auditory objects while listening to competing speakers. *Proceedings of the National Academy of Sciences of the United States of America* 109, 11854–9. doi:10.1073/pnas.1205381109

Ding, N. and Simon, J. Z. (2013). Adaptive Temporal Encoding Leads to a Background-Insensitive Cortical Representation of Speech. *Journal of Neuroscience* 33, 5728–5735. doi:10.1523/JNEUROSCI.5297-12.2013

Duchateau, J., Kong, Y. O., Cleuren, L., Latacz, L., Roelens, J., Samir, A., et al. (2009). Developing a reading tutor: Design and evaluation of dedicated speech recognition and synthesis modules. *Speech Communication* 51, 985–994

Elzhov, T. V., Mullen, K. M., Spiess, A.-N., and Bolker, B. (2016). *minpack.lm: R Interface to the Levenberg-Marquardt Nonlinear Least-Squares Algorithm Found in MINPACK, Plus Support for Bounds*. R package version 1.2-1

Etard, O. and Reichenbach, T. (2019). Neural speech tracking in the theta and in the delta frequency band differentially encode clarity and comprehension of speech in noise. *Journal of Neuroscience* 39, 5750–5759

Francart, T., van Wieringen, A., and Wouters, J. (2008). APEX 3: a multi-purpose test platform for auditory psychophysical experiments. *Journal of Neuroscience Methods* 172, 283–293

Gillis, M., Decruy, L., Vanthornhout, J., and Francart, T. (2021a). Hearing loss is associated with delayed neural responses to continuous speech. *bioRxiv*

Gillis, M., Vanthornhout, J., Simon, J. Z., Francart, T., and Brodbeck, C. (2021b).
Neural markers of speech comprehension: measuring EEG tracking of linguistic speech
representations, controlling the speech acoustics. *Journal of neurocience* , [Accepted for
publication]

Gwilliams, L. and Davis, M. H. (2022). Extracting language content from speech sounds:
the information theoretic approach. In *Speech Perception* (Springer). 113–139

[Dataset] Heeris, J. (2014). Gammatone filterbank toolkit 1.0. `https://github.com/`
`detly/gammatone`

Hertrich, I., Dietrich, S., Trouvain, J., Moos, A., and Ackermann, H. (2012). Magnetic
brain activity phase-locked to the envelope, the syllable onsets, and the fundamental
frequency of a perceived speech signal. *Psychophysiology* 49, 322–334. doi:10.1111/j.
1469-8986.2011.01314.x

Iotzov, I. and Parra, L. (2019). EEG can predict speech intelligibility To. *J. Neural Eng.* 16,
036008 (11p). doi:10.1088/1741-2552/ab07fe

Keuleers, E., Brysbaert, M., and New, B. (2010). Subtlex-nl: A new measure for dutch
word frequency based on film subtitles. *Behavior research methods* 42, 643–650

Koskinen, M., Kurimo, M., Gross, J., Hyv, A., and Hari, R. (2020). NeuroImage Brain
activity re fl ects the predictability of word sequences in listened continuous speech.
NeuroImage 219, 116936. doi:10.1016/j.neuroimage.2020.116936

Kraus, F., Tune, S., Ruhe, A., Obleser, J., and Woestmann, M. (2020). Unilateral acoustic
degradation delays attentional separation of competing speech. *bioRxiv*

Lesenfants, D., Vanthornhout, J., Verschueren, E., Decruy, L., and Francart, T. (2019).
Predicting individual speech intelligibility from the neural tracking of acoustic- and
phonetic-level speech representations. *Hearing Research* 380, 1–9. doi:10.1016/j.heares.
2019.05.006

MacPherson, A. and Akeroyd, M. A. (2014). A method for measuring the intelligibility of
uninterrupted, continuous speech. *The Journal of the Acoustical Society of America* 135,
1027–1030

Maris, E. and Oostenveld, R. (2007). Nonparametric statistical testing of eeg-and meg-data.
Journal of neuroscience methods 164, 177–190

Mirkovic, B., Debener, S., Schmidt, J., Jaeger, M., and Neher, T. (2019). Effects of
directional sound processing and listener's motivation on eeg responses to continuous
noisy speech: Do normal-hearing and aided hearing-impaired listeners differ? *Hearing*
Research 377, 260–270

Müller, J. A., Wendt, D., Kollmeier, B., Debener, S., Brand, T., and Hunter, C. R. (2019).
Effect of Speech Rate on Neural Tracking of Speech. *Frontiers in psychology* 10, 1–15.
doi:10.3389/fpsyg.2019.00449

Nourski, K. V., Reale, R. A., Oya, H., Kawasaki, H., Kovach, C. K., Chen, H., et al. (2009).
Temporal Envelope of Time-Compressed Speech Represented in the Human Auditory
Cortex. *The Journal of Neuroscience* 29, 15564–15574. doi:10.1523/JNEUROSCI.
3065-09.2009

Picton, T. W. (2011). *Human Auditory Evoked Potentials* (San Diego: Plural Publishing
inc.)

Sanders, L. D. and Neville, H. J. (2003). An erp study of continuous speech processing: I.
segmentation, semantics, and syntax in native speakers. *Cognitive Brain Research* 15,
228–240

Shannon, R. V., Zeng, F. G., Kamath, V., Wygonski, J., and Ekelid, M. (1995). Speech
recognition with primarily temporal cues. *Science* 270, 303–304

Slaney, M. (1998). Auditory toolbox. *Interval Research Corporation, Tech. Rep* 10

Somers, B., Francart, T., and Bertrand, A. (2018). A generic EEG artifact removal
algorithm based on the multi-channel Wiener filter. *Journal of neural engineering* 15.
doi:10.1088/1741-2552/aaac92

Van Canneyt, J., Gillis, M., Vanthornhout, J., and Francart, T. (2021). Neural tracking as an
objective measure of auditory perception and speech intelligibility. *bioRxiv*

Vanthornhout, J., Decruy, L., and Francart, T. (2019). Effect of task and attention on neural
tracking of speech. *BioRxiv* , doi: http://dx.doi.org/10.1101/568204doi:10.3389/fpsyg.

2019.00449

Vanthornhout, J., Decruy, L., Wouters, J., Simon, J. Z., and Francart, T. (2018). Speech

intelligibility predicted from neural entrainment of the speech envelope. *JARO* 19,

181–191. doi:10.1007/s10162-018-0654-z

Verschueren, E., Vanthornhout, J., and Francart, T. (2020). The effect of stimulus choice

on an EEG-based objective measure of speech intelligibility. *Ear & Hearing* , Publish

Ahead of preprintdoi:https://doi.org/10.1101/421727

Verschueren, E., Vanthornhout, J., and Francart, T. (2021). The effect of stimulus intensity

on neural envelope tracking. *Hearing Research* 403, 108175

Weissbart, H., Kandylaki, K. D., and Reichenbach, T. (2019). Cortical Tracking of

Surprisal during Continuous Speech Comprehension. *Journal of cognitive neuroscience*

32, 155–166. doi:10.1162/jocn_a_01467