CRISPR-Detector: Fast and Accurate Detection, Visualization, and Annotation

of Genome-Wide Mutations Induced by Gene Editing Events

Authors

Lei Huang [a,1], Dan Wang [d,b,1,*], Haodong Chen [c], Jinnan Hu [c], Xuechen Dai [b], Chuan

Liu [b], Anduo Li [b], Xuechun Shen [f], Chen Qi [a], Haixi Sun [b], Dengwei Zhang [b], Tong

Chen [e,*], Yuan Jiang [b,*]

Affiliations

a *College of Life Sciences, University of Chinese Academy of Sciences, Beijing*

100049, China.

b *BGI-Shenzhen, Shenzhen 518083, China.*

c *Sentieon Inc, San Jose, CA 94042, USA.*

d *BNU-HKBU United International College, Zhuhai 519087, China.*

e *National Resource Center for Chinese Materia Medica, China Academy of Chinese*

Medical Sciences, Beijing 100700, China.

f *School of Biology and Biological Engineering, South China University of*

Technology, Guangzhou 510006, China.

* Corresponding authors.

E-mail addresses: yjiang@completegenomics.com (Y. Jiang), chent@nrc.ac.cn (T. Chen),

danwang@uic.edu.cn (D. Wang).

[1] These authors contributed equally to this work.

Abstract

The leading edge of genome editing, driven by CRISPR/Cas technology, is

revolutionizing biotechnologies. In pace with the burst of novel genome editing

methods, bioinformatic tools to monitor the on/off-target events need to be more

evolved as well. Existing tools suffer from limitations in speed and scalability, and

they especially struggle with whole genome sequencing (WGS) data analysis which

has the potential to detect off-target mutations at a genome-wide level via an unbiased

manner. Here, we introduce our CRISPR-detector tool, which is a web-hosted or

locally deployable pipeline with five key innovations: 1) optimized scalability

allowing for WGS data analysis beyond BED (Browser Extensible Data) file-defined

regions; 2) improved accuracy benefiting from haplotype-based variant calling to

handle sequencing errors; 3) treated and control sample co-analysis to remove

background variants existing prior to genome editing; 4) integrated structural

variation (SV) calling; and 5) functional and clinical annotation of editing-induced

mutations.

Keywords: Genome editing; On/off-target; Genetic background removal; Structural

variation

Introduction

The clustered regularly interspaced short palindromic repeats (CRISPR)-based

technologies, which are inspired by adaptive immune systems in microorganisms,

have revolutionized the field of genome engineering. The RNA-guided CRISPR-

associated (Cas) nuclease is used for genome editing by simply specifying a ~20-nt

targeting sequence within its guide RNA (Jinek et al., 2012). Since the first report of

CRISPR/Cas9 editing technology in 2012, various novel CRISPR-based genome

editing tools have been introduced by different groups (Cong et al., 2013; Zetsche et

al., 2015; Abudayyeh et al., 2016; Liu et al., 2019; Pausch et al., 2020). Genome

editing methods have progressively become more flexible and precise, including

innovations such as base editors, which enable the direct conversion of one nucleotide

to another without producing DSBs in the target sequence, and prime editing which

can create targeted indels and introduce all 12 types of point mutations (Komor et al.,

2016; Gaudelli et al 2017; Kim et al., 2017; Anzalone et al 2019). This technology

creates exciting new opportunities for a plethora of life science applications including

therapeutic treatment, drug discovery, biofuel production, agriculture, and more. Early

clinical trials demonstrated CRISPR's general safety and utility, and many more trials

are underway (Lu et al., 2020; Frangoul et al., 2021; Gillmore et al., 2021). Despite

the many important applications of these editing tools, they each have their own

limitations. One common concern of the CRISPR/Cas technology is that editing

events may occur at undesired locations, i.e., off-target events. As a result, the

increased adoption of CRISPR-based treatment makes precision analysis—accurately

detecting on- and off- target events—a top priority for regulators including the FDA.

Accordingly, the FDA published guidance related to genome editing products in

March 2022 (https://www.fda.gov/regulatory-information/search-fda-guidance-

documents/human-gene-therapy-products-incorporating-human-genome-editing), in

which they raised concerns multiple times about detecting the type and frequency of

gene editing events. Therefore, the bioinformatic tools to monitor on/off-target events

need to become more accurate and capable of detecting true editing-induced

mutations—mutations introduced during gene editing as opposed to germline or

previously existing somatic variants.

Targeted amplicon sequencing has become the gold standard for the validation of

genome editing experiments (Akcakaya et al., 2018). Sequencing of amplicon focuses

on specific genomic areas at high depth, making it suitable to detect low allele

frequency (AF) mutations. Potential off-target sites can be predicted using tools such

as Cas-OFFinder to search the on-target DNA sequences against the whole genome

while allowing mismatches (preferred value: 1-5) and gaps (preferred value: 0-2) (Bae

et al., 2014). Primers are then designed to flank each on/off-target cut-site and pooled

for multiplex amplification assays. Genomic DNA from each edited sample is

transformed into libraries and enriched via polymerase chain reaction (PCR) for target

enrichment. Amplicons are then purified and sequenced using NGS platforms. NGS

technologies offer ultra-deep sequencing of amplicons ranging from 100 to 500 bp.

Along with the development of targeted amplicon sequencing technologies, tools

to monitor on/off-target events have been developed. Examples include CRISPR

genome analyzer (CRISPR-GA) (Güell et al., 2014), AGEseq (Xue and Tsai, 2015),

ampliconDIVider (Varshney et al., 2015), Cas-Analyzer (Park et al., 2017), ampliCan

(Labun et al., 2019), and CRISPResso1/2 (Pinello et al., 2016; Clement et al., 2019).

However, there are four main limitations to existing tools. The first involves speed

and scalability; most tools are designed to consider single or only a few amplicons for

analysis. However, with the increasing need to comprehensively cover all potential

off-target sites, large panel and even WGS analysis serve as good options. Second,

tools including CRISPR-GA, AGEseq, ampliconDIVider, Cas-Analyzer, and

CRISPResso1/2 do not support the co-analysis of paired treatment/control sequencing

data, and thus previously existing single nucleotide polymorphisms (SNPs) and indels

could be interpreted as CRISPR/Cas-induced mutations and lead to the incorrect

quantification of mutation events. Third, besides SNPs and indels, structural variation

is generally defined as an alteration within a region of DNA approximately 1 kb to 3

Mb in size (the operational range of structural variants has widened to include

events > 50 bp) including deletions, duplications, copy-number variants,

insertions, inversions, and translocations, which is ignored by current analysis. The

fourth drawback is that most existing pipelines do not estimate the functional or

clinical consequences resulting from editing-induced mutations. This annotation is

quite important for researchers whose genome editing projects are for therapeutic

purposes. To overcome these limitations, we herein propose a one-stop CRISPR-

detector platform.

Results

Design of CRISPR-detector

CRISPR-detector is designed to be able to process large datasets such as WGS data and output accuracy results. The pipeline accepts individual original FASTQ sequencing files from respective CRISPR/Cas-treatment and control experiments. Each input FASTQ file includes sequencing data from one or multiple amplicons, e.g., one on-target and its putative off-target amplicons. Then pipeline processes data in three procedures: Pre-processing step to align and sort reads; Variants Identification step to call and filter SNPs, indels, and SVs that could be resulted from editing events; and Output step to annotate and visualize results (Fig. 1A).

During its Pre-processing and variant identification steps, CRISPR-detector chooses to utilize Sentieon high performance computation modules to reach higher speed which is necessary for WGS analysis (Fig. 1B). Sentieon's modules are 3-20x times faster than corresponding opensource tools, and have better scalability for high threads computation environment. The Sentieon acceleration comes from a complete rewrite of the mathematical models of the open-source tools, using only C and C++ highly efficient languages, and better software engineering and resource management system to fully utilize CPU and memory resources.

The output of the web-hosted version of CRISPR-detector includes comprehensive analysis, intuitive visualization, and locus comparison. Specifically, CRISPR-detector primarily outputs: i) a summary webpage comparing and visualizing editing outcomes of the input amplicons; ii) detailed information on editing outcomes including frequency of SNPs and indels and a histogram of the indel sizes across the reference amplicon in the quantification window; iii) annotation of editing-induced mutations showing whether encoded protein sequences will be changed with filter-based annotation of mutations of clinical significance sourced from the ClinVar

database (Landrum et al., 2018), including pathogenic mutations and those related to

drug response, histocompatibility, and more.

In addition to the web-hosted version, a locally deployable CRISPR-detector

pipeline focusing on WGS analysis and SV calling was developed. The pipeline calls

not only regular SVs caused by the editing process but also viral vector insertion from

virus-mediated gene editing. The whole genome analysis capability provided by the

locally deployable version is unique and not available in any other gene editing

analysis pipelines.

Performance Benchmarks

1.SNP/Indel Identification from Simulated Amplicon Datasets

The accurate detection of SNPs and indels is one of the key features of a gene

editing analysis pipeline. To benchmark the accuracy of CRISPR-detector, we

generated simulated testing reads representing actual sequencing data and compared

the accuracy with three other popular pipelines including Cas-Analyzer, AGEseq, and

CRISPResso2. We introduced SNPs (1-3 per read) and indels (5-50 bp length) into

the simulated 150-bp paired-end reads at 50% frequency together with errors

introduced from the MiSeq default profile provided by the ART simulation tool

(Huang et al., 2012). The average running time was calculated from 3 repeated runs.

The speed of Cas-Analyzer and AGEseq are not shown as they were tested on

different computation platforms.

Compared to CRISPResso2, CRISPR-detector showed seven times faster

processing speed, and the reported mutation rate was closer to the expected value of 0%

for the control dataset and 50% for all other datasets (Fig. 2A). The faster speed of

CRISPR-detector benefits from utilizing Sentieon high performance computation

modules, such as alignment, sort, and variant calling. It should be noted that CRISPR-

detector's variant calling pipeline is based on haplotype assembly, which eliminates

sequencing errors more easily compared with simple pileup-based read statistics.

We then performed more detailed variant detection testing to evaluate CRISPR-

detector's performance on indels at different frequencies and lengths. We designed a

5-bp indel in a single simulated amplicon dataset at 5 different frequencies starting

from 0.01%. The testing dataset was processed by CRISPR-detector and

CRISPResso2. CRISPR-detector reported nearly the exact expected frequency value,

whereas CRISPResso2 included many more reads with sequencing errors incorrectly

reported as mutated reads (Fig. 2B). TNscope (Freed et al., 2018), the variant calling

module of CRISPR-detector performs well on 0.1% AF variants, because it utilizes a

haplotype assembly method to filter out sequencing error, and this strategy makes it

possible to filter out sequencing errors and identify very low AF variants as low as

0.1%.

Next, we simulated additional datasets to test the limits of CRISPR-detector in

detecting indels of different lengths. Based on the general perception of the length

limitations caused by short read sequencing, CRISPR-detector's indel detection length

is set as 50 bp for insertion and 71 bp for deletion. To demonstrate this performance,

we simulated 50 amplicon datasets with insertions ranging from 1-50 bp, and 72

amplicons with deletions ranging from 1-72 bp, each at 50% frequency. The

frequencies reported by CRISPR-detector across 1-50 bp insertions and 1-71 bp

deletions aligned very close to the expected value. In comparison, CRISPResso2's

reported value was higher than expected, and it failed to detect deletions larger than

50 bp (Fig. S1). For insertions and deletions longer than 50 bp, CRISPR-detector will

identify them through structural variation analysis modules.

CRISPR-detector can perform co-analysis with control sample data as input to

address existing germline mutations and possible somatic or hematopoiesis-related

mutations that were not introduced by a gene editing event (García-Nieto et al., 2019).

In this simulated co-analysis testing dataset, some of the variants were inserted in both

treatment and control reads to benchmark the pipeline's ability to detect intrinsic "true

positive" mutations (1-bp insertion at position 105 bp) in a noisy background with 7%

sequencing error, the same setting used for CRISPResso2. For all read types except

the 50-bp insertion, CRISPR-detector successfully identified true editing events

without false positives from variants existing in control samples (Table 1).

CRISPResso2 also offers batch mode to output and visualize variants at the same

location from different samples. While this allows the convenience of comparing

more than 2 samples, the ability to directly filter germline and other existing variants

from control samples is missing. In conclusion, CRISPR-detector significantly

increases users' efficiency in recognizing and confirming target variants.

2.Scalability on Pooled Amplicons

In a few years, the scope of NGS-based on/off-target editing detection has

expanded from only a few amplicons to hundreds of amplicons, to the coverage of all

potential off-target sites, and even to WGS to ensure that every portion of the genome

is screened. From a recent review, current mainstream in silico off-target prediction

algorithms reach 95% sensitivity if the top 200 potential off-target sites are considered

(Bao et al., 2021). This finding indicates a requirement for analysis tools to consider

speed and scalability during development. To deal with this need, CRISPResso2

provides two specific pipelines, CRISPRessoPooled and CRISPRessoWGS, for these

two input types. In comparison, CRISPR-detector's optimized high-performance

modules can handle small and large datasets from one single pipeline to provide

uncompromised accuracy and scalability.

For benchmarking, we generated 200 amplicons in the format of 150 bp paired-

end reads in which a large panel of SNPs, indels, and sequencing errors were

introduced, similar to our single amplicon benchmark. Accuracy and speed

performance are no different from the single amplicon test, and CRISPR-detector

consistently outperforms CRISPResso2 (Fig. 2C and 2D). It should be noted that

computation speed is not a bottleneck for small data. However, for larger datasets

such as WGS, alignment and variant calling are two critical steps affecting pipeline

speed, and CRISPR-detector utilizes and benefits from Sentieon's high-performance

alignment and sort modules.

3. Whole Genome Sequencing Performance

The main difference between WGS and amplicon datasets are the regions of

analysis (~3 GB vs < 1 KB) and the sequencing depth (< 100x vs > 10,000x). Whole

genome screening identifies more false positives, whereas insufficient sequencing

depth makes false negatives unavoidable. To evaluate the accuracy of CRISPR-

detector on a WGS analysis, we inserted simulated SNPs and indels into one

chromosome sequence using BAMSurgeon (Ewing et al., 2015). Specifically,

approximately 990 variants with 1-100% AFs were inserted into a 100x WGS dataset,

and approximately 967 variants with 3.3-100% AFs were inserted into a 30x WGS

dataset. To ensure at least 3 reads to support a reported variant, we only reported

variants with AFs above 5% for 100x WGS and AFs above 15% for 30x WGS.

Inserted reads and original reads are processed in co-analysis mode.

We found that co-analysis results were always better than only analyzing edited

samples (Table 2A). The accuracy of SNPs is lower than that of amplicons, but

acceptable, especially for the co-analysis of SNPs with AF > 15%. The accuracy of

indels is significantly lower than that of amplicons, which is partially due to the fact

that reads with indels are more difficult to map to the correct location in the full

genome. Thus the reported indel frequency is lower than the correct number and may

be filtered out by AF cutoff.

To validate this performance, a pair of 30x WGS samples ("Mutant" and

"Rescued") from a previous study was used (Wu et al., 2015). "Mutant" reads are

from control cells having a pre-existing homozygous 1 bp disease causing deletion

relative to the reference genome in the coding sequence of the mutant gene *Crygc*,

"Rescued" means the edited clone rescued by CRISPR-Cas9-introduced 1-bp

insertions 6-7 bp from the deletion. CRISPR-detector completed the "Mutant" group

WGS dataset in 3 repeated runs using a consistent and reasonable 4h19m running time

with 15 threads allocated (in total 65 core-hours), and it successfully detected the

homozygous 1 bp deletion (chr1 65118239) as expected. Similarly, the pipeline

completed the "Rescued" group sample in 5h36m and detected 2 insertions 6-7 bp

from the deletion (chr1 65118232; chr1 65118233). CRISPRessoWGS was not

included in this comparison, because in order to run WGS samples it requires a BED

file, which is not defined by the original study.

Structural Variation Identification

Gene editing introduces more than just short variants. For example, in viral-

mediated gene transfer events, it is important to know the exact genome insertion

location of the viral vectors to evaluate off-target event occurrence and functional

consequences. Therefore, structural variations should be considered in the analysis

pipeline design. A major purpose for conducting WGS on edited samples is to better

identify off-target structural variants. To benchmark the accuracy, we designed two

datasets for both general SV calling and vector insertion events.

We utilized the well-established PrecisionFDA dataset from HG002, in which a

total of 12,745 isolated, sequence-resolved insertion (7,281) and deletion (5,464) calls

longer than 50 bp are available, to serve as a truth set (Zook et al., 2020). SVs were

called from the CRISPR-detector pipeline and compared with the NIST truth set using

Truvari (https://github.com/spiralgenetics/truvari). To better evaluate the performance

of CRISPR-detector and to better understand the limitations of short read-based SV

calling compared to co-barcoded reads and long reads, we also compared the result

with some pipelines from a recently published study that used the same testing dataset

(Guo et al., 2021). Because insertions are more challenging and Truvari can only

recognize the exact match to the truth set, which significantly underestimates true

positives, we only showed the performance on deletions (Table 2B).

Deletions were grouped into two categories based on their length. In the 50 bp – 1

kb group where the majority of deletions exist, CRISPR-detector achieves 26.87%

recall and 80.76% precision and slightly outperforms Smoove

(https://brentp.github.io/post/smoove) on 100x co-barcoded reads. Long Ranger

(https://github.com/10Xgenomics/longranger) returned similar accuracy to CRISPR-

detector on 100x co-barcoded reads, and Sniffles returns better recall than any other

callers (Sedlazeck et al., 2018). For longer deletions (>1k), CRISPR-detector's

accuracy score is slightly lower than co-barcoded or long-read callers. It is widely

accepted that long read sequencing and co-barcoded read sequencing technologies are

more capable of identifying large deletions, especially for improving recall, but the

CRISPR-detector pipeline on short reads data still generates useful results. For the

most accurate SV detection, long read whole genome sequencing is preferentially

recommended, and CRISPR-detector will aim to adapt to these long read types in a

future release.

Next, we simulated 150 bp paired-end reads with mimic ~4.7k AAV vector

insertion in a 30x WGS dataset to see if CRISPR-detector reports the insertion

location. Because the inserted sequences are known, we modified the analysis pipeline

to overcome the incompetence of insertion detection from the general SV calling

pipeline. The AAV vector sequence was added into the human reference genome file

as a dummy chromosome. Reads thus can be mapped to both human and vector

sequences, and a translocation event can be reported to show the insertion location.

We also introduced AAV partial sequences to better mimic partial insertion and

simulated five scenarios, including insertion, reverse insertion, non-AAV sequence

insertion, partial swap, and insertion with foreign sequences. In all 5 scenarios,

CRISPR-detector returned the correct insertion location and always captured at least

one of the breakpoints (Fig. S2), giving users the ability to take a closer look at the

reported region and confirm the exact insertion format.

Assessing Real World Clinical Data

In addition to simulated datasets, we utilized 3 published clinical datasets to evaluate the accuracy of CRISPR-detector and compared our analysis either with the original results published with the datasets or with CRISPResso2. The 3 datasets included are 1) rhAMP-seq from IDT; 2) ABE8e-NRCH (Newby et al., 2021); and 3) SPACE (Grünewald et al., 2020).

The first dataset benchmarked was the rhAMP-seq sample data provided on the IDT website. For the true editing positions provided by IDT (detected by GATK4 with a tuned parameter) (Poplin et al., 2018), CRISPR-detector achieved 100% accuracy with no false positive or false negative reports (Table S1).

CRISPR-detector is also suitable for assessing base editing outcomes. We analyzed 479 off-target sites from the third primer pool identified by Cas-OFFinder and CIRCLE-seq (Bae et al., 2014; Tsai et al., 2017) that were amplified from genomic DNA from CD34+ SCD cells edited by ABE8e-NRCH or from unedited control SCD donor cells using rhAMP-Seq (IDT). Following the original study's methods, we calculated the statistical significance of ABE8e-NRCH mRNA off-target editing compared with control samples, by applying a Chi-square test. The 2x2 contingency table was constructed based on the number of edited reads and unedited reads, in treated and control groups. FDR was calculated using the Benjamini/Hochberg method. We applied the same cutoff thresholds as the original study: (1) FDR < 0.05 and (2) difference in editing frequency between treated and control > 0.5%.

As a result, among the 479 sites, 14 sites in the replicate 1 sample and 29 sites in the replicate 2 sample were identified as containing A•T-to-G•C mutations of significance. In replicate 1 sample, CRISPR-detector and CRISPResso2 agreed on all 479 sites. In the replicate 2 sample, the two pipelines showed discordance at only 3 sites (Fig. S3). Specifically, site "91469BDFFDAD44DZ0Z (off-target site 54)" was called positive only by CRISPResso2. The difference in editing frequency for this site

between the treated and the control was 0.8%. Two sites were called positive only by

CRISPR-detector. The differences in editing frequency between treated and control at

these sites were near the 0.5% cut-off value. While the truth is not available to

determine which calls are correct, current information indicates that these calls are on

the edge between positive and negative (Table S2).

The dual-deaminase base editor SPACE (Synchronous Programmable Adenine

and Cytosine Editor) can concurrently introduce A•T-to-G•C and C•G-to-T•A

substitutions (Grünewald et al., 2020). CRISPR-detector's performance was compared

with CRISPResso2 for 28 SPACE target sites with nCas9 treatment as control. Each

potential A•T-to-G•C and C•G-to-T•A position evaluated was categorized into 5

levels based on reported frequency: < 1%, 1%-10%, 10%-30%, 30%-60%, > 60%,

and the highest frequency within the 20-bp evaluation window was chosen to

represent the overall editing level for this protospacer. All 28 nCas9 samples showed

no targeted substitution, but every SPACE treated sample returned multiple

substitutions within the window.

CRISPR-detector and CRISPResso2 reported generally concordant editing levels

for all 28 SPACE-treated sites (Fig. S4); only 10 of 560 (1.8%) evaluated positions

showed discordant levels (Table S3). At these discordant positions, CRISPR-detector

typically reported slightly lower frequencies than CRISPResso2, which was the same

trend seen in our observations using simulated datasets.

In conclusion, CRISPR-detector showed identical accuracy as the IDT original

analysis pipeline for the rhAMP-seq dataset and the same accuracy as CRISPResso2

on the ABE8e-NRCH and SPACE datasets.

Functional Annotation of Editing Induced Mutations

ClinVar database is one of the largest public databases on human genomic

variants and interpretations of their relationships to diseases and other conditions

maintained by NCBI. Our pathogenicity annotations utilize this database but the

outcome may differ from true pathogenicity. We examined the annotation results of

the processed SPACE and ABE8e-NRCH datasets and found 1 variant returning

annotation from the ClinVar database. From the SPACE datasets, a stopgain C•G-to-

T•A mutation on *FANCF* site 1 was annotated to be pathogenic by ClinVar, and

associated with Fanconi anemia. Our tool provides a convenient way to display

ClinVar annotation if an off-target mutation exists in the ClinVar database.

We have added a clear statement in our user agreement that "The pathogenicity

annotations are based on the ClinVar database." The annotations are not intended for

direct diagnostic use or medical decision-making purposes.

Discussion

Comparison with Other Analysis Tools

In pace with the development of genome engineering, analysis toolkits to assess

the quality of genome editing have been developed and made available to the

community. Early published tools such as CRISPR-GA (2014), ampliconDIVider

(2015), and Cas-Analyzer (2017) only support single amplicon sequencing data,

whereas AGEseq (2015) and CRISPResso2 (2019) support pooled amplicon

sequencing data but do not support unbiased analysis of WGS data or SV calling.

Several widely-used tools for analyzing genome editing NGS data were compared

(Table 3). Clearly, CRISPR-detector is more comprehensive with functions that other

listed toolkits are not capable of, including genetic background removal and mutation

annotation, which significantly improve accuracy and show possible functional and

clinical consequences.

Other Potentially Useful Computation Modules

We considered whether read trimming and filtering steps should be included in

the pipeline and decided they were unnecessary. Sequencing quality has improved

greatly recently, and most modern sequencers are capable of generating raw reads

with only rare bases below Q30, and thus by default, the read filtering step is not

included. We suggest that users conduct QC using CRISPR-detector if they expect

sequencing quality issues. We also decided to exclude adapter and primer trimming

from the pipeline because primers are typically not included in the reference target

regions in this application. Adapters may exist in raw data, but they do not affect the

mapping result to a noticeable extent, and thus removing them may not be worth the

computational cost.

Benefits of Variant Clinical Annotation

Genomic variants may lead to clinically meaningful changes to protein function

and phenotypes, and it is important for off-target detection to evaluate the potential

clinical outcome of these introduced variants. The key here is to separate pathogenic

variants from others. Instead of requiring users to take the variant output and conduct

annotation on other platforms, we integrated the functional and clinical annotation

within the CRISPR-detector platform so that users can directly assess potential

clinical results.

Materials and methods

Pipeline Description

As shown in the CRISPR-detector flowchart (Fig. 1A), CRISPR-detector accepts

single/pooled amplicon deep-sequencing as well as WGS data as input. Input reads

are mapped to amplicon sequence(s) or a reference genome to call variants. If a

control group sample is provided, CRISPR-detector will use it to remove background

variants prior to analyzing the genome editing events of the treatment group sample.

For targeted amplicon sequencing data, basic information including amplicon

sequence(s) is compulsory, whereas sgRNA sequence(s) input is optional. After

variants are called, the CRISPR-detector web server supports the clinical annotation

of mutations for human samples and functional annotation for nine other species. The

locally deployable pipeline supports the use of a specific database built by users for

mutation annotation. The CRISPR-detector generates graphs and tables that quantify

and visualize the location and type of mutation(s) within the amplicon sequence(s).

For WGS data analysis, a reference genome is mandatory as input. The BED

format text file is optional and is used for calling variants at regions of interest such as

on/off-target sites. Our CRISPR-detector tool is capable of calling variants involving

SNPs and SVs. CRISPR-detector outputs a VCF (Variant Call Format) file, which

contains information about the variants called. Efficient tools for in vivo gene transfer,

such as AAV viral vectors (rAAVs), may nonspecifically integrate into the host cell

genome and cause insertional mutagenesis events, and if the viral vector sequence(s)

is provided, CRISPR-detector can also report the location of vector insertion events.

Webpage Input Module

On the CISPR-detector home page (https://db.cngb.org/crispr-detector), users can

upload FASTQ files, provide basic information, and set parameters. FASTQ

sequences from the treatment group are mandatory, whereas sequences from the

control group are optional, but recommended. Each of the input FASTQ files can be

sequencing data from a single amplicon or pooled amplicons. Although CRISPR-

detector does not provide sample separation based on sample indexes or barcodes, it

does support separated FASTQ files from pooled amplicon sequencing protocols

similar to those described in Hi-TOM (Liu et al., 2019).

Data Analysis Module

CRISPR-detector analyzes the input data in two stages: "preprocessing" and

"variant identification". In the preprocessing stage, reads from edited samples or

control samples are first mapped to either amplicon sequences or the human reference

genome using Sentieon Minimap2 (Li, 2018), which is an accelerated version of the

corresponding open-source Minimap2 that returns identical results. Next, all mapped

reads are sorted by the Sentieon "sort" utility when read ranks are adjusted by their

genomic locations. Then, a quality control step is conducted on the sorted BAM files

by the Sentieon "Quality Yield" utility to calculate a quality score distribution of the

aligned reads. A warning will be given to the users if the Q30 value (percentage of

mapped bases with quality scores greater than 30) is lower than 0.75 by default. The

claimed Q30 for Miseq is ~0.85, and thus a Q30 value lower than 0.75 may indicate

abnormal sequencing quality issues. The last step of this stage is deduplication by the

Sentieon "Dedup and LocusCollector" utility, which marks reads with the same

starting and ending positions to avoid duplicate counting. This "dedup" step is

necessary for WGS or probe hybridization-based capture sequencing but should be

skipped for amplicon sequencing.

The second "Variant Identification" stage transforms prepared BAM files into

variants. To begin, Sentieon TNscope is used with the default parameters to generate

SNP and indel candidate variants. Sentieon TNscope is developed on top of GATK

Mutect2 v3.8 and is specifically optimized for low AFs variant calling and integrated

structural variation calling functions (Freed et al., 2018; Benjamin et al., 2019). Then

structural variations are called by TNscope using default parameters if the pipeline is

run as a local version. Genetic background filtering is the next step, in which TNscope

generates candidate variants from control samples. Each candidate variant from edited

and control samples is tested with Fisher's exact test to calculate a p-value and

determine if its supporting features reach significance. Variants from edited samples

are filtered out if the p-value is higher than the user-determined cutoff (default 0.05).

The next step is to filter out low-quality reads. Specifically, reads marked by TNscope

other than "PASS", "triallelic_site", or "alt_allele_in_normal" are filtered out, and

variants with lower than input AF cutoff (default 0.005) or with less than input

supporting read depth (default 500) for amplicon data are filtered out. The last step is

to filter out variants that are not likely to be introduced by editing. When uploading an

amplicon dataset, users can provide guide RNA sequence(s) and input a

"cleavage_offset" parameter to define the center of the quantification window with

respect to the 3' end of the provided sgRNA sequence excluding the PAM. The

"window_size" parameter can also be designated to define the size (in bp) of the

quantification window extending from the center of the quantification window

defined by the "cleavage_offset" parameter. The default value of "window_size" is 0,

meaning analysis is conducted for whole amplicons. If the quantification window is

defined then any variants that do not overlap with the window are filtered out.

Functional and clinically important variants in the treatment group data are

annotated using the published ANNOVAR (version 2019 Oct24) tool and ClinVar

(version 20210501) databases (Wang et al., 2010). Functional variants provided by

ANNOVAR include frameshift, nonsynonymous, start-gain/loss, or stop-gain/loss

mutations (Fig.S5), and clinical variants are those marked pathogenic or likely

pathogenic in the ClinVar database, which provides the interpretation of variant

correlation with disease.

Result Visualization Module

By clicking the "Example" button on the webpage, example results for real

datasets are shown. The results webpage includes three parts:

1) A downloadable table summarizing the number of processed reads and the

frequency of different types of mutations on all the input loci (Table S4).

2) A batch output mode comparing the editing outcomes from all input loci,

producing figures comparing the general SNPs and indel ratios.

3) Results for individual input locus. The example figure shows the edited number

position of the identified SNPs and indels (Fig. 3A) and the indel size distribution

(Fig. 3B). The reported positions are from the co-analysis if control sample data

are available. Furthermore, detailed information on mutations including the

annotation of this locus is summarized in a downloadable table (Fig. 3C).

Locally Deployable Version

Due to data upload speed limitations, our web-hosted pipeline is inconvenient for

processing WGS data. To provide an alternative solution, a version for local

deployment that accepts NGS data larger than 100 MB, including WGS sequencing

data, has also been developed and is provided to the community (available at

https://github.com/hlcas/CRISPR-detector).

There are three differences between the web version and this locally deployable

version: 1) the local pipelines accept WGS and other large datasets; 2) structural

variants can be called; and 3) visualization modules and annotation functions are not

included, because the pipeline outputs VCF format files.

Structural variations are called using TNscope, which is based on evidence from

soft-clipped mapped reads and the discordance of read pairs. Specifically, the calling

occurs in three stages. In the first stage, the caller identifies all abnormally aligned

reads from treatment and control samples (if available). Concurrently, it builds a local

assembly around the split reads and filters out all haplotypes that exist in the control

samples and noisy haplotypes with little read support. In the second stage, it analyzes

the candidate haplotypes assembled around split reads and identifies consistent

haplotype pairs. These reads represent potential structural variant break-ends. In the

third stage, the caller looks for evidence from the discordant read pairs.

Data availability

Source code and scripts to simulate sequencing data are available at GitHub

(https://github.com/hlcas/CRISPR-detector). WGS datasets are available as the GEO

reference series SRP045395. SPACE and ABE8e-NRCH datasets can be accessed at

the NCBI Sequence Read Archive (PRJNA609075; PRJNA725249).

Credit authorship contribution statement

Lei Huang, **Haodong Chen**, **Jinnan Hu**: Conceptualization, Data curation,
Formal analysis, Investigation, Methodology, Resources, Software, Validation,
Visualization, Writing – Original draft, Review & Editing. **Xuechen Dai**, **Chuan Liu**,
Anduo Li, **Xuechun Shen**, **Chen Qi**: Investigation, Methodology, Validation,
Writing – Review & Editing. **Haixi Sun**, **Dengwei Zhang**: Conceptualization,
Methodology, Supervision, Writing – Review & Editing. **Yuan Jiang**, **Dan Wang,**
Tong Chen: Conceptualization, Funding acquisition, Investigation, Methodology,
Project administration, Supervision, Writing – Original draft, Review & Editing. All
authors read and approved the final manuscript.

Conflict of interest

Acknowledgments

We would like to thank Dr. Gao Qianqian for advising on our web server and
providing sequencing data and colleagues at China National GeneBank (Shenzhen)
and EHBIO Gene Technology (Beijing) for their guidance and help in constructing
the web server. The authors declare that the research was conducted in the absence of
any commercial or financial relationships that could be construed as a potential
conflict of interest. This work was supported by the Fundamental Research Funds for
the Central Public Welfare Research Institutes (ZZ13-YQ-095 and ZZXT201708) and
the Start-up Research Fund from BNU-HKBU United International College
(UICR0700053-23).

References

Jinek, M., Chylinski, K., Fonfara, I., Hauer, M., Doudna, J.A., Charpentier, E., 2012.
A programmable dual-RNA–guided DNA endonuclease in adaptive bacterial
immunity. Science 337, 816–821.

Cong, L., Ran, F.A., Cox, D., Lin, S., Barretto, R., Habib, N., Hsu, P.D., Wu, X.,
Jiang, W., Marraffini, L.A., et al., 2013. Multiplex genome engineering using
CRISPR/Cas systems. Science 339, 819–823.

Zetsche, B., Gootenberg, J.S., Abudayyeh, O.O., Slaymaker, I.M., Makarova, K.S.,
Essletzbichler, P., Volz, S.E., Joung, J., Van Der Oost, J., Regev, A., et al., 2015.
Cpf1 is a single RNA-guided endonuclease of a class 2 CRISPR-Cas system. Cell 163,
759–771.

Abudayyeh, O.O., Gootenberg, J.S., Konermann, S., Joung, J., Slaymaker, I.M., Cox,
D.B., Shmakov, S., Makarova, K.S., Semenova, E., Minakhin, L., et al., 2016. C2c2 is
a single-component programmable RNA-guided RNA-targeting CRISPR
effector. Science 353, aaf5573.

Liu, J.J., Orlova, N., Oakes, B.L., Ma, E., Spinner, H.B., Baney, K.L., Chuck, J., Tan,
D., Knott, G.J., Harrington, L.B., et al., 2019. CasX enzymes comprise a distinct
family of RNA-guided genome editors. Nature 566, 218–223.

Pausch, P., Al-Shayeb, B., Bisom-Rapp, E., Tsuchida, C.A., Li, Z., Cress, B.F., Knott,
G.J., Jacobsen, S.E., Banfield, J.F., Doudna, J.A., 2020. CRISPR-CasΦ from huge
phages is a hypercompact genome editor. Science 369, 333–337.

Komor, A.C., Kim, Y.B., Packer, M.S., Zuris, J.A., Liu, D.R., 2016. Programmable
editing of a target base in genomic DNA without double-stranded DNA
cleavage. Nature 533, 420–424.

Gaudelli, N.M., Komor, A.C., Rees, H.A., Packer, M.S., Badran, A.H., Bryson, D.I.,
Liu, D.R., 2017. Programmable base editing of A•T to G•C in genomic DNA without
DNA cleavage. Nature 551, 464–471.

Kim, Y.B., Komor, A.C., Levy, J.M., Packer, M.S., Zhao, K.T., Liu, D.R., 2017.
Increasing the genome-targeting scope and precision of base editing with engineered
Cas9-cytidine deaminase fusions. Nat Biotechnol. 35, 371–376.

Anzalone, A.V., Randolph, P.B., Davis, J.R., Sousa, A.A., Koblan, L.W., Levy, J.M.,

Chen, P.J., Wilson, C., Newby, G.A., Raguram, A., et al., 2019. Search-and-replace

genome editing without double-strand breaks or donor DNA. Nature 576, 149–157.

Lu, Y., Xue, J., Deng, T., Zhou, X., Yu, K., Deng, L., Huang, M., Yi, X., Liang, M.,

Wang, Y., et al., 2020. Safety and feasibility of CRISPR-edited T cells in patients

with refractory non-small-cell lung cancer. Nat Med. 26, 732–740.

Frangoul, H., Altshuler, D., Cappellini, M.D., Chen, Y.S., Domm, J., Eustace, B.K.,

Foell, J., de la Fuente, J., Grupp, S., Handgretinger, R., et al., 2021. CRISPR-Cas9

gene editing for sickle cell disease and β-thalassemia. N Engl J Med. 384, 252–260.

Gillmore, J.D., Gane, E., Taubel, J., Kao, J., Fontana, M., Maitland, M.L., Seitzer, J.,

O'Connell, D., Walsh, K.R., Wood, K., et al., 2021. CRISPR-Cas9 in vivo gene

editing for transthyretin amyloidosis. N Engl J Med. 385, 493–502.

Akcakaya, P., Bobbin, M.L., Guo, J.A., Malagon-Lopez, J., Clement, K., Garcia, S.P.,

Fellows, M.D., Porritt, M.J., Firth, M.A., Carreras, A., et al., 2018. In vivo CRISPR

editing with no detectable genome-wide off-target mutations. Nature 561, 416–419.

Bae, S., Park, J., Kim, J.S., 2014. Cas-OFFinder: a fast and versatile algorithm that

searches for potential off-target sites of Cas9 RNA-guided

endonucleases. Bioinformatics 30, 1473–1475.

Güell, M., Yang, L., Church, G.M., 2014. Genome editing assessment using CRISPR

Genome Analyzer (CRISPR-GA). Bioinformatics 30, 2968–2970.

Xue, L.J., Tsai, C.J., 2015. AGEseq: analysis of genome editing by sequencing. Mol

Plant. 8, 1428–1430.

Varshney, G.K., Pei, W., LaFave, M.C., Idol, J., Xu, L., Gallardo, V., Carrington, B.,

Bishop, K., Jones, M., Li, M., et al., 2015. High-throughput gene targeting and

phenotyping in zebrafish using CRISPR/Cas9. Genome Res. 25, 1030–1042.

Park, J., Lim, K., Kim, J.S., Bae, S., 2017. Cas-analyzer: an online tool for assessing

genome editing results using NGS data. Bioinformatics 33, 286–288.

Labun, K., Guo, X., Chavez, A., Church, G., Gagnon, J.A., Valen, E., 2019. Accurate

analysis of genuine CRISPR editing events with ampliCan. Genome Res. 29, 843–847.

Pinello, L., Canver, M.C., Hoban, M.D., Orkin, S.H., Kohn, D.B., Bauer, D.E., Yuan,

G.C., 2016. Analyzing CRISPR genome-editing experiments with CRISPResso. Nat

Biotechnol. 34, 695–697.

Clement, K., Rees, H., Canver, M.C., Gehrke, J.M., Farouni, R., Hsu, J.Y., Cole,

M.A., Liu, D.R., Joung, J.K., Bauer, D.E., et al., 2019. CRISPResso2 provides

accurate and rapid genome editing sequence analysis. Nat Biotechnol. 37, 224–226.

Landrum, M.J., Lee, J.M., Benson, M., Brown, G.R., Chao, C., Chitipiralla, S., Gu, B.,

Hart, J., Hoffman, D., Jang, W., et al., 2018. ClinVar: improving access to variant

interpretations and supporting evidence. Nucleic Acids Res. 46, D1062–D1067.

Huang, W., Li, L., Myers, J.R., Marth, G.T., 2012. ART: a next-generation

sequencing read simulator. Bioinformatics 28, 593–594.

Freed, D., Pan, R., Aldana, R., 2018. TNscope: accurate detection of somatic

mutations with haplotype-based variant candidate detection and machine learning

filtering. bioRxiv. https://doi.org/10.1101/250647.

García-Nieto, P.E., Morrison, A.J., Fraser, H.B., 2019. The somatic mutation

landscape of the human body. Genome Biol. 20, 1–20.

Bao, X.R., Pan, Y., Lee, C.M., Davis, T.H., Bao, G., 2021. Tools for experimental and

computational analyses of off-target editing by programmable nucleases. Nat

Protoc. 16, 10–26.

Ewing, A.D., Houlahan, K.E., Hu, Y., Ellrott, K., Caloian, C., Yamaguchi, T.N., Bare,

J.C., P'ng, C., Waggott, D., Sabelnykova, V.Y., et al., 2015. Combining tumor

genome simulation with crowdsourcing to benchmark somatic single-nucleotide-

variant detection. Nat Methods. 12, 623–630.

Wu, Y., Zhou, H., Fan, X., Zhang, Y., Zhang, M., Wang, Y., Xie, Z., Bai, M., Yin, Q.,

Liang, D., et al., 2015. Correction of a genetic disease by CRISPR-Cas9-mediated

gene editing in mouse spermatogonial stem cells. Cell Res. 25, 67–79.

Zook, J.M., Hansen, N.F., Olson, N.D., Chapman, L., Mullikin, J.C., Xiao, C., Sherry,

S., Koren, S., Phillippy, A.M., Boutros, P.C., et al., 2020. A robust benchmark for

detection of germline large deletions and insertions. Nat Biotechnol. 38, 1347–1355.

Guo, J., Shi, C., Chen, X., Wang, O., Liu, P., Yang, H., Xu, X., Zhang, W., Zhu, H.,

2021. stLFRsv: a germline structural variant analysis pipeline using co-barcoded

reads. Front. Genet. 12, 222.

Sedlazeck, F.J., Rescheneder, P., Smolka, M., Fang, H., Nattestad, M., Von Haeseler,

A., Schatz, M.C., 2018. Accurate detection of complex structural variations using

single-molecule sequencing. Nat Methods. 15, 461–468.

Newby, G.A., Yen, J.S., Woodard, K.J., Mayuranathan, T., Lazzarotto, C.R., Li, Y.,

Sheppard-Tillman, H., Porter, S.N., Yao, Y., Mayberry, K., et al., 2021. Base editing

of haematopoietic stem cells rescues sickle cell disease in mice. Nature 595, 295–302.

Grünewald, J., Zhou, R., Lareau, C.A., Garcia, S.P., Iyer, S., Miller, B.R., Langner,

L.M., Hsu, J.Y., Aryee, M.J., Joung, J.K., 2020. A dual-deaminase CRISPR base

editor enables concurrent adenine and cytosine editing. Nat Biotechnol. 38, 861–864.

Poplin, R., Ruano-Rubio, V., DePristo, M.A., Fennell, T.J., Carneiro, M.O., Van der

Auwera, G.A., Kling, D.E., Gauthier, L.D., Levy-Moonshine, A., Roazen, D., et al.,

2018. Scaling accurate genetic variant discovery to tens of thousands of

samples. bioRxiv. https://doi.org/10.1101/201178.

Tsai, S.Q., Nguyen, N.T., Malagon-Lopez, J., Topkar, V.V., Aryee, M.J., Joung, J.K.,

2017. CIRCLE-seq: a highly sensitive in vitro screen for genome-wide CRISPR–Cas9

nuclease off-targets. Nat Methods. 14, 607–614.

Liu, Q., Wang, C., Jiao, X., Zhang, H., Song, L., Li, Y., Gao, C., Wang, K., 2019. Hi-

TOM: a platform for high-throughput tracking of mutations induced by CRISPR/Cas

systems. Sci China Life Sci. 62, 1–7.

Li, H., 2018. Minimap2: pairwise alignment for nucleotide

sequences. Bioinformatics 34, 3094–3100.

Benjamin, D., Sato, T., Cibulskis, K., Getz, G., Stewart, C., Lichtenstein, L., 2019.

Calling   somatic   SNVs   and   indels   with   Mutect2. bioRxiv.

https://doi.org/10.1101/861054.

Wang, K., Li, M., Hakonarson, H., 2010. ANNOVAR: functional annotation of

genetic variants from high-throughput sequencing data. Nucleic Acids Res. 38, e164–

e164.

Figure legends

Fig. 1. Flowchart and module description of CRISPR-detector. **A:** CRISPR-detector

accepts single/pooled amplicon deep-sequencing as well as WGS data as input. The

control group sample is utilized for removing background variants existing prior to

genome editing for the treatment group sample. CRISPR-detector outputs

visualization results and functional annotations of editing-induced mutations for

targeted amplicon sequencing data, and VCF format text file for WGS data. **B:**

Description of analysis modules that have been used in the pipeline.

Fig. 2. Accuracy and running time benchmark for single amplicon and 200 amplicons

dataset. Amplicons in the format of 150 bp paired-end reads were simulated, to

represent a large panel in which SNPs, indels, and sequencing errors (profiled by ART)

were introduced**. A:** Simulated SNPs (1-3 per read) and indels (5-50 bp length) at 50%

frequency were inserted. Compared to CRISPResso2, CRISPR-detector showed 7

times faster processing speed and reported mutated reads % closer to the expected

value.

B: 5 bp indel was introduced at multiple frequencies ladder ranging 0.01 % to 100 %,

and processed by CRISPR-detector and CRISPResso2. Although neither tool

correctly reported indel frequency at 0.01% level, CRISPR-detector outperformed

CRISPResso2 at 0.1%-10% indels detection accuracy, by returning both mutated

reads (%) and Indel (%) closer to expected values. **C:** CRISPR-detector outperforms

CRISPResso2 on all 200 amplicons tested as its reported mutated reads frequency

were closer to the expected 50% and 0% value, while CRISPResso2 overestimated

mutated reads frequency by about 5%. **D:** CRISPR-detector runs 8 times faster than

CRISPResso2 on these 200 amplicons dataset, slightly faster than the acceleration rate

observed from the single amplicon benchmark.

Fig. 3. Example of data visualization for a single locus. These three figures and tables

are part of the visualized result of the web-hosted version of CRISPR-detector

pipeline. **A**: Frequency of identified SNPs and indels across the amplicon. **B:** Indel

size distribution. **C:** Detailed information on identified variants on this locus,

including function and clinical annotations.

Table 1. Identification of simulated insertion using co-analysis dataset.

Simulated Reads Type		Variant Detected				
Control Reads Type	Inserted Reads Type	Expected Value (%)	POS	REF	ALT	Mutated reads (%)
1 substitution	1 substitution & 1 bp insertion	50.0	105	-	C	49.6
2 substitutions	2 substitutions & 1 bp insertion	50.0	105	-	C	47.9
3 substitutions	3 substitutions & 1 bp insertion	50.0	105	-	C	47.9
5 bp deletion	5 bp deletion & 1 bp insertion	50.0	105	-	C	49.8
10 bp deletion	10 bp deletion & 1 bp insertion	50.0	105	-	C	65.8
50 bp deletion	50 bp deletion & 1 bp insertion	50.0	105	-	C	64.0
5 bp insertion	5 bp insertion & 1 bp insertion	50.0	105	-	C	48.5
10 bp insertion	10 bp insertion & 1 bp insertion	50.0	105	-	C	48.2
50 bp insertion	50 bp insertion & 1 bp insertion	50.0			Failed	

711   SNPs (1-3 per read) and indels (5-50 bp length) at 50% frequency together with

712   sequencing errors were simulated as the control reads group. Then a 1 bp insertion at

713   position was inserted into the control group to form inserted read group. Co-analysis

714   were conducted on both inserted reads and control reads. For all read types except the

50 bp insertion, CRISPR-detector successfully identified true editing events (the 1bp

insertion) without false positives of variants existing in control samples.

Table 2. SNP, indel, and SV Performance on WGS datasets.

A

AF > 5%	SNP		Insertions (1-50 bp)		Deletions (1-72 bp)	
	Sensitivity%	Specificity%	Sensitivity%	Specificity%	Sensitivity%	Specificity%
100x co-analysis	87.7	82.4	58.3	39.3	56.5	37
100x edited only	96.4	41.4	55.6	13.9	71.7	18.3
AF > 15%	SNP		Insertions (1-50 bp)		Deletions (1-72 bp)	
	Sensitivity%	Specificity%	Sensitivity%	Specificity%	Sensitivity%	Specificity%
30x co-analysis	98.8	99.3	13.3	50	23.7	66.7
30x edited only	97.3	70.9	16.7	18.8	23.7	27.3

B

Reads Type		30x Short Reads	100x Co-barcoded Reads		100x Long Reads
SV Length	Pipeline	CRISPR-detector	Smoove	Long Ranger	Sniffles
50-1000 bp	TP	1268	724	2304	4168
	FP	302	248	1279	5285
	FN	3451	3995	2415	551
	Recall	26.87%	15.34%	48.82%	88.32%
	Precision	80.76%	74.49%	64.30%	44.09%
> 1000 bp	TP	445	463	558	570
	FP	212	162	385	447
	FN	172	154	59	47
	Recall	72.12%	75.04%	90.44%	92.38%
	Precision	67.73%	74.08%	59.17%	56.05%

A: SNPs and indels accuracy benchmark. SNPs and indels were introduced into

one chromosome sequence. Only variants with AFs above 5% for 100x WGS, and

with AFs above 15% for 30x WGS were reported to ensure at least 3 reads to support

a reported variant. Sensitivity is calculated by TP/(TP+FN), and specificity is

calculated by TP/(TP+FP) [TP: True Positive; FN: False Negative; FP: False

Negative]. Inserted reads were processed in both co-analysis mode and edited only

mode. Co-analysis showed better accuracy than only analyzing the edited sample,

especially for specificity%. Due to a much larger analysis region, the accuracy of

WGS tends to be lower than that of amplicons. **B: SV accuracy benchmark.** We

utilized the well-established NIST GIAB reference sample HG002 dataset to serve as

a truth set. SVs were called from the CRISPR-detector pipeline and compared with the

NIST truth set using Truvari to determine True Positive (TP), False Positive (FP), and

False Negative (FN), and then to calculate Recall and Precision values. We also
displayed the results of other types of data and pipelines from a recently published
study that used the same HG002 truth dataset (Zook et al., 2020). In the 50 bp - 1 kb
group, CRISPR-detector reaches 26.87% recall and 80.76% precision and slightly
outperforms Smoove. Long Ranger returned similar accuracy to CRISPR-detector,
and Sniffles returns better recall than any other callers. For longer deletions (> 1 kb),
CRISPR-detector's accuracy score is slightly lower than co-barcoded or long-read
callers.

Table 3. Comparing functions of tools that assess genome editing results.

		CRISPR-detector	CRISPResso1/2	Cas-Analyzer	AGEseq	CRISPR-GA	ampliconDIVider
	Web-based	√	√		√	√	
	Editing tools	Any	Any	Cas9/Cpf1/ZFN/ TALEN/dCas9-Fok1	Any	Any	Cas9
Input	Pooled amplicon sequencing data	√	√		√		
	WGS data	Whole genome analysis	Regions of interest				
Output	Mutation types	Substitution; Indels; SV	Substitution; Indel	Substitution; Indel	Substitution; Indel	Indel	Indel
	Vector detection	√					
	Functional annotations	√	√				
	Pathogenic annotation	√					
Functional modules	Quality control	√	√	√	√	√	
	Mapping	√	√	√	√	√	
	Indels call	√	√	√	√	√	√
	Substitutions call	√	√	√	√		
	SV call	√					
	Genetic background removal	√					
	HDR*/NHEJ* computations		√	√		√	
	Inter-sample comparison	√	√				
	Graphical display	√	√	√	√	√	

* HDR: homology-directed repair; NHEJ: non-homologous end joining

Several widely-used tools for analyzing genome editing NGS data were included in
this comparison. CRISPR-detector headed most other tools in function completeness,
especially the capability to 1) process whole region of WGS data; 2) remove genetic

748   background when control sample is available; 3) functional and pathogenic annotation

749   of identified variants.

A

| Data | Pre-processing | Variants identification | Output |

Data

Single/pooled amplicon deep-sequencing
Whole genome sequencing from treated/untreated group (FASTQ)

Pre-processing

Align to amplicon sequences (for amplicon sequencing) or reference genome (for WGS) by "Sentieon Minimap2"

Sorted by "sort" utility

QC stats calculated by "QualityYield" utility

Deduplication (skipped for Amplicon) by "Dedup and LocusCollector" utility

Variants identification

Short variant calling by "TNscope" utility

Structural variation (SV) calling (local version only) by "TNscope" utility

Genetic background filtering

Low quality variants filtering

Editing-induced mutations

Output

Functional and pathogenetic annotation

Multiple loci comparison

Result visualization

B

Computation Module	Purpose
Sentieon Minimap2	Align reads to reference genome or amplicon sequences
Sentieon Sort	Sort aligned reads
Sentieon QualityYield	Check reads quality, and warn user if low quality
Sentieon Dedup and LocusCollector	Remove duplication reads, this step is skipped for amplicon data
Sentieon TNscope	Identify candidate SNPs, Indels, and SVs, conduct genetic background filtering
Python scripts	Filter variants with low quality or outside defined editing window
ANNOVAR	Annotate identified variants

A

| Reads type | Expected value (%) | CRISPR-detector | | CRISPResso2 | | Cas-Analyzer | AGEseq |
		Mutated reads (%)	Average running time (s)	Mutated reads (%)	Average running time (s)	Mutated reads (%)	Mutated reads (%)
unmodified	0.0	0.0	2	8.3	14	18.3	14.4
1 substitution	50.0	49.9	2	54.5	13	58.8	57.3
2 substitutions	50.0	50.0	2	53.6	14	58.5	57.1
3 substitutions	50.0	50.0	2	54.9	13	59.6	57.0
5 bp insertion	50.0	49.9	2	54.1	14	59.9	57.5
10 bp insertion	50.0	49.9	2	54.9	13	58.8	56.3
50 bp insertion	50.0	48.9	2	54.9	14	56.7	56.9
5 bp deletion	50.0	49.9	2	54.9	14	58.9	57.5
10 bp deletion	50.0	49.9	2	55.5	13	58.9	57.5
50 bp deletion	50.0	48.9	2	53.9	13	59.3	57.2

B

| Indel frequencies (%) Expected value | CRISPR-detector | | CRISPResso2 | |
	Mutated Reads (%)	Indel (%)	Mutated Reads (%)	Indel (%)
0.10	0.10	0.10	9.01	0.12
1.00	1.00	1.00	10.16	1.01
10.00	10.01	10.01	18.46	10.03
100.00	100.00	100.00	100.00	100.00

[1] Mutated Reads (%) is the percentage of mutated reads among all the reads

[2] Indel (%) is the percentage of reads with indels among all the reads

C

D

A

Frequency of mutations across the amplicon

B

Indel size distribution

C

Amplicon	Amplicon_Start	Amplicon_End	Ref	Alt	Alt allele frequency (%) | Control	Alt allele frequency (%) | Treatment	Chr	Start	End	Func. refGene	Gene. refGene	ExonicFunc. refGene	AAChange. refGene	CLNALLELEID	CLNDN	CLNDISDB	CLNREVSTAT	CLNSIG
ON	117	126	GTTGC	-	0.11	4.00	chr12	25245351	25245360	exonic	KRAS	frameshift deletion	KRAS:NM_0	.	.	.	.	.
ON	124	124	-	T	0.00	2.89	chr12	25245353	25245353	exonic	KRAS	frameshift insertion	KRAS:NM_0	.	.	.	.	.
ON	127	127	G	T	0.14	0.89	chr12	25245350	25245350	exonic	KRAS	nonsynonymous SNV	KRAS:NM_0	27622	Acute_mye	Human_Phenc	criteria_provided,x	Pathogenic
ON	120	123	GGAG	-	0.00	0.82	chr12	25245354	25245357	exonic	KRAS	frameshift deletion	KRAS:NM_0	.	.	.	.	.
ON	124	124	-	AT	0.00	0.45	chr12	25245353	25245353	exonic	KRAS	frameshift insertion	KRAS:NM_0	.	.	.	.	.
ON	123	131	GCTGC	-	0.00	0.39	chr12	25245346	25245354	exonic	KRAS	nonframeshift deletion	KRAS:NM_0	.	.	.	.	.
ON	122	122	-	GC	0.00	0.36	chr12	25245355	25245355	exonic	KRAS	frameshift insertion	KRAS:NM_0	.	.	.	.	.
ON	126	126	-	CACTL	0.00	0.36	chr12	25245351	25245351	exonic	KRAS	stopgain	KRAS:NM_0	.	.	.	.	.
ON	126	126	-	ACGC	0.00	0.35	chr12	25245351	25245351	exonic	KRAS	stopgain	KRAS:NM_0	.	.	.	.	.
ON	123	123	-	CATA	0.00	0.28	chr12	25245354	25245354	exonic	KRAS	frameshift insertion	KRAS:NM_0	.	.	.	.	.
ON	126	126	-	CT	0.00	0.28	chr12	25245351	25245351	exonic	KRAS	frameshift insertion	KRAS:NM_0	.	.	.	.	.
ON	129	129	-	CATC	0.00	0.28	chr12	25245348	25245348	exonic	KRAS	frameshift insertion	KRAS:NM_0	.	.	.	.	.
ON	131	131	-	GCCTL	0.00	0.28	chr12	25245346	25245346	exonic	KRAS	stopgain	KRAS:NM_0	.	.	.	.	.
ON	124	124	-	TCTTC	0.00	0.27	chr12	25245353	25245353	exonic	KRAS	frameshift insertion	KRAS:NM_0	.	.	.	.	.