CRISPR-Detector: Fast and Accurate Detection, Visualization, and Annotation

of Genome Wide Mutations Induced by Gene Editing Events

Authors

Lei Huang[1†], Dan Wang[2†*], Haodong Chen[3], Jinnan Hu[3], Xuechen Dai[2], Chuan Liu[2],

Anduo Li[2], Xuechun Shen[5], Chen Qi[1], Haixi Sun[2], Dengwei Zhang[2], Tong Chen[4*]

Yuan Jiang[2*]

Affiliations

1 College of Life Sciences, University of Chinese Academy of Sciences, Beijing,

China.

2 BGI-Shenzhen, Shenzhen, China.

3 Sentieon Inc, San Jose, CA, USA.

4 National Resource Center for Chinese Materia Medica, China Academy of Chinese

Medical Sciences, Beijing, China.

5 School of Biology and Biological Engineering, South China University of

Technology, Guangzhou, China.

***To whom correspondence should be addressed. Fax: 408.648.2161; Email:

yjiang@completegenomics.com.

Correspondence may also be addressed to Email: chent@nrc.ac.cn.

Correspondence may also be addressed to Email: wangdan6@genomics.cn.

† These authors contributed equally to this work.

Abstract

The leading edge of genome editing, driven by CRISPR/Cas technology, is

revolutionizing biotechnologies. In pace with the burst of novel genome editing

methods, bioinformatic tools to monitor the on/off-target events need to be more

evolved as well. Existing tools suffer from limitations in speed and scalability,

especially struggle in the whole genome sequencing data analysis which is believed to

replace amplicon sequencing and become mainstream data type due to the rapidly

decreasing sequencing cost. Here, we introduce our CRISPR-detector tool, which is a

web-hosted or locally deployable pipeline with five key innovations: 1) optimized

scalability allowing for whole genome sequencing data analysis beyond BED file-

defined regions; 2) improved accuracy benefited from haplotype based variant calling

to handle sequencing errors; 3) treated and control sample co-analysis to remove

background variants existing prior to genome editing; 4) integrated structural

variation (SV) calling; 5) functional and clinical annotation of editing-induced

mutations.

Introduction

Since the first report of CRISPR/Cas9 editing technology in 2012,[1] various novel

CRISPR-based genome editing tools have been introduced by different groups.[2-6]

From the initial methods that could only induce gene knockout to base editing,[1] which

enables the direct conversion of one nucleotide to another without producing DSBs in

the target sequence and the recent prime editing which can make targeted indels and

all 12 types of point mutations,[7-10] genome editing methods have progressively

become more flexible and precise. This opens up new exciting opportunities for a

plethora of life science applications including therapeutic treatment, drug discovery,

biofuel producing, agriculture and etc. Early clinical trials demonstrated CRISPR's

general safety and utility and many more trials are under way.[11-13] The increased pace

in CRISPR based treatment sets precision analysis, aka detecting on and off target

events, a top priority for regulators including the FDA. In fact, FDA published

guidance related to genome editing products in March 2022

(https://www.fda.gov/regulatory-information/search-fda-guidance-documents/human-

gene-therapy-products-incorporating-human-genome-editing), where it raised

concerns for detection of gene editing events type and frequency multiple times.

Therefore, the bioinformatic tools to monitor the on/off-target events need to be more

accurate and capable of detecting true editing-induced mutations.

Several tools have been developed to analyze targeted amplicon next-

generation sequencing (NGS) data. However, there are four main drawbacks for

existing tools. The first limitation involves speed and scalability; most tools are

designed to consider single or only a few amplicons for analysis. However, with the

increasing need to comprehensively cover all potential off-target sites, large panel or

even whole genome sequencing analysis should be conducted. Secondly, tools

including CRISPR-GA,[14] AGEseq,[15] ampliconDIVider,[16] Cas-Analyzer and

CRISPResso1/2 do not support the co-analysis of paired treatment/control sequencing

data,[17-19] and thus previously existing genetic background SNPs (Single Nucleotide

Polymorphisms) and indels could be interpreted as CRISPR/Cas-induced mutations

and lead to the incorrect quantification of mutation events. Third, beyond SNPs and

indels, structural variation is currently ignored by analysis. The fourth drawback is

that, to our knowledge, no existing pipeline estimates the functional or clinal

consequences resulting from editing-induced mutations. This annotation is quite

important for researchers whose genome editing projects are for therapeutic purposes.

To deal with these limitations, we herein propose a one-stop CRISPR-detector

platform. CRISPR-detector accepts raw FASTQ sequencing files from respective

CRISPR/Cas-treatment and control experiments. Each input FASTQ file includes

sequencing data from one or multiple amplicons, e.g., one on-target and its several

off-target amplicons. The output of the web-hosted version of CRISPR-detector

includes comprehensive analysis, intuitive visualization, and locus comparison.

Specifically, CRISPR-detector primarily outputs: i) a summary webpage comparing

and visualizing editing outcomes of the input amplicons; ii) detailed information on

editing outcomes including frequency of SNPs and indels and a histogram of the indel

sizes across the reference amplicon in the quantification window; iii) annotation of

editing-induced mutations showing whether encoded protein sequences are changed

and filter-based annotation of mutations of clinical significance sourced from the

ClinVar database,[20] including pathogenic, drug-response, histocompatibility, and

others.

In addition to the web-hosted version, a locally deployable CRISPR-detector

pipeline focusing on whole genome sequencing analysis and SV calling was

developed. The pipeline not only calls regular SVs caused by the editing process but

also virus vector insertion from viral-mediated gene editing. The whole genome

analysis capability available with the locally deployable version is unique and not

available in other gene editing pipelines.

Methods

In the analysis module, reads are mapped using Sentieon Minimap2, and short

variants are called using Sentieon TNscope module.[21] Sentieon Minimap2 is an

accelerated version of the corresponding opensource Minimap2,[22] returning identical

results two times faster. Sentieon TNscope is developed on top of GATK Mutect2

v3.8 and is specifically optimized for low allele frequency variant calling and

integrated structural variation calling functions. Later in the annotation stage, variants

are annotated using ANNOVAR (version 2019 Oct24) with the ClinVar (version

20210501) database.[23]

Structural variations are called using TNscope, which is based on evidence

from soft clips of mapped reads and the discordance of read pairs. Specifically, the

calling occurs in three stages. In the first stage, the caller identifies all abnormally

aligned reads from treatment and control samples (if available). Concurrently, it

builds a local assembly around the split reads and filters out all haplotypes that exist

in the control samples and noisy haplotypes with little read support. In the second

stage, it analyzes the candidate haplotypes assembled around split reads and identifies

consistent haplotype pairs. These reads represent potential break-ends of the structural

variants. In the third stage, the caller looks for evidence from the discordant read

pairs.

Results

Pipeline Description

As shown in CRISPR-detector flowchart (Fig. 1), CRISPR-detector accepts

single/pooled amplicon deep-sequencing as well as whole genome sequencing data as

input. Input reads are mapped to amplicon sequence(s) or reference genome to call

variants. If control group sample is provided, CRISPR-detector will utilize control

group sample to remove background variants existing prior to genome editing for

treatment group sample.

For targeted amplicon sequencing data, basic information including amplicon

sequence(s) is compulsory and sgRNA sequence(s) is optional to input. After variants

called, CRISPR-detector web server supports clinical annotation of mutations of

human cell experiments sample, and functional annotation for other 9 species. Local

deployable pipeline supports specific database built by users for mutations

annotations. CRISPR-detector outputs graphs and tables showing quantifications and

visualizations of the position and type of mutation(s) within the amplicon sequence(s).

For whole genome sequencing data analysis, reference genome is compulsory to

input. The BED (Browser Extensible Data) format text file is optional and used for

calling variants at regions of interest such as on/off target sites. CRISPR-detector is

capable of calling variants involving SNPs and SVs. CRISPR-detector outputs VCF

(Variant Call Format) format text file contains informations about variants called. As

efficient tools for in vivo gene transfer virus vectors like AAV vectors (rAAV) may

nonspecifically integrate into the host cell genome thus may cause insertional

mutagenesis events. If virus vector sequence(s) is provided, CRISPR-detector will be

capable of reporting the location of vector insertion events.

Input Webpage Module

On the home page, users can upload FASTQ files, provide basic information, and set parameters. FASTQ sequences from the treatment group are mandatory, whereas sequences from a control group are optional, but recommended. Each of the input FASTQ files can be sequencing data from a single amplicon or pooled amplicons.

Data Analysis Module

CRISPR-detector analyzes the input data in three main steps. In the first step, reads from both treatment and control (if available) samples are mapped to a reference sequence uploaded by the user, and then a quality control step is conducted when the quality scores of aligned reads are calculated and users will be warned if reads quality is lower than expected. Next, variants within quantification windows are called. In the treatment/control co-analysis mode, only editing-induced variants are called. In the third step, functional and clinically important variants in the treatment group data are annotated using the published ANNOVAR tool and ClinVar databases. Functional variants may potentially result in frameshift, nonsynonymous, start-loss, or stop-gain mutations, and clinical variants are those marked pathogenic or likely pathogenic in the ClinVar databases, which provides interpretation of variant correlation with disease.

Result Visualization Module

By clicking the "Demo" button on the webpage, example results for real dataset sequencing one on-target locus of the human *KRAS* gene and its corresponding 14 off-target loci is shown. This example result is from a published study,[24] and CRISPR-detector was used in analysis. The results webpage includes three parts:

1) A downloadable table summarizing the number of processed reads and the frequency of different types of mutations on all the input loci (Table 1).

2) A batch output mode comparing the editing outcomes from all input loci,

producing figures comparing the general SNPs and indel ratios. It should be noted

that ratios CRISPR-detector reports are considered as the maximum mutation ratio

across the amplicon or users defined quantification window.

3) Results for individual input locus. The example figure shows the edited number

position of the identified SNPs and indels (Fig. 2A) and indel size distribution

(Fig. 2B). The reported positions are from co-analysis if control sample data are

available. Furthermore, detailed information on mutations including the

annotation on this locus are summarized in a downloadable table (Fig. 2C).

Locally Deployable Version

Due to data upload speed limitations, our web-hosted pipeline is inconvenient for

processing whole genome sequencing data. To provide an alternative solution, a

locally deployable version that accepts NGS data larger than 100 MB, including WGS

sequencing data, has also been developed and is provided to the community (available

at https://github.com/hlcas/CRISPR-detector).

There are three differences between the web version and this locally

deployable version: 1) the local pipelines accept WGS and other large datasets; 2)

structural variants can be called; and 3) visualization modules and annotation

functions are not included, because the pipeline outputs VCF format files.

Performance Benchmarks

SNP/Indel Identification from Single Amplicon

The accurate detection of SNPs and indels is one of the key features for a gene editing

analysis pipeline. To benchmark the accuracy of CRISPR-detector, we generated

simulated testing reads representing actual sequencing data from on/off-target site

amplicons and compared the accuracy with three other popular pipelines including

"Cas-Analyzer", "AGEseq", and "CRISPResso2". We introduced SNPs (1-3 per read)

and indels (5-50 bp length) into the simulated 150 bp paired-end reads at 50%

frequency together with errors introduced from MiSeq default profile provided by

ART simulation tool.[25] Accuracy is calculated by comparing the pipeline reported

mutation percentage to the introduced frequency (50%). Average running time is

calculated from 3 repeated runs. The speed of Cas-Analyzer and AGEseq are not

shown as they were tested on different computation platforms.

Compared to CRISPResso2, CRISPR-detector showed 6 times faster

processing speed, and the nearly 100% accuracy also outperformed CRISPResso2

(Table 2). It should be noted that CRISPR-detector's variant calling pipeline is based

on haplotype assembly, which more easily eliminates sequencing errors compared

with simple pileup-based read statistics.

Then we performed more detailed variant detection testing, to evaluate CRISPR-

detector's performance on indels at different frequency and length. It should be noted

that TNscope, as the variant calling module of CRISPR-detector, utilized haplotype

assembling method to filter out sequencing error, and this strategy also makes it

difficult to identify variant below 0.1% considering sequencing errors at same

frequency level. So CRISPR-detector is capable of detecting editing events

with >0.1% frequency. We designed 5 bp indel in a single simulated amplicon dataset,

at 4 different frequencies starting from 0.1%. The testing dataset was processed by

CRISPR-detector and CRISPResso2. CRISPR-detector almost reached 100%

accuracy while 0.02% sequencing error indels reduced CRISPResso2's accuracy by

20% on the 0.1% indel frequency datapoint (Table 3).

In terms of indels at different length, we simulated additional datasets to test

CRISPR-detector's limitation. Due to limitation brought by short reads length,

CRISPR-detector's indel detection length is set as 50 bp for insertion, and 71 bp for

deletion. To demonstrate this performance, we simulated 50 amplicon datasets with

insertions ranging from 1-50 bp, and 72 amplicons with deletions ranging from 1-72

bp, all at 50% frequencies. CRISPR-detector maintains almost 100% accuracy across

1-50 bp insertions, and 1-71 bp deletions. As comparison, CRISPResso2's accuracy is

around 95%, and failed to detect deletions larger than 50 bp (Fig. 3).

CRISPR-detector can perform co-analysis with control sample data as input to

address existing germline mutations and possible somatic or hematopoiesis-related

mutations that were not introduced by a gene editing event.[26] In this simulated co-

analysis testing dataset, some of the variants were inserted in both treatment and

control reads to benchmark the pipeline's ability to detect "True positive" mutations

(1 bp insertion at position 105 bp) in a noisy background with 7% sequencing error.

For all read types except the 50 bp insertion, CRISPR-detector successfully

identified true editing events without false positive from variants existing in control

samples (Table 4). We tried to run the failed 50 bp insertion sample without a control

group and it ran through. This result shows a limitation of CRISPR-detector in

correctly mapping reads around such long and multiple insertions.

CRISPResso2 offers batch mode to output and visualize variants on the same

location from different samples. While this brings convenience for comparing more

than 2 samples together, the ability to directly filter germline and other existing

variants from control samples, which significantly increases users' efficiency in

recognizing and confirming target variants, is missing.

Scalability on pooled amplicons

In a few years' time, the scope of NGS-based on/off-target editing detection has

expanded from only a few amplicons, to hundreds of amplicons, to the coverage of all

potential off-target sites, and even to whole genome sequencing to ensure that every

portion of the genome is screened. From a recent review, current mainstream in silico

off-target prediction algorithms reach 95% sensitivity if the top 200 potential off-

target sites are considered.[27] This finding indicates a requirement for analysis tools to

consider speed and scalability during development. To deal with this need,

CRISPResso2 provides two specific pipelines, CRISPRessoPooled and

CRISPRessoWGS, for these two input types. In comparison, CRISPR-detector's

optimized high-performance modules are able to handle small and large datasets from

one single pipeline to provide uncompromised accuracy and scalability.

For benchmarking, we generated 200 amplicons in the format of 150 bp

paired-end reads, to represent a large panel in which SNPs, indels, and sequencing

errors were introduced, similar to our single amplicon benchmark.

Accuracy and speed performance are no different than the single amplicon test,

and CRISPR-detector consistently outperforms CRISPResso2 (Fig. 4). It should be

noted that processing speed is not a bottleneck for small data because input/output

limits the whole pipeline speed. However, for larger datasets, especially whole

genome sequencing, alignment and variant calling are two critical steps affecting

pipeline speed, and CRISPR-detector utilizes and benefits from high-performance

modules.

Whole Genome Sequencing Performance

The ability to process whole genome sequencing is a unique feature of CRISPR-

detector; CRISPRessoWGS requires a BED file to run WGS samples, and we believe

the goal of WGS is to cover all regions and identify potential off-target events as

opposed to considering only predicted high-probability regions. Actually

CRISPRessoWGS was not run through even with BED file input. Therefore, we did

not compare CRISPRessoWGS in the current benchmark but will include it in future

benchmarking when the new version can be run through, and the BED file

requirement can be removed.

Main difference of WGS and amplicon dataset are the regions to analysis (~3GB

vs <1KB), and sequencing depth (<100x vs >10,000x). The whole genome screening

brings higher false positive result, and less than sufficient sequencing depth makes

false native unavoidable. To evaluate the accuracy of CRISPR-detector on a WGS

analysis, we inserted 1000 SNPs and indels into one chromosome sequence using

BAMSurgeon.[28] Frequencies of inserted variants are ranging from 0.1% to 100%.

However, considering much lower sequencing depth of WGS comparing to amplicon,

we limited AF (Allele Frequency) for 100x WGS at 5% and above, and AF for 30x

WGS at 15% and above. This is to ensure at least 3 reads to support a reported variant.

Inserted reads and original reads are processed in co-analysis mode. Sensitivity is

calculated by TP/(TP+FN), and specificity is calculated by TP/(TP+FP).

We found that co-analysis result is always better than only analyzing edited

sample (Table 5). Accuracy of SNPs are lower than that from amplicons, but still

acceptable, especially co-analysis on SNPs with AF >15%. Accuracy of indels are

significantly lower than that from Amplicons, this is partially due to the fact that reads

with indels are more difficult to be mapped to the correct location genome-wide, thus

the reported indel frequency is lower than the correct number and may be filtered out

by AF cutoff.

To validate this performance, a pair of 30x whole genome sequencing samples

("Mutant" and "Rescued") from a previous study was used.[29] "Mutant" means control

cells having a pre-existing homozygous 1 bp disease causing deletion relative to the

reference genome in the coding sequence of the mutant gene *Crygc*, "Rescued" means

the edited clone rescued by CRISPR-Cas9 inducing 1 bp insertions 6-7 bp from the

deletion.

CRISPR-detector completed the "Mutant" group WGS dataset in 3 repeated runs

using a consistent and reasonable 4h19m running time with 15 threads allocated (in

total 65 core-hours), and it successfully detected the homozygous 1 bp deletion (chr1

65118239) as expected. Similarly, the pipeline completed the "Rescued" group

sample in 5h36m and detected 2 insertions 6-7 bp from the deletion (chr1 65118232;

chr1 65118233).

Assessing Real World Clinical Data

CRISPR-detector is simultaneously suitable for assessing base editing outcomes.

Published study reported a dual-deaminase base editor called SPACE (Synchronous

Programmable Adenine and Cytosine Editor) which can concurrently introduce A•T-

to-G•C and C•G-to-T•A substitutions.[30] CRISPR-detector's performance was

compared with CRISPResso2 on 28 on target sites by SPACE as treatment and nCas9

as control. Among the 28 on target sites, CRISPR-detector and CRISPResso2 showed

concordance in 23 sites. The other 5 sites (ABE site 17, ABE site 18, ABE site 19,

HEK site 2 and HEK site 3) were suggested as a form of MNPs (Multiple Nucleotide

Polymorphisms), which were shown as a combination of one deletion and one

insertion instead of complex substitutions, due to haplotype assembly process

(Supplementary Table 1).

Another dataset benchmarked was rhAMP-seq sample data provided by IDT

website. For the true editing positions provided by IDT (detected by GATK4 with a

tuned parameter), CRISPR-detector reached 100% accuracy with no false positive or

false negative report (Supplementary Table 2).

Additionally, we analyzed 480 off-target sites from the third primer pool

identified by CIRCLE-seq and CasOFFinder,[31-32] and amplified from genomic DNA

from CD34+ SCD cells edited by ABE8e-NRCH or unedited control SCD donor cells

using rhAMP-Seq (IDT).[33] Among the 480 sites, 27 sites were observed containing

A•T-to-G•C mutations. CRISPR-detector showed discordance on "Off-target site 54",

which we believe the signal was too weak to be considered as a real editing event.

Therefore, we did not report this site (Supplementary Table 3).

Structural Variation Identification

Gene editing not only introduces short variants but additional structural variations that

should not be excluded from analysis. A major purpose for conducting whole genome

sequencing on edited samples is to better identify off-target structural variants. In

addition, in viral-mediated gene transfer events, it is important to know the exact

genome insertion location of the virus vectors to evaluate off-target event occurrence

and functional consequences. To benchmark the accuracy, we designed two

benchmark datasets for both general SV calling and vector insertion events.

In the first part, we utilized the well-established PrecisionFDA dataset from

HG002, in which a total 12,745 isolated indel calls are available, to serve as a truth set.

[34] SVs were called from the CRISPR-detector pipeline and compared with the NIST

truth set using Truvari (https://github.com/spiralgenetics/truvari). To better evaluate

the performance of CRISPR-detector and to better understand the limitations of short

read-based SV calling compared to co-barcoded reads and long reads, we also

compared the result with some pipelines from a recently published study that used the

same testing dataset.[35] Because insertions are more challenging and Truvari can only

recognize the exact match to the truth set, which significantly underestimates true

positives, we only showed the performance on deletions (Table 6).

Deletions were grouped into 2 categories based on their length. In the 50 bp -

1 kb group where the majority of deletions exist, CRISPR-detector reaches 26.87%

recall and 80.76% precision and slightly outperforms Smoove

(https://brentp.github.io/post/smoove/) on 100x co-barcoded reads. Long Ranger

(https://github.com/10XGenomics/longranger) returned similar accuracy to CRISPR-

detector on 100x co-barcoded reads, and Sniffles returns better recall than any other

callers.[36] For longer deletions (>1k), CRISPR-detector's accuracy score is slightly

lower than co-barcoded or long-read callers. Overall, it is quite clear that long read

sequencing and co-barcoded read sequencing technologies are more capable of

identifying large deletions, especially for decent recall, but the CRISPR-detector

pipeline on short reads data still generates useful results. Nevertheless, we

recommend conducting long read whole genome sequencing for SV detection, and

CRISPR-detector will aim to adapt to these long read types in a future release.

367   Next, we simulated 150 bp paired-end reads with mimic ~4.7k AAV vector

368 insertion in a 30x WGS dataset to see if CRISPR-detector is able to report the

369 insertion location. Because the inserted sequences are known, we modified the

370 analysis pipeline to overcome the incompetence of insertion detection from the

371 general SV calling pipeline. The AAV vector sequence was added into the human

372 reference genome file as a dummy chromosome. Reads thus can be mapped to both

373 human and vector sequences, and a translocation event can be reported to show the

374 insertion location. We also introduced AAV partial sequences to better mimic partial

375 insertion and simulated five scenarios, including insertion, reverse insertion, non-

376 AAV sequence insertion, partial swap, and insertion with foreign sequences.

377   In all 5 scenarios CRISPR-detector returned the correct insertion location and

378 always captured at least one of the breakpoints (Fig. 5), giving users the ability to take

379 a closer look at the reported region and confirm the exact insertion format.

381 **Functional annotation of editing induced mutations**

382 We examined annotation result of the processed SPACE and ABE8e-NRCH datasets,

383 and found 1 variant returning annotation from ClinVar database. Annotating

384 mutations from SPACE datasets, a stopgain C•G-to-T•A mutation on *FANCF* site 1

385 were annotated to be pathogenic by ClinVar database, and associated with Fanconi

386 anemi. CRISPR-detector is convenient for users to predict the pathogenic variants

387 may be caused by genome editing tools both for on target and off target sites.

388   Our pathogenicity annotations totally depend on the ClinVar database and may be

389 different from the real pathogenicity. Our tool just assembles the function of ClinVar

390 annotation and provides a more convenient way for users who are interested in

391 whether the off-target happens in the ClinVar database which is one of the largest

392 public databases on human genomic variants and interpretations of their relationships

393 to diseases and other conditions maintained by NCBI. We also have added a clear

394 statement in our user agreement that "The pathogenicity annotations are based on

ClinVar database." The annotations are not intended for direct diagnostic use or

medical decision-making purpose.

Discussion

Comparison with other analysis tools

In pace with the development of genome engineering, analysis toolkit to assess the

quality of genome editing experiment have been developed and made available to

community. Early published tools like CRISPR-GA (2014), ampliconDIVider (2015)

and Cas-Analyzer (2016) only support single amplicon sequencing data, while

AGEseq (2015) and CRISPResso2 (2019) support pooled amplicon sequencing data

but do not support unbiased analysis of WGS data as well as SV calling. Besides,

CRISPR-detector is more comprehensive with functions including genetic

background removal and mutations annotations that other listed toolkits are not

capable of, which significantly improved the accuracy and directly showed the

possible function and clinical consequences. Several widely-used tools for analyzing

genome editing NGS data were compared (Table 7).

Other potentially useful computation modules

We considered whether read trimming and filtering steps should be included in the

pipeline and decided they were unnecessary. Sequencing quality has improved greatly

recently, and most modern sequencers are capable of generating raw reads with only

rare bases below Q30, and thus by default the read filtering step is not included. We

suggest that users conduct QC before input into CRISPR-detector if they expect

sequencing quality issues. The other step is adapter and primer trimming, and we also

decided to exclude these steps from the pipeline because primers are typically not

included in the reference target regions in this application. Adapters may exist in raw

data, but they do not affect the mapping result to a noticeable extent, and thus

removing them may not worth the computational cost.

Benefits of variant clinical annotation

Genomic variants may lead to clinically meaningful changes to protein function and phenotypes, and it is important for off-target detection to evaluate the potential clinical outcome of these introduced variants. The key here is to separate pathogenic variants from others. Instead of requiring users to take variant output and conduct annotation on other platforms, we integrated the functional and clinical annotation within the CRISPR-detector platform so that users can directly access clinical results.

Acknowledgments: We would like to thank Dr. Gao Qianqian for advising on our web server and providing sequencing data and colleagues at EHBIO Gene Technology (Beijing) for the guidance and help in constructing the web server. The authors declare that the research was conducted in the absence of any commercial or financial relationships that could be construed as a potential conflict of interest.

Funding: This work was supported by the Fundamental Research Funds for the Central Public Welfare Research Institutes (ZZ13-YQ-095 and ZZXT201708).

Author contributions: Y.J., T.C. and D.W. designed the study. L.H., D.W., H.C. and D.Z. wrote the bioinformatic pipelines. L.H., D.W. and H.S. designed the web server. L.H., H.C., X.D., C.L., A.L., X.S. and C.Q. acquired the data. L.H., J.H. and H.C. analyzed and interpreted the data. D.W., J.H. and L.H. drafted the manuscript. Y.J. and D.W. supervised the project and edited the manuscript. Y.J. provided the funding. J.H. and D.W. revised the manuscript critically for important intellectual content. All authors read and approved the final manuscript. **Competing interests:** The authors declare that they have no competing interests. **Data and materials availability:** Source code and scripts to simulate sequencing data are available at GitHub (https://github.com/hlcas/CRISPR-detector). WGS datasets available as as the GEO reference series SRP045395. SPACE and ABE8e-NRCH datasets can be accessed at the NCBI Sequence Read Archive (PRJNA609075; PRJNA725249).

References

1. Jinek M, Chylinski K, Fonfara I, et al. A programmable dual-RNA–guided DNA

endonuclease in adaptive bacterial immunity. *Science* 2012;337(6096):816-821.

DOI:10.1126/science.1225829.

2. Cong L, Ran FA, Cox D, et al. Multiplex genome engineering using CRISPR/Cas

systems. *Science* 2013;339(6121):819-823. DOI:10.1126/science.1231143.

3. Zetsche B, Gootenberg J S, Abudayyeh O O, et al. Cpf1 is a single RNA-guided

endonuclease of a class 2 CRISPR-Cas system. *Cell* 2015;163(3):759-771.

DOI:10.1016/j.cell.2015.09.038.

4. Abudayyeh O O, Gootenberg J S, Konermann S, et al. C2c2 is a single-component

programmable RNA-guided RNA-targeting CRISPR effector. *Science*

2016;353(6299):aaf5573. DOI:10.1126/science.aaf5573.

5. Liu J J, Orlova N, Oakes B L, et al. CasX enzymes comprise a distinct family of

RNA-guided genome editors. *Nature* 2019;566(7743):E8-E10. DOI:10.1038/s41586-

019-0908-x.

6. Pausch P, Al-Shayeb B, Bisom-Rapp E, et al. CRISPR-CasΦ from huge phages is a

hypercompact genome editor. *Science* 2020;369:333-337.

DOI:10.1126/science.abb1400.

7. Komor AC, Kim YB, Packer MS, et al. Programmable editing of a target base in

genomic DNA without double-stranded DNA cleavage. *Nature* 2016;533(7603):420-

424. DOI:10.1038/nature17946.

8. Kim Y B, Komor A C, Levy J M, et al. Increasing the genome-targeting scope and

precision of base editing with engineered Cas9-cytidine deaminase fusions. *Nat*

Biotechnol 2017;35(4):371-376. DOI:10.1126/science.abb1400.

9. Gaudelli NM, Komor AC, Rees HA, et al. Programmable base editing of A•T to

G•C in genomic DNA without DNA cleavage. *Nature* 2017;551(7681):464-471.

DOI:10.1038/nature24644.

10. Anzalone AV, Randolph PB, Davis JR, et al. Search-and-replace genome editing

without double-strand breaks or donor DNA. *Nature* 2019;576(7785):149-157.

DOI:10.1038/s41586-019-1711-4.

11. Lu Y, Xue J, Deng T, et al. Safety and feasibility of CRISPR-edited T cells in

patients with refractory non-small-cell lung cancer. *Nat Med* 2020;26:732–740.

DOI:10.1038/s41591-020-0840-5.

12. Frangoul H, Altshuler D, Cappellini MD, et al. CRISPR-Cas9 Gene Editing for

Sickle Cell Disease and β-Thalassemia. *N Engl J Med* 2021;384(3):252-260.

DOI:10.1056/NEJMoa2031054.

13. Gillmore JD, Gane E, Taubel J, et al. CRISPR-Cas9 In Vivo Gene Editing for

Transthyretin Amyloidosis. *N Engl J Med* 2021;385(6):493-502.

DOI:10.1056/NEJMoa2107454.

14. Güell M, Yang L, Church G M. Genome editing assessment using CRISPR

Genome Analyzer (CRISPR-GA). *Bioinformatics* 2014;30(20): 2968-2970:

DOI:10.1093/bioinformatics/btu427.

15. Xue L J, Tsai C J. AGEseq: analysis of genome editing by sequencing. *Mol Plant*

2015;8(9): 1428-1430. DOI:10.1016/j.molp.2015.06.001.

16. Varshney GK, Pei W, LaFave MC, et al. High-Throughput Gene Targeting and

Phenotyping in Zebrafish Using CRISPR/Cas9. *Genome Res* 2015;25(7):1030-42.

DOI:10.1101/gr.186379.114.

17. Park J, Lim K, Kim J S, et al. Cas-analyzer: an online tool for assessing genome

editing results using NGS data. *Bioinformatics* 2017;33(2): 286-288.

DOI:10.1093/bioinformatics/btw561.

18. Pinello L, Canver MC, Hoban MD, et al. Analyzing CRISPR genome-editing

experiments with CRISPResso. *Nat Biotechnol* 2016;34(7):695-697.

DOI:10.1038/nbt.3583.

19. Clement K, Rees H, Canver M C, et al. CRISPResso2 provides accurate and rapid

genome editing sequence analysis. *Nat Biotechnol* 2019;37(3):224-226.

DOI:10.1038/s41587-019-0032-3.

20. Landrum M J, Lee J M, Benson M, et al. ClinVar: improving access to variant

interpretations and supporting evidence. *Nucleic Acids Re*s 2018;46(D1): D1062-

D1067. DOI:10.1093/nar/gkx1153.

21. Freed D, Pan R, Aldana R. TNscope: Accurate Detection of Somatic Mutations

with Haplotype-based Variant Candidate Detection and Machine Learning Filtering.

2018; https://biorxiv.org/content/10.1101/250647v1.

22. Li H. Minimap2: pairwise alignment for nucleotide sequences. *Bioinformatics*

2018; 34(18):3094-3100. DOI:10.1093/bioinformatics/bty191.

23. Wang K, Li M, Hakonarson H. ANNOVAR: functional annotation of genetic

variants from high-throughput sequencing data. *Nucleic Acids Res* 2010;38(16):e164-

e164. DOI:10.1093/nar/gkq603.

24. Gao Q, Ouyang W, Kang B, et al. Selective targeting of the oncogenic KRAS

G12S mutant allele by CRISPR/Cas9 induces efficient tumor regression. *Theranostics*

2020;10(11):5137. DOI:10.7150/thno.42325.

25. Huang W, Li L, Jason R. Myers, et al. ART: a next-generation sequencing read

simulator, *Bioinformatics* 2012;28(4);593-594. DOI:10.1093/bioinformatics/btr708.

26. García-Nieto, P.E., Morrison, A.J. & Fraser, H.B. The somatic mutation landscape

of the human body. *Genome Biol* 2019;20:298. DOI:10.1186/s13059-019-1919-5.

27. Bao X R, Pan Y, Lee C M, et al. Tools for experimental and computational

analyses of off-target editing by programmable nucleases. *Nat Protoc* 2021;16(1):10-

26. DOI:10.1038/s41596-020-00431-y.

28. Ewing, A., Houlahan, K., Hu, Y. et al. Combining tumor genome simulation with

crowdsourcing to benchmark somatic single-nucleotide-variant detection. *Nat*

Methods 2015;12:623-630. DOI:10.1038/nmeth.3407.

29. Wu, Y., Zhou, H., Fan, X. et al. Correction of a genetic disease by CRISPR-Cas9-

mediated gene editing in mouse spermatogonial stem cells. *Cell Res* 2015;25:67-79.

DOI:10.1038/cr.2014.160.

30. Grünewald J, Zhou R, Lareau C A, et al. A dual-deaminase CRISPR base editor

enables concurrent adenine and cytosine editing. *Nat Biotechnol* 2020;38(7): 861-864.

DOI:10.1038/s41587-020-0535-y.

31. Tsai SQ, Nguyen NT, Malagon-Lopez J, Topkar VV, Aryee MJ, Joung JK.

CIRCLE-seq: a highly sensitive in vitro screen for genome-wide CRISPR-Cas9

nuclease off-targets. *Nat Methods* 2017;14(6):607-614. DOI:10.1038/nmeth.4278.

32. Bae S, Park J, Kim JS. Cas-OFFinder: a fast and versatile algorithm that searches

for potential off-target sites of Cas9 RNA-guided endonucleases. *Bioinformatics*

2014;30(10):1473-1475. DOI:10.1093/bioinformatics/btu048.

33. Newby, G.A., Yen, J.S., Woodard, K.J. et al. Base editing of haematopoietic stem

cells rescues sickle cell disease in mice. *Nature* 2021;595:295-302.

DOI:10.1038/s41586-021-03609-w.

34. Zook, J.M., Hansen, N.F., Olson, N.D. et al. A robust benchmark for detection of

germline large deletions and insertions. *Nat Biotechnol* 2020;38:1347-1355.

DOI:10.1038/s41587-020-0538-8.

35. Guo J, Shi C, Chen X, et al. stLFRsv: A Germline Structural Variant Analysis

Pipeline Using Co-barcoded Reads. *Front. Genet*

2021;12:636239. DOI:10.3389/fgene.2021.636239.

36. Sedlazeck F J, Rescheneder P, Smolka M, et al. Accurate detection of complex

structural variations using single-molecule sequencing. *Nat Methods* 2018;15(6):461-

468. DOI:10.1038/s41592-018-0001-7.

559   **Figures and Tables**

amplicon	n_reads|treatment	n_reads|control	substitution%	insertion%	deletion%	indel%	modified%
ON	51326	28370	0.89	3.62	5.21	8.00	8.00
OT1	31944	16035	0.00	0.00	0.00	0.00	0.00
OT2	14963	12116	0.00	0.00	0.00	0.00	0.00
OT3	30303	16208	0.00	0.00	0.00	0.00	0.00
OT4	18801	20543	9.63	0.00	0.00	0.00	9.63
OT5	27888	35844	0.00	0.00	0.00	0.00	0.00
OT7	42631	42635	0.00	0.00	0.00	0.00	0.00
OT8	14040	29633	0.00	0.00	0.00	0.00	0.00
OT9	12976	25703	0.00	0.00	0.00	0.00	0.00
OT10	27942	19998	0.00	0.00	0.00	0.00	0.00
OT11	37896	45899	0.00	0.00	0.00	0.00	0.00
OT12	32091	65750	0.00	0.00	0.00	0.00	0.00
OT13	58203	25622	0.00	0.00	0.00	0.00	0.00
OT14	26453	35578	0.00	0.00	0.00	0.00	0.00

562   **Table 1. Example result for all loci.** A downloadable table summarizing the number

563   of processed reads and the frequency of different types of mutations on all the input

564   loci.

Reads Type	CRISPR-detector			CRISPResso2			Cas-Analyzer		AGEseq	
	Mutated reads (%)	Accuracy (%)	Average Running time (s)	Mutated reads (%)	Accuracy (%)	Average Running time (s)	Mutated reads (%)	Accuracy (%)	Mutated reads (%)	Accuracy (%)
unmodified	0.0	100.0	2	8.3	91.7	14	18.3	81.7	14.4	85.6
1 substitution	49.9	99.9	2	54.5	95.5	13	58.8	91.3	57.3	92.7
2 substitutions	50.0	100.0	2	53.6	96.4	14	58.5	91.5	57.1	93.0
3 substitutions	50.0	100.0	2	54.9	95.1	13	59.6	90.5	57.0	93.1
5 bp insertion	49.9	99.9	2	54.1	95.9	14	59.9	90.1	57.5	92.6
10 bp insertion	49.9	99.9	2	54.9	95.1	13	58.8	91.3	56.3	93.7
50 bp insertion	48.9	98.9	2	54.9	95.1	14	56.7	93.3	56.9	93.1
5 bp deletion	49.9	99.9	2	54.9	95.1	14	58.9	91.2	57.5	92.5
10 bp deletion	49.9	99.9	2	55.5	94.5	13	58.9	91.1	57.5	92.5
50 bp deletion	48.9	98.9	2	53.9	96.1	13	59.3	90.8	57.2	92.8

579 **Table 2. Accuracy and processing time of a single amplicon.** Compared to

580 CRISPResso2, CRISPR-detector showed 7 times faster processing speed, and the

581 nearly 100% accuracy also outperformed CRISPResso2.

Indel frequencies (%)	CRISPR-detector			CRISPResso2		
	Mutated Reads (%)	Indel (%)	Accuracy (%)	Mutated Reads (%)	Indel (%)	Accuracy (%)
0.1	0.10	0.10	100.00	9.01	0.12	80.00
1	1.00	1.00	100.00	10.16	1.01	99.00
10	10.01	10.01	99.90	18.46	10.03	99.70
100	100.00	100.00	100.00	100.00	100.00	100.00

584 **Table 3. Performance on 0.1%-100% indel frequencies.** CRISPR-detector

585 outperformed CRISPResso2 at low frequency indels detection accuracy.

Simulated Reads Type					Variant Detected	
Control Reads Type	Inserted Reads Type	POS	REF	ALT	Mutated reads (%)	Accuracy (%)
1 substitution	1 substitution & 1 bp insertion	105	-	C	49.6	99.6
2 substitutions	2 substitutions & 1 bp insertion	105	-	C	47.9	97.9
3 substitutions	3 substitutions & 1 bp insertion	105	-	C	47.9	97.9
5 bp deletion	5 bp deletion & 1 bp insertion	105	-	C	49.8	99.8
10 bp deletion	10 bp deletion & 1 bp insertion	105	-	C	65.8	84.2
50 bp deletion	50 bp deletion & 1 bp insertion	105	-	C	64.0	86.0
5 bp insertion	5 bp insertion & 1 bp insertion	105	-	C	48.5	98.5
10 bp insertion	10 bp insertion & 1 bp insertion	105	-	C	48.2	98.2
50 bp insertion	50 bp insertion & 1 bp insertion				Failed	

595 **Table 4. Identification of insertion at position 105 using co-analysis dataset.** For

596 all read types except the 50 bp insertion, CRISPR-detector successfully identified true

597 editing events without false positive from variants existing in control samples.

AF > 5%	SNV		Insertions (1-50 bp)		Deletions (1-72 bp)	
	Sensitivity%	Specificity%	Sensitivity%	Specificity%	Sensitivity%	Specificity%
100x co-analysis	87.7	82.4	58.3	39.3	56.5	37.0
100x edited only	96.4	41.4	55.6	13.9	71.7	18.3
AF > 15%	SNV		Insertions (1-50 bp)		Deletions (1-72 bp)	
	Sensitivity%	Specificity%	Sensitivity%	Specificity%	Sensitivity%	Specificity%
30x co-analysis	98.8	99.3	13.3	50.0	23.7	66.7
30x edited only	97.3	70.9	16.7	18.8	23.7	27.3

600 **Table 5: Performance on synthetic WGS datasets. SNVs and indels are**

601 **tested.** Co-analysis showed better accuracy than only analyzing edited sample,

602 especially specificities. Due to a much larger analysis region, accuracy of WGS is

603 lower than that from amplicons.

Reads Type		30x Short Reads	100x Co-barcoded Reads		100x Long Reads
SV Length	Pipeline	TNscope	Smoove	Long Ranger	Sniffles
50-1000 bp	TP	1268	724	2304	4168
	FP	302	248	1279	5285
	FN	3451	3995	2415	551
	Recall	26.87%	15.34%	48.82%	88.32%
	Precision	80.76%	74.49%	64.30%	44.09%
> 1000 bp	TP	445	463	558	570
	FP	212	162	385	447
	FN	172	154	59	47
	Recall	72.12%	75.04%	90.44%	92.38%
	Precision	67.73%	74.08%	59.17%	56.05%

611 **Table 6. SV accuracy benchmark.** In the 50 bp - 1 kb group, CRISPR-detector

612 reaches 26.87% recall and 80.76% precision and slightly outperforms Smoove. Long

613 Ranger returned similar accuracy to CRISPR-detector, and Sniffles returns better

614 recall than any other callers. For longer deletions (>1k), CRISPR-detector's accuracy

615 score is slightly lower than co-barcoded or long-read callers.

	CRISPR-detector	CRISPResso1/2	Cas-Analyzer	AGEseq	CRISPR-GA	ampliconDIVider
Web-based	√	√	√	√	√	
Editing tools	Any	Any	Cas9/Cpf1/ZFN/TALEN/dCas9-Fok1	Any	Any	Cas9
Pooled amplicon sequencing data	√	√		√		
WGS data	Whole genome anaylsis	Regions of interest				
Mutation types	Substitution; Indels; SV	Substitution; Indel	Indel	Substitution; Indel	Indel	Indel
Vector detection	√					
Inter-sample comparison	√	√				
Genetic background removal	√					
Functional annotations	Frameshift; Non-synonymous substitution; Startloss/Stopgain	Frameshift; Splice site				
Pathogenic annotation	√					

Table 7. Comparing functions of tools that assess genome editing results. Several

widely-used tools for analyzing genome editing NGS data.

Fig. 1. Flowchart of CRISPR-detector. CRISPR-detector accepts single/pooled

amplicon deep-sequencing as well as whole genome sequencing data as input. Control

group sample is utilized for removing background variants existing prior to genome

editing for treatment group sample. CRISPR-detector outputs visualizations results

and functional annotations of editing-induced mutations for targeted amplicon

sequencing data, and VCF format text file for whole genome sequencing data.

Fig. 2. Example result for single locus. (A) Frequency of identified substitutions and

indels across the amplicon; **(B)** Indel size distribution; **(C)** Detailed information on

mutations including the annotation on this locus.

Fig. 3. Accuracy benchmark on 1-50 bp insertions and 1-72 bp deletions. (A)

Both CRISPR-detector and CRISPResso2 correctly report 1-50 bp insertions, while

CRISPR-detector shows slightly higher accuracy. **(B)** CRISPR-detector is capable of

reporting 1-71 bp deletions while CRISPResso2 only reports 1-52 bp deletions.

Fig. 4. Accuracy and speed for 200 amplicon testing. (A) CRISPR-detector

outperforms CRISPResso2 on accuracy; **(B)** CRISPR-detector runs 8 times faster than

CRISPResso2.

Scenario 1: Insertion	Break Point	Inserted Chromosome	Inserted Position	AAV position	Supported Reads Number
	bnd_0	chr22	29807035	pAAV-MCS:101	11
	bnd_2	chr22	29807038	pAAV-MCS:2102	14

Scenario 2: Reverse Insertion	Break Point	Inserted Chromosome	Inserted Position	AAV position	Supported Reads Number
	bnd_4	chr22	30910099	pAAV-MCS:3500	10

Scenario 3: Non-AAV Insertion	Break Point	Inserted Chromosome	Inserted Position	AAV position	Supported Reads Number
	None				

Scenario 4: Partially swap	Break Point	Inserted Chromosome	Inserted Position	AAV position	Supported Reads Number
	bnd_8	chr22	45434256	pAAV-MCS:3501	9
	bnd_10	chr22	45434753	pAAV-MCS:4200	10

Scenario 5: Insertion with added sequences	Break Point	Inserted Chromosome	Inserted Position	AAV position	Supported Reads Number
	bnd_14	chr22	48273825	pAAV-MCS:1246	22
	bnd_12	chr22	48273826	pAAV-MCS:2308	15

Fig. 5. AAV sequence insertion detection. Five simulated scenarios tested, including insertion, reverse insertion, non-AAV sequence insertion, partial swap, and insertion with foreign sequences. CRISPR-detector returned the correct insertion location.