GENERALIZATION IN SENSORIMOTOR NETWORKS CONFIGURED WITH NATURAL LANGUAGE INSTRUCTIONS

Reidar Riveland
Department of Basic Neuroscience
University of Geneva
reidar.riveland@unige.ch

Alexandre Pouget
Department of Basic Neuroscience
University of Geneva
alexandre.pouget@unige.ch

November 30, 2022

ABSTRACT

One of humans' most fundamental cognitive feats is the ability to interpret linguistic instructions in order to perform novel tasks without any explicit experience with the task. Yet, the computations that the brain might use to accomplish such a feat remains poorly understood. Here we use the latest advances in Natural Language Processing to create a neural model of generalization based on linguistic instructions. Models are trained on a set of commonly studied psychophysical tasks, and receive instructions embedded by a pre-trained language model. Our best models can perform a previously unseen task with a performance of 85% correct on average based solely on linguistic instructions (i.e. 0-shot learning). We found that language scaffolds sensorimotor representations such that activity for interrelated tasks share a common geometry with the semantic representations of instructions, allowing language to cue the proper composition of practiced skills in unseen settings. Finally, we show how this model can generate a linguistic description of a novel task it has identified using only motor feedback, which can subsequently guide a partner model to perform the task. Our models offer several experimentally testable predictions outlining how linguistic information must be represented in order to facilitate flexible and general cognition in the human brain.

Keywords Natural Language Processing · Cognitive Control · Computational Neuroscience

Introduction

In a laboratory setting, animals require numerous trials carefully presented over a period of weeks in order to acquire a new behavioral task. This is in part because the only means of communication with non-linguistic animals is simple positive and negative reinforcement signals. By contrast, it is common to give written or verbal instructions to human subjects which allows them to perform new tasks relatively quickly. For instance, a subject told to 'press the button in the direction of the stimulus presented with highest intensity', would know what to do right away. Indeed, for simple tasks like this one, human subjects would perform nearly perfectly on the very first trial (i.e. 0-shot learning), even if they had no previous experience with the particular task. Alternatively, human subjects can also learn to correctly perform a task in the absence of linguistic instructions, e.g. through positive and negative reinforcement, and, once training is completed, subjects can typically explain how they solved the task with natural language.

The dual ability to use the information in an instruction to immediately perform a novel task and, conversely, produce a linguistic description of the demands of a task once it has been learned are two unique cornerstones of human communication. Yet, the computational principles and representational structures that underlie these abilities remain poorly understood.

One influential systems-level explanation of our ability to generalize performance posits that flexible inter-region connectivity in the prefrontal cortex (PFC) allows for the reuse of practiced sensorimotor representations in novel settings [1, 2, 3, 4, 5]. By recombining practiced stimulus-response patterns according to the ostensible demands of a previously unseen task, we can leverage well-established abilities and perform on new tasks in very few practice trials. More

recently, multiple works have observed that when subjects are required to flexibly recruit different stimulus-response patterns in order to switch between tasks, neural representations are organized according to the abstract structure of the task set [6, 7, 8, 9]. This disentangled geometry may allow for the easy reuse of task sub-components. Lastly, recent modeling work has begun to explore the neural mechanisms of compositional computation in a non-linguistic setting. For example, a recurrent neural network (RNN) trained on a set of psychophysical tasks will share dynamical motifs across tasks with similar demands (e.g. the same ring attractor to store a circular variable across tasks that require memory). By reusing underlying computational dynamics networks exhibit faster learning in novel settings. This work forms a strong basis for explanations of flexible cognition in humans but leaves open the essential question of how linguistic information by itself can immediately reconfigure a sensorimotor network so that it performs a novel task well on the very first attempt. From the opposite perspective, few studies have investigated the linguistic and semantic processing hierarchy that directly informs sensorimotor control (although see [10], [11], [12], [13]). Overall it remains unclear what representational structure we should expect from brain areas that are responsible for integrating linguistic information in order to reorganize sensorimotor mappings on the fly.

These questions become all the more pressing given that recent advances in machine learning have led to artificial intelligent systems that exhibit human-like language skills, both within the language domain itself and in multi-modal settings [14, 15, 16]. Recent works have matched neural data recorded during passive listening and reading tasks to activations in autoregressive language models (e.g. GPT), arguing that there is a fundamentally predictive component to language comprehension [17, 18]. However, comprehension during passive listening is only one of many interrelated notions of linguistic knowledge. Indeed, part of the essential utility of understanding language is not simply that we can exchange information between individuals, but further that each individual can correctly interpret and then execute the actions that this linguistic information suggests we take. Some high-profile machine learning models do show the ability to use natural language as a prompt to perform a linguistic task or render an image, but these models are designed with a specific engineering goal in mind and, especially in text-to-image models, this makes their outputs difficult to interpret in terms of a sensorimotor mapping that we might expect to occur in a biological system. We therefore seek a setting where we can leverage the power of these language models in a way that results in tractable neural predictions on how the human brain processes natural language in order to generalize across sensorimotor tasks.

To that end, we train a recurrent neural network (Sensorimotor-RNN) model on a set of simple psychophysical tasks. On each trial, the model receives natural language instructions for the present task embedded through a transformer architecture pre-trained on one of several natural language processing objectives. Both the type of tasks we use and the neural network modeling of such tasks have a rich history in the experimental and computational neuroscience literature respectively [19, 20, 21, 22, 23, 24, 25].

We find that instruction embeddings produced by models which learn to jointly embed images and language together (i.e. a multi-modal objective) allow Sensorimotor-RNNs to perform an entirely novel task at 85% correct on average. By contrast, models trained on next-word prediction performed relatively poorly despite massive advantages in model size and pre-training scope. Generalization in our models is supported by a representational geometry which captures task subcomponents and is shared between instruction embeddings and sensorimotor activity. In our best performing models, this structure emerges as activity ascends the language processing hierarchy. We also find that individual neurons modulate their tuning based on the semantics of instructions. Finally, we demonstrate how a network trained to interpret linguistic instructions can invert this understanding and produce a linguistic description of a previously unseen task based on the information in motor feedback signals. Communicating these instructions to a partner model results in a performance of 85% across tasks compared to 26% performance when directly sharing latent task representations, demonstrating the importance of natural language as an information encoding scheme that is shared between otherwise independent sets of neurons. To our knowledge, this is the first neural model demonstrating how a sensorimotor network can exploit linguistic information to generalize performance and communicate task knowledge.

Results

Instructed models and task set.

To examine how linguistic information leads to generalization across sensorimotor tasks, we train Sensorimotor-RNNs on a set of 50 interrelated psychophysical tasks that require various cognitive capacities which are well-studied in the literature [23]. These include perceptual decision-making [19, 22], inhibitory control [26], matching tasks [27, 28], confidence judgements [29], context-dependent tasks [20], time estimation, [21] and combinations of these and other skills. For all tasks, models receive a sensory input and task-identifying information and must output motor response activity appropriate for the task (Fig. 1a). Input stimuli are encoded by two 1-D maps of neurons, each representing a different input modality, with periodic Gaussian tuning curves to angles (over $[0, 2\pi]$). As a result, a specific input value, i.e., a specific angle, is encoded by a hill of activity across the 1D maps. Output responses are encoded in the same way,

Figure 1 | Instructed Models Learn the Task Set. a. Diagram of models: SIMPLENET consists of an RNN that receives information about the current task through 1 of 50 orthogonal rule vectors indexing each task. Instructed Models use an identical RNN, but receive information about task type by embedding a natural language instruction for the task using a pre-trained transformer architecture. Example instruction for the 'AntiDM' task shown. **b.** Example trials for 4 tasks, consisting of a fixation unit (fix.) two sensory modalities (mod.1, mod. 2) and target response. In each case, identical inputs require varying responses across different tasks.

via hills of activity, encoding specific output angles. Our 50 tasks are roughly divided into 5 groups, 'Go', 'Decision Making', 'Comparison', 'Duration' and 'Matching', where within group tasks share similar sensory input structures but may require divergent responses. For instance, in the decision making task (DM), the network must respond in the direction of the stimulus with the highest contrast immediately after the extinction of the fixation point whereas in the anti-decision making task (AntiDM), the network must instead respond in the direction of the stimulus with the weakest contrast (Fig. 1b). Fig. 1b also illustrates a delayed match to stimuli (DMS) task and a delayed non-match to stimuli (DNMS) task, which also require different responses for the same input. Given the possibility of such divergent responses, networks must properly infer the task demands for a given trial from task-identifying information in order to perform all tasks simultaneously (see Methods for task details, see Supplementary Info. 12 for example trials of all tasks).

In our models, task-identifying input is either non-linguistic or linguistic. For our non-linguistic control model, called SIMPLENET, the identity of a task is represented by one of 50 orthogonal rule vectors which index each task (Fig. 1a, SIMPLENET). As an added control we also test a non-linguistic model with additional densely connected layers between the task rule and the Sensorimotor-RNN called SIMPLENETPLUS.

Instructed Models use a pre-trained transformer architecture [30] to embed natural language instructions for the tasks at hand. These embeddings are then passed to the Sensorimotor-RNN as task-identifying information (Fig. 1a, Instructed Models). Crucially, for each task we formulate a set of 20 unique instructions (15 training, 5 validation), forcing instructed models to leverage the semantics shared across different formulations of descriptions for the same task (see Supplementary Info. 10 for full instruction set).

We test various types of language models that share the same basic architecture but differ in their size and also their pre-training objective, which endows them with different kinds of linguistic knowledge. First, we tested two autoregressive models, GPT and GPTXL, which are trained to predict the next word in a text given all the preceding context [31]. This allows the model to complete texts from prompts with striking fluency [32]. Previous work has demonstrated that GPT can account for continuous next-word prediction and degree of surprise for unexpected words in ECoG data from participants listening to narrative stories [18], whereas activations from the hidden layers of GPTXL

are predictive of of fMRI and EEG data taken from language areas while humans read sentences [17]. This validation against neural data makes it an important benchmark for computational models of language processing in humans. The BERT model receives bi-directional inputs and is trained to identify masked words within a piece of text [33]. BERT also uses a simple unsupervised sentence level objective, in which the network is given two sentences and must determine whether they follow each other in the original text. S-BERT [34] is trained like BERT but receives additional tuning on the Stanford Natural Language Inference task [57], a hand-labeled dataset detailing the logical relationship between two candidate sentences (see Methods). Lastly, we also use the language embedder from CLIP, a multi-modal model which learns a joint embedding space of images and their text captions [36]. Importantly, the clip text encoder isn't exposed to any word-level predictive pre-training and derives its linguistic knowledge wholly from training to match the latent spaces of both linguistic and visual modalities.

We use a basic model size of 100M parameters for GPT, BERT, and S-BERT. GPTXL is an order of magnitude larger with 1.5 billion parameters while CLIP uses 60M parameters. We call a Sensorimotor-RNN using a given language model to embed instructions LANGUAGEMODELNET (e.g. GPTNET for a model that embeds instructions using GPT). For each language model we average the last hidden state of the transformer over the instruction length and pass this fixed length representation through a set of linear weights that results in a 64-dimensional instruction embedding across all models. This last set of linear weights trains with the Sensorimotor-RNN on our task set whereas transformer weights are frozen. Finally, as a control we also test a shallow, Bag of Words embedding scheme that only uses word count statistics to embed each instruction.

First, we verify our models can perform all tasks simultaneously. For non-linguistic *simpleNet* high performance across all tasks is simply a question of the representational power of the Sensorimotor-RNN, as the contextual information about each task is already perfectly separated. The problem is more complicated with linguistic inputs because models must first infer the common semantic content between 15 distinct instruction formulations for each task before it can properly select the relevant mapping in the Sensorimotor-RNN. We find that all of our instructed models can process linguistic instructions to perform the entire task set simultaneously except for GPTNET, in which case performance asymptotes below the 95% threshold for some tasks. Hence, we relax the performance threshold to 85% for models which use GPT to embed instructions (Supplementary Info. Fig. 1, see Methods for training details).

To test whether our model can generalize performance to new linguistic instructions for the learned tasks, we tested all architectures on a set of validation instructions, with no further training (Supplementary Info. Fig. 2). In general, CLIPNET and SBERTNET are our best performing models, achieving an average performance of 95% and 94% respectively on validation instructions. This demonstrates that networks infer the proper semantic content even for entirely novel instructions. All other models achieve a performance of greater than 80% averaged across all tasks, but unlike CLIPNET and SBERTNET, exhibit individual tasks where performance drops below 50%.

Generalization to novel tasks.

We next examine how training networks to perform tasks with natural language instructions can help those networks generalize performance to novel tasks. To this end, we trained individual networks on 45 tasks and then tested network performance when exposed to each of the 5 held out tasks. Results are shown in Fig. 2.

Our uninstructed control model SIMPLENET performs at 39% on average on the very first presentation of the novel tasks (0-shot generalization). This serves as a baseline for generalizing performance, as orthogonal task rules contain no information about how tasks relate to one another. Note that given how we score trials and the continuous nature of motor outputs (see Methods), a random network would effectively perform at 0% correct. However, any exposure to the task set will also allow models to learn the basic structure of tasks (e.g. always repress response during fixation, always respond to a coherent angle etc.). In these cases, even though models have no knowledge about specific task demands they can nonetheless make better guesses. Therefore, 39% is not random level performance per se, but rather baseline performance achieved by the default response mode of a network trained and tested on a task set with shared structure. The added representational power in SIMPLENETPLUS doesn't aid in this generalization, achieving just 37% on average across tasks.

Next we tested generalization in networks that received linguistic instructions. GPTNET, exhibits a 0-shot generalization of 57%. This is a definite improvement over our non-linguistic model. Strikingly though, the relatively large size and extensive pre-training of GPT produces generalization performance which remains well below BOWNET, which achieves a performance of 64% on unseen tasks. Perhaps even more striking is that increasing the size of GPT by an order of magnitude to the 1.5 billion parameters used by GPTXL only results in modest gains over BOWNET, with GPTNETXL achieving 68% on held out tasks. BERTNET achieves a slightly better generalization performance than BOWNET of 66%, and only lags 2% behind GPTNETXL despite using less than one tenth the number of parameters. Next we tested models using SBERT to embed instructions. SBERT starts from the pre-trained weights of BERT but

Figure 2 | Model Performance on Novel Tasks. a. Learning curves for the first 100 exposures to held out tasks averaged over all tasks for models with five random initialization. **b.** Histogram showing distribution of zero-shot performance across tasks.

also learns from an additional supervised objective designed to produce good sentence embeddings [34, 57]. With this model we see a large separation in generalization performance compared to the language models tested above which mostly use word-level pre-training objectives. SBERTNET can perform an unseen task at 79% correct on average. Finally, we find that our best performing model CLIPNET can perform a never before seen task with a performance of 85% on average. This is a notable result primarily because of the multi-modal nature of the pre-training objective that shapes the instruction embeddings in CLIP. That these embeddings produce such strong generalization is especially striking given that different task demands must sometimes be inferred entirely from subtle linguistic cues like word ordering and clause structure (e.g. in the 'Comparison' and 'Duration' task groups). Fig. 2b. shows a histogram of the number of tasks for which each model achieves a given level of performance. Again, CLIPNET manages to perform over half of the task set nearly perfectly in the zero-shot setting.

To validate that our best performing models truly leveraged the semantics of instructions to generalization performance, we presented the network with the sensory input for one held out task, while providing the linguistic instructions for a different held out task. Models that truly infer the proper sensorimotor response based on the semantic content of instructions should be most penalized by this manipulation. As predicted, swapping instructions destroys the capacity to generalize in all of our instruction models (reducing CLIPNET to 31% correct averaged across tasks, Supplementary Info. Fig. 4.1).

In line with some past studies [23], we also tested models in a setting where task type information for a given task was represented as a composition of information for related tasks in the training set. As an example, for SIMPLENET an 'AntiDMMod1' task would be represented as $(rule(\text{AntiDMMod2}) - rule(\text{DMMod2})) + rule(\text{DMMod2})$. In an important way this is an unfair comparison: we are giving the model oracle knowledge about how the previously unseen test task relates to tasks the network has acquired during training, and this is exactly the problem that our successful language models ostensibly solve. Nevertheless, we find that even when provided this knowledge, SIMPLENET with compositional rules achieves only 60% correct across tasks, worse than all our instructed models. Further, for models trained on all tasks, using compositional rules for SIMPLENET *reduces* performance to 65% down from 99% when using standard rules. By contrast, using the equivalent composition of the relevant instruction embeddings for CLIPNET results in sustained performance of 87% across held out tasks and 95% for models trained on all tasks (Supplementary Info. Fig. 5).

We also test a more stringent hold-out procedure where we purposefully choose 4-6 tasks from the same family of tasks to hold-out during training, forcing models to infer an entire set of interrelated sensorimotor mappings from language instructions (Supplementary Info. Fig. 4.2). Overall, performance decreases in this more difficult setting though our best performing model still shows strong generalization, with CLIPNET achieving 73% correct on novel tasks, well above the performance of SIMPLENET at 39%.

The discrepancy in performance between our instructed models is striking given that each model used to embed instructions exhibits impressive language skills in their own right. Most notable is the gulf in zero-shot generalization between CLIPNET (85%) and GPTNETXL (68%) which exists despite the discrepancy in size (CLIPNET uses 4% of the number of parameters used by GPTNETXL), the fact that they share the same basic architecture, and the ability of GPTXL to generate fluid sentences from a prompt. Taken together these results strongly suggest that in order to represent linguistic information such that it can successfully configure sensorimotor networks, it isn't sufficient to simply use any very powerful language processing system. Rather the problem of generalizing based on instructions requires a specific type of linguistic processing, which tends to emerge from models that seek good embeddings of entire sentences, especially using multi-modal objectives. With our models we can also induce a kind of rudimentary multi-modal language processing scheme by allowing the weights of language models to tune according to the loss experienced during sensorimotor training. This manipulation improves the generalization performance across all models (except for CLIPNET where performance slightly declines), though the relative ranking of model performance is unchanged (Supplementary Info. Fig. 4.3).

Next, we move to an analysis of the instruction embedding spaces produced by different language models, the resultant structure in Sensorimotor-RNN activations across different tasks, and how shared geometry between both these spaces aids in generalization.

Shared structure in language and sensorimotor networks support generalization.

In order to assess what properties of language embeddings lead to strong generalization across sensorimotor tasks, we first examined the representations that emerge in Sensorimotor-RNNs and in the final layer of our language models across different tasks.

First, we note that like in other multitasking models, units in our Sensorimotor-RNNs exhibit functional clustering, where similar subsets of neurons show high variance across similar sets of tasks (Supplementary Info. Fig. 6). Moreover, we find that models can learn unseen tasks by only training Sensorimotor-RNN input weights and keeping the recurrent dynamics constant (Supplementary Info. Fig. 7). Past work has shown that this clustering and the ability to recruit new skills while recurrent dynamics are fixed are characteristic of networks that are able to factorize their computations and reuse the same set of underlying neural resources across different settings [23, 24].

We then examined the geometry that exists between the neural representations of related tasks. We plotted the first 3 PCs of Sensorimotor-RNN hidden activity at stimulus onset in a CLIPNET, GPTNETXL and SIMPLENET performing modality specific DM and AntiDM tasks. Here models receive input for a decision-making task in both modalities but must only account for the stimuli in the modality relevant for the current task. We observe that a pattern of abstract relations emerges among tasks depending on how instructions are embedded, and afterwards offer a quantitative analysis of this abstract structure across all held out tasks and all models. Results are shown in Fig. 3.

Already, we can see this structure in task representations for models that have been trained on all tasks (Fig. 3a,b,c. Column 1). In particular, activity is organized along task relevant axes, namely a 'Standard' vs. 'Anti' direction in activity space that is consistent whether applied to 'Mod1' or 'Mod2' and therefore abstract with respect to these tasks (dashed arrows). 'Mod1' vs. 'Mod2' conditions are largely separable for SIMPLENET across 'Standard' and 'Anti' versions of the task, though the extent to which they share a consistent axis in activity space and can therefore qualify as abstract is unclear. When we examine the same representations for SIMPLENET with 'AntiDMMod1' held out of training, this structure is largely destroyed, resulting in a zero-shot performance of 22% on 'AntiDMMod1' task (Fig. 3a. Column 2). With tasks held out GPTXLNET also fails to maintain the structure originally observed in the model trained on all tasks, despite the fact that it uses a large and powerful language model to process information about task demands (Fig. 3b. Column 2). This results in a zero-shot performance on 'AntiDMMod1' of 6%. For instructed models we can also examine the relationships in and amongst instruction embeddings that inform computation in the Sensorimotor-RNNs. For GPTXLNET with 'AntiDMMod1' held out of training, instruction embeddings for 'Mod1' vs. 'Mod2' tasks are clearly separable while the 'Standard' vs. 'Anti' tasks in each modality cluster together (Fig. 3b. Column 2), largely reflecting the structure exhibited in sensorimotor task representations. Unlike previous models CLIPNET is able to maintain the abstract geometry of its task representations in a setting where 'AntiDMMod1' has been held out of training, which requires properly inferring the position of 'AntiDMMod1' relative to this geometry despite having never experienced an 'AntiDMMod1' trial during training. In the case of 'AntiDMMod1' this leads to a zero-shot performance of 87% correct. Strikingly, if we examine instruction representation produced by CLIPNET we see that the language model produces the same structured relations among instruction representations that were observed in task representations, again, despite the fact that the model never experiences 'AntiDMMod1' instructions during training.

Figure 3 | Structured Representations in Instructed Models. a.-c. First three PC's of sensorimotor hidden activity in for models trained on all tasks (1st column), for models with 'AntiDMMod1' held out of training (2nd column), for instruction representations in the embedding layer where 'AntiDMMod1' is held out of training. **a.** SIMPLENET **b.** GPTNETXL **c.** CLIPNET **d.** Cross Condition Generalization Performance scores for held out tasks for each layer in the model hierarchy **e.** Correlation between held out task CCGP and zero-shot performance.

To more precisely quantify the structure that may exist between representations of tasks and instructions across the entire task set and all models we measure the Cross Condition Generalization Performance (CCGP) of these representations [6]. CCGP measures the ability of a linear decoder trained to differentiate one set of conditions (e.g. 'DMMod2' and 'AntiDMMod2') to generalize to an analogous set of test conditions (e.g. 'DMMod1' and 'AntiDMMod1'). Intuitively, this captures the extent to which models have learned to place sensorimotor activity along abstract task axes (e.g. the 'Anti' dimension). This measure serves as an important bridge between our models and representations in biological brains, as high CCGP scores and related measures have been observed in experiments that required human participants to flexibly switch between different interrelated tasks [7, 2]. In particular, single-cell recordings in MFC exhibit high CCGP for related task demands, which allows for rapid switching between different task types and output modalities [7]. So far however, no study has investigated how processing linguistic instructions might help shape this structure.

CCGP decoding scores for different layers in our model are shown in Fig. 3d. For each instructed model, scores for 12 transformer layers (the last 12 of a total of 24 transformer layers for GPTNETXL or the entire language model otherwise), the 64-dimensional embedding layer, and the Sensorimotor-RNN task representations are plotted. Importantly, these measures are computed over models with tasks held out of training and so capture how well models infer proper task relations in novel settings (see Methods for details). Among models, there is a notable discrepancy in how abstract structure as measured by CCGP emerges in the hierarchy. Autoregressive models (GPTNETXL, GPTNET) and BERTNET, which generalize poorly relative to other transformer-based instructed models, also show a low CCGP throughout language model layers followed by a jump in CCGP in the embedding layer. This is predominantly because weights feeding into this layer are tuned during sensorimotor training to ensure all Sensorimotor-RNNs receive task information as a 64-dimensional vector. The implication of this spike is that most of the useful representational processing that comes with embedding instructions using these models occurs principally via this final set of weights as opposed to occurring gradually throughout the entire language model hierarchy. By contrast, our best performing models SBERTNET and CLIPNET employ language representations where high CCGP scores emerge gradually through the layers in their respective language models. As a result instructions have been organized according to much of the requisite structure in the last layer of the language model. Finally, the ranking of CCGP scores in Sensorimotor-RNNs closely reflects the ranking of 0-shot performance in Fig. 2a., with CLIPNET exhibiting the most consistent abstract structure for held out tasks and our non-linguistic SIMPLENET lagging far behind instructed models. Indeed, in a more fine-grained analysis we found that the CCGP scores associated with a held out task correlate with the zero-shot performance a model achieved on that task (Fig. 3e.).

This analysis strongly suggests that models exhibiting generalization do so by relating practiced and novel tasks in a structured geometry that captures the relevant subcomponents of each task. Models are able to correctly infer these relations because they are guided by language models which themselves embed task instructions according to the same basic structure. Hence, successful models can leverage the linguistic relations between practiced and novel instruction sets to cue sensorimotor activity for an unseen task in the proper region of RNN activity space relative to this geometry, thereby composing practiced behaviors to perform well in a novel setting.

We can verify this relation again using a task switching test. If language models' ability to properly relate linguistic information contained in novel and practiced instructions is truly responsible for inducing the proper structure for held out task representations, then swapping instructions should destroy this structure and sharply reduce CCGP scores for Sensorimotor-RNNs. As expected, CCGP scores for all instructed models fall below 0.6 with swapped instructions, a worse score than our non-linguistic SIMPLENET (Supplementary Info. Fig. 8).

Semantic modulation of single unit tuning properties.

In the previous section we outlined the structured representational scheme that allows our best performing instructed models to generalize performance to unseen tasks. With our artificial models we can go a step further and examine tuning profiles of individual neurons in our Sensorimotor-RNNs, allowing us to make predictions for single-unit activity in human experiments. As one would expect, we found that individual neurons are tuned to a variety of task relevant variables, such as the position of the input in a 'Go' task, or the difference in intensity between the input stimuli in a decision making task. Critically, however, we find neurons where this tuning varies predictably within a task group and is modulated by the semantic content of instructions in a way that reflects task demands.

For instance, for the 'Go' family of tasks, unit 39 shows direction selectivity that shifts by π between 'Pro' and 'Anti' tasks, reflecting the relationship of task demands in each context (Fig. 4a). This flip in selectivity is observed even for the 'AntiGo' task, which was held out during training. Hence, the observed reversal is induced solely by the linguistic instructions, with no additional training. Again, note that tuning curves are produced by the same set of stimuli, and hence the only factor responsible for the variation in tuning is the input instructions for the task. We make sure to use the full range of instructions for each task.

Figure 4 | Semantic Modulation of Single Unit Tuning Properties a.) Tuning curves for example *clipNet* sensorimotor unit that modulates tuning according to task demands in the 'Go' family. **b.)** Tuning curves for example *clipNet* sensorimotor unit in the 'Matching' family of tasks plotted in terms of difference in angle between two stimuli. **c)** Full activity traces for modality specific 'DM' and 'AntiDM' tasks for different levels of relative stimulus strength. **d)** Full activity traces for tasks in the 'Comparison' family of tasks for different levels of relative stimulus strength.

Additionally, Unit 147 for the 'Matching' family of tasks modulates activity between 'Match' (DMS, DMC) and 'Non-Match' (DNMS, DNMC) conditions when plotted against the relative distance between the two stimuli in the trial. For both, 'DNMS' and 'DNMC' this neuron is active in situations that require the model to respond i.e. in the opposite side of the display for the category task and when the stimuli are far apart for the 'DNMS'. By contrast, for 'Matching' tasks this neuron is most active when the relative distance between the two stimuli is small. Again this is true even for 'DMS' which has been held out of training.

We can also examine how the content of instructions affects the temporal evolution of neural activity for single units across the relevant trial epochs. Fig. 4c. shows traces of Unit 175 activity in modality specific versions of 'DM' and 'Anti DM' tasks ('AntiDMMod1' is held out of training) for different levels of contrast ($contrast = str_{stim1} - str_{stim2}$). In all tasks, we observe ramping activity where the rate of ramping is relative to the strength of evidence (in this case, contrast). This motif of activity has been reported in various previous studies [37, 38]. However, in our models we observe that an evidence accumulating neuron can swap the sign of its integration in response to a change in linguistic instructions, which allows models to meet opposing demands of 'Standard' and 'Anti' versions of the task. Moreover, this modulation of neural tuning is accomplished in a 0-shot setting, when the pre-synaptic weights of the neuron have never explicitly tuned to the 'AntiDMMod1' task. Finally, we see a similar pattern in the time course of activity for trials

in the 'Comparison' family of tasks (Fig. 4d.). These tasks add a level of complexity to the classic 'Decision-Making' tasks; in the COMP1 task, the network must respond in the direction of the first stimulus if it has higher intensity than the second stimulus, and must not respond otherwise. In COMP2, it must respond to the second stimulus if the second stimulus is higher intensity, and not respond otherwise. For 'Anti' versions, the demands of stimulus ordering are the same except the model has to choose the stimuli with the weakest contrast. The added syntactic complexity makes these tasks particularly demanding. Yet we still find individual neurons that modulate their tuning with respect to task demands, even for held out tasks (in this case 'COMP2'). For example unit 82, is active when the network should repress response. For 'COMP1' this unit is highly active with negative contrast (i.e. $str_{stim2} > str_{stim1}$), but flips this sensitivity in 'COMP2' and is highly active with positive contrast (i.e. $str_{stim1} > str_{stim2}$). Importantly, this relation is reversed when the goal is to select the weakest stimuli, in which case the unit shows high activity for a relatively strong versus a relatively weak first stimulus in 'AntiCOMP1' and 'AntiCOMP2' tasks respectively. Hence, despite these subtle syntactic differences in instruction sets, the language embedding can reverse the tuning of this unit in a task-appropriate manner.

Linguistic communication between networks.

So far we have offered an account of what representations emerge in a network that understands the sensorimotor implications of linguistic instructions. We now seek to model the complementary human ability to describe a particular sensorimotor skill with words once it has been acquired. To do this we invert the language-to-sensorimotor mapping our models learn during training so that they can provide a linguistic description of a task based only on the state of sensorimotor units. First, we construct an output channel, which we call the Production-RNN (Fig. 5a-c; blue), to map the information contained in the Sensorimotor-RNN to the linguistic instructions. To train this network, we used a self-supervised procedure: when the network is presented with sensory inputs and linguistic instructions that drive sensorimotor activity, these same instructions are used as targets to train the Production-RNN (Fig. 5a, see Methods for training details). We then pose the following problem to our networks: after training, suppose the network is tested on a sequence of trials in which it is presented with a sensory input and the correct motor feedback for a task, but without the linguistic instructions that normally provide the essential information about task demands. Our goal is to determine whether models can use the information in the motor feedback signal to provide an appropriate linguistic instruction for the task and verify that these instructions can effectively guide the performance of another network. In order to drive networks to perform a task in the absence of instructions, we begin by randomly initializing activity in the embedding layer of the model. We then present the network with a series of example trials for a specific task along with motor feedback and update embedding layer activity in order to reduce the error between the output of the model and the motor feedback signal (Fig. 5b.). Importantly, all model weights remain frozen during this procedure. Once the activity in the embedding layer drives sensorimotor units to achieve a performance criteria over the series of example trials, we use the Production-RNN to decode a linguistic description of the current task. Finally, to evaluate the quality of these instructions we input them to a partner model and measure partner model performance across tasks with produced instructions. All instructing and partner models used in this section are CLIPNETs (see Methods for details).

We first plot a confusion matrix where both Sensorimotor-RNN and Production-RNN are trained on all tasks (Fig. 5d). Each entry in the confusion matrix indicates whether the decoded instruction was included in one of the instruction sets used during self-supervised training. Crucially, the 'Novel' column indicates a decoded instruction that was not included in the training set for the Production-RNN (see Methods for details). Overall, these novel instructions make up 62% of all decoded instructions (see Supp. Info 11 for decoded novel instructions). Of course, the novelty of these instructions says nothing about how well they convey information about the current task. To test this, we evaluate a partner model's performance on generated instructions i.e. the first network infers the task demands and communicates these demands via linguistic instructions to the second network. Results are shown in Fig. 5e, top left.

When the partner model is trained on all tasks, performance on all decoded instructions is 93% on average across tasks (solid, blue bar). Communicating instructions to partner models with tasks held out of training also results in good performance (81%) meaning that partner models can generalize to unseen tasks based on produced instructions (hatched, blue bar). Importantly, this information is present even for 'novel' instructions, where average performance is 91% for partner models trained on all tasks and 79% for partner models with hold-out tasks (green bars). This is only 6% below the performance of CLIPNET zero-shot generalization evaluated with experimenter provided instructions (85%).

Given that the instructing and partner models share the same architecture, one would expect that it is more efficient for the two networks to use direct neural communication, instead of language-based communication. For instance, we can forgo the language component of communication altogether and simply copy the embedding inferred by one model into the input of the partner model. This results in only 32% correct performance on average, compared to 93% for linguistic communication, and only 31% performance when testing partner networks on tasks that have been held out of

Figure 5 | Communication Between Networks a. Illustration of self-supervised training procedure for the linguistic production network (blue). Red dotted line indicates gradient flow. **b.** Illustration of motor feedback used to drive task performance in the absence of linguistic instructions. **c.** Illustration of the partner model evaluation procedure used to evaluate the quality of instructions generated from the instructing model **d.** Confusion matrix of instructions produced from sensorimotor activity evoked by embeddings inferred in **b**. **e.** Performance of partner models in different training regimes given produced instructions or direct input of embedding vectors. Axes indicate the training regime of the instructing model.

training (yellow bars). The reason for this drop off is straightforward: the instructing and partner networks share the same architecture but not the same weights. Because of differences in initial conditions, course of training, etc. the same competencies in each model are realized by a different set of weights. Accordingly, using a neural representation tuned for one set of weights won't necessarily produce good performance in the other.

We also want to determine the extent to which our models can leverage their ability to generalize to unseen tasks in order to produce useful instructions for novel tasks, again only using information gained from motor feedback. We begin with an instructing model Sensorimotor-RNN with tasks held out of training, after which we freeze the weights in this network and expose the system to example trials of all tasks to train the Production-RNN. We emphasize here that during training the Production-RNN attempts to decode from sensorimotor hidden states induced by instructions for tasks the network has never experienced before (as in Fig 5a), whereas during test time instructions are produced from sensorimotor states that emerge entirely as a results of minimizing a motor error (as in Fig. 5b,c). This contrast in train and test conditions makes the task of decoding non-trivial. Yet, we nonetheless find that such a system can produce quality instructions even from tasks which the Sensorimotor-RNN was never exposed to during training (Fig 5.e bottom left). In this setting a partner model trained on all tasks performs at 85% correct across tasks, while partner models with tasks held out of training perform at 76%. Here 75% of produced instructions are novel so we see a very small decrease of 1% when we test the same partner models only on novel instructions. Like above, context representations induce a relatively low performance of 26% and 29% correct for partners trained on all tasks and with tasks held out respectively.

Lastly, we test our most extreme setting where tasks have been held out for both Sensorimotor-RNNs and Production-RNNs (Fig. 5e., bottom right). Here again we find that produced instructions induce a performance of 75% and 68% for

partner models trained on all tasks and with tasks held out respectively. Though this is a decrease in performance from our previous set-ups, the fact that models can produce sensible instructions at all in this double held out setting is striking. Previously we showed that the production network could produce valid, novel instructions for tasks where instructions for that task were included in the training set (Fig 5d. first column, green bars). Here we go a step further and ask the system to infer the proper combination and ordering of words such that the resulting sentence effectively explains a task which the system itself has never seen nor tried to describe before, and again, to produce this instruction in a setting where the only information about task demands comes in the form of motor feedback. The fact that the system succeeds to any extent in this setting speaks to strong inductive biases introduced by training the Sensorimotor-RNNs in the context of rich interrelations in and amongst tasks.

Discussion

In this study we use the latest advances in natural language processing to build tractable models of some quintessential human language skills: the ability to interpret instructions to guide actions in novel settings and the ability to produce a description of a task once it has been learned. We have shown that recurrent neural networks can learn to perform a set of psychophysical tasks simultaneously using a pre-trained language transformer to embed a natural language instruction for the current task. Our best performing models can leverage these embeddings to perform a brand new task on the very first trial, with an average performance of 85% correct based solely on a linguistic description. Instructed models that generalize performance do so by leveraging the shared structure of instruction embeddings and tasks representations, such that an inference about the relations between practiced and novel instructions leads to a good inference about what sensorimotor transformation is required for the unseen task. Finally, once a network understands how to interpret instructions to perform a sensorimotor task, it can invert this process and provide a linguistic description for a previously unseen task based only on the sensorimotor contingency it observes, in the absence of any linguistic input. We find that communicating through language, as opposed to directly via latent neural representations, is essential for effectively passing information between independent sets of sensorimotor neurons. To our knowledge, this is the first account of how linguistic understanding and communication can extend both the generality and transferability of knowledge in a network of sensorimotor neurons.

Our models make several predictions for what neural representations to expect in brain areas that integrate linguistic information in order to exert control over sensorimotor areas. Our first prediction comes from the CCGP analysis of our model hierarchy, which suggests that when human subjects must generalize across (or switch between) a set of related tasks based on instructions, the neural geometry observed amongst sensorimotor mappings should also be present in instruction representations that emerge from the language processing hierarchy. This prediction is well grounded in the existing experimental literature where multiple studies have observed the type of abstract structure we find in our Sensorimotor-RNNs also exists in sensorimotor areas of biological brains [6, 39, 40, 2]. In Sensorimotor-RNNs that were best able to maintain this structure in a novel setting, we found the analogous structure gradually emerged from language modules responsible for inferring task demands based on linguistic information. Hence, we predict that the gradual emergence of this task related structure in language areas is an essential component of instructed action in humans, and should guide experiments examining the interface between language processing and sensorimotor control. Based on the success of multi-modal training for language models, we also predict that the highest levels of this language processing hierarchy should have ready access to a rich array of information from other modalities that may help shape its representations. Finally, we predict that individual units involved in implementing sensorimotor mappings should modulate their tuning properties on a trial by trial basis according to the semantics of the input instructions. This theoretical insight may be especially useful to interpret high resolution imaging data and multi-unit recordings in humans, our only example of organisms with sophisticated linguistic competencies.

One notable negative result of our study is the relatively poor generalization performance of GPTNET and, in particular, GPTNETXL, which used at least an order of magnitude more parameters than other models to process instructions. This is particularly striking given that activity in these models is predictive of many behavioral and neural signatures of human language processing in both passive listening and reading tasks [17, 18]. These studies argue that there is an essential predictive component of word-level language processing and that these computations are captured by autoregressive language models. Nonetheless, embedding instructions with these systems failed to engender the characteristic human ability to generalize based on instructions, and also didn't produce the structured language embeddings that we found in our best performing models. Given this, a synthesis of these results may result in a holistic understanding of the entire language hierarchy. For example, future imaging studies may be guided by the representations in both autoregressive models and our best performing models to more precisely delineate a full gradient of brain areas involved in each stage of language processing, from low-level next word prediction to higher level structured sentence representations to the sensorimotor control that language informs.

Our results also highlight the major advantages of linguistic communication. Our networks can compress the information they have gained through experience of motor feedback and transfer that knowledge to a partner network such that the partner can forgo this learning process and simply follow a given instruction to perform the task. Further, they can communicate knowledge to a partner network even for tasks that the instructing network itself has never previously experienced. Though rudimentary in our example, the ability to endogenously produce a description of how to accomplish a task after a period of practice (motor feedback, in our case) is a hallmark human language skill and underlies much of the utility of linguistic communication in a community of speakers. Finally, the failure to transfer performance by simply sharing latent representations demonstrates that in order to effectively communicate information in a group of otherwise independent networks of neurons, it needs to pass through a representational medium that is equally interpretable by all members of the group. In humans and for our best performing instructed models, this medium is language.

A series of works in reinforcement learning has investigated using language and language-like schemes to aid agent performance. Agents receive language information in a variety of ways such as through step-by-step descriptions of action sequences [41, 42, 43, 44, 45], learning policies conditioned on a language goal [46, 47, 48, 49], by shaping a reward function given language inputs [50, 51] or by leveraging the predictive power of pre-trained models to aid directly in planning and action selection [52, 53]. These studies often deviate from natural language and receive linguistic inputs that are parsed or simply refer to environmental objects, or conversely output actions in the form of a language which is hand coded to interface with the action space of the agent's virtual environment. Further, unlike our models, none of these agents demonstrate any clear connection to the experimental literature, and their task environments make them poor candidates to develop testable neural predictions. Some larger versions of the pre-trained language models we use to embed instructions also display instruction following behavior in their own domains e.g. GPT-3, PALM [54], LaMDA[55], [14], and InstructGPT [15] in the modality of language and DALL-E [16] and Stable Diffusion [56] in a language to image modality. The semantic and syntactic understanding displayed in these models is impressive. However, the output of these models are difficult to interpret in terms of a motor output and so it is again difficult to formulate the computation used in these models as a prediction about the dynamics of a sensorimotor system tuned to interpret language. DALL-E's language to image mapping at least shows some cross-modal language understanding, but it has yet to be demonstrated that the model uses language as a genuine instruction as opposed to merely a prompt (for example, can the model infer control from language as in 'draw a black dog or a blue fish but not both'?). In all, none of these models offer a representational account of *how* language might be used to induce generalization over sensorimotor mappings in the brain.

Our models by contrast make tractable predictions for what population and single unit neural representations are required to support generalization and can guide future experimental work examining the interplay of linguistic and sensorimotor skills in humans. Many cognitive competencies are as of yet unaddressed by our task set and our instruction sets fall short of capturing every aspect of complexity exhibited in the full range of human language. However, by developing interpretable models that can both understand instructions as guiding a particular sensorimotor response, and communicate the results of sensorimotor learning as an intelligible linguistic instruction, we have begun to explain the power of language in encoding and transferring knowledge in networks of neurons.

References

[1] Michael W Cole, Jeremy R Reynolds, Jonathan D Power, Grega Repovs, Alan Anticevic, and Todd S Braver. Multi-task connectivity reveals flexible hubs for adaptive task control. *Nature neuroscience*, 16(9):1348–1355, 2013.

[2] Takuya Ito, Guangyu Robert Yang, Patryk Laurent, Douglas H Schultz, and Michael W Cole. Constructing neural network models from brain data reveals representational transformations linked to adaptive behavior. *Nature Communications*, 13(1):1–16, 2022.

[3] Earl K. Miller and Jonathan D. Cohen. An integrative theory of prefrontal cortex function. *Annual Review of Neuroscience*, 24(1):167–202, 2001. PMID: 11283309.

[4] Michael W Cole, Todd S Braver, and Nachshon Meiran. The task novelty paradox: Flexible control of inflexible neural pathways during rapid instructed task learning. *Neuroscience & Biobehavioral Reviews*, 81:4–15, 2017.

[5] Hannes Ruge, Theo AJ Schäfer, Katharina Zwosta, Holger Mohr, and Uta Wolfensteller. Neural representation of newly instructed rule identities during early implementation trials. *Elife*, 8:e48293, 2019.

[6] Silvia Bernardi, Marcus K Benna, Mattia Rigotti, Jérôme Munuera, Stefano Fusi, and C Daniel Salzman. The geometry of abstraction in the hippocampus and prefrontal cortex. *Cell*, 183(4):954–967, 2020.

[7] Juri Minxha, Ralph Adolphs, Stefano Fusi, Adam N. Mamelak, and Ueli Rutishauser. Flexible recruitment of memory-based choice representations by the human medial frontal cortex. *Science*, 368(6498):eaba3313, 2020.

[8] Ramon Nogueira, Chris C. Rodgers, Randy M. Bruno, and Stefano Fusi. The geometry of cortical representations of touch in rodents. *bioRxiv*, 2021.

[9] Takuya Ito, Tim Klinger, Douglas H. Schultz, John D. Murray, Michael W. Cole, and Mattia Rigotti. Compositional generalization through abstract representations in human and artificial neural networks, 2022.

[10] Ana F Palenciano, Carlos González-García, Juan E Arco, Luiz Pessoa, and María Ruz. Representational organization of novel task sets during proactive encoding. *Journal of Neuroscience*, 39(42):8386–8397, 2019.

[11] Alberto Sobrado, Ana F. Palenciano, Carlos González-García, and María Ruz. The effect of task demands on the neural patterns generated by novel instruction encoding. *Cortex*, 149:59–72, 2022.

[12] Carlos González-García, Juan E Arco, Ana F Palenciano, Javier Ramírez, and María Ruz. Encoding, preparation and implementation of novel complex verbal instructions. *Neuroimage*, 148:264–273, 2017.

[13] Paul S Muhle-Karbe, John Duncan, Wouter De Baene, Daniel J Mitchell, and Marcel Brass. Neural coding for instruction-based task sets in human frontoparietal and visual cortex. *Cerebral Cortex*, 27(3):1891–1905, 2017.

[14] Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners. *CoRR*, abs/2005.14165, 2020.

[15] Xu Jiang Diogo Almeida Carroll L. Wainwright Pamela Mishkin Chong Zhang Sandhini Agarwal Katarina Slama Alex Ray John Schulman Jacob Hilton Fraser Kelton Luke Miller Maddie Simens Amanda Askell Peter Welinder Paul Christiano Jan Leike Ryan Lowe Long Ouyang, Jeff Wu. Training language models to follow instructions with human feedback. https://cdn.openai.com/papers/Training_language_models_to_follow_instructions_with_human_feedback.pdf.

[16] Aditya Ramesh, Mikhail Pavlov, Gabriel Goh, Scott Gray, Chelsea Voss, Alec Radford, Mark Chen, and Ilya Sutskever. Zero-shot text-to-image generation. *CoRR*, abs/2102.12092, 2021.

[17] Martin Schrimpf, Idan Asher Blank, Greta Tuckute, Carina Kauf, Eghbal A. Hosseini, Nancy Kanwisher, Joshua B. Tenenbaum, and Evelina Fedorenko. The neural architecture of language: Integrative modeling converges on predictive processing. *Proceedings of the National Academy of Sciences*, 118(45), 2021.

[18] Ariel Goldstein, Zaid Zada, Eliav Buchnik, Mariano Schain, Amy Price, Bobbi Aubrey, Samuel A Nastase, Amir Feder, Dotan Emanuel, Alon Cohen, et al. Shared computational principles for language processing in humans and deep language models. *Nature neuroscience*, 25(3):369–380, 2022.

[19] Joshua I Gold and Michael N Shadlen. The neural basis of decision making. *Annu. Rev. Neurosci.*, 30:535–574, 2007.

[20] Maxime Chevée, Eric A. Finkel, Su-Jeong Kim, Daniel H. O'Connor, and Solange P. Brown. Neural activity in the mouse claustrum in a cross-modal sensory selection task. *Neuron*, 110(3):486–501.e7, 2022.

[21] Sofia Soares, Bassam V Atallah, and Joseph J Paton. Midbrain dopamine neurons control judgment of time. *Science*, 354(6317):1273–1277, 2016.

[22] Christopher Summerfield and Floris P De Lange. Expectation in perceptual decision making: neural and computational mechanisms. *Nature Reviews Neuroscience*, 15(11):745–756, 2014.

[23] Guangyu Robert Yang, Madhura R Joglekar, H Francis Song, William T Newsome, and Xiao-Jing Wang. Task representations in neural networks trained to perform many cognitive tasks. *Nature neuroscience*, 22(2):297–306, 2019.

[24] Laura Driscoll, Krishna Shenoy, and David Sussillo. Flexible multitask computation in recurrent networks utilizes shared dynamical motifs. *bioRxiv*, 2022.

[25] Alexis Dubreuil, Adrian Valente, Manuel Beiran, Francesca Mastrogiuseppe, and Srdjan Ostojic. The role of population structure in computations through neural dynamics. *Nature Neuroscience*, pages 1–12, 2022.

[26] Douglas P Munoz and Stefan Everling. Look away: the anti-saccade task and the voluntary control of eye movement. *Nature Reviews Neuroscience*, 5(3):218–228, 2004.

[27] Earl K Miller, Cynthia A Erickson, and Robert Desimone. Neural mechanisms of visual working memory in prefrontal cortex of the macaque. *Journal of neuroscience*, 16(16):5154–5167, 1996.

[28] David J Freedman and John A Assad. Neuronal mechanisms of visual categorization: an abstract view on decision making. *Annual review of neuroscience*, 39:129–147, 2016.

[29] Nick Yeung and Christopher Summerfield. Metacognition in human decision-making: confidence and error monitoring. *Philosophical Transactions of the Royal Society B: Biological Sciences*, 367(1594):1310–1321, 2012.

[30] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. *CoRR*, abs/1706.03762, 2017.

[31] Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, Ilya Sutskever, et al. Language models are unsupervised multitask learners. *OpenAI blog*, 1(8):9, 2019.

[32] Dario Amodei Daniela Amodei Jack Clark Miles Brundage Ilya Sutskever Alec Radford, Jeffrey Wu. Better language models and their implications, 2019.

[33] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: pre-training of deep bidirectional transformers for language understanding. *CoRR*, abs/1810.04805, 2018.

[34] Nils Reimers and Iryna Gurevych. Sentence-bert: Sentence embeddings using siamese bert-networks, 2019.

[35] Samuel R. Bowman, Gabor Angeli, Christopher Potts, and Christopher D. Manning. A large annotated corpus for learning natural language inference. *CoRR*, abs/1508.05326, 2015.

[36] Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, Gretchen Krueger, and Ilya Sutskever. Learning transferable visual models from natural language supervision. *CoRR*, abs/2103.00020, 2021.

[37] Michael N Shadlen and William T Newsome. Neural basis of a perceptual decision in the parietal cortex (area lip) of the rhesus monkey. *Journal of neurophysiology*, 86(4):1916–1936, 2001.

[38] Alexander C Huk and Michael N Shadlen. Neural activity in macaque parietal cortex reflects temporal integration of visual motion signals during perceptual decision making. *Journal of Neuroscience*, 25(45):10420–10436, 2005.

[39] Matthew F Panichello and Timothy J Buschman. Shared mechanisms underlie the control of working memory and attention. *Nature*, 592(7855):601–605, 2021.

[40] Edward H Nieh, Manuel Schottdorf, Nicolas W Freeman, Ryan J Low, Sam Lewallen, Sue Ann Koay, Lucas Pinto, Jeffrey L Gauthier, Carlos D Brody, and David W Tank. Geometry of abstract learned knowledge in the hippocampus. *Nature*, 595(7865):80–84, 2021.

[41] David Chen and Raymond Mooney. Learning to interpret natural language navigation instructions from observations. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 25, pages 859–865, 2011.

[42] Junhyuk Oh, Satinder P. Singh, Honglak Lee, and Pushmeet Kohli. Zero-shot task generalization with multi-task deep reinforcement learning. *CoRR*, abs/1706.05064, 2017.

[43] Mohit Shridhar, Jesse Thomason, Daniel Gordon, Yonatan Bisk, Winson Han, Roozbeh Mottaghi, Luke Zettle-moyer, and Dieter Fox. ALFRED: A benchmark for interpreting grounded instructions for everyday tasks. *CoRR*, abs/1912.01734, 2019.

[44] Devendra Singh Chaplot, Kanthashree Mysore Sathyendra, Rama Kumar Pasumarthi, Dheeraj Rajagopal, and Ruslan Salakhutdinov. Gated-attention architectures for task-oriented language grounding. *CoRR*, abs/1706.07230, 2017.

[45] Howard Chen, Alane Suhr, Dipendra Kumar Misra, Noah Snavely, and Yoav Artzi. Touchdown: Natural language navigation and spatial reasoning in visual street environments. *CoRR*, abs/1811.12354, 2018.

[46] Victor Zhong, Tim Rocktäschel, and Edward Grefenstette. RTFM: generalising to novel environment dynamics via reading. *CoRR*, abs/1910.08210, 2019.

[47] Pratyusha Sharma, Antonio Torralba, and Jacob Andreas. Skill induction and planning with latent language. *CoRR*, abs/2110.01517, 2021.

[48] Yiding Jiang, Shixiang Gu, Kevin Murphy, and Chelsea Finn. Language as an abstraction for hierarchical deep reinforcement learning. *CoRR*, abs/1906.07343, 2019.

[49] Jacob Andreas, Dan Klein, and Sergey Levine. Modular multitask reinforcement learning with policy sketches. *CoRR*, abs/1611.01796, 2016.

[50] Dzmitry Bahdanau, Felix Hill, Jan Leike, Edward Hughes, Arian Hosseini, Pushmeet Kohli, and Edward Grefenstette. Learning to understand goal specifications by modelling reward. *arXiv preprint arXiv:1806.01946*, 2018.

[51] Prasoon Goyal, Scott Niekum, and Raymond J. Mooney. Using natural language for reward shaping in reinforcement learning. *CoRR*, abs/1903.02020, 2019.

[52] Wenlong Huang, Pieter Abbeel, Deepak Pathak, and Igor Mordatch. Language models as zero-shot planners: Extracting actionable knowledge for embodied agents, 2022.

[53] Shuang Li, Xavier Puig, Yilun Du, Clinton Wang, Ekin Akyurek, Antonio Torralba, Jacob Andreas, and Igor Mordatch. Pre-trained language models for interactive decision-making, 2022.

[54] Aakanksha Chowdhery, Sharan Narang, Jacob Devlin, Maarten Bosma, Gaurav Mishra, Adam Roberts, Paul Barham, Hyung Won Chung, Charles Sutton, Sebastian Gehrmann, Parker Schuh, Kensen Shi, Sasha Tsvyashchenko, Joshua Maynez, Abhishek Rao, Parker Barnes, Yi Tay, Noam Shazeer, Vinodkumar Prabhakaran, Emily Reif, Nan Du, Ben Hutchinson, Reiner Pope, James Bradbury, Jacob Austin, Michael Isard, Guy Gur-Ari, Pengcheng Yin, Toju Duke, Anselm Levskaya, Sanjay Ghemawat, Sunipa Dev, Henryk Michalewski, Xavier Garcia, Vedant Misra, Kevin Robinson, Liam Fedus, Denny Zhou, Daphne Ippolito, David Luan, Hyeontaek Lim, Barret Zoph, Alexander Spiridonov, Ryan Sepassi, David Dohan, Shivani Agrawal, Mark Omernick, Andrew M. Dai, Thanumalayan Sankaranarayana Pillai, Marie Pellat, Aitor Lewkowycz, Erica Moreira, Rewon Child, Oleksandr Polozov, Katherine Lee, Zongwei Zhou, Xuezhi Wang, Brennan Saeta, Mark Diaz, Orhan Firat, Michele Catasta, Jason Wei, Kathy Meier-Hellstern, Douglas Eck, Jeff Dean, Slav Petrov, and Noah Fiedel. Palm: Scaling language modeling with pathways, 2022.

[55] Romal Thoppilan, Daniel De Freitas, Jamie Hall, Noam Shazeer, Apoorv Kulshreshtha, Heng-Tze Cheng, Alicia Jin, Taylor Bos, Leslie Baker, Yu Du, YaGuang Li, Hongrae Lee, Huaixiu Steven Zheng, Amin Ghafouri, Marcelo Menegali, Yanping Huang, Maxim Krikun, Dmitry Lepikhin, James Qin, Dehao Chen, Yuanzhong Xu, Zhifeng Chen, Adam Roberts, Maarten Bosma, Vincent Zhao, Yanqi Zhou, Chung-Ching Chang, Igor Krivokon, Will Rusch, Marc Pickett, Pranesh Srinivasan, Laichee Man, Kathleen Meier-Hellstern, Meredith Ringel Morris, Tulsee Doshi, Renelito Delos Santos, Toju Duke, Johnny Soraker, Ben Zevenbergen, Vinodkumar Prabhakaran, Mark Diaz, Ben Hutchinson, Kristen Olson, Alejandra Molina, Erin Hoffman-John, Josh Lee, Lora Aroyo, Ravi Rajakumar, Alena Butryna, Matthew Lamm, Viktoriya Kuzmina, Joe Fenton, Aaron Cohen, Rachel Bernstein, Ray Kurzweil, Blaise Aguera-Arcas, Claire Cui, Marian Croak, Ed Chi, and Quoc Le. Lamda: Language models for dialog applications, 2022.

[56] Robin Rombach, Andreas Blattmann, Dominik Lorenz, Patrick Esser, and Björn Ommer. High-resolution image synthesis with latent diffusion models, 2021.

Methods

Model Architecture

Sensorimotor-RNN

The base model architecture and task structure used in this paper follows [23]. All networks of sensorimotor units,
denoted SensorimotorRNN are Gated Recurrent Units [59] using ReLU non-linearities with 256 hidden units each.
Broadly, inputs to the networks are made up of two components 1) sensory inputs, X_t and 2) task identifying information,
I_t. We initialize hidden activity in the GRU as $h^0 \in \mathbb{R}^{256}$ with values set to 0.1. All networks of sensorimotor units use
the same hidden state initialization, so we omit h^0 in network equations. At each time step, a read-out layer Linear$_{\text{out}}$
decodes motor activity, $\hat{y}_t$, from the recurrent activity hidden units, h_t, according to:

$$h_t = \text{SensorimotorRNN}(X_t, I_t; h_{t-1}) \qquad\qquad h_t \in \mathbb{R}^{256}$$
$$\hat{y}_t = \sigma(\text{Linear}_{\text{out}}(h_t)) \qquad\qquad\qquad \hat{y}_t \in \mathbb{R}^{33}$$

641 where σ denotes the sigmoid function. Sensory inputs X_t are made up of 3 channels, two sensory modalities $x_{\text{mod1},t}$
642 and $x_{\text{mod2},t}$, and a fixation channel $x_{\text{fix},t}$. Each of these inputs is continuously valued. Both $x_{\text{mod1},t}, x_{\text{mod2},t} \in \mathbb{R}^{32}$ and
643 stimuli in these modalities are represented as hills of activity with peaks determined by units' preferred directions
644 around a one-dimensional circular variable. Preferred directions for each of the 32 inputs units are evenly spaced
645 between 0 and 2π. For an input at direction θ, the activity of a given input unit u_i with preferred direction θ_i is

$$u_i = str * 0.8 \exp\left[-0.5 * \left(\frac{8|\theta - \theta_i|}{\pi}\right)^2 \right]$$

where str is the coefficient describing stimulus strength. The fixation channel $x_{\text{fix},t} \in \mathbb{R}^1$ is a single unit simulating a
fixation cue for the network. In all, sensory input $X_t = (x_{mod1,t}, x_{mod2,t}, x_{fix,t}) \in \mathbb{R}^{65}$. Accordingly, motor output,
$\hat{y}_t$ consists of both a 32-dimensional ring representing directional responses to the input stimulus as well as a single unit
representing model fixation, so that $\hat{y}_t \in \mathbb{R}^{33}$

For all models, task identifying information, i.e., the task rule layer for *simpleNet* and the instructions embedding layer
for the instructed model (Fig. 1a), $I_t \in \mathbb{R}^{64}$. Further, task identifying information is presented throughout the duration
of a trial and remains constant such that $I_t = I_{t\prime} \ \forall t, t\prime$. For all models, task identifying info I_t and sensory input X_t
are concatenated as inputs to the SensorimotorRNN, so that the input dimensionality of all recurrent networks is 129.

Non-Linguistic Models

For our non-linguistic model SIMPLENET, we generate set of orthogonal task rules by constructing an orthogonal matrix
using the Python package scipy.stats.ortho_group, and assign rows of this matrix to each task type. This results in a set
of 50 orthogonal 64-dimensional vectors uniquely associated with each task type, which are used by SIMPLENET as
task identifying information in our simulations.

SIMPLENETPLUS uses additional hidden layers with 128 units to process orthogonal tasks rules I_t into a vector $\bar{I}_t$
which is used by SensorimotorRNN as task identifying information.

$$\bar{I}_t^{'} = ReLU(\text{Linear}_{\text{RuleEmb1}}(I_t)) \qquad\qquad \bar{I}_t^{'} \in \mathbb{R}^{128}$$
$$\bar{I}_t^{'} = ReLU(\text{Linear}_{\text{RuleEmb2}}(I_t^{'})) \qquad\qquad \bar{I}_t^{'} \in \mathbb{R}^{128}$$
$$\bar{I}_t = ReLU(\text{Linear}_{\text{RuleEmb3}}(\bar{I}_t^{'})) \qquad\qquad \bar{I}_t \in \mathbb{R}^{64}$$

Pre-trained Transformers

For our instructed models, task identifying information is computed by embedding natural language instructions. The
main language modules we test use pre-trained transformer architectures to produce I. In order to get a fixed length
embedding for each instruction we use average pooling over the sequence length in the transformer's last hidden layer
and subsequently use a linear layer to output a 64-dimensional vector. Suppose we have an input instruction $w_1 \dots w_{\mathcal{T}}$,
then

$$h^{tran.} = \text{transformer}(w_1 \dots w_{\mathcal{T}}), \qquad\qquad h^{tran.} \in \mathbb{R}^{\dim_{\text{trans.}} \times \mathcal{T}}$$
$$h^I = \text{mean}(h^{tran.}), \qquad\qquad\qquad h^I \in \mathbb{R}^{\dim_{\text{trans.}}}$$
$$I = \text{Linear}_{\text{embed}}(h^I), \qquad\qquad\qquad I \in \mathbb{R}^{64}$$

where $\dim_{\text{trans.}}$ is the inherent dimensionality of the transformer model. For GPTNET, BERT, and SBERT, $\dim_{\text{trans.}} = 768$
and each model uses a total of 100M parameters; for GPTNETXL $\dim_{\text{trans.}} = 1600$ and the model uses 1.5B parameters;
for CLIP, $\dim_{\text{trans.}} = 512$ and model uses 60M parameters.

Besides differing size, transformers differ in the type of pre-training objective used to tune the model parameters and
therefore also differ in the types of linguistic representations each model possesses. GPT is trained on a traditional
language modeling objective i.e. predict next word given a context of words [31]. GPTXL follows the same objective but
trains for longer on a larger dataset [32]. Both models are fully autoregressive. BERT, by contrast, takes bi-directional
language inputs (future and past words) and is tasked with predicting masked words that appear in the middle of input
phrases. Additionally, BERT is trained on a simple sentence prediction task where the model must determine if input
sentence 1 is followed by input sentence 2 in the training corpus. This endows BERT with some rudimentary notion of
sentence level semantics. Extending this principle, SBERT is explicitly trained to produce fixed length embeddings of
whole sentences [34]. It takes pre-trained BERT networks and uses them in a siamese architecture [58] which allows
the weights of the model to be tuned in a supervised fashion according to the Stanford Natural Language Inference
dataset [57]. Natural language inference is a three-way categorization task where the network must infer the logical
relationship between sentences: whether a premise sentence implies, contradicts, or is unrelated to a hypothesis sentence.
The sentence representations produced by these networks have been shown to match human judgements of sentence
similarity across several datasets. Finally, CLIP is trained to jointly embed images and language [36]. It uses data
from captioned images and is asked to properly categorize which text and images pairs match or are mismatched in
the dataset via a contrastive loss. Hence, CLIP simultaneously shapes the language and image embedding spaces in
complementary ways. For our models, we discard the image recognition network and simply use the language embedder.
Full PyTorch implementations and model details can be found at the Huggingface library [61].

BoW Model

We also use a Bag of Words embedding to test a comparatively simple language processing scheme. Here, instructions
are represented as a vector of binary activations the size of the instruction vocabulary, where each unit indicates the
inclusion or exclusion of the associated vocabulary word in the current instruction. For our instruction set $|vocab| = 181$.
This vector is then projected through a linear layer into 64-dimensional space.

$$h_i^{\text{BoW}} = \begin{cases} 1 & \text{if } w_i \in (w_1 \dots w_w\mathcal{T}) \\ 0 & \text{otherwise} \end{cases} \qquad\qquad h^{\text{BoW}} \in \mathbb{R}^{|vocab|}$$
$$I = \text{Linear}_{\text{embed}}(h^{\text{BoW}}), \qquad\qquad\qquad I \in \mathbb{R}^{64}$$

Tasks Sets

Tasks were divided into 5 interrelated subgroups: the 'Go' group, the 'Decision-Making' group, the 'Matching' group,
and the 'Comparison' group and the 'Duration' group. Each group possesses its own internal structure which relates
tasks to one another. Depending on the task, multiple stimuli may appear over the course of the stimulus epoch. Also
depending on the task, models may be required to respond in a particular direction or repress response altogether.
Unless otherwise specified, 0-mean Gaussian noise is added independently at each time step and to each input unit
and the variance of this noise is drawn randomly from $\mathbb{U}[0.1, 0.15]$. The timing of stimuli differ among the tasks type.
However, for all tasks trials can be divided into a preparatory, stimulus, and response epoch. The stimulus epoch can
further be divided into three parts, stim1, delay and stim2, although these distinct parts aren't used by all tasks. A trial
lasts for a total of $T = 150$ times steps. Let dur_{epoch} denote the duration in simulated time steps of a given epoch. Then

$$dur_{\text{response}} \sim \{i | 20 < i \le 25; i \in \mathbb{N}\}$$
$$dur_{\text{stim1}}, dur_{\text{stim2}} \sim \{i | 37 < i \le 50; i \in \mathbb{N}\}$$
$$dur_{\text{delay}} \sim \{i | 15 < i \le 25; i \in \mathbb{N}\}$$
$$dur_{\text{prep.}} = 150 - (dur_{\text{response}} + dur_{\text{stim1}} + dur_{\text{stim2}} + dur_{\text{delay}})$$

703 For tasks that don't utilize a delay structure stim1, stim2, and delay epochs are grouped together in a single stimulus
704 epoch where $dur_{\text{stimulus}} = dur_{\text{stim1}} + dur_{\text{stim2}} + dur_{\text{delay}}$. Unless otherwise specified a fixation cue with a constant
705 strength $str_{\text{fix}} = 1$ is activated throughout the prep. and stimulus epochs. For example trials of each task see
706 Supplementary Info. 12.

'Go' Tasks

The 'Go' family of tasks includes 'Go', 'RTGo', 'AntiGo', 'AntiRTGo' and modality specific versions of each task
denoted with either 'Mod1' and 'Mod2.' In both the 'Go' and 'AntiGo' tasks, a single stimulus is presented at the
beginning of the stimulus epoch. The direction of the presented stimulus is generated by drawing from a uniform
distribution between 0 and 2π, i.e. $\theta_{\text{stim}} \sim \mathbb{U}[0, 2\pi]$. The stimulus will appear in either modality 1 or modality 2 with
equal probability. The strength of the stimulus is given by $str_{\text{stim}} \sim \mathbb{U}[1.0, 1.2]$. In the 'Go' task the target response
is in the same direction as the presented stimulus i.e. $\theta_{\text{stim}} = \theta_{\text{target}}$, while in the 'Anti Go' task the direction of the
response should be in the opposite of the stimulus direction, $\theta_{\text{stim}} + \pi = \theta_{\text{target}}$. For modality specific versions of each
task, a stimulus direction is drawn in each modality $\theta_{\text{stim, mod1}} \sim \mathbb{U}[0, 2\pi]$ and $\theta_{\text{stim, mod2}} \sim \mathbb{U}[0, 2\pi]$ and for modality
specific Go-type tasks

$$\theta_{\text{target}} = \begin{cases} \theta_{\text{stim, mod1}} & \text{if Mod1 Task} \\ \theta_{\text{stim, mod2}} & \text{if Mod2 Task} \end{cases}$$

717 while for modality specific AntiGo-type tasks

$$\theta_{\text{target}} = \begin{cases} \theta_{\text{stim, mod1}} + \pi & \text{if Mod1 Task} \\ \theta_{\text{stim, mod2}} + \pi & \text{if Mod2 Task} \end{cases}$$

718 For 'RT' versions of the 'Go' tasks stimuli are only presented during the response epoch and the fixation cue is never
719 extinguished. Thus the presence of the stimulus itself serves as the response cue and the model must respond as quickly
720 as possible. Otherwise stimuli persist through the duration of the stimulus epoch.

'Decision-Making' Tasks

The 'Decision-Making' family of tasks includes 'DM' (decision-making), 'Anti DM', 'MultiDM' (multi-sensory
decision making), 'AntiMultiDM,' modality specific versions of each of these tasks and finally confidence based
versions of 'DM' and 'AntiDM.' For all tasks in this group, two stimuli are presented simultaneously and
persist throughout the duration of the stimulus epoch. They are drawn according to $\theta_{\text{stim1}} \sim \mathbb{U}[0, 2\pi]$ and
$\theta_{\text{stim2}} \sim \mathbb{U}[(\theta_{\text{stim1}} - 0.2\pi, \theta_{\text{stim1}} - 0.6\pi) \cup (\theta_{\text{stim1}} + 0.2\pi, \theta_{\text{stim1}} + 0.6\pi)]$. A base strength applied to both stim-
uli is drawn such that $str_{base} \sim \mathbb{U}[1.0, 1.2]$. A contrast is drawn from a discrete distribution such that $c \sim$
$\{-0.175, -0.15, -0.1, 0.1, 0.15, 0.175\}$ so the stimulus strength associated with each direction in a trial are given by
$str_{\text{stim1}} = str_{base} + c$ and $str_{\text{stim2}} = str_{base} - c$.

For the 'DM' task,

$$\theta_{\text{target}} = \begin{cases} \theta_{\text{stim1}} & \text{if } str_{\text{stim1}} > str_{\text{stim2}} \\ \theta_{\text{stim2}} & \text{otherwise} \end{cases}$$

731 and for the the 'Anti DM' task,

$$\theta_{\text{target}} = \begin{cases} \theta_{\text{stim1}} & \text{if } str_{\text{stim1}} < str_{\text{stim2}} \\ \theta_{\text{stim2}} & \text{otherwise} \end{cases}$$

For these versions of the tasks the stimuli are presented in either modality 1 or modality 2 with equal probability.
For the multi-sensory versions of each task, stimuli directions are drawn in the same manner and presented across
both modalities so that $\theta_{\text{stim1, mod1}} = \theta_{\text{stim1, mod2}}$ and $\theta_{\text{stim2, mod1}} = \theta_{\text{stim2, mod2}}$. Base strengths are drawn independently
for each modality. Contrasts for both modalities are drawn from a discrete distribution such that $c_{\text{mod1}}, c_{\text{mod2}} \sim$
$\{0.2, 0.175, 0.15, 0.125, -0.125, -0.15, -0.175, -0.2\}$. If both $|c_{\text{mod1}}| - |c_{\text{mod2}}| = 0$ then contrasts are redrawn in
order to avoid zero contrast trials during training. If both c_{mod1} and c_{mod2} have the same sign then contrasts are redrawn

to ensure that the the trial requires integrating over both modalities as opposed to simply performing a 'DM' task in
a single modality. Criteria for target response are measured as the strength of a given direction summed over both
modalities. So, for 'MultiDM'

$$\theta_{\text{target}} = \begin{cases} \theta_{\text{stim1,mod1}} & \text{if } str_{\text{stim1, mod1}} + str_{\text{stim1, mod2}} > str_{\text{stim2, mod1}} + str_{\text{stim2, mod2}} \\ \theta_{\text{stim2,mod1}} & \text{otherwise} \end{cases}$$

741 and for 'AntiMultiDM'

$$\theta_{\text{target}} = \begin{cases} \theta_{\text{stim1,mod1}} & \text{if } str_{\text{stim1, mod1}} + str_{\text{stim1, mod2}} < str_{\text{stim2, mod1}} + str_{\text{stim2, mod2}} \\ \theta_{\text{stim2, mod1}} & \text{otherwise} \end{cases}$$

Stimuli for modality specific versions of each task are generated in the same way as multi-sensory versions of the task.
Criteria for target response are the same as standard versions of 'DM' and 'AntiDM' tasks applied only to stimuli in the
relevant modality.

In confidence based decision-making tasks ('ConDM' and 'ConAntiDM') the stimuli directions are drawn in the same
way as above. Stimuli are shown in either modality 1 or modality 2 with equal probability. In each trial $str_{base} = 1$.
The contrast and noise for each trial is based on the thresholded performance of a SIMPLENET model trained on all
tasks except 'ConDM' and 'ConAntiDM'. Once this model has been trained, we establish a threshold across levels
of noise and contrasts for which the model can perform a 'DM' or an 'AntiDM' task at 95% correct. We then draw
contrasts and noises for trials from above and below this threshold with equal probability during training. In trials
where the noise and contrast levels fell below the 95% correct threshold the model must repress response, and otherwise
perform the decision-making task (either 'DM' or 'AntiDM').

'Comparison' Tasks

Our comparison task group includes 'COMP1', 'COMP2', 'MultiCOMP1', 'MultiCOMP2', 'Anti' versions of each of
these tasks, as well as modality specific versions of 'COMP1' and 'COMP2' tasks. This group of tasks is designed to
extend the basic decision-making framework into a setting with more complex control demands. These tasks utilize the
delay structure in the stimulus epoch so that stim1 appears only during the stim1 epoch, followed by a delay, and finally
stim2. This provides a temporal ordering on the stimuli. In 'COMP1' the model must respond to the first stimuli only if
has greater strength than the second and otherwise repress a response i.e.

$$\theta_{\text{target}} = \begin{cases} \theta_{\text{stim1}} & \text{if } str_{\text{stim1}} > str_{\text{stim2}} \\ \text{repress} & \text{otherwise} \end{cases}$$

760 Likewise, in 'COMP2', the model must respond to the second direction if it presented with greater strength than the
761 first otherwise repress response i.e.

$$\theta_{\text{target}} = \begin{cases} \theta_{\text{stim2}} & \text{if } str_{\text{stim2}} > str_{\text{stim1}} \\ \text{repress} & \text{otherwise} \end{cases}$$

762 In 'Anti' versions of the task the ordering criteria is the same except for stimuli with least strength i.e. for 'AntiCOMP1'

$$\theta_{\text{target}} = \begin{cases} \theta_{\text{stim1}} & \text{if } str_{\text{stim1}} < str_{\text{stim2}} \\ \text{repress} & \text{otherwise} \end{cases}$$

763 and for 'AntiCOMP2'

$$\theta_{\text{target}} = \begin{cases} \theta_{\text{stim2}} & \text{if } str_{\text{stim2}} < str_{\text{stim1}} \\ \text{repress} & \text{otherwise} \end{cases}$$

In multi-sensory settings the criteria for target direction is analogous to the multi-sensory decision-making tasks where strength is integrated across modalities. Likewise, for modality specific versions the criteria is only applied to stimuli in the relevant modality. Stimuli directions and strength for each of these tasks is drawn from the same distributions as the analogous task in the 'Decision-Making' family. However, during training we make sure to balance trials where responses are required and trials where models must repress response.

'Duration' Tasks

The 'Duration' family of tasks includes 'Dur1', 'Dur2', 'MultiDur1', 'MultiDur2', 'Anti' versions of each of these tasks and modality specific versions of 'Dur1' and 'Dur2' tasks. These tasks require models to perform a time estimation task with the added demand or stimuli ordering determining relevance for response. Like in 'Comparison' tasks stim1 is presented followed by a delay and then stim2. For 'Dur1' trials

$$\theta_{\text{target}} = \begin{cases} \theta_{\text{stim1}} & \text{if } dur_{\text{stim1}} > dur_{\text{stim2}} \\ \text{repress} & \text{otherwise} \end{cases}$$

Likewise for 'Dur2'

$$\theta_{\text{target}} = \begin{cases} \theta_{\text{stim2}} & \text{if } dur_{\text{stim2}} > dur_{\text{stim1}} \\ \text{repress} & \text{otherwise} \end{cases}$$

In 'Anti' versions of these tasks the correct response is in the direction of the stimulus with the shortest duration given the ordering criteria is met. Hence, for 'AntiDur1'

$$\theta_{\text{target}} = \begin{cases} \theta_{\text{stim1}} & \text{if } dur_{\text{stim1}} < dur_{\text{stim2}} \\ \text{repress} & \text{otherwise} \end{cases}$$

and for 'AntiDur2'

$$\theta_{\text{target}} = \begin{cases} \theta_{\text{stim2}} & \text{if } dur_{\text{stim2}} < dur_{\text{stim1}} \\ \text{repress} & \text{otherwise} \end{cases}$$

Across these tasks directions are drawn according to $\theta_{\text{stim1}} \sim \mathbb{U}[0, 2\pi]$ and $\theta_{\text{stim2}} \sim \mathbb{U}[(\theta_{\text{stim1}} - 0.2\pi, \theta_{\text{stim1}} - 0.6\pi) \cup (\theta_{\text{stim1}} + 0.2\pi, \theta_{\text{stim1}} + 0.6\pi)]$. Stimulus strengths are drawn according to $str_{\text{stim1}}, str_{\text{stim2}} \sim \mathbb{U}[0.8, 1.2]$. To set the duration of each stimulus we first draw $dur_{\text{long}} \sim \{i | 35 < i \le 50, i \in \mathbb{N}\}$ and $dur_{\text{short}} \sim \{i | 25 < i \le (dur_{\text{long}} - 8), i \in \mathbb{N}\}$. During training, we determine which trials for a given task should and should not require a response in order to evenly balance repress and respond trials. We then assign dur_{long} and dur_{short} to either stim1 or stim2 in so that the trial requires the appropriate response given the particular task type.

Again, criteria for correct response in the multi-sensory and modality specific versions of each tasks follow analogous tasks in the 'Decision-Making' and 'Comparison' groups where multi-sensory versions of the task require integrating total duration over each modality and modality specific tasks require only considering durations in the given task modality. For multi-sensory tasks we draw duration value $dur_{\text{Long}} \sim \{i | 75 < i \le 100, i \in \mathbb{N}\}$ and then split this value $dur_{\text{long0}} = dur_{\text{Long}} * 0.55$ and $dur_{long1} = dur_{\text{Long}} * 0.45$. We also draw a value $dur_{\text{Short}} = dur_{\text{Long}} - \Delta dur$ where $\Delta dur \sim \{i | 15 < i \le 25, i \in \mathbb{N}\}$. This value is then subdivided further into $dur_{\text{short0}} = dur_{\text{long1}} + \Delta dur_{\text{short}}$ where $\Delta dur_{\text{short}} \sim \{i | 19 < i \le 15, i \in \mathbb{N}\}$ and $dur_{\text{short1}} = dur_{\text{Short}} - dur_{\text{short0}}$. Short and long durations can then be allocated to the ordered stimuli according to task type. Drawing durations in this manner ensures that like in 'Decision-Making' and 'Comparison' groups, correct answer truly require models to integrate durations over both modalities, rather than simply performing the task in a given modality to achieve correct responses.

'Matching' Tasks

The 'Matching' family of tasks consists of 'DMS' (delay match to stimulus), 'DNMS' (delay non-match to stimulus), 'DMC' (delay match to category), 'DMNC' (delay non-match to category) tasks. For all tasks, stim1 is presented at the beginning of the stimulus epoch, followed by a delay, and the presentation of stim2. The stimulus strength is drawn according to $str_{\text{stim1}}, str_{\text{stim2}} \sim \mathbb{U}[0.8, 1.2]$. The input modality for any given trial is chosen at random with equal

probability. In both 'DMS' and 'DNMS' tasks, trials are constructed as 'matching stim' trials or 'mismatching stim' trials with equal probability. In 'matching stim' trials $\theta_{\text{stim1}} \sim \mathbb{U}[0, 2\pi]$ and $\theta_{\text{stim2}} = \theta_{\text{stim1}}$. In 'mismatch stim' trials, $\theta_{\text{stim1}} \sim \mathbb{U}[0, 2\pi]$ and $\theta_{\text{stim2}} \sim \mathbb{U}[(\theta_{\text{stim1}} - 0.2\pi, \theta_{\text{stim1}} - 0.6\pi) \cup (\theta_{\text{stim1}} + 0.2\pi, \theta_{\text{stim1}} + 0.6\pi)]$. For 'DMS', models must respond in the displayed direction if the stimuli match, otherwise repress response,

$$\theta_{\text{target}} = \begin{cases} \theta_{\text{stim1}} & \text{if } \theta_{\text{stim1}} = \theta_{\text{stim2}} \\ \text{repress} & \text{otherwise} \end{cases}$$

and for 'DNMS' models respond to the second direction if both directions are mismatched,

$$\theta_{\text{target}} = \begin{cases} \theta_{\text{stim2}} & \text{if } \theta_{\text{stim1}} \neq \theta_{\text{stim2}} \\ \text{repress} & \text{otherwise} \end{cases}$$

'DMC' and 'DNMC' tasks are organized in a similar manner. The stimulus input space is divided evenly into two categories such that cat1 $= \{\theta : 0 < \theta \leq \pi\}$ and cat2 $= \{\theta : \pi < \theta \leq 2\pi\}$. For 'DMC' and 'DNMC' tasks, trials are constructed as 'matching cat.' trials or 'mismatching cat.' trials with equal probability. In 'matching cat.' trials $\theta_{\text{stim1}} \sim \mathbb{U}[0, 2\pi]$ and $\theta_{\text{stim2}} \sim \mathbb{U}(\text{cat}_{\text{stim1}})$, where $\mathbb{U}(\text{cat}_{\text{stim1}})$ is a uniform draw from the category of stim1. In 'mismatch stim' trials, $\theta_{\text{stim1}} \sim \mathbb{U}[0, 2\pi]$ and $\theta_{\text{stim2}} \sim \mathbb{U}(-\text{cat}_{\text{stim1}})$ where $-\text{cat}_{\text{stim1}}$ is the opposite category as stim1. For 'DMC' the model must respond in the first direction if both stimuli are presented in the same category otherwise repress response,

$$\theta_{\text{target}} = \begin{cases} \theta_{\text{stim1}} & \text{if } \text{cat}_{\text{stim1}} = \text{cat}_{\text{stim2}} \\ \text{repress} & \text{otherwise} \end{cases}$$

and for 'DNMC' the model should respond to the second direction if both stimuli are presented in opposite categories otherwise repress response,

$$\theta_{\text{target}} = \begin{cases} \theta_{\text{stim2}} & \text{if } \text{cat}_{\text{stim1}} \neq \text{cat}_{\text{stim2}} \\ \text{repress} & \text{otherwise} \end{cases}$$

Target Output and Correct Criteria

The target output $y \in \mathbb{R}^{33 \times T}$ for a trial entails maintaining fixation in $y_1 = y_{\text{fix}}$ during the stimulus epoch, and then either responding in the correct direction or repressing activity in the remaining target response units $y_{2\ldots33}$ in the response epoch. Since the model should maintain fixation until response, target for fixation is set at $y_{\text{fix}} = 0.85$ during preparatory and stimulus epochs and $y_{\text{fix}} = 0.05$ in the response epoch. When a response is not required, as in the preparatory and stimulus epochs and with repressed activity in the response epoch, unit i takes on a target activity of $y_i = 0.05$. Alternatively, when there is a target direction for response,

$$y_i = 0.8 \exp\left[-0.5 * \left(\frac{8|\theta_{\text{target}} - \theta_i|}{\pi} \right)^2 \right] + 0.05$$

where θ_i is the preferred direction for unit i. Like in sensory stimuli, preferred directions for target units are evenly spaced values from $[0, 2\pi]$ allocated to the 32 response units.

For a model response to count as correct, it must maintain fixation i.e. $\hat{y}_{\text{fix}} > 0.5$ during preparatory and stimulus epochs. When no response is required $\hat{y}_i < 0.15$. When a response is required, response activity is decoded using a population vector method and $\theta_{\text{resp.}} \in (\theta_{\text{target}} - \frac{\pi}{10}, \theta_{\text{target}} + \frac{\pi}{10})$. If the model fails to meet any of these criteria the trial response is incorrect.

Model Training

During model training, model parameters are updated in a supervised fashion according to a masked Mean Squared Error Loss (mMSE) computed between the model motor response, $\hat{y}_{1\ldots T} = \hat{y}$ and the target $y_{1\ldots T} = y$ for each trial.

$$L = \text{mMSE}(y, \hat{y}) = mask * \langle (y_t - \hat{y}_t)^2 \rangle_t$$

Here $*$ denotes element-wise multiplication. Masks weigh the importance of different trial epochs. During preparatory and stimulus epochs mask weights are set to 1, during the first five time steps of the response epoch mask is set to 0, and during the remainder of the response epoch mask is set to 5. The mask value for the fixation is twice that of other values at all time steps.

For all models, we update $\Theta = \{\text{SensorimotorRNN}, \text{Linear}_{\text{out}}\}$ during training on our task set. For instructed models we additionally update $\text{Linear}_{\text{embed}}$ in the process of normal training. We train models using standard PyTorch machinery and an Adam optimizer. For all models we use an initial learning rate $lr = 0.001$ and decay the learning rate for each epoch by a factor of $\gamma = 0.95$. An epoch consists of 2400 mini-batches, with each mini-batch consisting of 64 trials. Task type remains consistent within batches, but in the case of instructed models, the instruction used to inform each trial is drawn at random across the 64 trials in the batch. Tasks are randomly interleaved during training so that the networks can learn all tasks simultaneously. Models train until they reach a threshold performance of 95% across all tasks (and train for a minimum of 35 epochs). We found that training for GPTNET tended to asymptote below performance threshold for multi-sensory versions of comparison tasks. This held true over a variety of training hyperparameters and learning rate scheduler regimes for training. Hence, we relax the performance threshold of GPTNET to 85%. For each model type we train 5 models that start from 5 different random initializations. Where applicable results are averaged over these initializations.

Hold-out Testing

During hold-out testing, we present models with 100 batches of one of the tasks that had been held out of training. For instructed model the only weights allowed to update during this phase are $\Theta = \{\text{SensorimotorRNN}, \text{Linear}_{\text{out}}, \text{Linear}_{\text{embed}}\}$. All weights of *simpleNet* are trainable in this context. We use a batch size of 256 and a learning rate of $8e - 4$. All additional results shown in the Supplemental Information Section 4 follow this procedure.

Cross Condition Generalization Performance Calculation

To calculate Cross Conditional Generalization Performance (CCGP) we train a linear decoder on a pair of tasks and then test that decoder on alternative pairs of task that have an analogous relationship. We group tasks into 8 dichotomies 'Go' vs. 'Anti', 'Standard' vs. 'RT', 'Weakest' vs. 'Strongest', 'Longest' vs. 'Shortest', 'First Stim.' vs. 'Second Stim', 'Stim Match' vs. 'Category Match', 'Matching' vs. 'Non-Matching', and 'Mod1' vs. 'Mod2'. As an example, the 'Go' vs. 'Anti' dichotomy includes ('Go', 'AntiGo'), ('GoMod1', 'AntiGoMod1'), ('GoMod2', 'AntiGoMod2'), ('RTGo', 'AntiRTGo'), ('RTGoMod1', 'AntiRTGoMod1'), ('RTGoMod2', 'AntiRTGoMod2') task pairs. For "RNN" task representations, we record activity at the time of stimulus onset for 250 example trials. For language representations, we input the instruction sets for relevant tasks to our language model and directly record activity in the "embedding" layer or take the sequence-averaged activity in each transformer layer. We train a linear decoder to classify task activity according to one pair of tasks, and subsequently test the same classifier on the remaining set of pairs. Train and test conditions are determined by dichotomies identified across the task set (see Supplemental Info. 9 for all dichotomies). To train and test decoders we use sklearn.svm.LinearSVC Python package. The CCGP score for a given task is the average decoding score achieved across all dichotomies where the task in question was either part of the train set or the test set. For model scores reported in the main text, we only calculate CCGP scores for models where the task in question has been held out of training. In this way we can capture the geometries that the models obtain in the zero shot setting. In Supplementary Info Fig. 8 we report scores on tasks where models have been trained on all tasks, and for models where instructions have been switched for the holdout task.

Language Production Training

Self-Supervised Language Production Network Training

Our language production framework is inspired by classic sequence to sequence modeling using RNNs [60]. We treat each time step in the sequence as a token position in the target sentence that we wish to decode. Our ProductionRNN is a GRU with 256 hidden units using ReLU non-linearities. At each step in the sequence a set of decoder weights $\text{Linear}_{\text{words}}$ attempts to decode the next token $w_{\tau+1}$ from the hidden state of the recurrent units. The hidden state of the ProductionRNN is initialized by concatenating the time average and maximum sensorimotor activity of a *clipNet* and passing that through weights $\text{Linear}_{\text{sm}}$. Using an instructed model means that training the ProductionRNN can proceed in a completely self-supervised manner. The linguistic instruction used to drive the initializing sensorimotor activity is in turn used as the target set of tokens for the ProductionRNN outputs. The first input to the ProductionRNN is always a special start-of-sentence token (<SOS>) and the decoder runs until an end-of-sentence token (<EOS>) is decoded or until input reaches a length of 30 tokens. Suppose $w_{1,k} \ldots w_{\mathcal{T},k} \in Instruct_k^i$ is the sequence of tokens in instruction k where k is in the instruction set for task i and X^i is sensory input for a trial of task i. For brevity, we denote the process

by which language models embed instructions as $Embed()$ (see *Pre-trained Transformers* above). The decoded token at the τ^{th} position, $\hat{w}_{\tau,k}$, is then given by

$$
\begin{aligned}
h_T^{sm} &= \text{SensorimotorRNN}(X^i, Embed(w_{1,k} \ldots w_{\mathcal{T},k})) & h_T^{sm} &\in \mathbb{R}^{T \times 256} \\
sm\_out &= (\text{mean}_T(h_T^{sm}), \text{max}_T(h_T^{sm}) & sm\_out &\in \mathbb{R}^{512} \\
h_0^{\text{decoder}} &= \text{relu}(\text{Linear}_{\text{sm}}(sm\_out)) & h_0^{\text{decoder}} &\in \mathbb{R}^{256} \\
h_\tau^{\text{decoder}} &= \text{ProductionRNN}(\hat{w}_{1,k} \ldots \hat{w}_{\tau-1,k}; h_0^{\text{decoder}}), & h_\tau^{\text{decoder}} &\in \mathbb{R}^{256} \\
p_{\hat{w}_{\tau,k}} &= \text{softmax}(\text{Linear}_{\text{words}}(h_{\tau,k}^{\text{decoder}})) & p_{\hat{w}_{\tau,k}} &\in \mathbb{R}^{|vocab|}, \\
\hat{w}_{\tau,k} &= \text{argmax}(p_{\hat{w}_{\tau,k}})
\end{aligned}
$$

The model parameters $\Theta^{\text{production}} = \{\text{Linear}_{\text{sm}}, \text{Linear}_{\text{words}}, \text{ProductionRNN}\}$ are trained using cross-entropy loss between the $p_{\hat{w}_{\tau,i}}$ and the instruction token $w_{\tau,k}$ provided to the SensorimotorRNN as input. We train for 80 epochs of 1600 batches with 64 trials per batch and with task type randomly interleaved. We use an Adam optimizer with an initial learning rate of $lr = 1e^{-4}$ and a decay rate of $\gamma = 0.99$. We also use a teacher forcing curriculum, where for some ratio of training batches we input the ground truth instruction token $w_{\tau,k}$ at each time step instead of the models decoded word $\hat{w}_{\tau,k}$. At each epoch, $teacher\_forcing\_ratio = 0.5 * \frac{80 - \text{epoch}}{80}$.

Obtaining Embedding Layer Activity Using Motor Feedback

We wish to determine whether or not networks can communicate task information gained during training on motor feedback, in the absence of linguistic instructions. To accomplish this for a task, i, we seek to optimize a set of embedding activity vectors $E^i \in \mathbb{R}^{64}$ such that when they are input to the model it will perform the task in question. Crucially, we freeze all model weights $\Theta = \{\text{SensorimotorRNN}, \text{Linear}_{\text{out}}, \text{Linear}_{\text{embedding}}\}$ and only update E^i according to the standard supervised loss on the motor output that comes from inputting E^i as task identifying information. For notional clarity GRU dependence on the previous hidden state h_{t-1} has been made implicit in the following equations.

$$
\begin{aligned}
\hat{y}^i &= \sigma(\text{Linear}_{\text{out}}(\text{SensorimotorRNN}(X^i, E^i))) \\
L &= mMSE(y, \hat{y})
\end{aligned}
$$

We optimize a set of 25 embedding vectors for each task, again using an Adam optimizer with an initial learning rate of $lr = 0.05$ which we decay by $\gamma = 0.8$ each epoch. An epoch lasts for 1200 batches with a batch length of 64 and we train for a minimum of 1 epoch or until we reach a threshold performance of 90% or 85% on 'DMC' and 'DNMC' tasks.

Producing Task Instructions

To produce task instructions we simply use the set E^i as task identifying information in the input of the SensorimotorRNN and use the ProductionRNN to output instructions based on the sensorimotor activity driven by E^i. For each task we use the set of embedding vectors to produce 50 instructions per task. We repeat this process for each of the 5 initializations of SensorimotorRNN, resulting in 5 distinct language production networks, and 5 distinct sets of learned embedding vectors. Reported results for each task are averaged over these 5 networks. For the confusion matrix (Fig. 5d), we report the average percentage that decoded instructions are in the training instruction set for a given task or a novel instruction. Partner model performance (Fig. 5e) for each network initialization is computed by testing each of the 4 possible partner networks and averaging over these results.

Code

All code used to obtain results can be found at https://github.com/ReidarRiveland/Instruct-RNN.

Methods References

[57] Samuel R. Bowman, Gabor Angeli, Christopher Potts, and Christopher D. Manning. A large annotated corpus for learning natural language inference. *CoRR*, abs/1508.05326, 2015.

[58] Jane Bromley, James W Bentz, Léon Bottou, Isabelle Guyon, Yann LeCun, Cliff Moore, Eduard Säckinger, and Roopak Shah. Signature verification using a "siamese" time delay neural network. *International Journal of Pattern Recognition and Artificial Intelligence*, 7(04):669–688, 1993.

[59] Junyoung Chung, Caglar Gulcehre, KyungHyun Cho, and Yoshua Bengio. Empirical evaluation of gated recurrent neural networks on sequence modeling. *arXiv preprint arXiv:1412.3555*, 2014.

[60] Ilya Sutskever, Oriol Vinyals, and Quoc V. Le. Sequence to sequence learning with neural networks. *CoRR*, abs/1409.3215, 2014.

[61] Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Rémi Louf, Morgan Funtowicz, and Jamie Brew. Huggingface's transformers: State-of-the-art natural language processing. *CoRR*, abs/1910.03771, 2019.