Distinguishing shadows from surface boundaries using local achromatic cues

Abbreviated Title: Distinguishing shadows from surface boundaries

Christopher DiMattina[1,2,3,*], Josiah Burnham[1,4], Betul Guner[1,3], Haley Yerxa[1,4]

[1]Computational Perception Laboratory, [2]FGCU Computational Facility, [3]Department of Psychology, & [4]Department of Software Engineering

Florida Gulf Coast University, Fort Myers, FL, USA 33965-6565

*Corresponding Author:
      Christopher DiMattina
      Whitaker Hall Room 215
      Florida Gulf Coast University
      10501 FGCU Blvd S.
      Fort Myers, FL 33965-6565

      Email: cdimattina@fgcu.edu
      Web: http://itech.fgcu.edu/faculty/cdimattina/
      Tel: (239)-590-1513

Conflict of Interest: The authors declare no competing financial interests.

Funding: This work was funded by NIH-R15-EY032732-01 to C.D.

Acknowledgements: We would like to thank FGCU graduates Michele DeAngelis and Lauren Anderson for help with developing the shadow database.

ABSTRACT

In order to accurately parse the visual scene into distinct surfaces, it is essential to determine whether a local luminance edge is caused by a boundary between two surfaces or a shadow cast across a single surface. Previous studies have demonstrated that local chromatic cues may help to distinguish edges caused by shadows from those caused by surface boundaries, but the information potentially available in local *achromatic* cues like contrast, texture, and penumbral blur remains poorly understood. In this study, we develop and analyze a large database of hand-labeled achromatic shadow edges to better understand what image properties distinguish them from occlusion edges. We find that both the highest contrast as well as the lowest contrast edges are more likely to be occlusions than shadows, extending previous observations based on a more limited image set. We also find that contrast and spatial frequency content can reliably distinguish the two edge categories with roughly 70% accuracy at 40x40 resolution. Logistic regression on a Gabor Filter bank (**GFB**) modeling a population of V1 simple cells separates the categories with roughly 80% accuracy, and furthermore exhibits tuning to penumbral blur. A Filter-Rectify Filter (**FRF**) style neural network extending the **GFB** model performed at roughly 90% accuracy and exhibited sensitivity to texture differences as well as penumbral blur. Comparing the performance of humans performing the same occlusion/shadow classification task as the models using the same stimuli reveals better agreement on an image-by-image basis between human performance and the **FRF** model than the **GFB** model. Taken as a whole, the present results suggest that in addition to color, local contrast, penumbral blur, texture cues may also play an important role in distinguishing edges caused by shadows from those caused by surface boundaries.

INTRODUCTION

Luminance edge detection is an essential visual computation for identifying the boundary between two surfaces (**Marr, 1982**; **Martin, Fowlkes & Malik, 2004; DiMattina, Fox, & Lewicki, 2012; Mely, Kim, McGill, Gou, & Serre, 2016**). However, it is well known that in natural images, luminance edges may arise from several causes other than surface boundaries: Specular reflections, changes in material properties, changes in surface orientation, and cast shadows all can give rise to changes in luminance that do not correspond to surface boundaries (**Ramachandran 1988; Mamassian, Knill, & Kersten, 1998; Vilankar, Golden, Chandler, & Field, 2014; Casati & Cavanagh, 2019**). Shadows are one class of luminance edge which are essential for to distinguish from other potential causes, since shadows do not indicate a change in surface reflectance properties, but simply a change in illumination (**Olmos & Kingdom, 2004**; **Kingdom, 2008, 2019**).

Recent work has addressed the question of how the visual system distinguishes material or reflectance edges from shadow edges in natural vision (**Breuil, Jennings, Bartheleme, Guyader, & Kingdom, 2019**). In their study, human observers classified both color and grayscale image patches viewed through an aperture as either shadow edges or material edges. These authors found that observers performed significantly better with the color images, and that a machine classifier making use of chromatic cues outperformed a machine classifier only using luminance cues. These findings are consistent with several studies suggesting an important role for color in distinguishing illumination from material (reviewed in **Kingdom, 2008, 2019**). In addition to improved performance with chromatic information, these investigators also observed improved performance with increasing aperture size. However, a similar improvement with aperture size was not observed with their machine classifiers. This may be because at larger spatial scales, texture information

becomes available which is not available at smaller spatial scales. Such information can be exploited by the human observers, but not by their machine classifiers, which did incorporate any texture measurements.

Here we address the question of what locally available *achromatic* information is available to distinguish surface occlusion boundaries from cast shadows. At least three possible sources of information are potentially available: (1) Differences in luminance, (2) Differences in spatial luminance profiles, and (3) Texture cues. Pursuant to (1), quantitative Bayesian classifier analyses demonstrate that on average occlusions can be distinguished from non-occlusions (with shadows being one kind of non-occlusion edge) using only Michaelson contrast (**Vilankar et al., 2014**). However, in this study a fairly limited set of images was used, and it did not focus specifically on shadows. Pursuant to (2), it is well known that the luminance edges arising from shadows are often more gradual than those arising from surface boundaries due to penumbral blur (**Casati & Cavanagh, 2019**), and furthermore human observers can reliably distinguish sharp and blurred edges (**Watson & Ahumada, 2011**). Pursuant to (3), although texture segmentation is extremely well studied both psychophysically and computationally (**Landy & Graham, 2004; Victor, Chubb & Conte, 2017**), to our knowledge no psychophysical work has directly considered the role of local texture cues for classifying shadow and occlusion edges.

To address these questions, we develop a publicly available database of shadow edges by hand-labeling a set of N = 47 natural images from the McGill Color Calibrated Image Database (**Olmos & Kingdom, 2004**). We compare basic contrast and spatial frequency statistics of these shadow edges to the same properties measured from a novel occlusion database derived from a subset of 20 of the 47 images, as well as a previously published occlusion database containing 100 images (**DiMattina et al., 2012**). We demonstrate that machine classifiers defined using only 3

statistics can reliably discriminate 40x40 patches containing shadows from patches containing surface boundaries at roughly 70% accuracy. We then evaluated the ability of an image-computable model comprised of a population of multi-scale Gabor filters resembling V1 simple cells to distinguish these two categories, attaining nearly 80% accuracy. Furthermore, we found that our Gabor filter bank (**GFB**) model exhibited clear tuning to penumbral blur, which often accompanies shadows. To test the hypothesis that local texture cues may be used to distinguish shadows from occlusion boundaries, we next trained a Filter-Rectify-Filter (**FRF**) model (**Landy & Graham, 2004; Zavitz & Baker, 2013, 2014; DiMattina & Baker 2019, 2021**) to solve the classification problem. Our best **FRF** model could classify 40x40 image patches at roughly 90% accuracy, and analysis of the hidden units in these trained models demonstrated that many represented spatial differences in texture. Additional testing of the **FRF** model revealed reduced performance with the removal of texture information, further underscoring the importance of local textures cues.

To compare human performance with that of machine classifiers, we performed a simple psychophysical experiment where observers classified 40x40 grayscale image patches as occlusion or shadow edges. We found that human observers performed on average somewhat worse than either of the machine classifiers (**GFB**, **FRF**), with the best human observers roughly equivalent to the **GFB** model and markedly worse than the **FRF** model. However, by correlating human and model classifications on an image-by-image basis, we observed a stronger correlation between human behavior and the **FRF** model than the **GFB** model. As the **FRF** model exhibits a strong sensitivity to texture cues, these results suggest that human observers are making use of textural cues to classify luminance changes as shadows or occlusions.

Overall, our results show that there are multiple, locally available achromatic cues which the visual system can potentially exploit to distinguish luminance changes arising from shadows from those caused by occlusion boundaries. It is of great interest for future research to explore the extent to which human observers utilize these various cues and how they combine with each other, and in the **DISCUSSION**, we suggest several future psychophysical and physiological experiments motivated by our current results.

RESULTS

Shadow edge database

Four observers hand-labeled all of the shadow boundaries in a set of N = 47 images (786 x 576 pixel resolution) taken from the McGill calibrated color image database (**Olmos & Kingdom, 2004**). Two images from our shadow database (**shad**), together with the shadow edges annotated by one observer, are shown in the top panels of **Fig. 1a.** A binary overlay of the labels obtained from all four observers is shown in the bottom panels of **Fig. 1a.** To compare the statistical properties of shadow edges with occlusion edges, we utilized a previously developed database (**DiMattina et al., 2012**) of hand-labeled occlusion boundaries taken N = 100 images from the McGill Dataset (**oset-1**). In addition to **oset-1**, we also developed a second occlusion database (**oset-2**) from a subset of shadow database images (20 out of 47 images) by having the same four observers hand label occlusions in these images. Two images from **oset-2** along with their hand-labeled occlusions are shown in **Fig. 1b**. All three databases (**shad**, **oset-1**, **oset-2**) are freely available to the scientific community at: https://www.fgcu.edu/faculty/cdimattina/.

Analysis of image patch statistics

Contrast statistics

Previous investigators have characterized some of the statistical properties of occlusion edges and non-occlusion edges (including shadows) in natural scenes (**Vilankar et al., 2014**; **Breuil et al., 2019**). To connect with these previous explorations, we measured some of these quantities from both the occlusion and shadow edges: (1) RMS contrast c_{RMS} (**Eq. 2**), and (2) Michelson contrast c_M (**Eq. 3**). All analyses were performed on 40x40 pixel (5% of larger image dimension) image patches from one of our databases (**shad**, **oset-1**, **oset-2**), with the constraint that all patches were

centered on a human-labeled edge (shadow or occlusion). Examples of image patches randomly selected from each dataset can be seen in **Supplementary Fig. S1**.

Figure 2a plots the overlaid probability distributions of these quantities for the shadow images (magenta curves) and both occlusion databases (**oset-1**: *top*, **oset-2**: *bottom*, green curves). We see that the distribution of Michelson contrast (c_M) for occlusions (green lines) spans the entire range of observed values, with occlusion edges giving rise to both the highest and lowest values. Furthermore, we see that occlusion edges are much more likely than shadow edges (magenta lines) to have very low values of c_M. We obtained median values of $c_M = 0.51$ for our shadow set, and $c_M = 0.30, 0.33$ for **oset-1** and **oset-2**, respectively. Median values are significantly different between shadows and both occlusion sets (rank-sum test, $p < 0.001$). Similar results were obtained for RMS contrast (c_{RMS}), although in this case the discrepancy between categories was smaller, and the distribution for occlusions was closer in shape to a normal distribution. For RMS contrast, we obtained median values of $c_{RMS} = 0.64$ for the shadows and $c_{RMS} = 0.47, 0.59$ respectively. Median values are significantly different between shadows and both occlusion sets (rank-sum test, $p < 0.001$). Large and highly significant positive correlations (Pearson's r) were observed between these two contrast measures for all datasets (**oset-1**: $r = 0.754$, $p < 0.001$; **oset-2**: $r = 0.722$, $p < 0.001$, **shad**: $r = 0.743$, $p < 0.001$).

Our finding that the lowest-contrast edges (by both measures) were occlusions rather than shadows is consistent with the fact that occlusion edges can often arise from two surfaces having identical mean luminance (**DiMattina et al., 2012**), whereas by definition a shadow edge requires a change in luminance. However, in agreement with previous measurements using a different set of occlusion patches identified using different methodology (**Vilankar et al., 2014**), we see that the far-right tails of the contrast distributions are dominated by occlusions, meaning that the

highest contrast edges are more likely to be occlusions rather than shadows. Since 19 of the 38 images analyzed by **Vilankar et al. (2014)** were also contained in **oset-1**, we repeated our analysis on this subset of images, finding results consistent with our analyses based on the full image set (**Supplementary Fig. S2**).

We also see from **Fig. 2a** that in our sample the distribution of c_M (but not c_{RMS}) appears to have some degree of bimodality. Most likely this reflects the properties of our database rather than the physics of shadow formation, as our shadow set contained a sub-set of images taken in conditions of strong illumination from a point source (the sun). Comparing the green curves on the top and bottom of **Fig. 2a**, we see a strong qualitative consistency between both sets of occlusion images. This provides us with reassurance that our measurements of contrast statistics reflect the general properties of occlusion edges rather than the idiosyncrasies of our databases.

Fig. 2b shows scatterplots of our measured quantities (c_M, c_{RMS}) for both occlusion (green symbols) and shadow edges (magenta) for both sets of occlusions. Dashed lines indicate the equal category probability contour obtained by fitting a logistic regression classifier to a test set (not shown). For **oset-1**, a classifier using these two cues can separate the test set shown here (not used to train the classifier) with an accuracy of 68.7%. For **oset-2**, the classifier separates the two categories in the test set with an accuracy of 69.6%.

Fig. 3 (*left + center*) illustrates examples of image patches near the 10[th], 50[th], and 90[th] percentiles when the 4000 images are sorted by each contrast measure (each patch is at most 8 ranks from the exact percentile rank). **Fig. 3a** shows occlusion images from both sets, and **Fig. 3b** shows the shadow images.

In our analyses, we applied our measurements to the grayscale converted (**Eq. 1**) RGB values obtained from the linearized images without any pre-normalization. This is because such operations may potentially reduce contrast cues. However, repeating these analyses where each individual linearized image patch was also normalized to lie in the range [0, 1] yielded nearly identical results (**Supplementary Fig. S3**). Normalization did not affect the accuracy of linear classification using the contrast statistics (**oset-1**: 70.7%, **oset-2**: 71.4%).

Spatial frequency statistics

As we see from inspection of **Fig. 3** and **Supplementary Fig. S1**, another potential cue for distinguishing shadow edges from occlusions is that often (but not always) shadows exhibit a gradual transition between luminance levels due to penumbral blur (**Casati & Cavanagh, 2019**). Therefore, we should expect that edges arising from shadows may have less energy in higher spatial frequency (SF) ranges than those arising from occlusions. Furthermore, occlusions may exist without any change in luminance, and have high-contrast high-SF textures on both sides of the boundary, whereas with shadows the texture on the darker half will generally have lower contrast. Analysis of the proportion π_h of stimulus energy at higher spatial frequencies (which we define as those frequencies above 10 cycles/image, with 20 cycles/image being the Nyquist limit) reveals that indeed there are significant differences between occlusions and shadows (**Fig. 4a**). Comparison of π_h distribution medians (rank-sum test) yielded significant results for both **oset-1** (occlusion median = 0.076, shadow median = 0.060, $p < 0.001$) and **oset-2** (occlusion median = 0.078, shadow median = 0.060, $p < 0.001$). Similar results were obtained when we increased our cutoff for high spatial frequencies to 15 cycles/image. Averaging the amplitude spectrum obtained from each patch (**Fig 4b**) reveals more energy at higher spatial frequencies for the occlusion images compared to shadow images. **Fig. 4c, d** shows scatterplots of π_h versus c_M and c_{RMS} for

both **oset-1** (*left*) **and oset-2** (*right*). Significant negative correlations were observed between both contrast measures and π_h for both occlusion sets and the shadow set. That is, higher contrast edges had a smaller proportion of their energy in high spatial frequencies. This makes sense because as we see from **Fig. 3**, the highest contrast edges (of either category) tend to have a strong difference in illumination over the spatial scale of the entire patch, which would give rise to a large low-spatial frequency component, as well as decreased energy at high SFs on the darker side. For occlusion **oset-1**, we obtain correlations between π_h and c_M, c_{RMS} of -0.492, -0.261, respectively ($p < 0.001$ both tests). For occlusion **oset-2**, we a obtain correlations between π_h and c_M, c_{RMS} of -0.315, -0.145, respectively ($p < 0.001$ both tests). For the **shad** set, we obtain correlations between π_h and c_M, c_{RMS} of -0.414 ($p < 0.001$) and -0.052 ($p = 0.002$).

Fig. 3a (*right*) shows edges from each set corresponding to the 10[th], 50[th], and 90[th] percentiles of π_h, and **Fig. 3b** (*right*) shows shadows at these same percentiles. We see occlusions with high values of π_h tend to arise when one or both adjacent surfaces is comprised of high-spatial frequency textures, and that shadows with high values of π_h occur when the shadow overlays a high-spatial frequency texture pattern. Although we observe significant differences in our measure of high spatial frequency content between edges and shadows (**Fig. 4b**), we find that when we add this variable to our logistic regression model, we do not observe an improvement in discrimination performance. Regressing on all three variables yielded performance of 68.5% for **oset-1** and 69.4% for **oset-2**. Performance was nearly identical for contrast variables measured from [0, 1] normalized images (**oset-1**: 72.8%, **oset-2**: 71.6%).

Image-computable machine learning classifiers

Our analysis of image patch statistics demonstrated that simple features like contrast and spatial frequency could separate the two categories well above chance at a resolution of 40x40 pixels. However, this simple set of intuitively defined features does not exhaust all the information potentially available to human or machine observers to separate these two categories. Therefore, we next considered the performance of various image-computable machine learning classifiers to gain insight into possible visual cues supporting edge classification.

Pixel-based classifier

We first considered the ability of a pixel-based (**PIX**) classifier (**Fig. 5a**) to separate these two categories. This linear template-based classification scheme suffers from the problem that our image patches were only loosely aligned, with the only restrictions being that the center pixel in each patch was an edge, the contour had a mean vertical orientation, and the left side was darker. Nevertheless, at the optimal hyperparameter value (**Supplementary Fig. S4**), we found reasonably strong performance of the **PIX** classifier for predicting the category for 4 test-sets of 1000 images not used for training or hyper-parameter optimization (**Table 1**). For **oset-1**, over 4 sets the average performance was 73.6% correct, and for **oset-2**, over 4 sets the average performance was 69.8%. These numbers are commensurate with the simple feature-based classifiers described in the previous section.

Set	PIX		GFB		FRF-4		FRF-6		FRF-10	
	os-1	*os-2*	*os-1*	*os-2*	*os-1*	*os-2*	*os-1*	*os-2*	*os-1*	*os-2*
65	0.728	0.681	0.798	0.791	0.875	0.886	0.884	0.889	0.883	0.898
66	0.744	0.704	0.800	0.820	0.879	0.923	0.888	0.910	0.902	0.930
67	0.733	0.717	0.810	0.800	0.874	0.895	0.889	0.894	0.902	0.904
68	0.740	0.690	0.789	0.804	0.865	0.878	0.879	0.888	0.888	0.892
AVG	*0.736*	*0.698*	*0.799*	*0.804*	*0.873*	*0.896*	*0.885*	*0.895*	*0.894*	*0.906*

Table 1: Classifier performance on test sets not used for training or hyper-parameter optimization.

Fig. 5b shows the linear templates learned by the **PIX** classifier trained on both stimulus sets. We see that the filters seem to combine a whole-patch luminance difference operation with a centrally located Gabor function that would be optimally activated by a sharp edge. Indeed, we see that when this classifier is presented with artificial edges having varying degrees of penumbral blur (**Fig. 5c**), the edge probability decreases (conversely, the shadow probability increases) as one increases the level of blur (**Fig. 5d**).

Gabor filter classifier

The initial representation of local image regions in the visual cortex is computed by the population of V1 simple cells, which are well modeled as bank of multi-scale linear Gabor filters with half-wave rectified outputs. We performed binomial logistic regression on the rectified and down-sampled (MAX pooling) outputs of a bank of physiologically plausible oriented Gabor filters (**Kovesi, 2000; Field, 1987**) defined at multiple spatial scales (8x8, 16x16, 32x32). We refer to this model illustrated in **Fig. 6a** as the **GFB** (Gabor Filter Bank) classifier, and Gabor filters at one spatial scale are illustrated in **Supplementary Fig. S5**. As we see from **Table 1**, the **GFB** classifier performed significantly better than the **PIX** classifier, and its performance was robust over a range of regularization hyper-parameters (**Supplementary Fig. S5**). For **oset-1**, over 4 sets the average performance was 79.9% correct and for **oset-2**, over 4 sets the average performance was 80.4% correct. As with the **PIX** classifier, we find that the **GFB** classifier exhibits sensitivity to

penumbral blur (**Fig. 7a**). By comparing the scales of the vertical axes with **Fig. 5d**, we see that it exhibits much more sensitivity than the **PIX** classifier.

To further understand model classification performance, we sorted a set of 1000 images (half shadow, half occlusion) not used for model training by the probability of being classified as an occlusion. We see from **Fig. 8a** that for each set of patches (**oset-1**: *left*, **oset-2**: *right*), the model occlusion probability varies continuously from 0 to 1, with most actual occlusions (shadows) being predicted to have a greater (less) than 50% chance of being occlusions, as indicated by the density of the symbols (+) indicating actual category (1 = occlusion, 0 = shadow). **Fig. 8b** shows patches from each category (occlusions: *green*, shadows: *magenta*) sorted by their occlusion probability. Applying the rule that patches with occlusion probability > 0.5 are categorized as occlusions, we see that shadows are much more likely to be mis-classified by the **GFB** (**oset-1**: 28.6% of shadows mis-classified, **oset-2**: 22.8%) than the other way around (**oset-1**: 9.4% of occlusions mis-classified, **oset-2**: 13.2%).

To determine the stimulus which would be judged by the **GFB** classifier as having the highest occlusion probability, we numerically found the stimulus to maximize the model output, shown in **Fig. 9a** (*left*). These stimuli seem to feature a high spatial frequency edge at the center of the image patch, with consistent results for both training sets. By minimizing the **GFB** classifier output, we can find the stimuli most likely to be classified as shadows (**Fig. 9a,** *right*). Note that these stimuli are mostly 'flat' near the center of the image patch. Unfortunately, neither of these stimuli obtained via optimization visually resembles the actual image patches from either category. Therefore, we can gain better intuition for what each model is looking for by plotting the edges (of both categories) most likely to be classified as occlusions or shadows, as shown in **Fig. 10**. Each quadrant shows a combination of actual category (vertical dimension) and predicted category

(horizontal dimension). We see that the occlusions most likely to be correctly classified as occlusions (*top left*) have low contrast with a sharp boundary between regions and quite often differences in texture on opposite sides of the border. The occlusions most likely to be mis-classified as shadows (*top right*) tend to have higher contrast and a somewhat more blurred edge. The shadows mis-classified as occlusions (*bottom left*) tend to have lower contrast and/or a sharper edge. And finally, the shadows which are most likely to be correctly classified (*lower right*) have high contrast and blurry edges.

Although we observe reasonably strong classification performance by the **GFB** model, it is unlikely to exploit all available information for distinguishing the two categories, even at the relatively localized scale tested here (40x40 pixels). One obvious reason is that texture differences, which provide strong evidence in favor of an occlusion and against a shadow, cannot be well represented by a population of linear spatial filters. In fact, it is well known that detecting texture boundaries requires multiple stages of filtering, as exemplified by the well-known "Filter-Rectify-Filter" (**FRF**) model of second-order vision (**Landy & Graham, 2004**). Given these obvious inadequacies, we next considered the ability of multi-layer neural networks implementing **FRF** models which can exploit texture information to classify these kinds of edges.

Filter-rectify-filter classifier

We next considered the performance of a Filter-Rectify-Filter (**FRF**) model to classify occlusion and shadow edges (**Fig. 6b**). **FRF** models have been long used for modeling texture segmentation (**Malik & Perona, 1990; Bergen & Landy, 1991; Baker, 1999; Landy & Graham, 2004; Zavitz & Baker, 2013, 2014; DiMattina & Baker, 2019, 2021**) and are mathematically similar to three-layer connectionist neural networks (**Rumelhart, Hinton, & Williams 1986; Bishop, 2006; Goodfellow, Bengio, & Courville, 2016**). The first filtering layer of this network was comprised

of the fixed, multi-scale Gabor filter bank used in the **GFB** classifier (**Fig. 6a**). The rectified, down-sampled outputs of this filter bank were then fed to a population of K hidden units ($K = 4, 6, 10$), the rectified outputs of which were linearly combined form a decision variable, which is finally passed into a sigmoid function to predict the occlusion probability.

Adding this hidden layer greatly improved classification performance, as one can see from **Table 1**. Averaged over 4 test folds not used for training or validation, for each **FRF** model and each set of test stimuli (**oset-1**, **oset-2**), performance approached or even exceeded 90% accuracy. Furthermore, we find that the effects of increasing the number of hidden units was quite modest, observing similar performance from all **FRF** models. As with the **GFB** model, we find in the **FRF** models a strong sensitivity to penumbral blur (**Fig. 7b**). **Fig. 8c** shows for **FRF-6** the predicted occlusion probabilities of the same two test sets evaluated on the **GFB** model, with **Fig. 8d** breaking down the patches by category (occlusions: *red*, shadows: *magenta*). In contrast to the **GFB** classifier, we see similar mis-classification rates for both occlusions (**oset-1**: 11.2%, **oset-2**: 10.2%) and shadows (**oset-1**: 11.0%, **oset-2**: 7.8%). Therefore, while both classifiers have similar performance for correctly classifying occlusions, the **FRF** classifier does a much better job of correctly identifying shadows. Similar results were obtained for **FRF-4** and **FRF-10** (**Supplementary Fig. S6**). Misclassification rates for all **FRF** classifiers, trained on both sets, are given in **Table 2**.

	Gabor		FRF-4		FRF-6		FRF-10	
	occl	*shad*	*occl*	*shad*	*occl*	*shad*	*occl*	*shad*
oset-1	0.094	0.286	0.162	0.090	0.112	0.108	0.092	0.104
oset-2	0.132	0.228	0.084	0.070	0.102	0.078	0.086	0.054

Table 2: Image mis-classification rates by category.

Fig. 11 shows the actual and predicted categories of the image patches in **oset-1** the **FRF-6** model predicts to have the highest probability of category membership, as in **Fig. 11**. We see that as with the **GFB** model, occlusions correctly classified as such (*top left*) tend to have low contrast and sharp borders, and shadows correctly classified as such (*bottom right*) tend to have high contrast and blurred borders. Occlusion patches mis-classified as shadows tend to have high contrast and smoother boundaries (*top right*), whereas shadows mis-classified as occlusions (*bottom left*) have lower contrast and sharper boundaries.

Since the performance of the **FRF** models is substantially better than the **GFB** model (by about 7-10% - see **Table 1**), it is of great interest to determine which image patches are correctly classified by the **FRF** models while being mis-classified by the **GFB** model. **Supplementary Fig. S7** shows a random selection of patches of each category that were correctly classified by the **FRF-6** model but not the **GFB** model. We see that many of the occlusions have high contrast and gradual borders, but visible texture differences on opposite sides that may have been picked up the **FRF** model but not the **GFB** model. Similarly, we see that many of the shadows correctly classified by the **FRF** model have the same texture but different shading on opposite sides.

To see what the hidden units in the **FRF** model are "looking for", we performed numerical optimization to find the stimulus that maximizes the response of each hidden unit. Results of this procedure are shown in **Fig. 12** for the **FRF-4**, **FRF-6** models. The weights do not clearly resemble either image category, or known receptive field structures, but we see that many of these units are capable of encoding differences in texture on opposite sides of the boundary. Numerically optimizing the model output to find the stimulus most likely to be classified as an occlusion or shadow, we obtain the stimuli shown in **Fig. 9b-d** for **FRF-4**, **FRF-6**, and **FRF-10**. We see that the stimulus most likely to be classified as an occlusion has high contrast texture on the left side,

and no texture on the right side. In comparison to the **GFB** model (**Fig. 9a**), there is less emphasis

on the boundary, and more on textural differences. Consistent with the **GFB** model, images likely

to be shadows are fairly "flat" in the middle.

To see how classification accuracy is affected as we reduce the pixel resolution, we

repeated our analysis using **FRF-4, FRF-6 and FRF-10** models for resolutions of 24, 16 and 8

pixels. As we see in **Table 3** reducing resolution drastically impairs the performance of our **FRF**

models. Comparing with **Table 1**, reducing the pixel resolution from 40x40 to 24x24 results in

about a 10% decrease in classification performance. This analysis is consistent with the hypothesis

that locally available texture information is useful for accurate edge classification by the **FRF**

model. By contrast, reducing the pixel resolution had a much less drastic effect on the performance

of the **GFB** model. For the **GFB** model, reducing the resolution 40x40 to 24x24 results in about a

5% decrease in classification performance (compare **Table 3** and **Table 1**). This suggests that the

GFB model is less sensitive to the removal of texture cues than the **FRF** model.

Size	GFB		FRF-4		FRF-6		FRF-10	
	oset-1	*oset-2*	*oset-1*	*oset-2*	*oset-1*	*oset-2*	*oset-1*	*oset-2*
8	0.6898	0.7077	0.7127	0.7115	0.7225	0.7320	0.7330	0.7325
16	0.7728	0.7523	0.7708	0.7533	0.7675	0.7710	0.7700	0.7673
24	0.7438	0.7695	0.7798	0.7750	0.7905	0.7850	0.7870	0.7988

Table 3: Model performance for reduced size images, averaged over 4 test sets.

To test the importance of texture cues for the **FRF** model more directly, we performed a

simple image manipulation procedure to remove texture information from occlusions (**DiMattina

et al. 2012**). Our method simply sets the intensity of each pixel on each side of the boundary equal

to the mean value measured from that side. This manipulation leaves the image Michelson contrast

(**Eq. 3**) unchanged since the mean intensity on each side remains identical. Examples of occlusion

patches manipulated in this manner are shown in **Fig. 13a**. The output of the **GFB** and **FRF** models

is an occlusion probability p (with shadow probability being $1 - p$). The output of each model is computed from the log-odds ratio $u = \ln \frac{p}{1-p}$ by applying the logistic link function. Therefore, we may recover the log-odds ratio by applying the inverse logistic link function σ^{-1} applied to the predicted occlusion probability. A positive log-odds ratio indicates that an image patch is more likely to be an occlusion, and a negative log-odds ratio indicates a shadow. **Fig. 13b** plots the log-odds ratio for the original occlusion images (*horizontal axis*) and the texture removed images (*vertical axis*) from **oset-1** (*top*) and **oset-2** (*bottom*). Values greater than zero indicate patches that are (correctly) classified as being occlusions, less than zero indicates patches mis-classified as shadows. We see that patches predicted to have a higher probability of being occlusions experience a much greater reduction in occlusion probability when texture is removed. This change in probability is shown explicitly in **Fig. 13c**, which plots the log-odds ratio of the original images against the difference Δ in log-odds ratios. A strong positive correlation of the original log-odds ratio with Δ was observed for both **oset-1** ($r = 0.9594$, $p < 0.001$, N = 191) and **oset-2** ($r = 0.9755$, $p < 0.001$, N = 596).

Interestingly, we see that occlusions which were mis-classified as shadows (original log-odds < 0) increase their occlusion probability, likely because the texture-removal operation creates a sharp boundary (**Fig. 13a**), thereby eliminating the blur which is taken as evidence for a shadow (**Fig. 7**). **Fig. 13d** explicitly plots a histogram of Δ for correctly classified occlusions for **oset-1** (*left*) and **oset-2** (*right*). Statistical testing reveals significantly positive (Wilcoxon rank-sum test) median value of Δ for both sets (**oset-1**: 0.72, $p < 0.001$; **oset-2**: 2.07, $p < 0.001$). **Fig. 13e** is the same as **Fig. 13d** but for occlusion patches which were incorrectly classified as shadows. We find a significantly negative median value of Δ for both sets (**oset-1**: -2.33, $p < 0.001$; **oset-2**: -2.41, $p < 0.001$). Similar results were obtained for **FRF-4**, **FRF-10**, as summarized in **Table 4**.

	occlusion		shadow	
	oset-1	*oset-2*	*oset-1*	*oset-2*
FRF-4	0.57	0.93	-2.51	-1.92
FRF-6	0.72	2.07	-2.33	-2.41
FRF-10	0.36	1.21	-2.68	-2.34

Table 4: Median values of Δ for occlusions classified as occlusions or incorrectly classified as for all **FRF** models (**oset-1**: N = 191; **oset-2**: N = 596) Median values were significantly different from zero with $p < 0.001$ (Wilcoxon rank-sum test).

Psychophysical experiment

Individual observer performance

A single-interval forced choice experiment was performed in which human observers classified 40x40 pixel grayscale natural image patches as being shadow or occlusion edges (see **METHODS** for details). This experiment is schematically illustrated in **Fig. 14a**, and was implemented online using Qualtrics for stimulus presentation and recording responses (**Supplementary Fig. S8**). **Fig. 14b** (*left*) shows the performance (proportion correct π_c) of all N = 18 observers who completed all three online experiments (with above-chance performance on the final two). We find the median observer (*large blue circles*) had performance of $\pi_c = 0.69$ (**QT-1**), $\pi_c = 0.688$ (**QT-2**), $\pi_c = 0.740$ (**QT-3**), with the best observer attaining performances (*black diamonds*) of $\pi_c = 0.805$, $\pi_c = 0.755$, $\pi_c = 0.80$ respectively. Performance was not significantly correlated across surveys for 2 of 3 possible pair-wise comparisons (**QT 1/2**: $r = 0.222$, $p = 0.376$; **QT 1/3**: $r = 0.54$, $p = 0.021$; **QT 2/3**: $r = 0.129$, $p = 0.611$). Therefore, for many analyses we pooled data across surveys. In these cases, the units of analysis will be referred to as *observer-surveys*. **Fig. 14b** (*right*) also shows performance quantified as d' for all experiments, and we observe a strong positive correlation between d' and π_c for each survey (**QT-1**: $r = 0.998$, $p < 0.001$; **QT-2**: $r = 0.993$, $p < 0.001$; **QT-3**: $r = 0.957$, $p < 0.001$) and across all N = 54 observer-surveys ($r = 0.985$, $p < 0.001$, N = 54).

Observer performance in standard signal detection theory is determined by the separation d' of the distributions of the decision variables corresponding to each category, as well as the decision criterion γ applied by the observer. In our SDT analysis, $\gamma < 0$ corresponds to a bias towards judging stimuli to be occlusions, and $\gamma > 0$ corresponds to a bias towards judging stimuli to be shadows. For 2 of the 3 surveys, the median value of γ was not found to be significantly different from zero using a Wilcoxon test (**QT-1**: median = 0.097, p = 0.042; **QT-2**: median = 0.082, p = 0.119; **QT-3**: median = -0.008, p = 0.856). Distributions of γ for each survey are shown in **Supplementary Fig. S9**. Pooling γ across surveys (**Fig. 14c**) reveals a median which was not significantly different from zero (Wilcoxon test, N = 54, median = 0.066, p = 0.059). Computing the ratio $|d'/\gamma|$ for $\gamma \neq 0$ (N = 51) reveals a median value of 8.78, with quartiles Q_1 = 3.92 and Q_3 =15.06. Therefore, any bias in the decision criterion is for most observers negligible compared to the distribution separation.

Since one of our goals is to compare human performance to that of machine observers, we want to not only compare the probability of correct response, but also the pattern of classification errors. For each observer and experiment, we measured the probability $P(s|O)$ that an occlusion was misclassified as a shadow, and the probability $P(o|S)$ that a shadow was misclassified as an occlusion. If there is no bias in either direction, the difference $P(s|O) - P(o|S)$ (**Fig. 14d**) should be zero. A positive value would indicate a greater likelihood of misclassifying occlusions as shadows than misclassifying shadows as occlusions. A negative value would indicate a greater likelihood of mis-classifying shadows as occlusions than the other way around. On an individual basis, this can be assessed using a difference of binomial proportion test (*Wald test*). Doing so revealed that over 54 observer-surveys (18 observers taking 3 surveys each), in 22/54 cases a significant bias was observed towards misclassifying one or the other stimulus categories. Of these,

6/22 observer-surveys exhibited a bias to misclassify occlusions as shadows, whereas in 16/22 observer-surveys we saw a bias to mis-classify shadows as occlusions. The proportion of observer-surveys which exhibited a significant bias to mis-classify shadows as occlusions does not differ significantly from chance (binomial proportion test, N = 22, p = 0.055). Over the full set of observer-surveys, comparing the median Wald statistic (**Fig. 14e**) to zero (sign-rank test) failed to reach the conventional criterion for statistical significance (median = -0.675, p = 0.057, N = 54).

Fig. 14f shows a scatterplot of $P(s|O)$ and $P(o|S)$, and we see that points are about equally likely to be above and below the diagonal.

Aggregate observer performance across images

In addition to analyzing performance of each individual observer, for each individual image (200 per set, for 3 image sets), we characterized the proportion of observers that classified it as a shadow or an occlusion. Doing this allows us to generate an *aggregate observer* (**AO**) model, which provides a model of average human performance against which the performance of machine classifiers (and other human observers not used to define the model) can be compared. Mathematically, the aggregate observer for K participants making a binary behavioral classification ($b = 0, 1$) of N images is given by $\mathcal{A} = \{\pi_i\}_{i=1}^n$, where π_i indicates the proportion of observers ($\pi_i = n_i/K$) for which $b_i = 1$. The **AO** model provides a statistical model of average human performance on the task. One can generate simulated datasets stochastically using the **AO** by generating response $b_i = 1$ to stimulus i with probability π_i, and response $b_i = 0$ with probability $1 - \pi_i$. Likewise, one can generate a stimulated dataset deterministically by setting $b_i = 1$ if $\pi_i \geq 0.5$, and $b_i = 0$ otherwise.

Fig. 15a shows the probability that each stimulus is classified as an occlusion by the **AO** (blue curves), with actual stimulus categories indicated by a black (+) symbol. We see that the overwhelming majority of the stimuli with low occlusion probability are shadows, and most stimuli with high occlusion probability are occlusions, with little bias in either direction. **Fig. 15b** breaks down these plots by the actual category of the image. **Tables 5-7** indicates the confusion matrices for each survey obtained from the **AO** using a deterministic rounding rule that sets $b_i = 1$ if $\pi_i \geq 0.5$, and $b_i = 0$ otherwise.

	predicted	
actual	*occlusion*	*shadow*
occlusion	88	12
shadow	19	81

Table 5: AO confusion matrix for experiment **QT-1**.

	predicted	
actual	*occlusion*	*shadow*
occlusion	74	26
shadow	21	79

Table 6: AO confusion matrix for experiment **QT-2**.

	predicted	
actual	*occlusion*	*shadow*
occlusion	88	12
shadow	24	76

Table 7: AO confusion matrix for experiment **QT-3**.

From these confusion matrices, we observe that the proportion correct for the **AO** (**QT-1**: 84.5%, **QT-2**: 76.5%, **QT-3**: 82.0%) is not significantly different from the best individual observer (95% CI of the difference: **QT-1**: [-0.034, 0.114], **QT-2**: [-0.074, 0.094], **QT-3**: [-0.057, 0.097]). Therefore, there seems to be a "wisdom of crowds" effect whereby averaging over a population of observers yields an aggregate observer that does as well as the best individuals. For each experiment, we tested whether the proportions of errors were biased in one or another direction,

with the null hypothesis being that the two proportions were equal. A binomial proportion test revealed no significant difference for **QT-1** ($p = 0.281$, N = 31), **QT-2** ($p = 0.559$, N = 47), or **QT-3** ($p = 0.066$, N = 36). Therefore, the **AO** is just as likely to mis-classify occlusions as shadows as it is to make the opposite error.

Comparison with machine classifiers

Correlation between log-odds ratios

For each image, the aggregate observer model (**AO**) specifies a probability that the image is an occlusion, much in the same manner as two machine classifiers investigated in an earlier paper. In order to see if images which were more likely to be categorized as occlusions by the **AO** were also more likely to be categorized as such by various machine observers, we developed a simple analysis procedure, which we now describe. Briefly, each of these machine classifiers at its final stage computes an intermediate variable $u_i = \ln \frac{p_i}{1-p_i}$ (the log-odds ratio) which is them passed through a monotonic sigmoidal non-linearity in order to compute a probability p_i of image i being an occlusion. By applying the inverse sigmoid function $u_i = \sigma^{-1}(p_i)$ to the probability computed by the model, we recover the value of the log odds ratio, which unlike the occlusion probabilities computed over the set of images (**Supplementary Fig. S10**) enjoys an approximately normal distribution. Applying this same inverse sigmoid function to the occlusion probability p_i computed from the **AO** permits recovers the corresponding log-odds $\sigma^{-1}(p_i)$ when $0 < p_i < 1$. Note that $\sigma^{-1}(0)$ and $\sigma^{-1}(1)$ are not well defined (being $-\infty$ and $+\infty$, respectively).

By correlating the log-odds ratios over the set of images for which it is defined, we can determine the extent various machine classifiers exhibit agreement with human observers. **Fig. 16** shows scatter-plots of the log odds ratios obtained from human and machine observers applied to

all images in each survey (**QT-1**, **QT-2**, **QT-3**) for both the **GFB** (*left column*) and **FRF** (*right column*) model. We see that each of these variables is approximately normally distributed for each category of image (*occlusions*: green, *shadows*: magenta), and observe significant positive correlations (Pearson's correlation r) between the **AO** and both the **GFB** (**QT-1**: $r = 0.565$, N = 185; **QT-2**: $r = 0.507$, N = 178; **QT-3**: $r = 0.532$, N = 166, $p < 0.001$ all tests) and **FRF** models (**QT-1**: $r = 0.654$, N = 185; **QT-2**: $r = 0.525$, N = 178 ; **QT-3**: $r = 0.654$, N = 166, $p < 0.001$ all tests). Although we see for each survey a stronger Pearson's correlation between the human data and **FRF** model than the **GFB** model, comparisons of these correlation coefficients failed to reached statistical significance (**QT-1**: $p = 0.1738$; **QT-2**: $p = 0.8181$, **QT-3**: $p = 0.0873$, two tailed tests), even when we pool data from all 3 experiments ($r_{\textbf{GFB}} = 0.531$, $r_{\textbf{FRF}} = 0.609$, $p = 0.0601$, N = 529, two-tailed test).

One limitation of the analysis presented above making use of the Pearson correlation between log-odds ratios is that it unfortunately excludes images which all human observers classify as "shadow" or "occlusion", since $\sigma^{-1}(p)$ is $-\infty$, $+\infty$ for $p = 0, 1$. The consequence of this is that lots of data which could potentially be useful for model comparison is excluded. To circumvent this problem, we can make use of non-parametric rank-order statistics (Spearman's rho ρ) to compute correlations between machine classifiers and the **AO** model using all the data. To test whether there was a stronger correlation between the **GFB** and **FRF** models and human behavior, we computed the Spearman correlation between the log-odds ratios from the **FRF** and **GFB** model and the **AO** for N = 1000 bootstrapped samples. We found that for all surveys a larger Spearman correlation between the **FRF** and the **AO** (**QT-1**: $\rho = 0.696$, **QT-2**: $\rho = 0.587$, **QT-3**: $\rho = 0.775$, $p < 0.001$ all tests) than the **GFB** and **AO** (**QT-1**: $\rho = 0.604$, **QT-2**: $\rho = 0.568$, **QT-3**: $\rho = 0.697$), and for 2/3 surveys the 95% CI of the difference did not contain zero (**QT-1**: [0.011,

0.183] , **QT-2**: [-0.067, 0.118], **QT-3**: [0.010, 0.165]). Pooling all three surveys also revealed a significantly larger correlation between the **FRF** and **AO** ($\rho = 0.692$) than the **GFB** and **AO** ($\rho = 0.624$), with a median difference $\Delta\rho = 0.068$ and the 95% CI of the difference $[0.022, 0.118]$ not containing zero. This analysis suggests that the **FRF** model is better capturing the aspects of the image humans are utilizing.

Decision variable correlation

We further explored the relative efficacy of the **FRF** and **GFB** models in accounting for human behavior using Decision Variable Correlation (**DVC**), an extension of signal detection theory (**Sebastian & Geisler, 2018**). This novel methodology assumes that for classification tasks both a human observer and a model (or two humans) make use of an internal, unobserved decision variable which each compares to some criterion to decide which stimulus was presented. Assuming the joint distribution of the human and model decision variables is a bivariate normal distribution with possibly non-zero covariance, by analyzing the patterns of agreement and disagreement between the model and human, it is possible to recover not only the distribution separations and decision criteria, but the covariance as well. DVC is particularly powerful for model comparison and selection, since it is possible for two models to predict performance (as percent correct) equally well, while not agreeing on which particular stimuli the human and model classify into each category. DVC has been fruitfully applied in several psychophysical domains including texture segmentation (**DiMattina & Baker, 2019**), stimulus detection in noise (**Sebastian, Semiller, & Geisler, 2020**), speed perception (**Chin & Burge, 2000**), and avian audition (**Henry & Abrams, 2021**).

Fig. 17a shows for surveys **QT-1**, **QT-2**, **QT-3** the DVC between each individual observer and each of the three models: **GFB**, **FRF**, and **AO**. We see for **QT-1** a significantly larger median

DVC for the **FRF** model than **GFB** model (sign-rank test, median **FRF**-**GFB** = 0.061, p = 0.001,

N = 18), and furthermore a significantly larger median DVC for the **AO** model than either **FRF**

(median **AO**-**FRF** = 0.052, p = 0.043) or **GFB** models (median **AO**-**GFB** = 0.114, p = 0.006). For

QT-2, we do not see a significant difference in DVC between the **FRF** and **GFB** models (median

FRF-**GFB** = -0.008, p = 0.349), but do see significantly better performance by the **AO** than either

FRF (median **AO**-**FRF** = 0.22, p < 0.001) or **GFB** (median **AO**-**GFB** = 0.192, p < 0.001).

Interestingly, for **QT-3** we see better median performance by the best machine classifier (**FRF**)

than the **AO** which was derived from other humans (median **AO**-**FRF** = -0.146, p = 0.022), as

well as better performance the **GFB** classifier (median **FRF**-**GFB** = 0.090, p = 0.02), which in

turn exhibited the same performance as humans (median **AO**-**GFB** = -0.037, p = 0.514). **Fig. 17b**

combines DVCs from all surveys. Here we observe significantly better performance for the **FRF**

model than the **GFB** model (median **FRF**-**GFB** = 0.045, p = 0.005), although we see the best

performance for the **AO** model (median **AO-GFB** = 0.142, p = 0.001; median **AO**-**FRF** = 0.061,

p = 0.021). **Fig. 17c** shows histograms of these differences between the DVCs for all model

comparisons, combined across the three surveys.

Analysis of mis-classification patterns

Another way to compare the performance of the models to human observers is to examine the

patterns of classification errors. If there is no bias in either direction in the pattern of mis-

classification errors, then the proportion of mis-classifications of shadows as occlusions (or vice

versa) should not differ from 0.5. This can be assessed for each machine classifier (**GFB**, **FRF**)

and the **AO** using a simple binomial proportion test. Here we list the proportion of classification

errors which involved classifying the patch as an occlusion (*occ/all*), together with the 95% CI of

the null hypothesis of equal probabilities of errors in either direction.

	QT-1		QT-2		QT-3	
	occ/all	*CI-95*	*occ/all*	*CI-95*	*occ/all*	*CI-95*
GFB	*10/33**	[10.9, 22.1]	13/34	[11.3, 22.7]	*12/44**	[15.5, 28.5]
FRF	9/17	[4.5,12.5]	*17/23**	[6.8, 16.2]	6/16	[4.1, 11.9]
AO	12/31	[10.0, 21.0]	26/47	[16.8, 30.2]	*12/36**	[12.1, 23.9]

Table 8: Number of mis-classifications of shadows as occlusions by each model.

We see from **Table 8** that for two surveys (**QT-1**, **QT-3**) the **GFB** is biased to make errors in the direction of shadows and away from occlusions, consistent with our previous observations. By contrast, for the **FRF** model, we only observe 1 survey with a bias (**QT-2**), this time in the direction of errors in favor of occlusions. Similarly, the **AO** only shows one survey with a bias (**QT-3**). Pooling across all three surveys (**QT-1**, **2**, **3**), for the **GFB**, 35/111 mis-classifications are in the direction of occlusions, with $p < 0.001$ (binomial proportion test, $N = 111$). By contrast, for the **FRF** model 32/56 mis-classifications are in the direction of occlusions, and we fail to see a significant bias ($p = 0.3496$, $N = 56$). Similarly, for the **AO**, 50/114 mis-classifications favor occlusions, exhibiting no significant bias ($p = 0.2234$, $N = 114$). Thus, we see a much stronger agreement between the **FRF** model and average human behavior (**AO**) based on patterns of mis-classification.

DISCUSSION

Summary of contributions

Here we analyzed the statistical properties of two important classes of luminance edges: (1) occlusion edges, and (2) shadow edges. Distinguishing these two possible edge causes has important implications for understanding perceptual organization, as one kind of edge indicates a surface boundary, whereas the other indicates a change in illumination. Following previous work (**Vilankar et al., 2014; DiMattina et al., 2012**), we measured basic contrast statistics from each category, demonstrating that occlusions exhibit both the highest observed contrasts, as well as the lowest contrasts. We also measured spatial frequency properties of each image category, demonstrating more high spatial frequency content in occlusion edges than shadows. V1 neurons are known to be sensitive to both spatial frequency and contrast (**Albrecht & Hamilton, 1982; Parker & Hawken, 1988**), so relevant information for discriminating these edge categories is potentially extracted at the earliest level of cortical processing. Implementing a simple Gabor Filter Bank (**GFB**) model inspired by V1 receptive field properties, we demonstrated that at a resolution of only 40x40 pixels these two edge categories can be distinguished at nearly 80% accuracy. Furthermore, we demonstrated that this model exhibits strong tuning to penumbral blur, an important shadow cue (**Mammasian et al., 1998**; **Elder, Trithart, Pintille & MacLean, 2004; Elder & Zucker, 1998**; **Elder, 1999; Casati & Cavanagh 2019**). To investigate the performance of models which can also take texture into account, we demonstrate that a Filter-Rectify-Filter (**FRF**) model, commonly used to model second-order vision (**Baker, 1999; Landy & Graham, 2004; Zavitz & Baker, 2013, 2014; DiMattina & Baker, 2019**), can perform at nearly 90% accuracy. Furthermore, this model's performance declines when texture information is removed, either by reducing image patch resolution or averaging regional pixel intensities.

The present study demonstrates that the absence of color information, relatively simple achromatic cues, and computations implemented by simple models, can reliably separate occlusions and shadows. Although there is most certainly an important role for contextual information from the larger scene in identifying shadow edges, locally available cues which are extracted early in the visual processing hierarchy potentially contribute substantial information to this process. This finding is consistent with many previous studies on edge detection (**McDermott, 2004; Zhou & Mel, 2008; DiMattina et al., 2012; Ing et al., 2010**), classification (**Vilankar et al., 2014; Ehinger, Adams, Graf, & Elder, 2017; Breuil et al., 2019**), and figure-ground assignment (**Burge, Fowlkes, & Banks, 2010; Ramenahalli, Mihalas, & Niebur, 2014**), all of which demonstrate that locally available information can provide information useful for global scene analysis. In the remainder of this **DISCUSSION**, we relate our findings to earlier studies, outline the limitations of our work, and consider possible future directions for research.

Relationship to previous psychophysical work

Most psychophysical studies concerning shadows have investigated the essential role that shadows play in three-dimensional scene interpretation (**Ramachandran, 1988; Elder et. al. 2004; Mammasian et al., 1998; Rensink & Cavanaugh, 2004; Wilder, Adams, & Murray, 2019**). By contrast, to our knowledge, only two previous studies directly speak to the issue of what locally available information can be used to distinguish shadows from other edge causes like occlusions (**Vilankar et al., 2014; Breuil et al., 2019**). We now discuss these studies in depth and how they relate to our present findings.

A previous investigation by **Vilankar et al. (2014)** characterized the statistical properties of achromatic occlusion edges and non-occlusion edges, a "catch-all" category including shadows, material changes, and surface orientation changes. Although they used local analysis windows

similar in size to our own (they used rectangular windows of 81x40 whereas we used square 40x40 windows), the images which they analyzed were at high resolution (1920x2560) as opposed to the lower resolution (576x786) images we analyzed. The consequence of this is that their analysis was more "local" than our own, with their smaller dimension (40) comprising only 1.56% of the larger dimension (2560) of the image patch, whereas our 40x40 patches subtended 5.08% of the larger dimension (786). Finally, their edges were initially identified using a Canny edge detector algorithm before being classified as occlusions or non-occlusions by human observers. As they note, this process clearly biases their samples towards edges containing stronger luminance differences, although they also analyzed a smaller set of hand-labeled edges and obtained similar results.

In their paper, they demonstrated that occlusions had higher contrast, on average, than non-occlusions. We found that when the comparison was restricted to occlusions and shadows, both the highest contrast patches as well as the lowest-contrast patches were occlusions (**Fig. 2**). Furthermore, when we analyzed occlusions from the subset of 19 images in **oset-1** that were also used in their study, the results were consistent with our general findings for both **oset-1** and **oset-2** (**Supplementary Fig. S2**). Therefore, it is unlikely that this discrepancy with our results arises from their use of a more limited image set (N = 38 images versus N = 100). It is important to note that there are two additional key differences which make direct comparison difficult: (1) We did not consider any non-occlusions apart from shadows in our analysis, and (2) They did not break down their non-occlusion stimuli into different categories in their analysis. Thus, it is possible that their finding that non-occlusions had lower contrast than occlusions would not have held if they had restricted themselves to only consider shadows.

Another interesting point of contact with **Vilankar et al. (2014)** is that in their study they plotted the luminance profiles of different categories of edges, including occlusions, non-occlusions, and shadows. They note a more gradual change in luminance for non-occlusions, including shadows, than for occlusions. We analyzed this using the FFT to demonstrate that on average occlusions have a greater proportion of their overall energy at high spatial frequencies, due in part to the fact that sharp edges require high spatial frequencies to approximate using a sum of cosines. Furthermore, all the image-computable models trained to distinguish shadows from occlusions exhibited tuning to penumbral blur, with increased blur leading to higher probability of an edge being classified as shadow (**Fig. 7**). Previous experiments suggest that humans are adept at distinguishing sharp from blurred edges (**McIlhagga & May, 2012; Ahumada & Watson, 2011**), and our analysis suggests this ability may help solve an important problem in natural scene analysis. Another factor which may contribute to the presence of more energy at higher spatial frequencies is that occlusions often have high spatial frequency textures with high contrast on both sides of the boundary (**Fig. 3**).

Another closely related study which served as a strong motivation for the present work is the study by **Breuil et al. (2019)** demonstrating the importance of chromatic cues for accurate edge classification as luminance or material. One interesting finding to arise from their study is that performance in the task for human subjects increased with edge size, whereas a similar improvement in performance was not observed with machine classifiers defined using luminance and chromatic cues. A reasonable interpretation of this result is that human observers were able to exploit textural cues which were not incorporated into the machine classifiers. Consistent with this interpretation, the present work also demonstrates that texture cues can be potentially exploited for distinguishing shadows from occlusions. Training "Filter-Rectify-Filter" (**FRF**) style classifiers

revealed hidden units exhibiting sensitivity to differences in texture (**Fig. 12**), and the stimuli most likely to be classified as occlusions by these models had different textures on each side of the edge (**Fig. 11**). Furthermore, reducing texture information by decreasing the image patch resolution decreased classification performance (**Table 3**), and removing texture from the image patches lead to a drastic reduction in occlusion probability for those images most likely to be occlusions (**Fig. 13**). The utility of texture for distinguishing changes in illumination from changes in material is relatively unsurprising, as different surfaces usually have different textures. However, what is perhaps quite surprising is our finding of just how much information highly localized texture differences (40x40 pixels) can contribute to edge classification.

A second interesting finding in **Breuil et al. (2019)** was that the benefits of color for edge classification were constant across a range of image patch sizes. Although in principle increasing the region size will increase the accuracy with which one can determine the chromatic properties of two surfaces, in practice most of this information is available in a small region near the boundary. Classification image studies have demonstrated that like luminance edges (**McIlhagga 2018**), chromatic edge detection and localization strongly emphasizes the boundary between regions (**McIlhagga & Mullen, 2018**), suggesting little integration over space. Their result is consistent with the analysis in **DiMattina et al. (2012)**, which found that over three spatial scales (8x8, 16x16, 32x32) adding chromatic information improved performance in the task of classifying image patches as occlusions or textures by approximately 5%, and this effect was not scale-dependent.

Limitations and future directions

The present study has several limitations, each of which provides a fruitful avenue for future work. Firstly, as in many other studies of perception and computer vision (**Mely et al., 2016; Zhou & Mel, 2008; Ramachandra & Mel, 2013; DiMattina et al., 2012; McDermott, 2004; Breuil et al., 2019; Martin et al., 2004**), we rely on image features annotated by human observers in a relatively small number of visual scenes. Therefore, the validity of such analyses relies on the assumption that the image sets chosen, and the region within these images which are annotated by human observers, are indeed representative of the natural visual environment.

Secondly, we focus here only on achromatic cues for shadow/occlusion classification, as previous work has rigorously investigated color and its importance for shadow edge/material edge classification (**Breuil et al., 2019**). It would be of great interest for future work to incorporate color into our neural network analyses. Given the potential utility of chromatic information for distinguishing illumination from material (**Olmos & Kingdom, 2004; Kingdom, 2019**), we might expect to find hidden units which learn to detect different colors on opposite sides of the boundary. Indeed, studies of deep neural networks trained on RGB images for classification tasks have been shown to learn filters specialized for detecting color edges while being insensitive to luminance (**McIlhagga & Mullen, 2018**). Despite the obvious interest of including chromatic cues, our work clearly demonstrates that they are by no means necessary for accurate shadow edge classification from local cues. A simple perusal of the grayscale images in **Fig. 1** serves as proof in fact that while most certainly useful, chromaticity is by no means necessary for edge classification, and perceptual organization more broadly.

Just because a cue is potentially available to solve some problem does not mean that it is utilized by human observers. Furthermore, when multiple cues are present, as is the case for the

current edge classification task, an important issue is how they are combined, for example, via probability summation (**Graham & Nachmias, 1971; Kingdom et al., 2015**), linear summation (**Ernst & Banks, 2002**), or some other cue-combination rule (**Jones, 2016**). The analyses in this paper simply demonstrate that certain cues (contrast, texture, penumbral blur) are potentially useful for solving this natural vision problem, and that simple neural computations can exploit these cues. It does not tell us exactly the rules by which these cues are combined by human observers, and what cues takes precedence in cases of conflict.

One way this can be addressed experimentally would be to create parametric stimuli closely resembling natural stimuli, and then systematically manipulating these stimuli to determine which aspects drive behavior. For instance, our results suggest that we could create a synthetic stimulus which would be likely classified as an occlusion by a human observer by juxtaposing two different naturalistic textures with a sharp luminance border super-imposed. As we blur the border and make the textures similar or identical, observers may be more likely to classify the patch as a shadow. By varying cues simultaneously and exploring effects on stimulus categorization, we can fit and compare multiple cue combination models (**Jones, 2016**) to better understand how texture, blur and color are integrated for shadow edge detection.

METHODS

Shadow and occlusion databases

Image sets and hand-labeling procedures

We obtained a set of N = 47 shadow images (786x576 resolution) taken from the McGill calibrated color image database (**Olmos & Kingdom, 2004**). The set of 47 images contained both natural and manmade objects. All selected images contained clear figure-ground organization and detectable shadow boundaries. Authors CD and BG with two other undergraduate researchers (LA, MD) used the image manipulation program GIMP (https://www.gimp.org/) to label the most noticeable shadows within the set of images. Each student was instructed to label the shadows individually, so their labels reflected their independent judgment. Examples of images from our shadow database (**shad**) are shown with the labeling of the shadow contours in each image by one observer (MD) shown in **Fig. 1a** (*top*). A binary union of the labels from all 4 observers is shown in **Fig. 1a** (*bottom*).

Image patches containing surface boundaries were obtained from two sets of images. One was a previously developed image database (**DiMattina et al., 2012**), also derived from a subset of N = 100 images (786 x 576) from the calibrated McGill image set. We refer to as this set of images as occlusion set-1 (**oset-1**). One potential limitation of **oset-1** is that the images in this set have almost no overlap with our set of N = 47 shadow images. Therefore, it at least possible that any statistical differences observed between shadow edges and occlusion edges could be a function of there being different surfaces present in the two image sets. Therefore, we developed a second occlusion database by having the same observers label all the occlusions in a subset of N = 20 images taken from our larger database of 47 shadow-labeled images. We refer to this second

database of occlusions taken from a subset of our 47 shadow images as occlusion set-2 (**oset-2**). Two example images from this set (**oset-2**) with labeled occlusions are shown in **Fig. 1b** (*top*), together with a binary label of the occlusions from all 4 observers (**Fig. 1b**, *bottom*). Our hand-labeled shadow database and both occlusion databases are freely available to the scientific and engineering communities at https://www.fgcu.edu/faculty/cdimattina/.

Image patch extraction methods

Both occlusion edges and shadow edges were extracted from the image as described in **DiMattina et al. (2012)**. Briefly, random pixels labeled as edges by a single observer were chosen, cycling through the set of observers who labeled each image (CD, LA, BG, MD). To ensure patches where the boundary separates two regions of approximately equal size, with no extraneous edges, a patch centered on an edge was only accepted for inclusion if the composite edge map (pooled over all observers) for the candidate patch comprised a single, connected dividing the patch into two regions, the smaller of which comprised at least 35% of the pixels. This procedure excludes T-junctions or highly convex edges, yielding mostly smooth edges as is evident from the image patches of both categories (occlusions, shadow) shown in this paper. We focused our analyses on 40x40 image patches, which in a 786x576 image constituted roughly 5% of the larger dimension, ensuring our analysis focused on relatively local cues.

Analysis of image patch statistics

Contrast statistics

Previous investigations have demonstrated interesting differences in the statistical properties of occlusion patches and non-occlusions (including shadows) and shown that these statistics can be utilized to reliably discriminate these two categories (**Vilankar et al. 2014; Breuil et al., 2019**).

Therefore, we measured some of these same quantities from our image patches at 40x40 resolution to provide basic descriptive statistics for the shadow and occlusion edges in our databases, and to determine the extent to which such simple statistics could be reliably exploited for image classification purposes.

From both the shadow and occlusion edges, we measured two quantities from linearized RGB versions of the images that were first converted to grayscale: (1) RMS contrast, and (2) Michelson contrast. Conversion to grayscale was accomplished using the standard formula

$$I = 0.2989 * R + 0.5870 * G + 0.1140 * B. \tag{1}$$

The RMS contrast of the grayscale image I is defined as

$$c_{RMS} = \frac{\sigma}{\mu}, \tag{2}$$

where σ is the standard deviation of the pixel intensities, and μ is the mean pixel intensity. Since our selection method only chose image patches which could be cleanly divided into two regions of approximately equal size (see **DiMattina et al. 2012** for details), we were also able to measure the Michelson contrast, which is defined as

$$c_M = \left| \frac{\mu_2 - \mu_1}{\mu_2 + \mu_1} \right|, \tag{3}$$

where μ_1, μ_2 denote the mean pixel intensity in each of the two regions.

Making use of the MATLAB machine learning toolbox function `fitclinear.m`, we trained a logistic regression classifier (**Bishop, 2006**) on these two variables to see to what extent they could distinguish the two image categories. This classifier was trained using a vector of these features (c_{RMS}, c_M) extracted from N = 16000 images (half each category) and tested on a set of these features measured from N = 4000 images (half each category) not used for training.

Spatial frequency analysis

In addition to contrast statistics, another potential cue for distinguishing edges caused by shadows from those caused by occlusion boundaries is spatial frequency content. Due to penumbral blur, many (but not all) shadows exhibit a gradual luminance change at their boundary (**Casati & Cavanagh, 2019**), whereas occlusions typically give rise to a relatively sharp luminance transition. Furthermore, psychophysical experiments using classification image techniques have demonstrated that human observers can reliably discriminate sharp luminance edges from blurry ones (**McIlhagga & May, 2012**), suggesting penumbral blur can be potentially employed for shadow identification. We applied the standard FFT to the 40x40 image patches from both categories, which were first pre-processed to have zero mean and identical energy. We then quantified the proportion of stimulus energy in various high spatial-frequency regions of the spectrum. This was accomplished by taking the rotational sum of the power spectrum and then taking the ratio π_h of power above 10 cycles/image to total stimulus power (Nyquist frequency for 40 x 40 images is 20 cycles/image). This parameter π_h was combined with the two contrast parameters c_{RMS}, c_M to reimplement the logistic regression classifier analysis described in the previous section with a larger feature set.

Image-computable classifier analyses

Three categories of image-computable machine classifiers were implemented in Python using Keras and Tensorflow (**Chollet, 2021**). All classifiers were tested on the same 4 sets of 1000 images not used for model training or validation (sets 65-68) to provide a fair comparison of their performance. To align the images to improve classification accuracy, image patches were rotated into a vertical orientation, and reflected into sine phase (if necessary) so that the left side was always darker than the right side.

Gabor filter bank classifier

The second model, which we will refer to as the Gabor Filter Bank (**GFB**) model, is illustrated schematically in **Fig. 6a**. In this model, a fixed set of multiscale Gabor filters (8, 16, 32 pixels) with spatial frequency bandwidths resembling V1 simple cells (**Kovesi, 2000**; **Field, 1987**) was convolved with an input image (40x40 pixels). At each scale, the set of oriented filters includes 6 orientations, 2 phases (even/odd), and 2 contrast polarities (+/-), for a total of 24 oriented filters (**Supplementary Fig. S4)**. The outputs of these filters were half-wave linear rectified (*relu*) and then down-sampled from 40x40 to 5x5 using MAX pooling (**Goodfellow, Bengio & Courville, 2006**). This yields a representation having 1800 dimensions. Binomial logistic regression (**Bishop, 2006**) was performed on these 1800 pooled filter responses as predictor variables with stimulus category (0 = shadow, 1 = occlusion) as the response variable. A set of N = 20000 images (sets 1-20) was broken into 5 folds for cross-validation to optimize the L2 regularization parameter. Therefore, each model was trained using N = 16000 images and validated on N = 4000 images (**Supplementary Fig. S5)**. The trained model with the best performance on the validation set was then evaluated on the test sets.

Filter-rectify-filter classifier

Finally, we implemented the Filter-Rectify-Filter (**FRF**) model often used to account for texture segmentation (**Landy & Graham, 2004; Victor et al., 2017**). This model is illustrated in **Fig. 6b**. As with the **GFB** model, the image was initially convolved with a set of fixed Gabor filters, and the linearly rectified (*relu*) outputs downsampled using MAX pooling. However, these down-sampled outputs were fed into a three-layer neural network classifier having N = 4, 6, or 10 hidden units with *relu* gain. N = 64000 images (sets 1-64) were broken into 8 folds for cross validation so that each model was trained on 56000 images and validated on 8000. The optimal hyperparameter

obtained for **FRF-10** was used for **FRF-4**, **FRF-6** as well, although there was little sensitivity to hyperparameter value (**Supplementary Fig. S5**). The models chosen for evaluating on the test set were all trained on the same set of images to permit fair comparison.

For analyzing the effects of texture removal on the FRF model (**Fig. 13**), occlusions having vertical or near-vertical orientation were chosen from each image database from a set of images not used for model training. Texture information was removed from these patches using the same method as in our previous work (**DiMattina et al., 2012**), by simply setting the intensity to each pixel in a region equal to the mean intensity over the region. Image patches manipulated in this manner are shown in **Fig. 13a**. This manipulation removes all texture cues while leaving Michelson contrast (**Eq. 2**) unchanged.

Psychophysical experiments

Participants

Participants in this study consisted of $N = 18$ undergraduate students attending Florida Gulf Coast University enrolled in Psychology courses PSB-4002 ("Brain and Behavior") and EXP-3202 ("Sensation and Perception") during the Fall 2021 semester. All participants in these two courses were given the opportunity to complete three experiments (**QT-1**, **QT-2**, **QT-3**) implemented as web surveys in return for extra credit in the course. Before each experiment, participants were required to review and accept an informed consent form. All procedures were approved beforehand by the Institutional Review Board of Florida Gulf Coast University (Protocol 2021-78), in accordance with the Declaration of Helsinki.

Procedure

The visual experiments were implemented as a web survey using Qualtrics, an online web survey program (https://www.qualtrics.com/). Participants accessed the link for the Qualtrics survey using their personal computers or smartphones. Image patches used in the Qualtrics surveys used in this study were selected from the McGill Calibrated Color Image Database (**Olmos & Kingdom, 2004**) and then converted to grayscale. In each survey, participants were shown a 40x40 image patch (resized to 96x96, in order to subtend roughly 2-3 degrees of visual angle at normal viewing distances) and asked to indicate whether this patch contained an occlusion edge or a shadow edge. Each survey contained 200 images, half of which belonged to each category, presented in random order. After their response, feedback (correct/incorrect) was provided before presenting the next stimulus. A schematic diagram of the experimental procedure is shown in **Fig. 14a**, and an example survey question is shown in **Supplementary Fig. S8**. For inclusion in the final analysis, students had to complete all three surveys in the correct order, have no blank responses, and perform better than chance (114 or more correct out of 200) on the final 2 surveys, indicating that they had obtained proficiency in the task. Although there were 37 participants who completed at least one survey, only 18 participants met the criteria for inclusion in the final analysis, mostly due to the fact that many participants failed to complete all three surveys.

REFERENCES

Albrecht, D. G., & Hamilton, D. B. (1982). Striate cortex of monkey and cat: contrast response function. *Journal of Neurophysiology*, *48*(1), 217-237.

Baker Jr, C. L. (1999). Central neural mechanisms for detecting second-order motion. *Current Opinion in Neurobiology*, *9*(4), 461-466.

Bergen, J. R., & Landy, M. S. (1991). Computational modeling of visual texture segregation. *Computational Models of Visual Processing*, *17*, 253-271.

Bishop, C. (2006). *Pattern Recognition and Machine Learning.* Springer.

Breuil, C., Jennings, B. J., Barthelmé, S., Guyader, N., & Kingdom, F. A. (2019). Color improves edge classification in human vision. *PLoS Computational Biology*, *15*(10), e1007398.

Burge, J., Fowlkes, C. C., & Banks, M. S. (2010). Natural-scene statistics predict how the figure–ground cue of convexity affects human depth perception. *Journal of Neuroscience*, *30*(21), 7269-7280.

Casati, R., & Cavanagh, P. (2019). *The Visual World of Shadows*. MIT Press.

Chin, B. M., & Burge, J. (2020). Predicting the partition of behavioral variability in speed perception with naturalistic stimuli. *Journal of Neuroscience*, *40*(4), 864-879.

Chollet, F. (2021). *Deep learning with Python (2nd Ed.).* Manning.

DiMattina, C., & Baker Jr, C. L. (2019). Modeling second-order boundary perception: A machine learning approach. *PLoS Computational Biology*, *15*(3), e1006829.

DiMattina, C., & Baker Jr., C.L. (2021). Segmenting surface boundaries using luminance cues. *Scientific Reports*, *11*(1), 1-15.

DiMattina, C., Fox, S. A., & Lewicki, M. S. (2012). Detecting natural occlusion boundaries using local cues. *Journal of Vision*, *12*(13), 15-15.

Ehinger, K. A., Adams, W. J., Graf, E. W., & Elder, J. H. (2017). Local depth edge detection in humans and deep neural networks. In *Proceedings of the IEEE International Conference on Computer Vision Workshops* (pp. 2681-2689).

Elder, J. H. (1999). Are edges incomplete? *International Journal of Computer Vision*, *34*(2), 97-122.

Elder, J. H., Trithart, S., Pintilie, G., & MacLean, D. (2004). Rapid processing of cast and attached shadows. *Perception*, *33*(11), 1319-1338.

Elder, J. H., & Zucker, S. W. (1998). Local scale control for edge detection and blur estimation. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, *20*(7), 699-716.

Ernst, M. O., & Banks, M. S. (2002). Humans integrate visual and haptic information in a statistically optimal fashion. *Nature*, *415*(6870), 429-433.

Field, D.J. (1987). Relations between the statistics of natural images and the response properties of cortical cells. *Journal of the Optical Society of America A 4(12)*, 2379-2394.

Goodfellow, I., Bengio, Y., & Courville, A. (2016). *Deep Learning*. MIT press.

Graham, N., & Nachmias, J. (1971). Detection of grating patterns containing two spatial frequencies: A comparison of single-channel and multiple-channels models. *Vision Research*, *11*(3), 251-IN4.

Henry, K. S., & Abrams, K. S. (2021). Normal tone-in-noise sensitivity in trained budgerigars despite substantial auditory-nerve injury: no evidence of hidden hearing loss. *Journal of Neuroscience*, *41*(1), 118-129.

Ing, A. D., Wilson, J. A., & Geisler, W. S. (2010). Region grouping in natural foliage scenes: Image statistics and human performance. *Journal of Vision*, *10*(4), 10-10.

Jones, P. R. (2016). A tutorial on cue combination and Signal Detection Theory: Using changes in sensitivity to evaluate how observers integrate sensory information. *Journal of Mathematical Psychology*, *73*, 117-139.

Kingdom, F. A. A. (2008). Perceiving light versus material. *Vision Research*, *48*(20), 2090-2105.

Kingdom, F. A. A. (2019). Colour vision helps distinguish light from material. *Current Opinion in Behavioral Sciences*, *30*, 15-20.

Kingdom, F. A. A., Baldwin, A. S., & Schmidtmann, G. (2015). Modeling probability and additive summation for detection across multiple mechanisms under the assumptions of signal detection theory. *Journal of Vision*, *15*(5), 1-1.

Kovesi, P. D. (2000). MATLAB and Octave functions for computer vision and image processing. *http://www. csse. uwa. edu. au/∼pk/research/matlabfns*

Landy, M. S., & Graham, N. (2004). Visual Perception of Texture. *The Visual Neurosciences*, 1106.

Malik, J., & Perona, P. (1990). Preattentive texture discrimination with early vision mechanisms. *Journal of the Optical Society of America A*, *7*(5), 923-932.

Mamassian, P., Knill, D. C., & Kersten, D. (1998). The perception of cast shadows. *Trends in Cognitive Sciences*, *2*(8), 288-295.

Marr, D. C. (1982). *Vision.* MIT Press.

Martin, D. R., Fowlkes, C. C., & Malik, J. (2004). Learning to detect natural image boundaries using local brightness, color, and texture cues. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, *26*(5), 530-549.

McDermott, J. (2004). Psychophysics with junctions in real images. *Perception*, *33*(9), 1101-1127.

McIlhagga, W. (2018). Estimates of edge detection filters in human vision. *Vision Research*, *153*, 30-36.

McIlhagga, W. H., & May, K. A. (2012). Optimal edge filters explain human blur detection. *Journal of Vision*, *12*(10), 9-9.

McIlhagga, W., & Mullen, K. T. (2018). Evidence for chromatic edge detectors in human vision using classification images. *Journal of Vision*, *18*(9), 8-8.

Mély, D. A., Kim, J., McGill, M., Guo, Y., & Serre, T. (2016). A systematic comparison between visual cues for boundary detection. *Vision Research*, *120*, 93-107.

Olmos, A., & Kingdom, F. A. (2004). A biologically inspired algorithm for the recovery of shading and reflectance images. *Perception*, *33*(12), 1463-1473.

Parker, A. J., & Hawken, M. J. (1988). Two-dimensional spatial structure of receptive fields in monkey striate cortex. *JOSA A*, *5*(4), 598-605.

Ramachandra, Chaithanya A., and Bartlett W. Mel. "Computing local edge probability in natural scenes from a population of oriented simple cells." *Journal of Vision* 13, no. 14 (2013): 19-19.

Ramachandran, V. S. (1988). Perception of shape from shading. *Nature*, *331*(6152), 163-166.

Ramenahalli, S., Mihalas, S., & Niebur, E. (2014). Local spectral anisotropy is a valid cue for figure–ground organization in natural scenes. *Vision Research*, *103*, 116-126.

Rensink, R. A., & Cavanagh, P. (2004). The influence of cast shadows on visual search. *Perception*, *33*(11), 1339-1358.

Rumelhart, D. E., Hinton, G. E., & Williams, R. J. (1986). Learning representations by back-propagating errors. *Nature*, *323*(6088), 533-536.

Sebastian, S., & Geisler, W. S. (2018). Decision-variable correlation. *Journal of Vision*, *18*(4), 3-3.

Sebastian, S., Seemiller, E. S., & Geisler, W. S. (2020). Local reliability weighting explains identification of partially masked objects in natural images. *Proceedings of the National Academy of Sciences*, *117*(47), 29363-29370.

Victor, J. D., Conte, M. M., & Chubb, C. F. (2017). Textures as probes of visual processing. *Annual Review of Vision Science*, *3*, 275-296.

Vilankar, K. P., Golden, J. R., Chandler, D. M., & Field, D. J. (2014). Local edge statistics provide information regarding occlusion and non-occlusion edges in natural scenes. *Journal of Vision*, *14*(9), 13-13.

Watson, A. B., & Ahumada, A. J. (2011). Blur clarified: A review and synthesis of blur discrimination. *Journal of Vision*, *11*(5), 10-10.

Wilder, J. D., Adams, W. J., & Murray, R. F. (2019). Shape from shading under inconsistent illumination. *Journal of Vision*, *19*(6), 2-2.

Zavitz, E., & Baker, C. L. (2013). Texture sparseness, but not local phase structure, impairs second-order segmentation. *Vision Research*, *91*, 45-55.

Zavitz, E., & Baker, C. L. (2014). Higher order image structure enables boundary segmentation in the absence of luminance or contrast cues. *Journal of Vision*, *14*(4), 14-14.

Zhou, C., & Mel, B. W. (2008). Cue combination and color edge detection in natural scenes. *Journal of Vision*, *8*(4), 4-4.

FIGURE CAPTIONS

Figure 1: Images from the shadow boundary database and one occlusion database.

(**a**) *Top*: Two representative images from our shadow database (**shad**) with shadow edges labeled by one observer. *Bottom:* Overlaid shadow boundaries obtained from all N = 4 observers.

(**b**) *Top:* Two representative images from **oset-2**, labeled by one observer. *Bottom:* Overlaid occlusion boundaries from all N = 4 observers.

Figure 2: Contrast statistics measured from shadow and occlusion edges (N = 2000 of each category). Green curves/symbols indicate occlusions, Magenta curves/symbols indicate shadows.

(**a**) Distributions of Michelson contrast (*left*) and RMS contrast (*right*) for our shadow database and two sets of occlusions (**oset-1**: *top*, **oset-2**: *bottom*). Note that for both occlusion sets, the highest and lowest contrast edges are occlusions.

(**b**) Two-dimensional scatterplot of contrast measurements for shadow and occlusion edges for both sets of occlusions. The dashed line indicates the optimal separating hyperplane learned by a logistic regression classifier trained on a different set of observations.

Figure 3: Example occlusion and shadow edges at varying percentiles of our contrast and spatial frequency measurements. Each image patch is within 8 ranks of the indicated percentile (out of N = 2000 total image patches analyzed).

(**a**) Occlusion edges at varying percentiles of each contrast measure (RMS: *left*; Michelson: *center*) and our spatial frequency measure (π_h: *right*) for both sets of occlusions (**oset-1**: *top*, **oset-2**: *bottom*).

(**b**) Same as (a), but for shadow edges from our database.

Figure 4: Measurement of stimulus power π_h in the high spatial frequency (>10 cycles/image) range. N = 2000 for each set of images.

(**a**) Probability distribution of π_h for our shadow database (magenta curves) and both occlusion sets (green curves).

(**b**) Rotational average of the amplitude spectrum for shadows (magenta curves) and both occlusion sets (green curves).

(**c**) Scatterplots of π_h and Michelson contrast c_M for shadows (magenta symbols) and both occlusion sets (green symbols).

(**d**) Same as (c) but for RMS contrast c_{RMS}.

Figure 5: Pixel-based (**PIX**) classifier trained to distinguish shadow and occlusion patches.

(**a**) Schematic illustration of **PIX** classifier, which performs logistic regression on the pixel intensity values $x_1, \ldots, x_n$ learning a set of weights $w_1, \ldots, w_n$ to accurately predict stimulus category.

(**b**) Linear classifier weights which optimally distinguish shadows from each occlusion set.

(**c**) Images with varying levels of blur. Images are adjusted to equalize Michelson contrast.

(**d**) **PIX** model predictions for model trained with each occlusion set. All stimuli on a given curve were set to the same fixed level of Michelson contrast.

Figure 6: Schematic illustration of Gabor Filter Bank (**GFB**) and Filter-Rectify-Filter (**FRF**) classifier models.

(**a**) **GFB** model. An image patch is analyzed by a bank of 72 oriented Gabor filters covering 3 spatial scales (8, 16, 32 pixels). The rectified filter outputs are down-sampled and MAX pooled to obtain a set of regressors $x_1, \dots, x_n$. Binomial logistic regression is performed to find a set of weights that optimally predict the probability that the patch is an occlusion.

(**b**) **FRF** model. This model is identical to the **GFB** model, except the regressors $x_1, \dots, x_n$ are then passed into a three-layer neural network having K hidden units (*gray circles*) to determine the probability an image patch is an occlusion edge.

Figure 7: Effects of edge blur on model predictions of edge probability.

(**a**) Gabor Filter Bank (**GFB**) model (see **Fig. 6a**).

(**b**) Same as (a) but for Filter-Rectify-Filter (**FRF**) models having varying numbers of hidden units (**Fig 6b**).

Figure 8: Occlusion edge probability predicted by the **GFB** model trained to distinguish shadows from occlusions taken from one of our sets (**oset-1**, **oset-2**). Models were tested on N = 1000 images not used for model training.

(**a**) Predicted probability of being an occlusion edge by the **GFB** model (*blue curve*). Image patches are sorted by their probability. Actual category is indicated by a (+).

(**b**) Occlusion probability predicted by the **GFB** model for each occlusion edge (*green curve*) and each shadow edge (*magenta curve*), sorted by occlusion probability.

(**c**) Same as (a) but for the **FRF-6** model. Similar results were obtained for **FRF-4**, **FRF-10** (**Supplementary Fig. S6**)

(**d**) Same as (b) but for the **FRF-6** model.

Figure 9: Stimuli that maximize + minimize the occlusion probability predicted by the **GFB** and **FRF** models trained to distinguish shadows from occlusions (**oset-1**, **oset-2**).

(**a**) *Left:* Stimuli obtained via numerical optimization with highest predicted occlusion probability by the **GFB** model. We see consistent results for both training sets, and over multiple optimization runs. *Right:* Same as left column, but with highest predicted shadow probability by the **GFB** model (equivalently, lowest predicted occlusion probability).

(**b**) Same as (a) but for **FRF-4**.

(**c**) Same as (a) but for **FRF-6**.

(**d**) Same as (a) but for **FRF-10**.

Figure 10: Occlusion and shadow edges with the 25 highest predicted probabilities by the **GFB** model of occlusion and shadow category membership. Actual category is indicated by the row, predicted category by the column. The upper left and lower right quadrants indicate correct classifications by the model.

Figure 11: Same as **Fig. 10**, but for the **FRF-6** model.

Figure 12: Optimal stimuli for the hidden units in the **FRF** models with 4 and 6 hidden units trained with both sets of occlusions (**oset-1**, **oset-2**).

(**a**) **FRF-4** hidden unit receptive fields. Sign of output weight is indicated with a (+) or (-).

(**b**) Same as (a) but for **FRF-6**.

Figure 13: Effects of removing texture information from image patches on responses of the FRF model.

(**a**) Averaging the pixel intensities on each side of the occlusion boundary remove texture information while leaving Michelson contrast unchanged.

(**b**) Inverse probability of being an occlusion for the original images (*horizontal axis*) versus the texture-removed images (*vertical axis*). We see that images for which the model predicts a high occlusion probability experience a drastic decrease in occlusion probability when texture is removed. *Top:* **oset-1**, *Bottom:* **oset-2**.

(**c**) Inverse probability of being an occlusion for the original images (horizontal axis) versus the change in occlusion probability when texture is removed (vertical axis). *Top:* **oset-1**, *Bottom:* **oset-2**.

(**d**) Change in occlusion probability for patches correctly classified as occlusions. Positive numbers indicate a decrease in occlusion probability, negative numbers an increase in occlusion probability. *Left:* **oset-1**, *Right:* **oset-2**.

(**e**) Same as (d) but for patches incorrectly classified as shadows.

Figure 14: Psychophysical experiment results.

(**a**) Schematic outline of our psychophysical task.

(**b**) *Left:* Performance of all observers on each survey, as measured by proportion correct. Blue dots indicate individual observers. Blue circles indicate the median, and black diamonds indicate maximum performance. *Right:* Same as left panel, but performance measured as d-prime.

(**c**) Distribution of the SDT decision criterion (γ) for all observers and surveys.

(**d**) Distribution of the difference $P(o|S) - P(s|O)$ in classification error probabilities. $P(o|S)$ indicates the probability a shadow is mis-classified as an occlusion, and $P(s|O)$ is the probability of an occlusion being mis-classified as a shadow.

(**e**) Distribution of the Wald statistic for the binomial proportion test testing whether there is a bias in mis-classifications, with the null hypothesis of equal mis-classification probabilities.

(**f**) Scatter plot of classification error probabilities.

Figure 15: Human performance on individual images.

(**a**) Predicted probability of being an occlusion edge by the **AO** (*blue curve*). Image patches are sorted by their probability. Actual category is indicated by a (+).

(**b**) Occlusion probability predicted by the **AO** for each occlusion edge (*green curve*) and each shadow edge (*magenta curve*), sorted by occlusion probability.

Figure 16: Log-odds ratios of human observers (**AO,** horizontal axes) and **GFB**, **FRF** models (vertical axes) for each image for all three surveys. Magenta symbols indicate image patches that are occlusions, green symbols indicate shadows. On the margins of each scatterplot we show the distributions of the log-odds ratios for each image category.

Figure 17: Decision-variable correlation analysis.

(**a**) DVC between models and individual observers for each experiment.

(**b**) Same as (a) but pooled across experiments.

(**c**) Histograms of differences in DVC for all possible comparisons of the three models.

Figure 1

Figure 2

Figure 3

Figure 4

Figure 5

Figure 6

Figure 7

Figure 8

Figure 9

Figure 10

Figure 11

Figure 12

Figure 13

Figure 14

Figure 15

Figure 16

Figure 17