Distinguishing shadows from surface boundaries using local achromatic cues

Abbreviated Title: Distinguishing shadows from surface boundaries

Christopher DiMattina[1,2,3,*], Josiah Burnham[1,4], Betul Guner[1,3], Haley Yerxa[1,4]

[1]Computational Perception Laboratory, [2]FGCU Computational Facility, [3]Department of Psychology, & [4]Department of Software Engineering

Florida Gulf Coast University, Fort Myers, FL, USA 33965-6565

*Corresponding Author:
      Christopher DiMattina
      Whitaker Hall Room 215
      Florida Gulf Coast University
      10501 FGCU Blvd S.
      Fort Myers, FL 33965-6565

      Email: cdimattina@fgcu.edu
      Web: http://itech.fgcu.edu/faculty/cdimattina/
      Tel: (239)-590-1513

Conflict of Interest: The authors declare no competing financial interests.

Funding: This work was funded by NIH-R15-EY032732-01 to C.D.

Acknowledgements: We would like to thank Curtis Baker for comments on the manuscript, and FGCU graduates Michele DeAngelis and Lauren Anderson for help with developing the database.

ABSTRACT

In order to accurately parse the visual scene into distinct surfaces, it is essential to determine

whether a local luminance edge is caused by a boundary between two surfaces or a shadow cast

across a single surface. Previous studies have demonstrated that local chromatic cues may help to

distinguish edges caused by shadows from those caused by surface boundaries, but the information

potentially available in local *achromatic* cues like contrast, texture, and penumbral blur remains

poorly understood. In this study, we develop and analyze a large database of hand-labeled

achromatic shadow edges to better understand what image properties distinguish them from

occlusion edges. We find that both the highest contrast as well as the lowest contrast edges are

more likely to be occlusions than shadows, extending previous observations based on a more

limited image set. We also find that contrast cues alone can reliably distinguish the two edge

categories with nearly 70% accuracy at 40x40 resolution. Logistic regression on a Gabor Filter

bank (**GFB**) modeling a population of V1 simple cells separates the categories with nearly 80%

accuracy, and furthermore exhibits tuning to penumbral blur. A Filter-Rectify Filter (**FRF**) style

neural network extending the **GFB** model performed at better than 80% accuracy, and exhibited

greater sensitivity to texture differences. Comparing the models with humans performing the same

occlusion/shadow classification task using the same stimuli reveals better agreement on an image-

by-image basis between human performance and the **FRF** model than the **GFB** model. Taken as

a whole, the present results suggest that local achromatic cues like contrast, penumbral blur, and

texture play an important role in distinguishing edges caused by shadows from those caused by

surface boundaries.

AUTHOR SUMMARY

Distinguishing edges caused by changes in illumination from edges caused by surface boundaries

is an essential computation for accurately parsing the visual scene. Previous psychophysical

investigations examining the utility of various locally available cues to classify edges as shadows

or surface boundaries have primarily focused on color, as surface boundaries often give rise to a

change in color whereas shadows will not. However, even in grayscale images we can readily

distinguish shadows from surface boundaries, suggesting an important role for achromatic cues in

addition to color. We demonstrate using statistical analysis of natural shadow and occlusion edges

that locally available achromatic cues can be exploited by machine classifiers to reliably

distinguish these two edge categories. These classifiers exhibit sensitivity to blur and local texture

differences, and exhibit reasonably good agreement with humans classifying edges as shadows or

occlusion boundaries. As trichromatic vision is relatively rare in the animal kingdom, our work

suggests how organisms lacking rich color vision can still exploit other cues to avoid mistaking

illumination changes for surface changes.

INTRODUCTION

Luminance edge detection is an essential visual computation for identifying the boundary between

two surfaces (**Marr, 1982**; **Martin, Fowlkes & Malik, 2004; DiMattina, Fox, & Lewicki, 2012;**

Mely, Kim, McGill, Gou, & Serre, 2016). However, it is well known that in natural images,

luminance edges may arise from several causes other than surface boundaries: Specular reflections,

changes in material properties, changes in surface orientation, and cast shadows all can give rise

to changes in luminance that do not correspond to surface boundaries (**Ramachandran 1988;**

Mamassian, Knill, & Kersten, 1998; Vilankar, Golden, Chandler, & Field, 2014; Casati &

Cavanagh, 2019). Shadows are one class of luminance edge which are essential to distinguish

from other potential causes, since shadows do not indicate a change in surface reflectance

properties, but simply a change in illumination (**Olmos & Kingdom, 2004**; **Kingdom, 2008,**

2019).

Recent work has addressed the question of how the visual system distinguishes material or

reflectance edges from shadow edges in natural vision (**Breuil, Jennings, Bartheleme, Guyader,**

& Kingdom, 2019). In their study, human observers classified both color and grayscale image

patches viewed through an aperture as either shadow edges or material edges. These authors found

that observers performed significantly better with the color images, and that a machine classifier

making use of chromatic cues outperformed a machine classifier only using luminance cues. These

findings are consistent with several studies suggesting an important role for color in distinguishing

illumination from material (reviewed in **Kingdom, 2008, 2019**). In addition to improved

performance with chromatic information, these investigators also observed improved performance

with increasing aperture size. This may be because at larger spatial scales, texture information

becomes available which is not available at smaller spatial scales.

Here we address the question of what locally available *achromatic* information is available

to distinguish surface occlusion boundaries from cast shadows. This question is important since

distinguishing material properties from the illuminant is a universal problem that all visual systems

face, yet trichromacy is relatively rare in the animal kingdom. The vast majority of mammals are

dichromats, and some mammals (for instance, owl monkeys) are actually cone monochromats.

For such organisms, chromatic cues will be less useful, or even completely unavailable, for shadow

segmentation. Furthermore, even in trichromatic species, color information is by no means

necessary to segment shadows, as a casual inspection of the grayscale images in **Fig. 1a** reveals.

This question is also important for the development of computer vision methods for shadow

segmentation and removal in grayscale images. Most algorithms developed for this purpose utilize

color information to distinguish changes in illumination from changes in surface reflectance (e.g.,

Olmos & Kingdom, 2004). However, in some computer vision applications chromatic

information may be unavailable, for instance when processing archival images which pre-date

color photography.

At least three possible sources of information are potentially available: (1) Differences in

luminance contrast, (2) Differences in spatial luminance profiles, and (3) Texture cues. Pursuant

to (1), quantitative Bayesian classifier analyses demonstrate that on average occlusions can be

distinguished from non-occlusions (with shadows being one kind of non-occlusion edge) using

only Michaelson contrast (**Vilankar et al., 2014**). However, in this study a fairly limited set of

images was used, and it did not focus specifically on shadows. Pursuant to (2), it is well known

that the luminance edges arising from shadows are often more gradual than those arising from

surface boundaries due to penumbral blur (**Casati & Cavanagh, 2019; Vilankar et al., 2014**),

and furthermore human observers can reliably distinguish sharp and blurred edges (**Watson &**

Ahumada, 2011). Pursuant to (3), although texture segmentation is extremely well studied both

psychophysically and computationally (**Landy & Graham, 2004; Victor, Chubb & Conte,**

2017), to our knowledge no psychophysical work has directly considered the role of local texture

cues for classifying shadow and occlusion edges.

To address these questions, we develop a publicly available database of shadow edges by

hand-labeling a set of N = 47 natural images from the McGill Color Calibrated Image Database

(**Olmos & Kingdom, 2004**). We compare basic contrast and spatial frequency statistics of these

shadow edges to the same properties measured from a novel occlusion database derived from a

subset of 20 of the 47 images, as well as a previously published occlusion database containing 100

images (**DiMattina et al., 2012**). We demonstrate that machine classifiers defined using only 2 or

3 statistics can reliably discriminate 40x40 patches containing shadows from patches containing

surface boundaries at nearly 70% accuracy when generalizing to images not used for training. We

then evaluated the ability of an image-computable model comprised of a population of multi-scale

Gabor filters resembling V1 simple cells to distinguish these two categories, attaining nearly 80%

accuracy when generalizing to images not used for training. Furthermore, we found that our Gabor

filter bank (**GFB**) model exhibited clear tuning to penumbral blur, a cue which often accompanies

shadows. To test the hypothesis that local texture cues may be used to distinguish shadows from

occlusion boundaries, we next trained a Filter-Rectify-Filter (**FRF**) model (**Landy & Graham,**

2004; Zavitz & Baker, 2013, 2014; DiMattina & Baker 2019, 2021; DiMattina, 2022) to solve

the classification problem. Our best **FRF** model could classify 40x40 image patches taken from

novel images at better than 80% accuracy on average. Analysis of the hidden units in these trained

models demonstrated that many represented spatial differences in texture. Additional testing of the

FRF model revealed reduced data-fitting performance with the removal of texture information,

further underscoring the importance of local textures cues.

To compare human performance with that of machine classifiers, we performed a simple

psychophysical experiment where observers classified 40x40 grayscale image patches as occlusion

or shadow edges. We found that the best human observers performed about as well as the machine

classifiers (**GFB**, **FRF**) performed generalizing to novel images (80% accuracy). By correlating

human and model classification performance on an image-by-image basis, we observed a stronger

correlation between human behavior and the **FRF** model predictions than the **GFB** model, even

though the performance of the **FRF** model (as measured by percent correct) was only slightly

better than the **GFB** model. As the **FRF** model exhibits a stronger sensitivity to texture cues, these

results suggest that human observers are making use of textural cues to classify luminance changes

as shadows or occlusions.

Overall, our results show that there are multiple, locally available achromatic cues which

the visual system can potentially exploit to distinguish luminance changes arising from shadows

from those caused by occlusion boundaries. It is of great interest for future research to explore the

extent to which human observers utilize these various cues and how they combine with each other,

and we suggest future psychophysical experiments motivated by our current results.

RESULTS

Shadow edge database

Four observers hand-labeled all of the shadow boundaries in a set of N = 47 images (786 x 576

pixel resolution) taken from the McGill calibrated color image database (**Olmos & Kingdom,**

2004). Two images from our shadow database (**shad**), together with the shadow edges annotated

by one observer, are shown in the top panels of **Fig. 1a.** A binary overlay of the labels obtained

from all four observers is shown in the bottom panels of **Fig. 1a.** To compare the statistical

properties of shadow edges with occlusion edges, we utilized a previously developed database

(**DiMattina et al., 2012**) of hand-labeled occlusion boundaries taken N = 100 images from the

McGill Dataset (**oset-1**). In addition to **oset-1**, we also developed a second occlusion database

(**oset-2**) from a subset of shadow database images (20 out of 47 images) by having the same four

observers hand label occlusions in these images.

Two images from **oset-2** along with their hand-labeled occlusions are shown in **Fig. 1b**,

and examples of image patches randomly selected from each dataset can be seen in **Fig. 1c**. The

total number of hand-labeled occlusions and shadows in these images is quite large, with the **shad**

database containing a total of 272,043 labeled shadow patches in 47 images. **oset-1** contains over

1.25 million occlusion patches (1,258,000), and **oset-2** contains 84,112 occlusion patches. All

three databases (**shad**, **oset-1**, **oset-2**) are freely available to the scientific community at:

https://www.fgcu.edu/faculty/cdimattina/.

Analysis of image patch statistics

Contrast statistics

Previous investigators have characterized some of the statistical properties of occlusion edges and

non-occlusion edges (including shadows) in natural scenes (**Vilankar et al., 2014**; **Breuil et al.,**

2019). To connect with these previous explorations, we measured some of these quantities from

both the occlusion and shadow edges: (1) RMS contrast c_{RMS} (**Eq. 2**), and (2) Michelson contrast

c_M (**Eq. 3**). All analyses were performed on 40 x 40 pixel (5% of larger image dimension) image

patches from one of our databases (**shad**, **oset-1**, **oset-2**), with the constraint that all patches were

centered on a human-labeled edge (shadow or occlusion).

Fig. 2a plots the overlaid probability distributions of these quantities for the shadow images

(magenta curves) and both occlusion databases (**oset-1**: *top*, **oset-2**: *bottom*, green curves). We see

that the distribution of Michelson contrast (c_M) for occlusions (green lines) spans the entire range

of observed values, with occlusion edges giving rise to both the highest and lowest values.

Furthermore, we see that occlusion edges are much more likely than shadow edges (magenta lines)

to have very low values of c_M. We obtained median values of $c_M = 0.51$ for our shadow set, and

$c_M = 0.30$, 0.33 for **oset-1** and **oset-2**, respectively. Median values are significantly different

between shadows and both occlusion sets (rank-sum test, $p < 0.001$). Similar results were obtained

for RMS contrast (c_{RMS}), although in this case the discrepancy between categories was smaller,

and the distribution for occlusions was closer in shape to a normal distribution. For RMS contrast,

we obtained median values of $c_{RMS} = 0.64$ for the shadows and $c_{RMS} = 0.47$, 0.59 respectively.

Median values are significantly different between shadows and both occlusion sets (rank-sum test,

$p < 0.001$). Large and highly significant positive correlations (Pearson's r) were observed between

these two contrast measures for all datasets (**oset-1**: $r = 0.754$, $p < 0.001$; **oset-2**: $r = 0.722$, $p < $

0.001, **shad**: $r = 0.743$, $p < 0.001$).

Our finding that the lowest-contrast edges (by both measures) were occlusions rather than

shadows is consistent with the fact that occlusion edges can often arise from two surfaces having

identical mean luminance (**DiMattina et al., 2012**), whereas by definition a shadow edge requires

a change in luminance. However, in agreement with previous measurements using a different set

of occlusion patches identified using different methodology (**Vilankar et al., 2014**), we see that

the far-right tails of the contrast distributions are dominated by occlusions, meaning that the

highest contrast edges are more likely to be occlusions rather than shadows. Since 19 of the 38

images analyzed by **Vilankar et al. (2014)** were also contained in **oset-1**, we repeated our analysis

on this subset of images, finding results consistent with our analyses based on the full image set

(**Supplementary Fig. S1**).

We also see from **Fig. 2a** that in our sample the distribution of c_M (but not c_{RMS}) appears

to have some degree of bimodality. Most likely this reflects the properties of our database rather

than the physics of shadow formation, as our shadow set contained a sub-set of images taken in

conditions of strong illumination from a point source (the sun). Comparing the green curves on the

top and bottom of **Fig. 2a**, we see a strong qualitative consistency between both sets of occlusion

images. This provides us with reassurance that our measurements of contrast statistics reflect the

general properties of occlusion edges rather than the idiosyncrasies of our databases.

Fig. 2b shows scatterplots of our measured quantities (c_M, c_{RMS}) for both occlusion (green

symbols) and shadow edges (magenta) for both sets of occlusions. For **oset-1**, a classifier using

these two cues can separate occlusions and shadows with an average performance of 67.7%

accuracy on test image sets not used for classifier training (taken from different images, see

METHODS), and 69.9% accuracy on the training sets (**Supplementary Table S1**). For **oset-2**,

the classifier separates the two categories in the test sets with an average accuracy of 68.5%, with

average accuracy of 70.7% on the training sets (**Supplementary Table S2**). Similar results were

obtained when the training and test sets were both sampled uniformly (with replacement) from all

images (see **METHODS**). In this analysis, the classifier trained on **16K** image patches predicts

test set category (**4K** patches) with accuracy of 68.7% for **oset-1**, and 69.6% for **oset-2**.

Fig. 3 (*left + center*) illustrates examples of image patches near the 10^{th}, 50^{th}, and 90^{th}

percentiles when the 4000 images are sorted by each contrast measure (each patch is at most 8

ranks from the exact percentile rank). **Fig. 3a** shows occlusion images from both sets, and **Fig. 3b**

shows the shadow images. In our analyses, we applied our measurements to the grayscale

converted (**Eq. 1**) RGB values obtained from the linearized images without any pre-normalization.

This is because such operations may potentially reduce contrast cues. However, repeating these

analyses where each individual linearized image patch was also normalized to lie in the range [0,

1] yielded nearly identical results (**Supplementary Fig. S2**).

<u>Spatial frequency statistics</u>

As we see from **Fig. 1c** and **Fig. 3**, another potential cue for distinguishing shadow edges from

occlusions is that many shadows exhibit a gradual transition between luminance levels due to

penumbral blur (**Casati & Cavanagh, 2019**). Therefore, we should expect that edges arising from

shadows may have less energy in higher spatial frequency (SF) ranges than those arising from

occlusions. Furthermore, occlusions may exist without any change in luminance, and have high-

contrast high-SF textures on both sides of the boundary, whereas with shadows the high-SF texture

on the darker half will generally have lower contrast. Analysis of the proportion π_h of stimulus

energy at higher spatial frequencies (which we define as those frequencies above 10 cycles/image,

with 20 cycles/image being the Nyquist limit) reveals that indeed there are significant differences

between occlusions and shadows (**Fig. 2c**). Comparison of π_h distribution medians (rank-sum test)

yielded significant results for both **oset-1** (occlusion median = 0.076, shadow median = 0.060, $p <$

0.001) and **oset-2** (occlusion median = 0.078, shadow median = 0.060, $p < 0.001$). Similar results

were obtained when we increased our cutoff for high spatial frequencies to 15 cycles/image.

Averaging the amplitude spectrum obtained from each patch (**Fig 2d**) reveals more energy at

higher spatial frequencies for the occlusion images compared to shadow images. **Fig. 2e, f** shows

scatterplots of π_h versus c_M and c_{RMS} for both **oset-1** (*left*) **and oset-2** (*right*). Significant negative

correlations were observed between both contrast measures and π_h for both occlusion sets and the

shadow set. That is, higher contrast edges had a smaller proportion of their energy in high spatial

frequencies. This makes sense because the highest contrast edges (of either category) tend to have

a strong difference in illumination over the spatial scale of the entire patch, which would give rise

to a large low-spatial frequency component, as well as decreased energy at high SFs on the darker

side. For occlusion **oset-1**, we obtain correlations between π_h and c_M, c_{RMS} of -0.492, -0.261,

respectively ($p < 0.001$ both tests). For occlusion **oset-2**, we a obtain correlations between π_h and

c_M, c_{RMS} of -0.315, -0.145, respectively ($p < 0.001$ both tests). For the **shad** set, we obtain

correlations between π_h and c_M, c_{RMS} of -0.414 ($p < 0.001$) and -0.052 ($p = 0.002$).

Fig. 3a (*right*) shows edges from each set corresponding to the 10^{th}, 50^{th}, and 90^{th}

percentiles of π_h, and **Fig. 3b** (*right*) shows shadows at these same percentiles. We see occlusions

with high values of π_h tend to arise when one or both adjacent surfaces is comprised of high-

spatial frequency textures, and that shadows with high values of π_h occur when the shadow

overlays a high-spatial frequency texture pattern. Although we observe significant differences in

our measure of high spatial frequency content between edges and shadows (**Fig. 2c**), we find that

when we add this variable to our logistic regression classifier, we do not observe an improvement

in discrimination performance. For **oset-1**, a classifier using all three cues can separate occlusions

and shadows with an average performance of 66.4% accuracy on the test image sets (non-

overlapping with training sets), and 69.7% accuracy on the training sets (**Supplementary Table**

S1). For **oset-2**, the classifier separates the two categories in the test sets with an average accuracy

of 65.9%, with average accuracy of 70.5% on the training sets (**Supplementary Table S2**). Similar

results were obtained with a second analysis in which both training and test sets were sampled

uniformly from the full database, with performance of 68.5% on the test set for **oset-1** and 69.4%

on the test set for **oset-2**.

Image-computable machine learning classifiers

<u>Gabor filter classifier</u>

Our analysis of image patch statistics demonstrated that simple features like contrast and spatial

frequency could separate the two categories well above chance at a resolution of 40x40 pixels.

However, this simple set of intuitively defined features does not exhaust all the information

potentially available to human or machine observers to separate these two categories. Therefore,

to gain additional insight we considered the performance of two biologically plausible image-

computable machine learning classifiers.

The initial representation of local image regions in the visual cortex is computed by the

population of V1 simple cells, which are well modeled as bank of multi-scale linear Gabor filters

with half-wave rectified outputs. We performed binomial logistic regression on the rectified and

down-sampled (MAX pooling) outputs of a bank of physiologically plausible oriented Gabor

filters (**Kovesi, 2000; Field, 1987**) defined at multiple spatial scales (8x8, 16x16, 32x32). We refer

to this model illustrated in **Fig. 4a** as the **GFB** (Gabor Filter Bank) classifier, and Gabor filters at

one spatial scale are illustrated in **Supplementary Fig. S3**.

The **GFB** classifier performed significantly better than the classifier defined on contrast

statistics (**Fig. 2**), and its performance was robust over a wide range of regularization hyper-

parameters (**Supplementary Fig. S4**). Breaking the images into 5 folds of non-overlapping images

revealed average test set performance of 78.5% correct for **oset-1** (**Supplementary Table S3**),

although average test set performance was slightly worse for **oset-2** (70.8% correct,

Supplementary Table S4). Average training set performance was about the same for both sets

(**oset-1**: 84.7%, **oset-2**: 82.8%). This poorer generalization ability for **oset-2** may have resulted

from the relatively small size of this occlusion set (only 20 images), leading to over-fitting of the

training data. When both test sets and training sets were sampled from the entire image database

uniformly (with replacement), we found much better model performance on the test sets (**oset-1:**

79.9%, **oset-2:** 80.4%), most likely because they were being trained and tested on similar (or even

identical) image patches (**Supplementary Table S5, Supplementary Fig. S5**).

To determine the stimulus which would be judged by the **GFB** classifier to be most likely

to be classified as an occlusion (or shadow), we numerically found the stimulus to maximize (or

minimize) the model output. Unfortunately, neither of these stimuli obtained via optimization

visually resembles the actual image patches from either category (**Supplementary Fig. S6a**).

However, we do see that the stimulus most likely to be classified as an occlusion has a sharp

border, whereas the stimulus most likely to be a shadow is relatively "flat" in the middle.

Therefore, we can gain better intuition for what each model is looking for by plotting the edges (of

both categories) most likely to be classified as occlusions or shadows, as shown in **Fig. 5a**. Each

quadrant shows a combination of actual category (vertical dimension) and predicted category

(horizontal dimension). We see that the occlusions most likely to be correctly classified as

occlusions (*top left*) have low contrast with a sharp boundary between regions and quite often

differences in texture on opposite sides of the border. The occlusions most likely to be mis-

classified as shadows (*top right*) tend to have higher contrast and a somewhat more blurred edge.

The shadows mis-classified as occlusions (*bottom left*) tend to have lower contrast and/or a sharper

edge. And finally, the shadows which are most likely to be correctly classified (*lower right*) have

high contrast and blurry edges.

<u>Filter-rectify-filter classifier</u>

We next considered the performance of a Filter-Rectify-Filter (**FRF**) model to classify occlusion

and shadow edges (**Fig. 4b**). **FRF** models have been long used for modeling texture segmentation

(**Malik & Perona, 1990; Bergen & Landy, 1991; Baker, 1999; Landy & Graham, 2004; Zavitz**

& Baker, 2013, 2014; DiMattina & Baker, 2019, 2021; DiMattina, 2022) and are

mathematically similar to three-layer connectionist neural networks (**Rumelhart, Hinton, &**

Williams 1986; Bishop, 2006; Goodfellow, Bengio, & Courville, 2016). The first filtering layer

of this network was comprised of the fixed, multi-scale Gabor filter bank used in the **GFB** classifier

(**Fig. 4a**). The rectified, down-sampled outputs of this filter bank were then fed to a population of

K hidden units ($K = 4, 6, 10$), the rectified outputs of which were linearly combined form a decision

variable, which is passed into a sigmoid function to predict the occlusion probability.

When training and test sets were derived from non-overlapping sets of images, adding this

hidden layer greatly improved classification performance on training sets, but yielded a more

modest improvement for the test sets. For the **FRF** model with 6 hidden units (**FRF-6**), the average

performance on training sets approached 90% accuracy (**oset-1**:86.3%, **oset-2**: 89.0%), but the

average test set performance (**oset-1**: 80.3%, **oset-2**: 73.8%, **Supplementary Tables S6, S7**) was

only somewhat better than the **GFB** model (**GFB - oset-1**: 78.5%, **oset-2**: 70.8%). Similar results

were obtained for **FRF-4** (**oset-1** – *train*: 85.2%, *test*: 79.9%; **oset-2** – *train*: 80.5%, *test*: 73.5%;

Supplementary Table S8, **S9**) and **FRF-10** (**oset-1** – *train*: 87.4%, *test*: 80.5%; **oset-2** – *train*:

91.2%, *test*: 73.6%; **Supplementary Table S10**, **S11**). As with the other models, performance was

relatively insensitive to the value of the regularization hyper-parameter (**Supplementary Figs. S7-**

S9). By contrast, when both the test and training sets were uniformly sampled (with replacement)

from all images, for each **FRF** model and each set of stimuli (**oset-1**, **oset-2**), performance on the

test sets was commensurate with that on the training sets, approaching 90% (**Supplementary**

Table S5). This is because in this case the model was being tested on patches which were very

similar (or identical) to those it was trained on.

As with the GFB, numerical maximization (or minimization) of FRF model output did not

yield stimuli that visually resembled either category (**Supplementary Fig. S6b-d**). As before, we

find the stimulus most likely to be an occlusion has a sharp boundary, whereas a shadow has a

gradual boundary. Numerically finding the optimal stimuli for the hidden units in each model

revealed that many hidden units seemed to be sensitive to differences in texture on opposite sides

of the boundary (**Supplementary Fig. S10**). This is consistent with the idea that texture differences

may be important for distinguishing shadows from surface boundaries (**Jiang et al., 2010;**

DiMattina 2022).

Fig. 5b shows the actual and predicted categories of the image patches in **oset-1** the **FRF-**

6 model predicts to have the highest probability of category membership. We see that as with the

GFB model, occlusions correctly classified as such (*top left*) tend to have low contrast and sharp

borders, and shadows correctly classified as such (*bottom right*) tend to have high contrast and

blurred borders. Occlusion patches mis-classified as shadows tend to have high contrast and

smoother boundaries (*top right*), whereas shadows mis-classified as occlusions (*bottom left*) have

lower contrast and sharper boundaries.

Models are sensitive to penumbral blur and texture

<u>Tuning for contrast and penumbral blur</u>

In order to understand what image features are being exploited by the **GFB** and **FRF** models to

distinguish the image categories, we considered the response of the models to luminance step edges

with varying levels of contrast and penumbral blur (**Fig. 6a**). **Fig. 6b** shows the response of the

GFB model to step edges with varying degrees of penumbral blur. Different curves denote

different levels of Michelson contrast (c_M), which is held constant (via numerical image re-scaling)

for each stimulus on the curve. We see that increasing the level of penumbral blur decreases the

probability that the stimulus is classified as an occlusion edge, or equivalently makes it more likely

to be classified as a shadow. Furthermore, we find that as contrast increases, the edge probability

also decreases, consistent with our analyses shown in **Fig. 2**. Similar results were obtained for the

FRF model, as illustrated in **Fig. 6c**. For both models, we see in **Fig. 6** that the sensitivity to both

the blur and contrast parameters can be quite dramatic, greatly affecting the edge classification

probability.

<u>Removal of texture information</u>

Our analyses of the two models suggests that they may be sensitive to texture differences on

opposite sides of the image patch. To test the importance of texture cues more directly, we

performed a simple image manipulation procedure to remove texture information from occlusions

(**DiMattina et al. 2012**). Our method simply sets the intensity of each pixel on each side of the

boundary equal to the mean value measured from that side. This manipulation leaves the image

Michelson contrast (**Eq. 3**) unchanged since the mean intensity on each side remains identical.

Examples of occlusion patches manipulated in this manner are shown in **Fig. 7a**. The output of the

GFB and **FRF** models is an occlusion probability p (with shadow probability being $1 - p$). The

output of each model is computed from the log-odds ratio $u = \ln\frac{p}{1-p}$ by applying the logistic link

function. Therefore, we may recover the log-odds ratio by applying the inverse logistic link

function σ^{-1} to the predicted occlusion probability. A positive log-odds ratio indicates that an

image patch is more likely to be an occlusion, and a negative log-odds ratio indicates a shadow.

Fig. 7b plots the log-odds ratio for both models (**FRF**: blue, **GFB**: green) for the original occlusion

images (*horizontal axis*) and the texture removed images (*vertical axis*) from **oset-1** (*top*) and **oset-**

2 (*bottom*). Values greater than zero indicate patches that are (correctly) classified as being

occlusions, less than zero indicates patches mis-classified as shadows. We see that patches

predicted to have a higher probability of being occlusions experience a much greater reduction in

occlusion probability when texture is removed. This change in probability is shown explicitly in

Fig. 7c, which plots the log-odds ratio of the original images against the difference Δ in log-odds

ratios. A strong positive correlation of the original log-odds ratio with Δ was observed for each

model for both **oset-1** (**FRF**: $r = 0.9594$, $p < 0.001$, **GFB**: $r = 0.9206$, $p < 0.001$, N = 191) and

oset-2 (**FRF**: $r = 0.9755$, $p < 0.001$, **GFB**: $r = 0.9776$, $p < 0.001$, N = 596).

Interestingly, we see that occlusions which were mis-classified as shadows (original log-

odds < 0) increase their occlusion probability, likely because the texture-removal operation creates

a sharp boundary (**Fig. 7a**), thereby eliminating the blur which is taken as evidence for a shadow

(**Fig. 6**). **Fig. 13d** explicitly plots a histogram of Δ for correctly classified occlusions for **oset-1**

(*left*) and **oset-2** (*right*) for both the FRF (*top*) and GFB models (*bottom*). For the FRF model,

statistical testing reveals significantly positive (Wilcoxon rank-sum test) median value of Δ for

both sets (**oset-1**: 0.716, $p < 0.001$; **oset-2**: 2.07, $p < 0.001$). By contrast, for the GFB model, for

oset-1 the median value of Δ fails to reach significance (median = 0.165, $p = 0.138$), although it is

significant for **oset-2** (median = 1.073, $p < 0.001$). **Fig. 7e** is the same as **Fig. 7d** but for occlusion

patches which were incorrectly classified as shadows. For the **FRF** model (*top*), we find a

significantly negative median value of Δ for both sets (**oset-1**: -2.33, $p < 0.001$; **oset-2**: -2.41, $p <$

0.001). For the GFB model (bottom) we also obtain significant negative values (**oset-1**: -2.334, p

< 0.001; oset-2: -1.861, $p < 0.001$).   Similar results were obtained for **FRF-4**, **FRF-10**, as

summarized in **Supplementary Table S12**.

430   For each pair of image patches (original and texture-removed), for each model we can

compute Δ (Δ_{FRF}, Δ_{GFB}) and then compute the difference $D = \Delta_{FRF} - \Delta_{GFB}$ in order to test the

hypothesis that removal of texture information has a stronger effect on the responses of the **FRF**

model than the **GFB** model ($D > 0$). Histograms of this difference D are shown in **Fig. 7f**, and in

both cases we obtain a median significantly greater than zero (**oset-1:** 0.724, $p < 0.001$; **oset-2**:

$0.755, p < 0.001$), suggesting that the **FRF** model is more sensitive to texture information.

Psychophysical experiment

<u>Individual observer performance</u>

A single-interval forced choice experiment was performed in which human observers classified

40x40 pixel grayscale natural image patches as being shadow or occlusion edges (see **METHODS**

for details). This experiment is schematically illustrated in **Fig. 8a**, and was implemented online

using Qualtrics for stimulus presentation and recording responses (**Supplementary Fig. S11**). The

first survey (**QT-1**) was considered a "practice" session, although we found similar results with

the "test" surveys (**QT-2**, **QT-3**) and hence included it in our final analysis. **Fig. 8b** (*left*) shows

the performance (proportion correct p_c) of all N = 18 observers who completed all three online

experiments (with above-chance performance on the final two). We find the median observer

(*large blue circles*) had performance of $p_c = 0.69$ (**QT-1**), $p_c = 0.688$ (**QT-2**), $p_c = 0.740$ (**QT-3**),

with the best observer attaining performances (*black diamonds*) of $p_c= 0.805, p_c= 0.755, p_c= 0.80$

respectively. Performance was not significantly correlated across surveys for 2 of 3 possible pair-

wise comparisons (**QT 1/2**: $r = 0.222, p = 0.376$; **QT 1/3**: $r = 0.54, p = 0.021$; **QT 2/3**: $r = 0.129,$

$p = 0.611$). Therefore, for many analyses we pooled data across surveys. In these cases, the units

of analysis will be referred to as *observer-surveys*. **Fig. 8b** (*right*) also shows performance

quantified as d' for all experiments, and we observe a strong positive correlation between d' and

p_c for each survey (**QT-1**: $r = 0.998, p < 0.001$; **QT-2**: $r = 0.993, p < 0.001$; **QT-3**: $r = 0.957, p <$

0.001) and across all N = 54 observer-surveys ($r = 0.985, p < 0.001, N = 54$).

Observer performance in standard signal detection theory is determined by the separation

d' of the distributions of the decision variables corresponding to each category, as well as the

decision criterion γ applied by the observer. In our SDT analysis, $\gamma < 0$ corresponds to a bias

towards judging stimuli to be occlusions, and $\gamma > 0$ corresponds to a bias towards judging stimuli

to be shadows. For 2 of the 3 surveys, the median value of γ was not found to be significantly

different from zero using a Wilcoxon test (**QT-1**: median $= 0.097, p = 0.042$; **QT-2**: median $=$

0.082, $p = 0.119$; **QT-3**: median $= -0.008, p = 0.856$). Distributions of γ for each survey are shown

in **Supplementary Fig. S12**. Pooling γ across surveys (**Fig. 8c**) reveals a median which was not

significantly different from zero (Wilcoxon test, N = 54, median $= 0.066, p = 0.059$). Computing

the ratio $|d'/\gamma|$ for $\gamma \neq 0$ (N = 51) reveals a median value of 8.78, with quartiles $Q_1 = 3.92$ and

$Q_3 = 15.06$. Therefore, any bias in the decision criterion is for most observers negligible compared

to the distribution separation.

Since one of our goals is to compare human performance to that of machine observers, we

want to not only compare the probability of correct response, but also the pattern of classification

errors. For each observer and experiment, we measured the probability $P(s|O)$ that an occlusion

was misclassified as a shadow, and the probability $P(o|S)$ that a shadow was misclassified as an

occlusion. If there is no bias in either direction, the difference $P(s|O) - P(o|S)$ (**Fig. 8d**) should

be zero. A positive value would indicate a greater likelihood of misclassifying occlusions as

shadows than misclassifying shadows as occlusions. A negative value would indicate a greater

likelihood of mis-classifying shadows as occlusions than the other way around. On an individual

basis, this can be assessed using a difference of binomial proportion test (*Wald test*). Doing so

revealed that over 54 observer-surveys (18 observers taking 3 surveys each), in 22/54 cases a

significant bias was observed towards misclassifying one or the other stimulus categories. Of these,

6/22 observer-surveys exhibited a bias to misclassify occlusions as shadows, whereas in 16/22

observer-surveys we saw a bias to mis-classify shadows as occlusions. The proportion of observer-

surveys which exhibited a significant bias to mis-classify shadows as occlusions does not differ

significantly from chance (binomial proportion test, N = 22, p = 0.055). Over the full set of

observer-surveys, comparing the median Wald statistic (**Fig. 8e**) to zero (sign-rank test) failed to

reach the conventional criterion for statistical significance (median = -0.675, p = 0.057, N = 54).

Fig. 8f shows a scatterplot of $P(s|O)$ and $P(o|S)$, and we see that points are about equally likely

to be above and below the diagonal.

Aggregate observer performance across images

In addition to analyzing performance of each individual observer, for each individual image (200

per set, for 3 image sets), we characterized the proportion of observers that classified it as a shadow

or an occlusion. Doing this allows us to generate an *aggregate observer* (**AO**) model, which

provides a model of average human performance against which the performance of machine

classifiers (and other human observers not used to define the model) can be compared.

Mathematically, the aggregate observer for K participants making a binary behavioral

classification ($b = 0, 1$) of N images is given by $\mathcal{A} = \{\pi_i\}_{i=1}^{n}$, where π_i indicates the proportion

of observers for which $b_i = 1$. The **AO** model provides a statistical model of average human

performance on the task. One can generate simulated datasets stochastically using the **AO** by

generating response $b_i = 1$ to stimulus i with probability π_i, and response $b_i = 0$ with probability

$1 - \pi_i$. Likewise, one can generate a stimulated dataset deterministically by setting $b_i = 1$ if $\pi_i \geq$

0.5, and $b_i = 0$ otherwise.

Fig. 9 shows the probability that each stimulus is classified as an occlusion by the **AO** (blue

curves), with actual stimulus categories indicated by a black (+) symbol. We see that the

overwhelming majority of the stimuli with low occlusion probability are shadows, and most

stimuli with high occlusion probability are occlusions, with little bias in either direction. **Fig. 9b**

breaks down these plots by the actual category of the image. **Table 1** indicates the confusion

matrices for each survey obtained from the **AO** using a deterministic rounding rule that sets $b_i =$

1 if $\pi_i \geq 0.5$, and $b_i = 0$ otherwise.

	QT-1		QT-2		QT-3	
	predicted		predicted		predicted	
actual	*occlusion*	*shadow*	*occlusion*	*shadow*	*occlusion*	*shadow*
occlusion	88	12	74	26	88	12
shadow	19	81	21	79	24	76

506   **Table 1: AO** confusion matrix for all experiments.

From these confusion matrices, we observe that the proportion correct for the **AO** (**QT-1**: 84.5%,

QT-2: 76.5%, **QT-3**: 82.0%) is not significantly different from the best individual observer (95%

CI of the difference: **QT-1**: [-0.034, 0.114], **QT-2**: [-0.074, 0.094], **QT-3**: [-0.057, 0.097]).

Therefore, there seems to be a "wisdom of crowds" effect whereby averaging over a population of

observers yields an aggregate observer that does as well as the best individuals. For each

experiment, we tested whether the proportions of errors were biased in one or another direction,

with the null hypothesis being that the two proportions were equal. A binomial proportion test

revealed no significant difference for **QT-1** ($p = 0.281$, N = 31), **QT-2** ($p = 0.559$, N = 47), or **QT-**

3 ($p = 0.066$, N = 36). Therefore, the **AO** is just as likely to mis-classify occlusions as shadows as

it is to make the opposite error.

Comparison with machine classifiers

<u>Correlation between log-odds ratios</u>

For each image, the aggregate observer model (**AO**) specifies a probability that the image is an

occlusion, much in the same manner as two machine classifiers investigated in an earlier paper. In

order to see if images which were more likely to be categorized as occlusions by the **AO** were also

more likely to be categorized as such by various machine observers, we developed a simple

analysis procedure, which we now describe. Briefly, each of these machine classifiers at its final

stage computes an intermediate variable $u_i = \ln \frac{p_i}{1-p_i}$ (the log-odds ratio) which is them passed

through a monotonic sigmoidal non-linearity in order to compute a probability p_i of image i being

an occlusion. By applying the inverse sigmoid function $u_i = \sigma^{-1}(p_i)$ to the probability computed

by the model, we recover the value of the log odds ratio, which unlike the occlusion probabilities

computed over the set of images (**Supplementary Fig. S13**) enjoys an approximately normal

distribution. Applying this same inverse sigmoid function to the occlusion probability p_i computed

from the **AO** permits recovers the corresponding log-odds $\sigma^{-1}(p_i)$ when $0 < p_i < 1$. Note that

$\sigma^{-1}(0)$ and $\sigma^{-1}(1)$ are not well defined (being $-\infty$ and $+\infty$, respectively).

By correlating the log-odds ratios over the set of images, we can determine the extent

various machine classifiers exhibit agreement with human observers. **Fig. 10** shows scatter-plots

of the log odds ratios obtained from human and machine observers applied to all images in each

survey (**QT-1**, **QT-2**, **QT-3**) for both the **GFB** (*left column*) and **FRF-10** (*right column*) model.

To test whether there was a stronger correlation between the **GFB** and **FRF** model and human

behavior, we computed the Spearman correlation between the log-odds ratios from the **FRF** and

GFB model and the **AO** for N = 1000 bootstrapped samples. We made use of Spearman rank-

order correlation ρ instead of Pearson's *r* because some images were classified by all observers as

shadows or occlusions, so that $p_i = 0$ or 1, making $\sigma^{-1}(p_i)$ is undefined. We found that for all

surveys a larger Spearman correlation between the **FRF** and the **AO** (**QT-1**: $\rho = 0.696$, **QT-2**:

$\rho = 0.587$, **QT-3**: $\rho = 0.775$, $p < 0.001$ all tests) than the **GFB** and **AO** (**QT-1**: $\rho = 0.604$, **QT-**

2: $\rho = 0.568$, **QT-3**: $\rho = 0.697$), and for 2/3 surveys the 95% CI of the difference did not contain

zero (**QT-1**: [0.011, 0.183] , **QT-2**: [-0.067, 0.118], **QT-3**: [0.010, 0.165]). Pooling all three

surveys also revealed a significantly larger correlation between the **FRF** and **AO** ($\rho = 0.692$) than

the **GFB** and **AO** ($\rho = 0.624$), with a median difference $\Delta\rho = 0.068$ and the 95% CI of the

difference $[0.022, 0.118]$ not containing zero. Similar results were obtained with **FRF-6**, with

median difference (pooling acoss surveys) between the correlations of $\Delta\rho = 0.073$ and 95% CI of

the difference $[0.028, 0.123]$ not containing zero. This analysis suggests that the **FRF** model is

better than the **GFB** model at capturing whatever aspects of the image humans are utilizing.

<u>Decision variable correlation</u>

We further explored the relative efficacy of the **FRF** and **GFB** models in accounting for human

behavior using Decision Variable Correlation (**DVC**), an extension of signal detection theory

(**Sebastian & Geisler, 2018**). This novel methodology assumes that for classification tasks both a

human observer and a model (or two humans) make use of an internal, unobserved decision

variable which each compares to some criterion to decide which stimulus was presented. Assuming

the joint distribution of the human and model decision variables is a bivariate normal distribution,

by analyzing the patterns of agreement and disagreement between the model and human, it is

possible to recover the covariance. DVC is particularly powerful for model selection, since it is

possible for two models to predict performance (as percent correct) equally well, while not

agreeing on which particular stimuli the human and model classify into each category. DVC has

been fruitfully applied in several domains, including texture segmentation (**DiMattina & Baker,**

2019), stimulus detection in noise (**Sebastian, Semiller, & Geisler, 2020**), speed perception (**Chin**

& Burge, 2000), and avian audition (**Henry & Abrams, 2021**).

Fig. 11a shows for surveys **QT-1**, **QT-2**, **QT-3** the DVC between each individual observer

and each of the three models: **GFB**, **FRF**, and **AO**. We see for **QT-1** a significantly larger median

DVC for the **FRF** model than **GFB** model (sign-rank test, median **FRF**-**GFB** = 0.061, p = 0.001,

N = 18), and furthermore a significantly larger median DVC for the **AO** model than either **FRF**

(median **AO**-**FRF** = 0.052, p = 0.043) or **GFB** models (median **AO**-**GFB** = 0.114, p = 0.006). For

QT-2, we do not see a significant difference in DVC between the **FRF** and **GFB** models (median

FRF-**GFB** = -0.008, p = 0.349), but do see significantly better performance by the **AO** than either

FRF (median **AO**-**FRF** = 0.22, $p < 0.001$) or **GFB** (median **AO**-**GFB** = 0.192, $p < 0.001$).

Interestingly, for **QT-3** we see better median performance by the best machine classifier (**FRF**)

than the **AO** which was derived from other humans (median **AO**-**FRF** = -0.146, p = 0.022), as

well as better performance the **GFB** classifier (median **FRF**-**GFB** = 0.090, p = 0.02), which in

turn exhibited the same performance as humans (median **AO**-**GFB** = -0.037, p = 0.514). **Fig. 11b**

combines DVCs from all surveys. Here we observe significantly better performance for the **FRF**

model than the **GFB** model (median **FRF**-**GFB** = 0.045, p = 0.005), although we see the best

performance for the **AO** model (median **AO**-**GFB** = 0.142, p = 0.001; median **AO**-**FRF** = 0.061,

$p = 0.021$). **Fig. 11c** shows histograms of these differences between the DVCs for all model

comparisons, combined across the three surveys.

<u>Analysis of mis-classification patterns</u>

Another way to compare the performance of the models to human observers is to examine the

patterns of classification errors. If there is no bias in either direction in the pattern of mis-

classification errors, then the proportion of mis-classifications of shadows as occlusions (or vice

versa) should not differ from 0.5. This can be assessed for each machine classifier (**GFB**, **FRF**)

and the **AO** using a simple binomial proportion test. Here we list the proportion of classification

errors which involved classifying the patch as an occlusion (*occ/all*), together with the 95% CI of

the null hypothesis of equal probabilities of errors in either direction.

	QT-1		QT-2		QT-3	
	occ/all	*CI-95*	*occ/all*	*CI-95*	*occ/all*	*CI-95*
GFB	*10/33**	[10.9, 22.1]	13/34	[11.3, 22.7]	*12/44**	[15.5, 28.5]
FRF	9/17	[4.5,12.5]	*17/23**	[6.8, 16.2]	6/16	[4.1, 11.9]
AO	12/31	[10.0, 21.0]	26/47	[16.8, 30.2]	*12/36**	[12.1, 23.9]

Table 2: Number of mis-classifications of shadows as occlusions by each model.

We see from **Table 2** that for two surveys (**QT-1**, **QT-3**) the **GFB** is biased to make errors in the

direction of shadows and away from occlusions, consistent with our previous observations. By

contrast, for the **FRF** model, we only observe 1 survey with a bias (**QT-2**), this time in the direction

of errors in favor of occlusions. Similarly, the **AO** only shows one survey with a bias (**QT-3**).

Pooling across all three surveys (**QT-1**, **2**, **3**), for the **GFB**, 35/111 mis-classifications are in the

direction of occlusions, with $p < 0.001$ (binomial proportion test, N = 111). By contrast, for the

FRF model 32/56 mis-classifications are in the direction of occlusions, and we fail to see a

significant bias ($p = 0.3496$, N = 56). Similarly, for the **AO**, 50/114 mis-classifications favor

occlusions, exhibiting no significant bias ($p = 0.2234$, $N = 114$). Thus, we see a much stronger

agreement between the **FRF** model and average human behavior (**AO**) based on patterns of mis-

classification.

DISCUSSION

Summary of contributions

Here we analyzed the statistical properties of two important classes of luminance edges: (1)

occlusion edges, and (2) shadow edges. Distinguishing these two possible edge causes has

important implications for understanding perceptual organization, as one kind of edge indicates a

surface boundary, whereas the other indicates a change in illumination. Following previous work

(**Vilankar et al., 2014; DiMattina et al., 2012**), we measured basic contrast statistics from each

category, demonstrating that occlusions exhibit both the highest observed contrasts, as well as the

lowest contrasts. We also measured spatial frequency properties of each image category,

demonstrating more high spatial frequency content in occlusion edges than shadows. V1 neurons

are known to be sensitive to both spatial frequency and contrast (**Albrecht & Hamilton, 1982;**

Parker & Hawken, 1988), so relevant information for discriminating these edge categories is

potentially extracted at the earliest level of cortical processing. Implementing a simple Gabor Filter

Bank (**GFB**) model inspired by V1 receptive field properties, we demonstrated that at a resolution

of only 40x40 pixels these two edge categories can be distinguished at nearly 80% accuracy.

Furthermore, we demonstrated that this model exhibits strong tuning to penumbral blur, an

important shadow cue (**Mammasian et al., 1998**; **Elder, Trithart, Pintille & MacLean, 2004;**

Elder & Zucker, 1998; **Elder, 1999; Casati & Cavanagh 2019**). To investigate the performance

of models which can also take texture into account, we demonstrate that a Filter-Rectify-Filter

(**FRF**) model, commonly used to model second-order vision (**Baker, 1999; Landy & Graham,**

2004; Zavitz & Baker, 2013, 2014; DiMattina & Baker, 2019), can perform at greater than 80%

accuracy.

In order to relate the performance of models to that of human observers, we implemented

a psychophysical experiment in which observers completed the same shadow/occlusion

classification task as we investigated in the models. The best human observers performed at levels

commensurate with the models, although the median observer was slightly worse. Breaking down

responses on an image-by-image basis, we found that while both the **FRF** and **GFB** models

exhibited positive correlations with human responses, on average the **FRF** models exhibited

greater correlations with human performance. Since the **FRF** model is more sensitive to texture,

this is consistent with the idea that locally available texture cues may play an important role. This

finding that local cues can be fruitfully exploited to assist global scene interpretation is consistent

with many previous studies on natural edge detection (**McDermott, 2004; Zhou & Mel, 2008;**

DiMattina et al., 2012; Ing et al., 2010), classification (**Vilankar et al., 2014; Ehinger, Adams,**

Graf, & Elder, 2017; Breuil et al., 2019), and figure-ground assignment (**Burge, Fowlkes, &**

Banks, 2010; Ramenahalli, Mihalas, & Niebur, 2014).

Relationship to closely related work

Most psychophysical studies concerning shadows have investigated the essential role that shadows

play in three-dimensional scene interpretation (**Ramachandran, 1988; Elder et. al. 2004;**

Mammasian et al., 1998; Rensink & Cavanaugh, 2004; Wilder, Adams, & Murray, 2019).

By contrast, to our knowledge, only two previous psychophysical studies directly speak to the

issue of what locally available information can be used to distinguish shadows from other edge

causes like occlusions (**Vilankar et al., 2014; Breuil et al., 2019**).

A previous investigation by **Vilankar et al. (2014)** characterized the statistical properties

of achromatic occlusion edges and non-occlusion edges, a "catch-all" category including shadows,

material changes, and surface orientation changes. Although they used local analysis windows

similar in size to our own (they used rectangular windows of 81x40 whereas we used square 40x40

windows), the images which they analyzed were at high resolution (1920x2560) as opposed to the

lower resolution (576x786) images we analyzed. The consequence of this is that their analysis was

more "local" than our own, with their smaller dimension (40) comprising only 1.56% of the larger

dimension (2560) of the image patch, whereas our 40x40 patches subtended 5.08% of the larger

dimension (786). Finally, their edges were initially identified using a Canny edge detector

algorithm before being classified as occlusions or non-occlusions by human observers. As they

note, this process biases their samples towards edges containing stronger luminance differences,

although they also analyzed a smaller set of hand-labeled edges and obtained similar results.

684   In their paper, they demonstrated that occlusions had higher contrast, on average, than non-

occlusions. We found that when the comparison was restricted to occlusions and shadows, both

the highest contrast patches as well as the lowest-contrast patches were occlusions (**Fig. 2**).

Furthermore, when we analyzed occlusions from the subset of 19 images in **oset-1** that were also

used in their study, the results were consistent with our general findings for both **oset-1** and **oset-**

2 (**Supplementary Fig. S1**). Therefore, it is unlikely that this discrepancy with our results arises

from their use of a more limited image set (N = 38 images versus N = 100). It is important to note

that there are two additional key differences which make direct comparison difficult: (1) We did

not consider any non-occlusions apart from shadows in our analysis, and (2) They did not break

down their non-occlusion stimuli into different categories in their analysis. Thus, it is possible that

their finding that non-occlusions had lower contrast than occlusions would not have held if they

had restricted themselves to only consider shadows.

696   Another interesting point of contact with **Vilankar et al. (2014)** is that in their study they

plotted the luminance profiles of different categories of edges, including occlusions, non-

occlusions, and shadows. They note a more gradual change in luminance for non-occlusions,

including shadows, than for occlusions. All the image-computable models trained to distinguish

shadows from occlusions exhibited tuning to penumbral blur, with increased blur leading to higher

probability of an edge being classified as shadow (**Fig. 6**). Previous experiments suggest that

humans are adept at distinguishing sharp from blurred edges (**McIlhagga & May, 2012;**

Ahumada & Watson, 2011), and our analysis suggests this ability may help solve an important

problem in natural scene analysis.

Another closely related study which served as a strong motivation for the present work is

the study by **Breuil et al. (2019)** demonstrating the importance of chromatic cues for accurate edge

classification as luminance or material. One interesting finding to arise from their study is that

performance in the task for human subjects increased with edge size, whereas a similar

improvement in performance was not observed with machine classifiers defined using luminance

and chromatic cues. A reasonable interpretation of this result is that human observers were able to

exploit textural cues which were not incorporated into the machine classifiers. Consistent with this

interpretation, the present work also demonstrates that texture cues can be potentially exploited for

distinguishing shadows from occlusions. Training "Filter-Rectify-Filter" (**FRF**) style classifiers

revealed hidden units exhibiting sensitivity to differences in texture (**Supplementary Fig. S10**),

and removing texture from the image patches lead to a drastic reduction in occlusion probability

for those images most likely to be occlusions (**Fig. 7**). The utility of texture for distinguishing

changes in illumination from changes in material is relatively unsurprising, as different surfaces

usually have different textures. However, what is perhaps quite surprising is our finding of just

how much information highly localized texture differences (40x40 pixels) can contribute.

Limitations and future directions

The present study has several limitations, each of which provides a fruitful avenue for future work. Firstly, as in many other studies of natural perception and computer vision (**Mely et al., 2016; Zhou & Mel, 2008; Ramachandra & Mel, 2013; DiMattina et al., 2012; McDermott, 2004; Breuil et al., 2019; Martin et al., 2004**), we rely on image features annotated by human observers in a relatively small number of visual scenes. Therefore, the validity of such analyses relies on the assumption that the image sets chosen, and the region within these images which are annotated by human observers, are indeed representative of the natural visual environment.

Secondly, we focus here only on achromatic cues for shadow/occlusion classification, as previous work has rigorously investigated color and its importance for shadow edge/material edge classification (**Breuil et al., 2019**). It would be of great interest for future work to incorporate color into our neural network analyses. Given the potential utility of chromatic information for distinguishing illumination from material (**Olmos & Kingdom, 2004; Kingdom, 2019**), we might expect to find hidden units which learn to detect different colors on opposite sides of the boundary. Indeed, studies of deep neural networks trained on RGB images for classification tasks have been shown to learn filters specialized for detecting color edges while being insensitive to luminance (**Krizhevsky, Sutskever, & Hinton, 2012; McIlhagga & Mullen, 2018**). Despite the obvious interest of including chromatic cues, our work clearly demonstrates that they are by no means necessary for accurate shadow edge classification from local cues. A simple perusal of the grayscale images in **Fig. 1a** serves as proof in fact that while most certainly useful, chromaticity is by no means necessary for edge classification, and perceptual organization more broadly.

The analyses in this paper simply demonstrate that certain cues (contrast, texture, penumbral blur) are potentially useful for solving this natural vision problem, and that simple

neural computations can exploit these cues. It does not tell us exactly the rules by which these cues

are combined by human observers (**Jones, 2016, Kingdom et al., 2015, Ernst & Banks, 2002**),

and what cues takes precedence in cases of conflict. One way this can be addressed experimentally

would be to create parametric stimuli closely resembling natural stimuli, and then systematically

manipulating these stimuli to determine which aspects drive behavior. For instance, our results

suggest that we could create a synthetic stimulus which would be likely classified as an occlusion

by a human observer by juxtaposing two different naturalistic textures with a sharp luminance

border super-imposed. As we blur the border and make the textures similar or identical, observers

may be more likely to classify the patch as a shadow. By varying cues simultaneously and

exploring effects on stimulus categorization, we can fit and compare multiple cue combination

models to better understand how texture, blur and color are integrated for shadow edge detection.

METHODS

Shadow and occlusion databases

<u>Image sets and hand-labeling procedures</u>

We obtained a set of N = 47 shadow images (786x576 resolution) taken from the McGill calibrated

color image database (**Olmos & Kingdom, 2004**). The set of 47 images contained both natural

and manmade objects. All selected images contained clear figure-ground organization and

detectable shadow boundaries. Authors CD and BG with two other undergraduate researchers (LA,

MD) used the image manipulation program GIMP (https://www.gimp.org/) to label the most

noticeable shadows within the set of images. Each student was instructed to label the shadows

individually, so their labels reflected their independent judgment. Examples of images from our

shadow database (**shad**) are shown with the labeling of the shadow contours in each image by one

observer (MD) shown in **Fig. 1a** (*top*). A binary union of the labels from all 4 observers is shown

in **Fig. 1a** (*bottom*).

Image patches containing surface boundaries were obtained from two sets of images. One

was a previously developed image database (**DiMattina et al., 2012**), also derived from a subset

of N = 100 images (786 x 576) from the calibrated McGill image set. We refer to as this set of

images as occlusion set-1 (**oset-1**). One potential limitation of **oset-1** is that the images in this set

have almost no overlap with our set of N = 47 shadow images. Therefore, it at least possible that

any statistical differences observed between shadow edges and occlusion edges could be a function

of there being different surfaces present in the two image sets. Therefore, we developed a second

occlusion database by having the same observers label all the occlusions in a subset of N = 20

images taken from our larger database of 47 shadow-labeled images. We refer to this second

database of occlusions taken from a subset of our 47 shadow images as occlusion set-2 (**oset-2**).

Two example images from this set (**oset-2**) with labeled occlusions are shown in **Fig. 1b** (*top*),

together with a binary label of the occlusions from all 4 observers (**Fig. 1b**, *bottom*). Our hand-

labeled shadow database and both occlusion databases are freely available to the scientific and

engineering communities at https://www.fgcu.edu/faculty/cdimattina/.

<u>Image patch extraction methods</u>

Both occlusion edges and shadow edges were extracted from the image as described in **DiMattina**

et al. (2012). Briefly, random pixels labeled as edges by a single observer were chosen, cycling

through the set of observers who labeled each image (CD, LA, BG, MD). To ensure patches where

the boundary separates two regions of approximately equal size, with no extraneous edges, a patch

centered on an edge was only accepted for inclusion if the composite edge map (pooled over all

observers) for the candidate patch comprised a single, connected dividing the patch into two

regions, the smaller of which comprised at least 35% of the pixels. This procedure excludes T-

junctions or highly convex edges, yielding mostly smooth edges as is evident from the image

patches of both categories (occlusions, shadow) shown in this paper. We focused our analyses on

40x40 image patches, which in a 786x576 image constituted roughly 5% of the larger dimension,

ensuring our analysis focused on relatively local cues. Representative patches from each set are

shown in **Fig. 1c**.

Analysis of image patch statistics

<u>Contrast statistics</u>

Previous investigations have demonstrated interesting differences in the statistical properties of

occlusion patches and non-occlusions (including shadows) and shown that these statistics can be

utilized to reliably discriminate these two categories (**Vilankar et al. 2014; Breuil et al., 2019**).

Therefore, we measured some of these same quantities from our image patches at 40x40 resolution

to provide basic descriptive statistics for the shadow and occlusion edges in our databases, and to

determine the extent to which such simple statistics could be reliably exploited for image

classification purposes.

From both the shadow and occlusion edges, we measured two quantities from linearized

RGB versions of the images that were first converted to grayscale: (1) RMS contrast, and (2)

Michelson contrast. Conversion to grayscale was accomplished using the standard formula

$$I = 0.2989 * R + 0.5870 * G + 0.1140 * B. \tag{1}$$

822   The RMS contrast of the grayscale image *I* is defined as

$$c_{RMS} = \frac{\sigma}{\mu}, \tag{2}$$

823   where σ is the standard deviation of the pixel intensities, and μ is the mean pixel intensity. Since

824   our selection method only chose image patches which could be cleanly divided into two regions

825   of approximately equal size (see **DiMattina et al. 2012** for details), we were also able to measure

826   the Michelson contrast, which is defined as

$$c_M = \left| \frac{\mu_2 - \mu_1}{\mu_2 + \mu_1} \right|, \tag{3}$$

where μ_1, μ_2 denote the mean pixel intensity in each of the two regions.

Making use of the MATLAB machine learning toolbox function `fitclinear.m`, we

trained a logistic regression classifier (**Bishop, 2006**) on these two variables to see to what extent

they could distinguish the two image categories. This was done in two different ways. In the first

analysis, we broke each image set (shadows, occlusions) into 5 blocks of non-overlapping images.

The images in **oset-1**, **oset-2** and **shad** comprising each block are listed in **Supplementary Tables**

S1, S2. We then trained the classifier on 4 of the blocks (*training sets,* ~ **50K** images) while testing

on the 5[th] (*test set, ~12K* images). We obtained an estimate of the classifier ability to generalize to

novel images by averaging test set performance over all 5 choices of test set. In a second analysis,

we trained on N = **16K** images sampled uniformly (with replacement) from all of the images. We

then tested classifier performance on a test set comprised of N = **4K** images also sampled uniformly

with replacement from all the images.

<u>Spatial frequency analysis</u>

In addition to contrast statistics, another potential cue for distinguishing edges caused by shadows

from those caused by occlusion boundaries is spatial frequency content. Due to penumbral blur,

many (but not all) shadows exhibit a gradual luminance change at their boundary (**Casati &**

Cavanagh, 2019), whereas occlusions typically give rise to a relatively sharp luminance transition.

Furthermore, psychophysical experiments using classification image techniques have

demonstrated that human observers can reliably discriminate sharp luminance edges from blurry

ones (**McIlhagga & May, 2012**), suggesting penumbral blur can be potentially employed for

shadow identification. We applied the standard FFT to the 40x40 image patches from both

categories, which were first pre-processed to have zero mean and identical energy. We then

quantified the proportion of stimulus energy in various high spatial-frequency regions of the

spectrum. This was accomplished by taking the rotational sum of the power spectrum and then

taking the ratio π_h of power above 10 cycles/image to total stimulus power (Nyquist frequency

for 40 x 40 images is 20 cycles/image). This parameter π_h was combined with the two contrast

parameters c_{RMS}, c_M to reimplement the logistic regression classifier analysis described in the

previous section with a larger feature set.

Image-computable classifier analyses

Three categories of image-computable machine classifiers were implemented in Python using

Keras and Tensorflow (**Chollet, 2021**). To align the images to improve classification accuracy,

image patches were rotated into a vertical orientation, and reflected into sine phase (if necessary)

so that the left side was always darker than the right side.

As a robust test of model generalization ability, image-computable models were trained on

4 blocks of images (training sets, **~50K** images) and tested on a 5th block (test sets, **~12K** images)

having no overlap with the training sets. This was repeated for a wide range of regularization

hyper-parameter values ($\log_{10} \lambda = -3, -2, -1, 0, 1, 2, 3$), and we report the average performance

over 5 test sets for the best hyper-parameter. In our analyses, we found that for all models the

performance was generally quite robust over a large range of hyper-parameter values. For

exploring model performance characteristics, and comparing model performance with human

performance, we trained the models using our full set of images. Therefore, for these analyses we

trained models on sets of **16K** (**PIX**, **GFB** models) or **56K** (**FRF** models) images sampled

uniformly with replacement from the entire dataset, and tested the models on much smaller sets of

4K images sampled uniformly from the entire dataset.

<u>Gabor filter bank classifier</u>

The second model, which we will refer to as the Gabor Filter Bank (**GFB**) model, is illustrated

schematically in **Fig. 4a**. In this model, a fixed set of multiscale Gabor filters (8, 16, 32 pixels)

with spatial frequency bandwidths resembling V1 simple cells (**Kovesi, 2000**; **Field, 1987**) was

convolved with an input image (40x40 pixels). At each scale, the set of oriented filters includes 6

orientations, 2 phases (even/odd), and 2 contrast polarities (+/-), for a total of 24 oriented filters

(**Supplementary Fig. S3**). The outputs of these filters were half-wave linear rectified (*relu*) and

then down-sampled from 40x40 to 5x5 using MAX pooling (**Goodfellow, Bengio & Courville,**

2006). This yields a representation having 1800 dimensions. Binomial logistic regression (**Bishop,**

2006) was performed on these 1800 pooled filter responses as predictor variables with stimulus

category (0 = shadow, 1 = occlusion) as the response variable.

Filter-rectify-filter classifier

Finally, we implemented the Filter-Rectify-Filter (**FRF**) model often used to account for texture

segmentation (**Landy & Graham, 2004; Victor et al., 2017**). This model is illustrated in **Fig. 4b**.

As with the **GFB** model, the image was initially convolved with a set of fixed Gabor filters, and

the linearly rectified (*relu*) outputs down-sampled using MAX pooling. However, these down-

sampled outputs were fed into a three-layer neural network classifier having N = 4, 6, or 10 hidden

units with *relu* gain. For analyzing the effects of texture removal on the FRF model (**Fig. 7**),

occlusions having vertical or near-vertical orientation were chosen from each image database from

a set of images not used for model training. Texture information was removed from these patches

using the same method as in our previous work (**DiMattina et al., 2012**), by simply setting the

intensity to each pixel in a region equal to the mean intensity over the region. Image patches

manipulated in this manner are shown in **Fig. 7a**. This manipulation removes all texture cues while

leaving Michelson contrast (**Eq. 2**) unchanged.

Psychophysical experiments

Participants

Participants in this study consisted of N = 18 undergraduate students attending Florida Gulf Coast

University enrolled in Psychology courses PSB-4002 ("Brain and Behavior") and EXP-3202

("Sensation and Perception") during the Fall 2021 semester. All participants in these two courses

were given the opportunity to complete three experiments (**QT-1**, **QT-2**, **QT-3**) implemented as

web surveys in return for extra credit in the course. Before each experiment, participants were

required to review and accept an informed consent form.   All procedures were approved

beforehand by the Institutional Review Board of Florida Gulf Coast University (Protocol 2021-

78), in accordance with the Declaration of Helsinki.

<u>Procedure</u>

The visual experiments were implemented as a web survey using Qualtrics, an online web survey

program (https://www.qualtrics.com/). Participants accessed the link for the Qualtrics survey using

their personal computers or smartphones. Image patches used in the Qualtrics surveys used in this

study were selected from the McGill Calibrated Color Image Database (**Olmos & Kingdom, 2004**)

and then converted to grayscale. In each survey, participants were shown a 40x40 image patch

(resized to 96x96, in order to subtend roughly 2-3 degrees of visual angle at normal viewing

distances) and asked to indicate whether this patch contained an occlusion edge or a shadow edge.

Each survey contained 200 images, half of which belonged to each category, presented in random

order. After their response, feedback (correct/incorrect) was provided before presenting the next

stimulus. A schematic diagram of the experimental procedure is shown in **Fig. 8a**, and an example

survey question is shown in **Supplementary Fig. S11**. For inclusion in the final analysis, students

had to complete all three surveys in the correct order, have no blank responses, and perform better

than chance (114 or more correct out of 200) on the final 2 surveys, indicating that they had

obtained proficiency in the task. Although there were 37 participants who completed at least one

survey, only 18 participants met the criteria for inclusion in the final analysis, mostly due to the

fact that many participants failed to complete all three surveys.

REFERENCES

Albrecht, D. G., & Hamilton, D. B. (1982). Striate cortex of monkey and cat: contrast response

function. *Journal of Neurophysiology*, *48*(1), 217-237.

Baker Jr, C. L. (1999). Central neural mechanisms for detecting second-order motion. *Current*

Opinion in Neurobiology, *9*(4), 461-466.

Bergen, J. R., & Landy, M. S. (1991). Computational modeling of visual texture

segregation. *Computational Models of Visual Processing*, *17*, 253-271.

Bishop, C. (2006). *Pattern Recognition and Machine Learning.* Springer.

Breuil, C., Jennings, B. J., Barthelmé, S., Guyader, N., & Kingdom, F. A. (2019). Color improves

edge classification in human vision. *PLoS Computational Biology*, *15*(10), e1007398.

Burge, J., Fowlkes, C. C., & Banks, M. S. (2010). Natural-scene statistics predict how the figure–

ground cue of convexity affects human depth perception. *Journal of Neuroscience*, *30*(21), 7269-

7280.

Casati, R., & Cavanagh, P. (2019). *The Visual World of Shadows*. MIT Press.

Chin, B. M., & Burge, J. (2020). Predicting the partition of behavioral variability in speed

perception with naturalistic stimuli. *Journal of Neuroscience*, *40*(4), 864-879.

Chollet, F. (2021). *Deep learning with Python (2nd Ed.).* Manning.

DiMattina, C. (2022). Luminance texture boundaries and luminance step boundaries are

segmented using different mechanisms. *Vision Research*, *190*, 107968.

DiMattina, C., & Baker Jr, C. L. (2019). Modeling second-order boundary perception: A machine

learning approach. *PLoS Computational Biology*, *15*(3), e1006829.

DiMattina, C., & Baker Jr., C.L. (2021). Segmenting surface boundaries using luminance

cues. *Scientific Reports*, *11*(1), 1-15.

DiMattina, C., Fox, S. A., & Lewicki, M. S. (2012). Detecting natural occlusion boundaries using

local cues. *Journal of Vision*, *12*(13), 15-15.

Ehinger, K. A., Adams, W. J., Graf, E. W., & Elder, J. H. (2017). Local depth edge detection in

humans and deep neural networks. In *Proceedings of the IEEE International Conference on*

Computer Vision Workshops (pp. 2681-2689).

Elder, J. H. (1999). Are edges incomplete? *International Journal of Computer Vision*, *34*(2), 97-

122.

Elder, J. H., Trithart, S., Pintilie, G., & MacLean, D. (2004). Rapid processing of cast and attached

shadows. *Perception*, *33*(11), 1319-1338.

Elder, J. H., & Zucker, S. W. (1998). Local scale control for edge detection and blur

estimation. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, *20*(7), 699-716.

Ernst, M. O., & Banks, M. S. (2002). Humans integrate visual and haptic information in a

statistically optimal fashion. *Nature*, *415*(6870), 429-433.

Field, D.J. (1987). Relations between the statistics of natural images and the response properties

of cortical cells. *Journal of the Optical Society of America A 4(12)*, 2379-2394.

Goodfellow, I., Bengio, Y., & Courville, A. (2016). *Deep Learning*. MIT press.

Henry, K. S., & Abrams, K. S. (2021). Normal tone-in-noise sensitivity in trained budgerigars

despite substantial auditory-nerve injury: no evidence of hidden hearing loss. *Journal of*

Neuroscience, *41*(1), 118-129.

Ing, A. D., Wilson, J. A., & Geisler, W. S. (2010). Region grouping in natural foliage scenes:

Image statistics and human performance. *Journal of Vision*, *10*(4), 10-10.

Jiang, X., Schofield, A. J., & Wyatt, J. L. (2010). Correlation-based intrinsic image extraction from

a single image. In: *European Conference on Computer Vision* (pp. 58-71). Springer, Berlin,

Heidelberg.

Jones, P. R. (2016). A tutorial on cue combination and Signal Detection Theory: Using changes in

sensitivity to evaluate how observers integrate sensory information. *Journal of Mathematical*

Psychology, *73*, 117-139.

Kingdom, F. A. A. (2008). Perceiving light versus material. *Vision Research*, *48*(20), 2090-2105.

Kingdom, F. A. A. (2019). Colour vision helps distinguish light from material. *Current Opinion*

in Behavioral Sciences, *30*, 15-20.

Kingdom, F. A. A., Baldwin, A. S., & Schmidtmann, G. (2015). Modeling probability and additive

summation for detection across multiple mechanisms under the assumptions of signal detection

theory. *Journal of Vision*, *15*(5), 1-1.

Kovesi, P. D. (2000). MATLAB and Octave functions for computer vision and image

processing. *http://www. csse. uwa. edu. au/∼pk/research/matlabfns*

Krizhevsky, A., Sutskever, I., & Hinton, G. E. (2012). Imagenet classification with deep

convolutional neural networks. *Advances in neural information processing systems*, *25*.

Landy, M. S., & Graham, N. (2004). Visual Perception of Texture. *The Visual Neurosciences*,

1106.

Malik, J., & Perona, P. (1990). Preattentive texture discrimination with early vision

mechanisms. *Journal of the Optical Society of America A*, *7*(5), 923-932.

Mamassian, P., Knill, D. C., & Kersten, D. (1998). The perception of cast shadows. *Trends in*

Cognitive Sciences, *2*(8), 288-295.

Marr, D. C. (1982). *Vision.* MIT Press.

Martin, D. R., Fowlkes, C. C., & Malik, J. (2004). Learning to detect natural image boundaries

using local brightness, color, and texture cues. *IEEE Transactions on Pattern Analysis and*

Machine Intelligence, *26*(5), 530-549.

McDermott, J. (2004). Psychophysics with junctions in real images. *Perception*, *33*(9), 1101-1127.

McIlhagga, W. H., & May, K. A. (2012). Optimal edge filters explain human blur

detection. *Journal of Vision*, *12*(10), 9-9.

McIlhagga, W., & Mullen, K. T. (2018). Evidence for chromatic edge detectors in human vision

using classification images. *Journal of Vision*, *18*(9), 8-8.

Mély, D. A., Kim, J., McGill, M., Guo, Y., & Serre, T. (2016). A systematic comparison between

visual cues for boundary detection. *Vision Research*, *120*, 93-107.

Olmos, A., & Kingdom, F. A. (2004). A biologically inspired algorithm for the recovery of shading

and reflectance images. *Perception*, *33*(12), 1463-1473.

Parker, A. J., & Hawken, M. J. (1988). Two-dimensional spatial structure of receptive fields in

monkey striate cortex. *JOSA A*, *5*(4), 598-605.

Ramachandra, Chaithanya A., and Bartlett W. Mel. "Computing local edge probability in natural scenes from a population of oriented simple cells." *Journal of Vision* 13, no. 14 (2013): 19-19.

Ramachandran, V. S. (1988). Perception of shape from shading. *Nature*, *331*(6152), 163-166.

Ramenahalli, S., Mihalas, S., & Niebur, E. (2014). Local spectral anisotropy is a valid cue for figure–ground organization in natural scenes. *Vision Research*, *103*, 116-126.

Rensink, R. A., & Cavanagh, P. (2004). The influence of cast shadows on visual search. *Perception*, *33*(11), 1339-1358.

Rumelhart, D. E., Hinton, G. E., & Williams, R. J. (1986). Learning representations by back-propagating errors. *Nature*, *323*(6088), 533-536.

Sebastian, S., & Geisler, W. S. (2018). Decision-variable correlation. *Journal of Vision*, *18*(4), 3-3.

Sebastian, S., Seemiller, E. S., & Geisler, W. S. (2020). Local reliability weighting explains identification of partially masked objects in natural images. *Proceedings of the National Academy of Sciences*, *117*(47), 29363-29370.

Victor, J. D., Conte, M. M., & Chubb, C. F. (2017). Textures as probes of visual processing. *Annual Review of Vision Science*, *3*, 275-296.

Vilankar, K. P., Golden, J. R., Chandler, D. M., & Field, D. J. (2014). Local edge statistics provide information regarding occlusion and non-occlusion edges in natural scenes. *Journal of Vision*, *14*(9), 13-13.

Watson, A. B., & Ahumada, A. J. (2011). Blur clarified: A review and synthesis of blur discrimination. *Journal of Vision*, *11*(5), 10-10.

Wilder, J. D., Adams, W. J., & Murray, R. F. (2019). Shape from shading under inconsistent

illumination. *Journal of Vision*, *19*(6), 2-2.

Zavitz, E., & Baker, C. L. (2013). Texture sparseness, but not local phase structure, impairs

second-order segmentation. *Vision Research*, *91*, 45-55.

Zavitz, E., & Baker, C. L. (2014). Higher order image structure enables boundary segmentation in

the absence of luminance or contrast cues. *Journal of Vision*, *14*(4), 14-14.

Zhou, C., & Mel, B. W. (2008). Cue combination and color edge detection in natural

scenes. *Journal of Vision*, *8*(4), 4-4.

1033

1034

1035

1036

1037

1038

1039

1040

1041

1042

1043

1044

1045

1046

1047

1048

1049

1050

1051

FIGURE CAPTIONS

Figure 1: Images from the shadow boundary database and one occlusion database.

(**a**) *Top*: Two representative images from our shadow database (**shad**) with shadow edges labeled

by one observer. *Bottom:* Overlaid shadow boundaries obtained from all N = 4 observers.

(**b**) *Top:* Two representative images from **oset-2**, with occlusions labeled by one observer. *Bottom:*

Overlaid occlusion boundaries from all N = 4 observers.

(**c**) Representative 40x40 image patches from each image set.

Figure 2: Contrast statistics measured from shadow and occlusion edges (N = 2000 of each

category). Green curves/symbols indicate occlusions, Magenta curves/symbols indicate shadows.

(**a**) Distributions of Michelson contrast (*left*) and RMS contrast (*right*) for our shadow database

and two sets of occlusions (**oset-1**: *top*, **oset-2**: *bottom*). Note that for both occlusion sets, the

highest and lowest contrast edges are occlusions.

(**b**) Two-dimensional scatterplot of contrast measurements for shadow and occlusion edges for

both sets of occlusions. The dashed line indicates the optimal separating hyperplane learned by a

logistic regression classifier trained on a different set of observations.

(**c**) Probability distribution of stimulus power π_h in the high spatial frequency (>10 cycles/image)

range for our shadow database (magenta curves) and both occlusion sets (green curves). N = 2000

for each set of images.

(**d**) Rotational average of the amplitude spectrum for shadows (magenta curves) and both occlusion

sets (green curves).

(**e**) Scatterplots of π_h and Michelson contrast c_M for shadows (magenta symbols) and both

occlusion sets (green symbols).

(**f**) Same as (c) but for RMS contrast c_{RMS}.

Figure 3: Example occlusion and shadow edges at varying percentiles of our contrast and spatial

frequency measurements. Each image patch is within 8 ranks of the indicated percentile (out of N

= 2000 total image patches analyzed).

(**a**) Occlusion edges at varying percentiles of each contrast measure (RMS: *left*; Michelson: *center*)

and our spatial frequency measure (π_h: *right*) for both sets of occlusions (**oset-1**: *top*, **oset-2**:

bottom).

(**b**) Same as (a), but for shadow edges from our database.

Figure 4: Schematic illustration of Gabor Filter Bank (**GFB**) and Filter-Rectify-Filter (**FRF**)

classifier models.

(**a**) **GFB** model. An image patch is analyzed by a bank of 72 oriented Gabor filters covering 3

spatial scales (8, 16, 32 pixels). The rectified filter outputs are down-sampled and MAX pooled to

obtain a set of regressors $x_1, \dots, x_n$. Binomial logistic regression is performed to find a set of

weights that optimally predict the probability that the patch is an occlusion.

(**b**) **FRF** model. This model is identical to the **GFB** model, except the regressors $x_1, \dots, x_n$ are then

passed into a three-layer neural network having *K* hidden units (*gray circles*) to determine the

probability an image patch is an occlusion edge.

1091

1092

Figure 5: Occlusion and shadow edges with the 25 highest predicted of occlusion and shadow

category membership. Actual category is indicated by the row, predicted category by the column.

The upper left and lower right quadrants indicate correct classifications by the model.

(**a**) **GFB** model

(**b**) **FRF** model

Figure 6: Effects of edge blur on model predictions of edge probability.

(**a**) Test image patches with varying levels of blur.

(**b**) Gabor Filter Bank (**GFB**) model (see **Fig. 4a**).

(**c**) Same as (a) but for Filter-Rectify-Filter (**FRF)** models having varying numbers of hidden units

(**Fig 4b**).

Figure 7: Effects of removing texture information from image patches on responses of the **GFB**

and **FRF** models.

(**a**) Averaging the pixel intensities on each side of the occlusion boundary remove texture

information while leaving Michelson contrast unchanged.

(**b**) Log-odds ratio of being an occlusion for the original images (*horizontal axis*) versus the

texture-removed images (*vertical axis*). We see that images for which the model predicts a high

occlusion probability experience a drastic decrease in occlusion probability when texture is

removed. *Top:* **oset-1**, *Bottom:* **oset-2**.

1111

(**c**) Log-odds ratio of being an occlusion for the original images (horizontal axis) versus the change

in occlusion probability when texture is removed (vertical axis). *Top:* **oset-1**, *Bottom:* **oset-2**.

(**d**) Change in occlusion probability for patches correctly classified as occlusions (*Top:* **FRF**,

Bottom: **GFB**). Positive numbers indicate a decrease in occlusion probability, negative numbers

an increase in occlusion probability. *Left:* **oset-1**, *Right:* **oset-2**.

(**e**) Same as (**d**) but for patches incorrectly classified as shadows.

(**f**) Difference $D = \Delta_{FRF} - \Delta_{GFB}$ in the reduction in edge probability with texture removal for each

image. Positive values of D indicate a greater reduction in edge probability with texture removal

for the **FRF** model than the **GFB** model.

Figure 8: Psychophysical experiment results.

(**a**) Schematic outline of our psychophysical task.

(**b**) *Left:* Performance of all observers on each survey, as measured by proportion correct. Blue

dots indicate individual observers. Blue circles indicate the median, and black diamonds indicate

maximum performance. *Right:* Same as left panel, but performance measured as d-prime.

(**c**) Distribution of the SDT decision criterion (γ) for all observers and surveys.

(**d**) Distribution of the difference $P(o|S) - P(s|O)$ in classification error probabilities. $P(o|S)$

indicates the probability a shadow is mis-classified as an occlusion, and $P(s|O)$ is the probability

of an occlusion being mis-classified as a shadow.

(**e**) Distribution of the Wald statistic for the binomial proportion test testing whether there is a bias

in mis-classifications, with the null hypothesis of equal mis-classification probabilities.

(**f**) Scatter plot of classification error probabilities.

Figure 9: Human performance on individual images.

(**a**) Predicted probability of being an occlusion edge by the **AO** (*blue curve*). Image patches are

sorted by their probability. Actual category is indicated by a (+).

(**b**) Occlusion probability predicted by the **AO** for each occlusion edge (*green curve*) and each

shadow edge (*magenta curve*), sorted by occlusion probability.

Figure 10: Log-odds ratios of human observers (**AO,** horizontal axes) and **GFB**, **FRF** models

(vertical axes) for each image for all three surveys. Magenta symbols indicate image patches that

are occlusions, green symbols indicate shadows. On the margins of each scatterplot we show the

distributions of the log-odds ratios for each image category.

Figure 11: Decision-variable correlation analysis.

(**a**) DVC between models and individual observers for each experiment.

(**b**) Same as (a) but pooled across experiments.

(**c**) Histograms of differences in DVC for all possible comparisons of the three models.

1146

1147

1148

1149

1150

1151

1152

1153

1154

1155

1156

1157   **Figure 1**

1158

1159

1160   **Figure 2**

1161

1162

1163

1164

1165

1166

1167 **Figure 3**

1168

1169

1170

1171

1172

1173

1174

1175

1176

1177

1178

1179

1180
1181

1182   **Figure 4**

1183

1184

1185

1186

1187

1188

1189

1190

1191

1192

1193

1194   **Figure 5**

1195

1196

1197

1198

1199

1200

1201

1202

1203

1204

1205

1206

1207

1208

1209

1210

1211

1212   **Figure 6**

1213

1214

1215

1216

1217   **Figure 7**

1218

1219

1220

1221

1222

1223   **Figure 8**

1224

1225

1226

1227

1228

1229

1230

1231

1232

1233

1234   **Figure 9**

1235

1236

1237

1238

1239

1240

1241

1242

1243

1244

1245

1246

1247   **Figure 10**

1248

1249

1250

1251

1252   **Figure 11**

1253

1254

1255

1256

1257

1258

1259

1260

1261

1262

1263

1264

1265

1266

1267

1268

1269

1270