sstar: A Python package for detecting archaic introgression from population genetic data with $S*$

Xin Huang[1, 2, *], Patricia Kruisz[3], Martin Kuhlwilm[1, 2, *]

[1] Department of Evolutionary Anthropology, University of Vienna, Djerassiplatz 1, 1030 Vienna, Austria.

[2] Human Evolution and Archaeological Sciences (HEAS), University of Vienna, Austria.

[3] Department Bio Data Science, Faculty of Engineering, University of Applied Sciences Wiener Neustadt, Biotech Campus Tulln, Konrad Lorenz-Straße 10, 3430 Tulln, Austria.

* Corresponding authors: xin.huang@univie.ac.at; martin.kuhlwilm@univie.ac.at

Abstract

$S*$ is a widely used statistic for detecting archaic admixture from population genetic data. Previous studies used freezing-archer to apply $S*$, which is only directly applicable to the specific case of Neanderthal and Denisovan introgression in Papuans. Here, we implemented sstar for a more general purpose. Compared with several tools, including SPrime, SkovHMM, and ArchaicSeeker2.0, for detecting introgressed fragments with simulations, our results suggest that sstar is robust to differences in demographic models, including ghost introgression and two-source introgression. We believe sstar will be a useful tool for detecting introgressed fragments in various scenarios and in non-human species.

Keywords: Introgression; Archaic admixture; $S*$; Python

Admixture between populations is a topic of great interest (Fontsere et al. 2019). To detect archaic admixture from population genetic data, a statistic named $S*$ was introduced to search for patterns of variation and linkage expected in the case of introgression (Plagnol and Wall 2006). This statistic has been applied in subsequent studies in modern humans (Huerta-Sanchez et al. 2014; Vernot and Akey 2014; Vernot et al. 2016; Xu et al. 2017; Jacobs et al. 2019) as well as other organisms (Cong et al. 2016; Kuhlwilm et al. 2019). Although the $S*$ statistic is a powerful approach for detecting introgressed fragments without source genomes (Browning et al. 2018), there is no user-friendly and versatile package available. A previous

implementation of *S** is freezing-archer (Vernot and Akey 2014; Vernot et al. 2016), which

was specifically designed with human demographic models and used for detecting

introgressed fragments from Neanderthals and Denisovans into Papuans (Vernot et al. 2016).

Users must carefully read and understand the source codes of freezing-archer before manually

changing the parameters inside the code. To improve the efficiency, robustness and

reproducibility when using *S** for detecting introgression, we implemented sstar.

The whole pipeline is illustrated in Figure 1A. We define the population without introgressed

fragments as the reference population, the population which received introgressed fragments

as the target population, and the population which donated introgressed fragments as the

source population (Supplementary Figure S1). We assume genotype data are diploid, biallelic,

phased and not missing in all individuals of the dataset. We also remove variants with derived

alleles that are fixed in both the reference and target populations. Users can calculate *S** for

sliding windows across genomes by defining the length of a window and step size. To assess

significance of *S** scores, users can simulate data under a demographic model without

introgression and build up a generalized linear model with different *S** scores, quantiles of *S**,

numbers of mutations, and local recombination rates to predict the expected *S** score, as

described previously (Vernot et al. 2016). If a genome from a potential source population is

available, users can calculate the source match rate between an individual from the target

population and an individual from the source population. If genomes from two different

source populations are available, the origin of candidate introgressed fragments can be

determined by comparing the source match rates with different source populations.

We evaluated the performance of sstar by simulation with msprime 1.0 (Kelleher et al. 2016;

Baumdicker et al. 2022) in different demographies and sample sizes. Two models tested ghost

introgression: a Human-Neanderthal model (Gower et al. 2021) and a Bonobo-Ghost

introgression model (Kuhlwilm et al. 2019). Two models tested two-source introgression: a

Human-Neanderthal-Denisovan model (Malaspinas et al., 2016; Jacobs et al., 2019) and a

Chimpanzee-Ghost-Bonobo model. For ghost introgression, we compared sstar with SPrime

(Browning et al. 2018), another tool using an *S**-like approach, and SkovHMM (Skov et al.

2018), a tool based on the hidden Markov model (HMM). In the Human-Neanderthal model,

our results show that sstar performed the best among these approaches, when detecting

introgression with 10 diploid reference individuals and 1 target individual (Figure 1B and

1C). In the Bonobo-Ghost model, SPrime performed poorly (Figure 1D and 1E), assigning the

whole sequence as introgressed. In this model, sstar and SkovHMM still could detect
introgressed fragments.

One key step in sstar is calculating the expected S^* scores with simulated data from
demographic models without introgression, requiring full knowledge on the population
history (Supplementary Figure S6–S9). Using approximate history (Supplementary Figure
S10–S13), our results suggest that sstar performed similarly when compared with those using
the full history (Figure 1B–1E). For two-source introgression, we compared sstar with
SPrime, and ArchaicSeeker2.0 (Yuan et al. 2021; Zhang et al. 2022), another HMM-based
tool. In the Human-Neanderthal-Denisovan model with large datasets, SPrime performed
well, though both sstar and SPrime performed better when identifying Denisovan fragments
than identifying Neanderthal fragments (Figure 1F and 1G). This may be due to the
Denisovan introgression event in Papuans being more recent and its admixture proportion
being larger than for the Neanderthal introgression. More ancient events like in the
Chimpanzee-Ghost-Bonobo model cannot be well determined by SPrime, while sstar still
retained power (Fig. 1H and 1I).

We conclude that sstar is robust for detecting introgressed fragments. Since no single tool
could perform well for detecting introgressed fragments under different demographies and
sample sizes, we believe sstar will be useful for exploring introgression in various scenarios,
especially small samples, and non-humans.

Data availability

Source codes for sstar can be found in https://github.com/admixVIE/sstar (last accessed on
June 15, 2022) and the manual can be found in https://sstar.readthedocs.io/en/latest/ (last
accessed on June 15, 2022). Codes for replicating the benchmark can be found in
https://github.com/admixVIE/sstar-analysis (last accessed on June 15, 2022). Computational
tools installed through conda can be found in https://github.com/admixVIE/sstar-
analysis/blob/main/environment.yml (last accessed on June 15, 2022). Tools listed below
cannot be installed through conda but can be found in the websites from their authors:
ArchaicSeeker2.0 (https://github.com/Shuhua-Group/ArchaicSeeker2.0, last accessed on June
15, 2022), ms program (Hudson 2002;
https://home.uchicago.edu/~rhudson1/source/mksamples.html, last accessed on June 15,
2022), SkovHMM (https://github.com/LauritsSkov/Introgression-detection, last accessed on

June 15, 2022), SPrime (https://github.com/browning-lab/sprime, last accessed on June 15,

2022), and SPrime pipeline (Zhou and Browning 2021;

https://github.com/YingZhou001/sprimepipeline, last accessed on June 15, 2022).

Demographic models in Demes YAML format (Gower et al. 2022) can be found in

https://github.com/admixVIE/sstar-analysis/tree/main/config/simulation/models (last accessed

on June 15, 2022).

Acknowledgments

103   We thank Benjamin Vernot for discussions on freezing-archer, Andrew Kern and Peter Ralph

104   for implementing Snakemake pipelines, Graham Gower for plotting demographic models with

105   demesdraw and help from the PopSim Consortium. This project has been funded by the

106   Vienna Science and Technology Fund (WWTF) and the City of Vienna through project

107   VRG20-001.

Author contribution

110   M.K. and X.H. designed the study. X.H. implemented sstar. M.K. tested sstar. X.H., P.K. and

111   M.K. implemented the benchmark pipelines. X.H. and M.K. analysed the data and wrote the

112   manuscript.

Competing interests

115   The authors declare no conflict of interests.

References

Adrion JR, Cole CB, Dukler N, Galloway JG, Gladstein AL, Gower G, Kyriazis CC,

Ragsdale AP, Tsambos G, Baumdicker F, et al. 2020. A community-maintained standard

library of population genetic models. *eLife* **9**: e54967.

Baumdicker F, Bisschop G, Goldstein D, Gower G, Ragsdale AP, Tsambos G, Zhu S, Eldon

B, Ellerman EC, Galloway JG, et al. 2022. Efficient ancestry and mutation simulation

with msprime 1.0. *Genetics* **220**: iyab229.

Browning SR, Browning BL, Zhou Y, Tucci S, Akey JM. 2018. Analysis of human sequence data reveals two pulses of archaic Denisovan admixture. *Cell* **173**: 53–61.

Cong Q, Shen J, Warren AD, Borek D, Otwinowski Z, Grishin N V. 2016. Speciation in Cloudless Sulphurs Gleaned from Complete Genomes. *Genome Biol. Evol.* **8**: 915–931.

Fontsere C, de Manuel M, Marques-Bonet T, Kuhlwilm M. 2019. Admixture in Mammals and How to Understand Its Functional Implications. *BioEssays* **41**: 1900123.

Gower G, Picazo PI, Fumagalli M, Racimo F. 2021. Detecting adaptive introgression in human evolution using convolutional neural networks. *eLife* **10**: e64669.

Gower G, Ragsdale AP, Gutenkunst RN, Hartfield M, Noskova E, Struck TJ, Kelleher J, Thornton KR. 2022. Demes: a standard format for demographic models. *bioRxiv*. https://www.biorxiv.org/content/10.1101/2022.05.31.494112v1, last accessed on June 15, 2022.

Hudson RR. 2002. Generating samples under a Wright-Fisher neutralmodel of genetic variation. *Bioinformatics* **18**: 337–338.

Huerta-Sanchez E, Jin X, Asan, Bianba Z, Peter BM, Vinckenbosch N, Liang Y, Yi X, He M, Somel M, et al. 2014. altitude adaptation in Tibetans caused by introgression of Denisovan-like DNA. *Nature* **512**: 194–197.

Kelleher J, Etheridge AM, McVean G. 2016. Efficient coalescent simulation and genealogical analysis for large sample sizes. *PLoS Comput. Biol.* **12**: e1004842.

Jacobs GS, Hudjashov G, Saag L, Kusuma P, Darusallam CC, Lawson DJ, Mondal M, Pagani L, Ricaut F-X, Stoneking M, et al. 2019. Multiple Deeply Divergent Denisovan Ancestries in Papuans. *Cell* **177**: 1010-1021.e32.

Kuhlwilm M, Han S, Sousa VC, Excoffier L, Marques-Bonet T. 2019. Ancient admixture from an extinct ape lineage into bonobos. *Nat. Ecol. Evol.* **3**: 957–965.

Peter BM. 2020. 100,000 years of gene flow between Neandertals and Denisovans in the Altai mountains. *bioRxiv*. https://www.biorxiv.org/content/10.1101/2020.03.13.990523v1, last accessed on June 15, 2022.

Plagnol V, Wall JD. 2006. Possible Ancestral Structure in Human Populations. *PLoS Genet.* **2**: e105.

Sankararaman S, Mallick S, Dannemann M, Prufer K, Kelso J, Paabo S, Patterson N, Reich

D. 2014. The genomic landscape of Neanderthal ancestry in present-day humans. *Nature*
507: 354–357.

Skov L, Hui R, Shchur V, Hobolth A, Scally A, Schierup MH, Durbin R. 2018. Detecting
archaic introgression using an unadmixed outgroup. *PLOS Genet.* **14**: e1007641.

Vernot B, Akey JM. 2014. Resurrecting Surviving Neandertal Lineages from Modern Human
Genomes. *Science* **343**: 1017–1021.

Vernot B, Tucci S, Kelso J, Schraiber JG, Wolf AB, Gittelman RM, Dannemann M, Grote S,
McCoy RC, Norton H, et al. 2016. Excavating Neandertal and Denisovan DNA from the
genomes of Melanesian individuals. *Science* **352**: 235–239.

Wall JD, Lohmueller KE, Plagnol V. 2009. Detecting ancient admixture and estimating
demographic parameters in multiple human populations. *Mol. Biol. Evol.* **26**: 1823–1827.

Xu D, Pavlidis P, Taskent RO, Alachiotis N, Flanagan C, DeGiorgio M, Blekhman R, Ruhl S,
Gokcumen O. 2017. Archaic Hominin Introgression in Africa Contributes to Functional
Salivary MUC7 Genetic Variation. *Mol. Biol. Evol.* **34**: 2704–2715.

Yuan K, Ni X, Liu C, Pan Y, Deng L, Zhang R, Gao Y, Ge X, Liu J, Ma X, et al. 2021.
Refining models of archaic admixture in Eurasia with ArchaicSeeker 2.0. *Nat. Commun.*
12: 6232.

Zhang R, Yuan K, Xu S. 2022. Detecting archaic introgression and 6odelling multiple-wave
admixture with ArchaicSeeker 2.0. *STAR Protocols* **3**: 101314.

Zhou Y, Browning SR. 2021. Protocol for detecting introgressed archaic variants with
SPrime. *STAR Protocols* **2**: 100550.

 Figure legends

Figure 1 sstar workflow and its performance in different demographic models and

sample sizes with SPrime, SkovHMM, and ArchaicSeeker2.0. Different points represent

precision and recall estimated with different cut-offs (Supplementary Table S1–S6). Area

under the curve (AUC) for each precision-recall curve was also estimated (Supplementary

Table S7–S8). For ArchaicSeeker2.0, we only used the best results inferred from

ArchaicSeeker2.0 and did not estimate AUC for ArchaicSeeker2.0, because ArchaicSeeker2.0

does not provide options to define candidate introgressed fragments with different cut-offs.

For each demographic model, we simulated a sequence with a length of 200 Mb and

replicated 100 times, then estimated the average performance of tools across different

replicates. Nref is the diploid sample size of the reference population. Ntgt is the diploid

sample size of the target population. For sstar and SkovHMM, we only used simulated data

with 1 diploid individual from the target population, because these two tools analyse data

individual by individual. sstar (full) are results inferred with generalized linear models

(GLMs) using simulated data from full demographic models without introgression

(Supplementary Figure S6–S9). sstar (constant) are results inferred with GLMs using

simulated data from constant size models without introgression (Supplementary Figure S10

and S11). sstar (only ref & tgt) are results inferred with GLMs using simulated data from

models with only the reference and target populations, these populations are also constant

(Supplementary Figure S12 and S13). src1 represents the performance for identifying the

introgressed fragments from the source population 1. src2 represents the performance for

identifying the introgressed fragments from the source population 2. **(A)** The sstar workflow.

$S*$ scores can be estimated without source genomes. Expected $S*$ scores can be obtained from

simulated data without introgression by constructing GLMs and regions with significant $S*$

can be determined. If a source individual is available, source match rates can be estimated. If

individuals from different source populations are available, the origin of the introgressed

fragments can be determined by comparing source match rates estimated from different

source individuals. **(B)** Precision-recall curves of sstar, SPrime, and SkovHMM for detecting

introgression without source genomes under a Human-Neanderthal model (Gower et al. 2021,

Supplementary Figure S2). **(C)** AUC scores for sstar, SPrime, and SkovHMM for detecting

introgression without source genomes under a Human-Neanderthal model (Supplementary

Figure S2). **(D)** Precision-recall curves of sstar, SPrime, and SkovHMM for detecting

introgression without source genomes under a Bonobo-Ghost model (Kuhlwilm et al. 2019,

Supplementary Figure S3). **(E)** AUC scores for sstar, SPrime and SkovHMM for detecting

introgression without source genomes under a Bonobo-Ghost model (Supplementary Figure

S3). **(F)** Precision-recall curves of sstar, SPrime, and ArchaicSeeker2.0 for detecting

introgression with source genomes from two source populations under a Human-Neanderthal-

Denisovan model from stdpopsim (Adrion et al. 2020, Supplementary Figure S4). The src1

population is the Neanderthal population. The src2 population is the Denisovan population.

(G) AUC scores for sstar and SPrime for detecting introgression with source genomes from

two source populations under a Human-Neanderthal-Denisovan model (Supplementary Figure

S4). **(H)** Precision-recall curves of sstar, SPrime, and ArchaicSeeker2.0 for detecting

introgression with source genomes from two source populations under a Chimpanzee-Ghost-

Bonobo model (Supplementary Figure S5) modified from Kuhlwilm et al. (2019). The src1

population is the Ghost population, the src2 population is the Bonobo population, both

introgressing into the Central Chimpanzee population. **(I)** AUC scores for sstar and SPrime

for detecting introgression with source genomes from two source populations under a

Chimpanzee-Ghost-Bonobo model (Supplementary Figure S5).