Humans prioritize walking efficiency or walking balance based on
environmental risk

Ashwini Kulkarni[1&], Chuyi Cui[1&], Shirley Rietdyk[1&], Satyajit Ambike[1¶*]

[1]Department of Health and Kinesiology, Purdue University, West Lafayette, IN

Keywords: proactive adaptation; adaptive gait; uncontrolled manifold; obstacle crossing

Running title: Synergistic control of MOS in human locomotion

*Corresponding author

E-mail: sambike@purdue.edu (SA)

[¶]These authors contributed equally to this work.

[&]These authors contributed equally to this work.

Abstract

In human gait, the body's mechanical energy at the end of one step is reused to achieve forward progression during the subsequent step, thereby reducing the required muscle work. During the single stance phase, humans rely on the largely uncontrolled passive inverted pendular motion of the body to perpetuate forward motion. Since inverted pendula are unstable, these passive body dynamics, while improving walking efficiency, also indicate that the individual will be less able to withstand an external perturbation during the single stance phase. Here we test the novel hypothesis that humans manipulate passive anterior-posterior (AP) stability via active selection of step length to either achieve energy-efficient gait or to improve stability when balance is threatened. We computed the AP margin of stability, which quantifies the passive dynamic stability of gait, for multiple steps as healthy young adults (N=20) walked on a clear and on an obstructed walkway. Participants used passive dynamics to achieve energy-efficient gait for all but one step; when crossing the obstacle with the leading limb, AP margin of stability was increased and indicated cautious gait, reflecting the greater threat to balance arising from a potential trip. Furthermore, AP margin of stability increased while approaching the obstacle, indicating that humans employ a *proactive strategy of manipulating passive dynamics* to meet the demands of the locomotor task. Finally, the step length and the center of mass motion co-varied to maintain the AP margin of stability for all steps in both tasks at the specific values for each step. We conclude that humans actively regulate step length to maintain specific levels of passive stability for each step during unobstructed and obstructed gait.

1. Introduction

On a clear, straight path, humans reduce the energy required for walking by selecting appropriate step length [1, 2]. The selected step length ensures that the kinetic energy at the end of a step is sufficient to passively rotate the body over the new stance foot, thereby achieving forward progression at low energetic cost. That is, humans rely on the largely uncontrolled passive motion of the body during the single stance phase of gait to perpetuate forward motion. This motion during the single stance phase resembles that of an inverted pendulum, and given that passive inverted pendula are unstable, the inverted pendular phase of walking may have the property that neighboring trajectories of the body's center of mass (CoM; abbreviations in Table 1) diverge. Therefore, although the overall gait cycle is usually stable (the divergence of CoM trajectories during the inverted pendular phase is corrected during the step to step transition via foot placement and/or push-off adjustments [3]), the largely passive motion during the single stance phase suggests that individuals will be less able to resist external perturbations and may be more susceptible to falling due to disturbances encountered during this phase. Therefore, although not aggressively controlling every phase in the gait cycle improves energy efficiency, it may also increase the threat to balance.

Given the zero-sum contributions of the passive inverted pendular motion to energy efficiency and stability, humans likely modulate the passive dynamics to either enhance forward progression or prioritize balance, as the context demands. The threat to balance will be low during unobstructed, straight-line walking, and therefore, passive dynamics will be used to improve efficiency. In contrast, when a locomotor task involves a higher risk of a forward loss of balance, e.g., when risk of tripping is higher, the passive dynamics will be more stable.

Furthermore, stability changes in motor behaviors cannot occur instantaneously, but must evolve over a characteristic time determined in part by the inertia of the body [4]. Therefore, we argue that a shift along the efficiency-stability spectrum will occur over multiple steps – at least for locomotor tasks that afford the time and space for such a shift to occur. For example, while crossing a visible, stationary obstacle, gait stability is altered not only when the feet cross the obstacle (i.e., crossing steps). Rather, changes in stability will be evident in the steps leading up to the obstacle (i.e., approach steps) to facilitate the transition from

unobstructed to obstructed gait. In the approach steps, visual information about the hazard is

being gathered [5, 6] and spatio-temporal gait characteristics (gait speed and foot placement

variability) are modified [7]. However, proactive stability adaptations in the anterior-posterior

(AP) direction during approach have not been examined, and it is likely that these stability

adaptations are a critical component of maintaining forward progression through challenging

environments.

We used the margin of stability in the anterior-posterior direction (MOS_{AP}), a stability metric

derived from the inverted pendulum model of gait [8], to investigate these ideas. MOS_{AP} at heel

contact during unobstructed gait is negative [9-11] indicating energy-efficient walking. Further,

MOS_{AP} is higher while crossing an obstacle compared to unobstructed gait [12, 13], suggesting

that passive stability is improved when the risk of tripping is higher [14]. Since the step length

influences the passive stability (MOS_{AP} is a function of step length and the body's motion), we

argue that humans actively select step length to maintain MOS_{AP} in a given locomotor context.

Therefore, our primary goal was to establish that humans control passive dynamic

stability, which will be reflected in the control of MOS_{AP} during unobstructed as well as

obstructed walking. We propose and test the novel hypothesis that the central nervous system

responds to changes in the body's motion with a corresponding correction in step length so

that the MOS_{AP} itself is invariant at each heel contact. MOS_{AP} will be maintained at different

values during unobstructed vs. obstructed walking. Our second goal was to quantify any

proactive adaptations in MOS_{AP} while approaching an obstacle. MOS_{AP} at heel contact is the

distance from the anterior boundary of the base of support (the leading heel) to the

extrapolated center of mass, or XcoM, which reflects the center of mass (CoM) state [8, 15]. To

address our first goal, we employed the uncontrolled manifold (UCM) method [16]. For each

heel contact, we computed the synergy index that quantifies the co-variation in the step length

and the XcoM that maintains MOS_{AP}. A positive synergy index indicates that MOS_{AP} was actively

controlled, i.e., stabilized at the specific across-trial mean MOS_{AP} for that step. A higher value

indicates a stronger synergy or higher stability of MOS_{AP}. We emphasize that stability of MOS_{AP}

is different from the stability of gait. MOS_{AP} is the measure of gait stability. In contrast, the

synergy index indicates the efficacy of control at stabilizing or maintaining MOS_{AP} at a specific

value for a given step. To address our second goal, i.e., to identify any proactive changes in gait

stability, we compared the MOS_{AP} values for the steps leading up to, while crossing and then

resuming unobstructed gait after crossing an obstacle.

We hypothesized that the synergy index will be greater than zero, indicating that the

step length and the XcoM co-vary to stabilize MOS_{AP} for all steps in both tasks (H1). In

particular, we expect a positive synergy index for both positive and negative MOS_{AP} values (for

various steps). Next, we hypothesized a task by step interaction for the synergy index (H2). The

synergy index will not be different across tasks (unobstructed and obstructed) for the steps at

the start and end of the walkway, but the synergy index will be lower while crossing an obstacle

placed in the middle of the walkway. The lower synergy index will reflect the greater motor

demands associated with the crossing steps; larger muscle activations required for stepping

over the obstacle [17] will be associated with greater noise [18], which will make stabilization

more difficult. Finally, we hypothesized a task by step interaction for MOS_{AP} (H3). The MOS_{AP}

will not be different across tasks for the steps at the start and end of the walkway, but the

MOS_{AP} will be higher for the approach steps 1-2 steps before the obstacle and for the crossing

steps. These changes are consistent with prioritization of safety over energy optimality [13, 19,

20].

Table 1. Abbreviations.

Anterior-posterior	AP
Medial-lateral	ML
Foot placements	fp
Center of mass	CoM
Center of mass velocity	V_{CoM}
Leg length	l
Acceleration due to gravity	g
Base of support	BOS
Extrapolated center of mass	XcoM

Margin of stability in anterior-posterior direction	MOS_{AP}
Uncontrolled manifold	UCM
Orthogonal manifold	ORT
Synergy index	ΔV
Synergy index z transformed	ΔV_Z
Variance along the uncontrolled manifold	V_{UCM}
Variance along the orthogonal manifold	V_{ORT}

2. Materials and Methods

2.1 Participants

Twenty-six healthy young adults participated in the study. We excluded six participants due to

poor kinematic tracking. Data from 20 participants (14 females, 22.3 ± 3.7 years, 1.7 ± 0.1 m,

66.9 ± 14.6 kg) were used for analysis. All participants walked without aid, had no orthopedic,

neuromuscular, or dementia disorders, and were independent in daily activities. Vision was

normal or corrected-to-normal. The study was approved by the University's Institutional Review

Board, and all participants provided written informed consent.

2.2 Equipment and Procedures

Participants walked at their self-selected speed on a 6.0 m walkway and stepped over an

obstacle when present (Fig. 1A). The obstacle was 100 cm wide × 0.4 cm deep. The height of

the obstacle was scaled to 25% of the participant's leg length. The obstacle was made of black

Masonite and designed to tip if contacted. The starting position was determined for each

participant such that they took five steps before reaching the obstacle, crossed the obstacle

with the right leg first and stopped three to four steps later (Fig. 1A).

Participants performed 20 trials each of walking with an obstacle (obstacle-crossing

task) and walking without an obstacle (no obstacle task). We collected kinematic data at 100 Hz

with a motion capture system (Vicon Vero, Oxford, UK) with marker clusters placed bilaterally

on the lower back, thigh, shank, and foot. We digitized the joint centers and posterior aspect of

the heels to identify their locations relative to the marker clusters. We also digitized the top

edge of the obstacle to identify its position.

136
Figure 1. Experimental task and basic definitions. Illustration of foot placements while
approaching (fp$_{-4}$ to fp$_{-1}$), crossing (fp$_{+1}$ and fp$_{+2}$) and after crossing (fp$_{+3}$) the obstacle, and of
steps while approaching (Step$_{-3}$ to Step$_{-1}$), crossing (Step$_0$ and Step$_{+1}$) and after crossing (Step$_{+2}$)
the obstacle **(A)**. Definitions of the extrapolated center of mass (XcoM) and margin of stability,
MOS$_{AP}$. Step length, XcoM and MOS$_{AP}$ are computed at the moment of lead heel contact in a
coordinate frame located where the rear heel contacted the ground **(B)**.

2.3 Analysis

Some trials were discarded due to poor kinematic tracking. To have the same number of trials for all participants and tasks, we selected 15 trials with good kinematic data. Fifteen trials are sufficient for reliable quantification of the synergy variables [21]. We filtered all kinematic data using a zero-lag, 4th order, low-pass Butterworth filter with a cut-off of 7 Hz. We identified seven foot placements (Fig. 1A) using the AP position of the heel [22]. We quantified spatiotemporal gait parameters and margin of stability at heel contact at the seven foot placements (fp_{-4} to fp_{+3}) and six steps ($Step_{-3}$ to $Step_{+2}$; Fig. 1A). Step length was defined as the distance between two consecutive heel contacts. CoM position was computed as the centroid of the triangle formed by the left and right anterior superior iliac spines and the center of the left and right posterior superior iliac spines [23]. CoM velocity was obtained by differentiating the CoM position data. The extrapolated center of mass (XcoM) was calculated in the sagittal plane as [15]:

$$XcoM = CoM + \frac{V_{CoM}}{\sqrt{\frac{g}{l}}},$$

where CoM is the anterior-posterior CoM position, V_{CoM} is the anterior-posterior CoM velocity, g is the acceleration due to gravity, and l is the participant's leg length (Fig. 1B). Leg length was calculated as the sagittal-plane distance between the CoM and the ankle of the limb that contacted the ground. We used the average of the leg length values obtained from the 15 trials for each step [24]. We computed MOS_{AP} at the instant of leading heel contact in a coordinate frame fixed at the location of the rear heel contact (Fig. 1B):

$$MOS_{AP} = Step\ length - XcoM, \qquad (1)$$

i.e., the distance from the anterior boundary of the base of support (BOS), defined by the position of the leading heel, to the XcoM. Negative MOS_{AP} (XcoM ahead of the anterior boundary of the BOS) indicates that the body possesses sufficient energy to passively rotate over the upright position and fall forward. This is interpreted as instantaneous passive instability in the gait. In contrast, positive MOS_{AP} values (XcoM is behind the anterior boundary of the BOS) indicate that the body does not possess sufficient energy to rotate beyond the

upright position, and it will eventually fall backward. This is interpreted as instantaneous

passive stability, presumably because the rear leg can arrest a backward fall.

We used the uncontrolled manifold (UCM) analysis to quantify the synergy stabilizing

MOS_{AP} at heel contact. A *synergy* is co-variation in a redundant sets of input body variables that

maintains important output variables that define task performance. The UCM method has been

widely used to quantify the synergistic covariation in body variables in a variety of human

movements including gait ([25, 26]; see [27, 28] for recent reviews). Importantly, in addition to

identifying task-specific covariation, the UCM method identifies the salient task variables

controlled by the nervous system.

Here, we use the UCM method to evaluate the hypothesis that the input variables – step

length and XcoM, co-vary to stabilize the output variable, i.e., MOS_{AP}. We performed the

analysis separately for each step for both tasks. We first obtain from the constraint equation

(Eqn. 1), the Jacobian matrix that relates small changes in the step length and XcoM to changes

in MOS_{AP}: J = [1   -1]. The one-dimensional null space of this Jacobian defines the UCM, and its

one-dimensional compliment defines the orthogonal (ORT) manifold. We pool the across-trial

step length and XcoM data for a particular step. The deviation in the step length and XcoM data

for each trial from the across-trial mean is projected onto the UCM and the ORT manifolds. The

variances in these projections are the V_{UCM} and the V_{ORT}, respectively. These variance

components yield the synergy index:

190
$$\Delta V = \frac{V_{UCM} - V_{ORT}}{\left(\frac{V_{UCM} + V_{ORT}}{2}\right)}.$$

The synergy index ΔV has a threshold value of zero. When $\Delta V > 0$, $V_{UCM} > V_{ORT}$. In general, this

implies that the control is organized so that most of the variability in the inputs is channeled

along the UCM, and therefore, it does not alter task performance, i.e., the output. Here, $\Delta V > 0$

implies that the step length and XcoM covary to stabilize MOS_{AP}, and we conclude that MOS_{AP} is

a controlled variable. Conversely, when $\Delta V < 0$, $V_{UCM} < V_{ORT}$. This implies that most of the

variability in the inputs alters task performance. Finally, $\Delta V = 0$ indicates that there is no task-

specific co-variation in the step length and XcoM. Here, $\Delta V \leq 0$ indicates that MOS_{AP} is not a

controlled variable.

The synergy index ΔV ranges from -2 to 2. Therefore, it was z-transformed for statistical

analysis [26, 29]:

201
$$\Delta Vz = \frac{1}{2} * \log\left[\frac{2 + \Delta V}{2 - \Delta V}\right].$$

202   Note that $\Delta V = 0$ translates to $\Delta Vz = 0$. We report ΔVz values in the Results section and use ΔVz

203   values to draw inferences, consistent with most previous studies [27].

2.4 Statistical analysis

To determine whether the synergies were present, we performed separate, one-sample t-tests

to test if ΔVz was significantly different from zero for each step in the two tasks (H1). To

determine whether the gait task and foot placement affected the synergy index (H2) and MOS_{AP}

(H3), we performed a two-way (task × step) repeated measures ANOVA on these variables. To

identify the source of changes in the synergy index and in MOS_{AP}, we performed the same

ANOVA separately on the variance components (V_{UCM}, V_{ORT}), and on the CoM position, CoM

velocity at heel contact and step length, respectively. For all ANOVA tests, we fit a generalized

linear model with nested random effects. For the ANOVA on UCM variables and step length, the

participant was the random effect. For all other variables, the trial number within each

participant was the random effect. Tukey-Kramer adjustments were used to perform the

following planned pairwise comparisons: (1) across-task comparison at each of the six steps (or

seven foot placements), and (2) all across-step (or foot placement) comparisons for the

obstacle-crossing task only. All analyses were performed using the PROC GLIMMIX procedure in

SAS 9.4 (Cary, NC, USA) with significance set at 0.05.

3. Results

Figure 2 shows data from one participant and represents the overall results. The figure

illustrates (1) the changes in various outcome variables while approaching, crossing, and

resuming gait after crossing an obstacle, and (2) how the variables compare with unobstructed

gait for each step. All outcome variables showed a task × step interaction (supporting H2 and

H3) indicating that the pattern of changes in the variables across steps was different for the

obstacle-crossing task compared to the no obstacle task. The largest across-task changes were

observed in all outcomes for the two crossing steps ($Step_0$ and $Step_{+1}$), and across-task changes

were apparent in some outcomes in the approach to the obstacle ($Step_{-3}$ to $Step_{-1}$). All variables

showed across-step changes for the obstacle-crossing task. The synergy index was greater than

zero, indicating that the step length and the XcoM co-varied to stabilize MOS_{AP} for all steps in

both tasks (supporting H1). In the detailed results below, we first present the results for the

UCM outcome variables describing the stability of MOS_{AP}. Then we present the results for

MOS_{AP}, followed by results for the variables that constitute MOS_{AP}: CoM position relative to

front heel, CoM velocity at heel contact, and step length.

Figure 2. Representative data from one participant. Figure illustrates changes in various
outcomes while approaching and crossing an obstacle, and then resuming unobstructed gait
(blue ellipses). Steps during unobstructed gait are included for comparison (red ellipses). The
45° line separates the regions of positive and negative MOS_{AP}; the white region above the line
represents passively unstable behavior, and the gray region below the line represents passively
stable behavior. The 45° line also represents the direction of the uncontrolled manifold (UCM).
Variations in step length and XcoM along this direction do not change MOS_{AP}. The ellipses are
centered at the centroid of the across-trial data for each step, and the major axes are aligned
with the 45° line. However, the flatness of the ellipses is representative. Changes in mean
values of the MOS_{AP} are reflected in the position of the ellipses in each chart. The flatness of
the ellipse reflects the synergy index, with flatter ellipses indicating higher synergy indices that
reflect stronger covariation between the step length and XcoM.

3.1 UCM variables

Synergy index

The synergy index (ΔVz) was significantly greater than zero at all steps for both tasks (t_{19} < 15.97, $p < 0.01$; Fig. 3A).

There was a task × step interaction for the synergy index ΔVz ($F_{5,209}$ = 2.89, p = 0.015; η_p^2 = 0.3; Fig. 3A). Post-hoc comparisons across tasks revealed that ΔVz was lower during the obstacle-crossing task compared to the no obstacle task for the lead ($step_0$) and trail crossing steps ($step_{+1}$). Post-hoc comparisons across steps for the obstacle-crossing task revealed that ΔVz was lower at the lead crossing step ($step_0$) compared to all non-crossing steps except $step_{-2}$, and ΔVz was lower at the trail crossing step ($step_{+1}$) compared to the last step ($step_{+2}$).

Variance components

There was a task × step interaction for V_{UCM} ($F_{5,209}$ = 3.12, p = 0.009; η_p^2 = 0.3; Fig. 3B). Post-hoc comparisons across tasks revealed that V_{UCM} was higher for the obstacle-crossing task compared to the no obstacle task at all but the first two steps ($step_{-3}$ and $step_{-2}$). Post-hoc comparisons across steps for the obstacle-crossing task revealed that V_{UCM} was higher at the lead crossing step ($step_0$) compared to the first two steps ($step_{-3}$ and $step_{-2}$).

There was a task × step interaction for V_{ORT} ($F_{5,209}$ = 16.51, $p < 0.001$; η_p^2 = 0.3; Fig. 3C). Post-hoc comparisons across task revealed that V_{ORT} was higher during the obstacle-crossing task compared to the no obstacle task at the lead ($step_0$) and trail ($step_{+1}$) crossing steps. Post-hoc comparisons across steps for the obstacle-crossing task revealed that V_{ORT} was higher at the lead crossing step ($step_0$) compared to all other steps, and V_{ORT} was higher at the trail crossing step ($step_{+1}$) compared to all steps except the lead crossing step (lower for $step_{+1}$ compared to $step_0$) and the preceding step ($step_{-1}$; no significant difference).

Figure 3. Outcomes of the synergy analysis. Synergy index **(A)**, V_{UCM} **(B)**, and V_{ORT} **(C)**. Data are
across-subject means (N=20), and error bars denote standard error. Asterisks denote significant
across-task differences at that step (p < 0.05). Across-step pairwise comparisons for the
obstacle-crossing task are indicated by the row of letters above the horizontal axis for each
panel. Steps that do not have letters in common are significantly different from each other (i.e.,
A is different from B, but A is not different from AB).

3.2 Margin of stability

MOS$_{AP}$

We observed a task × step interaction for MOS$_{AP}$ ($F_{6,4167}$ = 886.89, p < 0.001; η_p^2 = 0.9; Fig. 4A). Post-hoc comparisons across tasks revealed that MOS$_{AP}$ was higher (more stable) for the obstacle-crossing task than the no obstacle task at all except the first (fp$_{-4}$) and last two foot placements (fp$_{+2}$ and fp$_{+3}$). MOS$_{AP}$ was more negative (less stable) for fp$_{+2}$ (after trail foot crossing) for the obstacle-crossing task. All pair-wise across-step comparisons for the obstacle-crossing task are depicted in Fig. 4A. For brevity, we describe only some of the significant differences. Changes in MOS$_{AP}$ occurred before the obstacle was reached; MOS$_{AP}$ was higher (less stable) for fp$_{-1}$ relative to the two preceding foot placements. For the two crossing steps, MOS$_{AP}$ first changed from negative to positive for fp$_{+1}$, and then changed to the most negative value for fp$_{+2}$ relative to all foot placements.

CoM position relative to the rear heel

A task × step interaction was observed for the CoM position relative to the rear heel ($F_{6,4167}$ = 391.20, p < 0.001; η_p^2 = 0.9; Fig. 4B). Post-hoc comparisons across tasks revealed that CoM was closer to the rear heel at the foot placements of all approach steps and the lead crossing step (fp$_{-4}$ to fp$_{+1}$) for the obstacle-crossing task than the no obstacle task. Conversely, CoM was closer to the front heel at the foot placement for the trail crossing step (fp$_{+2}$) for the obstacle-crossing task. All pair-wise across-step comparisons for the obstacle-crossing task are depicted in Fig. 4B. For brevity, we describe only some of the significant differences. CoM position changed for the last three foot placements. The CoM was closer to the rear foot at the foot placement for the lead crossing step (fp$_{+1}$). It shifted forward, so that it was closer to the front heel at the foot placement for the trail crossing step (fp$_{+2}$). Finally, for the last step (fp$_{+3}$), CoM position was consistent with that for the approach steps.

CoM velocity at heel contact

We observed a task $\times$ step interaction for the CoM velocity at heel contact ($F_{6,4167}=$

161.52, $p < 0.001$; $\eta_p^2 = 0.8$; Fig. 4C). Post-hoc comparisons across tasks revealed that the CoM

velocity was lower for the obstacle-crossing task compared to the no obstacle task at all but the

first and the last foot placements (fp_{-4} and fp_{+3}). Post-hoc comparisons across steps for the

obstacle-crossing task revealed that the CoM velocity was lower at the first (fp_{-4}) and last (fp_{+3})

foot placement compared to other foot placements, except at the lead foot crossing (fp_{+1}),

where the CoM velocity was lower compared to all other foot placements.

Step length

We observed a task $\times$ step interaction for the step length ($F_{5,3569} = 149.09$; $p < 0.001$; η_p^2

$= 0.9$; Fig. 4D). Post-hoc comparisons across tasks revealed that step length was longer during

the obstacle-crossing task compared to the no obstacle task at the lead ($step_0$) and trail crossing

($step_{+1}$) steps. Post-hoc comparisons across steps for the obstacle-crossing task revealed that

step length increased one step before the crossing step ($step_{-1}$) compared to the first step ($step_{-3}$). Step length was highest for the lead crossing step ($step_0$), and then it shortened for the trail

$_3$). Step length was highest for the lead crossing step ($step_0$), and then it shortened for the trail

crossing step ($step_{+1}$), but remained longer than all steps except $step_0$. Finally, step length was

the shortest for the last step ($step_{+2}$) compared to all other steps.

Figure 4. MOS$_{AP}$ and its components. MOS$_{AP}$ **(A)**, CoM position at heel contact **(B)**, CoM velocity at heel contact **(C)** and step length **(D)**. Data are across-subject means (N=20), and error bars denote standard error. Asterisks denote significant task difference at that step (p < 0.05). Across-step pairwise comparisons for the obstacle-crossing task are indicated by the row of letters above the horizontal axis for each panel. Steps that do not have letters in common are significantly different from each other (i.e., A is different from B, but A is not different from AB).

4. Discussion

Our goals were to establish that MOS_{AP} is actively controlled during unobstructed as well as obstructed walking, and to quantify any proactive adaptations in MOS_{AP} during obstacle crossing. We report the novel finding that the central nervous system responds to changes in the body's motion with a corresponding correction in step length so that the MOS_{AP} itself is invariant at each heel contact (supporting H1). We also observed that the synergy index was lower while crossing an obstacle compared to earlier and later steps and compared to the corresponding steps during unobstructed gait (supporting H2). Finally, we observed proactive changes in MOS_{AP} in anticipation of a threat to balance; MOS_{AP} changed across steps for unobstructed versus obstructed gait (supporting H3). We argue below that (1) the positive synergy indices indicate that the passive stability is not a byproduct of another process, but that the step length is actively controlled to exploit the passive dynamics to achieve forward progression at low energetic cost; and (2) the proactive changes in the mean MOS_{AP} for the obstacle-crossing task reflect a stability-efficiency tradeoff. Because the MOS_{AP} quantifies the passive dynamic stability of gait, our results indicate that humans employ a *passive dynamics manipulation strategy* to exploit the passive AP body motion to meet specific ends dictated by the locomotor task.

4.1 Active control of MOS_{AP} during unobstructed and obstructed gait

The synergy index provides evidence for the control of MOS_{AP}

The first major finding of this study is that MOS_{AP} is a controlled variable for obstructed as well as unobstructed gait ($\Delta Vz > 0$ for all steps; Fig. 3A). In particular, the synergy index remains significantly larger than zero, even though the input variables that define the MOS_{AP} change over multiple steps for the obstacle-crossing task (Figs 2 and 4), and even when the gait is passively unstable ($MOS_{AP} < 0$ for all but one step in our data). Thus, the UCM analysis provides strong quantitative evidence that MOS_{AP} is controlled.

The variance components (Figs 3B, 3C) provide information regarding the underlying processes that stabilize MOS_{AP}. Higher V_{ORT} indicates higher variability in MOS_{AP}, whereas

higher V_{UCM} indicates greater compensatory covariance between XcoM and step length. We

observed that MOS_{AP} is more variable for the crossing steps (up to 205% increase in V_{ORT}

compared to earlier steps; Fig. 3C). This likely arises from the larger muscle activations and joint

moments required for the crossing steps compared to unobstructed steps [17, 30]. Higher

activations would increase signal-dependent noise [18], which will lead to more variable MOS_{AP}.

However, this increase is offset by an increase in V_{UCM} (up to 103% increase compared to earlier

steps; Fig. 3B). This compensation leads to MOS_{AP} stabilization overall (Fig. 3A).

Does the synergy arise from passive mechanics, or do neural mechanisms indicate active control?

It is unlikely that passive mechanics of the gait cycle alone can explain the positive

synergy indices that we observed. It is indeed likely that mechanics contribute; for example, a

greater push off force would result in a more anterior XcoM at the next heel contact, but it

would also tend to produce longer steps [2], thereby helping to maintain MOS_{AP}. However, the

step length is not entirely determined by a passively swinging leg. Rather, activity in the leg

muscles and power at the hip and knee joints indicate active control of the forward swinging

limb, which will alter the step length from what a passively swinging limb would yield [31]. It is

plausible that variations in muscle lengths from their reference values, arising from variations in

push off forces, will engage spinal stretch reflexes that will alter step length and contribute to

the observed MOS_{AP} synergy [32]. This explanation is consistent with the view that for steady

state, level gait, humans rely on spinal feedback for control in the AP direction [33, 34].

The contribution of neural mechanisms to the MOS_{AP} synergy may be even greater for

obstructed gait. We observed large fluctuations in the MOS_{AP} over the approach and crossing

steps (174% increase for fp_{+1} over fp_{-1}, and a 292% decline for fp_{+2} over fp_{+1}; Fig. 4A).

Nevertheless, the synergy index, although lower (38% decline for $Step_0$ relative $Step_{-1}$; Fig. 3A),

remained positive. The positive synergy index despite large fluctuations in related variables

over consecutive steps suggests the involvement of supraspinal mechanisms. Indeed,

supraspinal centers are involved in the control of the obstacle crossing steps [17]. Spinal reflex

responses in the stance leg flexors are enhanced, likely due to increased activity in the

prefrontal cortex, in preparation for swinging the leg over the obstacle. Furthermore, the

prefrontal cortical activity remains enhanced (compared to unobstructed walking) while

swinging the leg over the obstacle [17]. It is also known that visual information about the

obstacle is gathered during approach and used to alter gait characteristics [5, 6]. Gathering and

using visual information also implicates higher brain centers in the control of obstructed gait,

supporting our view that the MOS_{AP} synergy arises from spinal and supraspinal neural circuits.

We note both spinal and supraspinal structures are frequently mentioned as candidate

neurophysiological bases of synergies [35], although the specific mechanisms are unknown.

Our ideas parallel a similar proposal by Dingwell and colleagues. They investigated step-

to-step changes in the MOS in the medio-lateral (ML) direction in externally destabilized

environments and argued that MOS_{ML} is controlled during level walking [24, 36, 37]. The focus

of previous research on ML stability – versus AP stability – is consistent with the view that level

gait requires more control along the ML direction, and minimal control along the AP direction

[33]. The UCM analyses performed here show that the MOS is also controlled in the AP

direction by regulating step length – not only in gait tasks that require proactive adaptations,

but also during unobstructed gait.

4.2 Proactive changes in MOS_{AP} and the compromise between

stability and energy efficiency

The second major finding of this study is that the MOS_{AP} changes while approaching the

obstacle. When compared to unobstructed gait, greater stability was apparent three steps

before the obstacle (Fig. 4A). Changes in MOS_{AP} during approach and crossing resulted from

reduced speed, a more posterior CoM, and increased step length for some steps (Figs. 4B, 4C,

4D). Previous work has demonstrated that changes in MOS_{AP} and MOS_{ML} were evident during

the swing phase immediately prior to taking unnaturally long or quick steps [38], and in MOS_{ML}

one step before reaching the obstacle [39]. Here we extend this finding and demonstrate that

MOS_{AP} changes several steps before reaching the obstacle, indicating that the transition from

unobstructed to obstructed gait occurs over several steps.

Our findings extend the argument that passive dynamic stability is modulated in

response to perceived risk [14, 20]. For example, the substantive increase in MOS_{AP} for the lead

crossing step (Figs. 2, 4A) reflects cautious gait and may be a preemptive strategy against a

potential trip that will lead to a forward fall [40]. Similarly, the even-more-substantive

transition back to the least stable passive dynamics (lowest MOS_{AP}; Fig. 4A) following the trail

crossing step may reflect the reduced risk of a forward fall after the trail foot has crossed the

obstacle, and the exploitation of passive dynamics to propel the body forward to regain gait

speed.

These fluctuations in passive dynamic stability increase the energetic cost of

locomotion. The increase in MOS_{AP} over approach steps, and especially the positive MOS_{AP} for

the crossing step, indicates that the trailing leg must push off more so that the body can rotate

about and beyond the stance ankle. Furthermore, the lead crossing step ($step_0$) is a slower and

longer step (Figs 3C, 3D), which is inconsistent with the typical combination of a slower and

shorter step during unobstructed gait which reduces energetic cost [1, 41]. Therefore, our

results reflect a tradeoff between stability and energy efficiency, consistent with similar

arguments offered in the context of stair descent [20], and model-based optimization

computations of obstacle crossing behaviors [19].

In sum, inspecting changes in MOS_{AP} across tasks and steps leads to the conclusion that

MOS_{AP} is proactively adjusted (1) during the approach, likely to facilitate the transition from

unobstructed gait to the movements required to clear the obstacle, (2) while crossing an

obstacle, likely to prioritize safety over energy optimality, and (3) when resuming level gait to

regain gait speed. The large fluctuations in MOS_{AP} reflect a tradeoff between stability and

energy efficiency.

437 **4.3 Limitations**

We estimated the CoM location using four pelvis markers [23]. A rigorous whole-body

model could have provided slightly different estimates of the CoM motion. However, these

differences would influence MOS_{AP} similarly across all conditions, and using a different method

to obtain CoM kinematics would likely yield similar qualitative results and overall conclusions,

especially given the large effect sizes for all our outcome variables. We also observed effects of

gait initiation and termination in our data. Gait was initiated one step before the examined

steps, and gait was terminated one or two steps after the trail crossing step. Using a longer

walkway – with more steps before and after the obstacle – may alter the values of our outcome

variables. We do not expect that these changes will influence our key conclusions (control of

and proactive changes in MOS_{AP}). However, effects of gait initiation and termination on MOS_{AP}

behavior may be worth an independent investigation.

450   5. Conclusion

We demonstrated that the XcoM and the step length covary to maintain MOS_{AP}, indicating that

MOS_{AP} is controlled during unobstructed and obstructed gait. In conjunction with the

consistently negative MOS_{AP} values for most of the analyzed steps, we conclude that the MOS_{AP}

is controlled to exploit the passive dynamics and achieve forward progression at low energetic

cost. Furthermore, the value of MOS_{AP} is proactively altered while approaching an obstacle, and

MOS_{AP} shows substantial fluctuations for the two crossing steps. These changes reflect a

tradeoff between stability and energy efficiency. The changes during approach and lead

crossing steps indicate increasingly cautious gait with a growing preference for stability,

whereas the opposite change after the trail crossing step indicates a reversion to improving

efficiency when the risk to balance is reduced. Thus, our results indicate that humans employ a

passive dynamics manipulation strategy to exploit the passive AP body motion to meet specific

ends dictated by the locomotor task. We conclude that the UCM analysis of MOS_{AP} provides

new information regarding the control of balance during walking, especially for gait tasks

requiring proactive adaptations, and our methods could be valuable in understanding the

effects of age and pathology on gait.

References

1.   Kuo AD, Donelan JM, Ruina A. Energetic consequences of walking like an inverted pendulum:
step-to-step transitions. Exerc Sport Sci Rev. 2005;33(2):88-97. Epub 2005/04/12. doi:
10.1097/00003677-200504000-00006. PubMed PMID: 15821430.
2.   Kuo AD, Donelan JM. Dynamic principles of gait and their clinical implications. Phys Ther.
2010;90(2):157-174. Epub 2009/12/22. doi: 10.2522/ptj.20090125. PubMed PMID: 20023002; PubMed
Central PMCID: PMCPMC2816028.
3.   Joshi V, Srinivasan M. A controller for walking derived from how humans recover from
perturbations. J R Soc Interface. 2019;16(157):20190027. Epub 2019/08/15. doi: 10.1098/rsif.2019.0027.
PubMed PMID: 31409232; PubMed Central PMCID: PMCPMC6731497.
4.   Tillman M, Ambike S. The Influence of Recent Actions and Anticipated Actions on the Stability of
Finger Forces During a Tracking Task. Motor Control. 2020;24(3):365-382. Epub 2020/07/15. doi:
10.1123/mc.2019-0124. PubMed PMID: 32663389.
5.   Diaz GJ, Parade MS, Barton SL, Fajen BR. The pickup of visual information about size and location
during approach to an obstacle. PLoS One. 2018;13(2):e0192044. Epub 2018/02/06. doi:
10.1371/journal.pone.0192044. PubMed PMID: 29401511; PubMed Central PMCID: PMCPMC5798835.
6.   Patla AE, Vickers JN. Where and when do we look as we approach and step over an obstacle in
the travel path? Neuroreport. 1997;8(17):3661-3665. Epub 1998/01/14. doi: 10.1097/00001756-
199712010-00002. PubMed PMID: 9427347.
7.   Muir BC, Haddad JM, van Emmerik REA, Rietdyk S. Changes in the control of obstacle crossing in
middle age become evident as gait task difficulty increases. Gait Posture. 2019;70:254-259. Epub
2019/03/26. doi: 10.1016/j.gaitpost.2019.01.035. PubMed PMID: 30909004.
8.   Hof AL. The 'extrapolated center of mass' concept suggests a simple control of balance in
walking. Hum Mov Sci. 2008;27(1):112-125. Epub 2007/10/16. doi: 10.1016/j.humov.2007.08.003.
PubMed PMID: 17935808.
9.   Ohtsu H, Yoshida S, Minamisawa T, Katagiri N, Yamaguchi T, Takahashi T, et al. Does the balance
strategy during walking in elderly persons show an association with fall risk assessment? J Biomech.
2020;103:109657. Epub 2020/02/10. doi: 10.1016/j.jbiomech.2020.109657. PubMed PMID: 32035661.
10.   Ohtsu H, Yoshida S, Minamisawa T, Takahashi T, Yomogida SI, Kanzaki H. Investigation of balance
strategy over gait cycle based on margin of stability. J Biomech. 2019;95:109319. Epub 2019/08/31. doi:
10.1016/j.jbiomech.2019.109319. PubMed PMID: 31466715.
11.   Bruijn SM, Meijer OG, Beek PJ, van Dieen JH. Assessing the stability of human locomotion: a
review of current measures. J R Soc Interface. 2013;10(83):20120999. Epub 2013/03/22. doi:
10.1098/rsif.2012.0999. PubMed PMID: 23516062; PubMed Central PMCID: PMCPMC3645408.
12.   Raffegeau TE, Brinkerhoff SA, Kellaher GK, Baudendistel S, Terza MJ, Roper JA, et al. Changes to
margins of stability from walking to obstacle crossing in older adults while walking fast and with a dual-
task. Exp Gerontol. 2022;161:111710. Epub 2022/01/30. doi: 10.1016/j.exger.2022.111710. PubMed
PMID: 35090973.
13.   Hak L, Hettinga FJ, Duffy KR, Jackson J, Sandercock GRH, Taylor MJD. The concept of margins of
stability can be used to better understand a change in obstacle crossing strategy with an increase in age.
J Biomech. 2019;84:147-152. Epub 2019/01/16. doi: 10.1016/j.jbiomech.2018.12.037. PubMed PMID:
30642664.
14.   Hak L, Houdijk H, Beek PJ, van Dieen JH. Steps to take to enhance gait stability: the effect of
stride frequency, stride length, and walking speed on local dynamic stability and margins of stability.
PLoS One. 2013;8(12):e82842. Epub 2013/12/19. doi: 10.1371/journal.pone.0082842. PubMed PMID:
24349379; PubMed Central PMCID: PMCPMC3862734.

15.   Hof AL, Gazendam MG, Sinke WE. The condition for dynamic stability. J Biomech. 2005;38(1):1-
8. Epub 2004/11/03. doi: 10.1016/j.jbiomech.2004.03.025. PubMed PMID: 15519333.
16.   Scholz JP, Schoner G. The uncontrolled manifold concept: identifying control variables for a
functional task. Exp Brain Res. 1999;126(3):289-306. PubMed PMID: 10382616.
17.   Haefeli J, Vogeli S, Michel J, Dietz V. Preparation and performance of obstacle steps: interaction
between brain and spinal neuronal activity. Eur J Neurosci. 2011;33(2):338-348. Epub 2010/11/13. doi:
10.1111/j.1460-9568.2010.07494.x. PubMed PMID: 21070395.
18.   Harris CM, Wolpert DM. Signal-dependent noise determines motor planning. Nature.
1998;394(6695):780-784. Epub 1998/09/02. doi: 10.1038/29528. PubMed PMID: 9723616.
19.   Chou LS, Draganich LF, Song SM. Minimum energy trajectories of the swing ankle when stepping
over obstacles of different heights. J Biomech. 1997;30(2):115-120. Epub 1997/02/01. doi:
10.1016/s0021-9290(96)00111-x. PubMed PMID: 9001931.
20.   Bosse I, Oberlander KD, Savelberg HH, Meijer K, Bruggemann GP, Karamanidis K. Dynamic
stability control in younger and older adults during stair descent. Hum Mov Sci. 2012;31(6):1560-1570.
Epub 2012/08/03. doi: 10.1016/j.humov.2012.05.003. PubMed PMID: 22853941.
21.   Rosenblatt NJ, Hurt CP. Recommendation for the minimum number of steps to analyze when
performing the uncontrolled manifold analysis on walking data. J Biomech. 2019;85:218-223. Epub
2019/02/06. doi: 10.1016/j.jbiomech.2019.01.018. PubMed PMID: 30718066; PubMed Central PMCID:
PMCPMC6905614.
22.   Desailly E, Daniel Y, Sardain P, Lacouture P. Foot contact event detection using kinematic data in
cerebral palsy children and normal adults gait. Gait Posture. 2009;29(1):76-80. Epub 2008/08/05. doi:
10.1016/j.gaitpost.2008.06.009. PubMed PMID: 18676147.
23.   Whittle MW. Three-dimensional motion of the center of gravity of the body during walking.
Hum Movement Sci. 1997;16(2-3):347-355. doi: Doi 10.1016/S0167-9457(96)00052-8. PubMed PMID:
WOS:A1997WV17500014.
24.   McAndrew Young PM, Wilken JM, Dingwell JB. Dynamic margins of stability during human
walking in destabilizing environments. J Biomech. 2012;45(6):1053-1059. Epub 2012/02/14. doi:
10.1016/j.jbiomech.2011.12.027. PubMed PMID: 22326059; PubMed Central PMCID: PMCPMC3321251.
25.   Cui C, Kulkarni A, Rietdyk S, Barbieri FA, Ambike S. Synergies in the ground reaction forces and
moments during double support in curb negotiation in young and older adults. J Biomech.
2020;106:109837. Epub 2020/06/11. doi: 10.1016/j.jbiomech.2020.109837. PubMed PMID: 32517974.
26.   Kulkarni A, Cho H, Rietdyk S, Ambike S. Step length synergy is weaker in older adults during
obstacle crossing. J Biomech. 2021;118:110311. Epub 2021/02/19. doi:
10.1016/j.jbiomech.2021.110311. PubMed PMID: 33601182.
27.   Vaz DV, Pinto VA, Junior RRS, Mattos DJS, Mitra S. Coordination in adults with neurological
impairment - A systematic review of uncontrolled manifold studies. Gait Posture. 2019;69:66-78. Epub
2019/01/25. doi: 10.1016/j.gaitpost.2019.01.003. PubMed PMID: 30677709.
28.   Latash ML, Huang X. Neural control of movement stability: Lessons from studies of neurological
patients. Neuroscience. 2015;301:39-48. doi: 10.1016/j.neuroscience.2015.05.075. PubMed PMID:
26047732; PubMed Central PMCID: PMCPMC4504804.
29.   Ambike S, Penedo T, Kulkarni A, Santinelli FB, Barbieri FA. Step length synergy while crossing
obstacles is weaker in patients with Parkinson's disease. Gait Posture. 2021;84:340-345. Epub
2021/01/18. doi: 10.1016/j.gaitpost.2021.01.002. PubMed PMID: 33454501.
30.   Chou LS, Draganich LF. Stepping over an obstacle increases the motions and moments of the
joints of the trailing limb in young adults. J Biomech. 1997;30(4):331-337. Epub 1997/04/01. doi:
10.1016/s0021-9290(96)00161-3. PubMed PMID: 9075000.
31.   Winter DA. The Bionechanics and Motor Control of Human Gait: Normal, Elderly and
Pathological. Second ed. Kitchener, ON: Waterloo Biomechanics; 1991.

32.   Latash ML. One more time about motor (and non-motor) synergies. Exp Brain Res.
2021;239(10):2951-2967. Epub 2021/08/13. doi: 10.1007/s00221-021-06188-4. PubMed PMID:
34383080.
33.   Bauby CE, Kuo AD. Active control of lateral balance in human walking. J Biomech.
2000;33(11):1433-1440. Epub 2000/08/15. doi: 10.1016/s0021-9290(00)00101-9. PubMed PMID:
10940402.
34.   Collins SH, Kuo AD. Two independent contributions to step variability during over-ground human
walking. PLoS One. 2013;8(8):e73597. Epub 2013/09/10. doi: 10.1371/journal.pone.0073597. PubMed
PMID: 24015308; PubMed Central PMCID: PMCPMC3756042.
35.   Tillman M, Ambike S. Cue-induced changes in the stability of finger force-production tasks
revealed by the uncontrolled manifold analysis. J Neurophysiol. 2018;119(1):21-32. Epub 2017/09/22.
doi: 10.1152/jn.00519.2017. PubMed PMID: 28931612.
36.   McAndrew Young PM, Dingwell JB. Voluntarily changing step length or step width affects
dynamic stability of human walking. Gait Posture. 2012;35(3):472-477. Epub 2011/12/17. doi:
10.1016/j.gaitpost.2011.11.010. PubMed PMID: 22172233; PubMed Central PMCID: PMCPMC3299923.
37.   Kazanski M, Cusumano JP, Dingwell JB. Rethinking Margin of Stability: Incorporating Step-To-
Step Regulation to Resolve the Paradox. bioRxiv. 2021. doi: https://doi.org/10.1101/2021.12.01.470263.
38.   Sivakumaran S, Schinkel-Ivy A, Masani K, Mansfield A. Relationship between margin of stability
and deviations in spatiotemporal gait features in healthy young adults. Hum Mov Sci. 2018;57:366-373.
Epub 2017/10/11. doi: 10.1016/j.humov.2017.09.014. PubMed PMID: 28987772; PubMed Central
PMCID: PMCPMC5770210.
39.   Worden TA, Vallis LA. Stability control during the performance of a simultaneous obstacle
avoidance and auditory Stroop task. Exp Brain Res. 2016;234(2):387-396. Epub 2015/10/22. doi:
10.1007/s00221-015-4461-z. PubMed PMID: 26487180.
40.   Peebles AT, Reinholdt A, Bruetsch AP, Lynch SG, Huisinga JM. Dynamic margin of stability during
gait is altered in persons with multiple sclerosis. J Biomech. 2016;49(16):3949-3955. Epub 2016/11/28.
doi: 10.1016/j.jbiomech.2016.11.009. PubMed PMID: 27889188; PubMed Central PMCID:
PMCPMC5176013.
41.   Kuo AD. A simple model of bipedal walking predicts the preferred speed-step length
relationship. J Biomech Eng. 2001;123(3):264-269. Epub 2001/07/31. doi: 10.1115/1.1372322. PubMed
PMID: 11476370.

Supporting information

S1 Fig. Figure 1.tif. Figure 1. Experimental task and basic definitions. Illustration of foot
placements while approaching (fp_{-4} to fp_{-1}), crossing (fp_{+1} and fp_{+2}) and after crossing (fp_{+3}) the
obstacle, and of steps while approaching ($Step_{-3}$ to $Step_{-1}$), crossing ($Step_0$ and $Step_{+1}$) and after
crossing ($Step_{+2}$) the obstacle **(A)**. Definitions of the extrapolated center of mass (XcoM) and
margin of stability, MOS_{AP}. Step length, XcoM and MOS_{AP} are computed at the moment of lead
heel contact in a coordinate frame located where the rear heel contacted the ground **(B)**.
597
S2 Fig. Figure 2.tif. Figure 2. Representative data from one participant. Figure illustrates
changes in various outcomes while approaching and crossing an obstacle, and then resuming
unobstructed gait (blue ellipses). Steps during unobstructed gait are included for comparison

(red ellipses). The 45° line separates the regions of positive and negative MOS$_{AP}$; the white
region above the line represents passively unstable behavior, and the gray region below the line
represents passively stable behavior. The 45° line also represents the direction of the
uncontrolled manifold (UCM). Variations in step length and XcoM along this direction do not
change MOS$_{AP}$. The ellipses are centered at the centroid of the across-trial data for each step,
and the major axes are aligned with the 45° line. However, the flatness of the ellipses is
representative. Changes in mean values of the MOS$_{AP}$ are reflected in the position of the
ellipses in each chart. The flatness of the ellipse reflects the synergy index, with flatter ellipses
indicating higher synergy indices that reflect stronger covariation between the step length and
XcoM.

S3 Fig. Figure 3.tif. Figure 3. Outcomes of the synergy analysis. Synergy index **(A)**, V$_{UCM}$ **(B)**, and
V$_{ORT}$ **(C)**. Data are across-subject means (N=20), and error bars denote standard error. Asterisks
denote significant across-task differences at that step ($p < 0.05$). Across-step pairwise
comparisons for the obstacle-crossing task are indicated by the row of letters above the
horizontal axis for each panel. Steps that do not have letters in common are significantly
different from each other (i.e., A is different from B, but A is not different from AB).

S4 Fig. Figure 4.tif. Figure 4. MOS$_{AP}$ and its components. MOS$_{AP}$ **(A)**, CoM position at heel
contact **(B)**, CoM velocity at heel contact **(C)** and step length **(D)**. Data are across-subject means
(N=20), and error bars denote standard error. Asterisks denote significant task difference at
that step ($p < 0.05$). Across-step pairwise comparisons for the obstacle-crossing task are
indicated by the row of letters above the horizontal axis for each panel. Steps that do not have
letters in common are significantly different from each other (i.e., A is different from B, but A is
not different from AB).