slendr: a framework for spatio-temporal population genomic simulations on geographic landscapes

Martin Petr[1], Benjamin C. Haller[2], Peter L. Ralph[3], Fernando Racimo[1]

1. Lundbeck Foundation GeoGenetics Centre, Globe Institute, University of Copenhagen, Denmark
2. Department of Computational Biology, Cornell University, Ithaca, NY, USA
3. Institute of Ecology and Evolution, University of Oregon, Eugene, OR, USA

Abstract

One of the goals of population genetics is to understand how evolutionary forces shape patterns of genetic variation over time. However, because populations evolve across both time and space, most evolutionary processes also have an important spatial component, acting through phenomena such as isolation by distance, local mate choice, or uneven distribution of resources. This spatial dimension is often neglected, partly due to the lack of tools specifically designed for building and evaluating complex spatio-temporal population genetic models. To address this methodological gap, we present a new framework for simulating spatially-explicit genomic data, implemented in a new R package called *slendr* (www.slendr.net), which leverages a SLiM simulation back-end script bundled with the package. With this framework, the users can programmatically and visually encode spatial population ranges and their temporal dynamics (i.e., population displacements, expansions, and contractions) either on real Earth landscapes or on abstract custom maps, and schedule splits and gene-flow events between populations using a straightforward declarative language. Additionally, *slendr* can simulate data from traditional, non-spatial models, either with SLiM or using an alternative built-in coalescent *msprime* back end. Together with its R-idiomatic interface to the *tskit* library for tree-sequence processing and analysis, *slendr* opens up the possibility of performing efficient, reproducible simulations of spatio-temporal genomic data entirely within the R environment, leveraging its wealth of libraries for geospatial data analysis, statistics, and visualization. Here, we present the design of the *slendr* R package and demonstrate its features on several practical example workflows.

Introduction

Most evolutionary processes in nature have a spatial dimension. Indeed, since its beginnings, the field of population genetics has aspired to build interpretable models of spatial population dynamics (Guillot *et al.*, 2009; Barton, Etheridge and Véber, 2013). These include classic theoretical models such as Fisher's wave-of-advance model (Fisher, 1937), Wright's isolation-by-distance model (Wright, 1943), Kimura's stepping-stone model (Kimura, 1953; Kimura and Weiss,

1964), and Malecot's lattice model (Malécot, 1951; Nagylaki, 1976; Rousset, 1997). The field also
has a long history of modeling continuous spatial genetic variation (Levene, 1953; Slatkin, 1973;
Barton, 1979; Beerli and Felsenstein, 2001; McRae, 2006; Duforet-Frebourg and Blum, 2014;
Bradburd, Coop and Ralph, 2018), inferring spatial covariates associated with genetic patterns
(Hanks and Hooten, 2013) and detecting spatial barriers to migration (Safner *et al.*, 2011;
Petkova, Novembre and Stephens, 2016; Ringbauer *et al.*, 2018; Al-Asadi *et al.*, 2019; Marcus *et*
al., 2021). However, these latter efforts are hampered by a lack of good theoretical predictions for
continuous, two-dimensional models (Felsenstein, 1975; Barton, Depaulis and Etheridge, 2002),
and simulations can provide a valuable tool in the absence of analytical theory.
49
The dramatic increase in the number of published whole-genome sequences in the last 20 years
(1000 Genomes Project, 2010; Mallick *et al.*, 2016; Palkopoulou *et al.*, 2018; Feuerborn *et al.*,
2021), and the advent of ancient genomics (Green *et al.*, 2010; Rasmussen *et al.*, 2010), have
revealed previously unknown migration events in the history of several species, such as dogs
(Bergström *et al.*, 2020), horses (Librado *et al.*, 2021), elephantids (Meyer *et al.*, 2017), and
humans (Lazaridis *et al.*, 2014; Fu *et al.*, 2016). Since migration of populations involves spatial
displacement, populations trace their ancestry to different geographic locations (Ralph and Coop,
2013; Osmond and Coop, 2021; Wohns *et al.*, 2022). In the context of human history, processes
including past migration, gene flow, and population turnovers have been shown to have had a
major influence on the present-day distribution of genomic variation (Pickrell and Reich, 2014;
Slatkin and Racimo, 2016). Properly anchoring these past demographic events in both time and
space has been a focus for new modeling approaches (Racimo *et al.*, 2020; Osmond and Coop,
2021; Wohns *et al.*, 2022), and is a question of high interest not only in genetics (Bradburd and
Ralph, 2019) but also in ecology (Frachetti *et al.*, 2017; Loog *et al.*, 2017; Crabtree *et al.*, 2021;
Delser *et al.*, 2021).
65
Despite the key role of geography in population genetics, tools specifically designed for describing
and simulating complex spatio-temporal processes are still lacking. Spatial simulations are
important not just for rigorous testing and evaluation of existing inference tools and facilitating the
development of new inference methods (Liu *et al.*, 2006; Currat and Excoffier, 2011; Delser *et al.*,
2021; Osmond and Coop, 2021; Wohns *et al.*, 2022), but also for gaining intuition about the
expected behavior of the processes influencing the patterns of genetic variation under various
scenarios of spatial population dynamics (Felsenstein, 1975; Slatkin and Excoffier, 2012). While
powerful simulation approaches based on coalescent theory have been developed (Hudson,
2002; Ewing and Hermisson, 2010; Staab *et al.*, 2015; Kelleher, Etheridge and McVean, 2016),
these have little or no notion of spatiality due to fundamental obstacles to incorporating space into
the coalescent framework (Barton, Depaulis and Etheridge, 2002; Barton, Etheridge and Véber,
2010, 2013), although recent algorithmic advances are promising (Kelleher, Etheridge and
Barton, 2014). The first pioneering attempt at simulating spatial population genetic data was the
software package SPLATCHE (Currat, Ray and Excoffier, 2004; Currat *et al.*, 2019). However,
SPLATCHE's simulation engine is limited to discrete demes based on the stepping-stone model,
allows simulation of no more than two populations co-existing at a time, and is not suitable for
simulating sequence data at a whole-genomic scale (Currat *et al.*, 2019). The most advanced
simulator with spatial capabilities is currently the forward population genetic simulation framework

SLiM (Haller and Messer, 2017, 2019). Highly popular in the population genetics community, SLiM
contains a vast library of features for simulating individuals in continuous space (as opposed to
older approaches based on discrete demes), including spatial interactions between individuals,
neighborhood-based mate selection, and customisable offspring dispersal (Haller and Messer,
2019). Moreover, the recent implementation of tree-sequence recording in SLiM has opened up
the possibility of efficient simulation of massive genome-scale and population-scale datasets
(Haller *et al.*, 2019).

Despite these advances in population genetic simulations, geospatial data analysis remains a
complex field with a steep learning curve. Performing even basic manipulations of spatial
cartographic objects, handling diverse data formats, and transforming data between different
projections and coordinate reference systems (CRS) requires a non-trivial amount of domain-
specific knowledge (Lovelace, Nowosad and Muenchow, 2019). Moreover, because the
technicalities of geospatial computation are generally not within the scope of population genetic
software, available tools do not provide dedicated functionality for building complex and dynamic
spatial population models in a straightforward manner. Developing such models and simulating
data from them currently requires hundreds of lines of custom code, which is error-prone and
hinders reproducibility. Additionally, the lack of specific frameworks for analyzing and visualizing
spatially-explicit genomic data further hinders the methodological and empirical progress in spatial
population genetics. A flexible and easy-to-use simulation framework specifically designed for
developing spatio-temporal population models and analyzing spatial genomic data would expand
the horizons of the field, allowing researchers to evaluate the accuracy of novel spatial methods,
to test detailed hypotheses about demography and selection, and to answer entirely new kinds of
questions about the interactions between organisms across space and time. For instance, many
conceptual models and visualizations of past migration events involve depictions of movements
of large population ranges across a map as various environmental or cultural conditions change;
however, there is currently no easy way to simulate these movements and generate realistic
spatio-temporal genomic data.

To address these issues, we have developed a new programming framework, called *slendr*,
designed for simulating and analyzing spatially-explicit genomic data (available at www.slendr.net
with extensive documentation and tutorials). The core component of this framework is an R
package which leverages real Earth cartographic data (or, alternatively, an abstract user-defined
spatial landscape) to programmatically and visually encode spatial population boundaries and
their temporal dynamics across time and space, including expansions, migrations, population
splits, and gene flow. Because of the challenges involved in testing and validating complex
models, *slendr* encourages an interactive workflow in which each component of the model can be
inspected and visualized as the model is incrementally constructed in a "bottom-up" fashion.
Spatio-temporal models programmed in *slendr* can then be executed using a SLiM back-end
script which is bundled with the package and can be controlled by a dedicated R function without
leaving the R environment. Additionally, traditional, random-mating, discrete-deme, non-spatial
population models can also be simulated, either in forward time using the aforementioned SLiM
script or using an alternative coalescent *msprime* (Baumdicker *et al.*, 2022) back-end script which
is also bundled with the R package and can provide a more efficient simulation engine for non-

spatial models. Both simulation engines of *slendr* save genomic outputs in the form of an efficient
tree-sequence data structure (Kelleher *et al.*, 2018), and the *slendr* R package provides a set of
functions for loading and processing tree-sequence output files and computing population
statistics on them by seamlessly integrating the *tskit* tree-sequence analysis Python module into
its R interface. Additional functionality includes conversion of individual trees to a standard R *ape*
phylogenetic format (Paradis and Schliep, 2019), and automatic transformation of spatial tree-
sequence table data to the standardized *sf* format for geospatial data analysis in R (Pebesma,
2018).
Overall, the *slendr* R package facilitates reproducibility by providing a unified framework
for writing complete spatial simulation and analysis pipelines entirely in R, which we demonstrate
with several concrete examples.

Overview of the *slendr* design and typical workflow

From a software design perspective, the *slendr* R package represents a tight integration of three
distinct parts. First, it implements an interactive and visually-focused R interface for encoding
spatio-temporal population dynamics focused on building arbitrarily complex models from small
individual components (i.e., simple R objects), designed to require only a minimum amount of
code. Second, *slendr* includes two back-end simulation scripts implemented in SLiM (Haller and
Messer, 2019) and *msprime* (Baumdicker *et al.*, 2022). These scripts are bundled with *slendr*, are
specifically tailored to interpret *slendr* demographic models, and produce tree-sequence files as
output (Haller *et al.*, 2019). Lastly, *slendr* provides an interface to the *tskit* tree-sequence analysis
library (Kelleher *et al.*, 2018). Although this library is written in C and Python, *slendr* exposes its
functionality to the R environment in an R-idiomatic way, blending it naturally with the popular
"tidyverse" philosophy of data analysis (Wickham *et al.*, 2019).
Although these three parts operate at fundamentally different levels under the hood, this
integrated approach allows all steps of a *slendr* workflow—from specifying spatio-temporal
demographic models, to executing simulations and analyzing simulation results—to be performed
without leaving the R environment (**Figure 1**). This allows the user to leverage R's features for
visualization and interactive data analysis at every step of the analytic pipeline, and facilitates
reproducibility by eliminating the need to manually integrate disparate software tools and
programming languages (Sandve *et al.*, 2013). In this way, *slendr* follows the footsteps of the
original design of the S (and later R) languages: to present a consistent and convenient data-
analysis–focused domain-specific front end to more efficient and faster tools written in other
languages and frameworks (in this case SLiM and *msprime*) (Chambers, 2020).
161
162 In the remainder of this section we outline the individual steps of a typical *slendr* simulation and
163 analysis workflow, as well as describe the individual building blocks of the three main components
164 of the *slendr* framework mentioned above.
165

166
167
Figure 1. Schematic overview of a hypothetical *slendr* simulation and analysis workflow.
The colored rectangles on the left indicate individual steps of a hypothetical *slendr* workflow. Short
code snippets in matching colors on the right show examples of *slendr*'s declarative interface used
in each step, focusing only on a selected few relevant functions and their most important arguments
(additional optional arguments are replaced by the "..." ellipsis symbol). The full function reference
index can be found at slendr.net/reference. Note that regardless of whether a spatial or non-spatial
slendr model is being defined and simulated, the workflow remains identical: the same functions
are used for both types of models, and the spatial or non-spatial nature of a model is automatically
detected by *slendr*.

Defining the world

At the beginning of a *slendr* workflow, the user defines the parameters of the world that the
simulation will occupy using the function `world()` (**Figure 1**). If the simulated world represents
a region on Earth, the appropriate set of vectorised spatial features will be automatically
downloaded from a public-domain cartographic database (www.naturalearthdata.com). The user
can also specify a dedicated coordinate reference system (CRS) appropriate for the projection of
the geographic region of interest in order to minimize the distortion of distances and shapes
inherent to transforming geometries (in this case population ranges and landscape features) from
the three-dimensional Earth surface to its two-dimensional representation on a map. Alternatively,
the world can be represented by an abstract landscape, optionally with custom features such as
islands, barriers, or corridors. If a non-spatial deme-based model is to be simulated, this step can
be omitted and no changes to the downstream steps described below are needed.

Creating populations and scheduling demographic events

Populations in *slendr* are created with the `population()` function which creates a simple R object containing the parameters of the population that was created (**Figure 1**). In addition to specifying the name, time of appearance, and initial number of individuals for the new population, the user can also specify a `world` object and, if desired, a set of coordinates for the spatial range that the population will occupy. For convenience, the coordinates of all spatial objects in *slendr* (maps, geographic regions, population ranges) are always specified in the global geographical CRS (i.e., degrees of longitude and latitude) but are then automatically internally transformed into the chosen projected CRS (which uses units of meters) if it was specified when creating the `world` (**Figure 1**). This way, users can encode spatial coordinates in familiar units of longitude and latitude while *slendr* internally maintains the proper shapes and distances of spatial features by performing all spatial transformations in the projected CRS.

All *slendr* spatial objects are internally represented using a data type implemented by the R package *sf* (Pebesma, 2018), which has emerged as the *de facto* standard for geospatial data analysis in R (Lovelace, Nowosad and Muenchow, 2019). Despite the convenience of the *sf* framework, manipulation of geospatial objects in *sf* still requires writing a non-trivial amount of code dealing with low-level technical details (manipulating and transforming the coordinates of points, lines and polygons). Because most of these technical details are not relevant for specifying population genetic models, we designed a set of domain-specific functions for encoding spatial population dynamics which are expressed in terms of population genetics concepts rather than geometric transformations (**Figure 1**). For instance, the `move()` function accepts a *slendr* population object (i.e., internally an `sf` object, encapsulating the low-level geometric coordinates of the population), a trajectory given as a list of coordinates in longitude and latitude, and a timespan over which the population displacement should occur (*Example 3* and **Figure 4**). Other kinds of dynamic spatial events (population range expansions and contractions, for example) are implemented in an analogous manner. Other demographic events, such as population size changes and gene flow, can be scheduled similarly with another set of straightforward functions (**Figure 1**).

For spatial models, the user has the option to fine-tune the within-population individual dispersal and mating dynamics (described in detail in *Example 2* and **Figure 3**) using a set of parameters such as the maximum mating distance between individuals, the dispersal distance of offspring from their parents (and the kernel function of this dispersal), or the parameter influencing the uniformity of the dispersal of individuals within their population's spatial boundary. These can be assigned for each population separately or kept at their default values given in the `compile_model()` step (as we show in *Example 2*). The `competition` parameter determines the maximum neighborhood distance in which individuals in a SLiM simulation compete with each other for space. If this distance is small, then individuals with nearby neighbors have much lower fitness. If the distance is larger, then the effects of crowding are more diffuse. However, if this distance is larger than the dispersal distance (as in *Example 2*), populations tend to self-organize into an evenly-spaced grid of patches. (**Figure 3C**). Using the `competition` parameter, within-population dynamics can thus be fine-tuned to represent various levels of individual clustering into sub-groups (**Figure 3C**). In addition to the competition parameter, a `mating` parameter determines the maximum distance to which an individual will look for a mate to produce offspring.

Finally, a `dispersal` parameter determines how far an offspring can end up from its parent, and
a related `dispersal_fun` argument characterizes the density function for this dispersal:
"normal" (default), "uniform", "cauchy", "exponential", or "brownian"; more details are available in
the *slendr* R package documentation at slendr.net/reference). We note that changes in all three
spatial interaction and dispersal parameters can be also scheduled dynamically at specific times
throughout the run of a model with a *slendr* function `set_dispersal()`.

A standard feature of many population genetic frameworks is the specification of the times of
various demographic events in terms of generations, either forwards in time starting from
generation 1 (as is the case with SLiM) or backwards in time starting from time 0 "in the present"
(as is the case with coalescent frameworks such as *msprime*). This can be cumbersome in cases
when the events or samples of interest are traditionally specified in times of "years before present"
(such as dated ancient DNA samples), or in situations in which it would be desirable to simulate
future outcomes, as in ecological predictive modeling. Moreover, because these standard times
often need to be converted into generations by a factor specifying the length of the generation
time of the species of interest, this can easily lead to frustrating bugs in simulation scripts. To
ameliorate this situation, *slendr* allows the users to specify times in whichever time units they
would prefer, in either the forward or backward direction. The time direction is automatically
detected by *slendr* from the sequence of demographic events specified for a model (but can also
be set explicitly), and the conversion of event times into generations is performed in the
compilation step via the provided `generation_time` argument to `compile_model()`
(described below). Similarly, times of the tree-sequence nodes in *slendr*'s outputs (which are
specified by most simulation software in terms of generations backwards in time) are
automatically converted by *slendr* back into the units of time used by the user during model
specification.

Because every *slendr* demographic event function returns a modified population object which can
be further used as an input to other *slendr* functions, the R interface encourages a workflow in
which complex models are composed incrementally from smaller components (**Figure 1,**
Examples 1-3). Importantly, because each *slendr* function assures the consistency of the model
by enforcing appropriate constraints during the model definition process (e.g., a population cannot
be moved or participate in a gene-flow event at a time when it would not yet exist), this workflow
facilitates the early discovery of bugs before the simulation (which can be extremely
computationally costly) is even executed. This is further facilitated by a convenient set of plotting
functions, such as `plot_map()` and `plot_model()`, which can visualize the spatio-temporal
dynamics of the specified model (or its individual components) as the model is being incrementally
developed.

Model compilation

Having defined all the individual components of a population model (i.e., created all the necessary
population and gene-flow events), the user calls the function `compile_model()` to compile the
model configuration to a single R object (**Figure 1**)—a step in which *slendr* performs additional
checks for model consistency and correctness. Furthermore, this operation also transforms the

model components from their R representation into a set of files on disk, written in a format
interpretable by the built-in SLiM and *msprime* simulation back-end scripts which are used to
execute *slendr* models in the next phase, as described below. The compiled model object can
also be used as input for a built-in R-based interactive browser app built using the *shiny* R
package (Chang *et al.*, 2021) which allows the user to "play" the defined spatial model dynamics
over time and explore the "admixture graph" implied by the model (Patterson *et al.*, 2012) for
additional verification of the model's correctness. The functions `plot_map()` and
`plot_model()` mentioned above also accept a compiled model object as their input and produce
a static visualization of the model.

Scheduling sampling events and simulation

The *slendr* package comes bundled with two simulation back-end scripts which were tailored to
interpret the configuration files produced by the `compile_model()` function and simulate the
model, triggering all of the encoded population dynamics in the course of the simulation run.
The first back-end script is written in SLiM's programming language Eidos (Haller and
Messer, 2019), and can execute both spatial and non-spatial *slendr* models in a Wright–Fisher
setting by calling *slendr*'s `slim()` function. The second back-end script is implemented using
msprime (Baumdicker *et al.*, 2022) and is designed to interpret the compiled *slendr* model in a
non-spatial setting as a standard coalescent simulation by calling *slendr*'s `msprime()` function.
Both simulation engines can interpret the same *slendr* model without a need to make any
changes. For instance, a spatial model can be run with the *msprime* back end, in which case the
spatial component of the model is simply ignored. Because coalescent simulations are generally
much more computationally efficient than their forward-time counterparts, the *msprime* back end
of *slendr* can be useful for R users who would like to run a large number of traditional, non-spatial
simulation replicates efficiently without having to write custom Python *msprime* code or use its
ms-like command-line interface (Hudson, 2002). Importantly, the correctness of both *slendr*
simulation engines is validated using a set of automatic statistical tests on non-spatial models
which ensure that when a *slendr* model is run in both SLiM and *msprime*, the demographic events
specified by the model (population splits, population size changes, and gene-flow events) result
in equivalent site-frequency spectra and *f*-statistics (Patterson *et al.*, 2012) between both back
ends.
Leveraging the ability to save simulation outputs as a tree sequence (Kelleher *et al.*, 2019;
Speidel *et al.*, 2019) from both SLiM (Haller *et al.*, 2019) and *msprime* (Baumdicker *et al.*, 2022),
slendr embraces the tree sequence as its primary output format. This is powerful not only because
the tree sequence represents an extremely efficient representation of even large-scale population
genomic data, but also because it provides an elegant way to calculate many population genetic
statistics of interest, a feature which we describe in more detail in the next section. To specify
which simulated individuals should be recorded in the output tree sequence, *slendr* provides two
alternative approaches. First, if no explicit sampling schedule is specified, all individuals living at
the very end of a SLiM simulation run are explicitly sampled (i.e., "remembered") in the tree
sequence output, matching the default behavior of SLiM. If a *slendr* model is simulated with the
msprime back end, the number of recorded individuals will be equal to the population size of each
population at the start of the coalescent process looking backwards in time (i.e., in "the present").

Alternatively, *slendr* provides a flexible way to trigger sampling events via its
`schedule_sampling()` function, which allows one to specify the time (and, optionally, the
location) at which a sample comprising a given number of individuals from a given population
should be taken and recorded in the tree sequence (*Example 3*). To improve readability and
interpretation of *slendr* analysis code, every sampled individual can be referred to using its
readable name during tree-sequence processing and computation of statistics (*Examples 1, 2,*
and 4) rather than just by numeric identifiers as is the case with the default tree-sequence analysis
workflow with *tskit* (Kelleher *et al.*, 2018).

Data analysis

The default output of a *slendr* simulation is a tree sequence. However, because processing and
analysis of tree-sequence files requires a non-trivial knowledge of Python or C (Kelleher *et al.*,
2018) which many R users might not have, *slendr* provides an R-idiomatic interface to the most
commonly used *tskit* tree-sequence methods such as the allele frequency spectrum, Patterson's
f-statistics, and various summary statistics of population diversity (Patterson *et al.*, 2012; Ralph,
Thornton and Kelleher, 2020). This way, users can design population genetic models in R,
execute them from R using the built-in `slim()` or `msprime()` functions, and analyze the
resulting tree sequence data without having to leave the R environment for downstream statistical
analyses and plotting, and without the need to convert outputs to other bioinformatic or population
genetic file formats. Although primarily designed for analysis of tree sequences generated from
slendr models, the R-*tskit* interface can operate also on tree sequences without *slendr*-specific
metadata. Therefore, users who would prefer to run simulations with standard *msprime* or SLiM
scripts but are interested in analyzing their tree-sequence results in R will still find the *slendr* R
package useful. The reference manual at slendr.net/reference contains a complete list of *tskit*
tree-sequence methods that have been integrated into *slendr*'s R interface. If integration with
traditional tools such as PLINK (Purcell *et al.*, 2007) or ADMIXTOOLS (Patterson *et al.*, 2012) is
required, functions for exporting to VCF (Danecek *et al.*, 2011) and EIGENSTRAT (Patterson *et*
al., 2012) are also provided.
During a spatial simulation in SLiM, each sampled individual's location on the simulated
landscape is tracked and recorded in the tree sequence, encapsulating the full spatio-temporal
genealogical history that has been simulated. When the tree-sequence output file is then loaded
by *slendr*, *slendr* processes the spatial locations of nodes in the tree sequence (which represent
chromosomes of past and present individuals), and transforms them back into the original
coordinate system of the simulated world, adding additional annotation data such as readable
names of sampled individuals, population assignments of each individual and node, etc.
Furthermore, this information is exposed in an *sf*-compatible format, meaning that the spatio-
temporal information about ancestral relationships between simulated samples can be processed,
analyzed, and visualized using a wide range of R packages including *sf*, *ggplot2,* and *dplyr*
(Pebesma, 2018; Wickham *et al.*, 2019). Additionally, individual trees in the tree sequence can
be extracted by a *slendr* function, `ts_phylo()`, which converts *tskit*-formatted tree objects into
the format defined by the R phylogenetics package *ape*, which has been the standard for
phylogenetics in the R ecosystem for nearly two decades (Paradis and Schliep, 2019). This gives

slendr users even more options to analyze tree-sequence results with a large array of standard
phylogenetics tools available for the R environment (Paradis, 2011).

Installation and software dependencies

slendr is currently developed for macOS and Linux. It is available on the CRAN R package
repository at https://CRAN.R-project.org/package=slendr, and can be installed from the
interactive R console with the standard command `install.packages("slendr")`.
Development versions of *slendr* which contain latest bug fixes and new experimental features can
be installed from its GitHub repository using the R package *devtools* with the R command
`devtools::install_github("bodkan/slendr")`.
Two external software dependencies must be present on a user's system to leverage the
full functionality of *slendr*: a forward population genetic simulator SLiM (Haller and Messer, 2019)
(which is required for running spatial simulations and non-spatial simulations in the forward-time
setting) and a trio of Python modules *msprime* (Baumdicker *et al.*, 2022), *tskit* (Kelleher *et al.*,
2018) and *pyslim* (github.com/tskit-dev/pyslim) (which are needed to run *slendr* models as
coalescent simulations and to analyze tree-sequence data).
The SLiM software is available for all major operating systems and its installation
instructions can be found at messerlab.org/slim. Importantly, the current version of *slendr* requires
the latest release of SLiM 4.0. In order to use SLiM for simulations in *slendr*, the R session needs
to be aware of the path to the directory containing the SLiM binary. Calling `library(slendr)`
for the first time provides an informative message for the user on how this can be accomplished
by modifying the `$PATH` variable by editing the `~/.Renviron` file.
Because some users might find the experience of setting up a dedicated Python
environment with the necessary Python modules challenging (especially users who exclusively
work with R), *slendr* provides an R function `setup_env()` which automatically downloads a
completely separate Python distribution, and installs the required versions of *tskit*, *msprime*, and
pyslim modules in their correct required versions into a dedicated virtual environment without any
need for user intervention. Moreover, this Python installation and virtual environment are isolated
from other Python configurations that might be already present on the user's system, thus
avoiding potential conflicts with the versions of Python and Python modules required by *slendr*.
After a dedicated Python environment is created by `setup_env()`, calling `library(slendr)`
at any later point will activate this environment automatically. Therefore, although *slendr* uses
Python modules for internal handling of tree-sequence data and coalescent simulation, direct
interaction with Python is not necessary.
390

Practical examples

In the following sections, we present the features of the *slendr* R package with several practical
examples, each of which focuses on a different aspect of the *slendr* simulation framework. We
start by showing how traditional, non-spatial, random-mating models can be specified with a
minimum amount of R code (*Example 1*). We then proceed with two examples of spatial models:
first, a model showing how the degree of the spatial spread of a population can be adjusted by

setting the within-population individual-based dispersal dynamics (*Example 2*); second, a model
which schedules the movements of entire population ranges across a landscape (*Example 3*).
These examples are intended to demonstrate *slendr's* ability to define complex spatio-temporal
models incrementally, building them from simpler components. We also emphasize how *slendr*
model configuration and simulation steps naturally flow into data analysis, all within the R
environment. In the final demonstration (*Example 4*), we tap into the rich information embedded
in spatial tree sequences to visualize individual trees on a landscape, tracing the complex spatio-
temporal ancestry of an individual on the simulated map. Extended versions of these and many
other examples with complete reproducible code for simulation, analysis, and plotting can be
found as standard R package vignettes at *slendr's* website (www.slendr.net).
407

Example 1: Traditional non-spatial model

Regardless of whether a spatial or non-spatial model is defined and simulated, the *slendr*
workflow remains the same. Therefore, before we explore spatial models, we begin by showing
how a traditional, non-spatial population genetic model can be constructed with *slendr* and how
users can compute population genetic statistics on simulated tree-sequence outputs using
slendr's R interface to the *tskit* tree-sequence analysis library (Kelleher *et al.*, 2018) (represented
by functions with the `ts_*()` prefix, **Figure 1**).
First, we define an abstract demographic model similar to that which is commonly used in
teaching the principles behind the f_4-ratio ancestry proportion estimator (Patterson *et al.*, 2012).
In *slendr*, we define the model with a straightforward sequence of `population()` calls that
schedule the order of splits for several populations, taking care of parent–daughter population
relationships by providing the appropriate population object as a `parent` argument when creating
each daughter population (**Figure 2A**). We then schedule a single gene-flow event between the
populations *"b"* and *"x1"* by calling the `gene_flow()` function. After compiling the model with
`compile_model()`, we verify its correctness by visualizing the embedded population
relationships with `plot_model()` (**Figure 2B**)
As stated before, *slendr* provides two simulation back ends; here we use the coalescent
msprime back end to simulate the model, since SLiM's spatial capabilities are not required for this
simple non-spatial model. However, we note that the function `slim()` could be used in place of
the `msprime()` call to perform the equivalent forward-time simulation just as easily. By default,
slendr automatically loads the simulated tree-sequence object which can be immediately used for
analysis. In this example, we compute the pairwise divergence between random samples of 100
individuals from each population with the function `ts_divergence()` (**Figure 2C**). Finally, we
use the function `ts_f4ratio()` to compute the values of the f_4-ratio estimate of *"b"* ancestry in
populations *"x1"* and *"x2"*, which differ in whether or not they experienced gene flow from *"b"*
(**Figure 2D**). All other tree sequence analysis functions of *slendr* (**Figure 1**) can be accessed in
the same way. We note that because *slendr* assigns symbolic, permanent names to individuals
during sampling, the users can refer to them with these names during tree-sequence operations
such as simplification and when computing tree-sequence statistics.
437

Figure 2. Example 1: specifying a non-spatial model and computing statistics on tree-
sequence output. (A) A script which defines a model of a simple demographic history of six
populations, simulates it with the *msprime* back end by calling the function `msprime()`, and
performs analyses shown in **B**–**D**. **(B)** A visual overview of the compiled *slendr* model produced by
`plot_model()` prior to simulation. **(C)** Visualization of the data frame produced by
`ts_divergence()` on the output tree sequence simulated. **(D)** Ancestry proportions estimated
with `ts_f4ratio()` directly from the tree sequence output. As expected from the model definition,
the f_4-ratio statistic estimates indicate ~10% ancestry from "b" in the population "x1", but 0%
ancestry in population "x2"; this agrees with the model overview shown in panel B. Full *ggplot2*
visualization code for the figures can be found in a vignette dedicated to this paper at
www.slendr.net.

Example 2: Model with population dispersal dynamics

In our second example, we move from a non-spatial, random-mating model to a model which is
explicitly spatial. First, we create an abstract, circular world map using the function `world()`,
producing a completely featureless landscape (see *Example 3* for a more elaborate world map).
We then create a series of eight populations which all occupy that map, as specified by the `map`
argument to `population()`, but do not interact with each other. For simplicity, each population
forms its own evolutionary lineage without additional splits or gene-flow events. Importantly, we
set the `competition` parameter of each population to a value which forces the individuals to
assume an increasing degree of spatial subdivision which, in turn, affects the amount of diversity

expected in each population. Finally, we compile the model to a single object with
`compile_model()` and run it with the `slim()` back end, simulating 16.000 diploid genomes of
10 megabases each (**Figure 3A**). After the simulation finishes, we simplify the produced tree
sequence, overlay mutations on the simulated genealogies, and use the *slendr* function
`ts_diversity()` to compute the expected heterozygosity in a sample of 100 individuals from
each population, inspecting how heterozygosity is affected by the emergent spatial arrangement
of each population (**Figure 3B, C**). We note that some of the values of the spatial competition
distance parameter used in this example are quite large, especially compared to the much shorter
maximum distance of individual dispersal and mating. Although biologically rather unrealistic, the
competition distances have been chosen to give rise to very different degrees of spatial
subdivision and, consequently, to varying levels of population genetic diversity, with the intention
to demonstrate the ease with which a wide range of model dynamics can be configured by the
user.

A

```
map <- world(xrange = c(0, 10), yrange = c(0, 10),
             landscape = region(center = c(5, 5), radius = 5))

p1 <- population("pop1", time = 1, N = 2000, map = map, competition = 0)
p2 <- population("pop2", time = 1, N = 2000, map = map, competition = 9)
p3 <- population("pop3", time = 1, N = 2000, map = map, competition = 6)
p4 <- population("pop4", time = 1, N = 2000, map = map, competition = 5)
p5 <- population("pop5", time = 1, N = 2000, map = map, competition = 4)
p6 <- population("pop6", time = 1, N = 2000, map = map, competition = 3)
p7 <- population("pop7", time = 1, N = 2000, map = map, competition = 2)
p8 <- population("pop8", time = 1, N = 2000, map = map, competition = 1)

model <- compile_model(
  populations = list(p1, p2, p3, p4, p5, p6, p7, p8),
  generation_time = 1, simulation_length = 5000, resolution = 0.1,
  mating = 0.1, dispersal = 0.05
)

ts <- slim(model, sequence_length = 10e6, recombination_rate = 1e-8) %>%
  ts_simplify() %>%
  ts_mutate(mutation_rate = 1e-7)

# panel B
heterozygosity <- ts_samples(ts) %>%
  group_by(pop) %>%
  sample_n(100) %>%
  mutate(pi = ts_diversity(ts, name)$diversity)

locations <- ts_data(ts) %>% filter(time == max(time)) # panel C
```

B

C

spatial distributions emerged in the simulation

Figure 3. Example 2: a spatial model which involves the parametrization of within-population dispersal dynamics. (A) A complete script which defines eight populations as independent lineages or species, each with constant size and each defined with a different value of *slendr*'s spatial competition parameter, with analysis code to produce panels **B**–**C**. The simulation is run with *slendr*'s SLiM back end for 5000 generations, after which a tree sequence recording the genealogical history of 2000×8 diploid individuals is loaded, simplified, and mutated. Heterozygosity is then computed for 100 individuals randomly sampled from each population at the end of simulation. **(B)** Distribution of heterozygosities of individuals observed in all eight populations. **(C)** A snapshot of the spatial distributions which emerged as a result of the `competition` parameter value set for each population. Full visualization code for the figures can be found in a vignette dedicated to this paper at www.slendr.net.

Example 3: A toy model of movements and expansions of human populations in West Eurasia over the last 50,000 years

In this example we further expand on the *slendr* functionality demonstrated in the first two examples, introducing programming of expansions and migrations of entire population ranges across a realistic landscape—perhaps the most distinctive feature of *slendr*. The model we implemented here is inspired by large-scale population migrations and turnover events inferred from ancient DNA analyses of human remains from across West Eurasia (Lazaridis *et al.*, 2014; Allentoft *et al.*, 2015; Haak *et al.*, 2015), although we caution that it is simplified and intended only as an illustrative example.

Similarly to *Example 2*, we begin by defining a world map for the simulation (**Figure 4A**), in this case using realistic Earth cartographic data provided by the Natural Earth project (naturalearthdata.com). Because we focus on the broad region of West Eurasia, we select the most appropriate coordinate reference system (CRS) for projecting this region on a two dimensional map which is EPSG:3035. We then define a series of populations, specifying their approximate geographic ranges using simple polygons. We then use the functions `move()` and `expand_range()` to schedule when and where populations should migrate, and by what distance and how quickly their population ranges should expand across the landscape during simulation. We again use `plot_model()` to visualize the demographic history embedded in the *slendr* model as a non-spatial tree-like structure with gene-flow edges (**Figure 4B**); here, we also use `plot_map()` to get a "compressed" overview of the spatio-temporal population range dynamics on the simulated map (**Figure 4C**). We note that unlike in the two previous examples, which were specified in forward time units, this example expresses the timing of demographic events in units of "years before present" which is more natural to this model.

In the previous two code examples (**Figure 2A, 3A**) we used the default tree-sequence sampling of *slendr*, which implicitly records the genomes of all the diploid individuals alive at the end of a simulation. In this example, we instead use `schedule_sampling()` to specify a series of sampling events from each population every 1,000 years. We then execute the compiled model and the sampling schedule specified using the `slim()` back-end, which records only the scheduled set of sampled individuals in the tree-sequence output file.

520
521
Figure 4. Example 3: a demographic model on a real Earth landscape. (A) A *slendr* script which
defines a toy spatio-temporal model of human prehistory in West Eurasia, with analysis code that
produces panels **B**–**C**. For brevity, we do not specify the full set of coordinates for each spatial
demographic event or population range polygon, instead indicating them as ″...″; the complete
reproducible code can be found in a vignette dedicated to this paper at www.slendr.net. **(B)** Visual
summary of the non-spatial component of the demographic model, produced by `plot_model()`
with arrows indicating gene flow events. **(C)** A "compressed" view of spatio-temporal snapshots of
population ranges throughout the course of the model prior to the simulation, produced by
`plot_map()`.
531

532 Example 4: Visualization of individual trees and spatio-temporal ancestral
533 lineages across a landscape

534
In our final example (**Figure 5**), we return to the abstract toy model of West Eurasian prehistory
developed in *Example 3*. To leverage *slendr*'s power to simulate genomic data from complex
spatial demographic models, *slendr* makes it easy to tap into the large library of geospatial data
science packages available for R (Lovelace, Nowosad and Muenchow, 2019) by automatically
converting simulated spatial locations to an *sf*-compatible tabular format (Pebesma, 2018), as we
will see here.

To demonstrate the richness of the spatio-temporal information recorded in the tree
sequence, we use the full tree sequence produced by the code in **Figure 4A** and simplify it so
that it contains only the history of a small subset of the thousands of individuals sampled during
the spatio-temporal simulation (**Figure 5A**). We then extract the 10th tree in the tree sequence
with *slendr*'s function `ts_phylo()`, which converts a tree from the *tskit* tree sequence into an R
`phylo` format defined by the *ape* R package, a standard tool for phylogenetics in R (Paradis and
Schliep, 2019). Such tree objects can be analyzed by any of the dozens of R packages which
operate on *ape*'s `phylo` trees—for instance, in **Figure 5B** we show a visualization of this tree
using the R package *ggtree* (Yu *et al.*, 2017). Furthermore, because the tree was generated from
a spatially-annotated tree sequence, the user can extract information about the location of each
individual (or node) in the tree across space and time, as well as ancestral relationships between
nodes in the tree, using `ts_nodes()` and `ts_edges()` respectively. Crucially, because these
functions automatically convert locations into *sf*'s geospatial representation (including the
appropriate CRS projection), the results can be immediately plotted on a map with *ggplot2*, which
has built-in support for *sf* data (**Figure 5C**).
In addition to extracting and visualizing single trees representing a genealogy of a set of
sampled genomes descending from a common ancestor (spatial or non-spatial), *slendr* also
provides a way to extract the complete spatio-temporal ancestry of a single sample going back in
time across the entire tree sequence, potentially spanning many trees with thousands of the
sample's ancestors. This can be accomplished with the function `ts_ancestors()` which, in an
analogous way to `ts_nodes()` and `ts_edges()`, exposes the spatio-temporal information in
the tree sequence as an *sf* object which can be visualized on a map with *ggplot2*. In this example,
we use `ts_ancestors()` to reconstruct the spatio-temporal ancestry distribution for a single
simulated European individual ("EUR_581", represented by the black dot in **Figure 5D**). Because
this individual is diploid, we can trace the ancestry carried by its one chromosome through an
expansion from Anatolia (**Figure 5D**, right panel), while its other chromosome clearly traces its
ancestry to a population which migrated to central Europe from an eastern population (**Figure
5D**, left panel).
Note that by default, the tree sequence output of a *slendr* simulation only contains
information about ancestors which are represented by coalescent nodes in some marginal tree—
i.e. nodes which are a most recent common ancestor of some pair of sampled nodes. In this
example, in **Figure 5B** and **C** we can see that the most immediate ancestor (node number 13) of
one chromosome of the sampled individual "EUR_581" lived in the region of Anatolia, but the
ancestor of its second chromosome lived near the Pontic–Caspian steppe (node number 11); but
we do *not* know where all the ancestors along the edges between nodes 13-7 and 11-6, since
they were simplified away. Similarly, **Figure 5D** shows the distributions of locations of most recent
common ancestors, not *all* ancestors. The distribution of ancestors at a particular point in time
could be obtained by adding an appropriate sampling event to *slendr*'s sampling schedule and
then extracting ancestors from that time.
580

```
ts_small <- ts_simplify(ts, c("EUR_581", "ANA_120", "EHG_440", "EUR_597", "YAM_59"))

tree <- ts_phylo(ts_small, i = 10)   # panel B
nodes <- ts_nodes(tree)              # panel C
branches <- ts_edges(tree)           # panel C

ancestors <- ts_ancestors(ts, "EUR_581")  # panel D
```

581
582
Figure 5. Example 4: accessing and visualizing spatio-temporal information encoded in
trees and tree sequences simulated with the *slendr*. (A) A continuation of the script from
Example 3, showing how a (potentially very large) tree sequence generated from a *slendr* model
can be simplified to a subset of individuals with `ts_simplify()`. A single tree from the tree
sequence is then extracted with `ts_phylo()`, the tables of spatio-temporal locations of nodes and
branches of the tree are extracted by `ts_nodes()` and `ts_edges()`, and ancestry information
for one individual across the entire tree sequence is extracted with `ts_ancestors()`, in order to
produce the data plotted in **B**–**D**. **(B)** A visualization of the tree extracted by `ts_phylo()` using
standard visualization features of the *ggplot2* and *ggtree* R packages. Dotted lines indicate
shortened branches of ancient samples. **(C)** Visualization of the tree from panel **B** as a network

across the original spatial simulation landscape, with each node indicating the location of a particular individual who lived at some point during the simulation. Labels with two numbers correspond to the locations of sampled individuals, each carrying two chromosomes which are represented by two nodes in the tree sequence. All node numbers correspond to those shown in the tree in panel **B**. The plot was generated with *ggplot2* using the *sf*-formatted data extracted by `ts_nodes()` and `ts_edges()`. **(D)** A visualization of the spatio-temporal ancestry of a single simulated European individual, "EUR_581", using the information from the entire tree sequence. Each sub-panel shows the spatial ancestry distribution of one of the two chromosomes carried by this individual (the location of whom is indicated by a black dot), tracing its ancestry through different lineages all the way back to a population in Africa. For easier reference, the same black dots indicate the two chromosomes of this individual also in the tree in panel **B**. The *ggplot2* code for the figures is omitted for brevity. Full reproducible code examples including the visualization code can be found in a vignette dedicated to this paper at www.slendr.net.

Discussion

The *slendr* R package provides a new programmable framework for simulating complex spatio-temporal genomic data. The package implements a set of features for defining spatial population range dynamics with a declarative and visually-focused R interface and uses a tailor-made SLiM script as an efficient population genetic simulation engine. Additionally, *slendr* provides a convenient new way to simulate and analyze large-scale genomic data sets even from traditional, non-spatial demographic models using *msprime* entirely within the R environment.

Owing to its declarative interface, which requires little code even for complex models, the *slendr* package is highly accessible even to researchers or students with little or no prior experience in programming. One of the major challenges for novice population geneticists is having to learn how to integrate multiple different software tools and programming frameworks. R (R Core Team, 2021) is often the first language that biology and bioinformatics students learn, since it offers a large number of libraries for data analysis, statistics, and plotting (Wickham and Grolemund, 2016). For these users, *slendr* provides the opportunity to explore population genetic concepts and simulate realistic population genomic data as soon as they learn the most basic principles of R (i.e., how to call R functions and work with data frames), without first having to learn Python for *msprime* simulations (Baumdicker *et al.*, 2022), shell scripting for simulators from the *ms* family (Hudson, 2002; Staab *et al.*, 2015), or Eidos for SLiM (Haller and Messer, 2019).

Tree sequences provide an efficient way to compute many commonly used population genetic statistics directly on the simulated genealogies (Ralph, Thornton and Kelleher, 2020); because *slendr* uses the tree sequence as its default output format (Kelleher *et al.*, 2018; Haller *et al.*, 2019), in many cases users do not need to convert simulation outputs to external file formats such as VCF or EIGENSTRAT for analysis in other software. This way, *slendr* simulations can be readily used in model fitting and population genetic analyses in situations which have traditionally required converting simulated data to genotype files before analyzing them with population genetics tools such as PLINK (Purcell *et al.*, 2007) or ADMIXTOOLS (Patterson *et al.*, 2012). That said, export to VCF and EIGENSTRAT genotype file formats is supported with a single function call (`ts_vcf()` and `ts_eigenstrat()`) if needed.

A key principle in the design of *slendr* has been reproducibility (Sandve *et al.*, 2013): a complete *slendr* simulation and analysis workflow can be written as a single R script. Additionally,

the compilation of any *slendr* module produces a self-contained "bundle directory" containing all
model configuration files and simulation back-end scripts required to execute the model from the
command-line. Although accessing this directory is not necessary for standard workflows because
slendr operates entirely from R, these bundles can be checked into a git history and provided as
supplementary files along with a publication, allowing independent replication even without relying
on *slendr* itself.

Moving forward, we expect that the *slendr* framework will become a useful tool for
comparing and benchmarking inference methods for modeling spatial genomic processes (Peter
and Slatkin, 2013; Petkova, Novembre and Stephens, 2016; Marcus *et al.*, 2021; Muktupavela *et*
al., 2021). It will also enable the development of new approaches to spatial problems in population
genomics. There is great potential for deploying *slendr* in simulation-based inference methods,
especially thanks to its tight integration with the rest of the R modeling landscape, including
methods such as Approximate Bayesian Computation (Beaumont, Zhang and Balding, 2002).
However, as population genetic modeling is notoriously challenging due to the many parameters
involved in inference (population divergence times, times and magnitudes of gene-flow events
and population size changes, etc.) (Gravel *et al.*, 2011; Pickrell and Pritchard, 2012; Kamm *et al.*,
2020), care will have to be taken to ameliorate the curse of dimensionality.

In its current version, *slendr*'s spatial simulation maps are limited to landscapes that exhibit
binary habitability—i.e., any given location either is or is not habitable by individuals, without any
intermediate degrees of habitability. Future extensions of the *slendr* framework could include the
incorporation of fine-scaled geographic raster maps which would affect local carrying capacities
and influence population movements by introducing a cost of occupying a particular location. This
extension would require significant changes to the *slendr* back-end code, moving to modeling
population densities per unit of landscape area using non-Wright–Fisher dynamics, but the
necessary software building blocks are already supported by SLiM (Haller and Messer, 2019). A
recently published Python module *Geonomics* provides a similar possibility of population genetic
simulations on arbitrary landscape rasters (Terasaki Hart, Bishop and Wang, 2021). Implementing
such functionality in *slendr* would have the advantage of using a much more efficient SLiM
simulation engine and a greater ease of use due to *slendr*'s emphasis on visually-focused
interactive model design in R. The main challenge would therefore lie in making sure that the
additional complexity involved in making the *slendr*'s SLiM back end more flexible does not
compromise the current simplicity of its declarative interface. The benefits of this extension would
be numerous, including for genomic forecasting and predicting species ranges in the face of
climate change and ecological breakdown (Fitzpatrick and Keller, 2015; Exposito-Alonso *et al.*,
2019; Theodoridis *et al.*, 2020), and for constructing models of species distribution dynamics in
the ancient past (Wang *et al.*, 2021).

At the moment, *slendr* can only produce genome sequences from populations of a single
species due to the restrictions imposed by its simulation back end. However, many types of
genomic resources distributed across space and time are represented by fragmentary mixtures
of genomes from multiple species. This includes ancient microbiomes from human remains
(Rasmussen *et al.*, 2015), sedimentary DNA from permafrost, caves, or lake and marine cores
(Willerslev *et al.*, 2003; Parducci *et al.*, 2017; Armbrecht *et al.*, 2019; Vernot *et al.*, 2021), and
environmental DNA from water, soil, or air samples (Taberlet *et al.*, 2012; Stat *et al.*, 2017;
Lynggaard *et al.*, 2022). Latest developments in SLiM suggest a fruitful avenue for *slendr* in the

form of multi-species simulations. This would facilitate ecological modeling of species distributions
(Fordham *et al.*, 2021) or of past epidemics (Duchene *et al.*, 2020) from a fully genomic
perspective.
Ultimately, we hope that our new simulation framework will help generate new ideas about
the insights that can be gleaned from the rich spatio-temporal information hidden within DNA
sequences. Furthermore, we aspire to help budding researchers in population genetics get started
with simulations and build their intuition about population genetic concepts by developing models
using more traditional non-spatial methods and statistics, and we believe that *slendr* could be a
useful tool for teaching population genetics to students. We hope that by easily generating and
visualizing genomic models on real landscapes, we can spark new ways of thinking about how
organisms evolve (Bradburd and Ralph, 2019) and enable clearer discussions about the
fundamental interconnectedness of genomes across space and time (Mathieson and Scally,
2020).

Acknowledgements
693

We thank Moisès Coll Macià and Mariadaria Kathrine Ianni-Ravn for testing and feedback on
early versions of *slendr*, and the members of the Racimo group for valuable comments on the
design of the software and this manuscript. FR was supported by a Villum Young Investigator
Grant (project no. 00025300). MP was supported by a Lundbeck Foundation grant (R302-2018-
2155) and a Novo Nordisk Foundation grant (NNF18SA0035006) given to the GeoGenetics
Centre. PR was supported by NIH award R01HG010774.

References
700

1000 Genomes Project (2010) 'A map of human genome variation from population-scale
sequencing', *Nature*, 467(7319), pp. 1061–1073.

Al-Asadi, H. *et al.* (2019) 'Estimating recent migration and population-size surfaces', *PLoS*
genetics, 15(1), p. e1007908.

Allentoft, M.E. *et al.* (2015) 'Population genomics of Bronze Age Eurasia', *Nature*, 522(7555),
pp. 167–172.

Armbrecht, L.H. *et al.* (2019) 'Ancient DNA from marine sediments: Precautions and
considerations for seafloor coring, sample handling and data generation', *Earth-Science*
Reviews, 196, p. 102887.

Barton, N. (1979) 'Gene flow past a cline', *Heredity*, 43(3), pp. 333–339.

Barton, N., Depaulis, F. and Etheridge, A.M. (2002) 'Neutral evolution in spatially continuous
populations', *Theoretical population biology*, 61(1), pp. 31–48.

Barton, N., Etheridge, A.M. and Véber, A. (2013) 'Modelling evolution in a spatial continuum',
Journal of Statistical Mechanics: Theory and Experiment, 2013(01), p. P01002.

Barton, N., Etheridge, A. and Véber, A. (2010) 'A New Model for Evolution in a Spatial
Continuum', *Electronic Journal of Probability*, 15.

Baumdicker, F. *et al.* (2022) 'Efficient ancestry and mutation simulation with msprime 1.0',
Genetics, 220(3). doi:10.1093/genetics/iyab229.

Beaumont, M.A., Zhang, W. and Balding, D.J. (2002) 'Approximate Bayesian computation in
population genetics', *Genetics*, 162(4), pp. 2025–2035.

Beerli, P. and Felsenstein, J. (2001) 'Maximum likelihood estimation of a migration matrix and
effective population sizes in n subpopulations by using a coalescent approach', *Proceedings of*
the National Academy of Sciences of the United States of America, 98(8), pp. 4563–4568.

Bergström, A. *et al.* (2020) 'Origins and genetic legacy of prehistoric dogs', *Science*, 370(6516),
pp. 557–564.

Bradburd, G.S., Coop, G.M. and Ralph, P.L. (2018) 'Inferring Continuous and Discrete
Population Genetic Structure Across Space', *Genetics*, 210(1), pp. 33–52.

Bradburd, G.S. and Ralph, P.L. (2019) 'Spatial population genetics: It's about time', *Annual*
review of ecology, evolution, and systematics, 50(1), pp. 427–449.

Chambers, J.M. (2020) 'S, R, and data science', *Proceedings of the ACM on Programming*
Languages, pp. 1–17. doi:10.1145/3386334.

Chang, W. *et al.* (2021) *shiny: Web Application Framework for R*. Available at: https://CRAN.R-
project.org/package=shiny.

Crabtree, S.A. *et al.* (2021) 'Landscape rules predict optimal superhighways for the first
peopling of Sahul', *Nature human behaviour*, 5(10), pp. 1303–1313.

Currat, M. *et al.* (2019) 'SPLATCHE3: simulation of serial genetic data under spatially explicit
evolutionary scenarios including long-distance dispersal', *Bioinformatics* , 35(21), pp. 4480–
4483.

Currat, M. and Excoffier, L. (2011) 'Strong reproductive isolation between humans and
Neanderthals inferred from observed patterns of introgression', *Proceedings of the National*
Academy of Sciences, 108(37), pp. 15129–15134.

Currat, M., Ray, N. and Excoffier, L. (2004) 'splatche: a program to simulate genetic diversity
taking into account environmental heterogeneity', *Molecular ecology notes*, 4(1), pp. 139–142.

Danecek, P. *et al.* (2011) 'The variant call format and VCFtools', *Bioinformatics* , 27(15), pp.
2156–2158.

Delser, P.M. *et al.* (2021) 'Climate and mountains shaped human ancestral genetic lineages',
bioRxiv. doi:10.1101/2021.07.13.452067.

Duchene, S. *et al.* (2020) 'Temporal signal and the phylodynamic threshold of SARS-CoV-2',
Virus evolution, 6(2), p. veaa061.

Duforet-Frebourg, N. and Blum, M.G.B. (2014) 'Nonstationary patterns of isolation-by-distance:
inferring measures of local genetic differentiation with Bayesian kriging', *Evolution; international*

journal of organic evolution, 68(4), pp. 1110–1123.

Ewing, G. and Hermisson, J. (2010) 'MSMS: a coalescent simulation program including
recombination, demographic structure and selection at a single locus', *Bioinformatics* , 26(16),
pp. 2064–2065.

Exposito-Alonso, M. *et al.* (2019) 'Natural selection on the Arabidopsis thaliana genome in
present and future climates', *Nature*, 573(7772), pp. 126–129.

Felsenstein, J. (1975) 'A Pain in the Torus: Some Difficulties with Models of Isolation by
Distance', *The American naturalist*, 109(967), pp. 359–368.

Feuerborn, T.R. *et al.* (2021) 'Modern Siberian dog ancestry was shaped by several thousand
years of Eurasian-wide trade and human dispersal', *Proceedings of the National Academy of
Sciences of the United States of America*, 118(39). doi:10.1073/pnas.2100338118.

Fisher, R.A. (1937) 'The wave of advance of advantageous genes', *Annals of eugenics*, 7(4),
pp. 355–369.

Fitzpatrick, M.C. and Keller, S.R. (2015) 'Ecological genomics meets community-level modelling
of biodiversity: mapping the genomic landscape of current and future environmental adaptation',
Ecology letters, 18(1), pp. 1–16.

Fordham, D.A. *et al.* (2021) 'poems: R package for simulating species' range dynamics using
pattern-oriented validation', *Methods in ecology and evolution / British Ecological Society*,
12(12), pp. 2364–2371.

Frachetti, M.D. *et al.* (2017) 'Nomadic ecology shaped the highland geography of Asia's Silk
Roads', *Nature*, 543(7644), pp. 193–198.

Fu, Q. *et al.* (2016) 'The genetic history of Ice Age Europe', *Nature*, 534(7606), pp. 200–205.

Gravel, S. *et al.* (2011) 'Demographic history and rare allele sharing among human populations',
Proceedings of the National Academy of Sciences, 108(29), pp. 11983–11988.

Green, R.E. *et al.* (2010) 'A draft sequence of the Neandertal genome', *Science*, 328(5979), pp.
710–722.

Guillot, G. *et al.* (2009) 'Statistical methods in spatial genetics', *Molecular ecology*, 18(23), pp.
4734–4756.

Haak, W. *et al.* (2015) 'Massive migration from the steppe was a source for Indo-European
languages in Europe', *Nature*, 522(7555), pp. 207–211.

Haller, B.C. *et al.* (2019) 'Tree-sequence recording in SLiM opens new horizons for forward-time
simulation of whole genomes', *Molecular ecology resources*, 19(2), pp. 552–566.

Haller, B.C. and Messer, P.W. (2017) 'SLiM 2: Flexible, Interactive Forward Genetic
Simulations', *Molecular biology and evolution*, 34(1), pp. 230–240.

Haller, B.C. and Messer, P.W. (2019) 'SLiM 3: Forward Genetic Simulations Beyond the Wright-
Fisher Model', *Molecular biology and evolution*, 36(3), pp. 632–637.

Hanks, E.M. and Hooten, M.B. (2013) 'Circuit theory and model-based inference for landscape
connectivity', *Journal of the American Statistical Association*, 108(501), pp. 22–33.

Hudson, R.R. (2002) 'Generating samples under a Wright-Fisher neutral model of genetic
variation', *Bioinformatics* , 18(2), pp. 337–338.

Kamm, J. *et al.* (2020) 'Efficiently inferring the demographic history of many populations with
allele count data', *Journal of the American Statistical Association*, 115(531), pp. 1472–1487.

Kelleher, J. *et al.* (2018) 'Efficient pedigree recording for fast population genetics simulation',
PLoS computational biology, 14(11), p. e1006581.

Kelleher, J. *et al.* (2019) 'Inferring whole-genome histories in large population datasets', *Nature*
genetics, 51(9), pp. 1330–1338.

Kelleher, J., Etheridge, A.M. and Barton, N.H. (2014) 'Coalescent simulation in continuous
space: algorithms for large neighbourhood size', *Theoretical population biology*, 95, pp. 13–23.

Kelleher, J., Etheridge, A.M. and McVean, G. (2016) 'Efficient Coalescent Simulation and
Genealogical Analysis for Large Sample Sizes', *PLoS computational biology*, 12(5), p.
e1004842.

Kimura, M. (1953) '"Stepping Stone" model of population', *Annual report of the National Institute*
of Genetics , 3, pp. 62–63.

Kimura, M. and Weiss, G.H. (1964) 'The Stepping Stone Model of Population Structure and the
Decrease of Genetic Correlation with Distance', *Genetics*, 49(4), pp. 561–576.

Lazaridis, I. *et al.* (2014) 'Ancient human genomes suggest three ancestral populations for
present-day Europeans', *Nature*, 513(7518), pp. 409–413.

Levene, H. (1953) 'Genetic Equilibrium When More Than One Ecological Niche is Available',
The American naturalist, 87(836), pp. 331–333.

Librado, P. *et al.* (2021) 'The origins and spread of domestic horses from the Western Eurasian
steppes', *Nature*, pp. 1–7.

Liu, H. *et al.* (2006) 'A geographically explicit genetic model of worldwide human-settlement
history', *American journal of human genetics*, 79(2), pp. 230–237.

Loog, L. *et al.* (2017) 'Estimating mobility using sparse data: Application to human genetic
variation', *Proceedings of the National Academy of Sciences*, 114(46), pp. 12213–12218.

Lovelace, R., Nowosad, J. and Muenchow, J. (2019) *Geocomputation with R (Chapman &*
Hall/CRC The R Series). 1st edn. Routledge.

Lynggaard, C. *et al.* (2022) 'Airborne environmental DNA for terrestrial vertebrate community
monitoring', *Current biology: CB*, 32(3), pp. 701–707.e5.

Malécot, G. (1951) 'Un traitement stochastique des problèmes linéaires en génétique de
population', *Ann. Univ. Lyon. Sci. Sec.*, 14, pp. 79–117.

Mallick, S. *et al.* (2016) 'The Simons Genome Diversity Project: 300 genomes from 142 diverse

populations', *Nature*, 538(7624), pp. 201–206.

Marcus, J. *et al.* (2021) 'Fast and flexible estimation of effective migration surfaces', *eLife*, 10.
doi:10.7554/eLife.61927.

Mathieson, I. and Scally, A. (2020) 'What is ancestry', *PLoS genetics*, 16(3), p. e1008624.

McRae, B.H. (2006) 'Isolation by resistance', *Evolution; international journal of organic*
evolution, 60(8), pp. 1551–1561.

Meyer, M. *et al.* (2017) 'Palaeogenomes of Eurasian straight-tusked elephants challenge the
current view of elephant evolution', *eLife*, 6, p. e25413.

Muktupavela, R. *et al.* (2021) 'Modelling the spatiotemporal spread of beneficial alleles using
ancient genomes', *bioRxiv*. doi:10.1101/2021.07.21.453231.

Nagylaki, T. (1976) 'The relation between distant individuals in geographically structured
populations', *Mathematical biosciences*, 28(1), pp. 73–80.

Osmond, M.M. and Coop, G. (2021) 'Estimating dispersal rates and locating genetic ancestors
with genome-wide genealogies', *bioRxiv*. doi:10.1101/2021.07.13.452277.

Palkopoulou, E. *et al.* (2018) 'A comprehensive genomic history of extinct and living elephants',
Proceedings of the National Academy of Sciences of the United States of America, 115(11), pp.
E2566–E2574.

Paradis, E. (2011) *Analysis of Phylogenetics and Evolution with R (Use R!)*. 2nd edn. Springer.

Paradis, E. and Schliep, K. (2019) 'ape 5.0: an environment for modern phylogenetics and
evolutionary analyses in R', *Bioinformatics* . Edited by R. Schwartz, 35(3), pp. 526–528.

Parducci, L. *et al.* (2017) 'Ancient plant DNA in lake sediments', *The New phytologist*, 214(3),
pp. 924–942.

Patterson, N. *et al.* (2012) 'Ancient admixture in human history', *Genetics*, 192(3), pp. 1065–
1093.

Pebesma, E. (2018) 'Simple features for R: Standardized support for spatial vector data', *The R*
journal, 10(1), p. 439.

Peter, B.M. and Slatkin, M. (2013) 'Detecting range expansions from genetic data', *Evolution;*
international journal of organic evolution, 67(11), pp. 3274–3289.

Petkova, D., Novembre, J. and Stephens, M. (2016) 'Visualizing spatial population structure with
estimated effective migration surfaces', *Nature genetics*, 48(1), pp. 94–100.

Pickrell, J.K. and Pritchard, J.K. (2012) 'Inference of Population Splits and Mixtures from
Genome-Wide Allele Frequency Data', *PLoS genetics*. Edited by H. Tang, 8(11), p. e1002967.

Pickrell, J.K. and Reich, D. (2014) 'Toward a new history and geography of human genes
informed by ancient DNA', *Trends in genetics: TIG*, 30(9), pp. 377–389.

Purcell, S. *et al.* (2007) 'PLINK: a tool set for whole-genome association and population-based

linkage analyses', *American journal of human genetics*, 81(3), pp. 559–575.

Racimo, F. *et al.* (2020) 'The spatiotemporal spread of human migrations during the European
Holocene', *Proceedings of the National Academy of Sciences of the United States of America*,
117(16), pp. 8989–9000.

Ralph, P. and Coop, G. (2013) 'The Geography of Recent Genetic Ancestry across Europe',
PLoS biology. Edited by C. Tyler-Smith, 11(5), p. e1001555.

Ralph, P., Thornton, K. and Kelleher, J. (2020) 'Efficiently Summarizing Relationships in Large
Samples: A General Duality Between Statistics of Genealogies and Genomes', *Genetics*,
215(3), pp. 779–797.

Rasmussen, M. *et al.* (2010) 'Ancient human genome sequence of an extinct Palaeo-Eskimo',
Nature, 463(7282), pp. 757–762.

Rasmussen, S. *et al.* (2015) 'Early divergent strains of Yersinia pestis in Eurasia 5,000 years
ago', *Cell*, 163(3), pp. 571–582.

R Core Team (2021) 'R: A Language and Environment for Statistical Computing'. Vienna,
Austria: R Foundation for Statistical Computing. Available at: https://www.R-project.org/.

Ringbauer, H. *et al.* (2018) 'Estimating Barriers to Gene Flow from Distorted Isolation-by-
Distance Patterns', *Genetics*, 208(3), pp. 1231–1245.

Rousset, F. (1997) 'Genetic differentiation and estimation of gene flow from F-statistics under
isolation by distance', *Genetics*, 145(4), pp. 1219–1228.

Safner, T. *et al.* (2011) 'Comparison of Bayesian clustering and edge detection methods for
inferring boundaries in landscape genetics', *International journal of molecular sciences*, 12(2),
pp. 865–889.

Sandve, G.K. *et al.* (2013) 'Ten simple rules for reproducible computational research', *PLoS
computational biology*, 9(10), p. e1003285.

Slatkin, M. (1973) 'GENE FLOW AND SELECTION IN A CLINE', *Genetics*, 75(4), pp. 733–756.

Slatkin, M. and Excoffier, L. (2012) 'Serial founder effects during range expansion: a spatial
analog of genetic drift', *Genetics*, 191(1), pp. 171–181.

Slatkin, M. and Racimo, F. (2016) 'Ancient DNA and human history', *Proceedings of the
National Academy of Sciences*, 113(23), pp. 6380–6387.

Speidel, L. *et al.* (2019) 'A method for genome-wide genealogy estimation for thousands of
samples', *Nature genetics*, 51(9), pp. 1321–1329.

Staab, P.R. *et al.* (2015) 'scrm: efficiently simulating long sequences using the approximated
coalescent with recombination', *Bioinformatics* , 31(10), pp. 1680–1682.

Stat, M. *et al.* (2017) 'Ecosystem biomonitoring with eDNA: metabarcoding across the tree of life
in a tropical marine environment', *Scientific reports*, 7(1), p. 12240.

Taberlet, P. *et al.* (2012) 'Towards next-generation biodiversity assessment using DNA

metabarcoding', *Molecular ecology*, 21(8), pp. 2045–2050.

Terasaki Hart, D.E., Bishop, A.P. and Wang, I.J. (2021) 'Geonomics: Forward-Time, Spatially
Explicit, and Arbitrarily Complex Landscape Genomic Simulations', *Molecular biology and*
evolution, 38(10), pp. 4634–4646.

Theodoridis, S. *et al.* (2020) 'Evolutionary history and past climate change shape the distribution
of genetic diversity in terrestrial mammals', *Nature communications*, 11(1), p. 2557.

Vernot, B. *et al.* (2021) 'Unearthing Neanderthal population history using nuclear and
mitochondrial DNA from cave sediments', *Science*, 372(6542). doi:10.1126/science.abf1667.

Wang, Y. *et al.* (2021) 'Late Quaternary dynamics of Arctic biota from ancient environmental
genomics', *Nature*, 600(7887), pp. 86–92.

Wickham, H. *et al.* (2019) 'Welcome to the tidyverse', *Journal of Open Source Software*, p.
1686. doi:10.21105/joss.01686.

Wickham, H. and Grolemund, G. (2016) *R for Data Science*. ``O'Reilly Media, Inc.'', p. 520.

Willerslev, E. *et al.* (2003) 'Diverse plant and animal genetic records from Holocene and
Pleistocene sediments', *Science*, 300(5620), pp. 791–795.

Wohns, A.W. *et al.* (2022) 'A unified genealogy of modern and ancient genomes', *Science*,
375(6583), p. eabi8264.

Wright, S. (1943) 'Isolation by Distance', *Genetics*, 28(2), pp. 114–138.

Yu, G. *et al.* (2017) 'ggtree : An R package for visualization and annotation of phylogenetic trees
with their covariates and other associated data', *Methods in ecology and evolution / British*
Ecological Society, 8(1), pp. 28–36.