Humans Adapt Multi-Objective Control of Stepping To Perform Lateral Maneuvers While Walking

Short Title: Adapting Stepping to Laterally Maneuver

David M. Desmet [1], Joseph P. Cusumano [2], and Jonathan B. Dingwell [1,*]

[1] Department of Kinesiology, Pennsylvania State University, University Park, Pennsylvania, United States of America

[2] Department of Engineering Science & Mechanics, Pennsylvania State University, University Park, Pennsylvania, United States of America

* Corresponding Author:

Department of Kinesiology   Phone: 1-814-865-7761
276 Recreation Building   Email: dingwell@psu.edu
Pennsylvania State University   Web: http://biomechanics.psu.edu/
University Park, PA 16802

ABSTRACT [294 Words – Max = 300]

To successfully traverse their environment, humans must often perform maneuvers to achieve desired task

goals while simultaneously maintaining balance. Humans accomplish these tasks primarily by modulating

their foot placements. As humans are more unstable laterally, we must better understand how humans

modulate lateral foot placement. We previously developed a theoretical framework and corresponding

computational models to describe how humans regulate lateral stepping during straight-ahead continuous

walking. This framework yields goal functions for step width and lateral body position that define the walking

task and determine the set of all possible task solutions as Goal Equivalent Manifolds (GEMs). Here, we used

this framework to determine if humans can regulate lateral stepping during *non*-steady-state lateral maneuvers

by minimizing errors in accordance with these goal functions. Twenty young healthy adults each performed

four lateral lane-change maneuvers in a virtual reality environment. Within our general lateral stepping

regulation framework, we first re-examined the requirements of such transient walking tasks. Doing so

yielded new theoretical predictions regarding how steps during any such maneuver should be regulated to

minimize error costs, consistent with the goals required at each step and with how these costs are adapted at

each step during the maneuver. Humans performed the experimental lateral maneuvers in a manner

consistent with our theoretical predictions. Furthermore, their stepping behavior was well modeled by merely

adapting the parameters of our previous lateral stepping models from step to step. To our knowledge, our

results are the first to demonstrate humans can use evolving cost landscapes in real time to perform such an

adaptive motor task and, furthermore, that such adaptation can occur quickly – over only one step. Thus, the

predictive capabilities of our general stepping regulation framework extend to a much greater range of

walking tasks beyond just normal, straight-ahead walking.

AUTHOR SUMMARY [167 Words – Range = 150-200]

When we walk in the real world, we rarely walk continuously in a straight line. Indeed, we regularly have to

perform other tasks like stepping aside to avoid an obstacle in our path (either fixed or moving, like another

person coming towards us). While we have to be highly maneuverable to accomplish such tasks, we must also

remain stable to avoid falling while doing so. This is challenging because walking humans are inherently

more unstable side-to-side. Sideways falls are particularly dangerous for older adults as they can lead to hip

fractures. Here, we establish a theoretical basis for how people can accomplish such maneuvers. We show that

humans execute a simple lateral lane-change maneuver consistent with our theoretical predictions.

Importantly, we show that they can do so using simple adaptations of the same step-to-step regulation

strategies they use to walk in a straight line. Moreover, these same control processes also explain how humans

trade-off side-to-side stability to gain the maneuverability they need to perform such lateral maneuvers.

INTRODUCTION

To successfully traverse our environment, we humans must adapt to a wide variety of environment contexts

and changing task goals (e.g., Fig. 1A), all while maintaining balance. Indeed, humans readily avoid obstacles

[2] and/or other humans [3], step to targets [4-6], move laterally [7-9], navigate complex terrain [10-12], and

respond to destabilizing perturbations [13, 14]. To do so requires a high degree of maneuverability [7] and,

potentially, the ability to trade-off stability for maneuverability [8, 9]. While maneuverability has been widely

studied in animal locomotion [15, 16] and robotics [16, 17], far less is known about how humans accomplish

such tasks.

Humans accomplish these sorts of adaptive walking tasks primarily by modulating their foot placements.

Appropriate foot placement at each step can redirect center-of-mass accelerations and thus allows humans to

maintain balance [18-21]. This is especially important in the lateral direction where humans are thought to be

more unstable [19, 22, 23]. Indeed, laterally-directed falls are particularly injurious in older adults [24, 25].

Thus, it is important to better understand how humans adapt their lateral foot placements to maintain balance

while simultaneously achieving walking task goals.

Human walking exhibits considerable variability [26, 27], redundancy (i.e., the body has more mechanical

degrees of freedom than necessary to perform any movement) [28], and equifinality (i.e., humans can perform

most tasks an infinite number of ways) [29-31]. Computational models are necessary to fully understand how

humans perform accurate, goal-directed walking movements in the context of these challenges. Most prior

models of human walking (e.g., [22, 23, 32, 33]) address within-step "control," defined here as the processes

that drive the dynamics of each step to remain viable (i.e., to prevent falling) [34]. While ensuring viability is

indeed necessary to walk [35], it is not sufficient: humans engage in *purposeful* walking with a destination to

reach and/or other tasks to achieve. Control models that "just walk" (i.e., remain viable) do not address how

humans achieve such goal-directed walking.

We posit that locomotion is functionally hierarchical, consisting of both within-step control and step-to-step

regulation. To compliment within-step control models, we developed a motor regulation framework to

determine how humans adjust successive stepping movements [1, 29, 34, 36]. For a given walking task (e.g.,

Fig. 1A), this framework proposes goal functions that theoretically define the task and, accounting for

equifinality, determine the set of all possible task solutions as Goal Equivalent Manifolds (GEMs) [37-40].

The goal functions are incorporated into task-level costs, which we then use in an optimal control formalism

[41, 42] to generate relatively simple, phenomenological models of step-to-step motor regulation (i.e., "motor

regulation templates" [1, 29, 30]). For any proposed goal function, these templates predict how humans

would attempt to drive that goal function to zero at the next step, thus achieving perfect task performance on

average. For an appropriate choice of goal functions, these models successfully replicate human step-to-step

Figure 1. Defining Relevant Lateral Stepping Variables. A) Examples of people walking in common contexts that require adaptability, including walking on a winding path and avoiding an obstacle. B-C) Configuration of bipedal walking in both the frontal (B) and horizontal (C) planes. Coordinates are defined in a Cartesian system with $\{x,y,z\}$ axes shown in (B) and (C) and the origin defined as the geometric center of the available walking surface. The lateral positions of the left and right feet $\{z_L, z_R\}$ are used to derive the primary lateral stepping variables that are regulated from step-to-step: step width ($w = z_R - z_L$) and lateral body position ($z_B = \frac{1}{2}(z_L + z_R)$) [1].

dynamics in both the fore-aft [29] and lateral [1] directions. In the lateral direction in particular, multi-

objective regulation of primarily step width (w) and secondarily lateral position (z_B) captures human step-to-

step dynamics during continuous straight-ahead walking (Fig. 1B-C) [1, 13, 43]. Whether explicit models are

constructed or not, this overall theory and its hierarchical control/regulation schema provides a powerful

framework from which to interpret experimental results [13, 31, 43-50].

However, humans rarely perform long bouts of straight-ahead, continuous walking [51, 52]. Instead, humans

must frequently perform adaptive locomotor behaviors (i.e., maneuvers) when walking in the real world (e.g.,

Fig. 1A) [7-9]. Indeed, older adults often fall during such maneuvers because they incorrectly transfer their

body weight or they trip [53]. Because both such causes can be prevented with appropriate foot placement

[18-21], it is necessary to better understand how humans regulate foot placement as they execute typical

lateral maneuvers. Here, we aimed to determine how humans regulate their stepping during a simple lateral

maneuver: namely, a single lateral lane-change transition between periods of straight-ahead walking.

It is not clear *a priori* that our previous lateral stepping regulation framework can also emulate human

stepping during lateral maneuvers. This framework was originally developed to model straight-ahead steady-

state walking, under assumptions that step-to-step adjustments can be made without changing the fundamental

structure of within-step control, and that deviations from perfect performance are small. These assumptions

motivated us to select low-dimensional, single-step, linear regulators to model these step-to-step error-

correcting processes [1, 29, 30]. However, walking tasks requiring substantial *non*-steady-state lateral

maneuvers would seem to violate these assumptions. Lateral maneuvers that introduce large deviations from

steady-state might, for example, require changes to the within-step control structure, or induce substantial

nonlinearity. Lateral maneuvers might also require substantially greater impulses to execute, which may

necessitate additional compensatory motor and/or kinematic contributions and could result in higher

dimensionality. Furthermore, humans have been shown plan maneuvers more than one step in advance in

some contexts [54-57], which suggests the possible need for models that depend on more than one prior step.

Thus, one might reasonably posit that humans regulate stepping using entirely different control schemes when

executing lateral maneuvers far from steady state.

However, here we demonstrate that humans do indeed regulate lateral stepping during non-steady-state lateral

maneuvers in a manner consistent with our previous theoretical framework. We first apply concepts from the

general theory in a manner that satisfies the requirements of a non-steady-state lane change maneuver.

Specifically, we allow the task goals, task-level costs, and the weighting between competing costs to *adapt*

from each step to the next. We thus derive a model that yields explicit, empirically-testable predictions about

how the variability observed during such lateral maneuver tasks will be structured from step to step. We then

test these predictions against human experimental data. Lastly, we used the models with these additional

adaptive hierarchical elements to simulate how such lateral maneuvers are achieved over a sequence of steps.

In doing so, we demonstrate how humans modulate their stepping to trade-off lateral stability for

maneuverability to accomplish the lane change task. Thus, our hierarchical motor regulation framework can

be applied to a far wider range of walking tasks beyond just straight-ahead, steady-state walking.

RESULTS

Lateral Maneuvers in Humans

We analyzed data from a prior study conducted in our laboratory [58]. Young healthy participants walked in a

virtual reality environment. They walked on one of two parallel paths, the centers of which were 0.6m apart,

projected onto a 1.2m wide motorized treadmill (Fig. 2A). Following an audible cue, they executed a lateral

maneuver from the path they were walking on over to the adjacent path. Importantly, participants were given

no explicit instructions about how to execute this maneuver. We analyzed seventy-nine total maneuvers from

twenty participants.

Participants variably took 0-to-3 steps between the cue and initiating the maneuver (Fig. 2A[i-ii]). However,

once initiated, they performed each maneuver consistently (Fig. 2A[iii]-B). Participants completed nearly all

maneuvers with an ipsilateral transition step that involved a single, large step to reach the new path. One

participant, however, completed one of their maneuvers by taking a large cross-over step. Additionally, one

maneuver from another participant required three steps to reach the new path. These two non-conforming

Figure 2. Experimental Stepping Time Series and Errors. A) Time series of left (z_L; blue) and right (z_R; red) foot placements for (i) 38 transitions when the cue was given on a contralateral step relative to the direction of transition, (ii) 41 transitions when the cue was given on an ipsilateral step relative to the direction of transition, and (iii) all 79 transitions with respect to the initiation of the transition, defined as the last step taken on the original path. In (i)-(ii), the black dotted lines at step 0 indicate the onset of the audible cue. All transitions are plotted to appear from left to right. B) Time series of lateral position (z_B) and step width (w) for all transitions with respect to the initiation of the transition, with all transitions plotted to appear from left to right. C) Errors with respect to the stepping goals, [z_B^*, w^*]. For steps in the interval [-3, 0], z_B^* was defined as the experimental mean z_B during steady state walking before the transition. For steps in the interval [1, 7], z_B^* was defined as the experimental mean z_B during steady state walking after the transition. For all steps analyzed, w^* was defined as the experimental mean w during steady state walking. Error bars indicate experimental standard deviations at each step. Gray shaded regions indicate the mean standard deviation ($\pm$ 1) from all steady state walking steps.

maneuvers demonstrate that participants had many options: the task itself did not require them to complete the

maneuver in any specific way.

Participants completed nearly all lateral maneuvers in 4 non-steady-state steps. Participants first took a

"*preparatory*" step (step 0) prior to the transition, during which they slightly narrowed their step width and

incrementally moved towards the new path. They then took a large "*transition*" step (step 1) to cover most of

the transition distance. Participants took a subsequent "*recovery*" step (step 2) that again exhibited a slightly

narrowed step width. Participants then reached their final new goal position (step 3) and returned to steady-

state walking on their new path.

Steady-State Stepping Regulation Cannot Replicate Lateral Transitions

We first used our previous multi-objective model of lateral stepping regulation to test whether humans could

regulate stepping during lateral maneuvers using a constant regulation strategy like that used for continuous,

straight-ahead walking [1]. This model selects each new foot placement (z_L or z_R) as a weighted average of

independent predictions that minimize errors with respect to either a constant step width (w^*) or lateral

position (z_B^*) goal, consistent with multi-objective stochastic optimization of error costs with respect to these

two quantities (see Methods). For this model, the relative proportion of step width to lateral position

regulation was defined by ρ, where $\rho = 0$ indicates 100% z_B control (and hence, 100% weight on the z_B cost)

and $\rho = 1$ indicates 100% w control (100% weight on the w cost) [1]. This stepping regulation model

reproduced the key features of human stepping dynamics during continuous, straight-ahead walking for

constant values in the approximate range $0.89 \leq \rho \leq 0.97$ [1].

We assessed whether this model, with any constant value of ρ, could emulate the *non*-steady-state stepping

dynamics experimentally observed during the lateral maneuver task. We found that it was not capable of

doing so. The model did emulate steady-state stepping dynamics (Fig. 3C; Step -3) for constant values in the

range of approximately $0.83 \leq \rho \leq 0.92$, consistent with previous findings [1]. However, *no* simulations over

this range of ρ completed the lateral maneuver in the experimentally observed 4 steps (Fig. 3A-B; red).

Furthermore, while model simulations that weighted position and step width regulation similarly (i.e., $\rho \approx 0.5$)

approximately emulated average experimentally observed stepping time series and errors (Fig. 3A-B; blue),

they failed to emulate the stepping variability humans exhibited during either steady-state (Step -3) or

transition (Step 1) steps (Fig. 3C). Indeed, no single constant value of ρ emulated both steady-state and

transition stepping dynamics (Fig. 3C).

Re-Thinking Stepping Regulation for Non-Steady-State Tasks

Any biped (human, animal, robot, etc.) must enact step width and/or lateral position regulation via left and

right foot placement (Fig. 1C). The stepping goals, [z_B^*, w^*], which guide *steady-state* walking, individually

form diagonal, orthogonal Goal Equivalent Manifolds (GEMs) when plotted in the [z_L, z_R] plane (Fig. 4A) [1].

The intersection of these GEMs represents the multi-objective goal to maintain both z_B^* and w^* and therefore

defines the foot placement goal, [z_L^*, z_R^*], for the task. When viewed in this manner, it is evident that nearly

any substantive change in either stepping goal (i.e., Δz_B^* and/or Δw^*) will induce a diagonal shift of the

Figure 3. Constant Parameter Model Results. A) Simulated stepping time series (mean ± SD) of 1000 lateral transitions using the original, constant parameter model with $\rho = 0.90$ (red) and $\rho = 0.55$ (blue). For steps in the interval [-3, 0], we set z_B^* as the experimental mean z_B during steady state walking before the transition. For steps in the interval [1, 7], we set z_B^* as the experimental mean z_B during steady state walking after the transition. For all steps, w^* was defined as the experimental mean w during steady state walking. B) Stepping errors (mean ± SD) at each step relative to the stepping goals, $[z_B^*, w^*]$, for the same data as in (A). For both (A) and (B), gray bands indicate the middle 90% range from experimental data. C) Means and standard deviations of both regulated variables (z_B and w) during a steady state step (Step -3; left) and during the transition step (Step 1; right) for all values of $0 \leq \rho \leq 1$. Gray bands indicate 95% confidence intervals from the experimental data computed using bootstrapping. Green bands indicate ±1 standard deviation from 1000 model simulations at each value of ρ. Model simulations over the approximate range of $0.83 \leq \rho \leq 0.92$ fell within the experimental ranges for all variables for steady-state walking (Step -3; Left), as indicated by the region highlighted in yellow. However, no such range captured the experimental data during the transition step (Step 1; Right).

168   corresponding GEM(s) in the $[z_L, z_R]$ plane (Fig. 4A). This will necessitate corresponding changes in both left

169   *and* right foot placement, which therefore cannot be accomplished in a single step (Fig. 4A).

171   At minimum, two consecutive steps are required to execute nearly any maneuver involving some Δz_B^* and/or

Figure 4. Conceptual Depiction of Task Performance. A) When viewed in the $[z_L, z_R]$ plane, goals to maintain constant position (z_B^*) or step width (w^*) each form linear Goal Equivalent Manifolds (GEMs) that are diagonal to the z_L and z_R axes and orthogonal to each other. Any change from some initial (green) to final (blue) stepping goals, such as the theoretical rightward shift in z_B^* (Δz_B^*) and increase in w^* (Δw^*) depicted here, displaces these GEMs diagonally in the $[z_L, z_R]$ plane. This requires changes in both z_L and z_R to accomplish, and so cannot be achieved in any single step. B) At least two consecutive steps ($z_R \to z_L$, or $z_L \to z_R$) are required to accomplish a change in stepping goals (Δz_B^* and/or Δw^*). Both possible intermediate steps (labeled 'a' or 'b') have their own distinct stepping goals, $[z_B^*, w^*]$. C) An idealized four-step strategy, like that most commonly observed experimentally (Fig. 2), includes 3 intermediate steps, each with distinct stepping goals. D) Goal relevant deviations (δ_{zB} and δ_w) with respect to both the z_B^* and w^* GEMs. These deviations characterize the stepping distribution at a given step, reflecting the relative weighting of z_B and w regulation. E) During steady-state walking, humans exhibit stepping distributions strongly aligned to the w^* GEM, reflecting strong prioritization of step width over position regulation. For a two-step maneuver strategy (as in B), stepping distributions at the intermediate step are theoretically predicted to be approximately isotropic (i.e., nearly circular). F) For a four-step maneuver strategy with a large primary transition step and smaller preparatory and recovery steps (as in C), stepping distributions are theoretically predicted to be most isotropic at the primary transition step and intermediately isotropic at the preparatory and recovery steps.

Δw^* (Fig. 4B). The first step must be taken by either the left or right foot to either of two possible

intermediate foot placement goals in the $[z_L, z_R]$ plane (Fig. 4B). Indeed, we can derive exact stepping goals

for this intermediate step algebraically (see Methods). However, equifinality exists in both the number and

placements of steps that can be used to accomplish any Δz_B^* and/or Δw^* maneuver. For example, we

experimentally observed a four-step strategy to be most typical (Fig. 2). To represent such a strategy, we

incorporated (see Methods) a lateral offset (ε) for the preparatory and recovery steps and determined the foot

placements, $[z_L, z_R]$, and corresponding to transition stepping goals, $[z_B^*, w^*]$, at each of the corresponding

preparatory, transition, and recovery steps (Fig. 4C).

However, specifying these foot placements alone does not capture *how* any given biped might perform these

steps. Along any GEM, deviations tangent to the GEM are "goal equivalent" because they do *not* introduce

errors with respect to the goal. Conversely, deviations perpendicular to the GEM are "goal relevant" because

they *do* introduce such errors [29]. Humans typically exhibit greater variability along GEMs they exploit [37,

41, 42]. For multi-objective lateral stepping regulation, the $z_B{}^*$ and w^* GEMs are orthogonal (Fig. 4A). Thus,

goal equivalent deviations with respect to either GEM are goal relevant with respect to the other (Fig. 4D) [1].

Hence, the ratio of the δ_{z_B} and δ_w deviations with respect to both the $z_B{}^*$ and w^* GEMs theoretically reflects the

relative weighting of z_B and w regulation. For example, during steady-state walking, the distribution of human

steps is *anisotropic*: that is, the steps are strongly aligned along the w^* GEM (such that $\delta_{z_B}/\delta_w \gg 1$) because

humans heavily weight step width over position regulation [1].

When the stepping goals change (i.e., $\Delta z_B{}^*$ and/or Δw^*), our theoretical framework thus posits empirically

testable hypotheses about how these δ_{z_B}/δ_w ratios should also change at each step. For a minimum two-step

strategy (Fig. 4B), foot placement at the intermediate step should be as accurate as possible to minimize

stepping errors at the final step. Theoretically then, our framework predicts that stepping distributions at this

ideal intermediate step should not exhibit equifinality and hence would be approximately *isotropic* (i.e.,

circular), reflecting equal weighting of step width and position regulation (Fig. 4E). However, taking more

intermediate steps during any such $\Delta z_B{}^*$ and/or Δw^* maneuver reduces the accuracy required at each

individual step, as errors can be corrected at subsequent intermediate step(s) prior to reaching the final goal.

Our theory thus predicts that stepping distributions for multiple intermediate steps should be more isotropic

than at steady-state, but perhaps less than the ideal two-step case. For example, for a four-step strategy with a

large primary transition step and smaller preparatory and recovery steps (Fig. 4C), stepping distributions are

predicted to be most isotropic at the primary transition step and intermediately isotropic at the preparatory and

recovery steps (Fig. 4F).

We thus hypothesized that humans would regulate their stepping movements across these lane-change

maneuvers in accordance with these theoretical predictions. We tested this hypothesis by plotting

experimental data in the $[z_L, z_R]$ plane and fitting 95% prediction ellipses to the data for each relevant step

(Fig. 5). During steady-state walking both before and after the maneuver, participants' steps were strongly

aligned to the constant-w^* GEM (Fig. 5A), consistent with the expected strong prioritization of step width

regulation [1]. During each of the preparatory, transition, and recovery steps, the locations of the experimental

stepping distributions were consistent with the intersections of the predicted $z_B{}^*$ and w^* GEMs at each step

(Fig. 5B). Furthermore, the experimental stepping distributions themselves (Fig. 5C) were qualitatively

consistent with our theoretical predictions (Fig. 4F). The fitted 95% prediction ellipses at the preparatory and

Figure 5. Experimental Stepping Distributions. A) Experimental stepping data during the steady state periods before and after the transition projected onto the $[z_L, z_R]$ plane. These data were pooled across 16 steady-state steps before and after the transition from 20 participants performing 4 transitions each (1280 steps total). The diagonal dotted lines indicate the initial and final constant-$z_B{}^*$ (downward sloping) and constant-w^* (upward sloping) GEMs. B) Experimental stepping data during the preparatory, transition, and recovery steps from 78 analyzed transitions projected onto the $[z_L, z_R]$ plane, plotted to appear from left to right. The diagonal dotted lines indicate the predicted constant-$z_B{}^*$ and constant-w^* GEMs at each intermediate step. In both (A) and (B), gray dots indicate individual steps and the red ellipses depict 95% prediction ellipses derived using a Chi-Squared distribution. C) Experimental 95% prediction ellipse characteristics at each step: aspect ratio (top), calculated as the ratio of the eigenvalues of the covariance matrix of the ellipse, area (center), and orientation (bottom), calculated as the angular deviation (positive angles indicate counter-clockwise) from the orientation of the constant-w^* GEM. Error bars indicate ±95% confidence intervals at each step derived using bootstrapping. Gray dashed lines indicate the mean of each characteristic from the two steady state ellipses in (A).

transition steps were significantly more isotropic than that observed during steady-state walking (Fig. 5C; top), with the primary transition step being most isotropic as theoretically predicted (Fig. 4F). Thus, these

top), with the primary transition step being most isotropic as theoretically predicted (Fig. 4F). Thus, these

experimental data strongly support our hypothesis that humans regulate their movements from one step to the

next during these lane-change maneuvers by adapting their stepping goals and the relative weighting of z_B and

w regulation.

Adaptive Stepping Regulation for Lateral Maneuvers

Our theoretical predictions (Fig. 4) and confirmatory experimental results (Fig. 5) both strongly suggest that

humans can accomplish a range of substantially *non*-steady-state lateral maneuvers by simply changing how

they weigh different task-level costs from each step to the next. They do not need to adopt some entirely

different stepping regulation process. We therefore sought to determine the extent to which our previous

multi-objective model [1] could emulate such variations in stepping dynamics if we allowed the parameters of

our model to adapt from step-to-step.

Our regulator models are linear update equations (see Methods). Their behavior is controlled primarily by

three basic parameters: a pair of target values or stepping goals, $[z_B{}^*, w^*]$, a weight that indicates each

regulator's relative importance, ρ, and the additive noise, σ_a, that represents the strength of physiological

perceptual/motor noise. Here, we conducted three sequential numerical experiments to assess the effects of

adapting each of these model parameters on key stepping dynamics: time series, errors, and variance

distributions. We first incorporated adaptive stepping goals that we derived theoretically to approximate an

idealized four-step transition strategy (Fig. 4C). Next, we adapted the proportionality parameter, ρ, to reflect

the predicted stepping distributions (Fig. 4F). Finally, we increased the additive noise to reflect the observed

increase in variability during the lateral maneuver. Importantly, we did not attempt to precisely estimate the

model parameters, but rather selected parameters based on the idealized theoretical considerations described

above. This approach is analogous to using "templates" of legged locomotion to reveal the basic principles of

human walking by testing fundamental hypotheses about the underlying regulation strategies [59, 60].

We algebraically derived (see Methods) new stepping goals, $[z_B^*, w^*]$, for each consecutive step (Fig. 6A) that

approximated an idealized four-step lane-change maneuver strategy (Fig. 4C). These derived stepping goals

included a slightly narrower w^* and slight shift in z_B^* towards the new path at the preparatory step, a much

wider w^* and large shift in z_B^* towards the new path at the transition step, and a slightly narrower w^* and slight

shift in z_B^* towards the new path again at the recovery step. All other model parameters were assigned

constant values across all steps (Fig. 6A), equivalent to the original stepping regulation model [1]. Likewise,

during the steady-state periods before and after the lateral maneuver, all model parameters were also held

constant to reflect steady-state walking [1].

As expected, allowing the stepping goals to adapt at each consecutive step emulated the experimentally

observed stepping time series and errors, as well as the locations of the stepping distributions at each step of

the lateral maneuver (Fig. 6B-D). However, these parameter variations did not influence the shape, area, or

orientation of the stepping distributions, unlike what we observed experimentally (Fig. 6D-E). Thus, allowing

the stepping *goals* to adapt from step to step appears necessary, but is not sufficient to elicit experimentally

plausible stepping dynamics during lateral maneuvers.

Figure 6. Adaptive Stepping Goals. A) Model parameters. Here, stepping goals, $[z_B^*, w^*]$ were updated at each step to reflect an idealized four-step transition strategy. The control proportion (ρ) and additive noise (σ_a) were held constant across all steps. B) Stepping time series (mean ± SD) of 1000 simulated lateral transitions using the parameters in (A). C) Stepping errors (mean ± SD) for the simulations in (B). In both (B) and (C), gray bands indicate the middle 90% range from experimental data. D) Simulated stepping data from the preparatory, transition, and recovery steps projected onto the $[z_L, z_R]$ plane. Gray ellipses represent 95% prediction ellipses at each step from the experimental data. Blue ellipses represent 95% prediction ellipses from the 1000 simulated lateral transitions. The diagonal dotted lines indicate the predicted constant-z_B^* and constant-w^* GEMs at the preparatory, transition, and recovery steps. E) Ellipse characteristics (mean ± SD) at each step (as defined in Fig. 5): aspect ratio (top), area (center), and orientation (bottom). Gray bands indicate ±95% confidence intervals from the experimental data derived using bootstrapping. Adapting the stepping goals alone yielded experimentally plausible stepping time series (B), errors (C), and locations (D), but not stepping distributions (D). Thus, adaptive stepping goals are necessary but not sufficient to replicate human stepping during lateral maneuvers.

258   Next, we added the ability to adaptively modulate ρ at each step (Fig. 7A) to incorporate our theoretical

259   predictions for an idealized four-step lane-change maneuver (Figs. 4C & 4F). Typical steady-state walking

260   heavily weights regulating step width over lateral position (i.e., $\rho \approx 0.9$) [1], presumably to maintain lateral

261   stability. Conversely, we expect people to trade off stability to gain maneuverability [8, 9] while executing

262   this maneuver. We therefore set $\rho = 0.50$ at the transition step (Fig. 7A) to specify equal weighting of step

Figure 7. Adaptive Control Proportion. A) Model parameters. Here, in addition to adapting the stepping goals ([z_B^*, w^*]; Fig. 6), the control proportion (ρ) was also varied during the preparatory, transition, and recovery steps to reflect the hypothesized maneuverability and error correction at each step. Additive noise (σ_a) remained unchanged from the original, constant parameter model. B-E) Results obtained from 1000 simulated lateral transitions using the parameters in (A), with data plotted in an identical manner to Fig. 6B-E. Adding step-to-step modulation of ρ again captured experimental stepping time series and errors at each step (B-C). Here however, allowing ρ to adapt at each step also induced changes in prediction ellipse aspect ratios during the transition steps that were qualitatively similar to those observed experimentally. Modulating ρ however, did not induce corresponding changes in ellipse area (D-E). Thus, adapting ρ at each step is also necessary but not sufficient to emulate human stepping during lateral maneuvers.

width and position regulation (Fig. 4F), thereby maximizing maneuverability. We then set $\rho = 0.7$ at the

preparatory and recovery steps (Fig. 7A) to reflect an intermediate multi-objective cost weighting (Fig. 4F).

The same adaptive stepping goals (Fig. 6) were again incorporated here. All other model parameters were

assigned constant values across all steps (Fig. 7A).

Therefore, in addition to adapting both the stepping goals (Fig. 6) and ρ (Fig. 7) from step to step, we then

doubled the additive noise (σ_a) in the model at the preparatory and transition steps (Fig. 8A). Additive noise is

Figure 8. Adaptive Additive Noise. A) Model parameters. Here, in addition to adapting the stepping goals (Fig. 6) and ρ (Fig. 7), additive noise (σ_a) was also doubled at the preparatory and transition steps. B-E) Results obtained from 1000 simulated lateral transitions using the parameters in (A), with data plotted in an identical manner to Figs. 6-7. Adding σ_a modulation again emulated experimental stepping time series and errors (B-C), as well as the qualitative changes in the aspect ratio of the fitted ellipses during the maneuver (D-E). Furthermore, modulating σ_a emulated the experimentally observed increases in ellipse areas. Modulating σ_a also affected orientations of the fitted ellipses, although not entirely in the same ways as the experimental data (D-E). Therefore, adaptively modulating the stepping goals ([$z_B{}^*$, w^*]), control proportion (ρ), and additive noise (σ_a) in our existing model can elicit changes in stepping dynamics qualitatively similar to those observed in humans during this lateral maneuver.

thought to reflect physiologic noise from a variety of sources, including sensory, perceptual, and/or motor

processes [29]. Here, we assessed whether increasing this additive noise could emulate the increases in the

stepping distribution areas observed experimentally (Fig. 5B-C).

Allowing the stepping goals, ρ, and σ_a to adapt at each consecutive step again emulated the experimentally

observed stepping time series, stepping errors, and stepping distribution locations at each step of the lateral

maneuver (Fig. 8B-D) and qualitatively captured the shapes of the stepping distributions (Fig. 8D-E).

Increasing σ_a also increased the areas of the stepping distributions at the preparatory, transition, and recovery

steps (Fig. 8D-E). Interestingly, increasing σ_a also influenced the orientations of these distributions, inducing

a clockwise rotation at the preparatory step and a counterclockwise rotation at the transition step (Fig. 8D-E).

These rotations reflect the individual steps at which the increased variability was applied. Increasing the noise

at the preparatory step (shown here as taken with the left foot) can only increase variability in the horizontal

direction in the $[z_L, z_R]$ plane. Conversely, increasing the noise at the subsequent transition step (taken with

the right foot) can only increase variability in the vertical direction.

We designed these simulations specifically to emulate our theoretical predictions for an idealized four-step

lane-change maneuver (Figs. 4C & 4F). Taken together, the results demonstrate that adapting the stepping

goals ($[z_B{}^*, w^*]$; Fig. 6), the relative weight given to regulation for of those goals (ρ; Fig. 7), and the additive

noise (σ_a; Fig. 8) allowed our simulations to emulate the key changes in stepping dynamics observed during

this lateral maneuver task (Fig. 5).

DISCUSSION

Understanding how humans perform accurate, goal-directed walking movements in the face of inherent

variability, redundancy, and equifinality remains a fundamental question in human motor neuroscience. In

pursuit of this aim, we previously developed a theoretical framework to describe how humans regulate

stepping to achieve continuous, straight-ahead walking [1]. Models developed from this framework provide

goal-directed "stepping regulation templates" that are both analogous and complimentary to mechanical

templates that describe the *within*-step mechanics and dynamics of walking (e.g., [22, 23, 32, 33]). Here,

because humans rarely perform long bouts of steady-state walking [51, 52], we therefore examined how our

basic regulation template scheme could be used to model human stepping dynamics during a prescribed

lateral maneuver that, by necessity, strongly deviated from steady state motion.

Our *key theoretical contribution* is that we show how our previously developed theoretical stochastic optimal

control framework can model how humans adapt their lateral stepping to enact non-steady-state lateral

maneuvers (Fig. 4). Specifically, we show this can be accomplished by adding an additional layer to our

previous control hierarchy: namely, the processes responsible for adapting, on a step-by-step basis, the cost

landscapes governing stepping regulation. Our *key empirical contribution* is we then demonstrate (Fig. 5) that

humans do indeed execute lateral maneuvers in a manner consistent with our theoretical predictions. Our *key*

computational contribution is that we show that allowing the parameters in our lateral stepping regulation

model to adapt from each step to the next can emulate the changes in lateral stepping dynamics exhibited by

humans (Figs. 6-8). To our knowledge, our results are the first to demonstrate that humans use evolving cost

landscapes in real time to perform such an adaptive motor task and, furthermore, that such adaptation can

occur quickly – over only one step.

In our simulations (Figs. 6-8), we chose model parameters based on idealized theoretical considerations (Fig.

4), only loosely related to general trends observed in our experiment. While our resulting simulations did not

precisely "fit" the experimental data, they were not intended to. On the contrary, our aim was to demonstrate

that reasonable values of the parameters could yield the same basic dynamical and statistical stepping *features*

that humans exhibited during this lateral maneuver task (Fig. 8). This approach is directly analogous to using

mechanical "templates" of within-step dynamics of legged locomotion to reveal basic principles of walking

and to propose fundamental hypotheses about what high-level control strategies might be acting [59, 60].

Here, we used our theoretical framework to derive such hypotheses (Fig. 4). We then used both experiments

(Fig. 5) and simulations (Figs. 6-8) to validate the theoretical predictions facilitated by our templates [1] for

an entirely new locomotor context.

Many studies have used optimal control theory to model a myriad of individual motor tasks (e.g., [61-65]).

Such efforts, however, did not consider tasks where the task goals and/or movement objectives change as the

task is being performed. Likewise, many studies have addressed motor adaptation (e.g., [66, 67]) and/or

motor learning (e.g., [68, 69]), including for walking tasks (e.g., [70-72]). These paradigms, however, track

how task performance changes slowly over many repetitions (typically at least 10's to 100's), and not from

one repetition to the next. Furthermore, while multiple studies have demonstrated that such longer-term

adaptation can be replicated by "lag-1" type computational models that explicitly correct only for errors

experienced on one previous iteration of the task [73-79], those models were not *themselves* "adaptive". On

the contrary, they presumed some constant process (with constant model parameters) that achieved adaptation

over multiple repetitions of the task under consideration. In sum, none of these extremely well-trodden

paradigms quite capture the nature of the task we studied here.

Conversely, rapid adaptation in response to changing environmental contexts has been demonstrated in both

birdsong [80-82] and human speech [83]. This apparent plasticity of a well learned, crystalized behavior

suggests that vocalization may be controlled by a "malleable template," in which trial-by-trial variability is

used to adapt learned behaviors [84]. Such rapid adaptations have also been observed in both animal [15, 16,

85-88] and human [7-9] locomotion (i.e., maneuvers). As the associated motor planning processes occur

nearly instantaneously [89-91], this prior work supports our findings that humans can and do make rapid

adaptations to their stepping regulation to enact lateral maneuvers. Thus, in demonstrating that our lateral

stepping regulation framework successfully predicts how humans perform lateral maneuvers, our findings

support the notion that humans use a malleable template [84] to make "embodied decisions" [6] about how to

regulate their stepping movements in real time during ongoing locomotion.

Prior work has postulated the existence of a "stability-maneuverability trade-off" during lateral maneuvers [7,

8]. However, in the absence of a coherent, predictive, theoretical framework, this stability-maneuverability

trade-off has not been adequately defined, much less confirmed. We propose that our lateral stepping

regulation framework, and the models derived from it, provides the necessary theoretical and computation

foundation needed to describe how humans trade-off stability for maneuverability during lateral movements.

By extension, our findings suggest that stability and maneuverability in the context of locomotion are not

distinct and independent concepts, but rather different manifestations of the same underlying stepping

regulation process. Indeed, if stability and maneuverability were independent, as often assumed, humans

should be able to remain stable and maneuverable simultaneously. However, our theoretical framework (Fig.

4) demonstrates precisely how and why humans must trade-off some degree of stability (i.e., w-regulation) to

gain the maneuverability needed to perform lateral maneuvers.

Walking in the real world often requires maneuverability to adapt to changing environmental conditions or

goals. We suggest that such maneuvers are governed by a hierarchical control/regulation schema with at least

three distinct layers: low-level processes that govern within-step dynamics to ensure viability [34, 59, 60],

step-to-step regulation to achieve goal-directed walking [1, 29, 34, 36], and the presently demonstrated

modulation of stepping regulation to achieve adaptability. The ability of our lateral stepping regulation

framework to emulate human stepping during the lane change maneuver studied here demonstrates that its

predictive capabilities extend to a much greater range of walking tasks than initially thought, encompassing

not just steady state walking, but transient behaviors as well.

METHODS

Ethics Statement

Prior to participating, all participants signed informed consent statements approved by the Institutional

Review Board at The Pennsylvania State University.

Lateral Maneuvers in Humans

The data analyzed here were collected as part of a previous experiment involving twenty young healthy adults

(Table 1) [58]. All participants were screened to ensure they had no history of orthopedic problems, recent

lower extremity injuries, any visible gait anomalies, or were taking medications that may have influenced

their gait.

Table 1 – Participant Characteristics. All values except Sex are given as Mean ± Standard Deviation.

381
382

Characteristic:	Value:
Sex	9 M / 11 F
Age [yrs]	21.7 ± 2.6

Body Height [m]	1.73 ± 0.08
Body Mass [kg]	69.9 ± 12.1
Body Mass Index (BMI) [kg/m^2]	23.2 ± 2.7
Leg Length [m]	0.82 ± 0.06

384 The experimental protocols were described in detail previously [58]. Briefly, participants walked in an "M-

385 Gait" system, comprised of a 1.2m wide motorized treadmill in a virtual reality environment (Motek,

386 Amsterdam, Netherlands). Each participant walked at a constant speed of 0.75 m/s. Following a 4-minute

387 acclimation trial, participants completed several different walking trials involving path navigation. The data

388 analyzed here were generated from one such trial, during which participants were instructed to switch

389 between two parallel paths, centered 0.6m apart, following an audible cue (Fig. 2). Participants completed 6

390 maneuvers during one 4-minute walking trial, and were instructed to walk normally on their current path

391 between maneuvers. The first and last maneuvers occurred too close to the beginning and end of the walking

392 trial, respectively, to ensure participants were walking normally both before and after the maneuver.

393 Therefore, the present analysis included only the middle four maneuvers from each participant, for a total of

394 80 lateral maneuvers.

396 Kinematic data were recorded from 16 retroreflective markers placed on the head, pelvis, and feet of each

397 participant. Marker trajectories were collected at 120Hz using a 10-camera Vicon motion capture system

398 (Oxford Metrics, Oxford, UK) and post-processed using Vicon Nexus and D-Flow software (Motek,

399 Amsterdam, Netherlands). Marker trajectories were analyzed in MATLAB (MathWorks, Natick, MA). Heel

400 strikes were determined using a velocity-based detection algorithm [92]. Lateral foot placements (z_L and z_R)

401 were defined as the lateral location of the heel marker at each step. Step width (w) and lateral position (z_B)

402 were then determined at each step using Eq (1) (Fig. 1C).

404 We were unable to determine accurate heel strikes for one lateral maneuver and consequently excluded this

405 maneuver from further analyses. Stepping data from the remaining 79 maneuvers were normalized to a

406 constant direction (left-to-right) and to the initiation of the transition, defined here as the last step taken on the

407 original path. Means and standard deviations of step width and position were determined at each step of the

408 lateral maneuver. The steady-state mean step width was determined from all participants and all steps,

409 excluding the 5 steps before to 10 steps after each transition. The steady-state mean position was determined

410 similarly, but was determined separately for each path (left and right). These steady-state means were used to

411 define the stepping goals for this task, [$z_B{}^*$, w^*]: w^* was defined as the steady-state mean step width, and $z_B{}^*$

412 before and after the maneuver was defined as the steady-state mean position on the left path and the steady-

413 state mean position on the right path, respectively. Errors in both position and step width (mean±SD) were

414 determined at each step of each maneuver as the differences in each from these steady-state stepping goals

415 (Fig. 2C).

Model of Lateral Stepping Regulation

To model lateral stepping, the simplest, mechanically sufficient biped includes the lateral locations of the

center-of-mass and each of the two feet (z_{Ln} and z_{Rn}; Fig. 1B) [32, 93, 94]. We presume that left and right foot

placement are coordinated to achieve some more general walking task goal or goals. One such goal is to

maintain lateral balance by regulating step width (w_n; Fig. 1C) [23, 95-97]. Humans also regulate the lateral

position of the body's mass center with respect to their path [18, 94, 98, 99], approximated by the midpoint

between the two feet (z_{Bn}; Fig. 1C) during upright walking [93, 95]. By selecting appropriate foot placements,

$\{z_L, z_R\}$, humans can regulate both their center of mass position and step width, $\{z_{Bn}, w_n\}$ [1], via:

$$\begin{bmatrix} z_{Bn} \\ w_n \end{bmatrix} = \begin{bmatrix} \frac{1}{2} & \frac{1}{2} \\ -1 & 1 \end{bmatrix} \begin{bmatrix} z_{Ln} \\ z_{Rn} \end{bmatrix} \tag{1}$$

428   During continuous straight-ahead walking, multi-objective regulation of primarily step width and secondarily

429   lateral position captures human lateral step-to-step dynamics [1]. The regulation model minimizes errors with

430   respect to both step width and lateral position using the goal functions [37, 38, 40]:

$$F_{zB} = z_{Bn} - z_B^* $$
$$F_w = w_n - w^* \tag{2}$$

434   where the goal is to drive each $F \to 0$. The value of each regulated variable at the subsequent step is

435   determined independently using the state update equations:

$$z_{B(n+1)} = z_{Bn} + g\left(1 + \sigma_{zBm} v_{zm}\right)\left(u_{zB}\left(z_{Bn}\right)\right) + \sigma_{zBa} v_{zBa}$$
$$w_{(n+1)} = w_n + g\left(1 + \sigma_{wm} v_m\right)\left(u_w\left(w_n\right)\right) + \sigma_{wa} v_{wa} \tag{3}$$

439   where $\sigma_{\_m} v_{\_m}$ and $\sigma_{\_a} v_{\_a}$ represent multiplicative and additive noise terms, respectively.

441   The control inputs, $u_{zB}(z_{Bn})$ and $u_w(w_n)$, were derived analytically as stochastic optimal single-step regulators

442   with direct error feedback [1, 29, 30, 40], following the Minimum Intervention Principle [42, 64]. Such

443   controllers are optimal with respect to the following quadratic cost functions:

$$C_{zB} = \alpha e_{zB(n+1)}^2 + \gamma u_{zB}^2$$
$$C_w = \alpha e_{w(n+1)}^2 + \gamma u_w^2 \tag{4}$$

447   The first term of each cost function penalizes errors with respect to the goal function (Eq (2)) at the next step.

448   The second term penalizes "effort", quantified as the magnitude of the control input. Here, α and γ were

449   positive constants that weighted the two terms of each cost function [1]. The subsequent analytical derivation

450   [1] yielded control inputs as:

$$u_{zB}\left(z_{Bn}\right) = -\left(\frac{1}{1+\sigma_m^2+\left(\gamma/\alpha\right)}\right)\left(z_{Bn}-z_B^*\right)$$

(5)

$$u_w\left(w_n\right) = -\left(\frac{1}{1+\sigma_m^2+\left(\gamma/\alpha\right)}\right)\left(w_n-w^*\right)$$

The value of each regulated variable, $[z_B, w]$, at the subsequent step is determined independently using

separate, individual optimal controllers. Thus, two corresponding foot placements are determined, one using

the predicted value of position, and the other using the predicted value of step width. The final predicted value

of foot placement is determined as a weighted average (ρ) of the predictions from each regulated variable,

where $\rho = 0$ indicates 100% position control and $\rho = 1$ indicates 100% step width control [1]. Hence, stepping

regulation is conceived here as arising from a "mixture of experts" [63, 100]. In this way, the value of ρ

directly determines the shape of the cost landscape, as evidenced by the changing shapes of the variability

ellipses in the $[z_L, z_R]$ plane (Fig. 7).

As in our prior work [1], the following parameters were set to constant values for all simulations. The

baseline amplitude of the additive noise ($\sigma_{\_a}$) was set to the steady-state standard deviation of each variable.

The amplitude of the multiplicative noise ($\sigma_{\_m}$) was set to 10% of the additive noise level (i.e., $0.1 \cdot \sigma_{\_a}$). The

magnitude of the additive and multiplicative noise at a given step were determined from the Gaussian random

variables $v_{\_a}$ and $v_{\_m}$, respectively, each with zero mean and unit variance. Error correction was weighted

much more heavily than effort in the cost function by setting $\gamma/\alpha = 0.10$.

Steady-State Stepping Regulation

We determined if any constant value of ρ could emulate human stepping throughout the lateral maneuver

(Fig. 3C). For each value of ρ between $\rho = 0.00$ and $\rho = 1.00$, in increments of $\Delta\rho = 0.01$, we conducted 1000

batches of 1000 simulations of the lateral maneuver. For each batch, we determined the means and standard

deviations of both position and step width at each step. We then computed the overall mean and standard

deviation of each variable at each step across all batches. For each variable, simulated and experimental

values were compared by plotting the simulated overall mean ± 1SD against 95% confidence intervals of the

experimental data determined from bootstrapping [40, 101]. For a given value of ρ, we considered the model

successful at capturing human stepping if the simulated means and standard deviations of step width and

position fell within the corresponding experimental 95% confidence intervals at every step of the lateral

maneuver (Fig. 3C).

Stepping Regulation for Non-Steady-State Tasks

When the z_B^* and w^* GEMs are viewed in the $[z_L, z_R]$ plane, it is clear that at least one intermediate step is

necessary to accomplish any Δz_B^* and/or Δw^* maneuver (Fig. 4A). For the minimum two-step maneuver

strategy (Fig. 4B), the stepping goals for either transition step can be determined algebraically from the

steady-state initial, $[z_{Bi}^*, w_i^*]$, and final, $[z_{Bf}^*, w_f^*]$, stepping goals. We first determined the initial and final foot

placement goals from the initial and final stepping goals using Eq (1). The foot used to take the intermediate

step must be placed at that foot's final foot placement goal, while the stance foot remains at its initial foot

placement goal. For example, if the right foot is used to take the intermediate step (Fig. 4B; a), the

intermediate foot placement goals are $[z_{Li}^*, z_{Rf}^*]$. By transforming these intermediate foot placement goals

back into $[z_B, w]$ coordinates using Eq (1), and re-defining the final stepping goals as the initial stepping goals

plus the changes in the stepping goals, $[\Delta z_B^*, \Delta w^*]$, the intermediate stepping goals are:

$$z_B^{*a} = \tfrac{1}{2}\left(z_{Li}^* + z_{Rf}^*\right) = \tfrac{1}{2}\left(z_{Bi}^* - \tfrac{1}{2}w_i^*\right) + \tfrac{1}{2}\left[\left(z_{Bi}^* + \Delta z_B^*\right) + \tfrac{1}{2}\left(w_i^* + \Delta w^*\right)\right]$$
$$= z_{Bi}^* + \tfrac{1}{2}\Delta z_B^* + \tfrac{1}{4}\Delta w^*$$

494   (6)

$$w^{*a} = \left(z_{Rf}^* - z_{Li}^*\right) = \left[\left(z_{Bi}^* + \Delta z_B^*\right) + \tfrac{1}{2}\left(w_i^* + \Delta w^*\right)\right] - \left(z_{Bi}^* - \tfrac{1}{2}w_i^*\right)$$
$$= w_i^* + \Delta z_B^* + \tfrac{1}{2}\Delta w^*$$

The same procedure can be used to determine the stepping goals for an intermediate step taken with the left

foot (Fig. 4B; b) by simply reversing the initial and final components of the intermediate foot placement goals

and making the corresponding substitutions in Eq (6).

However, equifinality exists in the number of steps and their placements that can be used to accomplish any

Δz_B^* and/or Δw^* maneuver. Experimentally, we most commonly observed a four-step maneuver strategy with

distinct preparatory, transition, and recovery steps (Figs. 2, 4C). To determine the stepping goals associated

with an idealized version of such a four-step strategy, we first calculated a single intermediate offset (ε) by

averaging the experimental differences in foot placement at each preparatory and recovery step relative to

steady-state walking. Assuming a left-to-right transition with preparatory and recovery steps that were each

taken with the left foot, the foot placement goals at the preparatory, $[z_L^{*Pr}, z_R^{*Pr}]$, and recovery, $[z_L^{*Rc}, z_R^{*Rc}]$,

steps were defined as $[z_{Li}^*+\varepsilon, z_{Ri}^*]$ and $[z_{Lf}^*, z_{Rf}^*-\varepsilon]$, respectively. These foot placement goals were then

transformed back into $[z_B, w]$ coordinates using Eq (1) to determine the preparatory, $[z_B^{*Pr}, w^{*Pr}]$, and

recovery, $[z_B{}^{*Rc}, w^{*Rc}]$, stepping goals. The transition stepping goals, $[z_B{}^{*Tr}, w^{*Tr}]$, were then determined using

Eq (6) above, substituting the preparatory and recovery stepping goals for the initial and final stepping goals.

The stepping goals themselves, however, do not provide insight into *how* humans regulated their stepping

during the lateral maneuver. For a four-step maneuver strategy with a large primary transition step and

smaller preparatory and recovery steps, as was observed experimentally (Fig. 2), stepping distributions are

theoretically predicted to be most isotropic at the primary transition step and intermediately isotropic at the

preparatory and recovery steps.

We qualitatively assessed the accuracy of the theoretically predicted stepping goals and distributions by

comparing them to the experimental data at each step, plotted in the $[z_L, z_R]$ plane (Fig. 5B). The maneuver

completed with a large cross-over step was excluded from analyses of the stepping distributions, as this

maneuver was completed with a different stepping strategy. Using the remaining 78 maneuvers, we first

computed the covariance matrix of left and right foot placements at each step: $\mathbf{C} = \mathrm{cov}(z_L, z_R)$. We take $\{\lambda_1,$

$\lambda_2\}$ and $\{\mathbf{e}_1, \mathbf{e}_2\}$ to denote the eigenvalues and eigenvectors of $\mathbf{C}$, respectively. We then construct a 95%

prediction ellipse by scaling the eigenvalues by the 95th percentile critical value of the Chi-Squared

distribution:

527
$$\begin{bmatrix} z_L(t) \\ z_R(t) \end{bmatrix} = \begin{bmatrix} \mathbf{e}_1 & \mathbf{e}_2 \end{bmatrix} \begin{bmatrix} \sqrt{5.991\lambda_1}\,\cos(t) \\ \sqrt{5.991\lambda_2}\,\sin(t) \end{bmatrix}, \quad where: \quad t = 0 \ldots 2\pi. \tag{7}$$

529   Thus, we expect 95% of the data points to lie inside this ellipse, assuming a bivariate normal distribution. We

530   then characterized each such ellipse by its shape, size, and orientation (Fig. 5C). We defined the shapes of

531   each ellipse by their aspect ratio, computed as the ratio of the major- and minor-axis eigenvalues: λ_1/λ_2. We

532   computed the sizes of each ellipse as their area:

534
$$A = 5.991\pi\sqrt{\lambda_1\lambda_2}\ . \tag{8}$$

536   We computed the orientations of each ellipse as the angle of the major axis measured counterclockwise from

537   the w^* GEM:

539
$$\Delta\theta = \begin{cases} \dfrac{\pi}{4} & \textit{if } C_{2,1} = 0 \textit{ and } C_{1,1} \geq C_{2,2} \\[2mm] \dfrac{3\pi}{4} & \textit{if } C_{2,1} = 0 \textit{ and } C_{1,1} < C_{2,2} , \\[2mm] \mathrm{atan2}\left(\lambda_1 - C_{1,1}, C_{2,1}\right) + \dfrac{\pi}{4} & \textit{else} \end{cases} \qquad (9)$$

where the $C_{i,j}$ are the respective elements of the covariance matrix. For each ellipse characteristic

computed at each step, we then calculated 95% confidence intervals for these values using bootstrapping.

Adaptive Stepping Regulation for Lateral Maneuvers

We adapted parameters of our goal-directed multi-objective lateral stepping regulation model from step-to-

step to determine if such adaptions could model the observed stepping dynamics during the lateral maneuver

task. For each model iteration, all parameters not explicitly modulated were assigned a constant value in

accordance with our previous steady-state stepping regulation model [1]. We first replaced the stepping goals

$z_B{}^*$ and w^* in the model (Eq (2)) with the estimated adaptive stepping goals (see previous section) (Fig. 6A).

We next adapted ρ, the model parameter that specifies the relative weighting of step width and position

regulation. The values assigned to ρ were chosen based upon theoretical predictions of the maneuverability

and error correction requirements at each intermediate step (see previous section; Fig. 5). Specifically, we set

$\rho = 0.50$ at the transition step, specifying equal weighting of step width and position regulation. We set $\rho =$

0.7 at the preparatory and recovery steps, a value intermediate between the approximate value observed for

steady-state walking ($\rho \approx 0.9$) and the value of 0.5 used for the transition step (Fig. 7A).

Finally, in addition to the adaptive stepping goals and ρ modulation, we doubled the additive noise parameter

(σ_a) at the preparatory and transition steps (Fig. 8A). The increased area of the stepping distributions at the

preparatory, transition, and recovery steps reflects greater overall variability with respect to both the w^* and

$z_B{}^*$ GEMs. Additive noise is thought to reflect physiologic noise from sensory, perceptual, and/or motor

processes [29], which is expected to increase during the lateral maneuver task. Here, we increased the additive

noise (Fig. 8A) to determine the extent to which this would qualitatively capture the types of increases in

stepping distribution areas that we observed experimentally.

For each model iteration, we assessed the ability of the model to emulate the key changes in stepping

dynamics observed experimentally: stepping time series (Figs. 6-8B), stepping errors (Figs. 6-8C), and

stepping distributions (Figs. 6-8D-E) at each step of the lateral maneuver. The lateral maneuver was simulated

1000 times for each model iteration. All maneuvers were oriented from left-to-right, and the transition step

was specified to be taken with the ipsilateral (i.e., right) foot relative to the direction of the transition,

consistent with all but one of the experimentally observed maneuvers. Time series (mean±SD) of foot

placement (z_L and z_R), position (z_B), and step width (w) were calculated at each step of the simulated

maneuvers. Errors with respect to both position and step width (mean±SD) were calculated as the difference

in the simulated position and step width relative to the stepping goals at each step of the simulated maneuvers.

The simulated stepping time series and errors were compared to the middle 90% range of the experimental

data at each step. The simulated stepping distributions were characterized by the aspect ratio, area, and

orientation of a fitted 95% prediction ellipse (see previous section). Error bars at each step for each variable

were calculated as 95% confidence intervals using bootstrapping. The simulated ellipse characteristics were

compared to the bootstrapped 95% confidence intervals from the experimental data at each step for each

variable.

Statistical Comparisons

As the experimental and simulated data were structured in very different ways, standard inferential statistics

(e.g., t-test, ANOVA, etc.) would not be appropriate to compare these results. Furthermore, we could generate

a sufficiently large number of model simulations to ensure small p-values for almost any comparison, thereby

diminishing the comparative power of any such assessments. Instead, we used descriptive statistics (e.g.,

standard deviations, confidence intervals, etc.) to quantify the experimental observation values. We then

compared model predictions to these observations. We inferred that model predictions that fell within

experimentally observed standard deviations/confidence intervals were statistically consistent with the

experimental results. Additionally, the aim of this analysis was to determine if hierarchical adaption of our

goal-directed multi-objective lateral stepping regulation models could qualitatively emulate the same *types* of

changes in stepping dynamics observed during the lateral maneuver task. Descriptive statistics were sufficient

to accomplish this aim.

AUTHOR CONTRIBUTIONS

Conceptualization:	DMD; JPC; JBD
Data Curation:	DMD; JBD
Formal Analysis:	DMD; JPC; JBD
Funding Acquisition:	JPC; JBD
Investigation:	DMD
Methodology:	DMD; JPC; JBD
Project Administration:	JBD; JPC
Resources:	JPC; JBD
Software:	DMD; JPC; JBD
Supervision:	JPC; JBD
Validation:	DMD; JPC; JBD
Visualization:	DMD
Writing – Original Draft Preparation:	DMD
Writing – Review & Editing:	DMD; JPC; JBD

ACKNOWLEDGEMENTS

The authors thank Ms. Meghan Kazanski and Ms. Anna Render for their assistance with data collection. The authors thank Ms. Meghan Kazanski for her assistance with data processing and initial analyses.

FUNDING

This project was funded by the US National Institutes of Health / National Institute on Aging (NIA; Grant # R01-AG049735 & R21-AG053470; to JPC and JBD).

REFERENCES

1. Dingwell JB, Cusumano JP. Humans Use Multi-Objective Control to Regulate Lateral Foot Placement When Walking. PLoS Comput Biol. 2019;15(3):e1006850. doi: https://doi.org/10.1371/journal.pcbi.1006850.

2. Maeda RS, O'Connor SM, Donelan JM, Marigold DS. Foot placement relies on state estimation during visually guided walking. J Neurophysiol. 2017;117(2):480-91. doi: https://doi.org/10.1152/jn.00015.2016.

3. Moussaïd M, Helbing D, Garnier S, Johansson A, Combe M, Theraulaz G. Experimental study of the behavioural mechanisms underlying self-organization in human crowds. Proc Roy Soc B Biol Sci. 2009;276(1668):2755-62. doi: http://dx.doi.org/10.1098/rspb.2009.0405.

4. Matthis JS, Barton SL, Fajen BR. The critical phase for visual control of human walking over complex terrain. Proc Natl Acad Sci USA. 2017;114(32):E6720-E9. doi: https://doi.org/10.1073/pnas.1611699114.

5. Matthis JS, Yates JL, Hayhoe MM. Gaze and the Control of Foot Placement When Walking in Natural Terrain. Curr Biol. 2018;28(8):1224-33.e5. doi: https://doi.org/10.1016/j.cub.2018.03.008.

6. Gordon J, Maselli A, Lancia GL, Thiery T, Cisek P, Pezzulo G. The road towards understanding embodied decisions. Neuroscience & Biobehavioral Reviews. 2021;131:722-36. doi: https://doi.org/10.1016/j.neubiorev.2021.09.034.

7. Wu M, Matsubara JH, Gordon KE. General and Specific Strategies Used to Facilitate Locomotor Maneuvers. PLoS ONE. 2015;10(7):e0132707. doi: http://dx.doi.org/10.1371/journal.pone.0132707.

8. Acasio J, Wu MM, Fey NP, Gordon KE. Stability-maneuverability trade-offs during lateral steps. Gait Posture. 2017;52:171-7. doi: http://dx.doi.org/10.1016/j.gaitpost.2016.11.034.

9. Hsieh KL, Sheehan RC, Wilken JM, Dingwell JB. Healthy individuals are more maneuverable when walking slower while navigating a virtual obstacle course. Gait Posture. 2018;61:466-72. doi:

https://doi.org/10.1016/j.gaitpost.2018.02.015.

10. Barton SL, Matthis JS, Fajen BR. Visual regulation of gait: Zeroing in on a solution to the complex terrain problem. J Exp Psychol Hum Percep Perf. 2017;43(10):1773-90. doi: http://dx.doi.org/10.1037/xhp0000435. PubMed PMID: 1947580833; 2017-42972-005.

11. Kowalsky DB, Rebula JR, Ojeda LV, Adamczyk PG, Kuo AD. Human walking in the real world: Interactions between terrain type, gait parameters, and energy expenditure. PLoS ONE. 2021;16(1):e0228682. Epub 2021/01/14. doi: 10.1371/journal.pone.0228682. PubMed PMID: 33439858; PubMed Central PMCID: PMCPMC7806134.

12. Twardzik E, Duchowny K, Gallagher A, Alexander N, Strasburg D, Colabianchi N, et al. What features of the built environment matter most for mobility? Using wearable sensors to capture real-time outdoor environment demand on gait performance. Gait Posture. 2019;68:437-42.

13. Kazanski ME, Dingwell JB, Cusumano JP. How healthy older adults regulate lateral foot placement while walking in laterally destabilizing environments. J Biomech. 2020;104:109714.

14. Wu MM, Brown G, Gordon KE. Control of Locomotor Stability in Stabilizing and Destabilizing Environments. Gait Posture. 2017;55(Supplement C):191-8. doi: https://doi.org/10.1016/j.gaitpost.2017.04.021.

15. Birn-Jeffery AV, Hubicki CM, Blum Y, Renjewski D, Hurst JW, Daley MA. Don't break a leg: running birds from quail to ostrich prioritise leg safety and economy on uneven terrain. J Exp Biol. 2014;217(Pt 21):3786-96. Epub 2014/10/31. doi: 10.1242/jeb.102640. PubMed PMID: 25355848; PubMed Central PMCID: PMCPMC4213177.

16. Biewener AA, Bomphrey RJ, Daley MA, Ijspeert AJ. Stability and manoeuvrability in animal movement: lessons from biology, modelling and robotics. Proc Roy Soc B Biol Sci. 2022;289(1967):20212492. doi: doi:10.1098/rspb.2021.2492.

17. Othayoth R, Xuan Q, Wang Y, Li C. Locomotor transitions in the potential energy landscape-dominated regime. Proc Roy Soc B Biol Sci. 2021;288(1949):20202734. doi: doi:10.1098/rspb.2020.2734.

18. Bruijn SM, van Dieën JH. Control of human gait stability through foot placement. J R Soc Interface. 2018;15(143):1-11. doi: https://doi.org/10.1098/rsif.2017.0816.

19. Bauby CE, Kuo AD. Active Control of Lateral Balance in Human Walking. J Biomech. 2000;33(11):1433-40. doi: http://dx.doi.org/10.1016/S0021-9290(00)00101-9.

20. MacKinnon CD, Winter DA. Control of Whole Body Balance In The Frontal Plane During Human Walking. J Biomech. 1993;26(6):633-44. doi: https://doi.org/10.1016/0021-9290(93)90027-C.

21. Townsend MA. Biped Gait Stabilization Via Foot Placement. J Biomech. 1985;18(1):21-38. doi: http://dx.doi.org/10.1016/0021-9290(85)90042-9.

22. Hof AL. The 'extrapolated center of mass' concept suggests a simple control of balance in walking. Hum Mov Sci. 2008;27(1):112-25. doi: https://doi.org/10.1016/j.humov.2007.08.003.

23. Kuo AD. Stabilization of Lateral Motion in Passive Dynamic Walking. Int J Robotics Res. 1999;18(9):917-30. doi: https://doi.org/10.1177/02783649922066655.

24. Kelsey JL, Browner WS, Seeley DG, Nevitt MC, Cummings SR. Risk factors for fractures of the distal forearm and proximal humerus. The Study of Osteoporotic Fractures Research Group. Am J Epidemiol. 1992;135(5):477-89. Epub 1992/03/01. doi: 10.1093/oxfordjournals.aje.a116314. PubMed PMID: 1570814.

25. Parkkari J, Kannus P, Palvanen M, Natri A, Vainio J, Aho H, et al. Majority of Hip Fractures Occur as a Result of a Fall and Impact on the Greater Trochanter of the Femur: A Prospective Controlled Hip Fracture Study with 206 Consecutive Patients. Calcif Tissue Int. 1999;65(3):183-7. doi: http://dx.doi.org/10.1007/s002239900679.

26. Winter DA. Kinematic and Kinetic Patterns in Human Gait: Variability and Compensating Effects. Hum Mov Sci. 1984;3(1-2):51-76. doi: http://dx.doi.org/10.1016/0167-9457(84)90005-8.

27. Kang HG, Dingwell JB. Separating the Effects of Age and Speed on Gait Variability During Treadmill Walking. Gait Posture. 2008;27(4):572-7. doi: https://doi.org/10.1016/j.gaitpost.2007.07.009.

28. Bernstein N. The Coordination and Regulation of Movements. New York, NY: Pergamon Press; 1967.

29. Dingwell JB, John J, Cusumano JP. Do Humans Optimally Exploit Redundancy to Control Step Variability in Walking? PLoS Comput Biol. 2010;6(7):e1000856. doi: http://dx.doi.org/10.1371/journal.pcbi.1000856.

30. Dingwell JB, Cusumano JP. Identifying Stride-To-Stride Control Strategies in Human Treadmill Walking. PLoS

ONE. 2015;10(4):e0124879. doi: http://dx.doi.org/10.1371/journal.pone.0124879.

31. Dingwell JB, Salinas MM, Cusumano JP. Increased Gait Variability May Not Imply Impaired Stride-To-Stride Control of Walking in Healthy Older Adults. Gait Posture. 2017;55:131-7. doi: https://doi.org/10.1016/j.gaitpost.2017.03.018.

32. Hobbelen DGE, Wisse M. Active Lateral Foot Placement for 3D Stabilization of a Limit Cycle Walker Prototype. Int J Hum Robot. 2009;6(1):93-116. doi: http://dx.doi.org/10.1142/S0219843609001632.

33. Koolen T, de Boer T, Rebula J, Goswami A, Pratt J. Capturability-based analysis and control of legged locomotion, Part 1: Theory and application to three simple gait models. Int J Robotics Res. 2012;31(9):1094-113. doi: https://doi.org/10.1177/0278364912452673.

34. Patil NS, Dingwell JB, Cusumano JP. Viability, task switching, and fall avoidance of the simplest dynamic walker. bioRxiv. 2022:2022.01.16.476517. doi: 10.1101/2022.01.16.476517.

35. Zaytsev P, Wolfslag W, Ruina A. The Boundaries of Walking Stability: Viability and Controllability of Simple Models. IEEE Trans Robot. 2018;34(2):336-52. doi: 10.1109/TRO.2017.2782818.

36. Patil NS, Dingwell JB, Cusumano JP. Task-level regulation enhances global stability of the simplest dynamic walker. J R Soc Interface. 2020;17(168):20200278. Epub 2020/07/18. doi: 10.1098/rsif.2020.0278. PubMed PMID: 32674710; PubMed Central PMCID: PMCPMC7423424.

37. Cusumano JP, Cesari P. Body-Goal Variability Mapping in an Aiming Task. Biol Cybern. 2006;94(5):367-79. doi: https://doi.org/10.1007/s00422-006-0052-1.

38. Cusumano JP, Dingwell JB. Movement Variability Near Goal Equivalent Manifolds: Fluctuations, Control, and Model-Based Analysis. Hum Mov Sci. 2013;32(5):899-923. doi: http://dx.doi.org/10.1016/j.humov.2013.07.019.

39. Cusumano JP, Mahoney JM, Dingwell JB. The Dynamical Analysis of Inter-Trial Fluctuations Near Goal Equivalent Manifolds. Adv Exp Med Biol. 2014;826:125-45. doi: http://dx.doi.org/10.1007/978-1-4939-1338-1_9.

40. John J, Dingwell JB, Cusumano JP. Error Correction and the Structure of Inter-Trial Fluctuations in a Redundant Movement Task. PLoS Comput Biol. 2016;12(9):e1005118. doi: http://dx.doi.org/10.1371/journal.pcbi.1005118.

41. Todorov E. Optimality principles in sensorimotor control. Nat Neurosci. 2004;7(9):907-15. doi: http://dx.doi.org/10.1038/nn1309.

42. Todorov E, Jordan MI. Optimal feedback control as a theory of motor coordination. Nat Neurosci. 2002;5(11):1226-35. doi: https://doi.org/10.1038/nn963.

43. Render AC, Kazanski ME, Cusumano JP, Dingwell JB. Walking humans trade off different task goals to regulate lateral stepping. J Biomech. 2021;119:110314. Epub 2021/03/06. doi: 10.1016/j.jbiomech.2021.110314. PubMed PMID: 33667882; PubMed Central PMCID: PMCPMC8081051.

44. Bohnsack-McLagan NK, Cusumano JP, Dingwell JB. Adaptability of Stride-To-Stride Control of Stepping Movements in Human Walking. J Biomech. 2016;49(2):229-37. doi: https://doi.org/10.1016/j.jbiomech.2015.12.010.

45. Dingwell JB, Bohnsack-McLagan NK, Cusumano JP. Humans Control Stride-To-Stride Stepping Movements Differently for Walking and Running, Independent of Speed. J Biomech. 2018;76:144-51. doi: https://doi.org/10.1016/j.jbiomech.2018.05.034.

46. Decker LM, Cignetti F, Potter JF, Studenski SA, Stergiou N. Use of Motor Abundance in Young and Older Adults during Dual-Task Treadmill Walking. PLoS ONE. 2012;7(7):e41306. doi: http://dx.doi.org/10.1371/journal.pone.0041306.

47. Terrier P, Dériaz O. Persistent and anti-persistent pattern in stride-to-stride variability of treadmill walking: Influence of rhythmic auditory cueing. Hum Mov Sci. 2012;31(6):1585-97. doi: http://dx.doi.org/10.1016/j.humov.2012.05.004.

48. Roerdink M, Daffertshofer A, Marmelat V, Beek PJ. How to Sync to the Beat of a Persistent Fractal Metronome without Falling Off the Treadmill? PLoS ONE. 2015;10(7):e0134148. doi: http://dx.doi.org/10.1371/journal.pone.0134148.

49. Terrier P. Fractal Fluctuations in Human Walking: Comparison Between Auditory and Visually Guided Stepping. Ann Biomed Eng. 2016;44(9):2785-93. doi: http://dx.doi.org/10.1007/s10439-016-1573-y.

50. Roerdink M, de Jonge CP, Smid LM, Daffertshofer A. Tightening Up the Control of Treadmill Walking: Effects of

Maneuverability Range and Acoustic Pacing on Stride-to-Stride Fluctuations. Front Physiol. 2019;10:257. Epub 2019/04/11. doi: 10.3389/fphys.2019.00257. PubMed PMID: 30967787; PubMed Central PMCID: PMCPMC6440225.

51. Orendurff MS, Schoen JA, Bernatz GC, Segal AD, Klute GK. How Humans Walk: Bout Duration, Steps per Bout, and Rest Duration. J Rehabil Res Develop. 2008;45(7):1077-90. doi: http://dx.doi.org/10.1682/JRRD.2007.11.0197.

52. Lugade V, Kuntapun J, Prupetkaew P, Boripuntakul S, Verner E, Silsupadol P. Three-Day Remote Monitoring of Gait Among Young and Older Adults Using Participants' Personal Smartphones. J Aging Phys Act. 2021;29(6):1026-33. Epub 2021/08/05. doi: 10.1123/japa.2020-0353. PubMed PMID: 34348231.

53. Robinovitch SN, Feldman F, Yang Y, Schonnop R, Leung PM, Sarraf T, et al. Video capture of the circumstances of falls in elderly people residing in long-term care: an observational study. Lancet. 2013;381(9860):47-54. doi: http://dx.doi.org/10.1016/S0140-6736(12)61263-X.

54. Matthis JS, Fajen BR. Visual control of foot placement when walking over complex terrain. J Exp Psychol Hum Percep Perf. 2014;40(1):106-15. doi: http://psycnet.apa.org/doi/10.1037/a0033101.

55. Marigold DS, Patla AE. Gaze fixation patterns for negotiating complex ground terrain. Neuroscience. 2007;144(1):302-13. doi: https://doi.org/10.1016/j.neuroscience.2006.09.006.

56. Land MF. Eye movements and the control of actions in everyday life. Prog Retin Eye Res. 2006;25(3):296-324. Epub 2006/03/07. doi: 10.1016/j.preteyeres.2006.01.002. PubMed PMID: 16516530.

57. Patla AE, Vickers JN. How far ahead do we look when required to step on specific locations in the travel path during locomotion? Exp Brain Res. 2003;148(1):133-8. doi: https://doi.org/10.1007/s00221-002-1246-y.

58. Kazanski ME, Dingwell JB. Effects of age, physical and self-perceived balance abilities on lateral stepping adjustments during competing lateral balance tasks. Gait Posture. 2021;88:311-7. Epub 2021/06/26. doi: 10.1016/j.gaitpost.2021.05.025. PubMed PMID: 34171786.

59. Dickinson MH, Farley CT, Full RJ, Koehl MA, Kram R, Lehman S. How Animals Move: An Integrative View. Science. 2000;Apr 7; 288(5463):100-6. doi: https://doi.org/10.1126/science.288.5463.100.

60. Full RJ, Koditschek DE. Templates and Anchors: Neuromechanical Hypothesis of Legged Locomotion on Land. J Exp Biol. 1999;202(23):3325-32.

61. Engelbrecht SE. Minimum Principles in Motor Control. J Math Psychol. 2001;45(3):497-542. doi: https://doi.org/10.1006/jmps.2000.1295.

62. Collins JJ. The Redundant Nature of Locomotor Optimization Laws. J Biomech. 1995;28(3):251-67. doi: https://doi.org/10.1016/0021-9290(94)00072-C.

63. Wolpert DM, Ghahramani Z. Computational Principles of Movement Neuroscience. Nat Neurosci. 2000;3(Supp):1212-7. doi: doi: 10.1038/81497.

64. Scott SH. Optimal Feedback Control and the Neural Basis of Volitional Motor Control. Nat Rev Neurosci. 2004;5(7):532-46. doi: https://doi.org/10.1038/nrn1427.

65. Guigon E. A computational theory for the production of limb movements. Psychol Rev. 2021:No Pagination Specified-No Pagination Specified. doi: 10.1037/rev0000323.

66. Wolpert DM, Diedrichsen J, Flanagan JR. Principles of sensorimotor learning. Nat Rev Neurosci. 2011;12(12):739-51. doi: doi: 10.1038/nrn3112.

67. Shadmehr R, Smith MA, Krakauer JW. Error Correction, Sensory Prediction, and Adaptation in Motor Control. Annual Review of Neuroscience. 2010;33(1):89-108. doi: http://dx.doi.org/10.1146/annurev-neuro-060909-153135.

68. Haith AM, Krakauer JW. The multiple effects of practice: skill, habit and reduced cognitive load. Curr Opin Behav Sci. 2018;20:196-201. Epub 2019/04/05. doi: 10.1016/j.cobeha.2018.01.015. PubMed PMID: 30944847; PubMed Central PMCID: PMCPMC6443249.

69. Krakauer JW, Hadjiosif AM, Xu J, Wong AL, Haith AM. Motor Learning. Compr Physiol. 2019;9(2):613-63. Epub 2019/03/16. doi: 10.1002/cphy.c170043. PubMed PMID: 30873583.

70. Choi JT, Bastian AJ. Adaptation reveals independent control networks for human walking. Nat Neurosci. 2007;10(8):1055-62. doi: https://doi.org/10.1038/nn1930.

71. Reisman DS, Block HJ, Bastian AJ. Interlimb Coordination During Locomotion: What Can be Adapted and Stored?

J Neurophysiol. 2005;94(4):2403-15. doi: https://doi.org/10.1152/jn.00089.2005.

72. Abram S, Selinger J, Donelan J. Energy optimization is a major objective in the real-time control of step width in human walking. J Biomech. 2019;91(85-91).

73. Scheidt RA, Dingwell JB, Mussa-Ivaldi FA. Learning to Move Amid Uncertainty. J Neurophysiol. 2001;86(2):971-85.

74. van Beers RJ, van der Meer Y, Veerman RM. What Autocorrelation Tells Us about Motor Variability: Insights from Dart Throwing. PLoS ONE. 2013;8(5):e64332. doi: https://doi.org/10.1371/journal.pone.0064332.

75. van Beers RJ, Brenner E, Smeets JBJ. Random walk of motor planning in task-irrelevant dimensions. J Neurophysiol. 2013;109(4):969-77. doi: https://doi.org/10.1152/jn.00706.2012.

76. van Beers RJ. How Does Our Motor System Determine Its Learning Rate? PLoS ONE. 2012;7(11):e49373. doi: https://doi.org/10.1371/journal.pone.0049373.

77. van der Kooij K, Brenner E, van Beers RJ, Smeets JBJ. Visuomotor Adaptation: How Forgetting Keeps Us Conservative. PLoS ONE. 2015;10(2):e0117901. doi: 10.1371/journal.pone.0117901.

78. López-Moliner J, Vullings C, Madelain L, van Beers RJ. Prediction and final temporal errors are used for trial-to-trial motor corrections. Scientific Reports. 2019;9(1):19230. doi: 10.1038/s41598-019-55560-6.

79. Coltman SK, Beers RJv, Medendorp WP, Gribble PL. Sensitivity to error during visuomotor adaptation is similarly modulated by abrupt, gradual, and random perturbation schedules. J Neurophysiol. 2021;126(3):934-45. doi: 10.1152/jn.00269.2021. PubMed PMID: 34379553.

80. Tumer EC, Brainard MS. Performance variability enables adaptive plasticity of 'crystallized' adult birdsong. Nature. 2007;450(7173):1240-4. doi: https://doi.org/10.1038/nature06390.

81. Sober SJ, Brainard MS. Adult birdsong is actively maintained by error correction. Nat Neurosci. 2009;12(7):927-31. doi: https://doi.org/10.1038/nn.2336.

82. Veit L, Tian LY, Monroy Hernandez CJ, Brainard MS. Songbirds can learn flexible contextual control over syllable sequencing. eLife. 2021;10:e61610. doi: https://doi.org/10.7554/eLife.61610.

83. Hauser MD, Chomsky N, Fitch WT. The faculty of language: what is it, who has it, and how did it evolve? Science. 2002;298(5598):1569-79. Epub 2002/11/26. doi: 10.1126/science.298.5598.1569. PubMed PMID: 12446899.

84. Grafton ST. Malleable templates: reshaping our crystallized skills to create new outcomes. Nat Neurosci. 2008;11(3):248-9. doi: https://doi.org/10.1038/nn0308-248.

85. Daley MA, Biewener AA. Running over rough terrain reveals limb control for intrinsic stability. Proc Natl Acad Sci USA. 2006;103(42):15681-6. doi: https://doi.org/10.1073/pnas.0601473103.

86. Othayoth R, Thoms G, Li C. An energy landscape approach to locomotor transitions in complex 3D terrain. Proc Natl Acad Sci USA. 2020;117(26):14987-95. doi: 10.1073/pnas.1918297117.

87. Jindrich DL, Full RJ. Many-Legged Maneuverability: Dynamics of Turning in Hexapods. J Exp Biol. 1999;202(12):1603-23. doi: https://doi.org/10.1242/jeb.202.12.1603.

88. Full RJ, Kubow T, Schmitt J, Holmes P, Koditschek DE. Quantifying dynamic stability and maneuverability in legged locomotion. Integrative and Comparative Biology. 2002;42(1):149-57. doi: https://doi.org/10.1093/icb/42.1.149.

89. Gallivan JP, Chapman CS, Wolpert DM, Flanagan JR. Decision-making in sensorimotor control. Nat Rev Neurosci. 2018;19(9):519-34. Epub 2018/08/10. doi: 10.1038/s41583-018-0045-9. PubMed PMID: 30089888; PubMed Central PMCID: PMCPMC6107066.

90. Nashed JY, Crevecoeur F, Scott SH. Rapid Online Selection between Multiple Motor Plans. The Journal of Neuroscience. 2014;34(5):1769-80. doi: 10.1523/jneurosci.3063-13.2014.

91. Wong AL, Haith AM, Krakauer JW. Motor Planning. The Neuroscientist. 2015;21(4):385-98. doi: 10.1177/1073858414541484. PubMed PMID: 24981338.

92. Zeni JA, Richards JG, Higginson JS. Two simple methods for determining gait events during treadmill and overground walking using kinematic data. Gait Posture. 2008;27(4):710-4. doi: http://dx.doi.org/10.1016/j.gaitpost.2007.07.007.

93. Donelan JM, Kram R, Kuo AD. Mechanical and metabolic determinants of the preferred step width in human

walking. Proc Roy Soc B Biol Sci. 2001;268(1480):1985-92. doi: https://doi.org/10.1098/rspb.2001.1761.

94. Wang Y, Srinivasan M. Stepping in the direction of the fall: the next foot placement can be predicted from current upper body state in steady-state walking. Biol Lett. 2014;10(9):20140405. doi: http://dx.doi.org/10.1098/rsbl.2014.0405.

95. Donelan JM, Shipman DW, Kram R, Kuo AD. Mechanical and metabolic requirements for active lateral stabilization in human walking. J Biomech. 2004;37(6):827-35. doi: https://doi.org/10.1016/j.jbiomech.2003.06.002.

96. McAndrew PM, Wilken JM, Dingwell JB. Dynamic Stability of Human Walking in Visually and Mechanically Destabilizing Environments. J Biomech. 2011;44(4):644-9. doi: http://dx.doi.org/10.1016/j.jbiomech.2010.11.007.

97. McAndrew Young PM, Wilken JM, Dingwell JB. Dynamic Margins of Stability During Human Walking in Destabilizing Environments. J Biomech. 2012;45(6):1053-9. doi: http://dx.doi.org/10.1016/j.jbiomech.2011.12.027.

98. Rankin BL, Buffo SK, Dean JC. A Neuromechanical Strategy for Mediolateral Foot Placement in Walking Humans. J Neurophysiol. 2014;112(2):374-83. Epub April 30, 2014. doi: https://doi.org/10.1152/jn.00138.2014.

99. Stimpson KH, Heitkamp LN, Horne JS, Dean JC. Effects of walking speed on the step-by-step control of step width. J Biomech. 2018;68:78-83. doi: https://doi.org/10.1016/j.jbiomech.2017.12.026.

100. Ghahramani Z, Wolpert DM. Modular Decomposition in Visuomotor Learning. Nature. 1997;386(6623):392-5. doi: https://doi.org/10.1038/386392a0.

101. Efron B, Tibshirani RJ. An Introduction to the Bootstrap (1st Ed.). Chapman and Hall/CRC. 1994. doi: https://doi.org/10.1201/9780429246593.