1

Inference of B cell clonal families using heavy/light chain pairing

information

Duncan K. Ralph[1,*], Frederick A. Matsen IV[1,2,3,4]

1 Computational Biology Program, Fred Hutchinson Cancer Research Center,

Seattle, Washington, USA

2 Department of Genome Sciences, University of Washington, Seattle,

Washington, USA

3 Department of Statistics, University of Washington, Seattle, Washington,

USA

4 Howard Hughes Medical Institute, Computational Biology Program, Fred

Hutchinson Cancer Research Center, Seattle, Washington, USA

[*] **dralph@fredhutch.org**

ABSTRACT

Next generation sequencing of B cell receptor (BCR) repertoires has become a

ubiquitous tool for understanding the antibody-mediated immune response: it is

now common to have large volumes of sequence data coding for both the heavy

and light chain subunits of the BCR. However, until the recent development of

high throughput methods of preserving heavy/light chain pairing information,

these samples contained no explicit information on which heavy chain sequence

pairs with which light chain sequence. One of the first steps in analyzing such BCR

repertoire samples is grouping sequences into clonally related families, where each

stems from a single rearrangement event. Many methods of accomplishing this

have been developed, however, none so far has taken full advantage of the newly-available pairing information. This information can dramatically improve clustering performance, especially for the case of the light chain; the light chain has traditionally been challenging for clonal family inference because of its low diversity and consequent abundance of non-clonal families with indistinguishable naive rearrangements. Here we present a method of incorporating this pairing information into the clustering process in order to arrive at a more accurate partition of the data into clonally related families. We also demonstrate two methods of fixing imperfect pairing information, which may allow for simplified sample preparation and increased sequencing depth. Finally, we describe several other improvements to the *partis* software package (`https://github.com/psathyrella/partis`).

——————————————————————————————————-

INTRODUCTION

Antibodies are a primary component of the adaptive immune system, and are critical to the operation of immune memory. They are produced by B cells in a process that generates a vast diversity designed to prepare for encounter with any potential antigen. This process begins with somatic rearrangement of germline genes in naive B cells. Perhaps 50-80% of these naive cells are initially self-reactive, but during the course of maturation this is reduced to around 10%, largely due to central tolerance [1]. For B cells that go on to meet their cognate antigen, the process continues in germinal centers as affinity maturation proceeds via somatic hypermutation (SHM) and antigen driven selection.

We can think of this as two steps: first, the generation of an initial repertoire that tries to span the space of potential antigens such that there will be a naive antibody with some level of binding against any antigen. Second, once an antigen is encountered, any B cells producing "nearby" antibodies with some binding evolve "toward" the antigen, resulting in antibodies with higher affinity S1 Figure.

Antibodies consist of two analogous parts, called the heavy and light chains [2] (which we sometimes refer to simply as *heavy* or *light*, omitting the "chain"). To construct a heavy chain, one V, one D, and one J gene are selected randomly (but very non-uniformly) from among the many possibilities on each chromosome. The selected V, D, and J genes are joined together in such a way that at each junction some number of random "non-templated" nucleotides can be added, and a random number of nucleotides can be deleted from each gene's end. Light chain rearrangement is similar, except that it has no D genes, and only a limited amount of insertion and deletion [3]. Light chains are thus vastly less diverse than heavy: perhaps by a factor of 10^6 [4] or more [3]. Rare but potentially significant exceptions to this basic picture include the use of two D genes (VDDJ rearrangement) [2,5] and LAIR1 insertion [6].

During development each B cell first attempts a heavy chain rearrangement. If the result has V and J in frame with respect to each other and is free of stop codons, and if it can successfully pair with a special temporary *surrogate* light chain, the cell then goes on to attempt light chain rearrangement. While heavy chain rearrangement appears optimized to maximize diversity, light chain rearrangement instead maximizes the opportunities for generating a functional and non-self-reactive partner for that heavy chain [3,4]. Light chain genes within a locus, for instance, are found along both strands, so that intervening genes are not always excised in the first rearrangement, and are thus available for subsequent rearrangements. Rearrangement also initially favors the innermost genes in a locus, such that outer genes are preserved for subsequent attempts. Most species also have two independent light chains (kappa and lambda, commonly called IgK and IgL) on separate chromosomes, which again increases the number of opportunities to find a successful light chain partner once the resources have been expended to obtain a functional heavy chain (commonly called IgH). These methods of salvaging a potentially failed antibody, referred to as *receptor editing*, while more prevalent in light chain, also occur in heavy, for instance via VH replacement [4,7].

In both chains, successful rearrangement on one chromosome typically results in suppression of rearrangement on the other; this is called allelic exclusion. The process is, however, sometimes incomplete, resulting in *allelic inclusion*, or expression of multiple heavy or light chains at some frequency, which has been estimated at around 1% of cells [4, 8]. There also exist other less common processes that can result in expression of, for example, up to four light chains in a single cell [9].

The full paired antibody structure is arranged such that both heavy and light chains contribute to, and are necessary for, both binding and structural stability. Each chain has three loops, called *complementarity determining regions* (CDRs), that provide much of the antigen contact and, correspondingly, also most of the diversity. Of the three, two are encoded by the V germline (CDR1 and CDR2), while the third (CDR3) contains all of the junctional diversity generated by VDJ rearrangement. Because SHM is targeted to the CDRs, they also harbor most of the diversity generated during affinity maturation. The intervening framework (FWK) regions, on the other hand, are more important for structural stability, and thus are much less variable.

Analyzing antibody repertoires. Our ability to measure the B cell receptor (BCR) repertoires that result from the processes described above has improved over time [10]. Beginning in the 1990s, Sanger sequencing allowed the observation of hundreds of sequences. The more recent development of *next generation*, or *deep*, sequencing approaches has increased this to tens of thousands or millions. While this is still a small fraction of the total number of B cells (perhaps 10^9 in the blood alone [10]), it represents a significant, and potentially representative, observational window for circulating B cells. The deep sequencing of BCR repertoires has thus become ubiquitous in the last decade, and is now a key tool in understanding the adaptive immune response.

In order to analyze these data, we typically need to group sequences into *clonal families*, each stemming from a single rearrangement event. The simplest (and still widespread) method is to first group together sequences with the same V and

J genes, and then perform single-linkage clustering on the CDR3 sequence with some threshold (typically 0.9) [11]. This method is, unfortunately, often quite inaccurate, especially on repertoires with significant SHM [12]. Two basic reasons for this inaccuracy are that gene calls are often uncertain, and the threshold is not optimal for most samples. However a more fundamental issue is that it clusters on observed (mutated) sequences, which allows SHM to spread apart clonal families that should be merged (S2 Figure). A variety of approaches have addressed some of these problems separately, for instance by relaxing the requirement for exact gene calls [13, 14] and using more sophisticated thresholds [15–17]. However we have previously shown a substantial accuracy improvement by avoiding all three issues simultaneously [12] using distance-based clustering on inferred naive (rather than observed) sequences, combined with a hidden Markov model (HMM) describing VDJ rearrangement. By integrating over all possible naive rearrangements, the HMM's inference of clonal relationships remains entirely agnostic to the inherently uncertain inference of naive rearrangement parameters.

The performance of all of these clustering methods, however, has been until recently subject to a fundamental limitation. Because the heavy and light chains are found on separate chromosomes, they have been sequenced separately, leaving no information on which heavy and light chain sequences pair with each other (which we refer to as "pairing information", or "pair info" for short). This is clearly an issue if the goal is to synthesize actual antibodies — potential partners often must simply be guessed. However it also creates a problem of unavoidable overmerging in clonal family clustering when different rearrangement events lead to experimentally indistinguishable naive sequences. We refer to these as *collisions*, and they can be thought of as involving events whose naive sequences differ by fewer than perhaps 2-4 nucleotides, such that they are practically indistinguishable. While it is not possible to measure the actual frequency of such collisions using unpaired data, we can tell that they are common in light chain because experimentally measured cluster size distributions are vastly more clonal for light

than heavy [18]. Note that this unpaired data provides no information on the rate of heavy collisions, and gives only a lower bound on that rate for light. While the theoretical maximum diversity of heavy chain is large enough to suggest that heavy collisions might be rare, the actual distributions from which parameters are chosen are extremely far from uniform, with for instance the chance of different V gene choices varying by orders of magnitude [3]. This means that the actual collision frequency could be substantial. Note that we can further distinguish between *naive collisions*, in which the naive rearrangements are close to each other; and *mature collisions*, in which the mature sequences from two naive rearrangements have drifted close to each other (S2 Figure).

Fortunately, deep sequencing data with heavy/light pairing information (*paired data*) has become much more common in recent years [8, 19–23]. While previous approaches had low efficiency or cell throughput [24–27], current methods have improved on this. The most widespread method, from 10X Genomics, uses barcoded single cell droplets [22]. Other approaches, however, exist for instance using mass spectrometry [28], physical linking of heavy/light transcripts in droplets [8, 20], or emulsion-based single cell barcoding [21]. There is also the potential for various single cell RNAseq technologies to be applied to B cells [23].

This new paired data provides the opportunity to dramatically improve clustering by using pairing information to refine each single chain partition. For instance if two naive heavy rearrangements are indistinguishable, but their corresponding light rearrangements are chosen independently of each other, the two light families will almost always be easily distinguishable. This procedure is entirely dependent on the extent of this independence, i.e. the extent to which heavy/light pairing is uncorrelated in the underlying biological process, which we call "biological pairing correlation". For example if indistinguishable heavy events always had the same light partners (perfect correlation), pair info wouldn't help with clustering at all. Thankfully biological pairing correlations have so far been found to be small [29] or nonexistent [30, 31]. While previous work has noted the potential

for this approach to clustering improvement [32], there has not been a fully bench-marked implementation that takes advantage of all of the information that paired data has to offer, nor takes care of the quirks that this data has in practice.

Ideally, pairing information would consist entirely of pairs of sequences, one heavy and one light. In practice, we encounter imperfect pairing information both from the biological processes such as allelic inclusion described above, as well as from various experimental factors. Sequencing or amplification failure can result in zero partners ("no pairing information") for some sequences. Also, some fraction of droplets in paired data contain more than one cell, resulting in multiple potential partners ("multiple pairing information").

In this paper we introduce a method for refining single chain partitions using heavy/light pairing information. We compare performance on simulated samples against several single chain methods [17, 33], as well as a paired method that has been used [34] but not yet publicly benchmarked. We then show that our method's effect on cluster size distributions in real data is very similar to that in matched simulation samples. We also introduce two methods to fix imperfect pairing information: first, a method to disambiguate (or *clean*) pair info in samples that contain more than one cell per droplet; and second, a method to approximately pair (up to clonal family) sequences from a bulk sample that is matched to a single cell (paired) sample. Finally, we describe recent improvements to the single chain methods of the software package into which all of these methods are collected, partis.

RESULTS

Paired clustering method overview. Our paired clustering method proceeds in two steps: it first infers a partition for each chain individually, then uses the pairing information to combine them into a single, joint partition of the sequences. There are several options for the first, single chain clustering step, including a variety of tradeoffs between accuracy and speed (see Methods and https://bit.

196 `ly/3tuSGjE`). The second, paired clustering step refines these single chain parti-

197 tions, effectively splitting apart clusters in each chain based on information from

198 the other (Fig 1).

Fig 1. **Schematic representation of our paired clustering method** on two families in the heavy chain (left) and light chain (right). The naive sequences (green crosses) and trees (dashed black lines) represent the collision (i.e. occurrence of very similar VDJ rearrangements) of the two light chain families, while the heavy families are easily distinguishable. The first step of our method groups together apparently-clonal sequences using only single chain information, and would thus merge together the two light chain families. The second step, which refines the single chain partitions using information on which heavy and light chain sequences pair together ("pairing information"), would then use the difference in heavy clusters to split apart the light families.

Performance metrics. Before showing performance, we first describe our means

of evaluating performance, first directly on simulated data, and then indirectly

from real data.

The goal in measuring performance of a clustering method on simulation is to

quantify the correctness of an inferred partition relative to the known true parti-

tion. It is useful to consider separately the two ways that one can miscluster: by

merging a cluster with unrelated sequences, and also by splitting apart a true cluster. We can map these two errors onto the usual precision/sensitivity dichotomy by considering correctly (incorrectly) inferred clonal sequences as true (false) positives. While there are a number of further decisions involved in actually calculating these numbers (see Methods and [33]), it is useful to simply think of precision as the average purity of clusters (i.e. the fraction of sequences in a cluster that are truly clonal), and sensitivity as their average completeness (i.e. the fraction of a true clonal family that end up together). For brevity, and to emphasize that useful clustering usually requires that precision and sensitivity both be high, we sometimes use their harmonic mean (F1 score).

Validation results on real data differ from simulation in that they perfectly recapitulate the underlying biological processes together with all sources of experimental error; however in real data we also do not in general know the correct clustering. Two approaches have been used to partially avoid this limitation. One approach looks at samples consisting of a single clone, for instance from lymphomas, such that any splitting whatsoever is oversplitting. The other mixes together samples from different subjects, such that any inferred families with sequences from different subjects must be overmerged. The issue with these approaches is that they measure either oversplitting or overmerging alone, whereas a useful clustering method must simultaneously minimize both of these; it is trivial to construct a method that is very good at only one or the other. Thus instead of attempting to directly evaluate clustering performance on real data, we instead use it to first evaluate the fidelity of our simulation framework, and second to compare how similarly our method behaves on data and simulation. This approach is especially useful for paired clustering because the heavy and light partitions are, in a sense, independent sources of information on the single true partition. We choose to do the second step with cluster size distributions. While these are poor descriptors of overall clustering quality — they overemphasize the small clusters that dominate real repertoires (but which are often of little experimental interest), and can also

obscure large but compensating errors in precision and sensitivity — they visually emphasize the splitting that is at the core of paired clustering.

Disambiguating multiple pairing information (*pair info cleaning*), on the other hand, involves two somewhat separate goals. Correction of the actual pair info is of course important, but the effect of this on clustering performance is also of interest. By construction, our algorithm leaves no sequences with multiple partners (see Methods). After application, then, sequences are either correctly paired, mispaired (with the wrong sequence), or left unpaired. We thus first report these three fractions, then go on to calculate the effect on final clustering performance. Furthermore, in some cases a sequence that is not paired correctly, but is paired with a sequence from the correct clonal family, can be useful, since the pairing will often still result in a functional antibody. We thus also report the fraction of sequences paired with the correct clonal family, regardless of whether they are paired with the correct sequence in that family. When pairing sequences approximately in bulk samples, we also include sequences that are paired with "similar" families, defined as families with true naive sequences separated by hamming distance of three or less. The idea is that sequences from families that are this similar are likely to frequently result in functional antibodies, even if they are from the wrong family.

Clustering methods. We compare the performance of a variety of different clustering methods in this paper. We show two different methods from our partis software package: the full, default method, as well as a faster, more approximate method (*vsearch partis*) that is better suited to extremely large samples, or when quick results are more important than maximum accuracy.

We also show results from several other single chain methods (i.e. that use information from only a single chain). The simple method of grouping together sequences with the same V and J genes, followed by single-linkage distance-based clustering on CDR3 sequences is still widespread (we use a threshold of 0.9 in nucleotide distance and call it *VJ CDR3 0.9*). The SCOPer package implements

spectral clustering with a threshold set by looking for a minimum between two

maxima in the sample's pairwise distance distribution [17]. The MobiLLe package

simultaneously optimizes two criteria, minimizing diversity within families while

maximizing that between them [33]. The SCOPer package also has a paired op-

tion (used in [34]), which we use according to a script written by the authors of the

package https://bit.ly/3K8KfBa.

In order to provide intuitive context for the actual methods, we also show two

synthetic methods, which are generated directly from the simulated true partition.

The first, called *synth. 20% singleton*, randomly chooses 20% of sequences from the

true partition to split into singleton clusters. This is intended to show a baseline for

how a simple operation affects the performance metrics, and is also useful because

its performance is similar to the VJ CDR3 0.9 method. The second, called *synth.*

neighbor 0.03, merges together families that, with only single chain information,

are close to experimentally indistinguishable. It does this by merging families

whose true naive sequences are closer than 3% in hamming distance. While the

exact threshold is arbitrary, it has been chosen such as to provide a useful visual

indication of the naive collision frequency.

Simulation results. The goal of performance evaluation on simulation is to un-

derstand behavior in all regions of parameter space. While the entirety of this

space for BCR repertoires is extremely complex and high dimensional, it is only

important to vary those parameters that have a significant effect on performance.

For situations depending on the details of tree shape [35], for instance, this can

be quite complex; however the present case of clonal family clustering is much

simpler. This is because the difficulty of clustering is mostly determined only by

the number of mutations and the naive collision fraction. The normalized num-

ber of mutations (SHM fraction) can be thought of as the diameter of each family

in rearrangement space (S1 Figure), while the naive collision fraction is the typ-

ical distance between naive rearrangements (determined by the locus's inherent

diversity and the number of rearrangements).

Fig 2. **Clustering performance on simulation as a function of SHM (mean fraction of nucleotides mutated)** for heavy chain (left) and light chain (right). Each point is the mean F1 score ($\pm$ standard error, often smaller than points) over three samples, each consisting of 10,000 simulated rearrangement events with family sizes drawn from a geometric distribution with mean of three. In addition to the inference methods (shown in color), we include two *synthetic* partition methods (grey), which generate incorrect partitions starting from the true partition. These are purely to provide intuitive comparison: the first splits 20% of sequences, chosen at random, into singleton clusters; the second merges together families whose true naive sequences are closer than 3% in Hamming distance ("synth.", see text for details). The F1 score's component precision and sensitivity are plotted in S3 Figure, while the performance with and without using pairing information is compared for partis in S4 Figure and SCOPer in S5 Figure. Performance of partis as a function of the number of families (with SHM constant) is shown in S6 Figure. All methods are publicly available except for SCOPer, whose paired method was obtained via personal communication.

We show performance for all methods versus SHM fraction in terms of F1 score (Fig 2) and precision and sensitivity (S3 Figure). To show the effect of the paired clustering method itself, we also show performance versus SHM fraction using only single chain information for partis (S4 Figure and SCOPer (S5 Figure). We note that while the partis paired clustering algorithm improves both IgK (a lot) and IgH (a little) (S4 Figure), the paired version of the SCOPer method improves IgK a lot while worsening IgH (S5 Figure). The latter is driven by a substantial degradation in IgH sensitivity.

Since the diversity generating process is a constant for each locus, we show performance as a function of the distance between naive rearrangements only versus the number of rearrangement events (S6 Figure). Note that these parameters largely determine the difficulty of single and paired clustering together: the difficulty particular to the actual paired clustering algorithm is mostly determined by the level of biological pairing correlation, which in this paper we assume is approximately zero.

We also benchmark pair info cleaning. In current 10X data, multiple cells are typically encountered in only around 1% of droplets (although we have encountered a sample where this is around 40%). It would be useful to rescue even a small fraction of cells for analysis by disambiguating multiple pair info (they are typically discarded [36]). However, perhaps more importantly, an effective disambiguation algorithm (we call this *pair cleaning*) raises the possibility of purposefully overloading droplets in order to increase the total number of sequenced cells. It would also simplify sample preparation by reducing the necessity for mono-dispersed droplets [37]. Because our method uses clonal relationships to determine correct pairings, sequences in large families are more likely to be corrected than those in small clusters. We thus measure performance on simulation as a function of family size (Fig 3), and see that 1- and 2-sequence families are often left unpaired, especially with high numbers of cells per droplet. However in many practical cases, we are most interested in larger families, and we find for instance

Fig 3. **Effectiveness on simulation of the pair info cleaning method as a function of true family size,** shown as the fraction of sequences correctly paired (top left); and the fraction not correctly paired, split into those mispaired (bottom left) and left unpaired (bottom right). We also show the fraction that are paired with a sequence from the correct family, though not necessarily the correct sequence in that family (top right). Each point is the mean (± standard error, often smaller than points) over three samples, each consisting of 3,000 simulated rearrangement events (around 12,000 total heavy and light sequences). The family sizes are drawn from a distribution inferred from real data. The effects of these overloaded droplets and the pair info cleaning method on final clustering performance are shown in S7 Figure.

that sequences in families larger than 3 are correctly paired 80-85% of the time even with 10 cells per droplet (Fig 3 top left). If we relax this to include sequences that are paired with the wrong sequence, but from the correct family, this rises to around 90% (Fig 3 top right). We can also visualize performance by comparing overall results on samples with different family size distributions (S7 Figure). Here we show both samples with family sizes drawn from a distribution inferred from

real data (solid red line; this is about 70% singletons, and corresponds to the samples shown in Fig 3), as well as several samples where all families have the same, indicated size (dashed lines). This shows both the fraction of sequences correctly paired (top), and the effect of this on clustering performance (bottom).

Fig 4. **Effectiveness on simulation of the approximate bulk data pairing method as a function of true family size,** shown as the fraction of sequences paired with a sequence from the correct family (but not necessarily the correct sequence, left) and the fraction paired with a family similar to the correct family (right). The method merges together a single cell and a bulk sample drawn from the same pool of B cells, and the "bulk data fraction" shows the fraction of this merged sample that stems from the bulk sample. "Similar" families are defined as families with true naive sequences separated by nucleotide hamming distances of 3 or less, i.e. essentially experimentally indistinguishable, and likely with similar function. The fraction of sequences correctly paired, mispaired, and left unpaired are shown in S8 Figure. Other details same as in Fig 3.

Because bulk (unpaired) sequencing data can be produced with much greater depth than single cell (paired) samples, it might be possible to increase paired sequencing depth if we could apply pair info from a single cell sample to a matched bulk sample (i.e. a sample drawn from the same pool of cells). We have developed a method that accomplishes this using clonal family information from the merged bulk and single cell samples, such that bulk sequences in families with at least one paired cell will be paired with sequences from the correct (or at least similar) corresponding opposite-chain family. We include "similar" because these are families from the single chain partition (since we don't yet have pair info), so

will include collisions between different, largely indistinguishable, events. Such collisions can result in choosing a partner from the wrong family, but because the two families are very similar, the pairing may still be functional. We measure the performance of this method both vs true family size (since larger families are more likely to contain a paired sequence), and vs the fraction of the merged sample derived from bulk data; and report the fraction paired with both correct and similar families (Fig 4), and the fraction correct, incorrect, and unpaired (S8 Figure). We find, for instance, that with a bulk data fraction of 0.8 (i.e. if our total sequencing depth is five times our single cell sample), around 90% of sequences in families of 10 or larger are paired with a sequence from the correct family (Fig 4 left), and > 99% are paired with a similar family (Fig 4 right). Note that sequences that are not paired with a similar family are essentially all left unpaired, i.e. very few sequences are paired with a family significantly different from their correct partner. These unpaired sequences are from families that did not happen to contain any single cell (paired) sequences. Note also that by construction, the fraction actually correctly paired is simply the single cell (non-bulk) fraction of the sample (S8 Figure).

We also measure the time required for each method (Fig 5). While bulk BCR sequencing samples can contain millions of sequences, at the moment paired data typically has only 1,000 to 10,000. This means that even the slowest methods finish in minutes on typical paired data. For single chain clustering there is a rough tradeoff between accuracy and time required. The partis implementation of paired clustering using these single chain clusters, however, does not take a significant amount of time (a few seconds on 10,000 sequence pairs). We do not show memory usage, since we do not find it to be a limiting factor (for instance the 10,000 sequence pair samples used less than around a GB).

Real data results. We show clustering results on real data in the form of cluster size distributions for single and joint partitions. These are shown for a sample

Fig 5. **Time required for clustering** for a variety of methods for both single chain clustering (top, for IgH [left] and IgK [right]) and paired clustering (excluding single chain partitioning, bottom left). Each point is the mean (± standard error, often smaller than points) over two samples with the indicated size, run on a single desktop with a 14-core Intel i-99940X processor and 128GB memory (maximum memory usage of the 100K samples was around 9GB). The size of each family is drawn from a geometric distribution with mean 10.

from the 10X website [38] together with results on a parameter-matched simulation sample (Fig 6), and similarly for three other samples in `https://doi.org/10.5281/zenodo.5860144`. The extent of splitting, i.e. the difference between the single and joint distributions in either data or simulation, tells us the paired clustering method's determination of the extent of single-chain overmerging.

Furthermore, the similarity of the data and simulation distributions for both single and joint partitions gives us confidence that both the single chain simulation, and the uncorrelated pairing assumption, suitably approximate the underlying processes for the purposes of benchmarking. The discrepancies between

Fig 6. **Cluster size distributions on real data (thin lines) and simulation (thick lines) for single chain (no paired clustering, blue/green) and joint (with paired clustering, black/red) partitions** for IgH (top), IgK (bottom left) and IgL (bottom right). The real data sample is from the 10X website [38], while the simulation sample is generated to match that particular real data sample, i.e. from parameters inferred from that real data sample. Direct comparisons of other parameter distributions for these two samples are shown for a handful of parameters in S9 Figure. Comparisons for all parameters, along with similar analyses for three other real data samples from [38] may also be found at `https://doi.org/10.5281/zenodo.5860144`.

data and simulation in IgH are partly the result of small sample size: this particular simulation sample did not recapitulate the very tail of the data distribution (i.e. the single data cluster of size 18), but if we had drawn many such samples they (by construction) would have sampled the very tail. For light chain,

on the other hand, the single chain distributions are well matched, but the simulation joint distribution is less clonal than that in data. It is possible that this reflects a breakdown of the assumption of no biological pairing correlation: low (but non-zero) correlation in data would manifest as having split fewer than expected light clusters based on heavy information (and vice versa). Overall, we think these discrepancies are minor for our current purposes, and in the future plan to more thoroughly investigate biological pairing correlation in data. We also directly compare distributions for a handful of other parameters on data and simulation for this sample (S9 Figure, with all other parameters and samples in `https://doi.org/10.5281/zenodo.5860144`).

Fig 7. **Pair info cleaning effectiveness on real data** for a relatively well-paired sample (left, same sample as Fig 6) and a sample with substantial numbers of multiply-paired sequences (right, not yet published). The x axis shows the number of sequences paired with each sequence ("paired seqs per seq") before and after application of our pair info cleaning algorithm. Thus for example a perfectly paired sample (with perfect allelic exclusion, no dropout, etc.) would have all sequences in the 1-bin (i.e. uniquely paired), while a sample with two cells in each droplet would have all sequences in the 3-bin. So an ideal application of our algorithm would leave every sequence uniquely paired (all in the 1-bin), but in practice some are left unpaired (0-bin).

We also show the results of our pair cleaning algorithm on two real data samples (Fig 7). The first, demonstrating typical (low) levels of multiple pairing information (i.e. multiple cells per droplet), corresponds to an example dataset from the

10X website [38]. The second, on the other hand, is a 10X sample from our collab-

orators where less than half of sequences start out uniquely paired (not yet pub-

lished). Our method leaves both samples with the majority of sequences uniquely

paired, while a small fraction are left unpaired.

General partis improvements. While many improvements have been incorpo-

rated into the partis methods since initial publication [39], recent changes to the

inference of the collection of parameters necessary to specify a naive rearrange-

ment (gene calls, insertions, and deletion lengths), which we refer to as an *anno-*

tation, are particularly significant and will be described here. In order to handle

large data sets, the emission probabilities in the multi-HMM are calculated inde-

pendently, i.e. the evolution of each family is viewed as a star tree for annotation

purposes. This is of course a poor approximation for families that have highly

imbalanced trees (those with large variance in root-to-tip distances). In order to

address this, we have introduced an iterative *subcluster annotation* scheme (see

Methods) that maintains the speed of the star tree assumption, but largely amelio-

rates the inaccuracy in annotation (Fig 8). Here we compare to several methods:

linearham [40], which uses a Bayesian phylogenetic HMM to fully calculate the

posterior probabilities of different trees and annotations; and IgBLAST, which is

one of the most popular general annotation methods. The current default "full"

partis comes closer to replicating linearham's accuracy while running much more

quickly (linearham typically takes minutes to hours on single families). It is impor-

tant to note, however, that linearham provides vastly more (and better) informa-

tion in its posterior probabilities than are in partis's largely heuristic uncertainty

estimates, so is much better suited to detailed analysis of single families.

DISCUSSION

We have introduced methods to enable inference of B cell clonal families on

samples with heavy/light chain pairing information. We first showed a method

Fig 8. **Naive sequence inference accuracy on simulation as a function of tree imbalance.** Accuracy is measured as the hamming distance separating the true and inferred naive sequences. Tree imbalance (the standard deviation of root-to-tip distances) is shown for samples with precisely zero imbalance ("n/a", since it uses a different simulation framework), and samples generated from the imbalanced trees from [40]. Several partis versions are shown: "1-seq." uses only information from each single sequence for its annotation (rather than from all family members); "star" approximates each family as a star tree (as in partis versions before May 2021 `https://bit.ly/3KIjFiF`); "full" is the current default, including subcluster annotation, which improves on the star tree assumption by iteratively annotating small subtrees. Each point is the mean (± standard error) over two samples with 15% mean nucleotide SHM, each consisting of 50 simulated rearrangement events with sizes of around 50 (drawn from geometric for zero imbalance; otherwise taken from the trees from [40]).

to refine single chain partitions using pairing information. This method dramati-

cally improves accuracy on simulation compared to a variety of other single chain

methods, and gives compatible results on real data. We then showed two meth-

ods that use inferred clonal family information to fix initially imperfect pairing

information. The first method disambiguates (or *cleans*) pair info in samples that

contain more than one cell per droplet, which could simplify sample preparation

by reducing the need for mono-dispersed droplets, as well as allowing overloading of droplets to increase sequencing depth. This method can salvage pair info for around 90% of sequences in families larger than three even in samples with 5-10 cells per droplet. The second method uses pair info from a single cell sample to approximately pair (correct up to family) sequences in a matched bulk sample (i.e. drawn from the same pool of B cells). Finally, we showed that our new subcluster annotation scheme improves annotation accuracy on families with imbalanced phylogenetic trees.

As far as we are aware, previous work in this area consists of a study that used early 10X data to investigate the potential for improving heavy partitions with light chain information [32]. Using four samples with sizes of 1,000-10,000, the authors performed single chain SCOPer clustering on heavy chain sequences, then looked for heavy clusters consisting of sequences whose light chain partners were "inconsistent", defined as different V gene, J gene, or CDR3 length. Since inference of these quantities is quite accurate, such clusters likely represent heavy chain families that were erroneously merged, and thus cases where light chain information could improve clustering. They found the fraction of such inconsistent clusters to be between 83 and 97% on the four samples, which is roughly in line with the collision frequency that we see in simulation (S6 Figure top left, difference between grey dashed line and 1, N families between 1k and 10k). It is important to note, however, that while the collision frequency is small for small samples, it increases very rapidly with the number of families, i.e. light chain information is much more important for larger samples. Another important point is that it is not possible to determine how many of these inconsistent clusters stem from actual collisions, as opposed to simply inaccurate or suboptimal clustering. The ideas from [32] have been implemented in SCOPer and used in practice [34].

We are not aware of any prior work in the vein of our pair info cleaning and approximate bulk pairing approaches.

There is room for improvement in our paired clustering method. The inference of clonal families with pairing information would be more intuitively straightforward, and likely also more accurate, if we used pairing information from the start. In other words, when preclustering with hamming distance on inferred naive sequences, we could use the distance over both heavy and light chain sequences. Then, in the likelihood-based HMM clustering, we could at each step simply take the product of likelihoods over both chains. However, this would require rewriting tens of thousands of lines of C++ and Python code to operate on two simultaneous rearrangement events (heavy and light), rather than one at a time, while still maintaining the existing single-chain functionality.

The effectiveness of our pair info cleaning method suggests that it may be possible to purposefully overload droplets in order to achieve higher sequencing depth. This idea is quite similar to that explored with the pairSEQ algorithm for T cells [41]. The difference for B cells, compared to T cells, is that clonal assignment is not trivial; however with partis the assignment is accurate enough that the approach appears feasible. We also note that we have used the pair cleaning algorithm with good results on (not-yet-published) non-10X data that flow-sorted cells into wells, but left multiple cells in some wells. Our method may also allow for simplified sample preparation, since the Poisson statistics determining cell-bead co-encapsulation often require very dilute suspensions to achieve mono-dispersion, which compromises efficiency [37].

Our approximate bulk sample pairing method suggests that paired sequencing depth could also be increased by using matched single cell and bulk samples drawn from the same pool of cells (e.g. a single blood draw). In contrast to pair info cleaning (disambiguating multiple cells per droplet), this approximate bulk pairing comes with the substantial caveat that we are seeking only to pair sequences with the correct family, not the correct sequence. For detailed phylogenetic studies, for instance, this will often not be sufficient. In some cases, however, we are simply searching for functional antibodies, and most sequences from the

correct family will likely still work. It is also worth noting that we can probably apply both approaches together: overload droplets in a single cell sample to get more real paired sequences, and then combine this with a bulk sample which we can then approximately pair.

One improvement to the actual pair cleaning method would be to distinguish multiply-paired heavy chains from multiple cells in a droplet. As suggested in [19], the latter would result in apparent cross-pairing of all pairs, while the former would show only limited combinations.

Another potential future direction is the investigation of biological pairing correlations. Earlier work in this area with small sample sizes found no evidence for biological pairing correlation, using single cell PCR of genomic DNA from 144 IgM cells [30], and 365 IgG cells [31]. Later work with larger samples, however, detected pairing preferences for a small proportion of germline genes using 545 human and 1456 mouse antibodies from the KabatMan database [29]. Evidence for the coevolution of particular non-self-reactive heavy/light gene combinations [3] provides additional, independent support for some level of preference. Work on T cells, meanwhile, while not necessarily informative for B cells, has found that heavy/light chain pairing is almost, but not quite, uniformly random [42].

METHODS

Paired clustering algorithm. The goal of clonal family inference is to construct a partition of the sample by grouping together the sequences stemming from each single rearrangement event. Our paired clustering method does this in two basic steps: it first clusters heavy and light chains individually with the partis single chain partition method, then refines these *single chain partitions* using their mutual pairing information. While we will give an overview of the single chain method, we refer to the original publication for details [12].

Single chain clustering. partis single chain clustering begins by collapsing together all sequences with identical inferred naive sequences. We will use *cluster* to mean

a set of sequences together with its ordering. Here, and at each later stage, upon forming a new cluster we immediately infer the annotation (the collection of gene calls, insertions, and deletion lengths necessary to specify a naive rearrangement) of that cluster. This is because annotation inference on several simultaneous sequences is much more accurate than on single sequences (see Key Translation below).

Single chain clustering then proceeds via hierarchical agglomeration. This consists of considering each pair of clusters in the current partition and merging the pair deemed most likely to be clonal, with a likelihood calculated with a multi-HMM describing that cluster of sequences. This is repeated until none of the pairs are more likely to be clonal than non-clonal. At each step, we ignore cluster pairs whose inferred naive sequences are very different, and immediately merge those that are very similar, using per-sample thresholds that vary with mean SHM level, and that were originally calculated with a simulation-based optimization procedure [12]. We thus only calculate the HMM likelihood for cluster pairs with somewhat similar naive sequences. The multi-HMM lets us calculate separately the likelihood that two sequences stem from the same rearrangement, and that each of them stem from separate events. We thus simply merge pairs for which the first is larger, and stop clustering when no pairs meet this criterion (or, optionally, continue beyond this point to explore less-likely partitions). The end result is thus not just a single partition, but a list of partitions together with their likelihoods.

The vsearch partis method similarly begins by grouping together sequences with identical inferred naive sequences. Each such group is then represented by its common naive sequence, and these are then grouped by CDR3 length. Each such CDR3 length class is then passed to the vsearch clustering method [43], which performs highly optimized distance-based clustering using a specified threshold. We use a threshold chosen with a simulation optimization procedure similar to, but separate from, that described above for naive hamming preclustering.

Refinement with pairing information. At this point we have partitions for the heavy and light chains that each contain sequences from the same cells. We want to resolve the discrepancies between these two partitions. Most commonly, a single cluster in one partition will correspond to multiple clusters in the other, and these multiple clusters will usually have very different annotations (e.g. different CDR3 lengths). While we handle the more general case of arbitrarily discrepant clusters, this common case leads to the choice of a fundamental bias in our approach: when resolving discrepancies we look only to split clusters, not merge them. Another way to look at this is that information from the other chain can give us an extremely strong signal that we should split a cluster (if the multiple clusters are very different), but on the other hand given multiple clusters in the current chain, having very similar sequences in the other chain is not a clear signal that we should merge them. Thus the net effect of our method is almost always to split apart single chain clusters; however because of the need to consider all clusters at once, this splitting is not accomplished directly, but instead by avoiding specific merges.

We now introduce the algorithm more formally. For this, the underlying key objects are pairs of heavy and light chain sequences and clusters thereof. We can think about these pairs as actual pairs of sequences, or as an identifier that is shared between a heavy chain sequence and a light chain sequence, but is unique among such pairs. These identifiers correspond to the labels in (Fig 9). Assume we are given a partition P_h on the pairs/identifiers based on heavy chain sequences and light chain partition on the pairs/identifiers P_l based on light chain sequences.

We begin by considering, in turn, each cluster in both the heavy partition P_h and light partition P_l (see Algorithm 1). Consider a cluster C_l from P_l: its size and constituent light chain sequences have been determined during single chain clustering by the likelihood that they are clonally related. We will walk through the algorithm to completion using C_l. We now want to see if there might be convincing evidence in P_h that we should split C_l. We thus proceed by collecting the list of clusters from P_h that overlap with C_l, which we call $\{C_h^i\}$ (Fig 9).

Fig 9. **Resolving discrepancies for one cluster between the heavy and light partitions (left) and incorporating a (different) group of resolved clusters into the final partition (right).** Left: After selecting a single cluster C_l from one partition, we then take all clusters from the other partition (the $\{C_h^i\}$) that contain any of the same three sequences **a**, **b**, and **c**. We then determine how C_l should be split apart using the $\{C_h^i\}$, and finish with the resulting "resolved" clusters C_R^i. Right: After several rounds of discrepancy resolution, we have a partially complete final partition P_f into which we must incorporate each new group of resolved clusters C_R^i. We do this by removing common sequences from the larger of any two clusters that share sequences (regardless of whether the larger cluster is in P_f or in C_R^i). In this case, this means we remove the **e** from **de** in P_f, as well as removing the **f** from **ef** in C_R^i.

In order to determine if and how to split apart C_l using the $\{C_h^i\}$, we first separate the $\{C_h^i\}$ into groups by CDR3 length. Since inferred CDR3 length is essentially always correct, we definitely want to split C_l apart into sets if the corresponding heavy chain sequences have a different CDR3 length. Within each such CDR3 group, we also want to split clusters that have different enough inferred naive sequences that they confidently come from different rearrangements. For each cluster in the CDR3 group, we thus make a list of clusters from which it should be split (its "split list"): those with inferred naive hamming distance above some threshold. This threshold is currently that described for *vsearch partis* above, and depends on the sample's SHM level, but is typically around 5%. Future optimization of this threshold may prove worthwhile; however so far we

have found clustering performance to be quite insensitive to its value (results not shown), likely because most splits involve very different families that are either far from this threshold or have different CDR3 lengths.

The algorithm implements the splitting in terms of "split lists" for each cluster that contain other clusters with which it should *not* be merged. The splitting procedure described above is then actually implemented by merging together all clusters that do not appear in each other's split lists (Fig 9). This effectively preserves all the between-cluster boundaries in each partition of which we are relatively confident, while merging everything else.

We have now "resolved" the discrepancies between C_l and the $\{C_h^i\}$, and thus call the resulting clusters the resolved clusters C_R^i. Note that C_l and the $\{C_h^i\}$ do not in general contain identical sequences.

We must now incorporate the resolved C_R^i into the final partition P_f (Fig 9). Since the C_R^i constitute a sub-partition (i.e. have no duplicate sequences), adding the first group of them, when P_f is empty, is trivial. As we proceed, however, and P_f grows, their incorporation becomes increasingly complex, since the $\{C_h^i\}$ (and thus C_R^i) for one C_l can in general overlap in a complicated way with the $\{C_h^i\}$ for another C_l. In other words, when we finish a new group of C_R^i, we must go through the clusters already in P_f with which these C_R^i overlap, and decide whether to believe the splits between existing clusters in P_f, or the new ones in C_R^i. Since the goal of the discrepancy resolution procedure from which we derive the C_R^i is to introduce new splits about which we are highly confident, and because a new split is likely based on new information, we do this largely by believing the more-highly-split alternative. To accomplish this, we examine each pair of clusters (one from the C_R^i and one from P_f) that share sequences. If this is the first such pair, we simply remove and discard the common sequences from whichever of the clusters is larger. For subsequent pairs, in order to avoid merging sequences from different resolved clusters, we must remove the common sequences from both, and add the common sequences as their own cluster.

We have just resolved the discrepancies between one cluster C_l in P_l and all

clusters in C_h with which it overlaps. We then repeat this procedure for every

other cluster in P_l, and similarly every cluster in P_h. The final result is then a

single partition that we use for both heavy and light chain sequences.

Pair info cleaning. Ideally, the pairing information for a sequence would always

consist of a single unique paired sequence with reciprocal pairing information. In

practice, however, due either to failed sequencing of one chain, the presence of

multiple cells per droplet, or a combination of the two, we can also get zero or

more than one paired sequence. Because our paired clustering algorithm requires

that all sequences have precisely one partner, we have developed a method to

infer which of a number of potential partners is correct. In cases where it cannot,

it removes all pairing information from the sequence. The result is thus that after

application all sequences have either zero or one partner.

Our method is based on the observation that correct pair info will be shared

among members of a clonal family, while spurious partners will not. This depends

on the fact that the processes that apportion cells to droplets are entirely indepen-

dent of clonal family identity. If we consider a single cluster C_h in the heavy chain

partition, the correct partner for each sequence will be in the same family as the

correct partners of other sequences in C_h (Fig 10). For this cluster C_h we collect the

families of all opposite-chain sequences that appear in a droplet with a member of

C_h, and sort these opposite-chain families by the number of C_h members with

which they're paired. For each sequence in C_h with multiple potential partners,

we then choose as its final partner the opposite-chain sequence that is a member

of the opposite-chain family with the most such "votes". In the case of ties, if the

tied sequences are from the same opposite chain family we choose one at random

(since they likely stem from the same physical molecule); otherwise we discard all

pairing information for the sequence. Whenever we choose a unique partner for a

sequence, we remove both sequences from the pair info of all other sequences.

Algorithm 1: Paired clustering method.

---

1 **function** **resolve_clusters**(C_l, $\{C_h^i\}$)

    // Resolve clustering discrepancies between C_l and $\{C_h^i\}$: reapportion seqs from them into **rslvd_clusters**, always splitting by CDR3, and sometimes also by naive hamming distance.

2   **if** length of $\{C_h^i\}$ < 2 **then**

3   **return** C_l

4   **rslvd_clusters**: list of resolved clusters to return

5   **len_groups**: $\{C_h^i\}$ grouped by CDR3 length

6   **for** lgrp **in** len_groups **do**

7   **split_lists**: for each cluster in $\{C_h^i\}$, a list of clusters with which it should *not* be merged

8   **for** $\mathbf{c_1}$, $\mathbf{c_2}$ **in** all pairs of clusters in **lgrp do**

9   **if** naive hamming distance between $\mathbf{c_1}$ and $\mathbf{c_2}$ $> d_0$ **then**

10   Add $\mathbf{c_1}$ to **split_lists**[$\mathbf{c_2}$]

11   Add $\mathbf{c_2}$ to **split_lists**[$\mathbf{c_1}$]

12   **len_rclusts**: resolved clusters for this CDR3 length group

13   **for** cclust **in** lgrp **do**

14   **if** a cluster **c** exists in **len_rclusts** that has no overlap with any cluster in **split_lists**[cclust] **then**

15 $\mathbf{c} := \mathbf{c} \cup \mathbf{cclust}$

16   **else**

17   Append **cclust** to **len_rclusts**

18   Append **len_rclusts** to **rslvd_clusters**

19   **return** **rslvd_clusters**

20 **final_partition**: final, joint partition

21 P_h, P_l: single chain heavy and light partitions

22 **for** C_l **in** P_l **do**

23 $\{C_h^i\}$: all clusters in P_h that overlap with C_l

24   **rslvd_clusters** = resolve_clusters(C_l, $\{C_h^i\}$)

25   **for** fclust **in** final_partition **do**

26   **rf_clusts**: clusters in **rslvd_clusters** that overlap with **fclust**

27   **for** rfc **in** rf_clusts **do**

28   **ovrlp**: intersection of **rfc** and **fclust**

29   **if** rfc is the first cluster in **rf_clusts then**

30   Remove **ovrlp** from the larger of **rfc** or **fclust**

31   **else**

32   Remove **ovrlp** from both **rfc** and **fclust**

33   Append **ovrlp** to **rslvd_clusters** as a new cluster

34   Append **rslvd_clusters** to **final_partition**

35 **for** C_h **in** P_h **do**

36   Same procedure as for C_l

Fig 10. **Schematic representation of the pair info cleaning algorithm** showing five droplets, each with some combination of IgH, IgK, and IgL sequences, with subscripts (and color combinations) indicating clonal families. The top left, top right, and bottom left droplets have unique pairings, so require no action. The top middle and bottom right droplets, on the other hand, require disambiguation. In the top middle droplet, h_1 has two potential light chain partners: k_1 and k_3. Since k_1 has three h_1 family members paired with it across all the droplets, while k_3 has only one, we choose k_1 (red arrow). A similar procedure is then followed for the bottom right droplet.

Sequences with zero potential partners can thus arise either in the original data

(e.g. from sequencing failure), or as the result of our algorithm's inability to deter-

mine a unique partner. In either case, we are left with a sequence that we want to

include in the final partition, but for which we have no pair info. For each such

sequence we thus make note of its nearest (by hamming distance) paired single

chain family member, then ignore the unpaired sequences during paired cluster-

ing. After paired clustering, each such unpaired sequence is then added to the

final family of its nearest paired single chain family member. If the unpaired se-

quence was in a family with no paired sequences, that family remains together;

any unpaired singletons remain as singletons. The idea is that nearby sequences,

i.e. with shared mutation patterns, come from the same sublineage in the tree.

Thus in cases where different sublineages in actuality stem from different, collided rearrangement events, sequences that have no pair info will be able to piggy back on the clustering refinement from those that do.

There are a number of ways to improve on this algorithm. Since our power to determine correct pairings comes from partition information, more accurate partitions would likely improve performance. Because having pair info immediately and dramatically improves partition accuracy, a procedure that iteratively applied pair cleaning and paired clustering would be an easy way to accomplish this. We would first clean pair info using initial single chain partitions, then run paired clustering with this initial pair info, then re-run pair info cleaning with these improved partitions, and so on. An integrated approach, perhaps utilizing a simultaneous likelihood on pair info and partitioning, would probably be even better, although likely also much more difficult to implement. Within each family and droplet in the existing algorithm, it would probably also be better to start with the sequences most likely to be correctly paired, so that once they're successfully paired they can be eliminated from the potential partners of others.

Approximate bulk pairing. While single cell (paired) data is increasingly easy to produce, bulk (unpaired) data can still be produced with much greater depth. We have thus developed an algorithm that, given single cell and bulk samples drawn from the same pool of B cells, allows to approximately pair sequences from the bulk data using pair info from the single cell data. By "approximately" we mean that it can pair sequences with partners from the correct family, although often not the correct sequence. In many cases, however, this will be sufficient to create a functional antibody.

As with pair info cleaning, we begin with the single chain partitions. For each cluster containing at least one paired sequence, we pair each unpaired sequence with the partner of the nearest (by hamming distance) paired sequence. Unpaired

sequences in clusters with no paired sequences are left unpaired. This has the effect of synchronizing pair info among sequences in sublineages within each cluster, which is important since these single chain clusters will contain significant numbers of collisions.

Because the accuracy of this procedure depends on the accuracy of the partitions, as with pair info cleaning an approach that iteratively applied bulk pairing and paired clustering would likely be significantly more accurate.

General partis improvements. While there have been many changes to various parts of partis since the original clustering paper, we highlight two here, partly because they are important, and partly as representative examples.

Subcluster annotation. As described above and in [39], the partis multi-HMM that is used for simultaneous inference on multiple sequences calculates emission probabilities at each position separately for each sequence. This is necessary for computational efficiency: simply multiplying together a number for each sequence is extremely fast. However, it is equivalent to assuming a star tree phylogeny for the family; or equivalently that every mutation in every sequence occurred as a separate mutation event. This is of course a poor assumption for some families, particularly those with highly unbalanced trees (i.e. with large variance in root-to-tip distances).

The most accurate course of action would to incorporate the full phylogenetic likelihood into the emission probabilities. This is what is done by linearham [40], which uses a Bayesian phylogenetic HMM to calculate the posterior probabilities of different trees and annotations. While linearham is extremely useful for analyzing single lineages, the approach will never be fast enough to run on entire repertoires. We thus developed an iterative *subcluster annotation* scheme that maintains the speed of the star tree assumption, but largely ameliorates the inaccuracy in annotation.

The basic premise of subcluster annotation is that, zoomed in far enough, every tree looks like a star tree. We thus maintain the star tree assumption, but instead of

applying it to the entire family of size N, we apply it only to subclusters of a certain size n_s by splitting the family into (roughly) N/n_s subclusters using a procedure described below. We then extract the resulting N/n_s inferred naive sequences, and treat them as the observed sequences, again splitting into subclusters of (roughly) size n_s. We then iterate until we are left with a single cluster of (roughly) size n_s. The optimal subcluster size n_s, as determined by extensive simulation validation (results not shown), is around 3, although accuracy is not particularly sensitive to this value.

Also note that we refer to sizes as "roughly" equal because when dividing a family of arbitrary size into integer-sized subclusters, we cannot, in general, make all subclusters exactly the same size. Note also that the goals of making all sub-clusters the same size, and of making each of them close to n_s, are in conflict. We have chosen to implement it such that the parameter n_s is the maximum cluster size, i.e. if it is set to 3, then all clusters are of size 3 or 2, thereby prioritizing sim-ilarity of cluster sizes. For instance, an initial cluster with size 10 would first be split into 4 clusters with sizes 3, 3, 2, and 2; then two with sizes 2 and 2, and finally a single cluster with size 2.

The sequences in each subcluster are determined by the order of sequences in the original cluster; since each cluster is constructed via hierarchical agglomera-tion while maintaining cluster order during merges, this means that similar se-quences tend to end up in the same subcluster. For example, in this size 10 cluster example we would in the first step draw cluster boundaries between the third and fourth sequences, between the sixth and seventh sequences, and between the eighth and ninth sequences. We also tried constructing subclusters by choosing sequences uniformly at random, as well as with k-means clustering, but results did not improve (results not shown).

The end result of this procedure is that the naive sequence inferred on the final cluster is, effectively, the result of weighting by the tree structure, and represents the naive sequence of the entire family.

Subcluster annotation typically takes a similar amount of time to the original star tree method. Annotation time for each [sub]cluster is linear in its size, so each individual subcluster step is parallelized and much faster; but there are now several steps to run, along with some processing infrastructure between steps. For instance annotating a 3000 sequence cluster with the old method takes about 5 seconds; with subcluster annotation this requires 8 steps, each taking between 0.3 and 1 seconds, resulting in a total time of also around 5 seconds.

Key translation. The multi-HMM, which forces multiple sequences through the same path in the HMM, is an integral part of both the forward and Viterbi calculations used for clustering [39]. The inferred naive sequence from the Viterbi algorithm, for instance, is much more accurate on multiple sequences than on one alone [39]. The accuracy of both the naive sequence (S10 Figure) and likelihood (results not shown) calculations, however, increase quite quickly with the number of sequences. Because the time required, on the other hand, scales linearly with the number of sequences, we thus implemented a subsampling scheme such that during hierarchical agglomeration we never calculate on more than a relatively modest number of simultaneous sequences. Because this effectively translates the key constructed from the unique IDs for a cluster into a different, smaller, key we refer to it as "key translation".

During hierarchical agglomeration, we thus replace each cluster larger than some size n_t with a smaller cluster consisting of n_t uniform randomly chosen sequences. We found that a value of n_t around 15 was optimal for both the forward calculation and for naive inference (full results not shown, although see S10 Figure), although both values can be adjusted on the command line if desired. Partly because hierarchical agglomeration involves calculations for a large number of potential cluster merges that do not end up occurring, this technique increases speed by as much as an order of magnitude on samples with large and/or similar clusters (S11 Figure). Upon completion of clustering, for maximum accuracy we calculate

the likelihood of and annotation for the final partition using the full clusters (with no key translation).

One complication is that we very commonly encounter a long series of sequential steps that each merge a singleton into a much larger cluster. Each individual step is very unlikely to significantly change either the forward probability or inferred naive sequence, so it is very wasteful to recalculate at every step. For merges in which one cluster is much larger than the other (by default 4 times larger) we thus retain the larger parent's values without recalculation. Keeping track of these translations and propagating them through merging steps is quite involved, but for further details we refer to the relevant section of code `https://git.io/JSiOi`.

——-

ACKNOWLEDGEMENTS

We would first like to thank our collaborators who created data that was used during development of these methods: Leslie Goo, Lisa Levoir, Jay Lubow, Julie Overbaugh, Jamie Guenthoer, Michelle Lilly, and Zak Yaffe. We would also like to thank the Kleinstein lab for help with SCOPer, and Kristian Davidsen for help editing the manuscript, as well as for suggesting the possibility of approximately pairing bulk data with a matched single cell sample.

This work supported by NIH grants R01 AI146028 (PI Matsen), U01 AI150747 (PI Rustom Antia), as well as R01 AI120961 and R01 AI138709 (PI Julie Overbaugh). The research of Frederick Matsen was supported in part by a Faculty Scholar grant from the Howard Hughes Medical Institute and the Simons Foundation, and he is an investigator of the Howard Hughes Medical Institute. Scientific Computing Infrastructure at Fred Hutch funded by ORIP grant S10OD028685.

REFERENCES

1. Nemazee D. Mechanisms of central tolerance for B cells. Nat Rev Immunol. 2017 May;17(5):281–294.

2. Chi X, Li Y, Qiu X. V(D)J recombination, somatic hypermutation and class switch recombination of immunoglobulins: mechanism and regulation. Immunology. 2020 Jul;160(3):233–247.

3. Collins AM, Watson CT. Immunoglobulin Light Chain Gene Rearrangements, Receptor Editing and the Development of a Self-Tolerant Antibody Repertoire. Front Immunol. 2018 Oct;9:2249.

4. Nemazee D. Receptor editing in lymphocyte development and central tolerance. Nat Rev Immunol. 2006 Oct;6(10):728–740.

5. Safonova Y, Pevzner PA. V(DD)J recombination is an important and evolutionary conserved mechanism for generating antibodies with unusually long CDR3s. Genome Res. 2020 Sep;.

6. Pieper K, Tan J, Piccoli L, Foglierini M, Barbieri S, Chen Y, et al. Public antibodies to malaria antigens generated by two LAIR1 insertion modalities. Nature. 2017 Aug;548(7669):597–601.

7. Watson LC, Moffatt-Blue CS, McDonald RZ, Kompfner E, Ait-Azzouzene D, Nemazee D, et al. Paucity of V-D-D-J rearrangements and VH replacement events in lupus prone and nonautoimmune TdT-/- and TdT+/+ mice. J Immunol. 2006 Jul;177(2):1120–1128.

8. DeKosky BJ, Kojima T, Rodin A, Charab W, Ippolito GC, Ellington AD, et al. In-depth determination and analysis of the human paired heavy- and light-chain antibody repertoire. Nat Med. 2015 Jan;21(1):86–91. Available from: `http://dx.doi.org/10.1038/nm.3743`.

9. Leenders AM, Kroeze LI, Rijntjes J, Luijks J, Hebeda KM, Darzentas N, et al. Multiple immunoglobulin kappa rearrangements within a single clone unraveled by NGS-based clonality assessment. J Mol Diagn. 2021 May;.

10. Georgiou G, Ippolito GC, Beausang J, Busse CE, Wardemann H, Quake SR. The promise and challenge of high-throughput sequencing of the antibody repertoire. Nat Biotechnol. 2014 Feb;32(2):158–168.

11. Gilchuk P, Bombardi RG, Erasmus JH, Tan Q, Nargi R, Soto C, et al. Integrated pipeline for the accelerated discovery of antiviral antibody therapeutics. Nat Biomed Eng. 2020 Nov;4(11):1030–1043.

12. Ralph DK, Matsen FA 4th. Likelihood-Based Inference of B Cell Clonal Families. PLoS Comput Biol. 2016 Oct;12(10):e1005086.

13. Gupta NT, Vander Heiden J, Uduman M, Gadala-Maria D, Yaari G, Kleinstein SH. Change-O: a toolkit for analyzing large-scale B cell immunoglobulin repertoire sequencing data. Bioinformatics. 2015 10 Jun;.

14. Bolotin DA, Poslavsky S, Mitrophanov I, Shugay M, Mamedov IZ, Putintseva EV, et al. MiXCR: software for comprehensive adaptive immunity profiling. Nat Methods. 2015 29 Apr;12(5):380–381.

15. Glanville J, Kuo TC, von Büdingen HC, Guey L, Berka J, Sundar PD, et al. Naive antibody gene-segment frequencies are heritable and unaltered by chronic lymphocyte ablation. Proc Natl Acad Sci U S A. 2011 Dec;108(50):20066–20071.

16. Vigneault F, Kleinstein SH. Hierarchical clustering can identify B cell clones with high confidence in Ig repertoire sequencing data. The Journal of. 2017;.

17. Nouri N, Kleinstein SH. A spectral clustering-based method for identifying clones from high-throughput B cell repertoire sequencing data. Bioinformatics. 2018 Jul;34(13):i341–i349.

18. Doepker LE, Simonich CA, Ralph D, Shipley MM, Garrett M, Gobillot T, et al. Diversity and Function of Maternal HIV-1-Specific Antibodies at the Time of Vertical Transmission. J Virol. 2020 Apr;94(9).

19. DeKosky BJ, Ippolito GC, Deschner RP, Lavinder JJ, Wine Y, Rawlings BM, et al. High-throughput sequencing of the paired human immunoglobulin heavy and light chain repertoire. Nat Biotechnol. 2013 Feb;31(2):166–169. Available from: `http://dx.doi.org/10.1038/nbt.2492`.

20. McDaniel JR, DeKosky BJ, Tanno H, Ellington AD, Georgiou G. Ultra-high-throughput sequencing of the immune receptor repertoire from millions of lymphocytes. Nat Protoc. 2016 Mar;11(3):429–442. Available from: `http://dx.doi.org/10.1038/nprot.2016.024`.

21. Grigaityte K, Carter JA, Goldfless SJ, Jeffery EW, Hause RJ, Jiang Y, et al. Single-cell sequencing reveals $\alpha\beta$ chain pairing shapes the T cell repertoire; 2017.

22. Zheng GXY, Terry JM, Belgrader P, Ryvkin P, Bent ZW, Wilson R, et al. Massively parallel digital transcriptional profiling of single cells. Nat Commun. 2017 Jan;8:14049.

23. Kulkarni A, Anderson AG, Merullo DP, Konopka G. Beyond bulk: a review of single cell transcriptomics methodologies and applications. Curr Opin Biotechnol. 2019 Aug;58:129–136.

24. Marcus JS, Anderson WF, Quake SR. Microfluidic single-cell mRNA isolation and analysis. Anal Chem. 2006 May;78(9):3084–3089.

25. White AK, VanInsberghe M, Petriv OI, Hamidi M, Sikorski D, Marra MA, et al. High-throughput microfluidic single-cell RT-qPCR. Proc Natl Acad Sci U S A. 2011 Aug;108(34):13999–14004.

26. Furutani S, Nagai H, Takamura Y, Aoyama Y, Kubo I. Detection of expressed gene in isolated single cells in microchambers by a novel hot cell-direct RT-PCR method. Analyst. 2012 Jun;137(13):2951–2957.

27. Turchaninova MA, Britanova OV, Bolotin DA, Shugay M, Putintseva EV, Staroverov DB, et al. Pairing of T-cell receptor chains via emulsion PCR. Eur J Immunol. 2013 Sep;43(9):2507–2515.

28. Shaw JB, Liu W, Vasil Ev YV, Bracken CC, Malhan N, Guthals A, et al. Direct Determination of Antibody Chain Pairing by Top-down and Middle-down Mass Spectrometry Using Electron Capture Dissociation and Ultraviolet Photodissociation. Anal Chem. 2020 Jan;92(1):766–773.

29. Jayaram N, Bhowmick P, Martin ACR. Germline VH/VL pairing in antibodies. Protein Eng Des Sel. 2012 Oct;25(10):523–529.

30. Brezinschek HP, Foster SJ, Dörner T, Brezinschek RI, Lipsky PE. Pairing of variable heavy and variable kappa chains in individual naive and memory B cells. J Immunol. 1998 May;160(10):4762–4767.

31. de Wildt RM, Hoet RM, van Venrooij WJ, Tomlinson IM, Winter G. Analysis of heavy and light chain pairings indicates that receptor editing shapes the human antibody repertoire. J Mol Biol. 1999 Jan;285(3):895–901.

32. Zhou JQ, Kleinstein SH. Cutting Edge: Ig H Chains Are Sufficient to Determine Most B Cell Clonal Relationships. J Immunol. 2019 Oct;203(7):1687–1692.

33. Abdollahi N, de Septenville A, Ripoche H, Davi F, Bernardes JS. A multi-objective based clustering for inferring BCR clones from high-throughput B cell repertoire data; 2021.

34. Hoehn KB, Ramanathan P, Unterman A, Sumida TS, Asashima H, Hafler DA, et al. Cutting Edge: Distinct B Cell Repertoires Characterize Patients with Mild and Severe COVID-19. J Immunol. 2021 May;.

35. Ralph DK, Matsen FA 4th. Using B cell receptor lineage structures to predict affinity. PLoS Comput Biol. 2020 Nov;16(11):e1008391.

36. Horns F, Dekker CL, Quake SR. Memory B Cell Activation, Broad Anti-influenza Antibodies, and Bystander Activation Revealed by Single-Cell Transcriptomics. Cell Rep. 2020 Jan;30(3):905–913.e6.

37. Luo X, Chen JY, Ataei M, Lee A. Microfluidic Compartmentalization Platforms for Single Cell Analysis. Biosensors. 2022 Jan;12(2).

38. Datasets -Single Cell Immune Profiling -Official 10x Genomics Support;. Accessed: 2022-3-18. https://support.10xgenomics.com/single-cell-vdj/datasets/5.0.0/sc5p_v2_hs_B_postvax_10k_5gex_B.

39. Ralph DK, Matsen FA IV. Consistency of VDJ Rearrangement and Substitution Parameters Enables Accurate B Cell Receptor Sequence Annotation. PLoS Comput Biol. 2016 Jan;12(1):e1004409. Available from: http://dx.doi.org/10.1371/journal.pcbi.1004409.

40. Dhar A, Ralph DK, Minin VN, Matsen FA IV. A Bayesian Phylogenetic Hidden Markov Model for B Cell Receptor Sequence Analysis. 2019 Jun;.

41. Howie B, Sherwood AM, Berkebile AD, Berka J, Emerson RO, Williamson DW, et al. High-throughput pairing of T cell receptor α and β sequences. Sci Transl Med. 2015 Aug;7(301):301ra131.

890   42. Shcherbinin DS, Belousov VA, Shugay M. Comprehensive analysis of structural and sequencing

891   data reveals almost unconstrained chain pairing in TCR$\alpha\beta$ complex. PLoS Comput Biol. 2020

892   Mar;16(3):e1007714.

893   43. Rognes T. Github Repository. 2015;Available from: `https://github.com/torognes/`

894   `vsearch`.

S1 Figure. **Schematic representation of the space of possible antibodies/antigens, or** *rearrangement space*. The immune system populates the space with naive rearrangements (green crosses) such that any antigen (red squares) will be somewhat near to an antibody. After stimulation by its cognate antigen, a B cell will migrate to a germinal center and undergo affinity maturation to move its offspring closer to the antigen (black tree).

S2 Figure. **Schematic representation of clustering error in re-arrangement space.** If clustering (red circles) is performed on observed (mutated) sequences (black dots), sequences in a family are unnecessarily far from each other. It is much better to cluster on the inferred naive ancestor (blue crosses) of each sequence (and, as clustering progresses, the naive ancestor inferred on the entire cluster at that point in time). Clustering on observed sequences thus conflates SHM (distance from black dots to blue crosses) with inference inaccuracy (distance from blue crosses to green crosses).

S3 Figure. **Clustering performance on simulation vs SHM in terms of precision (top) and sensitivity (bottom)** for heavy chain (left) and light chain (right). See Fig 2, which combines these values into the F1 score, for details.

S4 Figure. **Clustering performance on simulation vs SHM comparing single-chain to full (paired) partis clustering** in terms of F1 score (top), precision (middle) and sensitivity (bottom) for heavy chain (left) and light chain (right). See Fig 2, for details and compare to S5 Figure for SCOPer.

S5 Figure. **Clustering performance on simulation vs SHM comparing single-chain to full (paired) SCOPer clustering** in terms of F1 score (top), precision (middle) and sensitivity (bottom) for heavy chain (left) and light chain (right). See Fig 2 for details and compare to S4 Figure for partis.

 S6 Figure. **Clustering performance on simulation as a function of the number of families for single chain (no pair info, top) and joint partitions (with paired clustering, bottom)** for heavy chain (left) and light chain (right). In order to focus on the effect of family collisions (unrelated families that are experimentally indistinguishable), we show performance only in terms of precision, and on samples consisting only of singletons. Each point is the mean ($\pm$ standard error, often smaller than points) over three samples with 15% mean nucleotide SHM, each consisting of the indicated number of singleton families. See Fig 2 for details.

S7 Figure. **Effectiveness on simulation of the pair info clean-ing method as a function of number of cells per droplet, on samples with a variety of family size distributions** in terms of fraction of sequences correctly paired (top) and F1 score of the re-sulting joint partitions (bottom). Results shown for samples with family sizes drawn from a distribution inferred from real data (solid red line; corresponds to Fig 3), and where all families have the same, indicated size (dashed lines). Each point is the mean (± standard error, often smaller than points) over three samples, each consisting of 3,000 simulated rearrangement events. With no pair info cleaning, any cells that share droplets (i.e. all points to the right of 1) would have no pair info, which results in perfor-mance as shown for single-chain clustering, with very poor IgK precision (S4 Figure middle right, dashed green).

S8 Figure. **Effectiveness on simulation of the bulk data pairing method as a function of true family size,** shown as the fraction of sequences correctly paired (top); and the fraction not correctly paired, split into those mis-paired (bottom left) and left unpaired (bottom right). Note that essentially by construction, the fraction correctly paired is simply the paired (non-bulk) fraction of the sample; the goal of the method is to pair sequences with a sequence from the correct family, but not necessarily the correct sequence (Fig 4).

S9 Figure. **Comparison of parameter distributions on a real data sample (green) and a simulation sample generated using parameters inferred from that real data sample (red)** (see details in Fig 6). Shown here are cluster size distributions (top left), D gene usage (top middle), D 5' deletion lengths for all D genes together (top right), per-position SHM frequencies for IGHJ3*02 (bottom left), number of J segment mutations (over all J genes, bottom middle), and sequence amino acid content (bottom right). Distributions for all other parameters, and for the same studies performed on three other real data samples, may be found at https://doi.org/10.5281/zenodo.5860144.

S10 Figure. **Naive sequence inference accuracy on simulation as a function of family size.** Accuracy is measured as the hamming distance separating the true and inferred naive sequences. Each point is the mean ($\pm$ standard error) over three samples, each consisting of 50 simulated rearrangement events with the indicated size.

S11 Figure. **Time required for clustering with a single process vs the maximum calculated cluster size** on samples with 5000 sequences divided among the indicated number of families, each restricted to the same gene combination and CDR3 length to eliminate irrelevant families. Clusters larger than (approximately) the indicated size are subsampled for the Viterbi and forward calculations during clustering (see text).