AIRRscape: an interactive tool for exploring B-cell receptor repertoires and antibody responses

Eric Waltari[1,*], Saba Nafees[1], Joan Wong[1], Krista M. McCutcheon[1,#], John E. Pak[1,*]

[1]Chan Zuckerberg Biohub, San Francisco, California, United States of America

[*]Corresponding authors

E-mail: eric.waltari@czbiohub.org (EW) or john.pak@czbiohub.org (JEP)

[#]Current address: Immune-Onc Therapeutics Inc, Palo Alto, California, United States of America

Short title (65 characters): *AIRRscape: an interactive tool for exploring antibody repertoires*

Abstract

The sequencing of antibody repertoires of B-cells at increasing coverage and depth has led to the identification of vast numbers of immunoglobulin heavy and light chains. However, the size and complexity of these Adaptive Immune Receptor Repertoire sequencing (AIRR-seq) datasets makes it difficult to perform exploratory analyses. To aid in data exploration, we have developed AIRRscape, an R Shiny-based interactive web browser application that enables B-cell receptor (BCR) and antibody feature discovery through comparisons among multiple repertoires. Using AIRR-seq data as input, AIRRscape starts by aggregating and sorting repertoires into interactive and explorable bins of germline V-gene, germline J-gene, and CDR3 length, providing a high-level view of the entire repertoire. Interesting subsets of repertoires can be quickly identified and selected, and then network topologies of CDR3 motifs can be generated for further exploration. Here we demonstrate AIRRscape using patient BCR repertoires and sequences of published monoclonal antibodies to investigate patterns of humoral immunity to three viral pathogens: SARS-CoV-2, HIV-1, and DENV (dengue virus). AIRRscape reveals convergent antibody sequences among datasets for all three pathogens, although HIV-1 antibody datasets display limited convergence and idiosyncratic responses. We have made AIRRscape available on GitHub to encourage its open development and use by immuno-informaticians, virologists, immunologists, vaccine developers, and other scientists that are interested in exploring and comparing multiple immune receptor repertoires.

Author Summary

Technological advances in next generation sequencing have allowed for broad experimental sampling of immune repertoires, providing insight into how our immune system responds to infection, vaccination, autoimmunity, and cancer. The scale of these "big data", however, make it difficult to bioinformatically extract the key sequence features that are shared across multiple repertoires. With AIRRscape, we enable large-scale immune repertoire visualization and analysis that requires no knowledge of the command line or advanced programming. By providing the community with an open-source, interactive, and user-friendly interface, we reduce the barriers to exploring immune repertoires at scale. We demonstrate the use of AIRRscape to characterize features of immune responses to viral infection that are shared across multiple repertoire datasets.

1. Introduction

Individual B-cell receptor (BCR) repertoires have exceptional diversity, estimated to be greater than 10^9 in a single adult [1,2]. Improvements in sequencing capability over the past twenty years have allowed a wider sampling of BCR sequences to be uncovered [e.g. 3–5]. These adaptive immune receptor response sequence (AIRR-seq) datasets can offer a complex and information-rich glimpse into B-cell immune responses to vaccination and infection. For example, with analyses of AIRR-Seq data comes an increasing recognition that convergence among BCR repertoires, sometimes termed 'public' clonotypes [1,2,6,7], is important for understanding the humoral immune response to natural infections and for improving vaccine design.

The size of AIRR-Seq datasets can make it challenging to visualize the BCR sequence features of individual repertoires, let alone of multiple repertoires concurrently. Several groups have developed metrics to assess similarity among entire BCR repertoires [8,9], but few open-source tools enable facile, multi-dimensional visualization and exploration of these repertoires. Notable examples of higher-level BCR repertoire visualizations (e.g. for features such as V-gene and J-gene usage, CDR3 length, and CDR3 amino acid sequence motifs) include Circos plots [10], radial phylogenies [11], and clouds summarizing clonotype networks [12]. While powerful in offering a global overview of AIRR-Seq data, these methods are not amenable to interactive exploration, in particular to uncover and display antibody convergence.

To enable simultaneous interactive visualization of multiple BCR repertoires and in-depth data exploration, we have developed an open-source tool called AIRRscape. Analysis using AIRRscape begins with the generation of sequence feature heatmaps, which can span both individual or combined AIRR-Seq datasets. Visual comparison of these heatmaps in their entirety provides a simple and intuitive global overview of differences in three coupled AIRR-Seq dataset features: 1) V- and J-gene usage; 2) CDR length, and 3) either somatic hypermutation (SHM) or sequence read count. AIRRscape enables extraction of all sequences that fit a particular set of features from the heatmap (individual or combined datasets) into bins for finer scale local analysis. Topologies or phylogenetic networks of CDRH3 or CDRL3 amino acid motifs can be generated, on the fly, to examine clonotypes and study antibody convergence among multiple studies and patients. Recognizing the lack of consensus on how to define clonal lineages [2], we allow users to select from a range of CDR3 identity thresholds to define and visualize antibody convergence. AIRRscape can be deployed using R Shiny [13], allowing the tool to be easily used on any web browser without advanced programming or command-line expertise.

Here we use AIRRscape to examine collections of antibodies and BCR repertoires from three types of viral infections to address several questions. For SARS-CoV-2: how representative are published antibodies relative to healthy and COVID-19 patient repertoires, and how common are convergent antibody responses [14–16]? For HIV-1: how comparable are published anti-HIV-1 antibodies relative to SARS-CoV-2 antibodies as well as to HIV-1 patient repertoires, and how common are public antibody motifs [reported in 7]? For DENV: how

78 common are the convergent antibodies reported in recent studies [17–19]? We show that
79 AIRRscape provides an intuitive and explorable visualization of the convergent antibody
80 responses that occur in patients infected with SARS-CoV-2 or DENV, as well as the
81 idiosyncratic responses that are typical in HIV-1 due to high SHM.
82

2. Material and Methods

2.1 Datasets

Recent efforts by the AIRR Community [20,21] have led to the organization and
standardization of T-cell and B-cell repertoire analysis, enhancing the accessibility of BCR
repertoire datasets. Here we utilize two AIRR data repositories, iReceptor and Observed
Antibody Space [22–24], to gather BCR repertoire datasets in response to three viral
pathogens: SARS-CoV-2, HIV-1, and DENV, the causative agents of COVID-19, AIDS, and
dengue, respectively. Datasets primarily come from studies examining patient bulk BCR
repertoires [7,11,14,17,18,25–29]. We also examine repositories of known monoclonal
antibodies collated from multiple antibody discovery studies: CoV-AbDab for COVID-19 [30],
and for HIV/AIDS the IEDB and CATNAP databases [31,32] and a recent dataset by Yacoob et
al. [33]. For dengue, we focus on a set of described plasmablast sequences from two patients
[17,19]. All datasets are summarized in Table 1.
97

Table 1. Datasets used in AIRRscape.

Dataset	Data type	Sample	Reference	Source	Number of sequences
COVID-19	*SARS-CoV-2 mAbs*		2	CoV-AbDab database (2)	*4,306*
COVID-19	patient bulk repertoire	p11	11	iReceptor (22)	9,385
COVID-19	patient bulk repertoire	7450	26	iReceptor	15,645
COVID-19	patient bulk repertoire	galson-01	14	iReceptor	29,745
COVID-19	patient bulk repertoire	M5	25	iReceptor	18,711
Dengue	*dengue mAbs*		19	(19)	*79*
Dengue	patient bulk repertoire	d13	17	SRA	32,495
Dengue	patient bulk repertoires	45 patients	18	Observed Antibody Space (23)	198,119
Healthy control	bulk repertoire		28	SRA	50,942
HIV-1	*HIV-1 mAbs*		31	IEDB (31)	*98*
HIV-1	*HIV-1 mAbs*		32	CATNAP (32)	*441*
HIV-1	*HIV-1 mAbs*		33	(33)	*83*
HIV-1	patient bulk repertoire	NIH45	29	iReceptor	14,644
HIV-1	patient bulk repertoire	MT1214	27	iReceptor	33,855
HIV-1	patient bulk repertoires	6 CAPRISA patients	7	Observed Antibody Space	184,294

2.2 Data processing

BCR repertoire datasets are first downloaded either as flat files, which follow AIRR community standards, or as sequence files that are partially processed [e.g. the pRESTO

module of the Immcantation suite, 34]. For the repertoires in the latter category, the processing
is completed using two Change-O scripts from the Immcantation suite, 'changeo-igblast' and
'changeo-clone' [35]. The collated lists of antibodies against SARS-CoV-2 and HIV-1 are
focused on protein sequence and do not include SHM, the % nucleotide divergence from
germline, which thus needs to be calculated separately. For those antibody sequences we first
run a tblastn search to find perfectly matched nucleotide sequences, and then use the Change-
O scripts for processing (after checking to ensure the source is the same antibody without
codon optimization). The resulting repertoire datasets now follow the AIRR community
standards, with columns indicating the assigned V-gene (*v_call*), assigned J-gene (*j_call*),
mutation from germline V-gene (*v_identity*), and assigned V(D)J junction amino acid sequence
(*junction_aa*).
114
A function within a custom R script is used to further modify the BCR repertoire datasets
before visualization with Shiny. First we calculate the level of SHM from germline V-gene using
the standard column *v_identity*. We also calculate CDR3 amino acid length as defined by the
international ImMunoGeneTics information system® (IMGT) by removing the first and last
residue in the standard column *junction_aa*, with the new value called *cdr3length_imgt*. All
sequences with stop codons and sequences with CDR3 lengths that are missing, not divisible
by 3, or fewer than 3 amino acids are then removed. Lastly, we create additional columns used
in our tool, namely *gf* for the assigned V-gene family, *gf_jgene* for the V-gene family + J-gene
assignment, *ncount* for the count of sequences per unique combination of *gf_jgene* +
cdr3length_imgt, and *shm_mean* and *shm_max* for mean or maximum SHM, respectively, per
unique combination of *gf_jgene* + *cdr3length_imgt*.
126
To visualize multiple repertoires simultaneously, sets of antibodies and/or repertoires are
combined in two ways. We first visualize a set as separate faceted panels for individual
repertoires (see 2.3). We then combine these repertoires into a single panel, to enable searches
of antibody convergence. Due to their broader importance, only heavy chain antibody
sequences are visualized in each of these combined repertoires [36,37]. For all of the
repertoire-based visualizations, we compact the individual repertoires by collapsing all
sequences with the same *gf_jgene* + *cdr3length_imgt* bin assignments and identical CDR3
amino acid motifs. In datasets containing multiple individuals, we compact only individual
repertoires before combining them. A depiction of the workflow of dataset processing is
summarized in Fig 1.
137
138   **Fig 1. Workflow of repertoire data retrieval and processing.**
139

2.3 AIRRscape application
AIRRscape is developed as an interactive web application using R Shiny. We use
AIRRscape to visualize the main features of BCR repertoire datasets from processed flat files.
To begin, researchers can explore a generated heatmap with either multiple panels of individual
BCR repertoires (Fig 2A) or a single panel combining multiple repertoires (Fig 2B). The x-axis of
the heatmap shows antibodies binned according to their assigned V-gene family + J-gene
germline, while the y-axis shows CDR3 length. For this visualization, the user selects a dataset

along with one of three parameters for coloring the bins: by percent of overall total antibody
sequences, by average SHM of the bin, or by maximum SHM of the bin. The user can then
hover over the paneled heatmaps to view an interactive popup displaying a bin's attributes (Fig
2B). Clicking on a single bin or selecting multiple bins using a drawn rectangle produces a table
of antibodies and their features (Fig 3). Within the table, users can query by or focus on any of
the antibody features loaded in the datasets. Selected antibodies can be downloaded or further
explored via their topologies (i.e. their phylogenetic relationship, with the caveat that convergent
antibodies are not clonally related).
155
156 **Fig 2. AIRRscape visualization of immune repertoires.** Heatmaps comparing characteristics
157 of (A) separate and (B) combined datasets for anti-SARS-CoV-2 and anti-HIV-1 antibodies.
158
159 **Fig 3. AIRRscape interface showing antibodies and CDR3 amino acid topology of**
160 **selected antibody bin.** Selected bin is highlighted in the red box of Fig 2B.
161
Below the table of selected antibodies, AIRRscape displays interactive topologies of
CDR3 amino acid sequence similarity (Fig 3). Binning antibodies both by germline assignment
as well as CDR3 length enables examination of these CDR3 motifs in a phylogenetic
framework, since the CDR3 motifs will be 'aligned' when constrained to bins with a given CDR3
length. The labels of the topology tips conveniently display antibody names, assigned V-genes,
and CDR3 amino acid sequences. The major advantage of this approach is that thousands of
antibody CDR3 sequences can be visualized via a web browser for quick and easy exploration
by researchers without command-line expertise.
170
AIRRscape allows for multiple options to create CDR3 topologies. First, a user may
select a set of antibodies from the table for constructing their topology via either the neighbor-
joining or parsimony tree building methods [38]. Alternatively, a user can select a single
antibody sequence of interest to identify all similar sequences in that bin within a chosen amino
acid identity threshold. AIRRscape will then display a parsimony topology of these nearest
sequences. The options for identity threshold are 50%, 70% [used in 7], 80% [used in 6], and
100% [used in 1]. Topology tip colors are unique to each dataset. Lastly, the user has the ability
to change both the height and width of the topology. Height adjustment allows the user to more
easily visualize a small topology or examine a large topology (up to 500 sequences) across
more than one visible page; adjusting the width allows the user to see the full tip label when
there are long branch lengths.
182
Two custom R scripts, *airrscape_preprocessing.R* and *airrscape_processing.R*, are
included to document the data processing and to convert files that follow the aforementioned
AIRR community standards for loading into AIRRscape. AIRRscape can be run locally using
RStudio within a browser or be deployed onto a local server or service such as
https://shinyapps.io. Both the pre-processing scripts and the R Shiny code for AIRRscape are
available on GitHub at https://github.com/czbiohub/AIRRscape.
189

3. Results

To illustrate the utility of AIRRscape, we used it to explore the adaptive BCR responses to three viral pathogens: SARS-CoV-2, HIV-1 and DENV.

3.1 anti-SARS-CoV-2 antibody datasets share characteristics and convergent motifs

We first examined the CoV-AbDab database of validated monoclonal anti-SARS-CoV-2 antibodies and compared them to published bulk BCR repertoires of four COVID-19 patients, as well as to a healthy control bulk BCR repertoire. We visualized 2,153 paired antibody sequences from the CoV-AbDab dataset and a single representative repertoire from each study of COVID-19 patient bulk repertoires [11,14,25,26; Table 1]. After removing duplicate sequences (as described in 2.2), we compared 73,536 COVID-19 patient antibody CDRH3 motifs and 50,942 healthy control motifs (Fig 4).

Fig 4. AIRRscape heatmaps comparing anti-SARS-CoV-2 antibodies, bulk BCR repertoires of four COVID-19 patients, and a healthy control bulk BCR repertoire.

We first asked how representative the anti-SARS-CoV-2 antibodies are relative to patient repertoires and relative to a healthy control repertoire, based on the heatmap visualizations in AIRRscape. This analysis revealed that the overall pattern of heavy chain V-gene + J-gene usage versus CDRH3 length distribution does not differ among the CoV-AbDab dataset, the four patient repertoires, and the healthy control repertoire (Fig 4). The most common V+J gene family assignments in all datasets were IGHV3+IGHJ4, IGHV3+IGHJ6, IGHV4+IGHJ4, IGHV4+IGHJ6, IGHV1+IGHJ4 and IGHV1+IGHJ6. A notable visual difference between the datasets was the presence or absence of sequences assigned to IGHV7 (Fig 4), which is not unexpected given that this gene 'family' consists of a single functional V-gene that does not occur in all individuals [1]. SHM levels among the anti-SARS-CoV-2 antibodies (mean 2.3%) were lower than the four patient repertoires (overall mean 3.7%) and the healthy control repertoire (mean 3.3%), although the patient from the Galson et al. study had noticeably higher SHM levels (mean 5.5%). These data suggest that a majority of neutralizing antibodies against SARS-CoV-2 do not diverge greatly from germline and therefore would be more easily and broadly elicited among patients.

Next we used AIRRscape to visualize convergent clonotypes among anti-SARS-CoV-2 antibodies and COVID-19 patient bulk BCR repertoires. Visualizations were created based on their *gf_jgene* + *cdr3length_imgt* bin assignments, where a bin *x_y_z* represents IGHV*x* germline assignment + IGHJ*y* germline assignment + CDR3 length of *z* aa. As use cases, we focused on three recently reported convergences, visualized as four bins: both *3_4_11* and *3_6_11* for an IGHV3-53-based cluster as reported by Yuan et al. [16] and Galson et al. [14]; *3_6_14* for a large cluster found by Galson et al. [14]; and *1_3_16* for a cluster reported by Robbiani et al. [15]. Within each bin, we selected one published monoclonal antibody and examined the topology of similar CDRH3 motifs among all the COVID-19 datasets, using the

80% aa sequence identity threshold selected by Soto et al. [6]. As expected, convergence
across all four bins was observed (Fig 5; S1-3 Figs), with each containing 12–30 CDRH3 motifs
from the CoV-AbDab dataset; these motifs were found across seven or more unique studies.
Three of the bins show convergent motifs among multiple patient repertoires (Fig 5; S1 and S3
Fig), with two also showing convergence among three of the four patient repertoires.
Furthermore, two of the bins show convergence to the healthy control repertoire (Fig 5; S1 Fig).
The three convergent motifs seen in multiple COVID-19 patient repertoires were also found in
the dengue patient repertoires (see 3.3), although convergence across both CDRH3 and exact
V-gene usage was only observed for one motif. While SHM is not included in the CDRH3
topologies, examination of the convergent sequences indicated that they all show low SHM (0-
4%).
244
245   **Fig 5. SARS-CoV-2 convergent clonotypes to mAb DH1149 in the 3_6_14 bin.** An 80%
246   identity threshold is used to calculate convergence. Tips are colored by dataset source. Purple
247   tips are published anti-COVID-19 antibodies from 7 different studies, dark gray tips are antibody
248   sequences from a healthy donor BCR repertoire, and orange through brown shaded tips are
249   antibody sequences from COVID-19 patient BCR repertoires.
250

251 3.2 anti-HIV-1 antibody datasets display idiosyncrasies

We collated anti-HIV-1 monoclonal antibodies from two databases and one study [31–
33], and compared this set to published bulk BCR repertoires of eight HIV-1 patients. From the
databases we visualized 358 sequences. For the HIV-1 patient bulk BCR repertoires, 33,855
antibody motifs from patient MT1214 [27], 14,644 from patient NIH45 [29], and 184,294 from six
CAPRISA patients [7] were visualized after removing duplicate sequences (see 2.2; S4 Fig).
Although patient NIH45 was only sequenced for IGHV1 genes, this partial 'repertoire' was
included because it is the original source of the broadly neutralizing antibody VRC01 [29].
259
The heatmap visualizations in AIRRscape were used to compare published anti-HIV-1
antibodies to anti-SARS-CoV-2 antibodies and to two HIV-1 patient repertoires. While the
number of anti-HIV-1 antibodies was sparse relative to that of anti-SARS-CoV-2 antibodies, they
appeared to have similar heavy chain V-gene + J-gene usage (Fig 2A). There were noticeable
differences in both SHM and CDRH3 length, consistent with previous anti-HIV-1 antibody
repertoire characterizations [39,40]. The anti-HIV-1 antibody dataset showed higher SHM (mean
12.6% vs. 2.3%, Fig 2A) and longer CDRH3 lengths (20.4 vs. 15.8 aa) than the CoV-AbDab
dataset. Comparing published anti-HIV-1 antibodies with the HIV-1 patient repertoires also
revealed higher SHM (mean 12.6% vs. 5.0%) and longer CDRH3 lengths (mean 20.4 vs. 16.0
aa), which contrasts with the COVID-19 results in 3.1 (S4 Fig) and indicates strong diversifying
selection away from unmutated, naive antibodies.
271
We used AIRRscape to visualize convergent clonotypes among anti-HIV-1 antibodies
and HIV-1 patient bulk BCR repertoires, focusing on ten recently reported convergences from
Setliff [7], visualized as eight bins, as well as the inferred VRC01 germline CDR3 motif [29]. As
per 3.1, we selected one published monoclonal antibody within each bin and examined the
topology of similar CDRH3 motifs among all the HIV-1 datasets, this time using a lower 70% aa

sequence identity threshold and requiring identical V-gene assignment, following Setliff et al. [7].
Four of the bins showed limited convergence among HIV-1 datasets (Fig 6; S5 Fig), with motifs
shared among two, three, or four patient repertoires. Despite including two antibody datasets
from studies on the VRC01 antibody lineage, we notably could not find any convergence to the
VRC01 germline CDR3 motif among the HIV-1 datasets. The complex evolution from germline
and mutational requirements of neutralizing HIV-1 antibodies are consistent with the rarity of
success in naturally achieving humoral neutralization in infected individuals and with challenges
encountered in vaccine development.
285
Fig 6. HIV-1 convergent clonotypes to antibodies from Setliff (2018; Fig 4). (A) Convergent
clonotypes to mAb 02-o in the 1_4_13 bin. (B) Convergent clonotypes to mAb 02-s in the
1_4_14 bin. (C) Convergent clonotypes to mAb HK20 in the 1_3_15 bin. A 70% identity
threshold is used to calculate convergence. Tips are colored by dataset source. Purple tips are
published anti-COVID-19 antibodies, and green shaded tips are antibody sequences from HIV-1
patient BCR repertoires.
292

3.3 Dengue antibody datasets share convergent motifs

AIRRscape was used to visualize both reported and potentially undiscovered
convergence among the collated dengue datasets. We searched for convergence between 38
unique antibody sequences from plasmablasts isolated from two Colombian dengue patients
and bulk BCR repertoires of dengue patients from Colombian and Nicaraguan cohorts. Patient
bulk BCR repertoires consist of one Colombian patient [d13; 17] and a collection of 45
Nicaraguan patient repertoires [18]. After removing duplicate sequences we compared 32,495
antibody motifs from Patient d13 and 198,119 from the Nicaraguan cohort (S6 Fig).
301
302   Evidence of convergent antibody motifs was previously found in independent studies of
303 the Colombian (n = 2) and Nicaraguan (n = 45) patients. Plasmablast sequences in the
304 Colombian patients were reported to cluster into 15 clonal families, with one clonal family (CF1)
305 found in both patients [19]. Similarly, analysis of the Nicaraguan cohort found six CDRH3 motifs
306 common to multiple patients [18].
307
In our analysis, we began with each of the 15 plasmablast clonal families, and searched
for similar CDRH3 motifs among the full dengue dataset, using the 80% aa sequence identity
threshold as per Soto et al. [6]. Five of the 15 clonal families showed convergence across both
Colombian and Nicaraguan cohorts (Table 2; Fig 7; S7-9 Figs). Of these five, we identified CF1
from the Colombian cohort as the most prevalent clonal family in the Nicaraguan dataset,
occurring in 16 donors (Table 2; Fig 7). We also found a previously unreported instance of
convergence in the Colombian dataset. CDRH3 motifs from the CF6 clonal family identified in
patient d20 were also found in the patient d13 bulk BCR repertoire, as well as in two patient
repertoires from the Nicaraguan bulk dataset (Table 2; S7 Fig).
317
318

Table 2. Dengue convergence to plasmablast clonal families.

Clonal family	V_J_CDR3 length	Plasmablast donor	Colombian p13 Bulk matches?	Nicaraguan cohort matches?	Nicaraguan sequence matches	Nicaraguan donors with match
CF1	4_5_10	p13, p20	yes	yes	41	**16**
CF2	1_4_15	p13	yes	no		
CF3	1_5_16	p13	yes	no		
CF4	1_4_16	p20	no	no		
CF5	1_3_17	p13	yes	no		
CF6	1_4_13	p20	**yes**	yes	2	**2**
CF7	1_5_16	p13	yes	yes	24	**5**
CF8	1_5_17	p13	yes	yes	1	**1**
CF9	1_5_20	p13	yes	yes	7	**3**
CF10	3_5_14	p13	yes	no		
CF11	3_6_23	p13	yes	no		
CF12	3_4_17	p20	no	no		
CF13	4_5_18	p13	yes	no		
CF14	4_4_15	p20	no	no		
CF15	4_5_23	p13	yes	no		

Fig 7. Dengue convergent clonotypes to CF1 (Zanini 2018). An 80% identity threshold is used to calculate convergence. Tips are colored by dataset source. Purple tips are plasmablast sequences reported by Zanini (2018) isolated from two Colombian patients (d13 and d20), blue tips are antibody sequences from the BCR repertoire of patient d13, and gold tips are antibody sequences from a cohort of Nicaraguan patient BCR repertoires.

The six common CDRH3 motifs reported in the Nicaraguan dengue patients were also
explored using AIRRscape. These six motifs group into two clusters by amino acid similarity.
We found that the first cluster is common among the Nicaraguan dengue cohort, occurring in 17
patients, but not seen in the Colombian dataset. Notably, we found that the second cluster was
convergent with the CF1 clonal family [19; S9 Fig], demonstrating its frequent occurrence.
These data demonstrate how repertoire convergence in populations can occur at different
geographic levels, some more restricted than others. This could be due to regional differences
or similarities in factors such as infection or vaccine history, genetics, and environment.
335

4. Discussion

337
The importance of understanding BCR repertoires has gained increasing appreciation,
especially as a result of the current COVID-19 pandemic. Along with rapidly advancing
sequencing capabilities, this has led to the study and publication of dozens of individual BCR
repertoires, particularly from patients infected by well-studied infectious pathogens as well as
from healthy controls [e.g. 1,6,11,14,15,25,29]. As with other examples of 'big data', there are
many challenges in managing these datasets. In response, the AIRR community has made
significant efforts to standardize and curate BCR repertoires [20–22]. However, visualization
and comparative analysis of these repertoires remains a challenge. To begin to address this
gap we developed AIRRscape, a tool that leverages AIRR community standards to visualize
multiple BCR repertoires quickly and simultaneously. AIRRscape provides a high-level view of
large datasets that allows researchers to straightforwardly investigate differences in commonly
used repertoire characteristics, such as V-gene usage, J-gene usage, CDR3 length, and
somatic hypermutation.
351
Recent studies have found measurable convergence between individual BCR
repertoires, particularly among individuals infected with a common antigen [2]. Such
convergence has great implications for understanding immune responses to antigens and
informing vaccine design. Therefore, a major aim of AIRRscape is to visualize related antibody
sequences, particularly from different repertoires, using the commonly accepted characteristics
of convergence, V-gene assignment, J-gene assignment, and CDR3 motif. We use phylogenetic
methods to more easily visualize and understand differences among the motifs, keeping in mind
that the visualizations are topologies of CDR3 motifs and not necessarily phylogenetic trees
indicating common ancestry, e.g. when multiple individual repertoires are compared. The
characteristics used to find convergence are the same as those used to define clonotypes, or
clonal clusters of antibodies within individuals. Given that no consensus on clonotype definitions
has been reached, with debate largely centered around thresholds of sequence identity in the
CDR3 motif, AIRRscape creates topologies based on CDR3 amino acid sequences while being
agnostic with respect to thresholds. Users may currently select one of four amino acid identity
thresholds, three of which are used in recent large-scale studies of BCR repertoires [1,6,7].
AIRRscape also does not require *a priori* clustering of clonotypes in the input datasets. Users
with pre-defined clonal families can employ another tool (Olmsted: https://olmstedviz.org) to
generate such visualizations.
370

We validated the utility of AIRRscape by exploring datasets of both antibodies and
patient bulk BCR repertoires for three viral pathogens: SARS-CoV-2, HIV-1, and DENV. Among
the COVID-19 datasets, we first visually confirmed that the set of known anti-SARS-CoV-2
antibodies is broadly similar both to a healthy BCR repertoire and to a collection of COVID-19
patient repertoires, as measured by heavy chain V-gene + J-gene usage, CDRH3 length
distribution, and relatively low levels of SHM from germline. This is consistent with studies made
in the first months of the COVID-19 pandemic, which concluded that anti-SARS-CoV-2
antibodies could likely be induced by vaccines [41]. We then used AIRRscape to examine
convergence among anti-SARS-CoV-2 antibodies and COVID-19 patient BCR repertoires as
reported by multiple studies [14–16]. With an amino acid sequence identity threshold of 80%,
we find that the COVID-19 convergent motifs are indeed present in currently known anti-SARS-
CoV-2 antibodies as well as in four COVID-19 patient bulk BCR repertoires. COVID-19
convergent motifs were also identified among repertoires of healthy controls and dengue
patients, which would not be expected to contain antibodies against SARS-CoV-2, but could be
explained by the relative proximity of the motifs to germline sequences and/or to infection with
other coronaviruses. Convergence of neutralizing antibody sequences among multiple COVID-
19 repertoires is a strong indicator of similarity in SARS-CoV-2 immune responses and
suggests that vaccines eliciting these antibodies will be broadly effective [15,42]. The discovery
that these antibody sequences are public (i.e. also identified in our dengue and healthy control
samples) suggests that there is a general pre-existing foundation in populations towards
COVID-19 protection. Such a primed immune repertoire bodes well for robust vaccine
responses. Repertoires of patients infected by different SARS-CoV-2 variants could be explored
using AIRRscape to find potential convergence among these datasets. Such convergence
would indicate antibody motifs with potential to neutralize the range of known SARS-CoV-2
variants, which could be prioritized for reverse vaccinology research or development.
396
In contrast to the COVID-19 datasets, the HIV-1 datasets are mostly idiosyncratic but do
show limited convergence. Using AIRRscape, we first visualized characteristics of anti-HIV-1
antibodies and eight HIV-1 patient bulk BCR repertoires. The heatmaps show high SHM, a
common feature of neutralizing antibodies against HIV-1. Notably, this collection of antibodies
displays much higher SHM levels than anti-SARS-CoV-2 antibodies. We then searched for
convergence in CDRH3 motifs between anti-HIV-1 antibodies and eight HIV-1 patient bulk BCR
repertoires, using a more permissive threshold of 70% CDR3 sequence identity. Still, we found
limited convergence among the HIV-1 datasets and no convergence to the VRC01 germline
CDR3 motif [29]. While the limited convergence appears at odds with the reporting of VRC01-
like antibodies in multiple HIV-1 patients [7,43], the VRC01 class varies in CDRH3 similarity and
is instead defined by 20-35% SHM in the germline VH1-2 gene and a 5 aa CDRL3 length
[44,45]. These idiosyncratic characteristics underscore the difficulty in vaccine development for
HIV-1.
410
Examination of dengue datasets revealed evidence of convergent antibody motifs
among two patient cohorts from Colombia and Nicaragua. Visualizing 15 focal plasmablast
clonal families in AIRRscape, we found five were common to both patient cohorts, often in
multiple patients. The most common convergent lineage CF1, seen in both Parameswaran [18]

and Zanini [19], was found not to be broadly neutralizing against all DENV serotypes [17].
However, the second most commonly found lineage, CF7, includes the mAb J9 that Durham et
al. [17] found to be broadly neutralizing. That one of two tested convergent antibody lineages
shows broad neutralization suggests further investigations of convergence may be beneficial for
focusing antibody discovery and vaccine design. Broad neutralization could be particularly
important for treating dengue, where antibody-enhanced disease is a problem.
421
As AIRRscape is in active development, we note some limitations and also envision
future enhancements. AIRRscape is primarily an exploratory tool focused on visualization but
various metrics could be used to formally measure overlap between repertoires [RDI;
46,sumrep; 47]. AIRRscape does not visualize all of the sequences in the bulk BCR repertoire
datasets; due to size and computing limitations in the Shiny application, large datasets are
collapsed when V-gene + J-gene assignments as well as CDR3 amino acid motifs are identical.
Similarly, to facilitate construction of topologies of CDR3 amino acid motifs we focus on those
with exact same lengths, although it has been shown that functionally similar antibodies may
have different CDR3 lengths [48,49]. While the variability of CDR3 is typically crucial for defining
antigen specificity [37,50], other CDRs can also be important in antigen recognition; in those
cases, AIRRscape could be modified to visualize changes outside of CDR3. With respect to
identifying convergence, AIRRscape creates bins based on assigned germline V-gene families;
thus, CDR3 topologies can indicate convergence even if antibodies have different germline V-
genes within a family. While this definition of convergence is intended to cluster closely related
germline genes such as IGHV3-53 & IGHV3-66, it may be too broad in some cases. As an aid,
we include the full V-gene assignments in the topology tip names, and we note that restricting
the antibody list to one gene will limit searches to only convergences with matching V-genes.
Lastly, although AIRRscape can quickly and easily search for known antibody sequences,
examine overall repertoire patterns, and find convergence, users currently cannot initiate
searches for identical motifs across datasets.
442
Despite these current limitations, AIRRscape is a useful tool for quick and thorough
exploration of large BCR repertoire datasets. We have released the source code on GitHub so
that interested research groups may use other datasets or incorporate more features. While we
have loaded datasets from one healthy control and three diseases, we have designed the pre-
processing R script so that any AIRR-compliant datasets may be visualized. Similarly, the code
could be further modified to meet the desires of immuno-informaticians, virologists, and
immunologists, for instance with respect to the CDR3 sequence identity thresholds,
phylogenetic tree options, or color and visualization schemes. While our focus is on infectious
disease, AIRRscape can be similarly used for autoimmunity and cancer biology, for example to
compare healthy vs. autoimmune or cancer patient repertoires. We hope that AIRRscape will be
useful for the research community and that interested parties will take advantage of its open
source nature to contribute improvements.
455

Acknowledgments

457 We would like to acknowledge members of the CZ Biohub Data Science platform for
458 thoughtful discussion, and Sandra L. Schmid for comments on the manuscript.

Author Contributions

E.W. and J.E.P. conceived of the project. E.W. designed and wrote software. E.W. performed bioinformatic analysis. E.W. and S.N. documented and implemented code repository. E.W. wrote the first draft of the manuscript. E.W., S.N., J.W., K.M.M., and J.E.P revised the draft and approved the final manuscript.

Data availability statement

All AIRRscape code and data loaded for visualization, as well as code for processing similar datasets are available on a GitHub repository at https://github.com/czbiohub/AIRRscape.

References

1. Briney B, Inderbitzin A, Joyce C, Burton DR. Commonality despite exceptional diversity in the baseline human antibody repertoire. Nature. 2019;566: 393–397. doi:10.1038/s41586-019-0879-y

2. Raybould MIJ, Rees AR, Deane CM. Current strategies for detecting functional convergence across B-cell receptor repertoires. mAbs. 2021;13: 1996732. doi:10.1080/19420862.2021.1996732

3. Chaudhary N, Wesemann DR. Analyzing Immunoglobulin Repertoires. Frontiers in Immunology. 2018;9: 462. doi:10.3389/fimmu.2018.00462

4. Dunn-Walters D, Townsend C, Sinclair E, Stewart A. Immunoglobulin gene analysis as a tool for investigating human immune responses. Immunological Reviews. 2018;284: 132–147. doi:10.1111/imr.12659

5. Wardemann H, Busse CE. Novel Approaches to Analyze Immunoglobulin Repertoires. Trends in Immunology. 2017;38: 471–482. doi:10.1016/j.it.2017.05.003

6. Soto C, Bombardi RG, Branchizio A, Kose N, Matta P, Sevy AM, et al. High frequency of shared clonotypes in human B cell receptor repertoires. Nature. 2019;566: 398–402. doi:10.1038/s41586-019-0934-8

7. Setliff I, McDonnell WJ, Raju N, Bombardi RG, Murji AA, Scheepers C, et al. Multi-Donor Longitudinal Antibody Repertoire Sequencing Reveals the Existence of Public Antibody Clonotypes in HIV-1 Infection. Cell Host & Microbe. 2018;23: 845-854.e6. doi:10.1016/j.chom.2018.05.001

8. Miho E, Yermanos A, Weber CR, Berger CT, Reddy ST, Greiff V. Computational Strategies for Dissecting the High-Dimensional Complexity of Adaptive Immune Repertoires. Front Immunol. 2018;9. doi:10.3389/fimmu.2018.00224

9. Rubelt F, Bolen CR, McGuire HM, Heiden JAV, Gadala-Maria D, Levin M, et al. Individual heritable differences result in unique cell lymphocyte receptor repertoires of naïve and antigen-experienced cells. Nature Communications. 2016;7: 11112. doi:10.1038/ncomms11112

10. Muggen AF, de Jong M, Wolvers-Tettero ILM, Kallemeijn MJ, Teodósio C, Darzentas N, et al. The presence of CLL-associated stereotypic B cell receptors in the normal BCR repertoire from healthy individuals increases with age. Immun Ageing. 2019;16: 22. doi:10.1186/s12979-019-0163-x

11. Schultheiß C, Paschold L, Simnica D, Mohme M, Willscher E, Wenserski L von, et al. Next-Generation Sequencing of T and B Cell Receptor Repertoires from COVID-19 Patients Showed Signatures Associated with Severity of Disease. Immunity. 2020;53: 442-455.e4. doi:10.1016/j.immuni.2020.06.024

506   12.   Horns F, Vollmers C, Croote D, Mackey SF, Swan GE, Dekker CL, et al. Lineage tracing of
507   human B cells reveals the in vivo landscape of human antibody class switching. Neher RA,
508   editor. eLife. 2016;5: e16578. doi:10.7554/eLife.16578

509   13.   Chang W, Cheng J, Allaire JJ, Xie Y, McPherson J. shiny: Web Application Framework for
510   R. 2020. Available: https://CRAN.R-project.org/package=shiny

511   14.   Galson JD, Schaetzle S, Bashford-Rogers RJM, Raybould MIJ, Kovaltsuk A, Kilpatrick GJ,
512   et al. Deep sequencing of B cell receptor repertoires from COVID-19 patients reveals
513   strong convergent immune signatures. bioRxiv. 2020; 2020.05.20.106294.
514   doi:10.1101/2020.05.20.106294

515   15.   Robbiani DF, Gaebler C, Muecksch F, Lorenzi JCC, Wang Z, Cho A, et al. Convergent
516   antibody responses to SARS-CoV-2 in convalescent individuals. Nature. 2020;584: 437–
517   442. doi:10.1038/s41586-020-2456-9

518   16.   Yuan M, Liu H, Wu NC, Lee C-CD, Zhu X, Zhao F, et al. Structural basis of a shared
519   antibody response to SARS-CoV-2. Science. 2020;369: 1119–1123.
520   doi:10.1126/science.abd2321

521   17.   Durham ND, Agrawal A, Waltari E, Croote D, Zanini F, Fouch M, et al. Broadly neutralizing
522   human antibodies against dengue virus identified by single B cell transcriptomics. eLife.
523   2019;8: e52384. doi:10.7554/eLife.52384

524   18.   Parameswaran P, Liu Y, Roskin KM, Jackson KKL, Dixit VP, Lee J-Y, et al. Convergent
525   Antibody Signatures in Human Dengue. Cell Host & Microbe. 2013;13: 691–700.
526   doi:10.1016/j.chom.2013.05.008

527   19.   Zanini F, Robinson ML, Croote D, Sahoo MK, Sanz AM, Ortiz-Lasso E, et al. Virus-
528   inclusive single-cell RNA sequencing reveals the molecular signature of progression to
529   severe dengue. PNAS. 2018;115: E12363–E12369. doi:10.1073/pnas.1813819115

530   20.   Breden F, Luning Prak ET, Peters B, Rubelt F, Schramm CA, Busse CE, et al.
531   Reproducibility and Reuse of Adaptive Immune Receptor Repertoire Data. Frontiers in
532   Immunology. 2017;8: 1418. doi:10.3389/fimmu.2017.01418

533   21.   Rubelt F, Busse CE, Bukhari SAC, Bürckert J-P, Mariotti-Ferrandiz E, Cowell LG, et al.
534   Adaptive Immune Receptor Repertoire Community recommendations for sharing immune-
535   repertoire sequencing data. Nat Immunol. 2017;18: 1274–1278. doi:10.1038/ni.3873

536   22.   Corrie BD, Marthandan N, Zimonja B, Jaglale J, Zhou Y, Barr E, et al. iReceptor: A
537   platform for querying and analyzing antibody/B-cell and T-cell receptor repertoire data
538   across federated repositories. Immunological Reviews. 2018;284: 24–41.
539   doi:10.1111/imr.12666

540   23.   Kovaltsuk A, Leem J, Kelm S, Snowden J, Deane CM, Krawczyk K. Observed Antibody
541   Space: A Resource for Data Mining Next-Generation Sequencing of Antibody Repertoires.
542   The Journal of Immunology. 2018;201: 2502–2509. doi:10.4049/jimmunol.1800708

543   24.   Olsen TH, Boyles F, Deane CM. Observed Antibody Space: A diverse database of
544   cleaned, annotated, and translated unpaired and paired antibody sequences. Protein
545   Science. 2021;2021: 1–6. doi:10.1002/pro.4205

546   25.   Kuri-Cervantes L, Pampena MB, Meng W, Rosenfeld AM, Ittner CAG, Weisman AR, et al.
547   Comprehensive mapping of immune perturbations associated with severe COVID-19.
548   Science Immunology. 2020;5: eabd7114. doi:10.1126/sciimmunol.abd7114

549   26.   Nielsen SCA, Yang F, Jackson KJL, Hoh RA, Röltgen K, Jean GH, et al. Human B Cell
550   Clonal Expansion and Convergent Antibody Responses to SARS-CoV-2. Cell Host &
551   Microbe. 2020;28: 516-525.e5. doi:10.1016/j.chom.2020.09.002

552   27.   Waltari E, Jia M, Jiang CS, Lu H, Huang J, Fernandez C, et al. 5′ Rapid Amplification of
553   cDNA Ends and Illumina MiSeq Reveals B Cell Receptor Features in Healthy Adults,
554   Adults With Chronic HIV-1 Infection, Cord Blood, and Humanized Mice. Frontiers in
555   Immunology. 2018;9: 628. doi:10.3389/fimmu.2018.00628

28.   Waltari E, McGeever, Aaron, Friedland, Natalia, Kim PS, McCutcheon KM. Functional

enrichment and analysis of Antigen-Specific memory B cell antibody repertoires in PBMCs.
Frontiers in immunology. 2019;10: 1452. doi:10.3389/fimmu.2019.01452

29. Wu X, Zhang Z, Schramm CA, Joyce MG, Do Kwon Y, Zhou T, et al. Maturation and
Diversity of the VRC01-Antibody Lineage over 15 Years of Chronic HIV-1 Infection. Cell.
2015;161: 470–485. doi:10.1016/j.cell.2015.03.004

30. Raybould MIJ, Kovaltsuk A, Marks C, Deane CM. CoV-AbDab: the coronavirus antibody
database. Bioinformatics. 2020;37: 734–735. doi:10.1093/bioinformatics/btaa739

31. Mahajan S, Vita R, Shackelford D, Lane J, Schulten V, Zarebski L, et al. Epitope Specific
Antibodies and T Cell Receptors in the Immune Epitope Database. Front Immunol. 2018;9.
doi:10.3389/fimmu.2018.02688

32. Yoon H, Macke J, West AP, Foley B, Bjorkman PJ, Korber B, et al. CATNAP: a tool to
compile, analyze and tally neutralizing antibody panels. Nucleic Acids Res. 2015;43:
W213–W219. doi:10.1093/nar/gkv404

33. Yacoob C, Pancera M, Vigdorovich V, Oliver BG, Glenn JA, Feng J, et al. Differences in
Allelic Frequency and CDRH3 Region Limit the Engagement of HIV Env Immunogens by
Putative VRC01 Neutralizing Antibody Precursors. Cell Reports. 2016;17: 1560–1570.
doi:10.1016/j.celrep.2016.10.017

34. Vander Heiden JA, Yaari G, Uduman M, Stern JN, O'Connor KC, Hafler DA, et al.
pRESTO: a toolkit for processing high-throughput sequencing raw reads of lymphocyte
receptor repertoires. Bioinformatics. 2014;30: 1930–1932.
doi:10.1093/bioinformatics/btu138

35. Gupta NT, Vander Heiden JA, Uduman M, Gadala-Maria D, Yaari G, Kleinstein SH.
Change-O: a toolkit for analyzing large-scale B cell immunoglobulin repertoire sequencing
data. Bioinformatics. 2015;31: 3356–3358. doi:10.1093/bioinformatics/btv359

36. Zhou JQ, Kleinstein SH. Cutting Edge: Ig H Chains Are Sufficient to Determine Most B Cell
Clonal Relationships. The Journal of Immunology. 2019;203: 1687–1692.
doi:10.4049/jimmunol.1900666

37. Xu JL, Davis MM. Diversity in the CDR3 Region of VH Is Sufficient for Most Antibody
Specificities. Immunity. 2000;13: 37–45. doi:10.1016/S1074-7613(00)00006-6

38. Holder M, Lewis PO. Phylogeny estimation: traditional and Bayesian approaches. Nat Rev
Genet. 2003;4: 275–284. doi:10.1038/nrg1044

39. Scheid JF, Mouquet H, Feldhahn N, Seaman MS, Velinzon K, Pietzsch J, et al. Broad
diversity of neutralizing antibodies isolated from memory B cells in HIV-infected individuals.
Nature. 2009;458: 636–640. doi:10.1038/nature07930

40. Sok D, Burton DR. Recent progress in broadly neutralizing antibodies to HIV. Nat Immunol.
2018;19: 1179–1188. doi:10.1038/s41590-018-0235-7

41. Kreer C, Zehner M, Weber T, Ercanoglu MS, Gieselmann L, Rohde C, et al. Longitudinal
Isolation of Potent Near-Germline SARS-CoV-2-Neutralizing Antibodies from COVID-19
Patients. Cell. 2020;182: 843-854.e12. doi:10.1016/j.cell.2020.06.044

42. Kreer C, Gruell H, Mora T, Walczak AM, Klein F. Exploiting B Cell Receptor Analyses to
Inform on HIV-1 Vaccination Strategies. Vaccines. 2020;8: 13.
doi:10.3390/vaccines8010013

43. Zhou T, Zhu J, Wu X, Moquin S, Zhang B, Acharya P, et al. Multidonor Analysis Reveals
Structural Elements, Genetic Determinants, and Maturation Pathway for HIV-1
Neutralization by VRC01-Class Antibodies. Immunity. 2013;39: 245–258.
doi:10.1016/j.immuni.2013.04.012

44. West AP, Diskin R, Nussenzweig MC, Bjorkman PJ. Structural basis for germ-line gene
usage of a potent class of antibodies targeting the CD4-binding site of HIV-1 gp120.
PNAS. 2012;109: E2083–E2090. doi:10.1073/pnas.1208984109

45. Wu X, Kong X-P. Antigenic landscape of the HIV-1 envelope and new immunological
concepts defined by HIV-1 broadly neutralizing antibodies. Current Opinion in Immunology.

2016;42: 56–64. doi:10.1016/j.coi.2016.05.013

46. Bolen CR, Rubelt F, Vander Heiden JA, Davis MM. The Repertoire Dissimilarity Index as a
method to compare lymphocyte receptor repertoires. BMC Bioinformatics. 2017;18: 155.
doi:10.1186/s12859-017-1556-5

47. Olson BJ, Moghimi P, Schramm CA, Obraztsova A, Ralph D, Vander Heiden JA, et al.
sumrep: A Summary Statistic Framework for Immune Receptor Repertoire Comparison
and Model Validation. Front Immunol. 2019;10. doi:10.3389/fimmu.2019.02533

48. Barnes CO, Jette CA, Abernathy ME, Dam K-MA, Esswein SR, Gristick HB, et al. SARS-
CoV-2 neutralizing antibody structures inform therapeutic strategies. Nature. 2020; 1–6.
doi:10.1038/s41586-020-2852-1

49. Barnes CO, West AP, Huey-Tubman KE, Hoffmann MAG, Sharaf NG, Hoffman PR, et al.
Structures of Human Antibodies Bound to SARS-CoV-2 Spike Reveal Common Epitopes
and Recurrent Features of Antibodies. Cell. 2020;182: 828-842.e16.
doi:10.1016/j.cell.2020.06.025

50. Greiff V, Bhat P, Cook SC, Menzel U, Kang W, Reddy ST. A bioinformatic framework for
immune repertoire diversity profiling enables detection of immunological status. Genome
Medicine. 2015;7: 49. doi:10.1186/s13073-015-0169-8

625
626

Figures

Fig 1. Workflow of repertoire data retrieval and processing.

Fig 2. AIRRscape visualization of immune repertoires. Heatmaps comparing characteristics of (A) separate and (B) combined datasets for anti-SARS-CoV-2 and anti-HIV-1 antibodies.

Fig 3. AIRRscape interface showing antibodies and CDR3 amino acid topology of selected antibody bin. Selected bin is highlighted in the red box of Fig 2B.

Fig 4. AIRRscape heatmaps comparing anti-SARS-CoV-2 antibodies, bulk BCR repertoires of four COVID-19 patients, and a healthy control bulk BCR repertoire.

Fig 5. SARS-CoV-2 convergent clonotypes to mAb DH1149 in the 3_6_14 bin. An 80% identity threshold is used to calculate convergence. Tips are colored by dataset source. Purple tips are published anti-COVID-19 antibodies from 7 different studies, dark gray tips are antibody sequences from a healthy donor BCR repertoire, and orange through brown shaded tips are antibody sequences from COVID-19 patient BCR repertoires.

Fig 6. HIV-1 convergent clonotypes to antibodies from Setliff (2018; Fig 4). (A) Convergent clonotypes to mAb 02-o in the 1_4_13 bin. (B) Convergent clonotypes to mAb 02-s in the 1_4_14 bin. (C) Convergent clonotypes to mAb HK20 in the 1_3_15 bin. A 70% identity threshold is used to calculate convergence. Tips are colored by dataset source. Purple tips are published anti-HIV-1 antibodies, while green shaded tips are antibody sequences from HIV-1 patient BCR repertoires.

Fig 7. Dengue convergent clonotypes to CF1 (Zanini 2018). An 80% identity threshold is used to calculate convergence. Tips are colored by dataset source. Purple tips are plasmablast sequences reported by Zanini (2018) isolated from two Colombian patients (d13 and d20), blue tips are antibody sequences from the BCR repertoire of patient d13, and gold tips are antibody sequences from a cohort of Nicaraguan patient BCR repertoires.

Supporting Information

S1 Fig. SARS-CoV-2 convergent clonotypes to mAb C102 in the 3_4_11 bin. An 80% identity threshold is used to calculate convergence. Tips are colored by dataset source. Purple tips are published anti-COVID-19 antibodies from 12 different studies, dark gray tips are antibody sequences from a healthy donor BCR repertoire, and orange through brown shaded tips are antibody sequences from COVID-19 patient BCR repertoires.

S2 Fig. SARS-CoV-2 convergent clonotypes to mAb C125 in the 1_3_16 bin. An 80% identity threshold is used to calculate convergence. Tips are colored by dataset source. Purple tips are published anti-COVID-19 antibodies from 7 different studies, dark gray tips are antibody sequences from a healthy donor BCR repertoire, and orange through brown shaded tips are antibody sequences from COVID-19 patient BCR repertoires.

S3 Fig. SARS-CoV-2 convergent clonotypes to mAb BD-498 in the 3_6_11 bin. An 80% identity threshold is used to calculate convergence. Tips are colored by dataset source. Purple tips are published anti-COVID-19 antibodies from 15 different studies, dark gray tips are antibody sequences from a healthy donor BCR repertoire, and orange through brown shaded tips are antibody sequences from COVID-19 patient BCR repertoires.

S4 Fig. AIRRscape heatmaps comparing anti-HIV-1 antibodies and bulk BCR repertoires of eight HIV-1 patients.

S5 Fig. HIV-1 convergent clonotypes to mAb CAP351_6m_6041 (Setliff 2018; Fig 3) in the 1_6_14 bin. A 70% identity threshold is used to calculate convergence. Tips are colored by dataset source. Purple tips are published anti-COVID-19 antibodies, and green shaded tips are antibody sequences from HIV-1 patient BCR repertoires.

S6 Fig. AIRRscape heatmaps comparing isolated dengue plasmablasts and bulk BCR repertoires of dengue patients from Colombian and Nicaraguan cohorts.

S7 Fig. Dengue convergent clonotypes to CF6 (Zanini 2018). An 80% identity threshold is used to calculate convergence. Tips are colored by dataset source. Purple tips are plasmablast sequences reported by Zanini (2018) isolated from two Colombian patients (d13 and d20), blue tips are antibody sequences from the BCR repertoire of patient d13, and gold tips are antibody sequences from a cohort of Nicaraguan patient BCR repertoires.

S8 Fig. Dengue convergent clonotypes to CF7 (Zanini 2018). An 80% identity threshold is used to calculate convergence. Tips are colored by dataset source. Purple tips are plasmablast sequences reported by Zanini (2018) isolated from two Colombian patients (d13 and d20), blue tips are antibody sequences from the BCR repertoire of patient d13, and gold tips are antibody sequences from a cohort of Nicaraguan patient BCR repertoires.

S9 Fig. Dengue convergent clonotypes to Parameswaran (2018) motif ARQIGNWFDP
similar to CF1 (Zanini 2018). An 80% identity threshold is used to calculate convergence. Tips
are colored by dataset source. Purple tips are plasmablast sequences reported by Zanini (2018)
isolated from two Colombian patients (d13 and d20), blue tips are antibody sequences from the
BCR repertoire of patient d13, and gold tips are antibody sequences from a cohort of
Nicaraguan patient BCR repertoires.
674