Discordant genotype calls across technology platforms elucidate variants with systematic errors in

next-generation sequencing

Elizabeth G. Atkinson[1,2,3,*], Mykyta Artomov[1,2,*], Konrad J. Karczewski[1,2,4], Alexander A. Loboda[1,2,5,6], Heidi L.

Rehm[1,4,7], Daniel G. MacArthur[2,8], Benjamin M. Neale[1,2,4*], Mark J. Daly[1,2,9*]

[1]Analytic and Translational Genetics Unit, Department of Medicine, Massachusetts General Hospital, Boston,

MA, USA

[2]Stanley Center for Psychiatric Research, Broad Institute of MIT and Harvard, Cambridge, MA, USA

[3]Department of Molecular and Human Genetics, Baylor College of Medicine, Houston, TX, USA

[4]Program in Medical and Population Genetics, Broad Institute of MIT and Harvard, Cambridge, MA, USA

[5]ITMO University, Saint-Petersburg, Russia

[6]Almazov National Medical Research Center, St. Petersburg, Russia

[7]Center for Genomic Medicine, Massachusetts General Hospital, Boston, MA, USA

[8]Centre for Population Genomics, Garvan Institute of Medical Research and Murdoch Children's Research

Institute, Australia

[9]Institute for Molecular Medicine Finland, University of Helsinki, Helsinki, Finland

*These authors contributed equally to this work.

Corresponding author contact information:

elizabeth.atkinson@bcm.edu; artomov@broadinstitute.org

(202) 246-0666

Analytic and Translational Genetics Unit

Richard B. Simches Building, 6th Floor

185 Cambridge Street

Boston, MA 02114

Running Title: Discordant genotyping across sequencing technologies

Keywords: next-generation sequencing; whole exome sequencing; GWAS; variant calling; allele frequencies

Abstract

Large-scale next-generation sequencing (NGS) datasets have been transformative for informing clinical

variant interpretation and as reference panels for statistical and population genetic efforts. While such

resources are often treated as ground truth, we find that in widely used reference datasets such as the

Genome Aggregation Database (gnomAD), some variants pass gold standard filters yet are systematically

different in their genotype calls across sequencing technologies. The inclusion of such discordant sites in

study designs involving multiple sequencing platforms (e.g. whole genome and/or different whole-exome

captures) could bias results and lead to false-positive hits in association studies due to technological artifacts

rather than a true relationship to the phenotype. Here, we describe this phenomenon of discordant genotype

calls across sequencing technologies, characterize the error mode of wrong calls, provide a blacklist of

discordant sites identified in gnomAD that should be treated with caution in analyses, and present a metric

and machine learning classifier trained on gnomAD data to identify likely discordant variants in other

datasets. We find that different NGS technologies have different sets of variants at which this problem occurs

but that there are characteristic variant features that can be used to predict discordant behavior. Discordant

sites are largely shared across ancestry groups, though different populations are powered for discovery of

different variants. We find that the most common error mode is that of a variant being heterozygous for one

platform and homozygous for the other, with heterozygous in the genomes and homozygous reference in the

exomes making up the majority of miscalls.

Introduction

While next-generation sequencing (NGS) technologies have been transformative for genomics research, they have an appreciable error rate (Ma et al. 2019) as a cost of their high-throughput capacity. To account for this, sophisticated pipelines have been developed for the detection and removal of incorrect sequencing calls(Li et al. 2019; McKenna et al. 2010; Adelson et al. 2019; Highnam et al. 2015; Anderson et al. 2010; Lam et al. 2019). However, even with gold-standard filtering, spurious genotype calls can infiltrate datasets and potentially skew results. This is of particular importance with datasets that aggregate calls generated by multiple sequencing platforms, as different platforms have distinct error modes. Identifying variants that have technical artifacts affecting genotype calls is of major importance, as such loci give misleading information regarding population allele frequencies, and could be incorrectly identified as being phenotypically meaningful in gene discovery.

By leveraging the unprecedented size and depth of the gnomAD database(Karczewski et al. 2020; Lek et al. 2016), we comprehensively characterize trends in genotype calling depending on the sequencing technology. Specifically, we note that a subset of variants, despite passing standard quality filters(Karczewski 2017), produce discordant allele frequencies in data generated using different DNA sequencing technologies, stemming from unreliable variant calling. This can not be explained by population stratification, as this effect is observed even when looking at the same set of individuals. Such unreliably genotyped variants should therefore be screened out of analyses. Including these variants in gene discovery efforts, particularly in study designs where case and control data are represented by different combinations of sequencing platforms, could result in their appearance as false-positive associations.

In this article, we comprehensively characterize the observation of discordant genotyping depending on technology using a large set of diverse individuals from the gnomAD database, including a subset of participants who underwent both whole-exome and whole-genome sequencing (WES/WGS). Correcting for this technical error, whether by removing the gnomAD blacklist variants provided here or by identifying user-identified spurious calls with our freely distributed machine learning predictor, should be incorporated as a step in QC pipelines to avoid spurious associations, particularly in large-scale studies aggregating data from multiple sources.

Results

Discordance in genotype calls across NGS technologies replicates across ancestries

We sought to compare allele frequencies across variants found within exome and genome sequencing

datasets in gnomAD to test whether there are regions with significant bias associated with sequencing

technology. We first focused on the largest population represented in gnomAD 0.2 – the Non-Finnish

Europeans (NFE). Using the full release of gnomAD version 2.1.1, we filtered the data to include only sites

that were present and had a quality determination of PASS in both the genomes and exomes (Karczewski et

al. 2020). To ensure sufficient power, we filtered for sites with allele count (AC) >10 and ran a Fisher's Exact

Test (FET) on the difference in the number of alternate AC to total alleles (allele number, AN) between these

two datasets. A non-negligible fraction of sites were significantly discordant in their calls (**Figure** 1A). We

also tested other less stringent AC thresholds (AC>1 and AC>5) and observed that trends in discordance

between the platforms were consistent across AC cutoffs (**Figure** S1).

When comparing allele frequencies between sequencing platforms it is critical to control for ancestry, as

populations will have differing frequencies at many loci simply due to demography(Auton and Salcedo 2015;

Gravel et al. 2011; Bergström et al. 2020). To assess if ancestry affected discordance rates, we ran FET

concordance tests across all gnomAD continental groups (**Figure 1B**). Total discordant variant counts were

directly related to the sample size of the population in question and were not enriched for any given ancestry

(**Figure S2**). While novel discordant variants were discovered in each population, most variants observed in

other populations were shared with the NFE (86.9%, **Figure 1B, Table S1**). Replication of the same variants

across multiple ancestries strengthens the argument of a shared technical artifact and suggests ancestral

bias between exome and genome datasets is unlikely to be a confounding factor.

Error mode of discordant calls

Next, we aimed to classify the error mode resulting in discordant calls using the individuals with both

WES and WGS data. As 946 individuals underwent both whole exome and whole genome sequencing, we

were able to examine the rates and error modes of discordant genotype calls without concern over

population structure or differing sample composition; since these are the same individuals, any difference in

AF and/or genotype calls can be conclusively determined to be due to technical artifacts. We tallied the

number of sites in each pairwise exomes-genomes genotype category (6,333 sites; **Figure** S3) to classify

miscall error mode. Of the 6 possible error modes (homozygous reference/heterozygous, homozygous

reference/homozygous variant, or homozygous variant/heterozygous for both dataset directions), we find that

the majority of calls, 57.7%, are a heterozygous genotype call in the genomes but a homozygous reference

genotype call in the exomes (**Figure 1D, S4**). We also note that different sequencing platforms have different

rates of discordant calls, though due to sharing restrictions we can not identify platform names with certainty.

Overall, ~16% of the variants that were present and PASS in both exomes and genomes in the overlapping

individuals had at least one discordant call.

Next, we examined the discordance of allele frequencies, again with a FET. Usually in cohort-based

comparisons the expected distribution of FET *p value*s is represented by a uniform distribution. Since we are

looking at the same individuals, it is expected that allele frequencies should be identical (i.e. p=1). We

observe the presence of many variants substantially deviating from expectations, representing loci with

significantly different MAF in the exomes vs the genomes (**Figure 1C**).

Figure 1. Discordance in genotype calls across NGS technologies. **A**) FET concordance test *p* value for

shared, PASS sites in the gnomAD NFE exomes and genomes. Bars are colored by variant type: insertion

(ins), deletion (del), or single-nucleotide variant (snv). **B**) 'Bad' sites are replicated across ancestry groups in

gnomAD. Sites flagged as discordant in both the NFE and another ancestry group are plotted in gray, those

new sites not in the NFE are shown in black. **C**) QQ plot for the FET *p* value of shared variants in a set of

946 individuals for whom both WES and WGS data was available. **D**) Different exome captures' contribution

to discordant sites. Bars are colored by the error mode that was observed for the discordant genotype call:

heterozygous (het), homozygous reference (HomRef) or homozygous variant (HomVar) in either the exomes

(E) or genomes (G).

Identification of discordant sites

We next sought to identify problematic sites failing a FET test of concordant WEGS/WES frequency estimates in the largest subset of gnomAD, the NFE. Based on the distribution of p values from this test, we decided upon a threshold of $p<1\times10^{-5}$ to determine the classification of a variant as 'bad' or 'good' (**Figures 1, S5**). Distributions of metadata features for the good vs bad sites do show trends in several features, though no feature alone perfectly explains the phenomenon (**Figure** S6). They also highlight a difference in discordance patterns of indels vs SNVs. SNVs show a pattern of higher AF in genomes as compared to exomes, while indels do not have this trend. Indels are also generally less stable in allele frequency estimates than SNVs. It, therefore, appears that two distinct technical error modes might be affecting miscalls in indels vs SNVs, rather than one shared mechanism. As many of these indels fell in the low complexity regions of the genome, it is likely that a mapping issue is responsible for their miscalls. To correct this, we therefore recommend excluding the low complexity regions from stringent analyses. A comprehensive description of gnomAD structural variant calling and considerations is published and can be found in a gnomAD blog (Collins et al. 2020)https://gnomad.broadinstitute.org/news/2019-03-structural-variants-in-gnomad/(Collins et al. 2020). In general, when there was discordance, the genomes were found to have a higher MAF than the exomes (**Figure S1B**). The trend in MAF difference aligns with the most commonly observed error mode in genotyping.

Having confirmed that there was a systematic and significant AF discordance between sequencing platforms, we used our FET tests to generate a list of bad sites that may be excluded from analyses. Again, these blacklisted sites represent variants that were a PASS in gnomAD QC in both the exomes and genomes, but are unreliably genotyped depending on the sequencing technology used. Given a situation where, for example, a case cohort has been exome sequenced while the control cohort has been genome sequenced, such sites could give false-positive associations due to the resulting AF differences. We, therefore, recommend for them to be treated with caution or broadly excluded (in addition to standard cohort QC) unless thorough confirmation of their validity in a particular dataset has been done.

Recovering filtered concordant sites

In addition to generating this blacklist of bad sites that should be excluded despite being a PASS in gnomAD QC, we investigated whether additional trustworthy sites could be rescued from the 'Non-PASS' list based on our AF concordance criteria. Non-PASS variants are those that did not meet all required passing criteria in the gnomAD QC pipeline(Karczewski et al. 2019). We tested this by conditioning on PASS in one dataset, Non-PASS in the other, and re-ran the concordance pipeline requiring the following threshold in both datasets AC>1, DP > 10, and AF>0.01% to add a higher level of stringency for recovering sites. In total, there were 41,584 sites that met these criteria of which 30,683 were instances where the genomes are a Non-PASS and the exomes are a PASS. Approximately half of these sites had p values greater than 1×10^{-5}, which we consider to be reliable. The exomes represent the vast majority of sequences in gnomAD, which may make their results more stable. For analyses that require less stringent QC, we provide these sites which can be optionally retained, given that they pass cohort QC in the individual dataset.

Predicting technical bias for variants.

We used features based on variant annotations generated during variant calling (e.g. variant quality, mapping quality, etc.) to build a random forest predictor that detects the presence of technical bias for a particular variant (**Sup. Table S3**). Model training and validation was performed using several approaches. First, we used a leave-one-out cross validation using the exome dataset from gnomAD. In 22 trials (one for each of the 22 autosomes) we set aside one chromosome and used the other 21 for model training. Then, the model was tested on the variants from the chromosome that was not used for training. Using the FET p value threshold for the discordance analysis we classified the variants into 'bad' (with p < threshold) and 'good' (p > = threshold) groups. By varying the FET p value threshold discriminating the groups we performed ROC analysis. Since representation of the classes varies depending on the selected threshold we used the class weights for balancing the classes (in this and the following tests the weight for the 'bad' class was set as the fraction of 'bad' variants in the training data and the weight for the 'good' class was set to 1). The area under the ROC curve (ROC AUC) for such a model was estimated as 0.841 (**Figure 2A**).

Next, we used variant annotations from the gnomAD genomes dataset for training and variant annotations from the gnomAD exomes as a test sample. These are two separate datasets that are well-powered to detect biases in allele frequencies and ensure full independence between test and training samples. In this setting our model again reliably predicted discordant variants, with ROC AUC=0.803 (**Figure 2A**). Feature importance analysis of the model suggests that variant quality, inbreeding coefficient, and quality by depth are the key parameters discriminating variants with and without evidence for technical bias. Therefore, current protocols for alignment and variant calling are leaving a notable footprint which can be used to detect platform biases (**Figure 2B**).

Finally, we used data from the 1000 Genomes Project (1000 Genomes Project Consortium et al. 2012)as an independent public dataset for testing the predictor. Exome sequences from 1,393 samples (**Sup. Table S4**) were used to create the variant call set following GATK best practices. Variant annotations were used to classify variants using the gnomAD genomes data as a training sample. Due to sample size, the 1000 Genomes data is significantly less powered to detect technical biases compared to gnomAD. Therefore, it is harder to confidently identify ground truth for discordant variants. Identical 1000 Genomes samples from exome and genome sequencing were used to detect variants with a signature of technical bias using the AF concordance FET described here (**Sup. Table S5**). Due to the power limitations, instead of performing ROC analysis we compared the FET p values for the variants classified as having evidence of technical bias ('bad') and those without such an evidence ('good', **Fig 2C**).

Figure 2. Reliable classification of discordant variants based on variant annotations. A) ROC analysis

for two random forest predictor validation approaches using either leave-one-out analysis on the exomes, or

the genomes as a training set to classify exome variants; **B**) Feature importance analysis for the random

forest model; **C**) Comparison of concordance analysis FET *p* values for variants from 1000 Genomes

classified using the random forest predictor trained on the gnomAD genomes dataset.

This random forest model trained on the gnomAD genome v2.1 dataset was incorporated into a freely

distributed R package called *DNAdiscover* - DNA DISCOrdant Variant IdentifiER

(https://github.com/na89/DNAdiscover). The package uses variant annotations to predict whether a variant is

likely to be 'discordant' or 'concordant' and performs well with both genome and exome sequencing data.

Discordant variants are reported in published studies and are predicted to be functionally important

We first observed the phenomenon of variant discordance through the investigation of GWAS variants in

the COVID host genetics initiative and the UK Biobank(COVID-19 Host Genetics Initiative 2021). When

inspecting top associated variants that did not have strong LD friends, we noticed that many had discordant

frequencies between GWAS arrays and gnomAD, and this often corresponded to variants that had

discrepant frequencies between the gnomAD exomes and genomes. We thus suggest that the blacklist

provided herein can be used for quality control of GWAS variants.

To investigate whether discordant variants may be spuriously attributed phenotypic relevance, we

annotated all variants with their predicted functional consequence using the Ensembl Variant Effect Predictor

(VEP) (McLaren et al. 2016). Blacklisted variants appear in all functional consequence categories, including

11536 that are annotated as missense (Figure S7, Table S5). Such variants are tempting to prioritize for

functional followup given their apparentl functional importance despite having GWAS signal likely driven by

the observed genotype calling artifact.

To see if blacklist sites have been reported in peer-reviewed publications, we intersected genome-wide

significant variants ($p < 5 \times 10^{-8}$) from the GWAS catalog (Welter et al. 2014) with our discordant sites list.

Seventeen bad variants were found in the GWAS catalog, underscoring the importance of controlling for this

artifact, as it may impact downstream interpretation of association findings (Table S2). Variants in this list

have been associated with multiple health-related phenotypes including schizophrenia, telomere length, and

blood protein levels. Of these 17, half are multi-allelic and approximately a third are indels, echoing our

earlier results of a higher discordance rate for these variant types than bi-allelic SNVs. Additionally, more

than half of the 17 are present in the first megabase of the chromosome, suggesting that areas flanking the

telomeres should be treated with caution.

Discussion

The need for extremely large sample sizes to obtain sufficient statistical power in genetic studies

requires the creation of datasets that may go beyond the financial capabilities of many research groups. This

leads to the creation of meta-datasets that have contributions from many individual studies, thus creating heterogeneity in the technologies that were used for genotyping. Therefore, identification of DNA variants that are susceptible to technical bias when genotypes originate from multiple sequencing platforms is vital in order to avoid false-positive associations and analyses of the artificially inflated allele frequencies. This is of particular concern in instances where cases may originate from one sequencing effort and controls from another.

Here, we identify and describe a technical artifact arising from NGS that may affect cohort data variant quality despite the following of gold standard QC procedures. We present our metric for the identification of discordant sites, provide a blacklist of the discordant variants in gnomAD which should be treated with caution, and release an openly-available software package containing our random forest predictor that reliably classifies untrustworthy variants in user cohort data. Excluding variants with signals of discordance across sequencing platforms will result in higher quality results and reduces the risk of spurious associations in gene discovery. We provide a blacklist of variants failing our discordance test in the gnomaD v2 dataset for immediate exclusion. We additionally provide an R-package with a predictor trained on gnomad whole genome sequencing data for use in other cohort data to identify sites with features indicative of unreliable genotype calls.

Based on the examinations presented in this manuscript, we recommend researchers using aggregated cohort data to implement the following QC procedures to ensure the elimination of discordant sites:

- Drop any variant that fails in both the gnomAD exomes and genomes
- Consider dropping any variant that fails in the gnomAD exomes, as these represent the bulk of gnomAD data
- Drop the blacklist variants presented here that are PASS in both the gnomAD exomes and genomes but that are discordant in frequency across technologies
- Drop variants that are flagged by our random forest predictor, *DNAdiscover,* in an independent dataset, as each technology has a distinct genotyping error mode
- Remove the low complexity regions
- Optional: skeptically retain sites that are on the 'recovered' list here

Methods

Characterizing discordance in genotype calls across NGS technologies

All analyses were conducted using the Hail software program on the Google Cloud platform (GCP 2021). Plots were created using Bokeh and ggplot2 (Jolly 2018; Wickham 2011). Concordance metrics for genotype calls were generated from the overlapping individuals with the command hail.methods.concordance(). Using the full release of gnomAD version 2.1 (Karczewski et al. 2020), we filtered to include only sites that were both present and had a quality determination of PASS in the genomes and exomes. We split multi-allelic variants, retained only sites that are present and PASS in both exomes and genomes, filtering to only bi-allelic sites with AC > 1 and AF > 0.01% in either dataset for the NFE. Starting with all sites with at least 1 alternate allele, and subsequently for sites with AC>5 and 10, we calculated the allele frequency (AF) in the genomes and exomes separately and ran a Fisher's Exact Test (FET) on the difference in the number of alternate AC to total alleles (allele number, AN) between these two datasets. Specific filters for various steps are described in their relevant *Results* section. The R libraries *dplyr, reshape2, pROC, ROCR* and *RandomForest* were used to process variant annotations, evaluate predictor quality and build a DNAdiscover using R-4.0.3 (Wickham et al. 2015; Wickham 2012; Robin et al. 2011; Sing et al. 2005; Liaw et al. 2002).

Acknowledgements

We thank the members of the gnomAD and Hail teams for their assistance with this project. This project was supported by the National Institute of Mental Health (K01 MH121659 and T32 MH017119 to E.G.A.) and the National Human Genome Research Institute (U24HG011450). A.A.L. was supported by the Ministry of Science and Higher Education of the Russian Federation (Agreement No. 075-15-2020-901, Institutional grant to Almazov National Medical Research Center). M.A. was in part funded by the Aging Biology Foundation.

Author Contributions

E.G.A. and M.A. designed and implemented pipelines, ran analyses, and drafted the primary manuscript. K.J.K., A.A.L. aided in code implementation and interpretation. H.R., D.M., B.M.N. and M.J.D. supervised and advised on the project. All authors reviewed and approved the final draft.

Data Access

gnomAD summary data is freely available at https://gnomad.broadinstitute.org/. Additional information and a discussion of the best practices for using gnomAD can be found at https://macarthurlab.org/blog/. *DNAdiscover* package for prediction of presence of the technical bias in variants coming from NGS and usage manual are available at https://github.com/na89/DNAdiscover. A blacklist of bad variants failing the discordance test in gnomAD is provided with this manuscript in the Supplementary Materials.

Competing Interests statement

M.J.D. is a founder of Maze Therapeutics. B.M.N. is a member of the Deep Genomics Scientific Advisory Board and serves as a consultant for the Camp4 Therapeutics Corporation, Takeda Pharmaceutical and Biogen. K.J.K is a consultant for Vor Biopharma. The remaining authors declare no competing interests.

References

1000 Genomes Project Consortium, Abecasis GR, Auton A, Brooks LD, DePristo MA, Durbin RM, Handsaker RE, Kang HM, Marth GT, McVean GA. 2012. An integrated map of genetic variation from 1,092 human genomes. *Nature* **491**: 56–65.

Adelson RP, Renton AE, Li W, Barzilai N, Atzmon G, Goate AM, Davies P, Freudenberg-Hua Y. 2019. Empirical design of a variant quality control pipeline for whole genome sequencing data using replicate discordance. *Sci Rep* **9**: 16156.

Anderson CA, Pettersson FH, Clarke GM, Cardon LR, Morris AP, Zondervan KT. 2010. Data quality control

in genetic case-control association studies. *Nat Protoc* **5**: 1564–1573.

Auton A, Salcedo T. 2015. The 1000 Genomes Project. *Assessing Rare Variation in Complex Traits* 71–85. http://dx.doi.org/10.1007/978-1-4939-2824-8_6.

Bergström A, McCarthy SA, Hui R, Almarri MA, Ayub Q, Danecek P, Chen Y, Felkel S, Hallast P, Kamm J, et al. 2020. Insights into human genetic variation and population history from 929 diverse genomes. *Science* **367**. https://science.sciencemag.org/content/367/6484/eaay5012/tab-pdf (Accessed March 19, 2020).

Collins RL, Brand H, Karczewski KJ, Zhao X, Alföldi J, Francioli LC, Khera AV, Lowther C, Gauthier LD, Wang H, et al. 2020. A structural variation reference for medical and population genetics. *Nature* **581**: 444–451.

COVID-19 Host Genetics Initiative. 2021. Mapping the human genetic architecture of COVID-19. *Nature*. http://dx.doi.org/10.1038/s41586-021-03767-x.

Gravel S, Henn BM, Gutenkunst RN, Indap AR, Marth GT, Clark AG, Yu F, Gibbs RA, 1000 Genomes Project, Bustamante CD. 2011. Demographic history and rare allele sharing among human populations. *Proc Natl Acad Sci U S A* **108**: 11983–11988.

Highnam G, Wang JJ, Kusler D, Zook J, Vijayan V, Leibovich N, Mittelman D. 2015. An analytical framework for optimizing variant discovery from personal genomes. *Nat Commun* **6**: 6275.

Jolly K. 2018. *Hands-On Data Visualization with Bokeh: Interactive web plotting for Python using Bokeh*. Packt Publishing Ltd.

Karczewski K. 2017. The genome Aggregation Database (gnomAD). *MacArthur Lab*. https://macarthurlab.org/2017/02/27/the-genome-aggregation-database-gnomad/ (Accessed May 13, 2020).

Karczewski KJ, Francioli LC, Tiao G, Cummings BB, Alföldi J, Wang Q, Collins RL, Laricchia KM, Ganna A, Birnbaum DP, et al. 2020. The mutational constraint spectrum quantified from variation in 141,456 humans. *Nature* **581**: 434–443.

Karczewski KJ, Francioli LC, Tiao G, Cummings BB, Alföldi J, Wang Q, Collins RL, Laricchia KM, Ganna A,

Birnbaum DP, et al. 2019. Variation across 141,456 human exomes and genomes reveals the spectrum of

loss-of-function intolerance across human protein-coding genes. *bioRxiv* 531210.

https://www.biorxiv.org/content/10.1101/531210v2 (Accessed May 13, 2020).

Lam M, Awasthi S, Watson HJ, Goldstein J, Panagiotaropoulou G, Trubetskoy V, Karlsson R, Frei O, Fan C-

C, De Witte W, et al. 2019. RICOPILI: Rapid Imputation for COnsortias PIpeLIne. *Bioinformatics*.

http://dx.doi.org/10.1093/bioinformatics/btz633.

Lek M, Karczewski KJ, Minikel EV, Samocha KE, Banks E, Fennell T, O'Donnell-Luria AH, Ware JS, Hill AJ,

Cummings BB, et al. 2016. Analysis of protein-coding genetic variation in 60,706 humans. *Nature* **536**: 285–

291.

Liaw A, Wiener M, Others. 2002. Classification and regression by randomForest. *R news* **2**: 18–22.

Li J, Jew B, Zhan L, Hwang S, Coppola G, Freimer NB, Sul JH. 2019. ForestQC: Quality control on genetic

variants from next-generation sequencing data using random forest. *PLoS Comput Biol* **15**: e1007556.

Ma X, Shao Y, Tian L, Flasch DA, Mulder HL, Edmonson MN, Liu Y, Chen X, Newman S, Nakitandwe J, et

al. 2019. Analysis of error profiles in deep next-generation sequencing data. *Genome Biol* **20**: 50.

McKenna A, Hanna M, Banks E, Sivachenko A, Cibulskis K, Kernytsky A, Garimella K, Altshuler D, Gabriel

S, Daly M, et al. 2010. The Genome Analysis Toolkit: a MapReduce framework for analyzing next-generation

DNA sequencing data. *Genome Res* **20**: 1297–1303.

McLaren W, Gil L, Hunt SE, Riat HS, Ritchie GRS, Thormann A, Flicek P, Cunningham F. 2016. The

Ensembl Variant Effect Predictor. *Genome Biol* **17**: 122.

Robin X, Turck N, Hainard A, Tiberti N, Lisacek F, Sanchez J-C, Müller M. 2011. pROC: an open-source

package for R and S+ to analyze and compare ROC curves. *BMC Bioinformatics* **12**: 77.

Sing T, Sander O, Beerenwinkel N, Lengauer T. 2005. ROCR: visualizing classifier performance in R.

Bioinformatics **21**: 3940–3941.

Welter D, MacArthur J, Morales J, Burdett T, Hall P, Junkins H, Klemm A, Flicek P, Manolio T, Hindorff L, et al. 2014. The NHGRI GWAS Catalog, a curated resource of SNP-trait associations. *Nucleic Acids Res* **42**: D1001–6.

Wickham H. 2011. ggplot2. *Wiley Interdiscip Rev Comput Stat* **3**: 180–185.

Wickham H. 2012. reshape2: Flexibly reshape data: a reboot of the reshape package. *R package version* **1**. http://cran.ms.unimelb.edu.au/web/packages/reshape2/.

Wickham H, Francois R, Henry L, Müller K, Others. 2015. dplyr: A grammar of data manipulation. *R package version 0 4* **3**: 156.

Google Cloud Computing, Hosting Services & APIs. *Google Cloud*. https://cloud.google.com/gcp/ (Accessed May 13, 2020a).

Hail. https://hail.is/ (Accessed May 13, 2020b).