Decision Tree Ensembles Utilizing Multivariate Splits Are Effective at Investigating Beta-

Diversity in Medically Relevant 16S Amplicon Sequencing Data

Josip Rudar[1], G. Brian Golding[2], Stefan C. Kremer[3], Mehrdad Hajibabaei[1]

[1] Department of Integrative Biology & Centre for Biodiversity Genomics, University of Guelph,

50 Stone Road East, Guelph, ON, N1G 2W1, Canada

[2] Department of Biology, McMaster University, 1280 Main St. West, Hamilton, ON, L8S 4K1,

Canada

[3] School of Computer Science, University of Guelph, 50 Stone Road East, Guelph, ON, NIG

2W1, Canada

Corresponding author info:

Josip Rudar – joe.rudar@gmail.com

Mehrdad Hajibabaei – mhajibab@uoguelph.ca

Abstract

Developing an understanding of how microbial communities vary across conditions is an important analytical step. We used 16S rRNA data isolated from human stool to investigate if learned dissimilarities, such as those produced using unsupervised decision tree ensembles, can be used to improve the analysis of the composition of bacterial communities in patients suffering from Crohn's Disease and adenomas/colorectal cancers. We also introduce a workflow capable of learning dissimilarities, projecting them into a lower dimensional space, and identifying features that impact the location of samples in the projections. For example, when used with the centered log-ratio transformation, our new workflow (TreeOrdination) could identify differences in the microbial communities of Crohn's Disease patients and healthy controls. Further investigation of our models elucidated the global impact ASVs had on the location of samples in the projected space and how each ASV impacted individual samples in this space. Furthermore, this approach can be used to integrate patient data easily into the model and results in models that generalize well to unseen data. Models employing multivariate splits can improve the analysis of complex high-throughput sequencing datasets since they are better able to learn about the underlying structure of the dataset.

Author Summary

There is an ever-increasing level of interest in accurately modeling and understanding the role that commensal organisms play in human health and disease. We show that learned representations can be used to create informative ordinations. We also demonstrate that the application of modern model introspection algorithms can be used to investigate and quantify the impact of taxa in these ordinations and that the taxa identified by these approaches have been associated with immune-mediated inflammatory diseases and colorectal cancer.

Introduction

The analysis of the composition of ecological communities is essential to determine their function within the broader environment and within host. The statistical analysis of differences between communities, beta diversity, is often an important aspect of statistical pipelines used to investigate ecological and metagenomic datasets. Central to the analysis of beta diversity is the calculation of pairwise distances or dissimilarities between samples. This calculation is carried out by carefully choosing and then applying a particular dissimilarity which is known to measure an important characteristic of the data. For example, some methods (such as correlation-based distance methods) perform well at measuring environmental gradients while others, such as the Jaccard distance, can perform well when one is interested in clustering data (1–3). When analyzing amplicon sequencing data another typical goal is to discover amplicon sequence variants (ASVs) or operational taxonomic units (OTUs) associated with each type of community. This task is inextricably linked to variations in the composition of communities, which can be captured using a distance metric or dissimilarity measure. This type of analysis is typically carried separately from the analysis of community composition using tools such as DESeq2, MetagenomeSeq, ANCOM, or LEfSE (3–8). Furthermore, the assumptions of these methods could contribute to higher false-positive and false-negative rates which could lead to potentially erroneous or incomplete interpretations (3,9,10). Therefore, it is preferable if impactful ASVs (or OTUs, etc) can be identified directly when investigating community composition. Furthermore, it is also important that these analyses are done using methods that make few (if any) assumptions about the underlying distribution of each ASV. Finally, for any method to be useful, it is important for it to consider dependencies between features (which can be genes, taxonomic groups, operational taxonomic units, amplicon sequence variants). By attempting to model these

dependencies, subtle differences between groups are more likely to be detected. This is

supported by recent work which has demonstrated that genomic, transcriptomic, and

metagenomic datasets are better understood if these relationships are considered (11–13).

Machine learning algorithms are uniquely suited to address these challenges. Unlike

statistical models, machine learning models tend not to assume anything about the underlying

distribution of each feature (4,5). Furthermore, some machine learning models, such as Random

Forests (RFs) and related classifiers, are capable of identifying dependencies between features

without the need for the user to explicitly include these dependencies in the model (11,14–17).

One, and arguably underused, ability inherent to this class of models is that they can be used in

an 'unsupervised' manner to learn a dissimilarity function (15,18,19). This is known as metric

learning and the learned dissimilarity function can be used to replace a more traditional method

(such as the Jaccard distance or Bray-Curtis dissimilarity) when investigating beta-diversity

(17,20). This approach is also advantageous since it learns to remove the influence of

uninformative features (21). Unsupervised Random Forests have previously been used to

discover similar cell populations in single-cell RNAseq data, identify different classes of renal

cell carcinomas tumors, and study the underlying structure of a population using shared genetic

variations (20,22,23). If this approach is applied to amplicon sequencing data it may be possible

to simultaneously visualize the differences between communities while also identifying which

features contribute most to the placement of each community within the projected space (17,20).

However, Random Forests do suffer an important limitation: the decision trees used to construct

the forest make axis-orthogonal cuts. Randomizing the selection of cut points at each node has

been shown to help since this results in the construction of better decision boundaries. However,

improvements such as these are not a solution since axis-orthogonal cuts are still made. To solve

this problem trees that can learn oblique or non-linear cuts should be used. Recent and historical

work using decision tree classifiers demonstrates that these types of splits often result in learning

a more appropriate representation of the data (11,24).

Recently, we have introduced a new algorithm, Large Scale Non-Parametric Discovery of

Markers (LANDMark), as an alternative to RFs (25). Like the RF, LANDMark is a tree-based

approach that recursively partitions samples until a stopping criterion is met. Unlike RFs,

LANDMark can use learned linear and non-linear models to partition samples (25). In this study,

we investigate LANDMark's ability to predict medically relevant outcomes, such as Crohn's

Disease and colorectal cancer, using amplicon sequence datasets. We also provide a workflow,

TreeOrdination, which uses LANDMark to quantify differences in the makeup of microbial

communities in an unsupervised manner. TreeOrdination and LANDMark's performance is

investigated using a synthetic and randomized dataset, a small case study, and a larger colorectal

cancer dataset (26–28). The code used to perform the analysis in this work can be found at:

https://github.com/jrudar/Unsupervised-Decision-Trees.

Methods

Dataset Description

Two human microbiome datasets were selected for use as case studies. The first dataset

was chosen since it contains samples from patients who suffer from immune-mediated

inflammatory diseases (IMID) (26). Differences between the microbiomes of patients suffering

from Crohn's disease (CD), ulcerative colitis (UC), multiple sclerosis (MS), and rheumatoid

arthritis (RA) were compared to healthy controls. This is an important area of research since

many people across the world suffer from these conditions. Therefore, models which are better

able to identify ASVs associated with these conditions can provide further insight into these

diseases. In this study, we used the CD-HC subset of data as a case study. The second dataset is

derived from the stool samples of healthy patients and those suffering from colorectal cancers

and adenomas. 16S rRNA gene sequencing was used to identify the composition of the colon

community in each of the 490 patients (28). This dataset is important due to the prevalence of

colorectal cancers in our society. Therefore, the ability to train models to detect the early stages

of cancer development and colorectal cancers will result in economic savings and the saving of

lives.

Bioinformatic Processing of Raw Reads

Raw sequences for each of the datasets were obtained from the Sequence Read Archive

(PRJNA450340 and SRP062005) (26,28). All bioinformatic processing of the raw reads was

prepared using the MetaWorks v1.8.0 pipeline (available online at:

https://githib.com/terrimporter/MetaWorks) (29). The default settings for merging reads were used

except for the parameter controlling the minimum fraction of matching bases, which was

increased from 0.90 to 0.95. This was done to remove a larger fraction of potentially erroneous

reads. Merged reads were then trimmed using the default settings MetaWorks passes to

CutAdapt. Since reads from SRP062005 were pre-processed and the primers removed no reads

were discarded during trimming. The remaining quality-controlled sequences were then de-

replicated and denoised using VSEARCH version 2.15.2 to remove putative chimeric sequences

(30). Finally, VSEARCH was used to construct a matrix where each row is a sample and each

column an Amplicon Sequence Variant (ASV). Taxonomic assignment was conducted using the

RDP Classifier (version 2.13) and the built-in reference set (31). ASVs that are likely to be

contaminants, specifically those likely belonging to chloroplasts and mitochondria, were

removed. From the remaining sequences, only those belonging to the domain *Bacteria* and

Archaea were retained for further analysis. A sample by ASV count matrix, where each row is a

sample and each column an ASV, was created for each dataset.

Calculation of Dissimilarities

Pairwise dissimilarities between samples were calculated using the Jaccard distance for

presence-absence data (Equation 1), the Aitchison distance for centered-log and robust centered-

log ratio data (Equation 2), and the Bray-Curtis dissimilarity (Equation 3) for data converted into

proportions. In addition, we investigated the performance of Extremely Randomized Trees

dissimilarity (Equations 4 and 5), and LANDMark dissimilarity. In these equations X_i and X_j

represent the i^{th} and j^{th} samples in X. Distances were calculated using the 'pairwise_distances'

function from scikit-learn (version 1.1.2) (32).

144
$$Jaccard\ Distance(X_i, X_j) = 1 - \frac{X_i \cap X_j}{X_i \cup X_j}\ (1)$$

145
$$Aitchison\ Distance(X_i, X_j) = \sqrt{\sum \left(CLR(X_i) - CLR(X_j)\right)^2}\ (2)$$

146
$$Bray - Curtis\ Dissimilarity(X_i, X_j) = \frac{\sum |X_i - X_j|}{\sum (X_i + X_j)}\ (3)$$

To calculate the Extra Trees dissimilarity, one simply determines the label of each

terminal leaf into which a sample falls. This is recorded for each decision tree in the forest.

These labels are then used to construct a binary matrix, $\bar{X}$, which simply describes the terminal

leaves into which each sample falls. Each row of $\bar{X}$ is a sample and each column is a leaf label.

The similarity between two samples is then found by calculating how often two samples share a

terminal node and dividing this count by the number of trees in the forest, N (Equation 4).

Finally, the similarity is turned into a dissimilarity according to Equation 5 (19,20,22,33).

154
$$S(X_i, X_j) = \frac{\overline{X}_i \overline{X}_j^T}{N} \quad (4)$$

155
$$D(X_i, X_j) = \sqrt{1 - S(X_i, X_j)} \quad (5)$$

LANDMark returns this binary representation directly (25). To calculate the dissimilarity

between samples in the LANDMark embedding, the Hamming distance can be used since we are

only interested in the positions where leaf labels are not shared. In these experiments, we used

LANDMark version 1.2.2 and the implementation of the Extra Trees classifier found in scikit-

learn (25,32).

To use decision tree ensembles in an unsupervised manner a second randomized dataset

is needed. To create the randomized dataset, a copy of the original count matrix was created.

Then, the counts of each ASV in the copy are randomly sampled without replacement (19,34).

The original data and randomized copy are then combined. To prevent Extra Trees and

LANDMark from using information about the original class labels, the rows in the randomized

dataset are assigned a label of "Random" while original samples are assigned a label of

"Original". The combined dataset and the new labels are then used to train the decision-tree

ensemble. Dissimilarities are calculated by passing the original data to the model to determine

which terminal leaves are associated with each sample.

TreeOrdination: Automating the Identification of Informative ASVs When Using Tree

Dissimilarities

We have developed a workflow, TreeOrdination, which uses a relatively simple set of

steps to create and analyze projections of high-dimensional amplicon sequencing data. This was

done to investigate if tree-based dissimilarities can be used to investigate beta diversity. The

TreeOrdination and LANDMark source code and documentation are available at

https://github.com/jrudar/LANDMark and https://github.com/jrudar/TreeOrdination.

TreeOrdination is a wrapper around the LANDMark and Uniform Manifold

Approximation and Projection (UMAP) algorithms (25,35). The default settings for LANDMark

were used except for the number of trees (which was set to 160), the 'use_nnet' parameter

(which was set to 'False'), and the 'max_samples_tree' parameter (which was set to 100) (25).

Upon completion of training, the original training data is passed through the classifier and the

binary matrix describing which terminal leaves each sample falls into is extracted. Multiple

LANDMark representations can be created and concatenated together. These representations can

be used to train an Extra Trees classifier to predict the original class labels. In addition, the

LANDMark representation is projected into a smaller 15-dimensional space using Uniform

Manifold Approximation and Projection (UMAP) version 0.5.3 (35,36). To create this projection

the 'min_dist' parameter is set to 0.001, while the 'n_neighbors' and 'metric' parameters are set

to 8 and "hamming", respectively. The 'PCA' functionality of scikit-learn is then used to

summarize the major directions of variation in UMAP representation (Supplementary Figure 1)

(32). To understand which ASVs impact the location of samples within the PCA projection, the

original data is then used to train an Extra Trees regression model to predict the location of each

sample in the projected space. This is necessary since calculating the impact that each ASV has

on the location of each sample in the projected space using the original model is a

computationally expensive task. Shapley scores are then used to calculate global feature

importance scores and per-sample importance scores, respectively (37,38). This method of

investigating black-box models uses game theory to calculate the importance and contribution of

each feature to the final prediction. This is done calculating how often a feature contributes to a

prediction when included with a coalition of other features.

Creation of Positive and Negative Controls

Positive and negative controls were created using a copy of the code found at

https://github.com/cameronmartino/deicode-benchmarking/blob/master/simulations (27). This

code was used in the simulations which tested robust centered log-ratio transformation

introduced by Martino et al. (2019) (27). Briefly, a synthetic dataset containing 200 samples and

1000 features was constructed according to the procedure found by Martino et al. (2019). This

was a positive control. A copy of this dataset was made, and each feature column was

independently permuted to create the negative control.

Analysis of Beta-Diversity and Generalization Performance in the Case Studies and Synthetic

Data

Samples were split into training and testing sets using repeated stratified 5-fold cross-

validation. Five repeats were used. ASVs occurring in two or fewer training samples (in the case

studies) and 5% of training samples (in the case of the control datasets) were identified. These

ASVs were then removed from both the training and testing samples. This filtration step was

taken since a reduction in the number of features can often lead to a more generalizable model

(39–41). Following this, the size of each training library was calculated, and the 15th percentile

of these sizes was found. Training and testing libraries were then rarefied so that each library

was this size and those smaller than the 15th percentile were removed (7). The rarefied data was

used for tests involving the presence-absence and proportion transformations. Tests using rCLR

and CLR transformed data did not involve rarefaction as these transformations can naturally

handle compositions (6,27,42,43). Count matrices were CLR and rCLR transformed using the

scikit-bio (version 0.5.7) and DEICODE (version 0.2.4) packages, respectively (27,44,45). To

produce the rCLR transformed data 1000 iterations of DEICODE's matrix completion algorithm

was used. Following this, the *U*, *V*, and *S* matrices (which are analogous to the sample loading,

feature loading, and eigenvalue matrix of singular value decomposition) were extracted for

further analysis (27). Randomized data for training unsupervised tree models were also created

as described above and the presence-absence, proportion, CLR, and rCLR transformations were

applied.

The transformed training data was used as input for a PerMANOVA analysis (using 999

replications). The training data was also projected using principal coordinates analysis (PCoA)

/Robust Principal Components Analysis (RPCA) and UMAP to create two-dimensional

projections which were used as input into another PerMANOVA analysis (using 999

replications). In this experiment, high F-statistics associated with significant p-values (defined as

$p \leq 0.05$) provide evidence that differences exist between groups and larger F-statistics provide

evidence for a better separation between groups. PCoA projections were created scikit-bio while

UMAP projections were created using the 'umap' package (35,44). In the case of rCLR

transformed data, this projection was automatically supplied in the form of the *U* matrix.

Unsupervised Extremely Randomized Trees and Unsupervised LANDMark projections were

created by training an Extra Trees and LANDMark Classifier. Both ensembles were consutructed

using 160 estimators. The 'use_nnet' and 'max_samples_tree' parameters of the LANDMark

classifier were set to 'False' and '100'. Dissimilarities calculated using the unsupervised

ensembles and the PCoA and UMAP projections of these dissimilarities were used as input into a

PerMANOVA analysis. Finally, TreeOrdination ordinations (using 160 estimators, 5

LANDMark classifiers, and 100 samples per tree) were created. These ordinations were also

used as input into a PerMANOVA analysis.

Where appropriate, the transformed and projected training data was also used to train an

Extra Trees and LANDMark classifier. The high-dimensional TreeOrdination embedding was

used to train an ExtraTrees classifier. The generalization performance of each model was

measured using the balanced accuracy score (from scikit-learn) (32). This was chosen since it

accounts for differences in class sizes when working with unbalanced datasets. To ascertain

which models performed the best a Wilcoxon Signed Rank test followed by the Benjamini-

Hochberg correction, implemented in the Python 'statannotations' package (version 0.5), was

used (46).

To investigate which ASVs are different between sample types, we construct a

TreeOrdination model (as described above) using the Crohn's Disease data. For this model, 70%

of the samples are used for training data while the remaining 30% are used for testing. Shapley

scores for each group were calculated to determine which features impact the location of samples

in ordination space (28,37,38). The projection was visualized using the Python 'seaborn'

(version 0.11.2) and 'matplotlib' (version 3.5.2) packages (47,48)

Analysis of Generalization Performance in the Colorectal Cancer Data

It is important to investigate how TreeOrdination and LANDMark behave when faced

with data where the differences between classes are not as clear. To carry out this investigation,

we used a large colorectal cancer dataset consisting of 490 samples (28). Since the goal of this

experiment is to determine how well models which make multivariate cuts perform when the

effect size between groups is smaller, a simplified analysis was conducted. The data was split

into two groups: normal vs colorectal cancer and normal vs. lesion (adenomas and colorectal

cancers). The generalization performance using the ASV data and ASV data complemented

using the fecal immunochemical test (FIT) was then measured (28). Five-fold stratified cross-

validation with five repeats was used to split the samples from each group into training and

testing data. ASVs found in fewer than 5% of samples in the training data were identified and

these ASVs were removed from both training and testing data. The counts for each sample were

transformed into frequencies, with zero counts being replaced using the multiplicative

replacement procedure and the centered-log-ratio transformation was then applied (45). A

random classifier (using a stratified sampling strategy), Extra Trees classifier (using 160 trees),

Random Forest classifier (using 160 trees), LANDMark classifier (using 160 trees with each tree

randomly selecting 100 samples, and the 'use_nnet' parameter set to False), and TreeOrdination

(using 160 trees with each tree randomly selecting 100 samples) were used to measure

generalization performance. The balanced accuracy and ROC-AUC scores were then calculated

on each fold. The Wilcoxon Signed Rank Test followed by the Benjamini-Hochberg correction

for multiple comparisons was used to determine if the generalization performance between

models was equivalent (46).

For each test (colorectal cancer vs normal, lesion vs normal) we measured the ability of

LANDMark and TreeOrdination to identify colorectal cancers and lesions. This was done by first

determining the probability threshold which maximizes the balanced accuracy score of the model

concerning the prediction of lesions. To do this we split each subset into training and testing

folds using five-fold stratified cross-validation with five repeats as described above. After

training each model, the probability of colorectal cancer was determined using the test set. These

probabilities were then averaged across folds. A list of probability thresholds (spaced evening

from 0 to 1.0 using increments of 0.01) was then used to determine the best possible cutoff for

colorectal cancer vs normal and the normal vs lesion models. Finally, we investigated which

ASVs were different between sample types by constructing a TreeOrdination model (as

described above). For this model, 80% of the samples were used for training data while the

remaining 20% were used for testing. Prediction probabilities were calculated using

TreeOrdination. The subset of adenoma and colorectal cancer samples at or above this threshold

were extracted and normal samples below this threshold in the test set were identified. These

samples were then grouped into FIT positive and FIT negative samples and plotted. Shapley

scores for each group were calculated to determine which features impact the location of samples

in ordination space (28,37,38).

Results

TreeOrdination Projections Result in Well Separated Groups in Simulated Data

Under each transformation using the negative controls, we observed low F-statistics and

non-significant p-values. This observation occurred irrespective of ordination type and model.

PerMANOVA was able to identify significant differences ($p \leq 0.001$) between groups found in

the positive controls across each cross-valiation fold (Figure 1). UMAP, Unsupervised

LANDMark, and TreeOrdination being among the best-performing methods (Figure 1).

However, the sole use of F-statistics (or an equivalent statistic) to demonstrate class separation in

the projection is not enough. Each ordination method should also be able to place new data of the

same class into a similar location in the ordination space. When running this experiment,

however, it quickly became apparent that creating ordinations using PCoA or RPCA results in an

important limitation. Specifically, both methods are unable to transform and project new data

into the space created using the training data. To do this, we would have needed to use all the

available data (train, test) and this would have resulted in data leakage since the test data would

influence the final projection. Therefore, to prevent data leakage and the reporting of overly

optimistic and potentially misleading results, the generalization performance of RPCA and PCoA

ordination methods were excluded (49). An overview of the important properties of each

ordination method is presented in Table 1. Of the remaining transformations, both LANDMark,

Extra Trees, and TreeOrdination models were successful at classifying unseen samples (Figure

2). Although statistically significant differences between models were observed, the size of these

differences is likely small in this test since all classifiers resulted in nearly perfect classification

results while balanced accuracy scores (Supplementary Figure 2). In contrast, when training

models using the negative control data, we observed random performance (Figure 3). Finally, our

results show that projecting data using UMAP resulted in good overall performance regardless of

distance or dissimilarity measure.

Learning Dissimilarities Can Result in Well-Separated Groups in the Crohn's Disease Case

Study

In this study, we used the Crohn's Disease dataset as a follow-up real-world test. In this

test the CLR transformation consistently resulted in large F-statistics and significant p-values (p

≤ 0.05) (Figure 4). Except with CLR transformed data, Unsupervised Extremely Randomized

Trees underperformed and often resulted in ordinations where differences between Crohn's

Disease patients and healthy controls could not be consistently detected. Even in the best case

(with the CLR transform), the F-statistics associated with Unsupervised Extremely Randomized

Trees ordinations was lower than those produced using the other ordination methods. We also

observed that transforming data into proportions resulted in poor quality ordinations. Although

reasonable ordinations were created when using the Bray-Curtis dissimilarity, the F-statistics

associated with these ordinations was lower than those produced using the presence-absence and

CLR transformations (Figure 4). The cross-validated generalization performance of models

trained on presence-absence and CLR transformed data was the best (Figure 5). No statistically

significant difference was observed in the generalization performance between models trained on

CLR transformed data. However, statistically significant differences were observed between

models trained on presence-absence data, proportions, and on UMAP transformed data

(Supplementary Figure 3). Balanced accuracy scores calculated using TreeOrdination models

were at least as good as those produced using LANDMark and Extra Trees. This result is

surprising because the predictive model in TreeOrdination is trained using a high-dimensional

embedding learned by at least one unsupervised LANDMark classifier.

LANDMark and TreeOrdination Can Be Used With Datasets Where Smaller Effect Size Exist

Between Conditions

Models in this section we will adopt the naming convention for models used in Baxter et

al. (2016). Specifically, classifiers trained on the combined ASV and FIT data will be called

ASV Multitarget Microbiota Test (MMT) models. All models trained to distinguish between

colorectal cancer and healthy controls performed better when incorporating FIT results with the

microbiome data (Figure 6). All models were better than random ($p \leq 0.0001$) and LANDMark

and TreeOrdination ASV MMT models performed particularly well in this test and our average

ROC-AUC scores for each model 0.953 and 0.953, respectively. These performed significantly

better than Extra Trees and Random Forest Classifiers ($p \leq 0.0001$) and the ROC-AUC score

from both models is comparable with that from the original study (0.952) (28). However, using

ROC-AUC scores as a measure of generalization performance can be optimistic when used with

models trained on imbalanced datasets (such as this one). To address this problem, we used the

balanced accuracy score since it is a better measure with imbalanced data. We found that scores

produced by LANDMark and TreeOrdination ASV MMT models (mean balanced accuracy

score of 0.88) are better than that of competing methods used here (Figure 6) and that this

difference was statistically significant ($p \leq 0.0001$). Since the TreeOrdination and LANDMark

models performed best, we used them to calculate the discrimination threshold which maximizes

the detection of colorectal cancer while minimizing the detection of normal tissue. These

thresholds were 0.30 for LANDMark and 0.43 for TreeOrdination. When using these thresholds,

both ASV MMT models discovered a substantial fraction of additional colorectal cancers (Figure

7 and Table 2) with the LANDMark model having a higher sensitivity when compared to FIT

and TreeOrdination at a cost of a lower specificity (Table 2). While detecting colorectal cancer is

important, it is also important to detect pre-cancerous adenomas. Therefore, we trained a model

to distinguish between lesions and normal tissue. We found that statistically signficant

differences exist between the generalization performance of various models and models that

included FIT results performed better (Figure 8). When training each classifier using the

combined ASV and FIT-score data, we observed that the balanced accuracy scores of Random

models did not differ significantly from Random Forests or Extra Trees. However, both

LANDMark and TreeOrdination ASV MMT models performed significantly better than Extra

Trees ($p \leq 0.0001$) and Random Forests ($p \leq 0.0001$) classifiers trained on the same data. Both

models resulted in a mean balanced accuracy scores of 0.63. Once again, we calculated the

optimal discrimination threshold for distinguishing lesions (adenomas and colorectal cancers)

from normal tissue. This threshold was found to be 0.69 for LANDMark and 0.66 for

TreeOrdination. Compared to FIT alone, the ASV MMT models resulted in better detection of

additional colorectal cancers and adenomas (Table 2). Interestingly, while both LANDMark and

TreeOrdination models performed well they differed in their ability to identify different types of

lesions with TreeOrdination trading sensitivity for increased specificity and the opposite

occurring in LANDMark (Figures 9).

TreeOrdination Can be Used to Identify Features Which Have a High Impact on Model

Performance

384   In the colorectal cancer dataset, the best discrimination threshold for a TreeOrdination

ASV MMT model was found to be 0.67. While the ability of the model to identify lesions was

lower than LANDMark (Table 2), this came with a marked improvement in specificity (Table 2,

Figure 9). A TreeOrdination projection, using the approximate embedding function, of predicted

lesions (samples over the discrimination threshold) and normal samples was created using the

test set data (Figure 10A). This transformation was a reasonable projection since the mean-

squared error between this approximation and the full embedding was small (1.1). Clear

differences in the location of lesions and normal tissue can be seen in the plot. This suggests that

there are differences between patients with colorectal lesions and those with normal tissue. This

observation is supported by way of a significant PerMANOVA (pseudo-F = 375.12, p ≤ 0.001,

R^2 = 0.99). Most of the variation between samples, approximately 87%, can be explained by the

first principal component, which appears to be associated with disease status. The variation along

this component appears to be predominantly driven by FIT scores (Figures 10B, 11, and 12).

Statistically significant differences were detected in the projection of adenomas and carcinoma

test samples (pseudo-F = 9.51, p ≤ 0.002, R^2 = 0.73) with variation between these groups being

driven by FIT score (Figure 10B). However, differences in the microbiome also appear to play a

role in determining where these samples are placed. While the impact of the microbiome is

minor compared to FIT scores, ASVs assigned to *Lachnospiraceae, Clostridiales,*

Anaerotruncus, and *Ruminococcaceae* are among the top features contributing to the placement

of adenomas and carcenomas. Although the microbiome appears to play a more muted role, the

sum of the Shapley scores for ASVs in FIT negative lesions tend to carry greater weight than

their FIT positive counterparts. This could indicate that FIT scores are used to determine the

region in which a sample is found while the composition of the microbiome is used to refine the

location of the sample within that region. Evidence for this comes from the higher Shapley

scores assigned to ASVs in FIT-negative samples (Figures 11 and 12).

The mean-squared error between the full and approximate TreeOrdination projections

created using the Crohn's Disease dataset was 0.54, indicating that the approximate embedding

is reasonable. Differences between the stool microbiome of Crohn's disease patients and healthy

controls were detected using PerMANOVA (pseudo-F = 31.06, $p \leq 0.003$, $R^2 = 0.99$). Nearly all

of the variation between samples, approximately 84%, can be explained by the first principal

component. This strongly suggests that disease status is associated with the variation along this

component. The ASVs which are predominantly associated with this variation belong to

Fournierella spp, *Staphylococcus spp*, *Dialister spp,* and *Ruminococcaceae* (Figure 13).

Discussion

The datasets investigated here were chosen since the human gut microbiome is an

important area of medical research and is becoming increasingly linked to important disease

phenotypes (26,28,50,51). Since machine learning models are becoming increasingly used to

identify predictive features, it is important to develop models that integrate ordination,

prediction, and the detection of differentially abundant taxa so that a better understanding of the

system and the composition and function of the human microbiome can be developed. The

choice of transformation and dissimilarity measure is often an important first consideration when

investigating microbiome data. It has long been known that the choice of dissimilarity measure

can influence our measurement and interpretation of the main gradients influencing the structure

of communities and taxonomic similarity between pairs of samples (52,53). For example, recent

investigations have demonstrated that this choice can result in misleading results due to the

sparsity inherent to the data, and differences in library size and sampling (39,54,55). To combat

these problems a multitude of dissimilarity measures and ordination approaches have been

developed to summarize and visualize ASV differences between sites (53). However, distance

metrics and other commonly used dissimilarity measures have difficulty capturing potential

dependencies between ASVs. For example, the Jaccard distance simply calculates the number of

shared ASVs over the total number of unique ASVs between two communities and it fails to

consider if the presence or absence of one ASV influences another (16). Furthermore, when

using measures that use abundance information, differences in abundance can create situations

where the sites that share the same species are more dissimilar than sites that have no species in

common. Finally, as the dimensionality of the dataset grows (the number of OTUs or ASVs

increases) there is an increasing probability many of these dimensions add noise to the dataset

(56,57). This can occur for several reasons. For example, chimeric reads, rare sequences,

inefficiencies during amplification due to primer design, and bioinformatic pipeline can

contribute irrelevant information that is difficult to remove (55,58). Many contemporary

dissimilarity measures are often sensitive to this noise since they have no way of reducing it

when the dissimilarity is being calculated (56,57). Although the application of transformations,

such as the centered log-ratio or converting to presence-absence, can mitigate some of these

issues there is yet to be a consensus on which approach is best (3,39,53,59).

It is also important to address the potential weaknesses of ordination methods such as PCoA,

Robust Principal Components Analysis (RPCA) (27), and UMAP. To begin, both PCoA and

RPCA are unable to transform new data. This is a problem since testing and validation sets are

unable to be transformed using these methods without introducing data leakage. Data leakage, in

this case, can occur if projections are created using the concatenated dataset (all training, testing,

and validation samples are used). When this happens, information about any withheld data is

included when the PCoA or RPCA objective function is optimized. This could bias the results

and potentially create machine learning models which produce overly optimistic and potentially

misleading results (49). With UMAP this is not a problem since UMAP can learn an appropriate

transformation using only the training data. This transformation can then be applied to test data

or new data without data leakage occurring. PCoA, RPCA, and to a lesser extent UMAP are also

problematic in that they require a dissimilarity measure to create an ordination. This potentially

makes these methods susceptible to the previously discussed assumptions and issues that come

with the use of such measures.

Our work presents results that attempt to address a gap ecology and microbial ecology –

using metric learning to model and understand community structure. These approaches to

measuring pairwise dissimilarity have been applied to the analysis of genomic and transcriptomic

datasets (18,20,22,33). Our foray into this domain shows that learning the pairwise dissimilarities

between samples can result in good projections which preserve the suspected biological

differences between groups. We show that UMAP is an excellent out-of-the-box replacement for

PCoA and RPCA. When using UMAP projections, we observed larger separations between

groups (measured using PerMANOVA) and models trained on the projected data were accurate

at identifying the class of test samples (See Figures 4-6). Further, training models using these

representations results in generalization performance that is at least as good as competing

methods (Figure 1 and 2). This supports a growing body of work that advocates for using UMAP

to study community composition (13,60). We also attempt to address the problems associated

with contemporary measures of dissimilarity (15,16,61). Specifically, we introduce an approach,

TreeOrdination, which can learn the pairwise dissimilarities between samples while potentially

accounting for dependencies between features since it uses a classifier, LANDMark, which

makes multivariate splits at each node. In previous work, we have shown that ensembles built

using such splits do a better job of modeling the underlying pattern in data (25). This is also well

supported by other work in the field (15,17,24,33). By using LANDMark, TreeOrdination also

minimizes the impact of noisy features through randomization (bootstrapping of training data at

each node, random selection of features, and models) and regularization (most models selected

for splitting are L1 or L2 regularized) (21,25). TreeOrdination also mitigates the weaknesses of

PCoA and RPCA since it can transform new data after training. Furthermore, it does not require

a distance metric since the dissimilarity function is learned. TreeOrdination can do this since it

first creates an intermediate embedding of the training data before using this embedding as input

for a UMAP projection (18,19,22,25). Once the initial embedding is learned, the training data is

no longer needed since each LANDMark model has learned to create an internal representation

of how to partition the space upon which the training samples are found (24,25,33,61). The

location of testing samples in this space can then be extracted and transformed into a lower-

dimensional space using UMAP. We show that this process works well when applied to real

metagenomic datasets. In these datasets, TreeOrdination's performance in these datasets was

competitive with its peers. However, we must note that we only examined two datasets and

metric learning approaches may not be suitable for all data. This is an important limitation of this

study and therefore it is up to the investigator to explore potential models and use the one best

suited for the data and question being asked.

A final contribution of our work is the link we identify between the original high-

dimensional representation of the data to the lower-dimensional projection. Specifically, we use

Shapley values to understand the impact that each feature (ASVs, OTUs, etc) has on the

ordination. In ordination approaches such as PCoA, this information is exposed as loading scores

along each principal component. However, these methods are limited in their ability to project

data when the pattern separating groups of samples is non-linear. Furthermore, they are sensitive

to outliers due to their reliance on a distance measure (56). Assuming groups can be separated

using some non-linear function, the weakness of these approaches can be easily verified if low

PerMANOVA F-statistics and high reconstruction losses between distances in the ordination and

the original space are observed. While UMAP represents an important improvement, since it is a

graph-based method that can model these non-linearities, we lose access to the loading scores

and interpretability if it is used (13,35,62). To address this problem, Shapley values can be used

to peer through the "black box" and quantify the impact that each feature has on the projection

(37,38).

Our results support this approach since we have identified ASVs belonging to organisms

associated with inflammation and colorectal cancer. This will not be an exhaustive discussion of

the organisms identified since the aim of this work is to show that methods, such as

TreeOrdination, are feasible. We observed that ASVs associated with *Ruminococcaceae* are

important in refining the location of samples in FIT-negative adenomas and colorectal cancers

and determining the location of samples in the Crohn's Disease dataset in TreeOrdination

models. The identification of this microbe is important since there is evidence to suggest that the

depletion of this family is associated with colorectal cancer and gut inflammation (63,64).

Indeed, relative to the geometric mean, the depletion of *Ruminococcaceae* in the test samples

pushes them to be more lesion-like (Figure 12). Our results also found commonalities with those

reported in the original study. For example, our results and those from Baxter et al. (2016) show

that *Lachnospiraceae* is an important predictive component and a low abundance of this group

tends to push models to be more lesion-like (28,64). *Anaerotruncus* also appeared to play a role

in refining the location of FIT-negative samples. The abundance of this genus relative to the

geometric mean of each sample suggests that high abundance will push samples to be less lesion-

like. This is an encouraging result since work has shown that an elevated abundance of

Anaerotruncus, a butyrate producer, may exert a protective effect by inhibiting glucose transport

and glycolysis (65,66). Additional support for our method comes from the results of the Crohn's

disease dataset. *Fournierella spp*, *Staphylococcus spp*, *Dialister spp,* and *Ruminococcaceae.*

were identified as the organisms with the strongest impact on the location of samples in the

TreeOrdination projection. We also identified ASVs assigned to *Ruminococcaceae, Gemmiger*

spp., and *Lachnospiraceae* as those which impact the location of samples in the TreeOrdination

projection. Encourgingly, these were also detected as important in original Forbes et al. (2018)

study (26). Some taxa, such as *Staphylococcus* and *Dialister*, have known associations with

Crohn's Disease, pro-inflammatory phenotypes, and other inflammatory diseases such as

Ankylosing Spondylitis (67–69). In addition, detecting ASVs assigned to *Ruminococcaceae* and

Lachnospiraceae as impactful is important validation since these are families are known to be

beneficial due to be producers of anti-inflammatory metabolites (28,70). We do acknowledge

that our investigation differed from the original investigations due to our use of ASVs. However,

our results are generally consistent with the wider interpretation of these studies: the composition

of the microbiome tends to shift so toward species that exert a pro-inflammatory effect (26,28).

Finally, these results demonstrate the power of TreeOrdination since the factors contributing to

the placement of individual samples can be investigated. This allows investigators to use a single

model to investigate community composition and differential abundance and predict the

properties of new samples.

Conclusions and Future Work

Our work has shown that unsupervised LANDMark (Oracle) and TreeOrdination models

can learn effective dissimilarity matrices. When paired with modern dimensionality reduction

approaches, such as UMAP, the global structure of the dataset is preserved. These

representations can then be combined with existing matrix factorization and model introspection

algorithms to create informative ordinations. Additional work should be conducted on larger

datasets to understand when metric learning should be used. Furthermore, by using larger

datasets the effect of individual differences will be reduced since a larger sample of the

population will be used in each test set (50). This will also be a good opportunity to conduct

additional comparisons between other commonly used transforms, dissimilarity measures, and

read clustering approaches. Finally, with respect to TreeOrdination, additional work needs to be

conducted in order to identify significantly different features. While there is still work to do, our

results support the use of metric learning as a replacement for traditional dissimilarity measures

in ecological research. These are advantageous since they can be used to limit the influence of

outliers and uninformative features. In the datasets used here we show there is a shift towards a

pro-inflammatory microbial community in the stool of patients suffering from Crohn's disease

and colorectal cancer and that our results are similar to those found elsewhere in the literature.

Finally, additional work should be conducted to determine more optimal ways of calculating the

dissimilarity between samples when using decision tree ensembles. This will hopefully lead to

improved ordinations and interpretations.

Acknowledgments

We would like to thank Dr. Katie McGee and Dr. Terri M. Porter for their thoughtful discussions

during the development of LANDMark. We would like to thank Dr. Marko Rudar for his

thoughtful review of the manuscript. Finally, we thank our reviewers and editor for their time

and comments. Their work has resulted in a considerably improved manuscript.

References

1. Silverman JD, Washburne AD, S M, David LA. A phylogenetic transform enhances analysis of
compositional microbiota data. eLife. 2017;6:21887.

2. Chen B, He X, Pan B, Zou X, You N. Comparison of beta diversity measures in clustering the high-
dimensional microbial data. PLoS One. 2021;16(2):e0246893.

3. Weiss S, Xu ZZ, Peddada S, Amir A, Bittinger K, Gonzalez A, et al. Normalization and microbial
differential abundance strategies depend upon data characteristics. Microbiome. 2017;5(27).

4. Love MI, Huber W, Anders S. Moderated estimation of fold change and dispersion for RNA-seq
data with DESeq2. Genome Biology. 2014 Dec 5;15(12):550.

5. Paulson JN, Stine OC, Bravo HC, M P. Robust methods for differential abundance analysis in marker
gene surveys. Nature Methods. 2013;10(12):1200–2.

6. Lin H, Peddada SD. Analysis of compositions of microbiomes with bias correction. Nature
Communications. 2020 Jul 14;11(1):3514.

7. Lin H, Peddada SD. Analysis of microbial compositions: a review of normalization and differential
abundance analysis. npj Biofilms and Microbiomes. 2020 Dec 2;6(1):60.

8. Segata N, Izard J, Waldron L, Gevers D, Miropolsky L, Garrett WS, et al. Metagenomic biomarker
discovery and explanation. Genome Biology. 2011;12:60.

9. Elhaik E. Principal Component Analyses (PCA)-based findings in population genetic studies are
highly biased and must be reevaluated. Scientific Reports. 2022 Aug 29;12(1):14683.

10.   Nearing JT, Douglas GM, Hayes MG, MacDonald J, Desai DK, Allward N, et al. Microbiome
589   differential abundance methods produce different results across 38 datasets. Nature
590   Communications. 2022 Jan 17;13(1):342.

591   11.   Kubinski R, Djamen-Kepaou JY, Zhanabaev T, Hernandez-Garcia A, Bauer S, Hildebrand F, et al.
592   Benchmark of data processing methods and machine learning models for gut microbiome-based
593   diagnosis of inflammatory bowel disease. bioRxiv [Internet]. 2021; Available from:
594   https://www.biorxiv.org/content/early/2021/05/04/2021.05.03.442488

595   12.   Dorrity MW, Saunders LM, Queitsch C, Fields S, Trapnell C. Dimensionality reduction by UMAP to
596   visualize physical and genetic interactions. Nature Communications. 2020 Mar 24;11(1):1537.

597   13.   Armstrong G, Martino C, Rahman G, Gonzalez A, Vázquez-Baeza Y, Mishne G, et al. Uniform
598   Manifold Approximation and Projection (UMAP) Reveals Composite Patterns and Resolves
599   Visualization Artifacts in Microbiome Data. mSystems. 0(0):e00691-21.

600   14.   Ryo M, Rillig MC. Statistically reinforced machine learning for nonlinear patterns and variable
601   interactions. Ecosphere. 2017;8(11):01976.

602   15.   Cutler RD, Edwards TC, Beard KH, Cutler A, Hess KT, Gibson J, et al. Random Forests for
603   Classification in Ecology. Ecology. 2007;88(11):2783–92.

604   16.   Touw WG, Bayjanov JR, Overmars L, Backus L, Boekhorst J, Wels M, et al. Data mining in the Life
605   Sciences with Random Forest: a walk in the park or lost in the jungle? Brief Bioinform.
606   2012;14(3):315–26.

607   17.   Rhodes JS, Cutler A, Moon KR. Geometry- and Accuracy-Preserving Random Forest Proximities
608   [Internet]. arXiv; 2022. Available from: https://arxiv.org/abs/2201.12682

609   18.   Breiman L. Random Forests. Machine Learning. 2001;45(1):5–32.

610   19.   Dalleau K, Couceiro M, Smail-Tabbone M. Unsupervised Extremely Randomized Trees. In: Phung D,
611   Tseng VS, Webb GI, Ho B, Ganji M, Rashidi L, editors. Advances in Knowledge Discovery and Data
612   Mining. Cham: Springer International Publishing; 2018. p. 478–89.

613   20.   Alhusain L, Hafez AM. Cluster ensemble based on Random Forests for genetic data. BioData
614   Mining. 2017 Dec 15;10(1):37.

615   21.   Mentch L, Zhou S. Randomization as Regularization: A Degrees of Freedom Explanation for
616   Random Forest Success. Journal of Machine Learning Research. 2020;21:171:1-171:36.

617   22.   Pouyan MB, Kostka D. Random forest based similarity learning for single cell RNA sequencing data.
618   Bioinformatics. 2018 Jul 1;34(13):i79–88.

619   23.   Chen X, Ishwaran H. Random forests for genomic data analysis. Genomics. 2012 Jun 1;99(6):323–9.

620   24.   Menze BH, M K, Splitthoff DN, K K, Hamprecht FA. On oblique random forests. In: Gunopulos D,
621   Hofmann T, Malerba D, Vazirgiannis M, editors. Machine Learning and Knowledge Discovery in
622   Databases. 2011. p. 453–69.

623   25.   Rudar J, Porter TM, Wright M, Golding GB, Hajibabaei M. LANDMark: An ensemble approach to the
624   supervised selection of biomarkers in high-throughput sequencing data. BMC Bioinformatics.
625   2022;23(1):110.

626   26.   Forbes JD, Chen CY, Knox NC, Marrie RA, El-Gabalawy H, de Kievit T, et al. A comparative study of
627   the gut microbiota in immune-mediated inflammatory diseases-does a common dysbiosis exist?
628   Microbiome. 2018 Dec 13;6(1):221–221.

629   27.   Martino C, Morton JT, Marotz CA, Thompson LR, Tripathi A, Knight R, et al. A Novel Sparse
630   Compositional Technique Reveals Microbial Perturbations. mSystems. 2019 Feb;4(1).

631   28.   Baxter NT, Ruffin MT, Rogers MAM, Schloss PD. Microbiota-based model improves the sensitivity
632   of fecal immunochemical test for detecting colonic lesions. Genome Medicine. 2016 Apr 6;8(1):37.

633   29.   Porter TM, Hajibabaei M. METAWORKS: A flexible, scalable bioinformatic pipeline for multi-marker
634   biodiversity assessments. bioRxiv. 2020;

635   30.   Rognes T, Flouri T, Nichols B, Quince C, Mahe F. VSEARCH: a versatile open source tool for
636   metagenomics. PeerJ. 2016;4:2584.

637   31.   Wang Q, Garrity GM, Tiedje JM, Cole JR. Naive Bayesian classifier for rapid assignment of rRNA
638   sequences into the new bacterial taxonomy. Applied and Environmental Microbiology. 2007
639   Aug;73(16):5261–7.

640   32.   Pedregosa F, Varoquaux G, Gramfort A, Michel V, Thirion B, Grisel O, et al. Scikit-learn: Machine
641   Learning in Python. Journal of Machine Learning Research. 2011;12:2825–30.

642   33.   Xiong C, Johnson D, Xu R, Corso JJ. Random Forests for Metric Learning with Implicit Pairwise
643   Position Dependence. In: Proceedings of the 18th ACM SIGKDD International Conference on
644   Knowledge Discovery and Data Mining [Internet]. New York, NY, USA: Association for Computing
645   Machinery; 2012. p. 958–66. (KDD '12). Available from: https://doi.org/10.1145/2339530.2339680

646   34.   Camargo A. PCAtest: testing the statistical significance of Principal Component Analysis in R. PeerJ.
647   2022;10:e12967.

648   35.   McInnes L, Healy J, Melville J. UMAP: Uniform Manifold Approximation and Projection for
649   Dimension Reduction. Journal of Open Source Software. 2020;3(29):861.

650   36.   Geurts P, Ernst D, Wehenkel L. Extremely Randomized Trees. Machine Learning. 2006;63(1):3–42.

651   37.   Lundberg SM, Lee S. A Unified Approach to Interpreting Model Predictions. In: 31st Conference on
652   Neural Information Processing Systems (NIPS 2017 [Internet]. Long Beach; 2017. Available from:
653   http://papers.nips.cc/paper/7062-a-unified-approach-to-interpreting-model-predictions.pdf.

654   38.   Lundberg SM, Erion G, Chen H, DeGrave A, Prutkin JM, Nair B, et al. From local explanations to
655   global understanding with explainable AI for trees. Nat Mach Intell. 2020;2(1):56–67.

656   39.   Gloor GB, Macklaim JM, Pawlovsky-Glahn V, Egozcue JJ. Microbiome Datasets Are Compositional:
657   And This Is Not Optional. Front Microbiol. 2017;8:2224.

40. Ranasinghe JA, Stein ED, Miller PE, Weisberg SB. Performance of two Southern California benthic
community indices using species abundance and presence-only data: relevance to DNA barcoding.
PLoS One. 2012;7(8):40875.

41. Wallen ZD. Comparison study of differential abundance testing methods using two large Parkinson
disease gut microbiome datasets derived from 16S amplicon sequencing. BMC Bioinformatics.
2021 May 25;22(1):265.

42. Gloor GB, Wu JR, Pawlowsky-Glahn V, Egozcue JJ. It's all relative: analyzing microbiome data as
compositions. Ann Epidemiol. 2016 May;26(5):322–9.

43. Greenacre M, Martínez-Álvaro M, Blasco A. Compositional Data Analysis of Microbiome and Any-
Omics Datasets: A Validation of the Additive Logratio Transformation. Frontiers in Microbiology
[Internet]. 2021;12. Available from:
https://www.frontiersin.org/article/10.3389/fmicb.2021.727398

44. team T scikit-bio development. scikit-bio: A Bioinformatics Library for Data Scientists, Students,
and Developers [Internet]. 2022. Available from: http://scikit-bio.org

45. Martín-Fernández JA, Barceló-Vidal C, Pawlowsky-Glahn V. Dealing with Zeros and Missing Values
in Compositional Data Sets Using Nonparametric Imputation. Mathematical Geology. 2003 Apr
1;35(3):253–78.

46. Charlier F, Weber M, Izak D, Harkin E, Magnus M, Lalli J, et al. Statannotations [Internet]. Zenodo;
2022. Available from: https://doi.org/10.5281/zenodo.7213391

47. Waskom ML. seaborn: statistical data visualization. Journal of Open Source Software.
2021;6(60):3021.

48. Hunter JD. Matplotlib: A 2D graphics environment. Computing in Science & Engineering.
2007;9(3):90–5.

49. Dong Q. Leakage Prediction in Machine Learning Models When Using Data from Sports Wearable
Sensors. Comput Intell Neurosci. 2022;2022:5314671.

50. Flynn K, Ruffin MT IV, Turgeon K, Schloss PD. Spatial Variation of the Native Colon Microbiota in
Healthy Adults. Cancer Prevention Research. 2018;11(7):393–402.

51. Aryal S, Alimadadi A, Manandhar I, Joe B, Cheng X. Machine Learning Strategy for Gut Microbiome-
Based Diagnostic Screening of Cardiovascular Disease. Hypertension. 2020;76(5):1555–62.

52. Bacaro G, Ricotta C, Mazzoleni S. Measuring beta-diversity from taxonomic similarity. Journal of
Vegetation Science. 2007;18(6):793–8.

53. Wildi O. Evaluating the Predictive Power of Ordination Methods in Ecological Context.
Mathematics [Internet]. 2018;6(12). Available from: https://www.mdpi.com/2227-7390/6/12/295

54. Leite MFA, Kuramae EE. You must choose, but choose wisely: Model-based approaches for
microbial community analysis. Soil Biology and Biochemistry. 2020;151:108042.

55. Hugerth LW, Andersson AF. Analysing Microbial Community Composition through Amplicon
Sequencing: From Sampling to Hypothesis Testing. Frontiers in Microbiology. 2017;8:1561.

56. Zimek A, Schubert E, Kriegel HP. A survey on unsupervised outlier detection in high-dimensional
numerical data. Statistical Analysis and Data Mining: The ASA Data Science Journal. 2012;5(5):363–
87.

57. Aggarwal CC, Hinneburg A, Keim DA. On the Surprising Behavior of Distance Metrics in High
Dimensional Space. In: Van den Bussche J, Vianu V, editors. Database Theory — ICDT 2001. Berlin,
Heidelberg: Springer Berlin Heidelberg; 2001. p. 420–34.

58. Schloss PD. Amplicon Sequence Variants Artificially Split Bacterial Genomes into Separate Clusters.
mSphere. 2021 Aug 25;6(4):e0019121.

59. McKnight DT, Huerlimann R, Bower DS, Schwarzkopf L, Alford RA, Zenger KR. Methods for
normalizing microbiome data: An ecological perspective. Methods in Ecology and Evolution.
2019;10(3):389–400.

60. Klimenko NS, Odintsova VE, Revel-Muroz A, Tyakht AV. The hallmarks of dietary intervention-
resilient gut microbiome. npj Biofilms and Microbiomes. 2022 Oct 8;8(1):77.

61. Tsagkrasoulis D, Montana G. Random forest regression for manifold-valued responses. Pattern
Recognition Letters. 2018;101:6–13.

62. Kobak D, Linderman GC. Initialization is critical for preserving global data structure in both t-SNE
and UMAP. Nature Biotechnology. 2021 Feb 1;39(2):156–7.

63. He T, Cheng X, Xing C. The gut microbial diversity of colon cancer patients and the clinical
significance. Bioengineered. 2021 Jan 1;12(1):7046–60.

64. Park J, Kim NE, Yoon H, Shin CM, Kim N, Lee DH, et al. Fecal Microbiota and Gut Microbe-Derived
Extracellular Vesicles in Colorectal Cancer. Frontiers in Oncology [Internet]. 2021;11. Available
from: https://www.frontiersin.org/articles/10.3389/fonc.2021.650026

65. Geng HW, Yin FY, Zhang ZF, Gong X, Yang Y. Butyrate Suppresses Glucose Metabolism of Colorectal
Cancer Cells via GPR109a-AKT Signaling Pathway and Enhances Chemotherapy. Frontiers in
Molecular Biosciences [Internet]. 2021;8. Available from:
https://www.frontiersin.org/articles/10.3389/fmolb.2021.634874

66. Bianchimano P, Britton GJ, Wallach DS, Smith EM, Cox LM, Liu S, et al. Mining the microbiota to
identify gut commensals modulating neuroinflammation in a mouse model of multiple sclerosis.
Microbiome. 2022 Oct 17;10(1):174.

67. Huang WQ, Huang HL, Peng W, Liu YD, Zhou YL, Xu HM, et al. Altered Pattern of Immunoglobulin
A-Targeted Microbiota in Inflammatory Bowel Disease After Fecal Transplantation. Front
Microbiol. 2022;13:873018.

68. Lopetuso LR, Petito V, Graziani C, Schiavoni E, Paroni Sterbini F, Poscia A, et al. Gut Microbiota in
Health, Diverticular Disease, Irritable Bowel Syndrome, and Inflammatory Bowel Diseases: Time for
Microbial Marker of Gastrointestinal Disorders. Digestive Diseases. 2018;36(1):56–65.

69. Tito RY, Cypers H, Joossens M, Varkas G, Van Praet L, Glorieus E, et al. Brief Report: Dialister as a
Microbial Marker of Disease Activity in Spondyloarthritis. Arthritis & Rheumatology.
2017;69(1):114–21.

70. Parada Venegas D, De la Fuente MK, Landskron G, González MJ, Quera R, Dijkstra G, et al. Short
Chain Fatty Acids (SCFAs)-Mediated Gut Epithelial and Immune Regulation and Its Relevance for
Inflammatory Bowel Diseases. Frontiers in Immunology [Internet]. 2019;10. Available from:
https://www.frontiersin.org/articles/10.3389/fimmu.2019.00277

Tables

Table 1: An overview of the properties of each ordination method.

	Can Be Trained Using Any Ecological Transformation	Can Be Used to Transform Unseen Data	Learns/Creates a Non-Linear Projection	Returns Importance Scores
TreeOrdination	Yes	Yes	Yes	Yes
Unsupervised LANDMark	Yes	Yes	Yes	Yes
Unsupervised Extremely Randomized Trees	Yes	Yes	Yes**	Yes
Uniform Manifold Approximation and Projection	Yes	Yes	Yes	No
Principal Components Analysis	No*	Yes	No	Yes
Principal Co-ordinates Analysis	Yes*	No	No	Yes
Robust Principal Components Analysis (DEICODE)	No (Robust Centered Log-Ratio Only)	No	No	Yes
*- Assumes samples are found in a Euclidean space (PCA). PCoA is a generalization of PCA to other distance/dissimilarity measures. ** - Although this is a type of non-linear classifier, axis-orthogonal cuts are made to separate samples at each node				

Table 2: Sensitivities and specificities for LANDMark and TreeOrdination ASV MMT models, TreeOrdination ASV MMT models, and FIT. Each 95% confidence interval was calculated using 2000 stratified bootstrap replicates.

Model	Sensitivity (95% CI)	Specificity (95% CI)
Normal vs. Cancer (FIT)	0.75 (0.68-0.83)	0.97 (0.94-0.99)
Normal vs. Adenoma (FIT)	0.16 (0.11-0.21)	0.97 (0.94-0.99)
Normal vs. Cancer Only (TreeOrdination MMT Model)	0.82 (0.74-0.88)	0.96 (0.94-0.99)
Normal vs. Cancer Only (LANDMark MMT Model)	0.83 (0.76-0.90)	0.95 (0.91-0.98)
Normal vs. Cancer (Lesion TreeOrdination MMT Model)	0.83 (0.77-0.90)	0.96 (0.96-0.98)
Normal vs. Adenoma (Lesion TreeOrdination MMT Model)	0.25 (0.19-0.31)	0.96 (0.93-0.98)
Normal vs. Lesion (Lesion TreeOrdination MMT Model)	0.47 (0.43-0.52)	0.96 (0.94-0.99)
Normal vs. Cancer (Lesion LANDMark MMT Model)	0.89 (0.83-0.94)	0.86 (0.80-0.91)
Normal vs. Adenoma (Lesion LANDMark MMT Model)	0.36 (0.30-0.43)	0.86 (0.81-0.91)
Normal vs. Lesion (Lesion LANDMark MMT Model)	0.56 (0.52-0.61)	0.86 (0.81-0.91)

Figures

Figure 1: PerMANOVA results for each test condition in the positive control data. The pseudo-F statistic is log-transformed to improve the readability of the chart. Higher statistics indicate a greater separation between groups of samples. The 95% confidence interval, calculated using 2000 bootstraps, is shown for each bar in black. Five-fold stratified cross-validation with five repeats was used to generate this data. Bars are colored according to the dissimilarity. Blue, green, and red bars represent data analyzed using the Jaccard distance, Bray-Curtis dissimilarity, and Euclidean distances. Orange bars are learned dissimilarities, while the purple bar are distances calculated using DEICODE.

Figure 2: Balanced accuracy score results for each test condition in the positive control data. Higher scores indicate a more accurate classifier. The 95% confidence interval, calculated using 2000 bootstraps, is shown for each bar in black. Five-fold stratified cross-validation with five repeats was used to generate this data.

Figure 3: Balanced accuracy score results for each test condition in the negative control data. Higher scores indicate a more accurate classifier. The 95% confidence interval, calculated using 2000 bootstraps, is shown for each bar in black. Five-fold stratified cross-validation with five repeats was used to generate this data.

Figure 4: PerMANOVA results for each test condition in the Crohn's Disease data. Higher pseudo-F statistics indicate greater separation between groups of samples (A). Panel (B) shows the distribution of p-values associated with the cross-validated distribution of pseudo-F statistics from (A). The 95% confidence interval, calculated using 2000 bootstraps, is shown for each bar in black. Five-fold stratified cross-validation with five repeats was used to generate this data.

Figure 5: Balanced accuracy score results for each test condition in the Crohn's Disease data. Higher scores indicate a more accurate classifier. The 95% confidence interval, calculated using 2000 bootstraps, is shown for each bar in black. Five-fold stratified cross-validation with five repeats was used to generate this data.

Figure 6: The ability of each model to identify patients with colorectal cancer. The balanced accuracy scores are reported on the left while the ROC-AUC scores are reported on the right. Each model was trained using centered log-ratio transformed data with (blue bars) and without (orange bars) the inclusion of FIT scores. These scores were generated using Fivefold Stratified Cross Validation with five repeats.

Figure 7: Results of the LANDMark-based ASV MMT model for distinguishing between normal and colorectal cancer. Points are colored based on the predicted labels and actual labels. The position of points along the y-axis was found by averaging the cross-validated probabilities of test samples. The black horizontal line represents the threshold maximizing the balanced accuracy score (0.30).

Figure 8: The ability of each model to identify patients with colorectal lesions (adenomas and colorectal cancers). The balanced accuracy scores are reported on the left while the ROC-AUC scores are reported on the right. Each model was trained using centered log-ratio transformed data with (blue bars) and without (orange bars) the inclusion of FIT scores. These scores were generated using five-fold stratified cross-validation with five repeats. LANDMark and TreeOrdination models trained on the combined ASV and FIT data tended to perform better than their counterparts in this task.

Figure 9: The discriminatory power of a LANDMark and TreeOrdination-based ASV MMT models. (A) The ability of LANDMark to distinguish between normal tissue, adenomas, and colorectal cancers at the given discrimination threshold (0.69). (B) The ability of TreeOrdination to distinguish between normal tissue, adenomas, and colorectal cancers at the given discrimination threshold (0.66). The position of points along the y-axis was found by averaging the cross-validated probabilities of test samples. The black line represents the threshold maximizing the balanced accuracy score (0.69).

Figure 10: TreeOrdination projection of test samples. (A) PCA axis 1 verses axis 2 constructed using the subset of lesions (colorectal cancers and adenomas) above the discrimination threshold and all normal samples below this threshold. (B) A summary of how the Shapley values impact the placement of adenomas and carcinomas along the first principal component.

Figure 11: Global feature impact scores in FIT positive and FIT negative samples. The impact of each feature's ability to discriminate the location of samples along PCA1 in the TreeOrdination projection of a FIT-positive adenomas (A), FIT-positive colorectal cancers (B), FIT-negative adenomas (C), and FIT-negative colorectal cancers (D).

Figure 12: Local importance values for an individual adenoma, colorectal cancer, and normal FIT negative samples. The placement of individual samples along the first principal component (the f(x) value) can be decomposed using Shapley values. An example of how ASVs and FIT scores impact the locations of an adenoma (A), colorectal cancer (B), and a normal sample (C) are shown. Along the left in grey is the FIT score and the abundance of each ASV relative to the geometric mean of the sample. Points are shifted to the left (blue) if they are pushed towards the "normal" region of the ordination and to the right (pink) if they are pushed to the region concentrated with lesions.

Figure 13: TreeOrdination projection of test samples from the Crohn's Disease dataset. (A) PCA axis 1 verses axis 2 constructed using test samples from the Crohn's Disease dataset. (B) A summary of how the Shapley values impact the placement of samples along the first principal component.

Supporting Information

Supplementary File 1 – Supplementary Figure 1: High-level overview of how TreeOrdination produces a projection. (A) Columns in a copy of the training data are randomized. The randomized data is then concatenated to the original data. (B) N LANDMark classifiers are trained on N unique randomizations of the original data. No information about the original sample labels is used to train these classifiers. (C) Using the training data, the leaf labels for each of the N LANDMark classifiers are extracted and concatenated together. The result is a binary matrix where each row is a sample and each column a leaf label. (D) Using this binary matrix, a UMAP/PCA transformer is trained. (E) Using the unseen or testing data, the leaf labels for each of the N LANDMark classifiers are extracted and concatenated together. The result is a binary matrix where each row is a sample and each column a leaf label. (F) The trained UMAP/PCA transformer from (D) is then used to transform this matrix.

Supplementary File 2 – Supplementary Figure 2: Balanced accuracy score results for each test condition in the positive control data. Higher scores indicate a more accurate classifier. The 95% confidence interval, calculated using 2000 bootstraps, is shown for each bar in black. Five-fold stratified cross-validation with five repeats was used to generate this data. The statistical significance of each pairwise comparison was computed using the Wilcoxon test followed by a Benjamini-Hochberg correction. $p \leq 0.0001$ (****), $p \leq 0.001$ (***), $p \leq 0.01$ (**), $p \leq 0.05$ (*), $p > 0.05$ (ns).

Supplementary File 3 – Supplementary Figure 3: Balanced accuracy score results for each test condition in the Crohn's Disease data. Higher scores indicate a more accurate classifier. The 95% confidence interval, calculated using 2000 bootstraps, is shown for each bar in black. Five-fold stratified cross-validation with five repeats was used to generate this data. The statistical significance of each pairwise comparison was computed using the Wilcoxon test followed by a Benjamini-Hochberg correction. $p \leq 0.0001$ (****), $p \leq 0.001$ (***), $p \leq 0.01$ (**), $p \leq 0.05$ (*), $p > 0.05$ (ns).

GitHub Link 1– Raw Data and Code Used to Run the Analysis

(https://github.com/jrudar/Unsupervised-Decision-Trees)

GitHub Link 2– TreeOrdination Code

(https://github.com/jrudar/TreeOrdination)

GitHub Link 3– LANDMark Code

(https://github.com/jrudar/LANDMark)