Decision Tree Ensembles Utilizing Multivariate Splits Are Effective at Investigating Beta-

Diversity in Medically Relevant 16S Amplicon Sequencing Data

Josip Rudar[1], G. Brian Golding[2], Stefan C. Kremer[3], Mehrdad Hajibabaei[1]

[1] Department of Integrative Biology & Centre for Biodiversity Genomics, University of Guelph,

50 Stone Road East, Guelph, ON, N1G 2W1, Canada

[2] Department of Biology, McMaster University, 1280 Main St. West, Hamilton, ON, L8S 4K1,

Canada

[3] School of Computer Science, University of Guelph, 50 Stone Road East, Guelph, ON, NIG

2W1, Canada

Corresponding author info:

Josip Rudar – joe.rudar@gmail.com

Mehrdad Hajibabaei – mhajibab@uoguelph.ca

Abstract

We investigated how well decision-tree ensemble classifiers can identify and quantify differences in the compositions of microbial communities using previously sequenced 16S rRNA gene from the lumen and mucosa of the proximal human colon and the stool of patients suffering from Crohn's Disease. Tree-based approaches were then compared to ordinations produced using the Jaccard and Aitchison metrics. Since these investigations favored tree-based approaches, they were used as a basis for a workflow capable of learning dissimilarities, projecting them into a lower dimensional space, and identifying the features impacting the location of samples in the projections. When used with the centered log-ratio transformation, our new workflow (TreeOrdination) was capable of identifying differences in the microbial communities of the proximal colon and between Crohn's Disease patients and healthy controls ($9.08 \leq$ Pseudo-F ≤ 30.31, $0.001 \leq p \leq 0.004$; $21.19 \leq$ Pseudo-F ≤ 101.83, $0.001 \leq p \leq 0.002$). These projections were often better than those produced using the Aitchison distance ($8.22 \leq$ Pseudo-F ≤ 13.34, $p \leq 0.004$; $15.20 \leq$ Pseudo-F ≤ 30.70, $p \leq 0.001$). TreeOrdination models also generalized well to unseen data. In the proximal colon dataset, for example, default TreeOrdination models resulted in balanced accuracy scores that were more likely to be higher than classifiers only trained on centered-log ratio transformed data. Finally, TreeOrdination was able to identify ASVs known to be associated with each type of sample while also identifying potential new biomarkers of immune-mediated inflammatory diseases, such as *Parolsenella*, in the Crohn's Disease dataset.

Author Summary

Distance and dissimilarity measures are often used to investigate the structure of biological communities. However, this investigation demonstrates that these measures can fail to capture important relationships in microbial communities since they are unable to properly

capture the geometry of the input space. For example, both the Jaccard and Aitchison metrics are

unable to identify subsets of samples where the presence of one feature depends on another.

Previous research has found that Random Forest embeddings can be used to create an alternative

dissimilarity measure for dimensionality reduction in genomic datasets. We show that

dissimilarities learned by decision tree ensembles, especially those using base-estimators capable

of partitioning data using oblique and non-linear cuts, can be superior since these approaches

naturally model the geometry of the input space.

Introduction

The statistical analysis of the composition of ecological communities, beta-diversity, is

essential to determine their function within hosts and the broader environment. Central to the

analysis of beta diversity is the calculation of pairwise distances or dissimilarities between

samples. This calculation is carried out by carefully choosing and then applying a particular

dissimilarity that is known to measure an important characteristic of the data. For example, some

methods (such as correlation-based distance methods) perform well at measuring environmental

gradients while others, such as the Jaccard distance, can perform well when one is interested in

clustering data, assuming this is even possible (1–4). One particularly important drawback

inherent to many dissimilarity measures is their inability to discover important geometric

properties of the input space. A considerable amount of work has demonstrated that many

genomic, transcriptomic, and metagenomic datasets are better understood if the underlying

geometry of the input space is considered. This better understanding can be reached since these

datasets do not often meet the "Assumption of Linearity" used by methods such as Non-Negative

Matrix Factorization, Principal Components Analysis and its generalization, Principal

Coordinates Analysis (5–8). Finally, these methods rarely explore correlations and other

dependencies between taxa. These dependencies and correlations commonly occur within

communities and, when investigated, the investigations are often limited in scope and a result of

specific actions on the part of the researcher (9).

Investigating community composition, such as detecting differentially abundant taxa,

often involves the use of different tools. For example, one may use PerMANOVA to identify if

there are differences between groups while then using another tool, such as ANCOM or

MetagenomeSeq, to identify the operational taxonomic units (OTUs) or amplicon sequence

variants (ASVs) which differentiate groups (10–16). Each of these tools has different sets of

assumptions and the violation of these assumptions could render the results meaningless. For

example, if distributional assumptions are not met an analysis could suffer from higher false-

positive and false-negative rates (3). This can then lead to potentially erroneous or incomplete

interpretations. Furthermore, it is important to note that discovering which features can

distinguish between communities is inextricably linked to the measure we use to identify if a

statistically significant difference in community structure exists. Therefore, a unified approach

using a single model to quantify differences between communities and samples would be very

useful when investigating ecologically and medically important data.

Machine learning (ML) algorithms are being increasingly applied to a wide array of

genomic, metagenomic, and transcriptomic data sets and we believe that they can be used to

create a unified approach to study high-throughput sequencing data. The literature is rich in

examples where ML has been used to identify biomarkers and create predictive models of these

datasets. Unlike statistical models, ML models tend to be non-parametric (16,17). Furthermore,

due to the way ML models such as neural networks and Random Forests learn, they are capable

of identifying dependencies between covariates without the need for the user to explicitly include

these terms in the model (9,18–20). Also, many ML models, such as tree-based ensembles, are

not linearly constrained. For this reason they can potentially learn a better understanding of the

geometry of the input space and therefore generalize well to unseen data (5,20).

In this work we explore the ability of tree-based ensembles to investigate high-

throughput sequencing data. Specifically, we focus on one, and arguably underused, ability

inherent to this class of models: they can be used in an 'unsupervised' manner to learn the

pairwise dissimilarities between samples (18,21). By using these classifiers in this way, it may be

possible to simultaneously visualize the differences between communities while also identifying

the features (ASVs, OTUs, genera, etc) which contribute most to the placement of each

community within the ordination space (20,22). While this can be done using principal

components analysis and similar algorithms these approaches suffer from two important

limitations: transformation of new data often requires the original data (in the case of robust

principal components analysis) and the algorithms are linearly constrained (5,23). Decision trees

also have limitations that need to be considered. For example, the most popular methods

(Random Forests, Extra Trees) make axis-orthogonal cuts. While improvements, such as the

additional randomization, can help these models find better decision boundaries these

improvements are not a solution to this drawback (24–26). Recently, we have introduced a

decision-tree ensemble called LANDMark (Large Scale Non-Parametric Discovery of Markers –

available at https://github.com/jrudar/LANDMark) that has the ability to learn oblique or non-

linear splits (25). Recent and historical work demonstrates that these types of splits often result in

more appropriate representations of the data generating function (5,26). Like the Random

Forests, LANDMark recursively partitions samples until a stopping criterion is met. Unlike

Random Forests, LANDMark can use learned linear and non-linear models to partition samples.

In our previous work we show that this results in a better representation of the decision boundary

between different types of samples (25).

In this study, we investigate the quality of the dissimilarity measures learned by

LANDMark and a modification of the Random Forest algorithm known as Extra Trees. These

measures of dissimilarity will be compared with those calculated using commonly used

dissimilarity measures such as the Jaccard and Aitchison metrics. The ability of each method to

identify differences between communities and the concordance between projections will be

investigated using commonly used statistics, such as PerMANOVA and Procrustes analysis.

Furthermore, we will show how machine learning can be used to identify ASVs associated with

patterns in the distribution of samples by applying state-of-the-art introspection methods to each

unsupervised decision-tree ensemble. The code used to perform the analysis in this work can be

found at: https://github.com/jrudar/Unsupervised-Decision-Trees.

Methods

Creation of Positive and Negative Controls

Positive and negative controls were created using a copy of the code found at

https://github.com/cameronmartino/deicode-benchmarking/blob/master/simulations (23). This

code was used in the simulations which tested robust centered log-ratio transformation

introduced by Martino et al. (2019) (23). Briefly, a synthetic dataset containing 200 samples and

1000 features was according to the procedure found in Martino et al. (2019). This was a positive

control. A copy of this dataset was made, and each feature column was independently permuted

to create the negative control. Both datasets were then analyzed using the methods described

below.

Dataset Selection

Two human microbiome datasets were selected for use as case studies in this work. The

first dataset was derived from the colons of healthy individuals (27) using 16S rRNA amplicon

sequencing. This dataset collected samples from the unprepared colons of healthy individuals

(27). In the original work, the authors examined differences in the abundance of OTUs between

the microbial communities of the proximal lumen (PL) and mucosa (PM), the distal lumen (DL)

and mucosa (DM), between the PL and the DL, and finally between the PM and the DM. The

second dataset was chosen since it contains samples from patients who suffer from immune-

mediated inflammatory diseases (IMID) (28). Differences between the microbiomes of patients

suffering from Crohn's disease (CD), ulcerative colitis (UC), multiple sclerosis (MS), and

rheumatoid arthritis (RA) were compared to healthy controls. Specifically, the work by Forbes et

al. (2018) investigated if disease-specific taxonomic biomarkers could be identified in each

patient's stool. In both studies, the authors used Random Forests to identify potential biomarkers

and the results of this work can be compared to the potential biomarkers identified by the

workflow presented here (21,28). Since the proximal region of the human colon and Crohn's

Disease represents two well-investigated research areas, these subsets from the datasets

described above were included as case studies in our work. Should our workflow be successful,

it should (at the very least) be able to replicate the findings described in Flynn et al. (2018) and

Forbes et al. (2018) while also supporting the wider body of work upon which these studies

draw.

Bioinformatic Processing of Reads

Raw sequences from two previously published datasets were obtained from the Sequence

Read Archive (PRJNA450340 and PRJNA418115) (27,28). All bioinformatic processing of the

raw reads was prepared using the MetaWorks v1.8.0 pipeline (available online at:

https://githib.com/terrimporter/MetaWorks) (29). The default settings for merging reads were

used except for the parameter controlling the minimum fraction of matching bases, which was

increased from 0.90 to 0.95. This was done to remove a larger fraction of potentially erroneous

reads. Merged reads were then trimmed using the default settings MetaWorks passes to

CutAdapt. Since reads from PRJNA418115 were pre-processed and the primers removed

(Personal Communication with Kaitlin Flynn, Ph.D. (kjflynn06@gmail.com) in January 2019),

no reads were discarded during trimming. The remaining quality-controlled sequences were then

de-replicated and denoised using VSEARCH 2.15.2 to remove putative chimeric sequences (30).

Finally, VSEARCH was used to construct a matrix where each row is a sample and each column

an Amplicon Sequence Variant (ASV). Taxonomic assignment was conducted using the RDP

Classifier (version 2.13) and the built-in reference set (31).

ASVs which are likely to be contaminants, specifically those likely belonging to

chloroplasts and mitochondria, were removed. From the remaining sequences, only those

belonging to the domain *Bacteria* and *Archaea* were retained for further analysis. In the IMID

dataset, only sequences assigned to *Firmicutes*, *Actinobacteria*, and *Tenericutes* were retained.

This was done since the original study found that OTUs assigned to other bacterial groups were

underrepresented (28). A site by ASV count matrix, where each row is a sample and each

column an ASV, was created for each subset of data under investigation. The count matrix was

filtered to remove ASVs found in two or fewer samples. This filtration step was taken since

reducing the size of the feature space can often lead to a more generalizable model (14,32,33).

Data Transformations

The filtered matrix must be transformed in such a way as to minimize the impact of

various technical factors, such as differences in library size (10). Our analyses examined three

transformations of the filtered matrix: the presence-absence transformation of rarefied samples,

the centered-log ratio (CLR) transformation, and the robust centered-log ratio (rCLR)

transformation (14,23,34). The presence-absence transformation was chosen since it reflects if

ASVs are simply present or absent. By using this approach, the differences in counts are ignored

while the impact of some effects, such as large differences in library size, can be somewhat

minimized by first creating a rarefied dataset before applying the transformation (3,23). To

prepare the rarefied libraries, we first calculated the sum of all counts in each sample and then

calculated the 15$^{\text{th}}$ percentile of these sums. The probability of each ASV occurring in each

sample was also calculated. ASVs were then sampled with replacement using the calculated

probabilities until the specified library size was reached (3). Libraries smaller than the 15$^{\text{th}}$

percentile than this were removed from the analysis (35).

Normalizing library sizes by rarefying and the presence-absence transformation can be

problematic since they throw away useful data due to the normalization of library sizes and, in

the case of presence-absence, ignoring differences in the abundance of reads (14). Since the

absolute size of each library is often irrelevant, a compositional approach is needed to analyze

the data (14,36). The CLR and rCLR transformations were used to account for the compositional

nature of these datasets. Filtered datasets were CLR transformed using the Scikit-Bio package

(version 0.5.7) (37). The closure operation was applied to each sample and zero-counts were

replaced using the multiplicative replacement procedure (13,38). Finally, the CLR

transformation was applied according to equation 1 where X_i is the i^{th} sample in X, $x_{D,i}$ is the D^{th}

feature in X_i, and $g(X_i)$ is the geometric mean of all the taxa in sample X_i. The rCLR

transformation, which is implemented in the DEICODE package, is similar to the CLR transform

and was developed to account for the sparse nature of microbiome data (23). Unlike the CLR

transformation, however, the rCLR is calculated using only the non-zero data from each sample.

Furthermore, for DEICODE to calculate the reconstructed matrix it must use all of the data

points. This procedure is not capable of identifying a rule which can be used to transform a new

set of data into the reduced space (23). In these experiments, DEICODE (version 0.2.4) was used

to generate two RPCA components using 1000 iterations of the matrix completion algorithm.

The U, V, and S matrices were extracted and used to reconstruct the rCLR transformed samples

(equation 2) (23). The U and V matrices contain sample and feature loading information for each

component while S is analogous to the matrix of eigenvalues used by singular-value

decomposition. This work was carried out in a Python 3.10 environment.

$$CLR(X_i) = \left[\log \frac{x_{1,i}}{g(X_i)}, \dots, \log \frac{x_{D,i}}{g(X_i)}\right] \ (1)$$

$$rCLR(X) = USV^T \ (2)$$

Calculation of Dissimilarities

The Jaccard distance and Aitchison distances are used since these metrics can be used

with compositional data (Equations 3 and 4). These metrics were used to calculate pairwise

dissimilarities for presence-absence and (r)CLR data, respectively. In these equations X_i and X_j

represent the i^{th} and j^{th} samples in X. $x_{k,i}$ and $x_{k,j}$ represent the k^{th} feature in samples x_i and x_j.

Distances were calculated using the 'pairwise_distances' function from Scikit-Learn (version

1.0.2) (39).

$$Jaccard\ Distance\ (X_i, X_j) = \frac{X_i \cap X_j}{X_i \cup X_j} \ (3)$$

$$Aitchison\ Distance\ (X_i, X_j) = \sqrt{\sum_{i=1}^{D} \Big(CLR(X_i) - CLR(X_j)\Big)^2}\ (4)$$

219   Tree-based models, using algorithms such as Extra Trees, have also been found to be an

220   effective means of capturing the dissimilarity between samples. To calculate the dissimilarities

221   using Extra Trees, one must first construct a similarity matrix, S. This matrix is constructed by

222   simply counting how often each pair of samples co-occur in the terminal leaves of each decision

223   tree across the forest (Equation 5).

$$Tree\ Similarity\ \Big(X_i, X_j\Big) = \frac{\overline{X_i}\,\overline{X_j}^T}{N}\ \ \ \ (5)$$

224   In this equation X_i and X_j are the i^{th} and j^{th} samples of X while $\overline{X_i}$ and $\overline{X_j}$ are one-hot encoded

225   representations of the terminal leaves into which X_i and X_j fall. N is the number of trees in the

226   forest. The pairwise similarity matrix is then converted into a dissimilarity matrix, D, using

227   equation 6 (22). This dissimilarity measure can then be used to investigate community

228   differences (22,40,41).

$$Tree\ Dissimilarity = \sqrt{1 - S}\ \ \ \ (6)$$

Unfortunately, for Extra Trees to generate a consistent set of one-hot encodings (for use

in equation 5), this method of calculating dissimilarities requires that the original dataset is

loaded whenever using the model for new data. While this can be addressed, developing a

workaround is outside of the scope of this work and will, likely, not be done by most users who

adopt this procedure. When developing LANDMark, this problem was addressed by returning

the entire set of nodes for each tree in the forest (25). Therefore, the one-hot encodings produced

by LANDMark can be used directly. This can be particularly useful since it allows LANDMark

to be used as a secondary transformation. Specifically, the dimensionality reduction is done

using the one-hot encodings instead of the dissimilarity matrix. In these experiments, we used

LANDMark version 1.1.4 and the implementation of the Extra Trees classifier found in Scikit-

Learn version. 128 trees were used to train each Extra Trees classifier. LANDMark was run at its

default settings except for the number of trees, which was set to 80, and the 'use_nnet'

parameter, which was set to 'False' to reduce training time. All tests were run on a computer

using an Intel Core i5-10400F CPU with 32 GB of RAM. This work was carried out in a Python

3.10 environment.

Regardless of which procedure is used, a second randomized dataset, X_R, is needed if one

is to use decision trees to calculate unsupervised dissimilarities. To create randomized datasets,

counts within each ASV are randomly sampled without replacement, thereby breaking the

correlation structure between ASVs without affecting count distributions (42,43). The original

and randomized samples are then combined. To prevent the supervised-learning model from

using information about the original class labels, the permuted dataset is assigned a label of

"Random" while original samples are assigned a label of "Original". The combined dataset is

then transformed using the rCLR, CLR, and presence-absence transformations. Twenty different

randomized datasets were created. The dissimilarities or one-hot encodings between pairs of real

samples from each dataset were then used for dimensionality reduction.

Dimensionality Reduction Using PCoA, RPCA, and UMAP

All samples were used to generate the initial ordinations. Principal Coordinates Analysis

(PCoA) was used to project presence-absence transformed data into a two-dimensional space.

This was done using the Scikit-Bio and Scikit-Learn packages (37,39). This procedure was also

used to transform the dissimilarities learned by the Extra Trees classifier and the one-hot

encodings learned using LANDMark. The Jaccard distance was used to calculate the distances

between pairs of LANDMark encodings. PCoA, using Euclidean distances, and Robust PCA

(RPCA), using DEICODE, were similarly used to project the CLR and rCLR transformed data,

respectively (13,23,37). Uniform Manifold Approximation and Projection (UMAP) was also

used to create projections. UMAP was chosen since it, like PCoA, can be used with any

dissimilarity matrix. Also, UMAP is not linearly constrained and can be used to transform new

data into the projected space. The latter is important since this is not possible when using PCoA

with non-Euclidean distances or RPCA. UMAP works by creating a non-linear projection. This

is accomplished by first constructing a non-linear graph of the input data and then finding an

embedding of this graph by minimizing the difference in the probability distribution between

neighboring points in the projection and original space via gradient descent (44). Projections

created using UMAP have been shown to generate better visualizations of complex data, such as

microbiome data (8,44). In these experiments, the Euclidean distance was used as the 'metric'

parameter for UMAP (version 0.5.3) when projecting with CLR and rCLR transformed data.

When projecting dissimilarities learned by Extra Trees and LANDMark, this parameter was set

to 'precomputed' and 'jaccard', respectively. Since the datasets are small, the 'n_neighbors'

parameter was set to 8. Finally, the 'min_dist' parameter was set to 0.001 to encourage the

formation of small clusters.

Statistical Assessment of Each Ordination

Each dissimilarity matrix was used as input for PerMANOVA (11). The p-value was

calculated using 999 replications. This analysis was completed using the 'permanova' function

from the Scikit-Bio package (37). The 'seaborn' and 'matplotlib' packages were used to plot the

PCoA, RPCA, and UMAP projections (45,46). A Python implementation of the PROTEST

procedure for a Procrustes analysis was used to assess the concordance between pairs of

projections (PCoA-PCoA, PCoA-UMAP, etc) (47). This procedure permutes the rows of one

projection and computes the probability of rejecting the null hypothesis (concordance between

datasets) using equation 7. In this equation m_{perm} represents the permuted test statistic and k is the

number of permutations (999 in this experiment). A 1 is added in the numerator and denominator

and this represents that fact that the observed statistic, m_{obs}, is a valid permutation and therefore

must be considered. For a Procrustes test, the test statistic is the sum of the squared residual

deviations between projections.

$$p - value = \frac{\sum_{i=1}^{k} 1(m_{perm,i} \leq m_{obs)}) + 1}{k + 1} \quad (7)$$

TreeOrdination: Automating the Identification of Informative ASVs When Using Tree

Dissimilarities

It can be challenging to identify which ASVs are responsible for differentiating

communities based on projections of the sample by ASV matrix. Machine learning represents a

unique direction through which this problem can be addressed since decision tree ensembles can

be used to efficiently capture important information about the geometric structure of the data

(20,25,26). To demonstrate how these approaches can be used we have developed a workflow,

TreeOrdination, which uses a relatively simple set of steps to create and analyze projections of

high-dimensional amplicon sequencing data. The TreeOrdination source code and documentation

are available at https://github.com/jrudar/TreeOrdination.

TreeOrdinatoin begins by creating N bootstrapped datasets. This parameter can be

configured by the user and is set to 20 by default. A randomized dataset, X_R, is then constructed

as described above. The original and randomized datasets are combined and used to train a

LANDMark classifier consisting of 80 decision trees (25). The neural network functionality of

the classifier is disabled in the default implementation to reduce training time. This classifier is

only used to distinguish the real data from its randomized counterpart. Upon completion of

training, the original training data is passed through the classifier to create an embedding that

describes the terminal leaves into which each sample falls. Twenty embeddings are created and

concatenated together. These are then used to train an Extra Trees classifier to predict the

original class labels. In addition to this, the embeddings are transformed into a smaller 15-

dimensional UMAP projection (44). To create this projection the 'min_dist' parameter is set to

0.001, while the 'neighbors' and 'metric' parameters are set to 8 and "jaccard", respectively.

Scikit-Learn's 'PCA' functionality is then used to construct a two-dimensional PCA projection

of this space (39). The original data is then used to train an Extra Trees regression model to

predict the location of each sample in the projected space. Features important for predicting the

location of samples in this space are then identified using SAGE and Shapley values (48–50).

These are calculated using the 'sage' (version 0.0.4) and 'shap' (version 0.41.0) packages.

Assessment of Generalization Performance

Presence-absence, center-log ratio, and robust center-log ratio transformed data were

projected using TreeOrdination. To compare if the generalization performance differed between

projections, each dataset was also projected into a two-dimensional space using PCoA (from

Scikit-Bio) or DEICODE's RPCA function in the case of rCLR transformed data (23). The

projected and original samples were then used to train Extra Trees, K-nearest neighbor, and

LANDMark classifiers (24,25,39). Before training, samples were split into training and testing

sets using five-fold cross-validation with two repeats. The generalization performance of each

model was then calculated using the test set (39). To test if generalization performance differed

between models and transforms, a Bayesian analysis, using Nadeau and Bengio's corrected t-test

implemented in the Python 'baycomp' package (version 1.0.2), was used (51). The region of

practical equivalence (ROPE), which represents the probability of two models having equivalent

performance, was defined as a difference in score within ±0.05. Although the choice for the size

of this region is arbitrary, this size was chosen since it represents the impact of roughly two

classification errors. Visualizations of the projected spaces were created using 'matplotlib'

(version 3.5.2) and 'seaborn' (version 0.11.2) in Python 3.10. Finally, we performed a literature

search of the best five ASVs identified using TreeOrdination to check if these ASVs are

associated with the sampling locations and diseases of interest.

Results

TreeOrdination Projections Result in Well Separated Groups in Simulated Data

In the simulated tests, the analysis using the negative controls confirmed that randomized

data will usually result in PerMANOVA F-statistics that are not significant regardless of

transformation. However, significant differences between groups was detected in several PCoA

projections of CLR transformed data (Figure S1). Upon further examination using cross-

validated balanced accuracy scores, the results demonstrated that the generalization performance

of supervised models trained on various splits of the negative control data was consistent with

the performance of random models (Table 1, Supplementary File 2). Substantial differences

between groups could be detected when positive controls were used to create TreeOrdination,

PCoA, or RPCA projections (Figure S2, Table 1, Supplementary File 2). For example, the range

in the F-statistics associated with the CLR transformed data, TreeOrdination projections of the

CLR transformed data, and PCoA projections of the CLR transformed data was 38.56 ± 0.94,

20512.55 ± 7364.14, and 749.32 ± 36.66, respectively. Pairwise Bayesian t-tests suggested that

these differences were not due to chance and the probability of TreeOrdination producing F-

statistics greater than those produced using PCoA projected transformed data is approximately

100%. This was also the case when using the presence-absence and rCLR transformed data (See

Supplementary File 2). On simulated data, at least, these results support our hypothesis that

learned dissimilarities and non-linear projections should be used to investigate beta diversity.

Table 1: Cross-validated generalization performance of each classification model when trained
using positive and negative control data. The average score and standard deviation of the average
score is reported.

Control	Classification Model	Centered Log-Ratio	Presence-Absence	Robust Centered Log-Ratio
Positive	3-KNN (PCoA/RPCA)	1	1	1
	3-KNN (Transformed Only)	0.98 ± 0.01	0.96 ± 0.04	1
	5-KNN (PCoA/RPCA)	1	1	1
	5-KNN (Transformed Only)	0.98 ± 0.01	0.98 ± 0.02	1
	Extra Trees (PCoA/RPCA)	1	1	1
	Extra Trees (Transformed Only)	0.98 ± 0.02	0.98 ± 0.02	1
	LANDMark (PCoA/RPCA)	1	1	1
	LANDMark (Transformed Only)	0.99 ± 0.02	0.99 ± 0.01	1
	Random (PCoA/RPCA)	0.49 ± 0.09	0.49 ± 0.09	0.505 ± 0.08
	Random (Transformed Only)	0.54 ± 0.08	0.50 ± 0.08	0.535 ± 0.10
	3-KNN (TreeOrdination)	1	1	1
	5-KNN (TreeOrdination)	1	1	1
	Extra Trees (TreeOrdination)	1	1	1
	LANDMark (TreeOrdination)	1	1	1
	Random (TreeOrdination)	0.53 ± 0.07	0.48 ± 0.09	0.53 ± 0.08
Negative	3-KNN (PCoA/RPCA)	0.55 ± 0.07	0.55 ± 0.07	0.49 ± 0.06
	3-KNN (Transformed Only)	0.50 ± 0.07	0.50 ± 0.09	0.49 ± 0.06
	5-KNN (PCoA/RPCA)	0.55 ± 0.08	0.55 ± 0.08	0.45 ± 0.06
	5-KNN (Transformed Only)	0.48 ± 0.07	0.48 ± 0.09	0.45 ± 0.06
	Extra Trees (PCoA/RPCA)	0.52 ± 0.08	0.47 ± 0.09	0.48 ± 0.08
	Extra Trees (Transformed Only)	0.51 ± 0.08	0.53 ± 0.06	0.47 ± 0.05
	LANDMark (PCoA/RPCA)	0.48 ± 0.06	0.50 ± 0.09	0.51 ± 0.05
	LANDMark (Transformed Only)	0.53 ± 0.08	0.55 ± 0.07	0.50 ± 0.04
	Random (PCoA/RPCA)	0.48 ± 0.07	0.54 ± 0.08	0.47 ± 0.08
	Random (Transformed Only)	0.53 ± 0.08	0.50 ± 0.07	0.51 ± 0.11
	3-KNN (TreeOrdination)	0.49 ± 0.09	0.53 ± 0.08	0.51 ± 0.07
	5-KNN (TreeOrdination)	0.47 ± 0.08	0.51 ± 0.05	0.49 ± 0.08

	Extra Trees (TreeOrdination)	0.53 ± 0.07	0.52 ± 0.09	0.49 ± 0.06
	LANDMark (TreeOrdination)	0.49 ± 0.05	0.49 ±0. 12	0.46 ± 0.09
	Random (TreeOrdination)	0.53 ± 0.06	0.49 ± 0.11	0.53 ± 0.08

All Methods Produce Projections That Will Result in Similar Interpretations

When using CLR and rCLR transformed data, a PROTEST analysis from each case study

implied that the configuration of samples within each of the projected spaces is similar (Figures

1A and 2A). A small amount of disparity was detected between the projections of rCLR

transformed data which likely arises due to the concatenation of randomized data to the original

samples. However, this did not appear to strongly impact the overall configuration of the

projections since we were able to reject the null hypothesis (permuted projections are more

concordant than the observed Procrustes statistic). The p-values calculated after permutation

PROTEST were below the 0.05 threshold. Due to the randomization in the selection of samples

and/or features during training, there is a greater disparity between the projections of tree-based

dissimilarities. Projections of LANDMark dissimilarities were usually consistent, except for a

small fraction of projections created using UMAP. The extra variability impacted UMAP

projections of Extra Trees dissimilarities the most and we were unable to reject the null

hypothesis for a large fraction of these projections. However, this is not completely surprising

given the tendency of this algorithm to produce different projections when given the same set of

data (52). Also, concordance between the different pairs of projections does not imply that these

projections are informative.

375
Fig 1: PROTEST and PerMANOVA results for the proximal colon case study. The
PROTEST statistic uses the Procrustes test to measure the concordance between two multivariate
datasets. One dataset is then permuted many times and the permuted statistic is calculated. The
null hypothesis (no concordance between projections) can be rejected if the p-value after

permutation is less than 0.05. The PerMANOVA F-statistic is the ratio of between groups
separation to within group separation. A higher F-statistic suggests greater separation between
groups. Boxen plots are used to visualize the distribution of test statistics between each pair of
projection methods (20 different projections per method). The results for the proximal colon are
reported. In panel (A) we show the distribution of the PROTEST statistic on the top and the
distribution of the p-values associated with this statistic on the bottom while panel (B) reports the
distribution of the F-statistic on the top and the p-values associated with this statistic on the
bottom.
388
Fig 2: PROTEST and PerMANOVA results for the proximal Crohn's Disease case study.
The PROTEST statistic uses the Procrustes test to measure the concordance between two
multivariate datasets. One dataset is then permuted many times and the permuted statistic is
calculated. The null hypothesis (no concordance between projections) can be rejected if the p-
value after permutation is less than 0.05. The PerMANOVA F-statistic is the ratio of between
groups separation to within group separation. A higher F-statistic suggests greater separation
between groups. Boxen plots are used to visualize the distribution of test statistics between each
pair of projection methods (20 different projections per method). The results for the proximal
colon are reported. In panel (A) we show the distribution of the PROTEST statistic on the top
and the distribution of the p-values associated with this statistic on the bottom while panel (B)
reports the distribution of the F-statistic on the top and the p-values associated with this statistic
on the bottom.
401
402

To answer this question, it was important to consider the separation between different

groups within each projection using PerMANOVA (Figures 1B and 2B). Generally, when the

CLR and rCLR transformation were applied to each dataset, statistically significant differences

between groups could be detected regardless of the projection method. In a small number of

instances, we were not able to reject PerMANOVA's null hypothesis and this only occurred

when using the UMAP projection on rCLR transformed data (Figure 2B). In the proximal colon

case study, when using tree-based dissimilarities alongside the presence-absence transformation

we were unable to detect differences between groups. Although this also occurred in the Crohn's

disease case study, this problem was usually restricted to projections created using UMAP.

Using UMAP to project the CLR, rCLR resulted in an increase in the magnitude of the F-statistic

in both case studies (Figures 1B and 2B). For example, the F-Statistic for the PCoA projection of

CLR transformed CD-HC samples was observed to be 23.68 ($p \le 0.001$) while a UMAP

projection of the same data resulted in an F-Statistic of 36.58 ± 3.36 with p-values ranging

between 0.001 and 0.007. However, increases in the magnitude of the F-statistic after using

UMAP to transform learned dissimilarities of presence-absence transformed data were

inconsistent. Finally, the F-statistics calculated using projections of tree-based dissimilarities

were competitive with those produced using projections of the transformed data. Bayesian t-tests

comparing the differences in the distribution of the F-statistic suggested that these observations

are not due to chance (Tables S1-S6). While our results are encouraging, they should be

interpreted conservatively since we only used two case-studies

The Choice of Classification Model Can Result in Significant Differences in Generalization

Performance

While concordance between projections and statistics which measure the separation

between groups of samples is important, one must also consider how well each transformation

and projection method can model the data. This is an important consideration since it may be

possible to extract useful information about which ASVs are responsible for correctly predicting

the class label of unseen data and the location of this data in the projected space. Unfortunately,

applying the rCLR and/or RPCA or using PCoA with non-Euclidean distances cannot transform

new data into the projected space. The only way that this could occur is if the samples used to

create the initial projection are combined with the testing samples. Therefore, it is likely the

results for rCLR transformed data could be slightly optimistic since some data leakage occurs.

TreeOrdination is more flexible since it can work with any type of transformed data.

In this work, we trained supervised models on each set of transformations and measured

the generalization performance of the trained models using the balanced accuracy score. We

found that this score differed considerably depending on the classifier and transformation (Figure

3). To start, we can confidently claim that all classifiers (regardless of transformation and

projection methods applied) performed better than random. When compared to training

supervised models on projected or full data, we observed that applying a secondary

transformation using TreeOrdination resulted in highly competitive balanced accuracy scores

(Figure 3) and that this is unlikely to be due to chance. For example, in the PL-PM dataset, the

generalization performance of the CLR-TreeOrdination transformation was always more likely

to generate a better model than the CLR transformation alone (Table 2). In the Crohn's Disease

dataset, the CLR-TreeOrdination approach was also favored although the likelihood of

approaches being equivalent was greater (Table 3). In addition, applying the presence-absence

transformation to the Crohn's Disease data resulted in the best generalization performance

(Figure 3. A full report of the results can be found in Tables S7-S12. Finally, the first two axes of

the projections created using TreeOrdination accounted for nearly all the multivariate variability

in each dataset and these projections and TreeOrdination projections tended to result in

projections with the largest PerMANOVA F-statistics (Figures 4 and 5). This figure also shows

that representations learned by TreeOrdination are capable of transforming unseen samples and

placing them near or into regions corresponding to the condition of interest. TreeOrdiantion is

one of the few approaches capable of taking in any type of transformed dataset and learning a

mapping that can then be applied to unseen data.

Table 2: Bayesian t-test results using balanced accuracy scores of centered log-ratio transformed
proximal colon data. The best result is highlighted in bold.

Comparison A	Comparison B	Mean A ± Std Deviation	Mean B ± Std Deviation	P(A > B)	P(A = B)	P(A < B)
TreeOrdination (Default)	LANDMark (Raw)	0.864 ± 0.092	0.811 ± 0.082	**0.520**	0.442	0.038
	LANDMark (Projection)		0.817 ± 0.163	**0.491**	0.304	0.206
	3-KNN (Raw)		0.756 ± 0.067	**0.849**	0.145	0.006

				0.532	0.398	0.070
	Extra Trees (Raw)		0.808 ± 0.109	**0.532**	0.398	0.070
	TreeOrdination (5-KNN)		0.878 ± 0.099	0.054	**0.771**	0.174
	Extra Trees (Projection)		0.758 ± 0.108	**0.815**	0.175	0.011
	5-KNN (Raw)		0.758 ± 0.093	**0.761**	0.209	0.030
	TreeOrdination (3-KNN)		0.856 ± 0.093	0.207	**0.664**	0.129
	5-KNN (Projection)		0.739 ± 0.081	**0.902**	0.095	0.003
	3-KNN (Projection)		0.758 ± 0.081	**0.840**	0.154	0.006
	TreeOrdination (LANDMark)		0.831 ± 0.094	0.348	**0.619**	0.033

459 Table 3: Bayesian t-test results using balanced accuracy scores of centered log-ratio transformed
460 Crohn's Disease data. The best result is highlighted in bold.

Comparison A	Comparison B	Mean A ± Std Deviation	Mean B ± Std Deviation	P(A > B)	P(A = B)	P(A < B)
TreeOrdination (Default)	LANDMark (Raw)	0.856 ± 0.120	0.863 ± 0.130	0.101	**0.733**	0.166
	LANDMark (Projection)		0.847 ± 0.109	0.047	**0.941**	0.011
	3-KNN (Raw)		0.822 ± 0.137	0.376	**0.574**	0.051
	Extra Trees (Raw)		0.838 ± 0.099	0.339	**0.467**	0.194
	TreeOrdination (5-KNN)		0.878 ± 0.130	0.023	**0.770**	0.207
	Extra Trees (Projection)		0.817 ± 0.114	0.400	**0.579**	0.022
	5-KNN (Raw)		0.823 ± 0.140	0.381	**0.538**	0.081
	TreeOrdination (3-KNN)		0.856 ± 0.120	0	**1**	0
	5-KNN (Projection)		0.856 ± 0.120	0	**1**	0
	3-KNN (Projection)		0.81 ± 0.131	0.462	**0.522**	0.016
	TreeOrdination (LANDMark)		0.856 ± 0.120	0	**1**	0

462 **Fig 3: Distribution of Balanced Accuracy Scores for each type of transformation and model**
463 The distribution of balanced accuracy scores changes depending on the type of transformation
464 and model in the (A) proximal colon and (B) Crohn's Disease datasets.
465

Fig 4: Comparison of each projection method. Data from the proximal colon is found along
the top row while Crohn's disease data is found along the bottom row. (A) Presence-Absence
transformation. (B) Robust Centered Log-Ratio transformation. (C) TreeOrdination
transformation, (D) Centered Log-Ratio transformation. (E) Presence-Absence transformation.
(F) Robust Centered Log-Ratio transformation. (G) TreeOrdination transformation, (H)
Centered Log-Ratio transformation.
473

474 **Fig 5: Distribution of the PerMANOVA F-Statistic when using TreeOrdination, PCoA**
475 **projection, and no projection.** The distribution of the PerMANOVA F-Statistic under each
476 condition when using data from the (A) proximal colon and (B) Crohn's Disease datasets.
477

ASVs Predicted to Have a High Impact on Model Performance is Consistent with Previously

Reported Results

Similar to the RPCA (or PCA in the case of CLR transformed data), TreeOrdination can

identify which features were used by the model to generate the ordination. Unfortunately, the

calculation of SAGE values using the full implementation of TreeOrdination is very expensive.

To address this issue, we employed an approximation that uses the original transformed data to

train an Extra Trees regression model to predict the location of each sample in the projected

space created using the UMAP/PCA transformations. By taking this approach, it becomes

feasible to calculate SAGE scores. These scores quantify how important each ASV is to the

model (Figures 6A and 7A). Test samples projected using the approximation roughly appear near

other samples of the same class (Figure 6B and Figure 7B). However, the configuration of test

points in the approximate projection does not fully mirror that which is produced using the full

TreeOrdination pipeline. To test if there is a significant difference in configurations between the

full and approximate projections, we conducted a PROTEST analysis. PROTEST results

suggested that the evidence for the alternative hypothesis (no difference between configurations)

exists for both case studies (Crohn's Disease: $m_{obs} = 0.02$, $p \leq 0.001$; Proximal Colon: $m_{obs} =$

0.10, p ≤ 0.001). Since both projections can be interpreted similarly, it is logical to ask which

factors impact the location of each sample in the projected space. Shapley scores represent a

powerful way to do this and were used in this work to identify these ASVs (Figure 6CD and

7CD).

498
Fig 6: Global and local feature importance scores for the proximal lumen dataset. (A)
Global feature importance scores calculated using SAGE. More important features will have a
higher SAGE value. (B) Configuration of the actual (left) and approximate (right) projections the
projection produced using TreeOrdination. Using the final TreeOrdination projection, an Extra
Trees Regressor was trained to predict the location of samples in the projected space given the
original centered log-ratio transformed training data. (C) A waterfall plot illustrating which
ASVs impact the projected location of an individual mucosal sample along the x-axis of
approximate projection in panel (B). ASVs with positive Shapley scores push the model towards
the positive part of the axis while those with negative Shapley scores push the model towards the
negative part of the axis. (D) Same as panel (C), only this time the sample is from the lumen.
509
Fig 7: Global and local feature importance scores for the Crohn's Disease dataset. (A)
Global feature importance scores calculated using SAGE. More important features will have a
higher SAGE value. (B) Configuration of the actual (left) and approximate (right) projections the
projection produced using TreeOrdination. Using the final TreeOrdination projection, an Extra
Trees Regressor was trained to predict the location of samples in the projected space given the
original centered log-ratio transformed training data. (C) A waterfall plot illustrating which
ASVs impact the projected location of an individual Crohn's Disease sample along the x-axis of
approximate projection in panel (B). ASVs with positive Shapley scores push the model towards
the positive part of the axis while those with negative Shapley scores push the model towards the
negative part of the axis. (D) Same as panel (C), only this time the sample is from a healthy
control.
521

For the microbial community of the distal human colon, TreeOrdination suggested that

several bacteria could be used to predict the location of proximal mucosal and luminal samples

in the projected space (Figure 6A). While not an exhaustive list, our approach suggested that

Ihubacter, *Lachnospiracea*, *Firmicutes*, and *Lactobacillus* are necessary to place these samples.

To understand the samples in each case study in better detail, it was important to quantify how

ASVs impact the location of individual samples (Figures 6CD and 7CD). We found that the

presence of an unclassified ASV (ASV 1141), strongly determines the location of samples across

the first principal axis. Furthermore, other ASVs belonging to the *Eubacteriaceae*,

Lachnospiracea, and *Clostridiales* all strongly impact the ability of the model to place samples.

Finally, we observed that the combined contribution of the other features helped impact the

overall prediction (Figures 6 C and D). For example, in the approximate projection learned by

the Extra Trees model, the model predicted that a mucosal sample should have a value of 0.902

along the PC1. Without any consideration of the contribution of the other 1421 features, the 10

features with the highest magnitude Shapley values would place this sample closer to luminal

samples (Figure 6C). These results demonstrate that the importance of an individual ASV should

not be investigated in isolation, but its role needs to be considered in a broader context. We also

identified several ASVs which are important for distinguishing between CD and HC samples.

Parolsenella, *Ruminococcaceae*, *Corynebacterium*, *Clostridiales*, *Coprococcus,*

Catenibacterium, and *Blautia* were among the top ASVs which can be used to predict the

location of each sample in the projected space (Figure 7A, C, and D). Interestingly, *Parolsenella*

was not identified by Forbes et al. (2018) as an important indicator of Crohn's Disease. Since

then, evidence has been found to suggest that it may have a role in the development of MS,

which is itself a class of IMID (53). Of the other bacteria identified by TreeOrdination,

Ruminococcaceae, *Corynebacterium, Clostridiales, Coprococcus, Catenibacterium,* and *Blautia*

have known associations with Crohn's Disease and/or other human (immune-mediated)

inflammatory diseases (53–57).

Discussion

The datasets investigated here were chosen since the human gut microbiome is an

important area of medical research and is becoming increasingly linked to important disease

phenotypes. The choice of transformation and dissimilarity measure is an important

consideration when investigating microbiome data. It has long been known that these choices can

influence our measurement and interpretation of the main gradients influencing the structure of

communities and taxonomic similarity between pairs of samples (3,10,14,58–60). To combat

these problems a multitude of transformations, dissimilarity measures, and ordination approaches

have been developed or proposed. Each combination of these approaches has its strengths and

can be used to summarize and investigate different aspects of community composition (3,59,61).

For example, some dissimilarity measures, such as Jaccard and Canberra, perform well for

detecting clusters and others are more applicable to detecting ecological gradients (4). While the

application of these transformations and/or using specific dissimilarities can help bring clarity to

the analysis, a review of the literature suggests there is no consensus on which approach is best

(3,14,59,61). Likely, the best combination of approaches will be dataset-dependent.

Recent innovations and developments in the field of machine learning have resulted in a

rapid increase in the number of studies employing these approaches. In the context of this work,

approaches which use tree-based dissimilarities to identify the pairwise relationships between

samples are very interesting since these dissimilarities are learned (20–22,25,26). Since decision-

tree models are not linearly constrained, these models could arrive at a better representation of

the underlying geometry of the samples (5,20,25,42). Our work supports this hypothesis due to

the improvements we observed in the F-statistics and overall configuration of samples in the

projected spaces when using non-linear transformations. Using the workflow developed here,

TreeOrdination, we show that complex machine learning models can be used to generate good

projections and identify important features which were used to create these projections. In

addition, the predictive models learned using TreeOrdination transformed data can learn an

internal representation that generalizes well to unseen data. This is an important capability as

RPCA and PCoA (with non-Euclidean distances) cannot be used to project unseen data into a

lower dimensional space (23). Our results support the growing body of work that demonstrates

that tree-based dissimilarities are useful for capturing and visualizing relationships between

samples and that biological datasets tend to lie on a non-linear manifold (7,8). For example, the

first two principal axes in each case study's TreeOrdination projection accounted for nearly all

the variance in each dataset and the placement of samples along this axis was usually associated

with sampling location or disease state. At first glance, it appears as though this is true for the

other projections (Figure 4). However, in each case study the first two principal axes of each

PCoA projection accounted for a small fraction of the total variance, suggesting that these

projections do not adequately explain the data. Also, while the first two principal axes of each

RPCA explained 100% of the variation within each dataset, the configuration of samples within

RPCA projections was more ambiguous than those produced using TreeOrdiantion projections.

In particular, there appeared to be more overlap between samples from each class.

We conjecture that the linearly constrained methods, such as PCoA, cannot account for the

complex geometry of the input space since these methods usually result in projections with low

amounts of explained variation along each principal axis and are associated with smaller lower

PerMANOVA F-Statistics. Indeed, it is trivial to show that PCoA is incapable of generating

good projections of highly non-linear toy data. When moving beyond toy data, there exists a

considerable amount of work advocating for the adoption of newer graph-based methods for the

analysis of biological data. For example, Elhaik (2022) demonstrates that the validity of the

results produced from one commonly used linear dimensionality reduction algorithm, PCA, can

be easily called into question due to artifacts within the data and the ease by which it can be

manipulated to produce favorable results (6). In addition, there is an ongoing debate around how

useful a projection is when the amount of explained variance for the first few axes is very low

(arbitrarily defined as less than 60%). Investigations using non-linear transformations of real

microbiome data using UMAP also supports this hypothesis. Armstrong et al. (2021)

demonstrated the ability of UMAP to resolve biologically relevant clusters and ecological

gradients using data from the human microbiome project and the '88 soils' dataset while Dorrity

et al. (2020) showed that clustering samples in UMAP space identified protein-protein

interactions more effectively than clustering the same data in PCA space (7,8).

In addition to working well with non-linear data, learned dissimilarities can be advantageous

since more "traditional" measures of dissimilarity have difficulty capturing potential

dependencies between ASVs. LANDMark and Extra Trees reduce this problem due to their

hierarchical nature. For example, in an Extra Trees model if the abundance and/or presence of

one ASV depends on another we should expect to see sub-trees using these ASVs to occur more

frequently. We also conjecture that LANDMark and other tree-dissimilarity measures work well

due to their ability to handle noisy data. Noise is often introduced due to the inclusion of

uninformative ASVs, potentially informative but highly variable ASVs, splitting a single

genome, and missing data due to incomplete sampling or the limitations of library amplification

and sequencing (10,14,62,63). Learned dissimilarity measures, such as those explored here, may

be capable of identifying and reducing the impact that uninformative ASVs exert when

measuring dissimilarity. For example, in an Extra Trees classifier, only the best randomly

selected cut point from a set of randomly selected ASVs is chosen to split each node (21). When

choosing splits in this manner the impact of uninformative ASVs tends to be minimized since

they are not selected as often. In addition, after the decision for the node is made, each set of

samples is partitioned into one of two child nodes irrespective of the magnitude of the unselected

features. This likely results in a strong regularizing effect across the entire forest (64).

LANDMark extends this idea by identifying which (regularized) linear or non-linear model is

best at discriminating between classes using a randomly selected subset of ASVs (25).

While a deeper and more detailed analysis of the ASVs identified here is outside the scope of

this work, TreeOrdination identified ASVs belonging to taxa known to be associated with the

proximal colon and Crohn's Disease. The primary focus of this work is to begin an investigation

into the role, advantages, and disadvantages that learned dissimilarities and non-linear

embeddings have in the interpretation of amplicon sequencing data. Our main contributions are

our results showing that tree-based dissimilarities can effectively capture biologically meaningful

information about samples and a proof-of-concept workflow that uses LANDMark to learn a

tree-based dissimilarity and low-dimensional representation of the original samples. These

representations can then be used to create predictive models which can subsequently be analyzed

using modern introspection methods to identify predictive sets of ASVs. We would also like to

note that, although simple dissimilarity and distance measures are unlikely to be expressive

enough to account for the nuances and complexities of modern amplicon sequencing datasets,

their use should not be outright dismissed. For one, the calculation of pairwise dissimilarities

using formulae is orders of magnitude faster than TreeOrdination or other learned dissimilarities.

These measures and metrics can also be used for exploratory purposes, an analysis that may be

time-consuming to do with learned dissimilarities. Finally, if the projections produced using

these dissimilarities account for a significant amount of explained variation, there is likely little

to be gained by applying more complex approaches.

Conclusions and Future Work

Our work has shown that unsupervised LANDMark models can learn effective dissimilarity

matrices. When paired with modern dimensionality reduction approaches, such as UMAP, an

informative lower-dimensional projection can be created. However, our work does have some

important limitations. First, the datasets used here are small. While we believe that our results

should hold with larger datasets, further testing is needed to determine if this is true. Secondly,

we only tested transformations and metrics which represent a more statistically sound way to

analyze compositional datasets. Other transformations, such as the geometric mean of pairwise

ratios, the isometric log-ratio, and cumulative sum scaling transformations were not tested since

we wanted to focus on three commonly used approaches, two of which account for the

compositionality inherent to this type of data (1,16,65). However, we hope to conduct a more

comprehensive analysis using a wider variety of transformation procedures in a more extensive

future comparative analysis. Finally, while we believe that tools such as LANDMark and

TreeOrdination are capable, the work presented here speaks to a broader conversation that is

occurring within the scientific community analyzing ecological and microbiome data.

Specifically, more evidence is coming to light which demonstrates the inadequacy of using

PCoA in the study of beta-diversity and that better insights into the data are likely to be

generated using non-linear tools. In addition, our work demonstrates the important role that ML

will play in the near future since ML can be used as an alternative to validate the results from

statistical approaches, such as PerMANOVA. For example, statistically significant

PerMANOVA results were recorded in some of the negative control tests. If taken in isolation,

these results could be misinterpreted. By using additional lines of evidence, such as the

generalization performance of cross-validated predictive models, we can come to a conclusion

that suggests that the data may not have predictive value. Therefore, we advocate for taking a

more holistic investigative approach. In doing so better conclusions can be drawn since multiple

measures of data quality are combined and weighed together. Although this is often more

difficult when working with ML models, since they are notoriously difficult to interpret, an

increasingly growing number of tools have been created to allow us to peek into these black

boxes.

Acknowledgments

We would like to thank Dr. Katie McGee and Dr. Terri M. Porter for their thoughtful discussions

during the development of TreeOrdination and LANDMark. We would also like to thank Dr.

Katie McGee for her suggestions on where to improve the message of our manuscript. Finally,

we extend our thanks to our reviewers for their helpful and insightful comments.

References

1. Silverman JD, Washburne AD, S M, David LA. A phylogenetic transform enhances analysis of
compositional microbiota data. eLife. 2017;6:21887.

2. Chen B, He X, Pan B, Zou X, You N. Comparison of beta diversity measures in clustering the high-
dimensional microbial data. PLoS One. 2021;16(2):e0246893.

3. Weiss S, Xu ZZ, Peddada S, Amir A, Bittinger K, Gonzalez A, et al. Normalization and microbial
differential abundance strategies depend upon data characteristics. Microbiome. 2017;5(27).

4. Kuczynski J, Liu Z, Lozupone C, McDonald D, Fierer N, Knight R. Microbial community resemblance
methods differ in their ability to detect biologically relevant patterns. Nat Methods. 2010
Oct;7(10):813–9.

5. Kubinski R, Djamen-Kepaou JY, Zhanabaev T, Hernandez-Garcia A, Bauer S, Hildebrand F, et al.
Benchmark of data processing methods and machine learning models for gut microbiome-based
diagnosis of inflammatory bowel disease. bioRxiv [Internet]. 2021; Available from:
https://www.biorxiv.org/content/early/2021/05/04/2021.05.03.442488

6. Elhaik E. Principal Component Analyses (PCA)-based findings in population genetic studies are
highly biased and must be reevaluated. Scientific Reports. 2022 Aug 29;12(1):14683.

7. Dorrity MW, Saunders LM, Queitsch C, Fields S, Trapnell C. Dimensionality reduction by UMAP to
visualize physical and genetic interactions. Nature Communications. 2020 Mar 24;11(1):1537.

8.   Armstrong G, Martino C, Rahman G, Gonzalez A, Vázquez-Baeza Y, Mishne G, et al. Uniform
695   Manifold Approximation and Projection (UMAP) Reveals Composite Patterns and Resolves
696   Visualization Artifacts in Microbiome Data. mSystems. 0(0):e00691-21.

697   9.   Ryo M, Rillig MC. Statistically reinforced machine learning for nonlinear patterns and variable
698   interactions. Ecosphere. 2017;8(11):01976.

699   10.   Hugerth LW, Andersson AF. Analysing Microbial Community Composition through Amplicon
700   Sequencing: From Sampling to Hypothesis Testing. Frontiers in Microbiology. 2017;8:1561.

701   11.   Anderson MJ, Walsh DCI. PERMANOVA, ANOSIM, and the Mantel test in the face of heterogeneous
702   dispersions: What null hypothesis are you testing? Ecological Monographs. 2013;83:557–74.

703   12.   Lin H, Peddada SD. Analysis of compositions of microbiomes with bias correction. Nature
704   Communications. 2020 Jul 14;11(1):3514.

705   13.   Gloor GB, Wu JR, Pawlowsky-Glahn V, Egozcue JJ. It's all relative: analyzing microbiome data as
706   compositions. Ann Epidemiol. 2016 May;26(5):322–9.

707   14.   Gloor GB, Macklaim JM, Pawlovsky-Glahn V, Egozcue JJ. Microbiome Datasets Are Compositional:
708   And This Is Not Optional. Front Microbiol. 2017;8:2224.

709   15.   Segata N, Izard J, Waldron L, Gevers D, Miropolsky L, Garrett WS, et al. Metagenomic biomarker
710   discovery and explanation. Genome Biology. 2011;12:60.

711   16.   Paulson JN, Stine OC, Bravo HC, M P. Robust methods for differential abundance analysis in marker
712   gene surveys. Nature Methods. 2013;10(12):1200–2.

713   17.   Love MI, Huber W, Anders S. Moderated estimation of fold change and dispersion for RNA-seq
714   data with DESeq2. Genome Biology. 2014 Dec 5;15(12):550.

715   18.   Cutler RD, Edwards TC, Beard KH, Cutler A, Hess KT, Gibson J, et al. Random Forests for
716   Classification in Ecology. Ecology. 2007;88(11):2783–92.

717   19.   Touw WG, Bayjanov JR, Overmars L, Backus L, Boekhorst J, Wels M, et al. Data mining in the Life
718   Sciences with Random Forest: a walk in the park or lost in the jungle? Brief Bioinform.
719   2012;14(3):315–26.

720   20.   Rhodes JS, Cutler A, Moon KR. Geometry- and Accuracy-Preserving Random Forest Proximities
721   [Internet]. arXiv; 2022. Available from: https://arxiv.org/abs/2201.12682

722   21.   Breiman L. Random Forests. Machine Learning. 2001;45(1):5–32.

723   22.   Alhusain L, Hafez AM. Cluster ensemble based on Random Forests for genetic data. BioData
724   Mining. 2017 Dec 15;10(1):37.

725   23.   Martino C, Morton JT, Marotz CA, Thompson LR, Tripathi A, Knight R, et al. A Novel Sparse
726   Compositional Technique Reveals Microbial Perturbations. mSystems. 2019 Feb;4(1).

24.   Geurts P, Ernst D, Wehenkel L. Extremely Randomized Trees. Machine Learning. 2006;63(1):3–42.

25.   Rudar J, Porter TM, Wright M, Golding GB, Hajibabaei M. LANDMark: An ensemble approach to the
supervised selection of biomarkers in high-throughput sequencing data. BMC Bioinformatics.
2022;23(1):110.

26.   Menze BH, M K, Splitthoff DN, K K, Hamprecht FA. On oblique random forests. In: Gunopulos D,
Hofmann T, Malerba D, Vazirgiannis M, editors. Machine Learning and Knowledge Discovery in
Databases. 2011. p. 453–69.

27.   Flynn K, Ruffin MT IV, Turgeon K, Schloss PD. Spatial Variation of the Native Colon Microbiota in
Healthy Adults. Cancer Prevention Research. 2018;11(7):393–402.

28.   Forbes JD, Chen CY, Knox NC, Marrie RA, El-Gabalawy H, de Kievit T, et al. A comparative study of
the gut microbiota in immune-mediated inflammatory diseases-does a common dysbiosis exist?
Microbiome. 2018 Dec 13;6(1):221–221.

29.   Porter TM, Hajibabaei M. METAWORKS: A flexible, scalable bioinformatic pipeline for multi-marker
biodiversity assessments. bioRxiv. 2020;

30.   Rognes T, Flouri T, Nichols B, Quince C, Mahe F. VSEARCH: a versatile open source tool for
metagenomics. PeerJ. 2016;4:2584.

31.   Wang Q, Garrity GM, Tiedje JM, Cole JR. Naive Bayesian classifier for rapid assignment of rRNA
sequences into the new bacterial taxonomy. Applied and Environmental Microbiology. 2007
Aug;73(16):5261–7.

32.   Ranasinghe JA, Stein ED, Miller PE, Weisberg SB. Performance of two Southern California benthic
community indices using species abundance and presence-only data: relevance to DNA barcoding.
PLoS One. 2012;7(8):40875.

33.   Wallen ZD. Comparison study of differential abundance testing methods using two large Parkinson
disease gut microbiome datasets derived from 16S amplicon sequencing. BMC Bioinformatics.
2021 May 25;22(1):265.

34.   McMurdie PJ, Holmes S. Waste Not, Want Not: Why Rarefying Microbiome Data Is Inadmissible.
PLoS Computational Biology. 2014;10(4):1003531.

35.   Lin H, Peddada SD. Analysis of microbial compositions: a review of normalization and differential
abundance analysis. npj Biofilms and Microbiomes. 2020 Dec 2;6(1):60.

36.   Greenacre M, Martínez-Álvaro M, Blasco A. Compositional Data Analysis of Microbiome and Any-
Omics Datasets: A Validation of the Additive Logratio Transformation. Frontiers in Microbiology
[Internet]. 2021;12. Available from:
https://www.frontiersin.org/article/10.3389/fmicb.2021.727398

37.   team T scikit-bio development. scikit-bio: A Bioinformatics Library for Data Scientists, Students,
and Developers [Internet]. 2022. Available from: http://scikit-bio.org

38. Martín-Fernández JA, Barceló-Vidal C, Pawlowsky-Glahn V. Dealing with Zeros and Missing Values
in Compositional Data Sets Using Nonparametric Imputation. Mathematical Geology. 2003 Apr
1;35(3):253–78.

39. Pedregosa F, Varoquaux G, Gramfort A, Michel V, Thirion B, Grisel O, et al. Scikit-learn: Machine
Learning in Python. Journal of Machine Learning Research. 2011;12:2825–30.

40. Pouyan MB, Kostka D. Random forest based similarity learning for single cell RNA sequencing data.
Bioinformatics. 2018 Jul 1;34(13):i79–88.

41. Xiong C, Johnson D, Xu R, Corso JJ. Random Forests for Metric Learning with Implicit Pairwise
Position Dependence. In: Proceedings of the 18th ACM SIGKDD International Conference on
Knowledge Discovery and Data Mining [Internet]. New York, NY, USA: Association for Computing
Machinery; 2012. p. 958–66. (KDD '12). Available from: https://doi.org/10.1145/2339530.2339680

42. Dalleau K, Couceiro M, Smail-Tabbone M. Unsupervised Extremely Randomized Trees. In: Phung D,
Tseng VS, Webb GI, Ho B, Ganji M, Rashidi L, editors. Advances in Knowledge Discovery and Data
Mining. Cham: Springer International Publishing; 2018. p. 478–89.

43. Camargo A. PCAtest: testing the statistical significance of Principal Component Analysis in R. PeerJ.
2022;10:e12967.

44. McInnes L, Healy J, Melville J. UMAP: Uniform Manifold Approximation and Projection for
Dimension Reduction. Journal of Open Source Software. 2020;3(29):861.

45. Hunter JD. Matplotlib: A 2D graphics environment. Computing in Science & Engineering.
2007;9(3):90–5.

46. Waskom ML. seaborn: statistical data visualization. Journal of Open Source Software.
2021;6(60):3021.

47. Jackson DA. PROTEST: A PROcrustean Randomization TEST of community environment
concordance. Écoscience. 1995;2(3):297–303.

48. Lundberg SM, Lee S. A Unified Approach to Interpreting Model Predictions. In: 31st Conference on
Neural Information Processing Systems (NIPS 2017 [Internet]. Long Beach; 2017. Available from:
http://papers.nips.cc/paper/7062-a-unified-approach-to-interpreting-model-predictions.pdf.

49. Lundberg SM, Erion G, Chen H, DeGrave A, Prutkin JM, Nair B, et al. From local explanations to
global understanding with explainable AI for trees. Nat Mach Intell. 2020;2(1):56–67.

50. Covert IC, Lundberg S, Lee SI. Understanding Global Feature Contributions with Additive
Importance Measures. In: Proceedings of the 34th International Conference on Neural Information
Processing Systems. Red Hook, NY, USA: Curran Associates Inc.; 2020. (NIPS'20).

51. Benavoli A, Corani G, Demšar J, Zaffalon M. Time for a Change: a Tutorial for Comparing Multiple
Classifiers Through Bayesian Analysis. Journal of Machine Learning Research. 2017;18(77):1–36.

52. Kobak D, Linderman GC. Initialization is critical for preserving global data structure in both t-SNE
and UMAP. Nature Biotechnology. 2021 Feb 1;39(2):156–7.

53. Perez-Muñoz ME, Sugden S, Harmsen HJM, Hart BA 't, Laman JD, Walter J. Nutritional and
ecological perspectives of the interrelationships between diet and the gut microbiome in multiple
sclerosis: Insights from marmosets. iScience. 2021;24(7):102709.

54. Assa A, Butcher J, Li J, Elkadri A, Sherman PM, Muise AM, et al. Mucosa-Associated Ileal Microbiota
in New-Onset Pediatric Crohn's Disease. Inflammatory Bowel Diseases. 2016 Jun;22(7):1533–9.

55. The HC, Florez de Sessions P, Jie S, Pham Thanh D, Thompson CN, Nguyen Ngoc Minh C, et al.
Assessing gut microbiota perturbations during the early phase of infectious diarrhea in Vietnamese
children. Gut Microbes. 2018 Jan 2;9(1):38–54.

56. Lewis JD, Chen EZ, Baldassano RN, Otley AR, Griffiths AM, Lee D, et al. Inflammation, Antibiotics,
and Diet as Environmental Stressors of the Gut Microbiome in Pediatric Crohn's Disease. Cell Host
Microbe. 2015 Oct 14;18(4):489–500.

57. Diling C, Xin Y, Chaoqun Z, Jian Y, Xiaocui T, Jun C, et al. Extracts from Hericium erinaceus relieve
inflammatory bowel disease by regulating immunity and gut microbiota. Oncotarget. 2017 Oct
17;8(49):85838–57.

58. Bacaro G, Ricotta C, Mazzoleni S. Measuring beta-diversity from taxonomic similarity. Journal of
Vegetation Science. 2007;18(6):793–8.

59. Wildi O. Evaluating the Predictive Power of Ordination Methods in Ecological Context.
Mathematics [Internet]. 2018;6(12). Available from: https://www.mdpi.com/2227-7390/6/12/295

60. Leite MFA, Kuramae EE. You must choose, but choose wisely: Model-based approaches for
microbial community analysis. Soil Biology and Biochemistry. 2020;151:108042.

61. McKnight DT, Huerlimann R, Bower DS, Schwarzkopf L, Alford RA, Zenger KR. Methods for
normalizing microbiome data: An ecological perspective. Methods in Ecology and Evolution.
2019;10(3):389–400.

62. Schloss PD. Amplicon Sequence Variants Artificially Split Bacterial Genomes into Separate Clusters.
mSphere. 2021 Aug 25;6(4):e0019121.

63. Edgar RC. UCHIME2: Improved chimera detection for amplicon sequences. bioRxiv [Internet].
2016; Available from: https://www.drive5.com/uchime/

64. Mentch L, Zhou S. Randomization as Regularization: A Degrees of Freedom Explanation for
Random Forest Success. Journal of Machine Learning Research. 2020;21:171:1-171:36.

65. Chen L, Reeve J, Zhang L, Huang S, Wang X, Chen J. GMPR: A robust normalization method for
zero-inflated count data with application to microbiome sequencing data. PeerJ. 2018;6:e4600.

829
830

Supporting Information

Additional File 1 – Supplementary Tables 1 to 12

Additional File 2 – Positive and Negative Control Results

Additional File 3 – Supplementary Figures 1 and 2

GitHub Link 1 – Raw Data and Code Used to Run the Analysis

(https://github.com/jrudar/Unsupervised-Decision-Trees)

GitHub Link 2 – TreeOrdination Package (https://github.com/jrudar/TreeOrdination)