Benchmarking the accuracy of structure-based binding affinity predictors on Spike-ACE2 Deep Mutational Interaction Set

Burcu Ozden[1,2], Eda Şamiloğlu[1,2], Mehmet Erguven[1], Can Yükrük[1], Mehdi Koşaca[1,2], Melis Oktayoğlu[1], Muratcan Menteş[1], Nazmiye Arslan[1], Gökhan Karakülah[1,2], Ayşe Berçin Barlas[1,2], Büşra Savaş[1,2], Ezgi Karaca[1,2]

[1]Izmir Biomedicine and Genome Center, Dokuz Eylul University Health Campus, Balçova, Izmir 35330, Turkey

[2]Izmir International Biomedicine and Genome Institute, Dokuz Eylül University, Izmir 35340, Turkey

Correspondence: ezgi.karaca@ibg.edu.tr

ABSTRACT

Since the start of COVID-19 pandemic, a huge effort has been devoted to understanding the Spike(SARS-CoV-2)-ACE2 recognition mechanism. To this end, two deep mutational scanning studies traced the impact of all possible mutations across Receptor Binding Domain (RBD) of Spike and catalytic domain of human ACE2. By concentrating on the interface mutations of these experimental data, we benchmarked six commonly used structure-based binding affinity predictors (FoldX, EvoEF1, MutaBind2, SSIPe, HADDOCK, and UEP). These predictors were selected based on their user-friendliness, accessibility, and speed. As a result of our benchmarking efforts, we observed that none of the methods could generate a meaningful correlation with the experimental binding data. The best correlation is achieved by FoldX (R = -0.51). Also, when we simplified the prediction problem to a binary classification, i.e., whether a mutation is enriching or depleting the binding, we showed that the highest accuracy is achieved by FoldX with 64% success rate. Surprisingly, on this set, simple energetic scoring functions performed significantly better than the ones using extra evolutionary-based terms, as in Mutabind and SSIPe. These observations suggest plenty of room to improve the conventional affinity predictors for guessing the variant-induced binding profile changes of a host-pathogen system, such as the Spike-ACE2. To aid such improvements we provide our benchmarking data at https://github.com/CSB-KaracaLab/RBD-ACE2-MutBench with the option to visualize our mutant models at https://rbd-ace2-mutbench.github.io/

Key words: binding affinity prediction, deep mutagenesis, SARS-CoV-2, ACE2, RBD

INTRODUCTION

At the beginning of 21st century, the emergence of Severe Acute Respiratory Syndrome Coronavirus (SARS-CoV)[1] and Middle East Respiratory Syndrome Coronavirus[2] led to serious public health concerns. Evolving from these viruses, during late 2019, a new SARS virus, SARS-CoV-2, caused the most severe pandemic of the 21st century[3]. SARS-CoV-2 infection is initiated upon having its Spike protein interacting with the host Angiotensin Converting 2 (ACE2) enzyme[4]. The widespread infection of SARS-CoV-2 compared to its predecessors was linked to higher binding affinity of Spike to ACE2[5]. Relatedly, alpha, beta, gamma, eta, iota, kappa, lambda, mu, and omicron SARS-CoV-2 variants were shown to have at least one mutation across the Spike-ACE2 interface[6]. This realization placed the characterization of interfacial Spike-ACE2 mutations at the center of COVID-19-related research. Within this context, in 2020, two deep mutational scanning (DMS) studies explored how Spike/ACE2 variants impact Spike-ACE2 interactions[7,8]. In these DMS studies, the residues on the Receptor Binding Domain (RBD) of Spike and the catalytic domain of human ACE2 were mutated into other 19 amino acid possibilities, followed by tracing of new RBD-ACE2 binding profiles.

In parallel to these experimental efforts, a handful of structure- and force field-based computational studies employed a comprehensive investigation of variation across the RBD-ACE2 interface (Table 1). Three such studies utilized two fast and user-friendly tools, FoldX and HADDOCK [9–11]. Blanco *et al.* used FoldX with the inclusion of water molecules (FoldXwater) to trace the binding enhancing RBD and ACE2 mutations [9]. From their 21 binding enhancing mutation predictions, nine of them were confirmed as affinity enhancing by the DMS set. Rodrigues *et al.* investigated the impact of ACE2 orthologs on their RBD

binding with HADDOCK, where they proposed five significantly affinity improving ACE2

mutations[10]. Among these, D30E and A387E were shown to be affinity enhancing in the

ACE2 DMS set. Complementary to this study, Sorokina *et al*. performed computational alanine

scanning on ACE2 with HADDOCK[11]. Here, three out of five mutations (N49A, R393A, and

P389A) were classified as binding enriching both by the computational predictions and the

DMS set. Two other studies made use of elaborate simulation techniques, mainly molecular

dynamics simulations. Laurini *et al.* performed molecular mechanics/Poisson–Boltzmann

alanine scanning and molecular dynamics simulations to find structurally and energetically

critical RBD-ACE2 residues[12]. They proposed eight hotspot positions on RBD and ACE2,

where three of them were characterized as affinity enhancing in the DMS sets. Gheeraert *et*

al. performed 1 μs long molecular dynamics simulations of five RBD variants (alpha, beta,

gamma, delta, and epsilon) in complex with ACE2[13]. They found that L452R, T478K (delta

variant) and N501Y (alpha, gamma variants) cause drastic structural changes across the RBD-

ACE2 interface. These mutations were classified as binding enriching in the RBD DMS set.

Table 1. Affinity impacting RBD and ACE2 variant/hotspot predictions. The predictions agreeing

with the experimental are underlined and shown in bold.

Work carried out by	Important RBD residues/mutations	Important ACE2 residues/ mutations	Approach
Blanco *et al.*[9]	V445M/R/W, **Q493F/L/M/Y**, **Q498F**/L/M/**Y**, T500K,	G326E	Variant modeling and interface score calculation with FoldXwater

	N501A/C/L/S/**T**, **V503R**/W/Y		
Rodrigues *et al.*[10]		Q24E, **D30E**, H34Y, L79H, **A387E**	Variant modeling and interface score calculation with HADDOCK
Sorokina *et al.*[11]		**N49A**, **R393A**, M383A, **P389A**, G354A	Alanine scanning and interface score calculation with HADDOCK
Laurini *et al.*[12]	**Q498**, T500, R403	D38, **K31**, E37, K353, **Y41**	Interaction and energy analysis through molecular dynamics and MM/PB alanine scanning
Gheeraert *et al.*[13]	**L452R**, **T478K**, **N501Y**		Interaction analysis through MD simulations

As presented in Table 1, accurate reproduction of RBD-ACE2 DMS profiles can be tricky

even when elaborate simulation techniques are used. So, if such time-intensive simulation

approaches are facing challenges in back-calculating the impact of RBD-ACE2 interface

variation, how far are the fast prediction tools that were heavily used in the early months of

pandemic, such as FoldX and HADDOCK, from accurately predicting the impact of RBD-ACE2

variations? To answer this question, we benchmarked six fast affinity prediction tools, i.e.,

FoldX, HADDOCK, EvoEF1, MutaBind2, SSIPe, and UEP [14–20] against the Spike-ACE2

interface DMS set. These predictors were selected based on their user-friendliness and speed,

since we wanted to put an emphasis on the accessibility of these tools to the researchers who

may not have programming experience or enough computing resources. Among these tools,

FoldX and EvoEF1 use intra- and inter-molecular energies derived from empirical force field

terms. HADDOCK scores complexes by combining intermolecular van der Waals,

electrostatics, and empirical desolvation terms. Mutabind and SSPIe utilize FoldX and EvoEF1,

respectively, to model the mutations. Both methods have their own scoring functions to

consider evolutionary-based information too. UEP scores mutations based on statistically

determined intermolecular contact potentials. HADDOCK, MutaBind2, and SSIPe can be run

through a web service. FoldX can be called over a GUI through a YASARA plugin. EvoEF1 and

UEP are available as stand-alone packages. Our benchmarking files can be accessed at

https://github.com/CSB-KaracaLab/RBD-ACE2-MutBench with the option to visualize our

mutant models at https://rbd-ace2-mutbench.github.io/

RESULTS and DISCUSSION

Benchmark Compilation

The deep mutational scanning (DMS) experiments performed by Chan *et al.* and Starr *et al.* [7,8] scan the impact of all possible amino acid variations imposed on the RBD domain of Spike and the catalytic domain of ACE2 on RBD-ACE2 binding. These studies classified mutations as binding enriching or depleting when compared to the wild type interaction. While compiling our benchmark set, our aim was (i) to select the DMS subset reporting on the variations across RBD-ACE2 interface since the selected methods are tuned to predict the impact of interface mutations, (ii) to include an equal number of binding enriching and depleting cases to obtain a balanced benchmark set.

The DMS sets contain 988 interfacial mutations, measured over 26 RBD and 26 ACE2 residues (calculated by PDBePISA[21] on 6m0j PDB[22]). 13% of these 988 mutations were profiled as binding enriching (42 for RBD and 89 for ACE2, Figure 1A) and the rest as binding depleting. As shown in Figure 1A, the binding enriching RBD mutations span a narrow enrichment range [0.01, 0.30], while for ACE2 this range increases to [0.03, 3.37]. We added all enriching cases into our benchmark. To fairly represent the depleting cases, we selected 131 mutations sampling the whole depleting data spread (Figure 1A). We then analyzed the individual binding profiles of selected mutations with heatmaps (Figure 1B). As can be observed from these heatmaps, on the RBD side, several mutations on Q493, S477, F490, N501, V503, E484, Q498 lead to better RBD-ACE2 binding (Figure 1B, Figure S1, Table S1). Among these, Q493R and S477N were observed in omicron; E484K in beta, gamma, eta, iota, mu; E484Q in kappa; N501Y in alpha, beta, gamma, mu, omicron variants[6]. On the ACE2 surface, the top enriching mutations came from T27, Q42, S19, and L79 positions (Figure 1C, Figure S1). All these residues, except S19, were reported as species-associated variations[23].

While appearing less frequently as binding enhancers, K31, E35, M82, and Y83 were earlier

listed as critical residues for RBD-ACE2 interactions (Figure 1B-C and Figure S1)[9,12,22]. All

these residue positions are situated around the core (at the rim) of the RBD-ACE2 interface.

The top enriching mutations on the RBD side are Q493M, S477D, F490K, N501F, V503M,

E484R, Q498H, and on the ACE2 side are T27L, Q42C, S19P (Table S1). Further investigation

of these mutations did not lead to a generalized pattern for understanding RBD-ACE2

recognition.

Figure 1. (A) RBD-ACE2 DMS benchmark set. The experimental binding profile distributions of the

interfacial RBD (yellow, n=494) and ACE2 (blue, n=494) mutations are represented with box-and-

whisker plots. Values >0 indicate binding enriching and values <0 indicate binding depleting

mutations. 26.5% of this data set is selected as our benchmark set (n=262): n=84 for RBD (42

enriching, 42 depleting) and n=178 for ACE2 mutations (89 enriching, 89 depleting cases)),

represented as gray dots. This panel was generated in Python 3.8 by using pandas, Numpy and

Seaborn libraries[34–39]. **(B) The experimental binding enrichment and depletion values of our**

benchmark set, RBD (top) and ACE2 (bottom). The values > 0 correspond to binding enriching

positions (light orange), while the values <0 represent the depleting ones (dark purple). The

positions leading often to binding enriching mutations are highlighted in orange. **(C) The structural**

depiction of enriching mutations. The interface residues of RBD-ACE2 complex are shown in

spheres. The color code of the spheres follows the largest binding value measured for a given

residue, as shown in Figure 1B. The important positions are highlighted with labels (yellow: RBD,

142   blue: ACE2). The illustration is generated in PyMOL[24] using PDB 6M0J[22].

Benchmarking the affinity predictors: seeking for a linear correlation

For all the mutations in our benchmark set (n=262), we calculated the score change

imposed by the mutations with FoldX, FoldXwater, EvoEF1, MutaBind2, SSIPe, and HADDOCK.

[14–20] (Figure S2). Then, we investigated whether there is any meaningful correlation with

the calculated score changes and experimental binding enrichment/depletion values (Figure

2A). Here, the expected perfect correlation would be -1 as larger experimental values and

smaller binding scores point to improved binding. As a result, we observed insignificant linear

correlations for HADDOCK, EvoEF1, and SSIPe predictors. Mediocre correlations with R values

ranging from -0.51 to -0.45 were observed for FoldX and MutaBind2. The best correlation (the

highest R-value) was obtained by FoldX (R = -0.51). Interestingly, including the water effect

into FoldX predictions by using FoldXwater did not improve the accuracy of the original

approach (R = -0.45 vs. R = -0.51). Furthermore, the enhanced scoring function of MutaBind2

built upon FoldX did not improve the original FoldX scoring (R = -0.49 vs. R = -0.51). The same

was observed for SSIPe, since it was built upon EvoEF1's sampling (R = -0.28 vs. -0.27). As the

naïve predictor, we run UEP on a subset of our benchmark (n=129), as UEP is tuned to predict

mutation-induced changes of residues that are in contact with more than two atoms. This

effort also resulted in an insignificant correlation.

We further calculated the pairwise correlations of score changes predicted by each

algorithm (Figure 2B). This comparison revealed that HADDOCK reports the most

distinct scores compared the other algorithms. This is understandable, as all the other

approaches stem from a similar prediction mentality of FoldX (Materials and Methods). We

computed all-atom Root Mean Square Deviations (RMSDs) of each generated mutant model

in an all-to-all fashion to understand whether the distinct behavior of HADDOCK came from

differentially modeled side chain formations (Figure S3). This analysis demonstrated that

HADDOCK indeed generates the largest RMSD models compared to the models computed by

the other tools. Notably, MutaBind2 and FoldX conformers resulted in the second highest

RMSD cases, indicating that the further minimization steps used by MutaBind2 significantly

impacts the final conformation of the side chains. As expected, EvoEF1 and SSIPe mutant

models came out to be identical, since SSIPe utilizes EvoEF1 to structurally model the

mutations.

Figure 2. (A) Correlations between experimental DMS benchmark set and the binding affinity

predictors. Data points for all scenarios are n=262, except UEP where the number of points is 129

(~50% of the benchmark set). R- and p-values were calculated by using statistics and scipy libraries

of Python 3.8. **(B) The correlation heatmap of the computational and the experimental scores.** The

correlation values are expressed in terms of Pearson Correlation Coefficients (PCC), ranging between

182   -1 and 1. Highly negatively (PCC = -1) and positively (PCC = 1) correlated predictors are colored with

183   dark purple and light orange, respectively.

Benchmarking the affinity predictors: seeking for a binary classification

Apart from analyzing the correlation between ΔScores and experimental binding

values, we also performed a binary assessment. In this assessment, the tools were tested

whether they can predict the direction of binding affinity change (enriching or depleting).

Accordingly, we counted a prediction as successful if the experimental and computational

data would agree whether a mutation is enriching or depleting. In this regard, the overall

prediction accuracy was calculated as the percentage of correct predictions (the success rate).

According to this binary assessment, the overall success rates of predictors varied between

54% and 64% (Figure 3A), where the top-ranking predictor again came out to be FoldX (64%)

(Figure 2A). FoldXwater ranked the second, once again implying that the inclusion of water

effects did not improve the prediction accuracy. When we analyzed ACE2 and RBD subsets

individually, better prediction rates for depleting mutations were consistently observed,

despite the narrow prediction range posed by the experimental data (Figure 3A). Strikingly,

MutaBind2 and SSIPe predicted most mutations as depleting, hinting at a problem in using

evolutionary-based terms in scoring the host-pathogen system RBD-ACE2. These

observations did not change, when we calculated the success rates only for the residues that

frequently lead to enriching mutations (the highlighted residues in Figure 1B-C). When we

further scored the lowest ranking predictor, HADDOCK's models with FoldX, HADDOCK's

success rate increased by 5% (from 54% from 59%) (Figure S4A). Normalizing HADDOCK

scores by the buried surface area (BSA) of the interface did not improve the success rates

(Figure S4A). On the UEP subset, the overall prediction performances vary within a broader

range, i.e., 49%-69% (Figure 3B), where the top two predictors became FoldX and FoldXwater

(69% vs. 66%) and the lowest performing predictors became UEP and HADDOCK (52% and

49%). On both datasets, all predictors had difficulties in predicting binding-enriching

mutations compared to the binding-depleting ones (Figure 3).

Figure 3. (A) The success rates on the benchmark set (n=262). (B) Success rates of predictors are

calculated by using UEP's data set (n= 129). In both panels, if the success rate changes drastically

compared to the overall dataset (first column on the left), it is shown in bold. The plots were

prepared by using R-Studio [25–28].

Volume and hydrophobicity biases are the most obvious misprediction determinants

To explore the prediction dependencies of each tool, we assessed their success rates

after classifying the benchmark cases according to volume, hydrophobicity, and flexibility

changes imposed by the mutations (Figure 4, Table S2, Figure S4B). The residue-based volume

values were taken from Zhi-hua *et al* [29], the hydrophobicity ones from Eisenberg *et al.* [30],

and the flexibility ones from Shapovalov and Dunbrack [31]. Per property, we calculated the

frequency distributions of the computed changes, given the enrichment or depletion status

of the original mutation (Figure 4A-C). To serve as a background, we calculated the frequency

distributions of the experimental data too (gray lines in Figure 4A-C). Here our assumption

was a discrepancy between the tails of the experimental data and the predictors' distributions

should point to an obvious bias for a given property. Accordingly, when we investigated the

volume change plots, we saw that all predictors had difficulties in predicting volume

decreasing mutations when the mutation induces an enrichment in binding (Figure 4A). In the

case of depleting mutations, only HADDOCK has an apparent bias toward classifying volume

increasing mutations wrongly. In the case of hydrophobicity change, for all predictors, there

is a slight tendency to classify hydrophobicity decreasing binding enriching mutations

wrongly. This is more pronounced for hydrophobicity decreasing and binding depleting

mutations for HADDOCK. We did not observe any bias for the predictors regarding the

changes in the side chain flexibilities.

To gauge whether the enriching and depletion mutation predictions were balanced

for a given property, we calculated the difference between the area under the curve of the

successfully predicted enriching and depletion mutations (ΔSuccess, Figure S4B). Here, our

assumption was, if the prediction is balanced, then the ΔSuccess should be close to zero. On

the other hand, the ΔSuccess values towards 100 and -100 should indicate extreme biases.

This analysis revealed that HADDOCK has moderate volume change bias with 34 ΔSuccess

score. Normalizing HADDOCK scores by the BSA of the interface doubled this bias leading to

78 ΔSuccess score. When HADDOCK models were scored with FoldX, the original 34 ΔSuccess

shifted to -31 ΔSuccess, resulting in a bias toward depleting mutations (Figure S4B). When we

considered the success rates based on hydrophobicity, we found out that FoldX tends to

predict depleting cases better with -31 ΔSuccess score. Inclusion of water in FoldX

(FoldXwater) increases this moderate bias (ΔSuccess score -36 vs -31). In this analysis too, we

could not find any relation between the flexibility change and success rate of predictors

(Figure 4C and Figure S4B). Finally, we found that ΔSuccess is extremely skewed for all metrics

for MutaBind2 and SSIPe, since they predict almost all mutations as depleting.

To present a complete analysis, we also investigated the impact of the

physicochemical property changes induced by each mutation on the prediction accuracy

(Figure 4D). The physicochemical change classes we considered were no change, polarity

loss/gain, and charge loss/gain. To serve as a background, we calculated the share of each

class within the original data set (gray bars in Figure 4D). As a result, we could not observe

any specific bias given a physicochemical property change. The success shares reflect the

general trends observed in successfully predicting binding enriching or depletion mutations,

as shown in Figure 4A.

Figure 4. The effects of mutation-induced changes in the amino acid physical properties on the

predictor's success rates according to (A) Volume change, **(B)** Hydrophobicity change, **(C)** Flexibility

change. The original data set distribution for a given binding class is plotted in gray. The other

predictors are colored as provided in the legend. Volume/hydrophobicity/flexibility-increasing

mutations reside on the "positive side" of the plot (x-axis value >0), whereas

volume/hydrophobicity/flexibility-decreasing mutations reside on the "negative side" of the pot (x-

axis value <0) **(D)** The percentage of the correctly predicted cases, given the physicochemical change

266   induced upon mutation when polarity and charge states are considered. and light colors represent

267   successfully predicted depleting and enriching cases, respectively. The original data share for a given

268   class in the dataset is plotted in grey.

CONCLUSION

In the early months of SARS-CoV-2 pandemic, several fast and user-friendlt mutation modeling and scoring tools, such as FoldX and HADDOCK, were heavily used to predict the impact of Spike/ACE2 variations across the Spike-ACE2 interface. Expanding on these efforts, in this work, we benchmarked six fast and commonly used structure-based binding affinity predictors (FoldX, EvoEF1, MutaBind2, SSIPe, HADDOCK, and UEP) against the RBD-ACE2 DMS binding data. As a result, we observed that none of the predictors could produce a meaningful correlation with the experimental data (best correlation R-value -0.51 was obtained with FoldX). Even when a binary classification (binding enriching/depleting) was considered, the highest accuracy was obtained by FoldX with 64% success rate. Furthermore, all predictors had difficulties in predicting binding enriching mutations, especially the ones using conservation-based terms in their scoring. Finally, the most obvious biases in mispredictions were found to be toward volume and hydrophobicity changes, especially for HADDOCK and FoldX, respectively.

These observations suggest plenty of room to improve the conventional affinity predictors for guessing the variant-induced binding profile changes of host-pathogen systems, such as Spike-ACE2. To aid such improvements we provide our benchmarking data at https://github.com/CSB-KaracaLab/RBD-ACE2-MutBench with the option to visualize our mutant models at https://rbd-ace2-mutbench.github.io/ . We hope that our benchmarking study will guide the computational community for being prepared not only for combatting SARS-CoV-2-related health concerns but also other infectious diseases.

MATERIALS and METHODS

Interfacial DMS value selection

The original DMS sets contained 3,819 and 2,223 point mutations for RBD and ACE2, respectively. From this set, we isolated the interfacial 988 RBD-ACE2 point mutations, for the following residues (calculated over 6m0j[22] with PDBePISA[21] (Figure 1C)):

Twenty-six RBD positions: R403, K417, V445, G446, Y449, Y453, L455, F456, Y473, A475, G476, S477, Q484, G485, F486, N487, Y489, F490, Q493, G496, Q498, T500, N501, G502, V503, and Y505.

Twenty-six ACE2 positions: S19, Q24, T27, F28, D30, K31, H34, E35, E37, D38, Y41, Q42, L45, L79, M82, Y83, T324, Q325, G326, N330, K353, G354, D355, R357, A386, R393.

Structure-based binding affinity predictors

Below are the brief scoring description of each predictor used. Except UEP, all predictors explicitly model the mutation according to predictor's force field.

FoldX: The scoring function of FoldX is a linear sum of vdW energy (ΔG_{vdw}), hydrophobic (ΔG_{solvH}) and polar group desolvation (ΔG_{solvP}) energies, hydrogen bond energy from water molecules (ΔG_{wb}), hydrogen bond energy (ΔG_{hbond}), electrostatic energy (ΔG_{el}), the electrostatic contribution of different polypeptides ($\Delta G k_{on}$), entropic penalty for backbone (ΔS_{mc}), entropic penalty of the side chain (ΔS_{sc}), and steric overlaps (ΔG_{clash}) (Eq. 1). FoldX also has an option to include the contribution of water molecules to the binding affinity (FoldXwater).

$$E_{FoldX} = a*\Delta G_{vdw} + b*\Delta G_{solvH} + c*\Delta G_{solvP} + d*\Delta G_{wb} + e*\Delta G_{hbond} + f*\Delta G_{el} + g*\Delta G k_{on} + h*T$$

$$\Delta S_{mc} + k*T\Delta S_{sc} + l*\Delta G_{clash} \text{ (Eq. 1)}$$

EvoEF1: The scoring function of EvoEF1 contains van der Waals (E_{vdw}), electrostatics (E_{elec}),

hydrogen bond (E_{HB}), desolvation energies (E_{solv}), and the energy of a reference state (E_{ref})

(Eq. 2).

$$E_{EvoEF1} = [E_{vdw} + E_{elec} + E_{HB} + E_{solv}] - E_{ref} \text{(Eq. 2)}$$

MutaBind2 and **SSIPe**: use FoldX and EvoEF1, respectively, to explicitly model the desired

mutation. MutaBind2 further imposes relaxation and utilizes extra force field and contact-

based terms, together with a metric measuring the evolutionary conservation of the mutation

site. All these terms are incorporated into a random forest based scoring algorithm. SSIPe

uses EvoEF1 energy terms and residue conservation-related terms, extracted from iAlign[32]

and PSI-BLAST[33].

HADDOCK: In this work, we used HADDOCK water refinement to model the mutations. The

complexes then scored according to the sum of three terms, van der Waals, electrostatic, and

desolvation energy (Eq.3). [34]

$$E_{HADDOCK} = w*EvdW + w*Eelec + w*Edesolv \text{(Eq. 3)}$$

UEP: UEP predicts the impact of all possible interfacial mutations, when the position of

interest has interactions with at least two other residues (within 5Å range). The scoring

function of UEP expands on the statistically determined intermolecular contact potentials.

To run FoldX and EvoEF1, we used their stand-alone packages

(http://foldxsuite.crg.eu/products#foldx,   https://github.com/tommyhuangthu/EvoEF).

HADDOCK, MutaBind2, and SSIPe were run on their servers, as given in

https://milou.science.uu.nl/services/HADDOCK2.2/,

https://lilab.jysw.suda.edu.cn/research/mutabind2/   https://zhanggroup.org/SSIPe/.

MutaBind2, SSIPe, and UEP directly provide the binding affinity change predictions, whereas

for the rest we calculated the predicted binding affinity change according to Eq. 4:

$$\Delta\Delta G_{predicted} = \Delta G_{mut} - \Delta G_{wt} \text{ (Eq. 4)}$$

A mutation is evaluated as binding enriching if the predicted binding value change

($\Delta Score_{predicted}$) is <0 and binding depleting, if ($\Delta Score_{predicted}$) is >0.

Performance evaluation according to change in amino acid physical properties upon a

mutation

The predictions were evaluated from the perspectives of volume, hydrophobicity,

flexibility, and physicochemical property change upon mutation ($\Delta Property_{change}$ =

$Property_{mutation}$ - $Property_{wildtype}$, Table S2). The physicochemical properties considered were:

polar amino acids - N, Q, S, T, Y; non-polar amino acids - A, G, I, L, M, F, P, W, V, C; charged

amino acids - H, E, D, R, K. Success rate and metric evaluations were performed in Python

3.8.5 with Pandas, Numpy, seaborn, and Matplotlib libraries [35–40]. For each category, the

percentage of successfully predicted cases were calculated by Eq .5.

Success rate = Correct-Predictions/All-Predictions*100 (Eq. 5)

DATA AVAILABILITY

All results including the codes and notebooks are deposited in Github (https://github.com/CSB-KaracaLab/RBD-ACE2-MutBench) and the models and the scores can be visualized at https://rbd-ace2-mutbench.github.io/ .

SUPPLEMENTARY INFORMATION

Supplementary Information are submitted with the manuscript.

ACKNOWLEDGEMENTS

All the simulations and analyses were carried out in the HPC resources of Izmir Biomedicine and Genome Center. The authors would like to thank João P. G. L. M. Rodrigues for the critical reading of our manuscript and providing help in building our results visualization page.

FUNDING

This work was supported by EMBO Installation Grant (no. 4421), Young Scientist Award granted by the Turkish Science Academy, and TÜSEB Research Grant (no. 3933).

AUTHOR CONTRIBUTIONS

B.O. performed statistical analysis and RMSD calculations, generated structural and statistical figures, edited and finalized all the figures, prepared the Github page, and wrote the manuscript. E.Ş., C.Y., and M.M. performed predictor runs. E.Ş. calculated the physical property and binary success rates, prepared the Github page, contributed to writing Introduction and Methods & Materials sections. M.E. generated heatmap tables for success rate results and wrote the manuscript. M.K. generated heatmaps for the RMSD calculations

and predictor scores. M.O. performed the most enriching mutation analysis. N. A. and G. K.

prepared the visualization page on Github. A.B.B. and B.S. worked on the conceptualization

of the benchmark set. E.K. conceptualized the study, overlooked the project, and wrote the

manuscript.

CONFLICT OF INTEREST

The authors declare no competing interests.

REFERENCES

[1]   LeDuc JW, Barry MA. SARS, the First Pandemic of the 21st Century. Emerg
386   Infect Dis 2004;10:e26. https://doi.org/10.3201/EID1011.040797_02.
387   [2]   Durai P, Batool M, Shah M, Choi S. Middle East respiratory syndrome
388   coronavirus: transmission, virology and therapeutic targeting to aid in outbreak
389   control. Exp Mol Med 2015;47:e181. https://doi.org/10.1038/EMM.2015.76.
390   [3]   Platto S, Xue T, Carafoli E. COVID19: an announced pandemic n.d.
391   https://doi.org/10.1038/s41419-020-02995-9.
392   [4]   Li W, Moore MJ, Vasllieva N, Sui J, Wong SK, Berne MA, et al. Angiotensin-
393   converting enzyme 2 is a functional receptor for the SARS coronavirus. Nature
394   2003;426:450. https://doi.org/10.1038/NATURE02145.
395   [5]   Ali A, Vijayan R. Dynamics of the ACE2–SARS-CoV-2/SARS-CoV spike protein
396   interface reveal unique mechanisms. Sci Rep 2020;10.
397   https://doi.org/10.1038/s41598-020-71188-3.
398   [6]   CoVariants n.d. https://covariants.org/ (accessed June 27, 2022).
399   [7]   Chan KK, Dorosky D, Sharma P, Abbasi SA, Dye JM, Kranz DM, et al. Engineering
400   human ACE2 to optimize binding to the spike protein of SARS coronavirus 2.
401   Science (1979) 2020;369. https://doi.org/10.1126/SCIENCE.ABC0870.
402   [8]   Starr TN, Greaney AJ, Hilton SK, Ellis D, Crawford KHD, Dingens AS, et al. Deep
403   Mutational Scanning of SARS-CoV-2 Receptor Binding Domain Reveals
404   Constraints on Folding and ACE2 Binding. Cell 2020;182:1295-1310.e20.
405   https://doi.org/10.1016/j.cell.2020.08.012.
406   [9]   Delgado Blanco J, Hernandez-Alias X, Cianferoni D, Serrano L. In silico
407   mutagenesis of human ACE2 with S protein and translational efficiency explain
408   SARS-CoV-2 infectivity in different species. PLoS Comput Biol
409   2020;16:e1008450. https://doi.org/10.1371/journal.pcbi.1008450.
410   [10]   Rodrigues JPGLM, Barrera-Vilarmau S, M. C. Teixeira J, Sorokina M, Seckel E,
411   Kastritis PL, et al. Insights on cross-species transmission of SARS-CoV-2 from
412   structural modeling. PLoS Comput Biol 2020;16:e1008449.
413   https://doi.org/10.1371/journal.pcbi.1008449.
414   [11]   Sorokina M, M. C. Teixeira J, Barrera-Vilarmau S, Paschke R, Papasotiriou I,
415   Rodrigues JPGLM, et al. Structural models of human ACE2 variants with SARS-
416   CoV-2 Spike protein for structure-based drug design. Sci Data 2020;7:309.
417   https://doi.org/10.1038/s41597-020-00652-6.
418   [12]   Laurini E, Marson D, Aulic S, Fermeglia M, Pricl S. Computational Alanine
419   Scanning and Structural Analysis of the SARS-CoV-2 Spike Protein/Angiotensin-
420   Converting Enzyme 2 Complex. ACS Nano 2020;14.
421   https://doi.org/10.1021/acsnano.0c04674.
422   [13]   Gheeraert A, Vuillon L, Chaloin L, Moncorgé O, Very T, Perez S, et al. Singular
423   Interface Dynamics of the SARS-CoV-2 Delta Variant Explained with Contact
424   Perturbation Analysis. J Chem Inf Model 2022;62:3107–22.
425   https://doi.org/10.1021/ACS.JCIM.2C00350.
426   [14]   Schymkowitz J, Borg J, Stricher F, Nys R, Rousseau F, Serrano L. The FoldX web
427   server: An online force field. Nucleic Acids Res 2005;33.
428   https://doi.org/10.1093/nar/gki387.

429	[15]	Pearce R, Huang X, Setiawan D, Zhang Y. EvoDesign: Designing Protein–Protein
430		Binding Interactions Using Evolutionary Interface Profiles in Conjunction with
431		an Optimized Physical Energy Function. J Mol Biol 2019;431.
432		https://doi.org/10.1016/j.jmb.2019.02.028.
433	[16]	Zhang N, Chen Y, Lu H, Zhao F, Alvarez RV, Goncearenco A, et al. MutaBind2:
434		Predicting the Impacts of Single and Multiple Mutations on Protein-Protein
435		Interactions. IScience 2020;23. https://doi.org/10.1016/j.isci.2020.100939.
436	[17]	Huang X, Zheng W, Pearce R, Zhang Y, Zhang Y. SSIPe: Accurately estimating
437		protein-protein binding affinity change upon mutations using evolutionary
438		profiles in combination with an optimized physical energy function.
439		Bioinformatics 2020;36. https://doi.org/10.1093/bioinformatics/btz926.
440	[18]	Van Zundert GCP, Rodrigues JPGLM, Trellet M, Schmitz C, Kastritis PL, Karaca E,
441		et al. The HADDOCK2.2 Web Server: User-Friendly Integrative Modeling of
442		Biomolecular Complexes. J Mol Biol 2016.
443		https://doi.org/10.1016/j.jmb.2015.09.014.
444	[19]	Honorato R V., Koukos PI, Jiménez-García B, Tsaregorodtsev A, Verlato M,
445		Giachetti A, et al. Structural Biology in the Clouds: The WeNMR-EOSC
446		Ecosystem. Front Mol Biosci 2021;8.
447		https://doi.org/10.3389/fmolb.2021.729513.
448	[20]	Amengual-Rigo P, Fernández-Recio J, Guallar V. UEP: an open-source and fast
449		classifier for predicting the impact of mutations in protein-protein complexes.
450		Bioinformatics 2021;37. https://doi.org/10.1093/bioinformatics/btaa708.
451	[21]	Krissinel E, Henrick K. Inference of Macromolecular Assemblies from Crystalline
452		State. J Mol Biol 2007;372:774–97. https://doi.org/10.1016/j.jmb.2007.05.022.
453	[22]	Lan J, Ge J, Yu J, Shan S, Zhou H, Fan S, et al. Structure of the SARS-CoV-2 spike
454		receptor-binding domain bound to the ACE2 receptor. Nature 2020;581:215–
455		20. https://doi.org/10.1038/s41586-020-2180-5.
456	[23]	Wan Y, Shang J, Graham R, Baric RS, Li F. Receptor Recognition by the Novel
457		Coronavirus from Wuhan: an Analysis Based on Decade-Long Structural Studies
458		of SARS Coronavirus. J Virol 2020;94. https://doi.org/10.1128/jvi.00127-20.
459	[24]	Schrödinger LLC and DW. PyMOL n.d.
460	[25]	Integrated Development Environment for R. RStudio n.d.
461	[26]	A Language and Environment for Statistical Computing. R n.d.
462	[27]	Kolde R. Pheatmap: Pretty Heatmaps 2019.
463	[28]	Neuwirth E. RColorBrewer: ColorBrewer Palettes 2014.
464	[29]	Lin Z, Long H, Bo Z, Wang Y, Wu Y. New descriptors of amino acids and their
465		application to peptide QSAR study. Peptides (NY) 2008;29:1798–805.
466		https://doi.org/10.1016/j.peptides.2008.06.004.
467	[30]	Eisenberg D, Schwarz E, Komaromy M, Wall R. Analysis of membrane and
468		surface protein sequences with the hydrophobic moment plot. J Mol Biol
469		1984;179:125–42. https://doi.org/10.1016/0022-2836(84)90309-7.
470	[31]	Shapovalov MV, Dunbrack RL. A Smoothed Backbone-Dependent Rotamer
471		Library for Proteins Derived from Adaptive Kernel Density Estimates and
472		Regressions. Structure 2011;19:844–58.
473		https://doi.org/10.1016/j.str.2011.03.019.

474   [32]   Gao M, Skolnick J. iAlign: a method for the structural comparison of protein–
475   protein interfaces. Bioinformatics 2010;26:2259–65.
476   https://doi.org/10.1093/bioinformatics/btq404.
477   [33]   Altschul SF, Madden TL, Schäffer AA, Zhang J, Zhang Z, Miller W, et al. Gapped
478   BLAST and PSI-BLAST: A new generation of protein database search programs.
479   Nucleic Acids Res 1997;25. https://doi.org/10.1093/nar/25.17.3389.
480   [34]   Dominguez C, Boelens R, Bonvin AMJJ. HADDOCK: A Protein–Protein Docking
481   Approach Based on Biochemical or Biophysical Information. J Am Chem Soc
482   2003;125:1731–7. https://doi.org/10.1021/ja026939x.
483   [35]   Van Rossum G, Drake FL, Harris CR, Millman KJ, van der Walt SJ, Gommers R, et
484   al. Python 3 Reference Manual. vol. 585. 2009.
485   [36]   Harris CR, Millman KJ, van der Walt SJ, Gommers R, Virtanen P, Cournapeau D,
486   et al. Array programming with NumPy. Nature 2020;585.
487   https://doi.org/10.1038/s41586-020-2649-2.
488   [37]   Kluyver T, Ragan-Kelley B, Pérez F, Granger B, Bussonnier M, Frederic J, et al.
489   Jupyter Notebooks—a publishing format for reproducible computational
490   workflows. Positioning and Power in Academic Publishing: Players, Agents and
491   Agendas - Proceedings of the 20th International Conference on Electronic
492   Publishing, ELPUB 2016, 2016. https://doi.org/10.3233/978-1-61499-649-1-87.
493   [38]   Anaconda Software Distribution. Anaconda Documentation 2020.
494   [39]   The pandas development team. Pandas-dev/pandas: Pandas. Zenodo 2020.
495   [40]   Waskom M. seaborn: statistical data visualization. J Open Source Softw 2021;6.
496   https://doi.org/10.21105/joss.03021.
497