1   TITLE: A pipeline for assessing the quality of images and metadata from crowd-sourced databases.

2   AUTHORS: Jackie Billotte, M.S.

4   ABSTRACT

Crowd-sourced biodiversity databases provide easy access to data and images for ecological education

and research. One concern with using publicly sourced databases; however, is the quality of their

images, taxonomic descriptions, and geographical metadata. The method presented in this paper

attempts to address this concern using a suite of pipelines to evaluate taxonomic consistency, how well

geo-tagging fits known distributions, and the image quality of crowd-sourced data acquired from

iNaturalist, a crowd-sourced biodiversity database. Additionally, it provides researchers that use these

datasets to report a quantifiable assessment of the taxonomic consistency. The pipeline allows users to

analyze multiple images from iNaturalist and their associated metadata; to determine the level of

taxonomic identification (family, genera, species) for each occurrence; whether the taxonomy label for

an image matches accepted nesting of families, genera, and species; and whether geo-tags match the

distribution of the taxon described using occurrence data from the Global Biodiversity Infrastructure

Facility (GBIF) as a reference. Additionally, image quality is assessed using BRISQUE, an algorithm that

allows for image quality evaluation without a reference photo. Entries from the order Araneae (spiders)

are used as a case study. Overall, the results suggest that iNaturalist can provide large metadata and

image sets for research. Given the inevitability of some low-quality observations, this pipeline provides a

valuable resource for researchers and educators to evaluate the quality of iNaturalist and other crowd-

sourced data.

Keywords*: biodiversity, iNaturalist, GBIF, metadata, pipeline, database, community science*

                                                     INTRODUCTION

In the past ten years, biodiversity, conservation, and taxonomical research have increasingly utilized

community science initiatives, including virtual platforms of user-uploaded biodiversity observations

(Cull, 2021; Mesaglio & Callaghan, 2021; Ryan et al., 2018). These large, crowd-sourced biodiversity

databases contribute to scientific advancement, with posted observations providing evidence of

unknown species, surveillance of field sites, and newly documented animal behaviors (Wilson et al.,

2020). For animal groups that are difficult to locate in the wild or whose collection would prove too

time-consuming and costly, crowd-sourced observations could provide information on species ranges or

invasions. For example, the first occurrence of *Pseudeuophrymings* (Araneae: Salticidae: Euophryini),

outside its native range was documented by non-experts on biodiversity databases (Kaldari, 2019). Since

observations from crowd-sourced data are usually accompanied by geographic information, erratic

comparison of these observations against known ranges can help highlight observations made well

outside the known range. Streamlining the use of free and crowd-sourced biodiversity databases could

make the detection of new species faster and more efficient (Michonneau & Paulay, 2014; "What Is

GBIF?," 2021). iNaturalist, one such crowd-sourced biodiversity database, provides a large platform for

gathering global biodiversity data. Founded in 2008 by Nate Agrin, Jessica Kline, and Ken-ichi Ueda as

part of a graduate school project for the University of California, Berkeley School of Informatics Master's

project (Agrin et al., 2014), iNaturalist has grown in popularity, and now contains more than 68 million

observations. Using iNaturalist and its accompanying mobile app, users can post images of organisms

and provide a geo-tagged location for that observation. Once a user posts an image, an image-based

machine learning algorithm suggests a taxonomic identification. Users can then vote in agreement with

that identification or suggest an alternative identification until one proposed taxonomy receives enough

votes for general acceptance. The program labels observations with agreed-upon taxonomic

identification and higher quality images as "Research grade" (Agrin et al., 2014). Like iNaturalist, the

Global Biodiversity Information Facility (GBIF) is an open-access infrastructure that provides

observational data of species using a range of published sources (Michonneau & Paulay, 2014; "What Is

GBIF?," 2021). The observation records from GBIF come from participating institutions and publications.

The curated data are available publicly, but unlike iNaturalist, contributions are limited to only approved

organizations, making the data, in theory, more robust, but also more limited ("What Is GBIF?," 2021).

52   Image and metadata quality remains a concern when using crowd-sourced data (Cull, 2021;

Moudrý & Devillers, 2020). Though sites implement some quality control, the volume of entries prevents

more detailed scrutiny of the data. If the data are of high enough quality, iNaturalist could be used as a

digital alternative to physical collections for rigorous morphological comparisons (Mugford et al., 2021).

These tasks would require consistently labeled images, no duplicate entries, correct geo-tags, and image

quality high enough to permit accurate identification and comparison (Hochmairid et al., 2020).

Currently, researchers and educators must evaluate entry quality manually. Given the millions of

observations recorded for any given taxonomic group, this process is time and resource intensive and

represents the biggest barrier to using crowd-sourced data. This study seeks to address this barrier by

providing a pipeline to quantify and assess the quality of data currently available on iNaturalist using the

order Araneae as a case study (Figure 1). Much like a physical pipeline, pipelines allow for the output of

the computing process to automatically feed into the next process, allowing information to flow in one

direction.

Fully assessing datasets acquired from iNaturalist (and similar databases) can illuminate areas that may

still need to improve and how the research community may create a more accurate and robust

database.

Figure 1: Workflow for pipeline suite. Data is acquired from iNaturalist and GBIF. The first pipeline compares the taxonomic consistency of the iNaturalist data. The second assesses the quality of the images using pyBRISQUE, and the third compares the geo-tagging from the iNaturalist observations to those obtained by GBIF. Bold dashed lines represent transitions between pipelines in the suite of pipelines. Data frames and assigned variables will be passed between pipelines. All outputs are saved to the working directory as *.csv* files.

69   METHODS AND MATERIALS

Data Acquisition

I applied the pipeline to observations from iNaturalist for the order Araneae as a case study. Spiders

constitute a valuable, yet understudied order of invertebrates (Nyffeler et al., 1994; Schwerdt et al.,

2018). Difficulties associated with locating, observing, and collecting spider specimens partly account for

the deficit of data on species ranges and diversity, and the lack of information on habitat and behavior

(Cardoso et al., 2011). Community science initiatives (projects that partner researchers with community

volunteers) help researchers expand arachnid research while also providing public outreach and

education (Cull, 2021).

While this pipeline was originally meant to be used with iNaturalist, its potential use with other

databases necessitates acquiring images and their accompanying metadata before using the pipeline, as

each database varies on how users access data. For the Araneae case study, I searched for and

downloaded observations for each family under the order Araneae on iNaturalist on July 21, 2021

("INaturalist," 2014). I then searched for and downloaded observations classified only to the order level.

The search for each family and the order Araneae were performed separately due to the limit that

iNaturalist places on the amount of observation metadata that can be downloaded per query. The limit

is 200,000 observations. Even by separating taxon into families, iNaturalist queries cannot return results

with over 200,000 observations. For queries that exceed the 200,000-observation limit, modifications

were made to one of the following criteria: Verifiable, Threatened, Introduced, Native, and Popular.

Criteria in these selections can be selected as either "Any," "Yes," or "No." By selecting "Yes" in one

criterion, downloading the results, and then running the same query again but changing the criterion

selection to "No," the limit was no longer exceeded. Other selections are detailed in Figure 2. I obtained

GBIF occurrence coordinates and image URLs using the Search Occurrences function for the order

Araneae ("GBIF.Org," n.d.).

Figure 2: Option selections for downloading query results using the downloading function in iNaturalist. Part A) is the selections for Section 1. B) shows the selections for Section 3. No changes are made to the default settings in Section 2.

The pipeline uses an input file in a *.csv* format (a sample input file can be downloaded at

https://github.com/jackiebillotte/Observation_Database_Assesment in the Sample Data file). The input

file for iNaturalist observations and GBIF occurrences must include columns for observation ID, time of

observation, date of observation, time zone, latitude, longitude, the images' current grade label, the

image URLs, taxonomic guess provided by the machine learning algorithm, and taxonomic labels at the

family, genus, and species level. The input file is read into Rstudio for analysis. The resulting data frame

for iNaturalist observations is queried for duplicate observations. Observations are considered duplicate

entries if two observations have the same time of observation and location (Hochmairid et al., 2020).

iNaturalist does not currently provide a method that allows users to bulk download images. Instead, the

image URLs are extracted from the input file into a separate URL list. Images are downloaded using the

list of URLs with an original bash script included in the pipeline (RStudio, 2020).

Taxonomic Consistency

To evaluate the consistency of the taxonomic data from iNaturalist, a taxonomic reference file is

needed. Several databases exist that can provide necessary taxonomic information on specific groups of

animals, such as The Global Lepidoptera Names Index (Beccaloni et al., 2003), and The Mammal

Diversity Database (Zenodo, 2022), and The Reptile Database (Uetz & Hallermann, 2021). This case study

used an updated species list from the World Spider Catalogue (WSC) downloaded on July 30th, 2021, as a

taxonomic reference. WSC collects arachnology literature and publications and maintains updated

taxonomic lists (Natural History Museum Bern, 2019).

The input file for taxonomic reference should include columns for the highest classification being used in

the pipeline, with consequent columns for all lower classifications (Supplemental 2). Taxonomic

identification for the highest order of classification and all subsequent lower classifications are

compared to the taxonomic reference file, respectively.

Figure 3: Taxonomic consistency workflow. Each observation could earn a maximum of three-points. Points were award as follows: iNaturalist observations were checked for family-level identification. Each level of taxonomic label (i.e. Family, Genus, and Species) was scored based on three criteria: 1) the label was present, 2) the label was an accepted name for that level of classification, 3) it agreed with all higher and lower taxonomic classifications. If these conditions were met, the observation was awarded an additional point. Lastly, observations were checked for species-level identification. To calculate the percent-correct the total number of observations positive for a level of identification was multiplied by three and then divided into the sum of all the scores for observations with each level of taxonomic identification.

The percentage of observations that include taxonomic labels at each level of classification and the

consistency of the assigned taxonomic names for each observation is then analyzed. If the identification

given for an observation matches the recognized taxonomic names at the appropriate level and was

consistent with accepted higher order names as they appear on the taxonomic reference file, then it is

recorded as correct. Correct labels are given one point per name. If the name on the observation is

either entered incorrectly, entered at the incorrect taxonomic level (such as the genus taxonomy being

recorded as the species), or does not align with the accepted higher order labels (i.e., the genus does

not belong to the family assigned to the observation) it is recorded as incorrect (Figure 3). Incorrect or

missing labels are given a score of zero. The awarded points are then divided by the number of

taxonomic levels, to produce an overall score (Figure 3).

Geo-Tagging

To assess geo-tagging data of observations, coordinates from iNaturalist and GBIF are filtered through

the *Clean Coordinates* R-package, which removes coordinates with common errors found in biological

and paleontological datasets (Zizka et al., 2019) These errors include locations at museum and zoo

facilities, zero set coordinates, and coordinates that fall outside of any coordinate values, such as a

latitude larger than 90°(Zizka et al., 2019).

Lists of the genera and species for observations from GBIF and iNaturalist are compiled and cross-

referenced so only families, genera, and species that appear on both remain. A subset of coordinate

data for both GBIF and iNaturalist are created, first by genera and then by species. Comparisons are

made at the family, genus, and species levels. A Raster file is generated using GBIF occurrences in the R-

program Raster and the raster polygon is divided into a grid GBIF and iNaturalist coordinates are

converted to spatial points and placed on the grid. A confusion matrix is produced using the *confmat*

function in the RStudio package GMDH2 (Dag et al., 2021). A confusion matrix is a type of contingency

table that can be used as a performance test for classifications (Fawcett, 2006). on the results of each

cell using the following parameters from Austen et al. (2018) (Figure 4):

• True Positive: GBIF observation is present and iNaturalist
• True Negative: No observations present
• False Positive: iNaturalist observation present but not GBIF
• False Negative: GBIF observation present but not iNaturalist
Accuracy and precision scores from the confusion matrix are reported for each taxonomic level.

Figure 4: Geo-tagging Workflow. Plotting Coordinates: GBIF occurrence records was cleaned using the R-package, *Clean Coordinates.* Comparisons of occurrence records (including latitudes and longitudes) for iNaturalist observations were made using the family-level of identification, the genus-level of identification, and the species-level of identification. For each taxon rank, occurrence data was obtained from the Global Biodiversity Information Facility (GBIF) for the order Araneae and subsetted in Rstudio by taxon rank. The subsetted occurrence records were used to create polygon maps, that were then converted to raster maps. GBIF and iNaturalist occurrence records were added to the cells of the raster map. A confusion matrix was used to calculate the accuracy and precision of the iNaturalist occurrence records.

Image Quality

Image quality is assessed using the python version of the MatLab program BRISQUE, *pybrisque*

(Gumbira, 2018). The BRISQUE algorithm scores the distortion in an image without the use of a

reference image, to create a final quality score based on a comparison between the image and a default

set of natural images (which are images captured directly from a camera without any post-processing)

with similar distortions (Mittal et al., 2012). Images are evaluated and assigned a score that usually falls

between 0 (higher quality) to 100 (lower quality) (Figure 5). Not all observations from iNaturalist

included images with copyright permissions that allow them to be downloaded and some observations

included multiple images, each with an individual score. Images are grouped by the highest shared

taxonomic order and an average score is reported. This process is repeated for images with

identification at lower taxonomic levels and a mean average score is calculated.

In addition to an overall average score, the image scores for the Araneae dataset are given at the family,

genus, and species levels. To determine if a relationship existed between the level of taxonomic

identification and the BRISQUE image score, I examined the normality of the data using Q-Q plots,

residual plots, and a Shapiro-Wilks test. As the data were non-normally distributed, I used a Kruskal-

Wallace test to compare the scores from the GBIF images, images with at most a family identification,

genus identification, and species identification. All means are presented with a ±1 standard error of the

mean.

Figure 5: BRISQUE Image Quality. BRISQUE evaluates images without the need for a reference photo. The higher the score the lower the quality of the image. A comparison between images with a low BRISQUE score (A and B) and high BRISQUE scores (C and D). A was given a BRISQUE score of 2.932 and B was given a score of 3.042, while C was given a BRISQUE score of 67.155 and D was given a BRISQUE score of 60.657. A side-by-side comparison of these images demonstrates how visual assessment of image quality can be inaccurate and subject to individual preference and vision. Providing a BRISQUE score helps to quantify the quality of an image used. [A: Dunbar, 2014), B: (Miseroy, 2017), C: (Cuarenta, 2017), D: (veravilla, 2017).]

Data Acquisition

For the order Araneae, I found 158,129 downloadable observations on iNaturalist. I found 78,310 unique

observations for the order Araneae on iNaturalist. Of the 129 families in the order Araneae recognized

by the WSC, 122 had observations (Natural History Museum Bern, 2019). I found no observations for

Archoleptonetidae (though, as of August 2021 one observation has been added), Barychelidae,

Huttoniidae, Mecicobothriidae, Myrmecicultoridae, Synaphridae, and Tetrablemmidae. Users of

iNaturalist identified 49.91% of observations to at least the family level and so could be found searching

by a specific family. Agelenidae ("Grass spiders") had the most observations, with 41,716. A mean

number of observations per family was 259.56 ±19.86. Archoleptonetidae and Penestomidae both had

only one observation.

Taxonomic Consistency

I found 156,842 of the downloadable observations with a family-level identification, of which 79.15%

were consistent with the taxonomic families listed on WSC. 99.86% of the 58,241 observations identified

to the genus level and 99.74% of the 27,500 observations identified to the species level were consistent

with established taxonomic names.

Observations may have more than one image associated with them, each with separate metadata. The

metadata associated with each image is referred to as that image's "record." I removed 2,170 of

425,950 records after cleaning the coordinates. iNaturalist observations with a family level identification

were 49.95% accurate and 99.90% precise. In terms of the geo-tagged coordinates, "accuracy" refers to

how often the coordinates from iNaturalist are present or absent in agreement with the coordinates

from GBIF and are calculated using the following equation:

189
$$Accuracy = \frac{(True\ Positive + True\ Negative)}{Total\ Observations}$$

190 'Precision" refers to the rate at which iNaturalist and GBIF coordinates are both present in cells on the

191 grid, to the total number of grid scales in which iNaturalist coordinates are present:

192
$$Percision = \frac{True\ Positive}{(True\ Positive + False\ Positive)}$$

I found comparable results at the genus and species levels, with the genus level resulting in an accuracy

of 49.97% and precision of 99.85%, and the species level resulting in an accuracy of 63.10% and

precision of 99.87%.

Image Quality

pyBRISQUE evaluated 118,834 images. The median image quality score was 29.00 (n = 115,093, range =

70.32637). Images of Orsolobidae received the highest average BRISQUE score (n = 7, median= 36.95,

range= 1.87), with a higher score indicating lower quality images. The family with the highest score and

> 10 observations was Phyxelididae (n = 22, median = 36.94). Atracidae had the lowest (n = 176, median

= 21.44, range = 26.92) and was also the family with the lowest score and > 10 observations.

202   DISCUSSION

Here, I present a method for assessing the metadata and image quality for data acquired from

iNaturalist, a crowd-sourced biodiversity database. Using the order Araneae, both the metadata and

images associated with observations in iNaturalist demonstrate that this platform provides a diverse

dataset for spiders (Order Araneae). This data assessment method was able to determine that, with few

exceptions, nearly every family in the order had some level of representation on iNaturalist. Automizing

a check of taxonomic labels against accepted taxonomic names permits the quick removal of

occurrences with inconsistent labels. Additionally, it provides researchers that use these data to report a

quantifiable assessment of the taxonomic consistency in a dataset.

Similarly, comparing geo-tagging data from iNaturalist observations to GBIF occurrences allows for a

quantifiable evaluation of that data via the confusion matrix results. Another benefit to using this

pipeline to compare geo-tagging data is the insight into the accuracy of the observations' taxonomic

labels it can provide. Observations that fall outside the raster generated by the occurrence data from

GBIF can be seen as outside the area where that organism has previously been shown to live. This could

also aid in determining if the iNaturalist taxonomic labels are accurate. Conversely, this method of

evaluating geo-tagging could help identify if a species was observed within a new range. While an

occurrence could fall outside of the GBIF raster for reasons unrelated to range expansion, once the

raster polygon is created using the GBIF occurrences, iNaturalist observations outside of the raster are

easily separated from the dataset and further investigated.

One major concern with using publicly sourced biodiversity photos is that without knowing the quality of

the images, reproducibility is difficult. iNaturalist categorizes images as either "research grade," "needs

ID," or "NA." iNaturalist's current method for assigning an observation as "research grade" or not

"research grade" requires that an observation reach a two-thirds consensus from users to confirm

identification (Agrin et al., 2014). Images currently marked "needs ID" could receive the consensus on

their taxonomic idea and be relabeled as "research grade." I found relatively consistent image quality

across families and between research grade and non-research grade observations ("needs ID" and

"NA"). While this system of categorization does provide some information on the quality of an image,

presenting a mean score for image sets on databases may help clarify the results researchers obtain

using iNaturalist (or another database) images, especially in the cases of machine learning programs.

The method presented for image assessment could also be used to set a threshold score, allowing only

images that meet a specific quality standard to be included in a set of images.

Additionally, this study highlights the importance of using quantifiable image quality assessment tools

like BRISQUE, especially for methods that use images for morphological evaluation of computer learning

software for identification. While not conducted here, it would be beneficial to perform a BRISQUE

assessment on any image used for research and to report the score or average score of images,

especially when sourced from public collections. Image quality could impact evaluations of coloring and

morphological structures. From a visual assessment of an image, the quality of that image may not be

obvious. Additionally, visual assessment of an image may be subject to personal bias or visual acuity

(Wang et al., 2004). Providing a quantitative score, such as a BRISQUE does, permits a uniform

understanding of the images being used. In the future, it would be beneficial to compare the BRISQUE

scores of images obtained from iNaturalist to those on image databases that only host published

images, such as GBIF.

One drawback to using crowd-sourced observations, however, is how usage patterns could affect the

metadata and number of high-quality images available for a specific group of animals. For example,

differences in the number of observations per family of Araneae might result from geographic areas

with a higher or lower user number of iNaturalist users, variation in numbers of people with access to

camera phones or reflect actual relative abundances.

Increasing the number of observations at the family level or lower is the best way to increase the

number of images and volume of metadata available to researchers from iNaturalist, since a lack of

identification, lack of consensus for that identification, or no lower order identification represents the

most common deficits for most observations. To help increase the diversity and quality of the

observations, researchers should employ methods to contribute to iNaturalist, such as educational

initiatives that engage students with the platform and encourage them to contribute images or by

making a habit of offering taxonomic identifications to images that require taxonomic identification.

For researchers to become more engaged with iNaturalist, however, some changes may be necessary.

For example, limits on how many observations could be downloaded at one time make broad studies,

such as the one using Araneae, more time-consuming than necessary. iNaturalist has recently launched

an Amazon Web Services (AWS) platform, but this platform does not include the image files from the

database, which limits the type of analyses researchers can conduct. In addition to a more economical

method to bulk download images, incorporating an image assessment algorithm like BRISQUE into the

metadata would increase the utility of iNaturalist to researchers. Providing a BRISQUE score would allow

users to filter downloads for a specific image quality without having to run the algorithm on large image

datasets. Finally, while not an issue for iNaturalist observations, problems exist in downloading images

from GBIF in bulk and keeping the image file names associated with the taxon. Another database may

experience similar problems.

Several databases are available for researchers to access occurrence data and images (Cull, 2021; Mason

Heberling et al., 2020; Moudrý & Devillers, 2020; Shirey et al., 2019). iNaturalist provides a user-friendly,

crowd-sourced database of images with the potential for broad research applications (Hochmairid et al.,

2020; Mesaglio & Callaghan, 2021; Nugent, 2020). It should be noted that any research that uses images

or metadata from iNaturalist should include methods that screen the data for duplicates, incorrectly

geo-tagged observations, and image quality.

The usefulness of this pipeline may be limited for systems with few observations on iNaturalist or GBIF

(who must have at least three occurrences to generate a raster polygon). Systems that lack a taxonomic

database could also present a challenge since this would require the user to generate the taxonomic

reference file from scratch. An alternative to creating a *de novo* taxonomic reference is sourcing

taxonomic names from an established database such as the Integrated Taxonomic Information System

(*Integrated Taxonomic Information System*, n.d.). GBIF also provides a taxonomic database. More

specialized taxonomy databases could also serve as a source of taxonomic comparison. The Mammal

Diversity Database is maintained by the American Society of Mammologists and provides an updated list

of known mammal taxonomic names and species. Similar initiatives exist for amphibians, ants (AntWeb),

birds (Avibase, IOC World Bird List), fungi, and reptiles. General and specialized databases could be

cross-referenced or used independently to generate the reference needed to assess taxonomic

consistency.

Taken together, this study demonstrates that iNaturalist can provide large metadata and image datasets

for research. This pipeline can be used to assess the taxonomic consistency, relationship to known

distributions, and image quality of large datasets of crowd-sourced data. This is a reliable method to

quickly analyze the data quality for specific taxa. With appropriate quality controls in place, the wealth

of knowledge supplied through crowd-sourced biodiversity databases can more reliably be used for

scientific discovery.

<u>Acknowledgments</u>

I would also like to acknowledge and thank the reviewers of this paper, Matthias Foellmer, Clive

Hambler, and Catherine Scott for their thoughtful comments and efforts in

improving our manuscript. I would like to thank Ruth Hufbauer, Richard Reading, and Lorna McCallister.

for providing comments on this manuscript.

<u>Conflict of Interest Statement</u>

I have no conflicts of interest to disclose.

<u>Authors Contribution</u>

The author confirms sole responsibility for the following: study conception and design, data collection,

analysis and interpretation of results, and manuscript preparation.

Data Availability

The R markdown code, iNaturalist metadata, GBIF metadata, and taxonomic data from World Spider

Catalog can be found at https://github.com/jackiebillotte/Observation_Database_Assesment along with

formatted examples of the data used.

References

Agrin, N., Kline, J., & Ueda, K. (2014). *Final Project Write-up: iNaturalist*.

Austen, G. E., Bindemann, M., Griffiths, R. A., & Roberts, D. L. (2018). Species identification by
conservation practitioners using online images: Accuracy and agreement between experts.
PeerJ, *2018*(1), 1–19. https://doi.org/10.7717/peerj.4157

Beccaloni, G., Scoble, M., Kitching, I., Simonsen, T., Robinson, G., Pitkin, B., Hine, A., Lyal, C., &
(Editors). (2003). *The Global Lepidoptera Names Index (LepIndex)*. World Wide Web Electronic
Publication. https://www.nhm.ac.uk/our-science/data/lepindex/lepindex/

Cardoso, P., Erwin, T. L., Borges, P. A. V, & New, T. R. (2011). The seven impediments in
invertebrate conservation and how to overcome them. *Biological Conservation*, *144*, 2647–
2655. https://doi.org/10.1016/j.biocon.2011.07.024

Cull, B. (2021). Potential for online crowdsourced biological recording data to complement
surveillance for arthropod vectors. *PLoS ONE*, *16*(4 April).
https://doi.org/10.1371/journal.pone.0250382

Dag, O., Karabulut, E., Alpar, R., & Kasikci, M. (2021). *GMDH2: Binary Classification via GMDH-Type*
Neural Network Algorithms. CRAN.

Fawcett, T. (2006). An introduction to ROC analysis. *Pattern Recognition Letters*, *27*(8), 861–874.
https://doi.org/10.1016/j.patrec.2005.10.010

GBIF.org. (n.d.). In *GBIF Occurrence Download*.

Gumbira, Akbar. (2018). *pybrisque* (1.0).

Hochmairid, H. H., Scheffrahn, R. H., Basille, M., & Booneid, M. (2020). *Evaluating the data quality*
of iNaturalist termite records. https://doi.org/10.1371/journal.pone.0226534

iNaturalist. (2014). *Reference Reviews*, *28*(8), 36–38. https://doi.org/10.1108/rr-07-2014-0203

Integrated Taxonomic Information System. (n.d.). Retrieved February 9, 2022, from
https://www.itis.gov/

Kaldari, R. (2019). New records of the exotic jumping spider Pseudeuophrys erratica (Araneae:
Salticidae: Euophryini) in the United States. *Peckhamia 188.1*, *August*, 1–3.

Mason Heberling, J., Miller, J. T., Noesgaard, D., Weingart C ⬚, S. B., Schigel, D., & Soltis, D. E.
(2020). Data integration enables global biodiversity synthesis. *The Proceedings of the National*
Academy of Sciences , *118*(6). https://doi.org/10.1073/pnas.2018093118/-/DCSupplemental

Mesaglio, T., & Callaghan, C. T. (2021). An overview of the history, current contributions and future
outlook of iNaturalist in Australia. *Wildlife Research*. https://doi.org/10.1071/WR20154

Michonneau, F., & Paulay, G. (2014). *Using iNaturalist to engage the public and learn more about*
echinoderms. *30*(1), 29–31. http://dx.doi.org/10.6084/m9.figshare.1040435

Mittal, A., Moorthy, A. K., & Bovik, A. C. (2012). No-reference image quality assessment in the
spatial domain. *IEEE Transactions on Image Processing*, *21*(12), 4695–4708.
https://doi.org/10.1109/TIP.2012.2214050

Moudrý, V., & Devillers, R. (2020). Quality and usability challenges of global marine biodiversity
databases: An example for marine mammal data. *Ecological Informatics*, *56*(December 2019).
https://doi.org/10.1016/j.ecoinf.2020.101051

Mugford, J., Moltchanova, E., Plank, M., Sullivan, J., Byrom, A., & James, A. (2021). Citizen science
decisions: A Bayesian approach optimises effort. *Ecological Informatics*, *63*, 101313.
https://doi.org/10.1016/j.ecoinf.2021.101313

Natural History Museum Bern. (2019). *NMBE - World Spider Catalog*. World Spider Catalog. Version
20.0. https://doi.org/10.24436/2

Nugent, J. (2020). iNaturalist: Citizen Science for the Digital Age. *The Science Teacher*, *87*(8), 58.

Nyffeler, M., Sterling, W. L., & Dean, A. A. (1994). How Spiders Make a Living. In *Environ. Entomol*
(Vol. 23, Issue 6).

RStudio, T. (2020). RStudio: Integrated Development for R. In *RStudio, PBC*.

Ryan, S. F., Adamson, N. L., Aktipis, A., Andersen, L. K., Austin, R., Barnes, L., Beasley, M. R., Bedell,
K. D., Briggs, S., Chapman, B., Cooper, C. B., Corn, J. O., Creamer, N. G., Delborne, J. A.,
Domenico, P., Driscoll, E., Goodwin, J., Hjarding, A., Hulbert, J. M., … Dunn, R. R. (2018). The
role of citizen science in addressing grand challenges in food and agriculture research.
Proceedings of the Royal Society B: Biological Sciences, *285*(1891).
https://doi.org/10.1098/rspb.2018.1977

Schwerdt, L., Elena de Villalobos, A., & Miles, F. P. (2018). Spiders as potential bioindicators of
mountain grasslands health: the Argentine tarantula Grammostola vachoni (Araneae,
Theraphosidae). *Wildlife Research*, *45*(1), 64. https://doi.org/10.1071/wr17071

Shirey, V., Seppälä, S., Branco, V. V., & Cardoso, P. (2019). Current GBIF occurrence data
demonstrates both promise and limitations for potential red listing of spiders. *Biodiversity*
Data Journal, *7*. https://doi.org/10.3897/BDJ.7.e47369

Uetz, P., & Hallermann, J. (2021). *The Reptile Database*. Zoological Museum Hamburg.
https://reptile-database.reptarium.cz/

What is GBIF? (2021). In *GBIF: The Global Biodiversity Information Facility*. gbif: The Global
Biodiversity Information Facility

Wilson, J. S., Pan, A. D., David, ·, General, E. M., & Koch, J. B. (2020). More eyes on the prize: an
observation of a very rare, threatened species of Philippine Bumble bee, Bombus irisanensis,
on iNaturalist and the importance of citizen science in conservation biology. *Journal of Insect*
Conservation, *24*, 727–729. https://doi.org/10.1007/s10841-020-00233-3

Zenodo. (2022). *Mammal Diversity Database (Version 1.8)*. Mammal Diversity Database.
https://www.mammaldiversity.org/

Zizka, A., Silvestro, D., Andermann, Tobias Azevedo, J., Duarte Ritter, Camila Edler, D., Farooq, H.,
Herdean, A., Ariza, M., Scharn, R., Svanteson, S., Wengstrom, N., Zizka, V., & Antonelli, A.
(2019). CoordinateCleaner: standardized cleaning of occurrence records from biological
collection databases. *Methods in Ecology and Evolution*, *10*, 7. https://doi.org/10.1111/2041-
210X.13152

382