NetAct: a computational platform to construct core transcription factor regulatory

networks using gene activity

[1,#]Kenong Su, [2,3,#]Ataur Katebi, [4]Vivek Kohar, [3,5]Benjamin Clauss, [2,3]Danya Gordin, [6]Zhaohui S.

Qin, , [7,8,9]R. Krishna M. Karuturi, [7,8]Sheng Li, [2,3,4,7*]Mingyang Lu

[1]Department of Biomedical Informatics, Emory University, Atlanta, GA 30322, USA.

[2]Department of Bioengineering, Northeastern University, Boston, MA 02115, USA.

[3]Center for Theoretical Biological Physics, Northeastern University, Boston, MA 02115, USA

[4]The Jackson Laboratory, Bar Harbor, ME 04609, USA.

[5]Genetics Program, Graduate School of Biomedical Sciences, Tufts University, Boston, MA

02111, USA.

[6]Department of Biostatistics and Bioinformatics, Emory University, Atlanta, GA 30322, USA.

[7]The Jackson Laboratory for Genomic Medicine, Farmington, CT 06032, USA.

[8]Dept of CSE, University of Connecticut, Storrs, CT

[9]Graduate School of Biological Sciences & Eng., University of Maine, Orono, ME

[*] To whom correspondence should be addressed, m.lu@northeastern.edu

[#] Equal contributions

Abstract

A major question in systems biology is how to identify the core gene regulatory circuit that governs the decision-making of a biological process. Here, we develop a computational platform for constructing core transcription-factor regulatory networks, named NetAct, using both transcriptomics data and literature-based transcription factor-target databases. NetAct robustly infers the activities of regulators using target expression, constructs networks based on transcriptional activity, and integrates mathematical modeling for validation. We show that NetAct outperforms existing algorithms in inferring transcriptional activity from our benchmark tests. We illustrate the application of NetAct to model networks driving TGF-β induced Epithelial-Mesenchymal transition and macrophage polarization.

Keywords

Background

One of the major goals of systems biology is to infer and model complex gene regulatory networks (GRNs) which underpin the biological processes of human disease[1–6]. Particularly important are those gene networks that control decisions regarding cellular state transitions (*e.g.*, replicative to quiescent[7–9], epithelial to mesenchymal (EMT)[10], pluripotent to differentiated[11,12]), given the central importance of such regulatory processes to both healthy development as well as diseases such as cancer.

To construct and model GRNs associated with the biological process under investigation, researchers have developed two primary systems biology approaches. The first is a *bottom-up approach*, in which researchers focus on identifying a core GRN composed of a small set of master regulators[13]. Once the core GRN is obtained, mathematical modeling is then applied to simulate the gene expression dynamics[14–17], which helps elucidate the potential gene regulatory mechanism driving the biological process in question. The current gold standard method for synthesizing a core GRN is by compiling data via an extensive literature search, *e.g.*, in these studies[18–20]. While this works well for systems where sufficient knowledge has been gained and accumulated, it is less effective in cases where key component genes and regulatory interactions have yet to be discovered. Due to the rapidly increasing numbers of biomedical publications, manual synthesis of literature information has become extremely time-consuming and prone to human error in data interpretation. One way to address the labor-intensive issue is to rely on existing manually curated databases, such as KEGG[21] and Ingenuity Pathway analysis (IPA)[22]. However, these databases often compile gene regulatory interactions from different tissues, species, or diseases. Therefore, it is hard to obtain context-specific interactions directly from these types of databases.

The second approach adopts a *top-down* perspective, in which researchers apply bioinformatics and statistical methods on genome-wide transcriptomics and/or genomics data to infer large-scale GRNs[13]. These data-driven methods are ideal for obtaining a global picture of gene regulation and the overall structure of gene-gene interactions. This approach also helps to characterize key regulators and regulatory

interactions between genes that are specific to the biological context of the study. However, conventional

bioinformatics methods for gene network inference are usually not designed to identify an integrated

working system. These methods typically rely on significance tests to determine the nodes and edges of a

gene network, yet it is rare to evaluate whether the constructed gene network is capable of operating as a

functional dynamical system[23]. Moreover, many statistical methods work well to identify the association

between genes, but not their causation, thus limiting the application value of the top-down approach in

characterizing gene regulatory mechanisms.

To overcome the above-mentioned issues, a relatively new approach has been explored in several

studies in which the top-down and bottom-up approaches are integrated to infer and model a core GRN[23–

30]. In this combined approach, a GRN is constructed with bioinformatics tools using genome-wide gene

expression data, followed by mathematical modeling of the GRN to simulate gene expression steady states

and explore their similarity with biological cellular states. The simulations can help validate the accuracy

of the constructed GRN and further clarify the regulatory roles of genes and interactions in driving cellular

state transitions. This combined approach helps to discover existing and new regulatory interactions specific

to the cell types and experimental conditions under study. Additionally, it helps pinpoint master regulators

and reduce the system's overall complexity. The GRN modeling is particularly crucial for cases with non-

trivial cellular state transitions, such as multi-step state transitions as observed in Epithelial-Mesenchymal

transition (EMT)[31], and bifurcating state transitions, as observed in stem cell differentiation[32]. This is

because the GRNs constructed by the top-down approach are not guaranteed to capture these state transition

patterns. So far, to the best of our knowledge, there is no computational platform available that utilizes this

combined approach for systematic GRN inference and modeling.

In this study, we introduce a computational platform, named NetAct, for modeling a core GRN of key

transcription factors (TFs) using both transcriptomics data and a literature-based TF-target database.

Integrating both resources allows us to take full advantage of the existing knowledgebase of transcriptional

regulation. NetAct adopts the combined top-down and bottom-up systems biology approaches, designed

specifically to address the following two major issues.

First, many network inference methods rely on correlations of gene expression data, yet the actual

transcriptional activities of many master regulators may not be reflected in their gene expression. Instead,

the activity may be better associated with either their protein level, the level of a certain posttranslational

modification, localization, or their DNA binding affinity. As a result, the master regulators with weak

correlations between expression level and transcriptional activity will likely be discarded in the network.

Some algorithms have been developed to infer the activities of regulators from transcriptomics data, such

as VIPER[33], NCA[34], AUCELL[35]. However, most of these algorithms 1) are not designed for gene network

modeling, or 2) still rely on coexpression of TF and targeted genes, or 3) do not take advantage of known

regulatory interactions from the literature, hindering their applicability as automated algorithms for generic

use.

Second, conventional mathematical modeling approaches have been applied over the years to simulate

the dynamics of a GRN, yet they are not particularly effective in analyzing core GRNs. A popular method

models the gene expression dynamics of a system using the chemical rate equations that govern the

associated gene regulatory processes. However, it is difficult to directly measure most of the kinetic

parameters of a GRN. Although some parameter values can be learned from published results, many others

are often based on educated guesses which significantly limits the predictive power of mathematical

modeling. Moreover, a core GRN is not an isolated system. Thus, an ideal modeling paradigm should also

consider other genes that interact with the core network. To address this infamous parameter issue, we have

developed the modeling algorithm RACIPE[26,36] in previous work that analyzes a large ensemble of

mathematical models with random kinetic parameters. RACIPE has been applied to model the dynamical

behavior of gene regulatory networks of different biological processes, such as Epithelial-Mesenchymal

transition[23,26], cell cycle[37], stem cell differentiation[38].

The new NetAct platform addresses the above-mentioned issues by (1) inferring the activities of TFs
for individual samples using the gene expression levels of their targeted genes, (2) identifying the regulatory
interactions between two TFs based on their activities rather than their expressions, (3) and subsequently
simulating the constructed core GRN with RACIPE to validate and evaluate the gene expression dynamics
of the core GRN. In the remainder of the manuscript, we will describe in detail the NetAct platform,
extensive benchmark tests for TF-target databases and TF activity inference, and two examples of
applications to model GRNs with time series gene expression data.

Results

We developed a computational systems-biology platform, named NetAct, to construct transcription
factor (TF)-based GRNs using TF activity. The method uniquely integrates both generic TF-target
relationships from literature-based databases and context-specific gene expression data. NetAct also
integrates our previously developed mathematical modeling algorithm RACIPE to evaluate whether the
constructed network functions properly as a dynamical system, and to evaluate the roles of every gene in
the network by in-silico perturbation analysis. NetAct contains three major steps: (1) identifying the core
TFs using gene set enrichment analysis (GSEA)[39] with an optimized TF-target gene set database (Fig. 1a);
(2) inferring TF activity (Fig. 1b); (3) constructing a core TF network (Fig. 1c). Then, the network is
validated and analyzed by simulating its dynamics using mathematical modeling by RACIPE. Details of
each step is given in the Methods section and Supplemental Material. In the following, we demonstrate how
we optimized the NetAct algorithm, compared its performance of activity inference with three existing
methods on in-silico gene expression data, and applied the network modeling approach to two biological
datasets.

Literature-based TF-target relationships facilitate TF inference

To establish a comprehensive gene set database containing TF-target relationships, we considered data

from different types of resources (Table S1). They are (D1) a literature-based database, consisting of data

from TRRUST[40], RegNetwork[41], TFactS[42], and TRED[43]; (D2) a gene regulatory network database

FONTOM5[44], whose interactions are extracted from networks constructed using RNA expression data from

394 individual tissues; (D3) a database derived from resources of putative TF binding targets, including

ChEA[45], TRANSFAC[46], JASPAR[47], and ENCODE[48]; and (D4) a database derived from motif-enrichment

analysis, RcisTarget[49]. These databases have been frequently used to study transcriptional regulations and

have already been utilized for network construction[26,50].

We evaluated the performance of these databases by GSEA on a benchmark dataset. This benchmark

dataset, denoted as *set B*, consists of a compilation of 11 microarray and 27 RNA-Seq gene expression data

(Table S2). Each of these datasets contains at least three samples under the normal condition (control) and

three samples under the treatment condition in which a specific TF is treated by knockdown (KD). We

applied GSEA (with slight modification, details in Methods) on the set *B* to evaluate whether the enrichment

analysis can detect the perturbed TFs. The underlying assumption is that, with a better TF-target gene set

database, GSEA will be more likely to detect the corresponding perturbed TFs. For each TF-target database

and each gene expression data in set *B*, we calculated the q-values of all the TFs in the database by GSEA

to determine whether the target genes of the perturbed TF are enriched in the differentially expressed genes.

We found that more significant q-values are usually associated with relatively larger number of targets for

each TF; however, too many (*e.g.*, greater than 2000) targets will result in non-significant q-values. The

summary statistics, such as the total number of TFs and the average number of target genes per TF, are

summarized in Table S1. Furthermore, these corresponding q-values from all the gene expression data are

converted to specificity and sensitivity values (see Methods), and different databases are compared based

on the area under the sensitivity-specificity curves (Fig. 1d). We found that the literature-based database

has the best overall performance, thus we used this database for further analyses. Our results are in line

with a previous benchmark study[51] that literature-based TF-target database outperforms others in capturing

transcriptional regulation.

Inferring TF activity without using TF expression

NetAct can accurately infer TF activity for an individual sample directly from the expression of genes

targeted by the TF (see Methods). In the following, we will illustrate how NetAct infers TF activity on two

cases of microarray KD experiments -- one case for shRNA KD of FOXM1 and shRNA KD of MYB in

lymphoma cells (GEO: GSE17172[52]), and another case for KD of BCL6 on both OCI-Ly7 and Pfeiffer

GCB-DLBCL cell lines (GEO: GSE45838[33]). NetAct first successfully identified the TFs who undergo

knockdown, *i.e.*, FOXM1, MYB and BCL6 in each case, respectively, by applying GSEA on the optimized

TF-target database (q value < 0.15).

Next, for each identified TF, NetAct calculates its activity using the mRNA expression of the direct

targets of the TF. We first constructed a Spearman correlation matrix from the expression of the targeted

genes. As shown in Fig. 2a, the correlation matrix after hierarchical clustering analysis typically consists

of two red diagonal blocks, two blue off-diagonal blocks, and the remaining elements with low correlations

which will be filtered out subsequently (details in Methods). Genes within the red block are positively

correlated with each other, while genes from the blue blocks are negatively correlated with each other.

However, if the correlation matrix is constructed from 100 or 200 randomly selected genes (Fig. 2bc), such

a clear pattern disappears. Thus, our observation suggests that genes from one of the red blocks are activated

by the TF, whereas genes from the other block are inhibited by the TF. Moreover, filtered genes are not

likely to be directly targeted by the TF in this context, or they are regulated by multiple factors

simultaneously and are thus likely not a good indicator for the TF activity.

We further evaluated how the filtering step removes noise and retains the important genes in the

analysis. We found that, after the filtering step, most of the differentially expressed (DE) genes remain, as

evidenced by Fig. 2d. Here, DE genes from each comparison were retrieved by using *limma* with a cutoff

of the adjusted p-values at 0.05 and a cutoff of the log2 fold changes at 2. Subsequently, for DE TFs we

evaluated the Spearman correlations between the TFs and the corresponding targeted genes. In traditional

approaches (such as ARACNe[1], WGCNA[53], and BEST[54]), the co-expression between a TF and its targeted

genes are commonly used to identify its association and assign the sign (activation or inhibition) of the

regulation. We found that, for each TF, most of the genes in a block either positively correlate with the TF

expression (Fig. 2fg, blue bars), or they negatively correlate with the TF expression (Fig. 2fg, red bars).

The tests demonstrate that, without directly using TF expression, NetAct can successfully identify two

groups of important target genes – genes in each group are either activated or inhibited by the TF. These

two groups of genes are further used to infer TF activity by a weighted average of their gene expression

(see Methods). Additionally, we found that the correlations between inferred TF activity and target

expression are usually higher than the correlations between TF expression and target expression (Fig. 2h).

Evaluating activity inference in a simulation benchmark

To evaluate the accuracy and robustness of inferring TF activity, we performed extensive benchmark

tests to compare NetAct with other existing methods (see below). We first performed the benchmark tests

on simulated data because TF activity is usually not directly measurable. The activity of a TF can be related

to its protein level or the level of a particular posttranslational modification, such as phosphorylation.

Therefore, it is very difficult to obtain the ground truth of TF activity from an experimental data set. Thus,

in this benchmark test, we will rely on mathematical modeling to simulate both the expression and activity

of each TF from a synthetic TF-target network. With this simulated data, we will benchmark NetAct against

other methods.

To establish the simulated benchmark data set, we first constructed a synthetic TF-target network with

a total of 30 TFs. Each TF has 20 target genes randomly selected with replacement from a pool of 1000

genes. In addition, each TF also regulates two (randomly selected) of the 30 TFs. This synthetic network

has a hierarchical structure, where target genes may be co-regulated by multiple TFs. The type of each TF-

to-TF regulation is either excitatory, inhibitory, or signaling, with a chance of 25%, 25%, and 50%,

respectively; the type of each TF-to-target regulation is either excitatory or inhibitory with a 50% chance

for each. Here, the signaling regulation changes the activity of a TF without changing its expression;

whereas the excitatory or inhibitory interactions changes both of the activity and expression. From one

realization of the synthetic network generation, the final synthetic network contains a total of 477 genes (30

TFs, 447 targeted genes) and 660 regulatory links (Fig. 3a).

To simulate the gene expression of the TF-target network, we applied a generalized version of the

mathematical modeling algorithm, RACIPE[37]. Using the network topology as the only input, RACIPE can

generate an ensemble of random models, each corresponds to a set of randomly sampled parameters. Here,

we used RACIPE to generate a set of simulated data including gene expression and TF activity for

benchmark. Some previous studies have also adopted a similar modeling approach for benchmarking[55,56].

To consider the effects of a signaling regulatory link, we generalized RACIPE to simulate both expression

and activity for each TF. See Supplemental Material for more details.

In the benchmark test, we used RACIPE to simulate 100 models with randomly picked kinetic

parameters. From these 100 models we obtained 83 stable steady-state gene expression and activity profiles

for the 477 genes. As expected, TF activity and target activity from a regulatory link are correlated (1^{st}

column, 2^{nd} row in Fig. 3b); TF activity and target expression (3^{rd} column, 2^{nd} row in Fig. 3b) are correlated;

and the expression of two target genes (Fig. 3c) are correlated. However, there is no strong correlation

between TF expression and target expression (2^{nd} column, 2^{nd} row in Fig. 3b) and, for a signaling regulatory

link, between TF activity and target expression (3^{rd} column, 4^{th} row in Fig. 3b). Next, we applied ARACNe

to predict the regulon (*i.e.*, the list of targeted genes by a specific TF) using either the simulated expression

profiles or the simulated activity profiles. We found that the regulons predicted from the activity profiles

are substantially more similar to the predefined regulons (measured by the Jaccard similarity[57]) than those

predicted from the expression profiles (Fig. 3d). The results indicate the need of using the TFs' activity,

instead of their expression, to identify TF-target relations.

Next, we compared NetAct with several related algorithms, NCA, VIPER, and AUCell, in inferring TF

activity using both the simulated expression profiles from the 83 models and a predefined regulon (*i.e.*, the

association of target genes for each TF). The predicted activity was then compared with the simulated

activity (ground truth) to evaluate the performance. To mimic the real-life scenario where the target

information may not be complete and accurate, we consider more challenging tests where the regulon data

is randomly perturbed. Here, for a specific perturbation level, we generated 100 sets of regulon data by

replacing a certain number of target genes for each TF with non-interacting genes. The numbers of replaced

genes are 0 (0% level of perturbation), 5 (25%), 10 (50%) and 15 (75%), respectively, in different tests. We

then evaluated the performance of NetAct, NCA, and VIPER. AUCell protocol advises to include the target

genes with only positive interactions in the regulons. To satisfy this criterion, we updated the regulons for

both unperturbed and perturbed regulons. For the unperturbed regulons, we retained only the positive

interactions; for the perturbed regulons, we retained the positive target genes that were not replaced and a

random half of the replaced target genes (assuming that half of the genes are positively regulated by the

TF). We then evaluated AUCell performance using these updated regulons (denoted AUCell 1) and non-

updated regulons (denoted AUCell 2). As shown in Fig. 4a, NetAct significantly outperforms each of the

other methods in reproducing the simulated activity profiles at each perturbation level. As expected, the

performance of NetAct is decreased by increasing the perturbation levels of the regulon data; however,

NetAct still performs reasonably well even when only 25% of the actual target genes are kept in the regulon

data. The results indicate that NetAct can robustly and accurately infer TF activity even with a noisy TF-

target database.

Furthermore, we tested another scenario where the test data contains simulated data from two

experimental conditions, *e.g.*, one representing an unperturbed condition and the other representing a

perturbed condition. Here, we used the same synthetic network but compiled 40 expression and activity

data from the above-mentioned simulation (unperturbed condition), together with 43 expression and activity

data from simulations in which a specific TF (TF9) is knocked down (perturbed condition). We then

performed a similar test as above and found that NetAct outperformed each of the other methods (Fig. 4b).

The notable performance gain of NetAct mainly emanates from the removal of incoherent (or noisy) targets

of a TF before the activity calculation in NetAct (see Methods).

Characterizing cellular state transitions by GRN construction and modeling

In the previous sections, we demonstrated the capability of NetAct in identifying the key TFs and

predicting TF activity. With these data, NetAct further constructs a TF-based GRN using the mutual

information (MI) of the activity from the identified TFs (details in Methods). We then applied RACIPE to

the constructed network to check whether the simulated network dynamics are consistent with experimental

observations. In the following, we show the utility of NetAct with two biological examples.

In the first case, we analyzed a set of time-series microarray data on A549 epithelial cells undergoing

TGF-β induced epithelial-mesenchymal transition (EMT) (GEO: GSE17708)[58]. According to the overall

structure of the transcriptomics profiles, we arranged samples from different time points into three groups

– early stage (time points 0, 0.5h and 1h), middle stage (time points 2h, 4h, and 8h) and late stage (time

points 16h, 24h, and 72h). We then performed three-way GSEA with our human literature-based TF-target

database to identify enriched TFs that are active between either early-middle, early-late and middle-late

timepoints. Forty-one TFs (q-value cutoff 0.01) were identified including many major transcriptional

master regulators, such as BRCA1, CTNNB1, MYC, TWIST1, TWIST2 and ZEB1, and factors that are

directly associated with TGF-β signaling pathway, such as SMAD3[59], FOS and JUN[60]. The hierarchical

clustering analysis (HCA) of the expression and activity profiles for these TFs is shown in Fig. 5a. While

the expression profiles are quite noisy, the activities show a clear gradual transition from the epithelial to

mesenchymal (M) state. Note that the signs of the activity of a few non-DE TFs were flipped according to

experimental evidence of protein-protein interactions and the nature of transcriptional regulation (see

Methods for detailed procedures and Table S3 for a list of the changes).

We then constructed a TF regulatory network (Fig. 5b) and performed mathematical modeling to

simulate the dynamical behavior of the network using RACIPE (Fig. 5cd). We found that, consistent with

the expression and activity profiles, the network clearly allows two distinct transcriptional clusters that can

be associated with E and M states. To assess the role of TGF-β signaling in inducing EMT, we performed

a global bifurcation analysis[26] in which the SMAD3 level is used as the control parameter. Here, SMAD3

was selected as it is the direct target of TGF-β signaling[59]. As shown in (Fig. 5e), when SMAD3 levels are

either very low or high, the cells reside in E or M states. However, when SMAD3 is at the intermediate

level, the cells could be driven into some rare hybrid phenotypes. These results are consistent with our

previous studies on the hybrid states of EMT[31,61]. Using RACIPE, we systematically performed perturbation

analyses by knocking down every TF in the network. Our simulation results (Fig. 5f) suggest that knocking

down TFs, such as RELA, SP1, EGR1, and CREBBP, *etc.*, has major effects in driving M to E transition

(MET), while knocking down TFs, such as TP53, AR, and KLF4, *etc.*, has major effects in driving E to M

transition (EMT). These predictions are all consistent with existing experimental evidence (Table S4).

In the second case, we studied the macrophage polarization program in mouse bone-marrow-derived

macrophage cells using time series RNA-seq data (GEO: GSE84517)[62]. In this experiment, macrophage

progenitor cells (denoted as UT condition) were treated with (1) IFNγ to induce a transition to the M1 state;

(2) IL4 to induce a transition to the M2 state; (3) both IFNγ and IL4 to induce a transition to a hybrid M

state. Here, we reprocessed the raw counts of RNA-seq with a standard protocol (details in Supplemental

Material). From principal component analysis (PCA) on the whole transcriptomics (Fig.6b), we found that

the gene expression undergoes distinct trajectories when macrophage cells were treated with either IFNγ

(M1 state) or IL4 (M2 state). When both IFNγ and IL4 were administered, the gene expression trajectories

are in the middle of the previous two trajectories, suggesting that cells are in a hybrid state (hybrid M state).

We aim to use NetAct to elucidate the crosstalk in transcriptional regulation downstream of cytokine-

induced signaling pathways during macrophage polarization.

Here, we applied GSEA on six comparisons – untreated versus IFNγ treated samples (one comparison

between the untreated and the treated after two hours, another between the untreated and the treated after

four hours, same for the other comparisons), untreated versus IL4 treated samples, and untreated versus

IFNγ+IL4 treated samples. Using our mouse literature-based TF-target database, we identified 79 TFs (q-

value cutoff 0.05 for UT vs IL4-2h and 0.01 for all others). The expression and activity profiles of these

TFs captures the essential dynamics of transcriptional state transitions during macrophage polarization

(Fig.6abc). NetAct successfully identified important TFs in these processes, including Stat1, the major

target of IFNγ, Stat2, Stat6, Cebpb, Nfkb family members, Hif1a and Myc[63–65]. Myc is known to be induced

by IL-4 at later phases of M2 activation and required for early phases of M1 activation[64]. Interestingly, we

find Myc has high expression in both IL4 stimulation and its co-stimulation with IFN but its activity is high

only in IL4 stimulation. We then constructed a TF regulatory network that connects 60 TFs (Fig.6d) and

simulated the network with RACIPE, from which we found that simulated gene expression (Fig.6f) matches

well with experimental gene expression data (Fig.6a). RACIPE simulations display disparate trajectories

from UT to IL4 or IFNγ activation and stimulation with both IL4 and IFNγ. Strikingly, we found in the

simulation that there is a spectrum of hybrid M states between M1 and M2 (Fig.6e), which is consistent

with experimental observations of macrophage polarization[63]. Moreover, we also predict from our GRN

modeling that the transition from UT to hybrid M is likely to first undergo a transition to either M1 or M2

before a second transition to hybrid M(Fig.6e). This is because of our observation from the simulation data

that there are fewer models connecting UT and hybrid M than any of the other two routes (*i.e.*, UT to M1,

and UT to M2) (Fig.S6). Taken together we showed that the NetAct-constructed GRN model captures the

multiple cellular state transitions during macrophage polarization.

In conclusion, we show that NetAct can identify the core TF-based GRN using both the literature-based

TF-target database and the gene expression data. We also demonstrate how RACIPE-based mathematical

modeling complements NetAct-based GRN inference in elucidating the dynamical behaviors of the inferred

GRNs. Together these two methods can be applied to infer biologically relevant regulatory interactions and

the dynamical behavior of biological processes.

Discussion

In this study, we have developed NetAct – a computational platform for constructing and modeling

core transcription factor (TF)-based regulatory networks. NetAct takes a data-driven approach to establish

gene regulatory network (GRN) models directly from transcriptomics data and takes a mathematical

modeling approach to characterize cellular state transitions driven by the constructed GRN. NetAct

specifically integrates both literature-based TF-target databases and transcriptomics data of multiple

experimental conditions to accurately infer TF transcriptional activity based on the expression of their target

genes. Using the inferred TF activity, NetAct further constructs a TF-based GRN, whose dynamics can then

be evaluated and explored by mathematical modeling. Our approach in combining top-down and bottom-

up systems biology approaches will contribute to a better understanding of gene regulatory mechanism of

cellular decision making. NetAct is made freely available as an R package[66].

One of the key components of NetAct is a pre-compiled TF-target gene set database. Here, we have

evaluated different types of TF-target databases in identifying knocked down TFs using publicly available

transcriptomics data sets. In this test, we have considered databases derived from literature, gene co-

expression, cis-motif prediction, and TF-binding motif data. Our benchmark tests suggest that the literature-

base database clearly outperformed the other databases. The literature-based database usually contains a

small (~30) number of target genes for each TF, but these data have direct experimental evidence, therefore

being more reliable than those from the other sources. However, the literature-based database for sure has

missing regulatory interactions, therefore maybe limiting the overall performance of NetAct. One way to

address this issue is to further update the literature-based database, once new information is available.

Another potential approach is to compile a database by combining different types of databases together.

However, this might be quite challenging as different databases have data of very different sizes (the

number of target genes) and quality. Future investigations on this direction can help to expand our

knowledge of transcriptional regulation and meanwhile improve the performance of the algorithm.

NetAct also has a unique approach to infer the TF activity from the gene expression of the target genes

with the consideration of activation/inhibition nature. From our in-silico benchmark tests, we found that

NetAct outperforms major activity inference methods, owing to the design of the filtering step and the use

of a high-quality TF-target database. NetAct is also robust against some inaccuracy in the TF-target

database and noises in gene expression data, because of its capability of filtering out irrelevant targets as

well as remaining key targets.

One potential issue is the assignment of the sign of TF activity, as it is algorithmically assigned

according to the correlation with TF expression. In the case where the TF expression is very noisy or the

expression is completely unrelated to TF activity, the sign assignment might be inaccurate. To deal with

this issue, we have devised a semi-manual approach that identifies the sign of TF activity according to the

sign of other interacting TFs. Another potential issue is that some TFs from the same family may have very

similar target genes, therefore NetAct will have difficulty in identifying exactly which TF from the family

is most relevant. Additional data resources, such as epigenomics[67], TF-binding data[35] and Hi-C data[68], will

be helpful to address this problem. One of the future directions is to design methods to integrate these data

resources.

Lastly, instead of constructing a global transcriptional regulatory network, NetAct focuses on modeling

a core regulatory network with only interactions between key TFs. The underlying hypothesis is that these

TFs and the associated regulatory interactions play major roles in controlling the gene expression of

different cellular states and the patterns of state transitions. With the core network identified using NetAct,

we can further perform simulations with mathematical modeling algorithms, such as RACIPE, to analyze

the control mechanism of the core network. These simulations allow us to generate new hypotheses, which

can be further tested experimentally. The validation data can further help to improve the model. Ideally,

this needs to be an iterative process to refine a core network model, which is indeed another interesting

future direction.

Conclusions

We developed NetAct, a computational platform for constructing and modeling core transcription-

factor regulatory networks using both transcriptomics data and literature-based transcription factor-target

gene databases. Utilizing both types of resources allows us to identify regulatory genes and links specific

to the data and fully take advantage of the existing knowledgebase of transcriptional regulation. Our method

in combining top-down and bottom-up systems biology approaches contributes to a better understanding of

the mechanism of gene regulation driving cellular state transitions.

Methods

Selecting Enriched TFs

For a comparison between two experimental conditions, we obtained a ranked gene list quantified by the absolute value of the test statistics (t statistics in microarray and Wald test statistics in RNA-Seq) from differential expression (DE) analysis[69], followed by gene set enrichment analysis (GSEA)[70] using our optimized transcription factor (TF)-target gene set database. Here, for each TF, the corresponding gene set consists of all its target genes. GSEA identifies important TFs whose targets are enriched in DE genes between the two conditions. The significance test is achieved through 10,000 permutations of the gene list names and TFs are kept for further analysis when q value is below a certain threshold cutoff (0.05 by default). For multiple comparisons, a set of enriched TFs are first identified from each pairwise comparison and then a union of the multiple sets of TFs is considered.

Inferring TF activity

TF activity is inferred from the expression of target genes retrieved from the TF-target database. NetAct defines the activity of the selected TFs using two different schemes – one using only the expression of target genes and the other using the expression of both the TF and its target genes. The second scheme is only used for the situation of noisy target gene expression. For each TF, the algorithm selects the better scheme according to their performance, as described below.

Without directly using TF expression: For each TF, its downstream targets are first divided into two modules using the Newman's community detection algorithm[71] on the pairwise Spearman correlation matrix of the target genes. Then, within each module some less-correlated genes are filtered out to improve the quality of the inference. Here, the filtering step is achieved as follows: (1) each target gene is assigned a vector of correlations with the other target genes, where the distance between two genes is calculated as the sum of squares of the correlation vectors of two genes. (2) k-mean algorithm is performed within each

cluster to determine the center vector. (3) genes are filtered out if the distance between the genes and the

center is larger than the average distance.

This step outputs two groups of genes – genes in one group are supposed to be activated by the TF,

while genes in the other group are inhibited by the TF. Note, at this stage, the nature of activation/inhibition

of the individual group is not yet determined. The activity of the TF is calculated as

$$A(TF) = \frac{\sum_{i=1}^{n} w_i g_i I_i}{\sum_{i=1}^{n} w_i} \quad \text{(eq 1)},$$

where g_i is the standardized expression value of a target gene i, w_i is the weighting factor defined as a Hill

function:

$$w_i = 1/[1 + (\frac{s_i}{s_0})^n] \quad \text{(eq 2)},$$

where s_i is the adjusted p value from DE analysis for gene i, the threshold S_0 is 0.05, and n is set to be 1/5

for best performance. I_i is 1 if the corresponding gene belongs to the first group and -1 if it belongs to the

second group. If the calculated TF activity pattern is not consistent with the TF expression trend (evaluated

by Spearman correlation), both the sign of the two groups and the sign of the activity are flipped.

Using TF expression: For each TF, its downstream targets are first divided into two groups according to

the sign of the Spearman correlation between the TF expression and the target expression. Similar to the

previous scheme, in each group, target genes are filtered out if the correlation value is less than the average

correlation of all the targets. The activity of the TF is also calculated using Equation 1.

Sign assignment for DE TF: For any DE TF (*i.e.*, there is significant difference in TF expression across cell

type conditions) of interest, NetAct computes the activity values from both the schemes (with or without

TF's expression), and selects the better way based on how well the activity values correlate with target

expression. To this end, NetAct calculates the absolute value of Spearman correlation between the TF

activity and the expression of each target, and selects the scheme whose activity gives larger average

correlations.

Sign assignment for non-DE TF: If the expression patterns of the identified TFs fail to show the significant

differences between cell type conditions, a semi-manual method to assign the sign of activity can be adopted.

Putative interaction partners between DE and non-DE TFs in the inferred network are identified using the

Fisher's Exact Test between TF targets in the NetAct TF-target database. The most significant pairs are

then cross referenced with STRING to identify instances of PPI. A literature search is then performed to

identify the nature of the PPI, and the sign of the non-DE TF is adjusted based on the DE TF and the type

of PPI. Note that the last step needs to be done manually for each modeling application. Table S3 shows

the details of TF sign flipping and supported experimental evidence for the two network modeling

applications.

Network construction and mathematical modeling

NetAct constructs a TF regulatory network using both the TF-TF regulatory interactions from the TF-

target database and the activity values. (1) The network is constructed using mutual information between

the activity values of two TFs. (2) Interactions are filtered out if they cannot be found in the database. (3)

The sign of each link is determined by the sign of the Spearman correlation between the activity of two TFs.

(4) We keep the interaction between two TFs if their mutual information is higher than a threshold cutoff.

With different cutoff values for mutual information, NetAct establishes networks of different sizes. To

identify the best network model capturing gene expression profiles, we apply mathematical modeling to

each of the TF networks using RACIPE[26]. RACIPE takes network topology as the input and generates an

ensemble of mathematical models with random kinetic parameters. By simulating the network, we expect

to obtain multiple clusters of gene expression patterns that are constrained by the complex interactions in

the network. RACIPE was also applied to generate simulated benchmark test sets for a synthetic TF-target

network (see Supplemental Material SI5).

Declarations:

Ethics approval and consent to participate

Not applicable

Consent for publication

Not applicable

Availability of data and materials

The information of the TF-target gene set databases are listed in Table S1. The public gene expression datasets for algorithm optimization and benchmark are listed in Table S2. The datasets and computational scripts for in-silico benchmark, the network modeling scripts, including those for data processing, network construction and network simulations, and the inferred network topology files are available in the GitHub repository at https://github.com/lusystemsbio/NetActAnalysis. The NetAct software is available at https://github.com/lusystemsbio/NetAct as an R package. NetAct is platform independent, written in R with a partial of codes in C++ for improved performance. NetAct is licensed under the MIT License.

Competing interests

The authors declare that they have no competing interests

Funding

509   The study is supported by startup funds from The Jackson Laboratory and Northeastern University, by the

510   National Cancer Institute of the National Institutes of Health under Award Number P30CA034196, and by

511   the National Institute of General Medical Sciences of the National Institutes of Health under Award Number

512   R35GM128717.

Authors' contributions

M.L conceived the study. K.S. developed and V.K. improved the NetAct algorithm. A.K. constructed and

performed in-silico benchmark. K.S. and V.K. performed benchmark tests on public experimental gene

expression data. B.C. and V.K. performed network modeling. D.D. helped to refine the NetAct code. S.L,

K.K., and Z.S.Q. provided conceptual input to the manuscript. K.S., A.K., V.K. and M.L wrote the

manuscript, with helps from all other authors. The authors read and approved the final manuscript.

Acknowledgements

Not applicable

Reference:

1. Margolin, A. A. *et al.* ARACNE: An Algorithm for the Reconstruction of Gene Regulatory Networks in a Mammalian Cellular Context. *BMC Bioinformatics* **7**, S7 (2006).

2. Alvarez, M. J. *et al.* Functional characterization of somatic mutations in cancer using network-based inference of protein activity. *Nat. Genet.* **48**, 838 (2016).

3. Ament, S. A. *et al.* Transcriptional regulatory networks underlying gene expression changes in Huntington's disease. *Mol. Syst. Biol.* **14**, e7435 (2018).

4. Chan, T. E., Stumpf, M. P. H. & Babtie, A. C. Gene Regulatory Network Inference from Single-Cell Data Using Multivariate Information Measures. *Cell Syst.* **5**, 251-267.e3 (2017).

5. Carré, C., Mas, A. & Krouk, G. Reverse engineering highlights potential principles of large gene regulatory network design and learning. *Npj Syst. Biol. Appl.* **3**, 17 (2017).

6. Fiers, M. W. E. J. *et al.* Mapping gene regulatory networks from single-cell omics data. *Brief. Funct. Genomics* doi:10.1093/bfgp/elx046.

7. Gérard, C. & Goldbeter, A. Temporal self-organization of the cyclin/Cdk network driving the mammalian cell cycle. *Proc. Natl. Acad. Sci.* **106**, 21643–21648 (2009).

8. Laub, M. T., McAdams, H. H., Feldblyum, T., Fraser, C. M. & Shapiro, L. Global Analysis of the Genetic Network Controlling a Bacterial Cell Cycle. *Science* **290**, 2144–2148 (2000).

9. Li, F., Long, T., Lu, Y., Ouyang, Q. & Tang, C. The yeast cell-cycle network is robustly designed. *Proc. Natl. Acad. Sci.* **101**, 4781–4786 (2004).

10. Nieto, M. A., Huang, R. Y.-J., Jackson, R. A. & Thiery, J. P. EMT: 2016. *Cell* **166**, 21–45 (2016).

11. Kim, J., Chu, J., Shen, X., Wang, J. & Orkin, S. H. An Extended Transcriptional Network for Pluripotency of Embryonic Stem Cells. *Cell* **132**, 1049–1061 (2008).

12. Loh, Y.-H. *et al.* The Oct4 and Nanog transcription network regulates pluripotency in mouse embryonic stem cells. *Nat. Genet.* **38**, 431 (2006).

13. Katebi, A., Ramirez, D. & Lu, M. Computational systems-biology approaches for modeling gene networks driving epithelial–mesenchymal transitions. *Comput. Syst. Oncol.* **1**, e1021 (2021).

14. Alon, U. *An Introduction to Systems Biology : Design Principles of Biological Circuits*. (Chapman and Hall/CRC, 2006). doi:10.1201/9781420011432.

15. Kirk, P. D. W., Babtie, A. C. & Stumpf, M. P. H. Systems biology (un)certainties. *Science* **350**, 386–388 (2015).

16. Chasman, D. & Roy, S. Inference of cell type specific regulatory networks on mammalian lineages. *Curr. Opin. Syst. Biol.* **2**, 130–139 (2017).

17. Ben-Jacob, E., Lu, M., Schultz, D. & Onuchic, J. N. The physics of bacterial decision making. *Front. Cell. Infect. Microbiol.* **4**, 154 (2014).

18. Dutta, P., Ma, L., Ali, Y., Sloot, P. M. A. & Zheng, J. Boolean network modeling of β-cell apoptosis and insulin resistance in type 2 diabetes mellitus. *BMC Syst. Biol.* **13**, 36 (2019).

19. Steinway, S. N. *et al.* Network Modeling of TGFβ Signaling in Hepatocellular Carcinoma Epithelial-to-Mesenchymal Transition Reveals Joint Sonic Hedgehog and Wnt Pathway Activation. *Cancer Res.* **74**, 5963–5977 (2014).

20. Zeigler, A. C. *et al.* Computational model predicts paracrine and intracellular drivers of fibroblast phenotype after myocardial infarction. *Matrix Biol.* **91–92**, 136–151 (2020).

21. Kanehisa, M., Furumichi, M., Sato, Y., Ishiguro-Watanabe, M. & Tanabe, M. KEGG: integrating viruses and cellular organisms. *Nucleic Acids Res.* **49**, D545–D551 (2021).

22. Krämer, A., Green, J., Pollard, J. & Tugendreich, S. Causal analysis approaches in Ingenuity
Pathway Analysis. *Bioinforma. Oxf. Engl.* **30**, 523–530 (2014).
23. Ramirez, D., Kohar, V. & Lu, M. Toward Modeling Context-Specific EMT Regulatory
Networks Using Temporal Single Cell RNA-Seq Data. *Front. Mol. Biosci.* **7**, 54 (2020).
24. Khan, F. M. *et al.* Unraveling a tumor type-specific regulatory core underlying E2F1-
mediated epithelial-mesenchymal transition to predict receptor protein signatures. *Nat.*
Commun. **8**, 198 (2017).
25. Udyavar, A. R. *et al.* Novel Hybrid Phenotype Revealed in Small Cell Lung Cancer by a
Transcription Factor Network Model That Can Explain Tumor Heterogeneity. *Cancer Res.*
77, 1063–1074 (2017).
26. Kohar, V. & Lu, M. Role of noise and parametric variation in the dynamics of gene
regulatory circuits. *Npj Syst. Biol. Appl.* **4**, 1–11 (2018).
27. Wooten, D. J. *et al.* Systems-level network modeling of Small Cell Lung Cancer subtypes
identifies master regulators and destabilizers. *PLOS Comput. Biol.* **15**, e1007343 (2019).
28. Moignard, V. *et al.* Decoding the regulatory network of early blood development from
single-cell gene expression measurements. *Nat. Biotechnol.* **33**, 269–276 (2015).
29. A common molecular logic determines embryonic stem cell self-renewal and
reprogramming. *EMBO J.* **38**, e100003 (2019).
30. Sha, Y., Wang, S., Zhou, P. & Nie, Q. Inference and multiscale model of epithelial-to-
mesenchymal transition via single-cell transcriptomic data. *Nucleic Acids Res.* **48**, 9505–
9520 (2020).
31. Lu, M., Jolly, M. K., Levine, H., Onuchic, J. N. & Ben-Jacob, E. MicroRNA-based
regulation of epithelial–hybrid–mesenchymal fate determination. *Proc. Natl. Acad. Sci.* **110**,
18144–18149 (2013).
32. Jang, S. *et al.* Dynamics of embryonic stem cell differentiation inferred from single-cell
transcriptomics show a series of transitions through discrete cell states. *eLife* **6**, e20487
(2017).
33. Alvarez, M. J. *et al.* Functional characterization of somatic mutations in cancer using
network-based inference of protein activity. *Nat. Genet.* **48**, 838 (2016).
34. Liao, J. C. *et al.* Network component analysis: Reconstruction of regulatory signals in
biological systems. *Proc. Natl. Acad. Sci.* **100**, 15522–15527 (2003).
35. Aibar, S. *et al.* SCENIC: single-cell regulatory network inference and clustering. *Nat.*
Methods **14**, 1083–1086 (2017).
36. Huang, B. *et al.* RACIPE: a computational tool for modeling gene regulatory circuits using
randomization. *BMC Syst. Biol.* **12**, 74 (2018).
37. Katebi, A., Kohar, V. & Lu, M. Random Parametric Perturbations of Gene Regulatory
Circuit Uncover State Transitions in Cell Cycle. *iScience* **23**, 101150 (2020).
38. Huang, B. *et al.* Decoding the mechanisms underlying cell-fate decision-making during stem
cell differentiation by random circuit perturbation. *J. R. Soc. Interface* **17**, 20200500 (2020).
39. Subramanian, A. *et al.* Gene set enrichment analysis: a knowledge-based approach for
interpreting genome-wide expression profiles. *Proc. Natl. Acad. Sci. U. S. A.* **102**, 15545–
15550 (2005).
40. Han, H. *et al.* TRRUST: a reference database of human transcriptional regulatory
interactions. *Sci. Rep.* **5**, 11432 (2015).
41. Liu, Z.-P., Wu, C., Miao, H. & Wu, H. RegNetwork: an integrated database of transcriptional
and post-transcriptional regulatory networks in human and mouse. *Database* **2015**, (2015).

42. Essaghir, A. & Demoulin, J.-B. A Minimal Connected Network of Transcription Factors
Regulated in Human Tumors and Its Application to the Quest for Universal Cancer
Biomarkers. *PLOS ONE* **7**, e39666 (2012).
43. Jiang, C., Xuan, Z., Zhao, F. & Zhang, M. Q. TRED: a transcriptional regulatory element
database, new entries and other development. *Nucleic Acids Res.* **35**, D137–D140 (2007).
44. Abugessaisa, I. *et al.* FANTOM5 transcriptome catalog of cellular states based on Semantic
MediaWiki. *Database J. Biol. Databases Curation* **2016**, (2016).
45. Lachmann, A. *et al.* ChEA: transcription factor regulation inferred from integrating genome-
wide ChIP-X experiments. *Bioinformatics* **26**, 2438–2444 (2010).
46. Wingender, E., Dietze, P., Karas, H. & Knüppel, R. TRANSFAC: A Database on
Transcription Factors and Their DNA Binding Sites. *Nucleic Acids Res.* **24**, 238–241 (1996).
47. Sandelin, A., Alkema, W., Engström, P., Wasserman, W. W. & Lenhard, B. JASPAR: an
open-access database for eukaryotic transcription factor binding profiles. *Nucleic Acids Res.*
32, D91–D94 (2004).
48. null, null. The ENCODE (ENCyclopedia Of DNA Elements) Project. *Science* **306**, 636–640
(2004).
49. Aibar, S. *et al.* SCENIC: single-cell regulatory network inference and clustering. *Nat.*
Methods **14**, 1083–1086 (2017).
50. Abugessaisa, I. *et al.* FANTOM5 transcriptome catalog of cellular states based on Semantic
MediaWiki. *Database J. Biol. Databases Curation* **2016**, baw105 (2016).
51. Garcia-Alonso, L., Ibrahim, M. M., Turei, D. & Saez-Rodriguez, J. Benchmark and
integration of resources for the estimation of human transcription factor activities. *bioRxiv*
337915 (2018) doi:10.1101/337915.
52. Alvarez, M. J., Sumazin, P., Rajbhandari, P. & Califano, A. Correlating measurements across
samples improves accuracy of large-scale expression profile experiments. *Genome Biol.* **10**,
R143 (2009).
53. Langfelder, P. & Horvath, S. WGCNA: an R package for weighted correlation network
analysis. *BMC Bioinformatics* **9**, 559 (2008).
54. Hu, M. & Qin, Z. S. Query Large Scale Microarray Compendium Datasets Using a Model-
Based Bayesian Approach with Variable Selection. *PLOS ONE* **4**, e4495 (2009).
55. Schaffter, T., Marbach, D. & Floreano, D. GeneNetWeaver: in silico benchmark generation
and performance profiling of network inference methods. *Bioinformatics* **27**, 2263–2270
(2011).
56. Margolin, A. A. *et al.* ARACNE: An Algorithm for the Reconstruction of Gene Regulatory
Networks in a Mammalian Cellular Context. *BMC Bioinformatics* **7**, S7 (2006).
57. Levandowsky, M. & Winter, D. Distance between Sets. *Nature* **234**, 34 (1971).
58. Sartor, M. A. *et al.* ConceptGen: a gene set enrichment and gene set relation mapping tool.
Bioinformatics **26**, 456–463 (2010).
59. Schiffer, M., Von Gersdorff, G., Bitzer, M., Susztak, K. & Böttinger, E. P. Smad proteins
and transforming growth factor-β signaling. *Kidney Int.* **58**, S45–S52 (2000).
60. Zhang, Y., Feng, X.-H. & Derynck, R. Smad3 and Smad4 cooperate with c-Jun/c-Fos to
mediate TGF-β-induced transcription. *Nature* **394**, 909–913 (1998).
61. Jolly, M. K. *et al.* Implications of the Hybrid Epithelial/Mesenchymal Phenotype in
Metastasis. *Front. Oncol.* **5**, (2015).
62. Piccolo, V. *et al.* Opposing macrophage polarization programs show extensive epigenomic
and transcriptional cross-talk. *Nat. Immunol.* **18**, 530–540 (2017).

63. Mosser, D. M. & Edwards, J. P. Exploring the full spectrum of macrophage activation. *Nat.*
Rev. Immunol. **8**, 958–969 (2008).

64. Bae, S. *et al.* MYC-mediated early glycolysis negatively regulates proinflammatory
responses by controlling IRF4 in inflammatory macrophages. *Cell Rep.* **35**, 109264 (2021).

65. Hu, X. & Ivashkiv, L. B. Cross-regulation of Signaling Pathways by Interferon-γ:
Implications for Immune Responses and Autoimmune Diseases. *Immunity* **31**, 539–550
(2009).

66. *NetAct: https://github.com/lusystemsbio/NetAct*.

67. Pliner, H. A. *et al.* Cicero Predicts cis-Regulatory DNA Interactions from Single-Cell
Chromatin Accessibility Data. *Mol. Cell* **71**, 858-871.e8 (2018).

68. Malysheva, V., Mendoza-Parra, M. A., Saleem, M.-A. M. & Gronemeyer, H. Reconstruction
of gene regulatory networks reveals chromatin remodelers and key transcription factors in
tumorigenesis. *Genome Med.* **8**, 57 (2016).

69. Ritchie, M. E. *et al.* limma powers differential expression analyses for RNA-sequencing and
microarray studies. *Nucleic Acids Res.* **43**, e47 (2015).

70. Subramanian, A. *et al.* Gene set enrichment analysis: A knowledge-based approach for
interpreting genome-wide expression profiles. *Proc. Natl. Acad. Sci.* **102**, 15545–15550
(2005).

71. Newman, M. E. J. Modularity and community structure in networks. *Proc. Natl. Acad. Sci.*
103, 8577–8582 (2006).

682
683

   Figure captions

Fig. 1. Schematics of NetAct. (**a**) First, key transcription factors (TF) is identified using gene set

enrichment analysis (GSEA) with a literature-based TF-target database. (**b**) Second, the TF activity of an

individual sample is inferred from the expression of target genes. From the co-expression and modularity

analysis of target genes, we find target genes that are either activated (blue), inhibited (red), or not

strongly related to the TF (grey). The activity is defined as the weighted average of target genes activated

by the TF minus the weighted average of target genes inhibited by the TF. (**c**) Lastly, a TF regulatory

network is constructed according to the mutual information of inferred TF activity and literature-based

regulatory interactions. (**d**) Performance of GSEA for various TF-target gene set databases. The plot

shows the sensitivity and specificity with different q-value cutoffs. The gene set databases in the

benchmark include the combined literature-based database (D1), FANTOM5-based databases (D2) with

20, 50, 100 target genes per TF, the combined experimental-based database (D3, ChIP), and RcisTarget

databases (D4), one with 10 targets per TF binding motif and another with 50 total number of targets per

TF.

710
Fig. 2. Illustration of the grouping scheme for target genes of a transcription factor. (**a**) shows the

co-expression matrix of MYB target genes in shRNA knockdown of MYB lymphoma cells by

hierarchical clustering analysis (Pearson correlation and complete linkage). (**b, c**) demonstrate the poor

clustering results from the co-expression of randomly selected 100 (in **b**) and 200 genes (in **c**). In panels

(**a – c**), the left subplots show the outcomes of all tested genes, and the right subplots show the outcomes

of genes after the filtering step. Compared to the random cases, MYB target genes have a clear pattern of

red and blue diagonal blocks from their co-expression. (**d, e**) show the percentage of differentially

expressed genes remained after the filtering step in the case of FOXM1 and MYB knockdown,

respectively. (**f, g**) show the proportion of genes from each group that are positively/negatively correlated

with the TF expression. (**h**) Pearson correlation (average and standard deviation) between TF activity and

target expression (red) and between TF expression and target expression (blue).

722
Fig. 3. Simulation of both gene expression and activity of a synthetic GRN. (**a**) shows the synthetic

GRN consisting of 30 TFs and 447 target genes. An edge of transcriptional activation is shown as black

line with an arrowhead; an edge of transcriptional inhibition as red line with a blunt head; an edge of

signaling interaction as green line with an arrowhead. Transcription factor labeled as TF9 was selected for

knockdown simulations. (**b**) shows the summary of the correlation analyses of the simulated expression

and activity. The left, middle, and right columns represent the outcomes for TF and target activities, TF

and target expressions, and TF activities and target expressions, respectively. For each category, the

histograms of Spearman correlations are shown for non-interacting gene pairs (first row), interacting gene

pairs (second row), gene pairs of excitatory transcriptional regulation (third row), gene pairs of excitatory

signaling regulation (fourth row), gene pairs of inhibitory transcriptional regulation (fifth row). (**c**) shows

the histograms of Spearman correlations for gene pairs of target genes from the same TF. (**d**) Jaccard

indices between the ground-truth regulons of the synthetic GRN and the regulons inferred by ARACNe

using either the simulated expression (red) or activity data (blue).

Fig. 4. The performance of activity inference from a simulation benchmark. TF activity was inferred

by various methods using the gene expression data simulated from the random TF-target network and TF

regulons. For each TF, we computed the Spearman correlations of all simulated models between the

inferred activity and simulated activity (ground truth), from which we obtained the average correlation

values over all TFs. The plots show the median of average correlations for the cases where we used the

the original regulons defined by the TF-target network (0% perturbation), and the regulons where 5 (25%

perturbation), 10 (50% perturbation), and 15 (75% perturbation) target genes are randomly replaced with

non-interacting genes, respectively. The median values were computed over 100 repeats of random

replacement for each perturbation level, and the values of the average correlations are reported for the

case of zero perturbation. Panels (**a**) and (**b**) show the results for NetAct (red), NCA (blue), VIPER

(cyan), AUCELL 1 where regulons contain only positively associated target genes (orange), and

AUCELL 2 where regulons contain all target genes (green) for the untreated case (**a**) and the knockdown

case (**b**), respectively.

Fig. 5 Network modeling of TGF-β induced EMT. Application of NetAct to an EMT in human cell

lines using microarray data. (**a**) Experimental expression and activity of enriched transcription factors.

(**b**) Inferred TF regulatory network. Blue lines and arrowheads represent gene activation; Red lines and

blunt heads represent gene inhibition. (**c**) The relationship between SMAD3 gene activity and the first

principal component of the activity of all network genes from RACIPE simulations. (**d**) Hierarchical

clustering analysis of simulated gene activity (with Pearson correlation as the distance function and

Ward.D2 linkage method). Colors at top indicate the two clusters from the simulated gene activity.

Fig 6. Network modeling of macrophage polarization. Application of NetAct to induced macrophage

polarization via drug treatment in mice using RNA-seq data. (**a**) Experimental expression and activity of

enriched TFs. (**b**) PCA projection of genome-wide gene expression profiles. Different point shapes

indicate time after treatment, and colors indicate treatment types (**c**) PCA projection of gene activity of

enriched TFs. (**d**) Inferred TF regulatory network. Blue lines and arrowheads represent gene activation;

 Red lines and blunt heads represent gene inhibition. **(e)** PCA projection of simulated gene activity of

 inferred network colored by mapping each model back to experimental data. **(f)** Hierarchical clustering

 analysis of simulated gene activity (with Pearson correlation as the distance function and Ward.D2

 linkage method). Colors at top indicate the mapped experimental conditions.

789   **Fig. 1.**

Fig. 2.

807   **Fig. 3.**

817 **Fig. 4.**

Fig. 5

Fig. 6.