NetAct: a computational platform to construct core transcription factor regulatory

networks using gene activity

[1,#]Kenong Su, [2,3,#]Ataur Katebi, [4]Vivek Kohar, [3,5]Benjamin Clauss, [2,3]Danya Gordin, [6]Zhaohui S.

Qin, , [7,8,9]R. Krishna M. Karuturi, [7,8]Sheng Li, [2,3,4,7*]Mingyang Lu

[1]Department of Biomedical Informatics, Emory University, Atlanta, GA 30322, USA.

[2]Department of Bioengineering, Northeastern University, Boston, MA 02115, USA.

[3]Center for Theoretical Biological Physics, Northeastern University, Boston, MA 02115, USA

[4]The Jackson Laboratory, Bar Harbor, ME 04609, USA.

[5]Genetics Program, Graduate School of Biomedical Sciences, Tufts University, Boston, MA

02111, USA.

[6]Department of Biostatistics and Bioinformatics, Emory University, Atlanta, GA 30322, USA.

[7]The Jackson Laboratory for Genomic Medicine, Farmington, CT 06032, USA.

[8]Dept of CSE, University of Connecticut, Storrs, CT

[9]Graduate School of Biological Sciences & Eng., University of Maine, Orono, ME

[*] To whom correspondence should be addressed, m.lu@northeastern.edu

[#] Equal contributions

Abstract

A major question in systems biology is how to identify the core gene regulatory circuit that governs

the decision-making of a biological process. Here, we develop a computational platform, named NetAct,

for constructing core transcription-factor regulatory networks using both transcriptomics data and

literature-based transcription factor-target databases. NetAct robustly infers regulators' activity using target

expression, constructs networks based on transcriptional activity, and integrates mathematical modeling for

validation. Our in-silico benchmark test shows that NetAct outperforms existing algorithms in inferring

transcriptional activity and gene networks. We illustrate the application of NetAct to model networks

driving TGF-β induced epithelial-mesenchymal transition and macrophage polarization.

29
30   **Keywords**

31   Systems biology, gene regulatory networks, gene regulatory circuits, cellular state transitions,

32   mathematical modeling, transcriptional activity, epithelial-mesenchymal transition, macrophage

33   polarization

Background

One of the major goals of systems biology is to infer and model complex gene regulatory networks (GRNs) which underpin the biological processes of human disease[1–6]. Particularly important are those gene networks that control decisions regarding cellular state transitions (*e.g.*, replicative to quiescent[7–9], epithelial to mesenchymal (EMT)[10], pluripotent to differentiated[11,12]), given the central importance of such regulatory processes to both healthy development as well as diseases such as cancer.

To construct and model GRNs associated with the biological process under investigation, researchers have developed two primary systems biology approaches. The first is a *bottom-up approach*, in which researchers focus on identifying a core GRN composed of a small set of master regulators[13]. Once the core GRN is obtained, mathematical modeling is then applied to simulate the gene expression dynamics[14–17], which helps elucidate the potential gene regulatory mechanism driving the biological process in question. The current practice for synthesizing a core GRN is by compiling data via an extensive literature search, *e.g.*, in these studies[18–20]. While this works well for systems where sufficient knowledge has been gained and accumulated, it is less effective in cases where key component genes and regulatory interactions have yet to be discovered. Due to rapid increase of biomedical publications, manual synthesis of literature information has become extremely time-consuming and prone to human error in data interpretation. One way to address the labor-intensive issue is to rely on existing manually curated databases, such as KEGG[21] and Ingenuity Pathway Analysis (IPA)[22]. However, these databases often compile gene regulatory interactions from different tissues, species, or diseases. Therefore, it is hard to obtain context-specific interactions directly from these types of databases.

The second approach adopts a *top-down* perspective, in which researchers apply bioinformatics and statistical methods on genome-wide transcriptomics and/or genomics data to infer large-scale GRNs[13]. These data-driven methods are ideal for obtaining a global picture of gene regulation and the overall structure of gene-gene interactions. This approach also helps to characterize key regulators and regulatory

interactions between genes that are specific to the biological context of the study. However, conventional

bioinformatics methods for gene network inference are usually not designed to identify an integrated

working system. These methods typically rely on significance tests to determine the nodes and edges of a

gene network, yet it is rare to evaluate whether the constructed gene network is capable of operating as a

functional dynamical system[23]. Moreover, many statistical methods work well to identify the association

between genes, but not their causation, thus limiting the applicative value of the top-down approach in

characterizing gene regulatory mechanisms.

To overcome the above-mentioned issues, a relatively new approach has been explored in several

studies in which the top-down and bottom-up approaches are integrated to infer and model a core GRN[23–

31]. In this combined approach, a GRN is constructed with bioinformatics tools using genome-wide gene

expression data, followed by mathematical modeling of the GRN to simulate gene expression steady states

and explore their similarity with biological cellular states. The simulations can help validate the accuracy

of the constructed GRN and further clarify the regulatory roles of genes and interactions in driving cellular

state transitions. This combined approach helps to discover existing and new regulatory interactions specific

to the cell types and experimental conditions under study. Additionally, it helps pinpoint master regulators

and reduce the system's overall complexity. The GRN modeling is particularly crucial for cases with non-

trivial cellular state transitions, such as multi-step state transitions as observed in Epithelial-Mesenchymal

Transition (EMT)[32], and bifurcating state transitions, as observed in stem cell differentiation[33]. This is

because the GRNs constructed by the top-down approach are not guaranteed to capture these state transition

patterns. So far, to the best of our knowledge, there is no computational platform available that utilizes this

combined approach for systematic GRN inference and modeling.

In this study, we introduce a computational platform, named NetAct, for inferring a core GRN of key

transcription factors (TFs) using both transcriptomics data and a literature-based TF-target database.

Integrating both resources allows us to take full advantage of the existing knowledgebase of transcriptional

regulation. NetAct adopts the combined top-down bioinformatics and bottom-up systems biology

approaches, designed specifically to address the following two major issues.

First, many network inference methods rely on correlations of gene expression data, yet the actual

transcriptional activities of many master regulators may not be reflected in their gene expression. Instead,

the activity may be better associated with either their protein level, the level of a certain posttranslational

modification, localization, or their DNA binding affinity. As a result, the master regulators with weak

correlations between the expression level and the transcriptional activity will likely be discarded in the

network. Some algorithms have been developed to infer the activities of regulators from transcriptomics

data, such as VIPER[34], NCA[35], AUCELL[36]. However, most of these algorithms 1) are not designed for

gene network modeling, or 2) still rely on coexpression of a TF and its targeted genes, or 3) do not take

advantage of known regulatory interactions from the literature, hindering their applicability as automated

algorithms for generic use in systems biology.

Second, conventional mathematical modeling approaches have been applied over the years to simulate

the dynamics of a GRN, yet they are not particularly effective in analyzing core GRNs. A popular method

models the gene expression dynamics of a system using the chemical rate equations that govern the

associated gene regulatory processes. However, it is difficult to directly measure most of the kinetic

parameters of a GRN. Although some parameter values can be learned from published results, many others

are often based on educated guesses which significantly limits the predictive power of mathematical

modeling. Moreover, a core GRN is not an isolated system. Thus, an ideal modeling paradigm should also

consider other genes that interact with the core network. To address this infamous parameter issue, we have

developed the modeling algorithm RACIPE[29,37,38] in previous work that analyzes a large ensemble of

mathematical models with random kinetic parameters. RACIPE has been applied to model the dynamical

behavior of gene regulatory networks of different biological processes, such as epithelial-mesenchymal

transition[23,29], cell cycle[38], stem cell differentiation[39].

The new NetAct platform addresses the above-mentioned issues by (1) inferring the activities of TFs for individual samples using the gene expression levels of their targeted genes, (2) identifying the regulatory interactions between two TFs based on their activities rather than their expressions, (3) and subsequently simulating the constructed core GRN with RACIPE to validate and evaluate the gene expression dynamics of the core GRN. In this paper, we describe in detail the NetAct platform, extensive benchmark tests for TF-target databases, TF activity inference, and network construction, and two examples of applications to model GRNs with time series gene expression data.

Results

We developed a computational systems-biology platform, named NetAct, to construct transcription factor (TF)-based GRNs using TF activity. The method uniquely integrates both generic TF-target relationships from literature-based databases and context-specific gene expression data. NetAct also integrates our previously developed mathematical modeling algorithm RACIPE to evaluate whether the constructed network functions properly as a dynamical system. It evaluates the roles of every gene in the network by in-silico perturbation analysis. NetAct has three major steps: (1) identifying the core TFs using gene set enrichment analysis (GSEA)[40] with an optimized TF-target gene set database (Fig. 1a); (2) inferring TF activity (Fig. 1b); (3) constructing a core TF network (Fig. 1c). Then, the network is validated and analyzed by simulating its dynamics using mathematical modeling by RACIPE (see Supplemental Material SI5). Details of each step is given in the Methods section and Supplemental Material. Below, we demonstrate how we optimized the NetAct algorithm, compared its performance of activity inference with three existing methods using in-silico gene expression data, and applied the network modeling approach to two biological datasets.

Literature-based TF-target relationships facilitate TF inference

To establish a comprehensive gene set database containing TF-target relationships, we considered data

from different sources (Table S1, also see Supplemental Material SI1). They are (D1) a literature-based

database, consisting of data from TRRUST[41], RegNetwork[42], TFactS[43], and TRED[44]; (D2) a gene regulatory

network database FANTOM5[45], whose interactions are extracted from networks constructed using RNA

expression data from 394 individual tissues; (D3) a database derived from resources of putative TF binding

targets, including ChEA[46], TRANSFAC[47], JASPAR[48], and ENCODE[49]; and (D4) a database derived from

motif-enrichment analysis, RcisTarget[50]. These databases have been frequently used to study transcriptional

regulations and have already been utilized for network construction[29,51].

We evaluated the performance of these databases by GSEA on a benchmark dataset. GSEA is a popular

statistical method that can be used to evaluate significant overlapping between a set of genes and

differentially expressed genes between two experimental conditions. Using various types of TF-target

databases, our goal is to find the best version of the database, so that GSEA can detect the target gene sets

of the relevant TFs to be statistically significant. This benchmark dataset, denoted as *set B*, consists of a

compilation of 11 microarray and 27 RNA-Seq gene expression data (Table S2). Each of these datasets

contains at least three samples under the normal condition (control) and three samples under the treatment

condition in which a specific TF is treated by knockdown (KD). We applied GSEA (with slight

modifications, details in Methods) on the set *B* to evaluate whether the enrichment analysis can detect the

perturbed TFs. The underlying assumption is that, with a better TF-target gene set database, GSEA will be

more likely to detect the corresponding perturbed TFs. For each TF-target database and each gene

expression data in set *B*, we calculated the q-values of all the TFs in the database by GSEA to determine

whether the target genes of the perturbed TF are enriched in the differentially expressed genes. We found

that more significant q-values are usually associated with relatively larger number of targets for each TF;

however, too many (*e.g.*, greater than 2000) targets will result in non-significant q-values. The summary

statistics, such as the total number of TFs and the average number of target genes per TF, are summarized

in Table S1. Furthermore, these corresponding q-values from all the gene expression data are converted to

specificity and sensitivity values (see Methods), and different databases are compared based on the area

under the sensitivity-specificity curves (Fig. 1d). We found that the literature-based database has the best

overall performance, thus we used this database for further analyses. Our results are in line with a previous

benchmark study[52] that literature-based TF-target database outperforms others in capturing transcriptional

regulation.

Inferring TF activity without using TF expression

NetAct can accurately infer TF activity for an individual sample directly from the expression of genes

targeted by the TF (see Methods). In the following, we will illustrate how NetAct infers TF activity on two

cases of microarray KD experiments -- one case for shRNA KD of FOXM1 and shRNA KD of MYB in

lymphoma cells (GEO: GSE17172[53]), and another case for KD of BCL6 on both OCI-Ly7 and Pfeiffer

GCB-DLBCL cell lines (GEO: GSE45838[34]). NetAct first successfully identified the TFs that undergo

knockdown in each case, *i.e.*, FOXM1, MYB and BCL6 respectively, by applying GSEA on the optimized

TF-target database (q value < 0.15).

Next, for each identified TF, NetAct calculates its activity using the mRNA expression of the direct

targets of the TF. We first constructed a Spearman correlation matrix from the expression of the targeted

genes. As shown in Fig. 2a, the correlation matrix after hierarchical clustering analysis typically consists

of two red diagonal blocks, two blue off-diagonal blocks, and the remaining elements with low correlations

which will be filtered out subsequently (details in Methods). Within the red blocks, the expression of any

column gene is positively correlated with that of any row gene; while within the blue blocks, the expression

of any column gene is negatively correlated with that of any row gene. This indicates that the genes in the

two red blocks are anti-correlated in gene expression with each other. However, if the correlation matrix is

constructed from 100 or 200 randomly selected genes (Fig. 2bc), such a clear pattern disappears. Thus, our

observation suggests that genes from one of the red blocks are activated by the TF, whereas genes from the

other block are inhibited by the TF. Moreover, filtered genes are not likely to be directly targeted by the TF

in this context, or they are regulated by multiple factors simultaneously and are thus likely not a good

indicator for the TF activity.

We further evaluated how the filtering step removes noise and retains the important genes in the

analysis. We found that, after the filtering step, most of the differentially expressed (DE) genes are retained,

as evidenced by Fig. 2d. Here, DE genes from each comparison were retrieved by using *limma* with a cutoff

for the adjusted p-values at 0.05 and a cutoff for the log2 fold changes at 2. Subsequently, for DE TFs we

evaluated the Spearman correlations between the TFs and the corresponding targeted genes. In traditional

approaches (such as ARACNe[1], WGCNA[54], and BEST[55]), the co-expression between a TF and its targeted

genes are commonly used to identify its association and assign the sign (activation or inhibition) of the

regulation. We found that, for each TF, most of the genes in a block either positively correlate with the TF

expression (Fig. 2fg, blue bars), or they negatively correlate with the TF expression (Fig. 2fg, red bars).

The tests demonstrate that, without directly using TF expression, NetAct can successfully identify two

groups of important target genes – genes in each group are either activated or inhibited by the TF. These

two groups of genes are further used to infer TF activity by a weighted average of their gene expression

(Equation 1 in Methods). Additionally, we found that the correlations between inferred TF activity and

target expression are usually higher than the correlations between TF expression and target expression (Fig.

2h).

Evaluating activity inference and network construction in a simulation benchmark

To evaluate the accuracy and robustness of inferred TF activity, we performed extensive benchmark

tests to compare NetAct with other existing methods. We first performed the benchmark tests on simulated

data because TF activity is usually not directly measurable. The activity of a TF can be related to its protein

level or the level of a particular posttranslational modification, such as phosphorylation. Therefore, it is

very difficult to obtain the ground truth of TF activity from an experimental data set. Thus, in this

benchmark test, we rely on mathematical modeling to simulate both the expression and activity of each TF

from a synthetic TF-target network. With this simulated data, we benchmark NetAct against other methods.

To establish the simulated benchmark data set, we first constructed a synthetic TF-target network with

a total of 30 TFs. Each TF has 20 target genes randomly selected with replacement from a pool of 1000

genes. In addition, each TF also regulates two (randomly selected) of the 30 TFs. This synthetic network

has a hierarchical structure, where a target gene may be co-regulated by multiple TFs. The type of each TF-

to-TF regulation is either excitatory, inhibitory, or signaling, with a chance of 25%, 25%, and 50%,

respectively; the type of each TF-to-target regulation is either excitatory or inhibitory with a 50% chance

for each. Here, the signaling regulation changes the activity of a TF without changing its expression;

whereas the excitatory or inhibitory interactions changes both of the activity and expression. From one

realization of the synthetic network generation, the final synthetic network contains a total of 477 genes (30

TFs, 447 targeted genes) and 660 regulatory links (Fig. 3a). See Supplemental Material SI4 for more details.

To simulate the gene expression of the TF-target network, we applied a generalized version of the

mathematical modeling algorithm, RACIPE[38]. Using the network topology as the only input, RACIPE can

generate an ensemble of random models, each corresponds to a set of randomly sampled parameters. Here,

we used RACIPE to generate simulated data including gene expression and TF activity for benchmark.

Some previous studies have also adopted a similar modeling approach for benchmarking[56,57]. To consider

the effects of a signaling regulatory link, we generalized RACIPE to simulate both expression and activity

for each TF. See Supplemental Material SI5 for more details.

In the benchmark test, we used RACIPE to simulate 100 models with randomly generated kinetic

parameters. From these 100 models we obtained 83 stable steady-state gene expression and activity profiles

for the 477 genes. As expected, TF activity and target activity from a regulatory link are correlated (1st

column, 2nd row in Fig. 3b); TF activity and target expression (3rd column, 2nd row in Fig. 3b) are correlated;

and the expression of two target genes (Fig. 3c) are correlated. However, there is no strong correlation

between TF expression and target expression (2nd column, 2nd row in Fig. 3b) and, for a signaling regulatory

link, between TF activity and target expression (3rd column, 4th row in Fig. 3b). Next, we applied ARACNe

to predict the regulon (*i.e.*, the list of targeted genes by a specific TF) using either the simulated expression

profiles or the simulated activity profiles. We found that the regulons predicted from the activity profiles

are substantially more similar to the predefined regulons (measured by the Jaccard similarity[58]) than those

predicted from the expression profiles (Fig. 3d). The results indicate the need of using the TF activity,

instead of TF expression, to identify TF-target relationships.

Next, we compared the performance of NetAct with several related algorithms, NCA, VIPER, and

AUCell, in inferring TF activity using both the simulated expression profiles from the 83 models and a

predefined regulon (*i.e.*, the association of each TF with its target genes) (details for the implementation of

these algorithms in Supplemental Information SI3). The predicted activity was then compared with the

simulated activity (ground truth) to evaluate the performance. To mimic the real-life scenario where the

target information may not be complete and accurate, we consider more challenging tests where the regulon

data is randomly perturbed. Here, for a specific perturbation level, we generated 100 sets of regulon data

by replacing a certain number of target genes for each TF with non-interacting genes. The numbers of

replaced genes are 0 (0% level of perturbation), 5 (25%), 10 (50%) and 15 (75%), respectively, in different

tests. We then evaluated the performance of NetAct, NCA, and VIPER. AUCell protocol advises to include

the target genes with only positive interactions in the regulons. To satisfy this criterion, we updated the

regulons for both unperturbed and perturbed regulons. For the unperturbed regulons, we retained only the

positive interactions; for the perturbed regulons, we retained the positive target genes that were not replaced

and a random half of the replaced target genes (assuming that half of the genes are positively regulated by

the TF). We then evaluated AUCell performance using these updated regulons (denoted AUCell 1) and

non-updated regulons (denoted AUCell 2). As shown in Fig. 4a (also Figs. S3-S6), NetAct significantly

outperforms each of the other methods in reproducing the simulated activity profiles at each perturbation

level. As expected, the performance of NetAct is decreased by increasing the perturbation levels of the

regulon data; however, NetAct still performs reasonably well even when only 25% of the actual target genes

are kept in the regulon data. The results indicate that NetAct can robustly and accurately infer TF activity

even with a noisy TF-target database.

Furthermore, we tested another scenario where the test data contains simulated data from two

experimental conditions, *e.g.*, one representing an unperturbed condition and the other representing a

perturbed condition. Here, we used the same synthetic network but compiled 40 expression and activity

data from the above-mentioned simulation (unperturbed condition), together with 43 expression and activity

data from the simulations in which a specific TF (TF9) is knocked down (perturbed condition). We then

performed a similar test as above and found that NetAct outperformed each of the other methods (Fig. S2

and Fig. S7a). The notable performance gain of NetAct mainly emanates from the removal of incoherent

(or noisy) targets of a TF before the activity calculation in NetAct (see Methods).

In addition, we performed a network construction benchmark of NetAct and a few other network

construction algorithms using the in-silico simulation data set, as shown in Fig. 4bcd. NetAct, using the

TF activity inferred from the original regulon database, outperforms not only network construction

methods using gene expression, such as GENIE3[59], GRNBoost2[60], and ppcor[61,62], but also GENIE3 using

the TF activity inferred by AUCell (Fig. 4b). The last approach was presented to mimic a popular method

SCENIC. Moreover, we evaluated the performance of NetAct when using a perturbed regulon database.

We found that NetAct remains performing well when the perturbation level is as large as 50%, when

evaluated by all the ground-truth interactions (Fig. 4c) and by those not presented in regulon database

(Fig. 4d). The latter case was designed to evaluate the capability of NetAct in predicting novel

interactions. We observed similar outcomes for the case of the second scenario of the simulation data

from two conditions (Fig. S7bcd) (see Supplemental Information SI6 for details of the benchmark

method). In summary, our in-silico benchmark test demonstrates the high performance of NetAct over

existing state-of-the-art methods in both inferring TF activity and gene regulatory networks.

Characterizing cellular state transitions by GRN construction and modeling

In the previous sections, we demonstrated the capability of NetAct in identifying the key TFs and

predicting TF activity. With these data, NetAct further constructs a TF-based GRN using the mutual

information (MI) of the activity from the identified TFs (details in Methods). We then applied RACIPE to

the constructed network to check whether the simulated network dynamics are consistent with experimental

observations. In the following, we show the utility of NetAct with two biological examples: epithelial-

mechanical transition (EMT) and macrophage polarization.

In the first case (EMT), we analyzed a set of time-series microarray data on A549 epithelial cells

undergoing TGF-β induced epithelial-mesenchymal transition (EMT) (GEO: GSE17708)[63]. According to

the overall structure of the transcriptomics profiles, we arranged samples from different time points into

three groups – early stage (time points 0h, 0.5h and 1h), middle stage (time points 2h, 4h, and 8h) and late

stage (time points 16h, 24h, and 72h). We then performed three-way GSEA with our human literature-

based TF-target database to identify enriched TFs that are active between either early-middle, early-late

and middle-late timepoints. Forty-one TFs (q-value cutoff 0.01) were identified including many major

transcriptional master regulators, such as BRCA1, CTNNB1, MYC, TWIST1, TWIST2 and ZEB1, and

factors that are directly associated with TGF-β signaling pathway, such as SMAD3[64], FOS and JUN[65]. The

hierarchical clustering analysis (HCA) of the expression and activity profiles for these TFs is shown in Fig.

5a. While the expression profiles are quite noisy, the activities show a clear gradual transition from the

epithelial to mesenchymal (M) state. Note that the signs of the activity of a few non-DE TFs were flipped

according to experimental evidence of protein-protein interactions and the nature of transcriptional

regulation (see Methods for detailed procedures and Table S3 for a list of the changes).

We then constructed a TF regulatory network (Fig. 5b) and performed mathematical modeling to

simulate the dynamical behavior of the network using RACIPE (Fig. 5cd). We found that, consistent with

the expression and activity profiles (Fig.5a), the network clearly allows two distinct transcriptional clusters

that can be associated with E (the yellow cluster in Fig.5d) and M states (the blue cluster in Fig.5d). To

assess the role of TGF-β signaling in inducing EMT, we performed a global bifurcation analysis[29] in which

the SMAD3 level is used as the control parameter (Fig. 5c). Here, SMAD3 was selected as it is the direct

target of TGF-β signaling[64]. As shown in (Fig. 5c), when SMAD3 level is either very low or high, the cells

reside in E or M states. However, when SMAD3 is at the intermediate level, the cells could be driven into

some rare hybrid phenotypes. These results are consistent with our previous studies on the hybrid states of

EMT[32,66]. Using RACIPE, we systematically performed perturbation analyses by knocking down every TF

in the network. Our simulation results (Fig. 5e) suggest that knocking down TFs, such as RELA, SP1,

EGR1, and CREBBP, *etc.*, has major effects in driving M to E transition (MET), while knocking down TFs,

such as TP53, AR, and KLF4, *etc.*, has major effects in driving E to M transition (EMT). These predictions

are all consistent with existing experimental evidence (Table S4).

Compared to a previous model of the EMT network based on an extensive literature survey[19], the

GRN constructed by NetAct identified some of the same regulators induced by the TGF-β pathway, such

as SMAD3/4, TWIST2, ZEB1, CTNNB1, NFKB1, RELA, FOS and EGR1. Because of the lack of

microRNAs and protein-protein interactions in the database, NetAct didn't identify factors like miR200

and signaling molecules like PI3K. Interestingly, the NetAct model identifies STAT1/3, which was

connected to other signaling pathways, such as HGF, PDGF, IGF1and FGR, but not TGF-β in the

previous network model. In addition, the NetAct model identified regulators in other important pathways

in TGF-β-induced EMT in cancer cells, *e.g.*, cell cycle pathway (RB1 and E2F1) and DNA damage

pathway (P53).

In the second case, we studied the macrophage polarization program in mouse bone-marrow-derived

macrophage cells using time series RNA-seq data (GEO: GSE84517)[67]. In this experiment, macrophage

progenitor cells (denoted as UT condition) were treated with (1) IFNγ to induce a transition to the M1 state;

(2) IL4 to induce a transition to the M2 state; (3) both IFNγ and IL4 to induce a transition to a hybrid M

state. Here, we reprocessed the raw counts of RNA-seq with a standard protocol (details in Supplemental

Material SI2). From principal component analysis (PCA) on the whole transcriptomics (Fig.6b), we found

that the gene expression undergoes distinct trajectories when macrophage cells were treated with either

IFNγ (M1 state) or IL4 (M2 state). When both IFNγ and IL4 were administered, the gene expression

trajectories are in the middle of the previous two trajectories, suggesting that cells are in a hybrid state

(hybrid M state). We aim to use NetAct to elucidate the crosstalk in transcriptional regulation downstream

of cytokine-induced signaling pathways during macrophage polarization.

Here, we applied GSEA on six comparisons – untreated versus IFNγ treated samples (one comparison

between the untreated and the treated after two hours, another between the untreated and the treated after

four hours, same for the other comparisons), untreated versus IL4 treated samples, and untreated versus

IFNγ+IL4 treated samples. Using our mouse literature-based TF-target database, we identified 79 TFs (q-

value cutoff 0.05 for UT vs IL4-2h and 0.01 for all others). The expression and activity profiles of these

TFs (Fig. 6abc) captures the essential dynamics of transcriptional state transitions during macrophage

polarization as follows. NetAct successfully identified important TFs in these processes, including Stat1,

the major target of IFNγ, Stat2, Stat6, Cebpb, Nfkb family members, Hif1a and Myc[68–70]. Myc is known to

be induced by IL-4 at later phases of M2 activation and required for early phases of M1 activation[69].

Interestingly, we find Myc has high expression in both IL4 stimulation and its co-stimulation with IFN but

its activity is high only in IL4 stimulation. We then constructed a TF regulatory network that connects 60

TFs (Fig. 6d) and simulated the network with RACIPE, from which we found that simulated gene

expression (Fig. 6f) matches well with experimental gene expression data (Fig.6a) (see Supplemental

Information SI7). RACIPE simulations display disparate trajectories from UT to IL4 or IFNγ activation and

stimulation with both IL4 and IFNγ. Strikingly, we found in the simulation that there is a spectrum of hybrid

M states between M1 and M2 (Fig. 6e), which is consistent with experimental observations of macrophage

polarization[68]. Moreover, we also predict from our GRN modeling that the transition from UT to hybrid M

is likely to first undergo a transition to either M1 or M2 before a second transition to hybrid M (Fig. 6e).

This is because of our observation from the simulation data that there are fewer models connecting UT and

hybrid M than any of the other two routes (*i.e.*, UT to M1, and UT to M2) (Fig. S10). Taken together we

showed that the NetAct-constructed GRN model captures the multiple cellular state transitions during

macrophage polarization.

In conclusion, we show that NetAct can identify the core TF-based GRN using both the literature-based

TF-target database and the gene expression data. We also demonstrate how RACIPE-based mathematical

modeling complements NetAct-based GRN inference in elucidating the dynamical behaviors of the inferred

GRNs. Together these two methods can be applied to infer biologically relevant regulatory interactions and

the dynamical behavior of biological processes.

Discussion

In this study, we have developed NetAct – a computational platform for constructing and modeling

core transcription factor (TF)-based regulatory networks. NetAct takes a data-driven approach to establish

gene regulatory network (GRN) models directly from transcriptomics data and takes a mathematical

modeling approach to characterize cellular state transitions driven by the inferred GRN. The method

specifically integrates both literature-based TF-target databases and transcriptomics data of multiple

394 experimental conditions to accurately infer TF transcriptional activity based on the expression of their target

395 genes. Using the inferred TF activity, NetAct further constructs a TF-based GRN, whose dynamics can then

396 be evaluated and explored by mathematical modeling. Our approach in combining top-down and bottom-

397 up systems biology approaches will contribute to a better understanding of gene regulatory mechanism of

398 cellular decision making. NetAct is made freely available as an R package[71].

400 One of the key components of NetAct is a pre-compiled TF-target gene set database. Here, we have

401 evaluated different types of TF-target databases in identifying knocked down TFs using publicly available

402 transcriptomics data sets. In this test, we have considered databases derived from literature, gene co-

403 expression, cis-motif prediction, and TF-binding motif data. Our benchmark tests suggest that the literature-

404 based database clearly outperformed the other databases. The literature-based database usually contains a

405 small (~30) number of target genes for each TF, but these data have direct experimental evidence, therefore

406 being more reliable than those from the other sources. However, the literature-based database for sure has

407 missing regulatory interactions, therefore maybe limiting the overall performance of NetAct. One way to

408 address this issue is to further update the literature-based database, once new information is available.

409 Another potential approach is to compile a database by combining different types of databases together.

410 However, this might be quite challenging as different databases have data of very different sizes (the

411 number of target genes) and quality. Future investigations on this direction can help to expand our

412 knowledge of transcriptional regulation and meanwhile improve the performance of the algorithm.

414 NetAct also has a unique approach to infer the TF activity from the gene expression of the target genes

415 with the consideration of activation/inhibition nature. From our in-silico benchmark tests, we found that

416 NetAct outperforms major activity inference methods, owing to the design of the filtering step and the use

417 of a high-quality TF-target database. NetAct is also robust against some inaccuracy in the TF-target

418 database and noises in gene expression data, because of its capability of filtering out irrelevant targets as

419 well as remaining key targets.

One potential issue is the assignment of the sign of TF activity, as it is algorithmically assigned

according to the correlation with TF expression. In the case where the TF expression is very noisy or the

expression is completely unrelated to TF activity, the sign assignment might be inaccurate. To deal with

this issue, we have devised a semi-manual approach that identifies the sign of TF activity according to the

sign of other interacting TFs. Another potential issue is that some TFs from the same family may have very

similar target genes, therefore NetAct will have difficulty in identifying exactly which TF from the family

is most relevant. Additional data resources, such as epigenomics[72], TF-binding data[36] and Hi-C data[73], will

be helpful to address this problem. One of the future directions is to design methods to integrate these data

resources.

Lastly, instead of constructing a global transcriptional regulatory network, NetAct focuses on modeling

a core regulatory network with only interactions between key TFs. The underlying hypothesis is that these

TFs and the associated regulatory interactions play major roles in controlling the gene expression of

different cellular states and the patterns of state transitions. With the core network identified using NetAct,

we can further perform simulations with mathematical modeling algorithms, such as RACIPE, to analyze

the control mechanism of the core network. These simulations allow us to generate new hypotheses, which

can be further tested experimentally. The validation data can further help to improve the model. Ideally,

this needs to be an iterative process to refine a core network model, which is indeed another interesting

future direction.

Conclusions

We developed NetAct, a computational platform for constructing and modeling core transcription-

factor regulatory networks using both transcriptomics data and literature-based transcription factor-target

gene databases. Utilizing both types of resources allows us to identify regulatory genes and links specific

to the data and fully take advantage of the existing knowledgebase of transcriptional regulation. Our method

446 in combining top-down and bottom-up systems biology approaches contributes to a better understanding of

447 the mechanism of gene regulation driving cellular state transitions.

Methods

Selecting Enriched TFs

For a comparison between two experimental conditions, we obtained a ranked gene list quantified by

the absolute value of the test statistics (t statistics in microarray and Wald test statistics in RNA-Seq) from

differential expression (DE) analysis[74], followed by gene set enrichment analysis (GSEA)[75] using our

optimized transcription factor (TF)-target gene set database. Here, for each TF, the corresponding gene set

consists of all its target genes. GSEA identifies important TFs whose targets are enriched in DE genes

between the two conditions. The significance test is achieved through 10,000 permutations of the gene list

names and TFs are kept for further analysis when q value is below a certain threshold cutoff (0.05 by

default). A C++ implementation of this version of GSEA, specifically for gene name permutations, has

been provided in NetAct for fast computation. For multiple comparisons, a set of enriched TFs are first

identified from each pairwise comparison and then a union of the multiple sets of TFs is considered.

In the database benchmark test, for each database, we computed the sensitivity and specificity values

for different q-value cutoffs. Here, for each cutoff value, we defined the sensitivity as the proportion of data

sets where the gene sets for the KD TFs were enriched with q-values below the cutoff value. We also

defined specificity as the fraction of cases where the gene sets for the other TFs (non-KD TFs in the

benchmark) were not enriched with q-values above the cutoff value. We then computed area under the ROC

curve (AUC) using the DescTools R package[76].

Inferring TF activity

TF activity is inferred from the expression of target genes retrieved from the TF-target database. NetAct

defines the activity of the selected TFs using two different schemes – one using only the expression of

target genes and the other using the expression of both the TF and its target genes. The second scheme is

only used for the situation of noisy target gene expression. For each TF, the algorithm selects the better

scheme according to their performance, as described below.

Without directly using TF expression: For each TF, its downstream targets are first divided into two

modules using the Newman's community detection algorithm[77] on the pairwise Spearman correlation

matrix of the target genes. Then, within each module some less-correlated genes are filtered out to improve

the quality of the inference. Here, the filtering step is achieved as follows: (1) each target gene is assigned

a vector of correlations with the other target genes, where the distance between two genes is calculated as

the sum of squares of the correlation vectors of two genes. (2) k-mean algorithm (k = 1) is performed within

each cluster to determine the center vector. (3) genes are filtered out if the distance between the genes and

the center is larger than the average distance.

This step outputs two groups of genes – genes in one group are supposed to be activated by the TF,

while genes in the other group are inhibited by the TF. Note, at this stage, the nature of activation/inhibition

of the individual group is not yet determined. The activity of the TF is calculated as

488
$$A(TF) = \frac{\sum_{i=1}^{n} w_i g_i I_i}{\sum_{i=1}^{n} w_i} \quad \text{(eq 1)},$$

489   where g_i is the standardized expression value of a target gene i, w_i is the weighting factor defined as a Hill

490   function:

491
$$w_i = 1/[1 + (\frac{s_i}{s_0})^n] \quad \text{(eq 2)},$$

where s_i is the adjusted p value from DE analysis for gene i, the threshold S_0 is 0.05, and n is set to be 1/5

for best performance (Fig. S8). I_i is 1 if the corresponding gene belongs to the first group and -1 if it belongs

to the second group. If the calculated TF activity pattern is not consistent with the TF expression trend

(evaluated by Spearman correlation), both the sign of the two groups and the sign of the activity are flipped.

According to our in-silico benchmark test (Fig. S9), we found that majority of the targets in one group are

activated by the TF, and majority of those in the other group are inhibited by the TF. For genes in the

inhibition group, the higher the TF activity, the more the genes are suppressed. Thus, the formula in

Equation (1) captures well the activity of TFs for their effects to both activating and inhibitory targets. We

also explored a few other community detection algorithms[78–80] and found they produced similar results (Fig.

S1).

Using TF expression: For each TF, its downstream targets are first divided into two groups according to

the sign of the Spearman correlation between the TF expression and the target expression. Similar to the

previous scheme, in each group, target genes are filtered out if the correlation value is less than the average

correlation of all the targets. The activity of the TF is also calculated using Equation 1.

Sign assignment for DE TF: For any DE TF (*i.e.*, there is significant difference in TF expression across cell

type conditions) of interest, NetAct computes the activity values from both the schemes (with or without

TF's expression), and selects the better way based on how well the activity values correlate with target

expression. To this end, NetAct calculates the absolute value of Spearman correlation between the TF

activity and the expression of each target, and selects the scheme whose activity gives larger average

correlations.

Sign assignment for non-DE TF: If the expression patterns of the identified TFs fail to show the significant

differences between cell type conditions, a semi-manual method to assign the sign of activity can be adopted.

Putative interaction partners between DE and non-DE TFs in the inferred network are identified using the

Fisher's Exact Test between TF targets in the NetAct TF-target database. The most significant pairs are

then cross referenced with the STRING database to identify instances of PPI. A literature search is then

performed to identify the nature of the PPI, and the sign of the non-DE TF is adjusted based on the DE TF

and the type of PPI. Note that the last step needs to be done manually for each modeling application. Table

S3 shows the details of TF sign flipping and supported experimental evidence for the two network modeling

applications.

Network construction and mathematical modeling

NetAct constructs a TF regulatory network using both the TF-TF regulatory interactions from the TF-

target database and the activity values. (1) The network is constructed using mutual information between

the activity values of two TFs. (2) Interactions are filtered out if they cannot be found in the TF-target

regulatory database (*i.e.*, D1). (3) The sign of each link is determined by the sign of the Spearman

correlation between the activity of two TFs. (4) We keep the interaction between two TFs if their mutual

information is higher than a threshold cutoff. With different cutoff values for mutual information, NetAct

establishes networks of different sizes. To identify the best network model capturing gene expression

profiles, we apply mathematical modeling to each of the TF networks using RACIPE[29]. RACIPE takes

network topology as the input and generates an ensemble of mathematical models with random kinetic

parameters. By simulating the network, we expect to obtain multiple clusters of gene expression patterns

that are constrained by the complex interactions in the network. RACIPE was also applied to generate

simulated benchmark test sets for a synthetic TF-target network (see Supplemental Material SI5).

Declarations:

Ethics approval and consent to participate

Not applicable

Consent for publication

Not applicable

Availability of data and materials

The information of the TF-target gene set databases is listed in Table S1. The public gene expression

datasets for algorithm optimization and benchmark are listed in Table S2. The datasets and computational

scripts for in-silico benchmark, the network modeling scripts, including those for data processing, network

construction and network simulations, and the inferred network topology files are available in the GitHub

repository at https://github.com/lusystemsbio/NetActAnalysis. The NetAct software is available at

https://github.com/lusystemsbio/NetAct as an R package. NetAct is platform independent, written in R with

a partial of codes in C++ for improved performance. NetAct is licensed under the MIT License.

Competing interests

556 The authors declare that they have no competing interests

Funding

559 The study is supported by startup funds from The Jackson Laboratory and Northeastern University, by the

560 National Cancer Institute of the National Institutes of Health under Award Number P30CA034196, and by

561 the National Institute of General Medical Sciences of the National Institutes of Health under Award Number

562 R35GM128717.

Authors' contributions

M.L conceived the study. K.S. developed and V.K. and A.K. improved the NetAct algorithm. A.K.

constructed and performed in-silico benchmark. K.S. and V.K. performed benchmark tests on public

experimental gene expression data. B.C. and V.K. performed network modeling. D.D. helped to refine the

NetAct code. S.L, K.K., and Z.S.Q. provided conceptual input to the manuscript. K.S., A.K., V.K. and M.L

wrote the manuscript, with helps from all other authors. The authors read and approved the final manuscript.

Acknowledgements

Not applicable

Reference:

1. Margolin, A. A. *et al.* ARACNE: An Algorithm for the Reconstruction of Gene Regulatory

Networks in a Mammalian Cellular Context. *BMC Bioinformatics* **7**, S7 (2006).

2. Alvarez, M. J. *et al.* Functional characterization of somatic mutations in cancer using network-

based inference of protein activity. *Nat. Genet.* **48**, 838 (2016).

3. Ament, S. A. *et al.* Transcriptional regulatory networks underlying gene expression changes in

Huntington's disease. *Mol. Syst. Biol.* **14**, e7435 (2018).

4. Chan, T. E., Stumpf, M. P. H. & Babtie, A. C. Gene Regulatory Network Inference from

Single-Cell Data Using Multivariate Information Measures. *Cell Syst.* **5**, 251-267.e3 (2017).

5. Carré, C., Mas, A. & Krouk, G. Reverse engineering highlights potential principles of large

gene regulatory network design and learning. *Npj Syst. Biol. Appl.* **3**, 17 (2017).

6. Fiers, M. W. E. J. *et al.* Mapping gene regulatory networks from single-cell omics data. *Brief.*

Funct. Genomics doi:10.1093/bfgp/elx046.

7. Gérard, C. & Goldbeter, A. Temporal self-organization of the cyclin/Cdk network driving the

mammalian cell cycle. *Proc. Natl. Acad. Sci.* **106**, 21643–21648 (2009).

8. Laub, M. T., McAdams, H. H., Feldblyum, T., Fraser, C. M. & Shapiro, L. Global Analysis of

the Genetic Network Controlling a Bacterial Cell Cycle. *Science* **290**, 2144–2148 (2000).

9. Li, F., Long, T., Lu, Y., Ouyang, Q. & Tang, C. The yeast cell-cycle network is robustly

designed. *Proc. Natl. Acad. Sci.* **101**, 4781–4786 (2004).

10. Nieto, M. A., Huang, R. Y.-J., Jackson, R. A. & Thiery, J. P. EMT: 2016. *Cell* **166**, 21–45

(2016).

11. Kim, J., Chu, J., Shen, X., Wang, J. & Orkin, S. H. An Extended Transcriptional Network for

Pluripotency of Embryonic Stem Cells. *Cell* **132**, 1049–1061 (2008).

12. Loh, Y.-H. *et al.* The Oct4 and Nanog transcription network regulates pluripotency in mouse

embryonic stem cells. *Nat. Genet.* **38**, 431 (2006).

13. Katebi, A., Ramirez, D. & Lu, M. Computational systems-biology approaches for modeling

gene networks driving epithelial–mesenchymal transitions. *Comput. Syst. Oncol.* **1**, e1021

(2021).

14. Alon, U. *An Introduction to Systems Biology : Design Principles of Biological Circuits*.

(Chapman and Hall/CRC, 2006). doi:10.1201/9781420011432.

15. Kirk, P. D. W., Babtie, A. C. & Stumpf, M. P. H. Systems biology (un)certainties. *Science*

350, 386–388 (2015).

16. Chasman, D. & Roy, S. Inference of cell type specific regulatory networks on mammalian

lineages. *Curr. Opin. Syst. Biol.* **2**, 130–139 (2017).

17. Ben-Jacob, E., Lu, M., Schultz, D. & Onuchic, J. N. The physics of bacterial decision

making. *Front. Cell. Infect. Microbiol.* **4**, 154 (2014).

18. Dutta, P., Ma, L., Ali, Y., Sloot, P. M. A. & Zheng, J. Boolean network modeling of β-cell

apoptosis and insulin resistance in type 2 diabetes mellitus. *BMC Syst. Biol.* **13**, 36 (2019).

19. Steinway, S. N. *et al.* Network Modeling of TGFβ Signaling in Hepatocellular Carcinoma

Epithelial-to-Mesenchymal Transition Reveals Joint Sonic Hedgehog and Wnt Pathway

Activation. *Cancer Res.* **74**, 5963–5977 (2014).

20. Zeigler, A. C. *et al.* Computational model predicts paracrine and intracellular drivers of

fibroblast phenotype after myocardial infarction. *Matrix Biol.* **91–92**, 136–151 (2020).

21. Kanehisa, M., Furumichi, M., Sato, Y., Ishiguro-Watanabe, M. & Tanabe, M. KEGG:

integrating viruses and cellular organisms. *Nucleic Acids Res.* **49**, D545–D551 (2021).

22. Krämer, A., Green, J., Pollard, J. & Tugendreich, S. Causal analysis approaches in Ingenuity

Pathway Analysis. *Bioinforma. Oxf. Engl.* **30**, 523–530 (2014).

23. Ramirez, D., Kohar, V. & Lu, M. Toward Modeling Context-Specific EMT Regulatory

Networks Using Temporal Single Cell RNA-Seq Data. *Front. Mol. Biosci.* **7**, 54 (2020).

24. Dunn, S., Li, M. A., Carbognin, E., Smith, A. & Martello, G. A common molecular logic

determines embryonic stem cell self-renewal and reprogramming. *EMBO J.* **38**, e100003

(2019).

25. Wooten, D. J., Gebru, M., Wang, H.-G. & Albert, R. Data-Driven Math Model of FLT3-ITD

Acute Myeloid Leukemia Reveals Potential Therapeutic Targets. *J. Pers. Med.* **11**, 193

(2021).

26. Udyavar, A. R. *et al.* Novel Hybrid Phenotype Revealed in Small Cell Lung Cancer by a

Transcription Factor Network Model That Can Explain Tumor Heterogeneity. *Cancer Res.*

77, 1063–1074 (2017).

27. Wooten, D. J. *et al.* Systems-level network modeling of Small Cell Lung Cancer subtypes

identifies master regulators and destabilizers. *PLOS Comput. Biol.* **15**, e1007343 (2019).

28. Khan, F. M. *et al.* Unraveling a tumor type-specific regulatory core underlying E2F1-

mediated epithelial-mesenchymal transition to predict receptor protein signatures. *Nat.*

Commun. **8**, 198 (2017).

29. Kohar, V. & Lu, M. Role of noise and parametric variation in the dynamics of gene

regulatory circuits. *Npj Syst. Biol. Appl.* **4**, 1–11 (2018).

30. Moignard, V. *et al.* Decoding the regulatory network of early blood development from

single-cell gene expression measurements. *Nat. Biotechnol.* **33**, 269–276 (2015).

31. Sha, Y., Wang, S., Zhou, P. & Nie, Q. Inference and multiscale model of epithelial-to-

mesenchymal transition via single-cell transcriptomic data. *Nucleic Acids Res.* **48**, 9505–

9520 (2020).

32. Lu, M., Jolly, M. K., Levine, H., Onuchic, J. N. & Ben-Jacob, E. MicroRNA-based

regulation of epithelial–hybrid–mesenchymal fate determination. *Proc. Natl. Acad. Sci.* **110**,

18144–18149 (2013).

33. Jang, S. *et al.* Dynamics of embryonic stem cell differentiation inferred from single-cell

transcriptomics show a series of transitions through discrete cell states. *eLife* **6**, e20487

(2017).

34. Alvarez, M. J. *et al.* Functional characterization of somatic mutations in cancer using

network-based inference of protein activity. *Nat. Genet.* **48**, 838 (2016).

35. Liao, J. C. *et al.* Network component analysis: Reconstruction of regulatory signals in

biological systems. *Proc. Natl. Acad. Sci.* **100**, 15522–15527 (2003).

36. Aibar, S. *et al.* SCENIC: single-cell regulatory network inference and clustering. *Nat.*

Methods **14**, 1083–1086 (2017).

37. Huang, B. *et al.* Interrogating the topological robustness of gene regulatory circuits by

randomization. *PLOS Comput. Biol.* **13**, e1005456 (2017).

38. Katebi, A., Kohar, V. & Lu, M. Random Parametric Perturbations of Gene Regulatory

Circuit Uncover State Transitions in Cell Cycle. *iScience* **23**, 101150 (2020).

39. Huang, B. *et al.* Decoding the mechanisms underlying cell-fate decision-making during stem

cell differentiation by random circuit perturbation. *J. R. Soc. Interface* **17**, 20200500 (2020).

40. Subramanian, A. *et al.* Gene set enrichment analysis: a knowledge-based approach for

interpreting genome-wide expression profiles. *Proc. Natl. Acad. Sci. U. S. A.* **102**, 15545–

15550 (2005).

41. Han, H. *et al.* TRRUST: a reference database of human transcriptional regulatory

interactions. *Sci. Rep.* **5**, 11432 (2015).

42. Liu, Z.-P., Wu, C., Miao, H. & Wu, H. RegNetwork: an integrated database of transcriptional

and post-transcriptional regulatory networks in human and mouse. *Database* **2015**, (2015).

43. Essaghir, A. & Demoulin, J.-B. A Minimal Connected Network of Transcription Factors

Regulated in Human Tumors and Its Application to the Quest for Universal Cancer

Biomarkers. *PLOS ONE* **7**, e39666 (2012).

44. Jiang, C., Xuan, Z., Zhao, F. & Zhang, M. Q. TRED: a transcriptional regulatory element

database, new entries and other development. *Nucleic Acids Res.* **35**, D137–D140 (2007).

45. Abugessaisa, I. *et al.* FANTOM5 transcriptome catalog of cellular states based on Semantic

MediaWiki. *Database J. Biol. Databases Curation* **2016**, (2016).

46. Lachmann, A. *et al.* ChEA: transcription factor regulation inferred from integrating genome-

wide ChIP-X experiments. *Bioinformatics* **26**, 2438–2444 (2010).

47. Wingender, E., Dietze, P., Karas, H. & Knüppel, R. TRANSFAC: A Database on

Transcription Factors and Their DNA Binding Sites. *Nucleic Acids Res.* **24**, 238–241 (1996).

48. Sandelin, A., Alkema, W., Engström, P., Wasserman, W. W. & Lenhard, B. JASPAR: an

open-access database for eukaryotic transcription factor binding profiles. *Nucleic Acids Res.*

32, D91–D94 (2004).

49. null, null. The ENCODE (ENCyclopedia Of DNA Elements) Project. *Science* **306**, 636–640

(2004).

50. Aibar, S. *et al.* SCENIC: single-cell regulatory network inference and clustering. *Nat.*

Methods **14**, 1083–1086 (2017).

51. Abugessaisa, I. *et al.* FANTOM5 transcriptome catalog of cellular states based on Semantic

MediaWiki. *Database J. Biol. Databases Curation* **2016**, baw105 (2016).

52. Garcia-Alonso, L., Ibrahim, M. M., Turei, D. & Saez-Rodriguez, J. Benchmark and

integration of resources for the estimation of human transcription factor activities. *bioRxiv*

337915 (2018) doi:10.1101/337915.

53. Alvarez, M. J., Sumazin, P., Rajbhandari, P. & Califano, A. Correlating measurements across

samples improves accuracy of large-scale expression profile experiments. *Genome Biol.* **10**,

R143 (2009).

54. Langfelder, P. & Horvath, S. WGCNA: an R package for weighted correlation network

analysis. *BMC Bioinformatics* **9**, 559 (2008).

55. Hu, M. & Qin, Z. S. Query Large Scale Microarray Compendium Datasets Using a Model-

Based Bayesian Approach with Variable Selection. *PLOS ONE* **4**, e4495 (2009).

56. Schaffter, T., Marbach, D. & Floreano, D. GeneNetWeaver: in silico benchmark generation

and performance profiling of network inference methods. *Bioinformatics* **27**, 2263–2270

(2011).

57. Margolin, A. A. *et al.* ARACNE: An Algorithm for the Reconstruction of Gene Regulatory

Networks in a Mammalian Cellular Context. *BMC Bioinformatics* **7**, S7 (2006).

58. Levandowsky, M. & Winter, D. Distance between Sets. *Nature* **234**, 34 (1971).

59. Huynh-Thu, V. A., Irrthum, A., Wehenkel, L. & Geurts, P. Inferring Regulatory Networks

from Expression Data Using Tree-Based Methods. *PLOS ONE* **5**, e12776 (2010).

60. Moerman, T. *et al.* GRNBoost2 and Arboreto: efficient and scalable inference of gene

regulatory networks. *Bioinformatics* **35**, 2159–2161 (2019).

61. Kim, S. ppcor: An R Package for a Fast Calculation to Semi-partial Correlation Coefficients.

Commun. Stat. Appl. Methods **22**, 665–674 (2015).

62. Pratapa, A., Jalihal, A. P., Law, J. N., Bharadwaj, A. & Murali, T. M. Benchmarking

algorithms for gene regulatory network inference from single-cell transcriptomic data. *Nat.*

Methods **17**, 147–154 (2020).

63. Sartor, M. A. *et al.* ConceptGen: a gene set enrichment and gene set relation mapping tool.

Bioinformatics **26**, 456–463 (2010).

64. Schiffer, M., Von Gersdorff, G., Bitzer, M., Susztak, K. & Böttinger, E. P. Smad proteins

and transforming growth factor-β signaling. *Kidney Int.* **58**, S45–S52 (2000).

65. Zhang, Y., Feng, X.-H. & Derynck, R. Smad3 and Smad4 cooperate with c-Jun/c-Fos to

mediate TGF-β-induced transcription. *Nature* **394**, 909–913 (1998).

66. Jolly, M. K. *et al.* Implications of the Hybrid Epithelial/Mesenchymal Phenotype in

Metastasis. *Front. Oncol.* **5**, (2015).

67. Piccolo, V. *et al.* Opposing macrophage polarization programs show extensive epigenomic

and transcriptional cross-talk. *Nat. Immunol.* **18**, 530–540 (2017).

68. Mosser, D. M. & Edwards, J. P. Exploring the full spectrum of macrophage activation. *Nat.*

Rev. Immunol. **8**, 958–969 (2008).

69. Bae, S. *et al.* MYC-mediated early glycolysis negatively regulates proinflammatory

responses by controlling IRF4 in inflammatory macrophages. *Cell Rep.* **35**, 109264 (2021).

70. Hu, X. & Ivashkiv, L. B. Cross-regulation of Signaling Pathways by Interferon-γ:

Implications for Immune Responses and Autoimmune Diseases. *Immunity* **31**, 539–550

(2009).

71. NetAct: https://github.com/lusystemsbio/NetAct.

72. Pliner, H. A. *et al.* Cicero Predicts cis-Regulatory DNA Interactions from Single-Cell

Chromatin Accessibility Data. *Mol. Cell* **71**, 858-871.e8 (2018).

73. Malysheva, V., Mendoza-Parra, M. A., Saleem, M.-A. M. & Gronemeyer, H. Reconstruction

of gene regulatory networks reveals chromatin remodelers and key transcription factors in

tumorigenesis. *Genome Med.* **8**, 57 (2016).

74. Ritchie, M. E. *et al.* limma powers differential expression analyses for RNA-sequencing and

microarray studies. *Nucleic Acids Res.* **43**, e47 (2015).

75. Subramanian, A. *et al.* Gene set enrichment analysis: A knowledge-based approach for

interpreting genome-wide expression profiles. *Proc. Natl. Acad. Sci.* **102**, 15545–15550

(2005).

76. Signorell, A. *et al.* DescTools: Tools for Descriptive Statistics. (2022).

77. Newman, M. E. J. Modularity and community structure in networks. *Proc. Natl. Acad. Sci.*

103, 8577–8582 (2006).

78. Reichardt, J. & Bornholdt, S. Statistical mechanics of community detection. *Phys. Rev. E* **74**,

016110 (2006).

79. Newman, M. E. J. Analysis of weighted networks. *Phys. Rev. E* **70**, 056131 (2004).

80. Newman, M. E. J. Finding community structure in networks using the eigenvectors of

matrices. *Phys. Rev. E* **74**, 036104 (2006).

 Figures

Fig.1. Schematics of NetAct. (**a**) First, key transcription factors (TFs) are identified using gene set

enrichment analysis (GSEA) with a literature-based TF-target database. (**b**) Second, the TF activity of an

individual sample is inferred from the expression of target genes. From the co-expression and modularity

analysis of target genes, we find target genes that are either activated (blue), inhibited (red), or not

strongly related to the TF (grey). The activity is defined as the weighted average of target genes activated

by the TF minus the weighted average of target genes inhibited by the TF. (**c**) Lastly, a TF regulatory

network is constructed according to the mutual information of inferred TF activity and literature-based

regulatory interactions. (**d**) Performance of GSEA for various TF-target gene set databases. The plot

shows the sensitivity and specificity with different q-value cutoffs. The gene set databases in the

benchmark include the combined literature-based database (D1), FANTOM5-based databases (D2) with

20, 50, 100 target genes per TF, the combined experimental-based database (D3, ChIP), and RcisTarget

databases (D4), one with 10 targets per TF binding motif and another with 50 total number of targets per

TF.

768
Fig.2. Illustration of the grouping scheme for target genes of a transcription factor. (**a**) shows the co-
expression matrix of MYB target genes in shRNA knockdown of MYB lymphoma cells by hierarchical
clustering analysis (Pearson correlation and complete linkage). (**b, c**) demonstrate the poor clustering
results from the co-expression of randomly selected 100 (in **b**) and 200 genes (in **c**). In panels (**a – c**), the
left subplots show the outcomes of all tested genes, and the right subplots show the outcomes of genes
after the filtering step. Compared to the random cases, MYB target genes have a clear pattern of red and
blue diagonal blocks from their co-expression. (**d**, **e**) show the percentage of differentially expressed
genes remained after the filtering step in the case of FOXM1 and MYB knockdown, respectively. (**f**, **g**)
show the proportion of genes from the activation group that are positively correlated with the TF
expression (red bars) and the proportion of genes from the inhibition group that are negatively correlated
with the TF expression (blue bars). (**h**) Pearson correlation (average and standard deviation) between TF
activity and target expression (red) and between TF expression and target expression (blue).

Fig. 3. Simulation of both gene expression and activity of a synthetic GRN. (a) shows the synthetic GRN consisting of 30 TFs and 447 target genes. An edge of transcriptional activation is shown as black line with an arrowhead; an edge of transcriptional inhibition as red line with a blunt head; an edge of signaling interaction as green line with an arrowhead. Transcription factor labeled as TF9 was selected for knockdown simulations. (**b**) shows the summary of the correlation analyses of the simulated expression and activity. The left, middle, and right columns represent the outcomes for TF and target activities, TF and target expressions, and TF activities and target expressions, respectively. For each category, the histograms of Spearman correlations are shown for non-interacting gene pairs (first row), interacting gene pairs (second row), gene pairs of excitatory transcriptional regulation (third row), gene pairs of excitatory signaling regulation (fourth row), gene pairs of inhibitory transcriptional regulation (fifth row). Here, the target activity is set to be the same as the target expression for non-TF genes. (**c**) shows the histograms of Spearman correlations for gene pairs of target genes from the same TF. (**d**) Jaccard indices between the ground-truth regulons of the synthetic GRN and the regulons inferred by ARACNe using either the simulated expression (red) or activity data (blue).

Fig. 4. The performance of activity and network inference from a simulation benchmark. **(a)** TF activity inference. TF activity was inferred by several methods using the gene expression data simulated from the synthetic TF-target gene regulatory network (GRN) and the corresponding regulons. For each TF, we computed Spearman correlations between the inferred activity and simulated activity (ground truth) for all the simulated models. Then, we calculated the average correlation values over all TFs. The plots show the median of average correlations for the cases where we used the original regulons defined by the TF-target network (0% perturbation), and the regulons where 5 (25% perturbation), 10 (50% perturbation), and 15 (75% perturbation) target genes are randomly replaced with non-interacting genes, respectively. The median values were computed over 100 repeats of random replacement for each perturbation level, and the values of the average correlations are reported for the case of zero perturbation. Shown are the results for NetAct (red), NCA (blue), VIPER (cyan), AUCELL 1 where regulons contain only positively associated target genes (orange), and AUCELL 2 where regulons contain all target genes (green). **(b-d)** Network inference. The panels show the performance of network inference algorithms from the simulation benchmark by the precision and recall for different link selection thresholds. **(b)** Network inference performance against all ground-truth regulatory interactions. Tested methods are GENIE3, GRNBoost2, and PPCOR, using transcription factor (TF) expression; GENIE3 using TF activity inferred by AUCell; NetAct using its inferred TF activity. For the latter two methods, original (unperturbed) regulons obtained from the regulatory network were used. **(c)** Network inference performance of NetAct against all ground-truth regulatory interactions using the regulons with 0% (the original), 25%, 50%, and 75% target perturbations. **(d)** Network inference performance of NetAct in discovering new regulatory interactions not existing in the regulons. NetAct was applied using the regulons at different perturbation levels (25%, 50%, and 75%). The benchmark results shown here are for the case of the untreated simulation. The results for the case of the knockdown simulation are shown in **Fig. S7**.

Fig. 5 Network modeling of TGF-β induced EMT. Application of NetAct to an EMT in human cell lines using time-series microarray data. (**a**) Experimental expression and activity of enriched transcription factors. (**b**) Inferred TF regulatory network. Blue lines and arrowheads represent gene activation; Red lines and blunt heads represent gene inhibition. (**c**) The relationship between SMAD3 gene activity and the first principal component of the activity of all network genes from RACIPE simulations. (**d**) Hierarchical clustering analysis of simulated gene activity (with Pearson correlation as the distance function and Ward.D2 linkage method). Colors at top indicate the two clusters from the simulated gene activity. The blue cluster represents the mesenchymal state, and the yellow cluster represents the epithelial state. The color legend for the heatmap is at the bottom right. (**e**) Knockdown simulations of the TF regulatory network. The bar plot shows the proportion of RACIPE models in each state (epithelial or mesenchymal) for the conditions of the knockdown of every TF.

Fig 6. Network modeling of macrophage polarization. Application of NetAct to induced macrophage polarization via drug treatment in mice using RNA-seq data. **(a)** Experimental expression and activity of enriched TFs. **(b)** PCA projection of genome-wide gene expression profiles. Different point shapes indicate time after treatment, and colors indicate treatment types **(c)** PCA projection of gene activity of enriched TFs. **(d)** Inferred TF regulatory network. Blue lines and arrowheads represent gene activation; Red lines and blunt heads represent gene inhibition. **(e)** PCA projection of simulated gene activity of inferred network colored by mapping each model back to experimental data. **(f)** Hierarchical clustering analysis of simulated gene activity (with Pearson correlation as the distance function and Ward.D2 linkage method). Colors at top indicate the mapped experimental conditions. The color legend of the heatmap is at the bottom.