Age-related reorganization of functional network architecture for language processing

Running title: Age-related reorganization of functional networks in language

Sandra Martin[1,2*], Kathleen A. Williams[1], Dorothee Saur[2], Gesa Hartwigsen[1]

[1] Lise Meitner Research Group Cognition and Plasticity, Max Planck Institute for Human Cognitive and Brain Sciences, Leipzig, Germany

[2] Language & Aphasia Laboratory, Department of Neurology, University of Leipzig Medical Center, Leipzig, Germany

Main text word count: 4996

Abstract: 150

Number of Figures: 6
Number of Tables: 2

*Correspondence should be addressed to:

Sandra Martin

Lise Meitner Research Group Cognition & Plasticity

Max Planck Institute for Human Cognitive and Brain Sciences

Stephanstr. 1a

04103 Leipzig, Germany

martin@cbs.mpg.de

phone: +49 341 99402683

Abstract

Cognitive aging is associated with widespread neural reorganization processes in the human brain. However, the behavioral impact of such reorganization is not well understood. The current neuroimaging study investigated age differences in the functional network architecture during language production. Combining task-based functional connectivity, graph theory and cognitive measures of fluid and crystallized intelligence, our findings show age-accompanied large-scale network reorganization even when older adults have intact word retrieval abilities. In particular, functional networks of older adults were characterized by reduced decoupling between systems, reduced segregation and efficiency, and a larger number of hub regions relative to young adults. Exploring the predictive utility of these age-related changes in network topology revealed high, albeit less efficient, performance for older adults whose brain graphs showed stronger dedifferentiation and reduced distinctiveness. Our results have important implications for theoretical accounts of neurocognitive aging, indicating a successful compensatory network reconfiguration at the cost of efficient wiring.

Keywords: aging, functional connectivity, semantic memory, graph theory, language production

Introduction

Communication is an essential human ability for everyday life. It draws on the general knowledge of words, concepts, and ideas we accumulate across the lifespan, so-called semantic memory, as well as personal experiences, also referred to as episodic memory[1]. Although communication abilities remain largely intact in healthy aging, and copious evidence has shown preservation or even increases in semantic memory through adulthood into very old age[2–4], memory problems in verbal communication, such as finding the right word and tip-of-the-tongue episodes, are a common complaint with increasing age[5]. This paradox has been explained in terms of less efficient access and retrieval processes during language production that rely on semantic and cognitive control functions like working memory, attention, and inhibitory control, and are well established to steadily decline with age[6]. Thus, the impact of aging on communicative abilities may vary as a function of an individual's cognitive control abilities and intact semantic memory. However, little is known about the neural mechanisms underlying those subtle changes in communicative abilities with age.

The recent conceptualization of the brain as a complex modular system[7,8] provides a unique framework to examine age-related changes in neural information processing and their consequences for behavior. To this end, graph-theoretical measures offer an analytical method to model such complex systems and explore organization principles of human brain networks[9,10]. Links between functional connectivity within and across specialized modules or neural networks and cognitive outcomes in young adults have revealed a topological organization of the brain that combines local information processing with global information integration aimed at optimizing global cost efficiency ("small world" organization)[11,12]. Age-related changes to this modular organization have been described as a general decline of functional network segregation evident in the form of decreased within- and enhanced between-network functional connectivity[13–15]. Moreover, increasing age has been associated with reduced small-world organization, modularity, and local and global efficiency of functional brain networks[16–19]. The impact of such reorganization on cognition remains debated. Most studies associated neural dedifferentiation with performance decline[13,18,20], whereas some have pointed towards a pattern of compensational response, where reduced network segregation counteracts the age-related decline of brain function to maintain successful performance[15].

While the majority of studies investigated functional connectivity from resting-state functional magnetic resonance imaging (fMRI), important insight can be gained through task-based functional connectivity. Interestingly, age-accompanied differences in network topology during task processing largely concur with reported patterns in resting-state in the form of stronger integration and reduced segregation[21–23]. However, their behavioral relevance seems to depend on the cognitive resources required for the task of interest. Research from domains well known to steadily decline with age, such as episodic and working memory, reported compensational recruitment of control and attention networks for successful performance[21,24,25] but also maintenance processes with age to preserve

neural resources despite structural deterioration[26,27]. A different picture emerges for cognitive

abilities that remain stable with age like language and creativity. Here, increased connectivity

between usually anti-correlated networks such as executive and default networks might be

advantageous for older adults when access to semantic memory and little cognitive control are

required so that they can rely on prior knowledge to maintain high performance[23,28,29].

Despite its relevance for successful verbal communication, research on age-related network

organization during semantic word retrieval is sparse. In this context, semantic fluency tasks are

especially valuable since they tap into semantic memory but also cognitive control processes and

are often linked to preserved albeit slower performance in older adults[30]. Previous studies revealed

age-related reduced functional connectivity within domain-specific networks during semantic word

retrieval, however, without affecting behavioral performance[31,32]. Furthermore, we recently showed

that functional connectivity within and between domain-general networks like the default and

multiple-demand network differently impacts the behavior of older and young adults during a

semantic fluency task, even when network coupling is age-invariant[29]. Thus, domains that are

usually well-preserved with age offer an opportunity to inform the current understanding of age-

accompanied changes in the architecture of functional brain networks and their behavioral

relevance regarding compensatory and aberrant mechanisms.

The present study addresses this gap by exploring age-related reorganization of functional

networks during processing of a semantic word retrieval task. Networks of task-based functional

connectivity in groups of healthy young and older adults were derived via data-driven, multivariate

methods. We were interested in age differences in the coupling of task-relevant networks and their

behavioral relevance. Furthermore, we applied graph-theoretical measures of brain system

segregation, integration, and network hubs to investigate the network topology in young and older

adults. Leveraging recent advances in network neuroscience, we used orthogonal minimum

spanning trees[33] (OMST) for the calculation of graph measures to avoid arbitrary thresholding of

functional connectivity matrices[34]. These measures were then related to participants' in-scanner

task performance and abilities of fluid and crystallized intelligence to examine the prognostic utility

of age-related changes in brain network topology. Exploring task-based network topologies as a

function of cognitive performance in a domain that is usually well preserved with age enabled us to

gain key insights into age-related reorganization processes within subjects and to inform theoretical

accounts regarding compensatory and detrimental effects of neurocognitive aging on behavior.

Results

The main objective of this study was to investigate age-related changes in integration and segregation of functional neural networks engaged in the goal-directed access to semantic memory. By contrasting a paced overt semantic fluency task with an overt counting task, we delineated neural networks specific to semantic access and control processes in healthy young (n = 30, mean = 27.6 years, SD = 4.3, range = 21–34) and older adults (n = 31, mean = 65.5 years, SD = 2.75, range = 60–69 years). Due to strong in-scanner motion (>1 voxel size), data from three older participants had to be excluded from further analyses, leading to a final sample size of 28 participants in the older group. While both groups were matched for gender, participants in the young group had significantly more years of education (t(55.86) = 5.21, p < 0.001). During one experimental session, participants completed two runs of the fMRI experiment (Figure 1a) followed by a neuropsychological assessment probing semantic knowledge as well as verbal- and non-verbal executive functions (Table 1). Consistent with previous research, older adults only performed better for the measure of semantic memory (spot-the-word test; t(54.39) = 3.14, p = 0.003), indicating a maintenance of semantic knowledge and an increase in vocabulary with age[4], while young adults performed better on all other tests (all at p < 0.01), which is consistent with the assumption of a general age-related decline of executive functions[6]. For all reported correlation analyses, neuropsychological measures were summarized via exploratory factor analysis (Methods). Results revealed an "executive functions" factor with high loadings on Trail Making Tests A (0.8) and B (0.71), Digit Symbol Substitution Test (0.73), and reading span test (0.45), and a "semantic memory" factor with spot-the-word test (0.5) and verbal fluency tests for hobbies (0.44) and surnames (0.98). For the in-scanner tasks, we fitted mixed-effects models accounting for individual variance of participants and semantic categories via random effects and the difference in years of education via covariate (Table S1). Likelihood-ratio tests showed that both age groups performed similarly (x^2 = 2.18, p = 0.14) and generally better for counting than semantic fluency (x^2 = 8.06, p = 0.005; Figure 1b). For response time, results showed an interaction between task and age group (x^2 = 79.73, p < 0.001) with older adults performing slower than young adults during the semantic fluency but not the counting task (Figure 1c).

Figure 1. Experimental design. (a) The fMRI experiment consisted of 43-s task blocks of overt paced semantic fluency and counting, which were presented in a pseudorandomized order and separated by 16-s rest periods. Two examples for each task are shown. There were 10 blocks per run for each task. At the beginning of a task block, a 2 s visual word cue indicated whether participants were expected to generate category exemplars or count forward (1 to 9) or backward (9 to 1). Participants were instructed to produce exactly one exemplar for a category or to say one number when the fixation cross turned green and to pause when the cross turned red. If they could not think of an exemplar, they were instructed to say "next". Each task block contained 9 trials of the same semantic category/counting task which were separated by jittered inter-stimulus intervals. (b) and (c) show behavioral results for each task and age group. While results revealed better performance for counting than semantic fluency in both groups but no difference in accuracy between age groups, older adults performed slower during semantic fluency than young adults.

Table 1. Characteristics and neuropsychological test results of participants

	Young adults (n = 30)	Older adults (n = 28)
Demographics		
Age (years)	27.6 (4.4)	65.2 (2.8)
Gender (F:M)	16:14	14:14
Education (years)	18.7 (2.6)	15.2 (2.5)*
Beck Depression Inventory (cut-off 18 points)	–	4.7 (4.1)
Neuropsychological		
Spot-the-word test (max. 40)	29.1 (3.2)	31.5 (2.5)*
Semantic fluency (sum surnames, hobbies)	51.2 (8.4)	40.7 (6.7)*
Reading span test (max. 6)	3.5 (1)	2.9 (0.7)*
Digit symbol substitution test (max. 90 in 90 s)	72.1 (11.4)	50.2 (10.4)*
Trail Making Test A (time in s)	17.3 (5.8)	25.4 (6.4)*

Trail Making Test B (time in s)	36.1 (11.9)	61.8 (29.4)*
Mini-Mental State Examination (max. 30 points)	–	28.36 (1.2)

163 *Note.* Mean values of raw scores with standard deviations. * Significant differences between age
164 groups at *p* < 0.01.

Goal-directed access to semantic memory involves default, semantic, and executive control networks

Using the data-driven method of group spatial independent component analysis (ICA) on the whole
data set, we defined functional cortical networks for the semantic task. The ICA identified 55
components of which 42 were clearly attributable to artifacts. From the resulting 13 non-noise
components, low-level sensory components including auditory, sensorimotor, and visual networks
were identified and removed since their roles were beyond the scope of our investigation. For
reference, all independent components are displayed in Figure S1.
The remaining seven components were submitted to one-sample t-tests and thresholded
controlling the family-wise error (FWE) rate at peak level with *p* < 0.05 and a cluster-extent
threshold of 10 voxels. Figure 2 shows the thresholded maps with their original component number.
To determine which cognitive network best described each component, we calculated the Jaccard
similarity coefficient (*J*) between our thresholded, binarized components of interest and template
masks of common resting-state[35] and semantic cognition networks[36]. Results showed similarity
above threshold (*J* = 0.15) for all component maps with distinct cognitive networks (Table 2). For
IC06, we found overlap with the frontoparietal control network C (CONT-C) and default mode
network A (DMN-A). Although spatial similarity was marginally higher for CONT-C than DMN-A
$(J_{\text{Control C}} - J_{\text{Default A}} = 0.01)$, we refer to this component as part of the default system. Significant
clusters included classic midline structures of the core default network[37] like posterior cingulate
cortex, precuneus, and prefrontal cortex (Figure 2). An additional analysis of similarity coefficients
between the component maps and the 7-networks parcellation[35] revealed a stronger similarity with
the default network as a whole for this component $(J_{\text{Control}} - J_{\text{Default}} = -0.03$; see Table S2 for results
with the 7-networks parcellation). Furthermore, a second component (IC13) showed strong similarity
with DMN-A. As described in Methods, we combined the component maps of IC06 and IC13 to
assess whether this would lead to a numerical improvement of *J*. Results showed that this was not
the case with *J* = 0.21 for the combined components which was below the similarity coefficient of
IC13 alone (*J* = 0.26). Thus, both components represented distinct parts of DMN-A and were hence
included in subsequent analyses. For IC13, we further included default mode network C (DMN-C),
which showed the second strongest overlap and was represented by significant clusters in bilateral
parahippocampal gyri. Indeed, a combined template of DMN-A and DMN-C led to a numerical
improvement in similarity compared to DMN-A alone $(J_{\text{Default A + C}} - J_{\text{Default A}} = 0.091)$. Thus, to gain

a comprehensive representation of the default network, both subsystems were combined and are

referred to as default mode network A+C (DMN-A+C).

Results of Jaccard calculations further revealed the following networks for the other

components: default mode network B (DMN-B; IC16) with peak activations in bilateral middle

temporal gyri (MTG), inferior and superior frontal gyri (IFG, SFG), and left angular gyrus (AG);

semantic network (SEM; IC18) with strong overlap with the semantic control network and peak

activations in left IFG, SFG, paracingulate gyrus, posterior superior temporal gyrus (STG), and AG;

frontoparietal control network B (CONT-B; IC09) with large clusters in bilateral SFG and middle

frontal gyri (MFG), AG, and posterior MTG; ventral attention network B (VAN-B; IC45) with peak

activation in prefrontal cortex including paracingulate gyrus, bilateral IFG and supramarginal gyri;

and dorsal attention network A (DAN-A; IC52) with large clusters in bilateral AG, and

temporooccipital cortex. Statistical tables with all significant clusters are reported in Supplementary

Table S3. The overlap between each component and the selected cognitive network is shown in

Figure 2.

Figure 2. ICA-derived networks and their overlap with cognitive networks. T-scores from one-
sided t-tests (FWE-corrected *p* < 0.05 at peak level) are displayed for the seven selected
component maps with their respective network label according to spatial similarity analysis.
Overlaps between the thresholded component map and the spatially most similar cognitive network
according to the Jaccard index are outlined on the surface of the brain. The areas of overlap were
used for subsequent network analyses.

Table 2. Jaccard indices for independent components and cognitive networks

	IC06	**IC09**	**IC13**	**IC16**	**IC18**	**IC45**	**IC52**
Frontoparietal control A	0.054	0.133	0.032	0.013	*0.151*	0.083	0.109
Frontoparietal control B	0.091	**0.210**	0.028	0.073	0.125	0.050	0.018
Frontoparietal control C	*0.168*	0.020	0.066	0.010	0.010	0.028	0.044
Default A	**0.154**	0.089	**0.255**	0.149	0.040	0.054	0.019
Default B	0.039	0.069	0.031	**0.263**	0.082	0.098	0.010

Default C	0.014	0.010	**0.122**	0.008	0.026	0.001	0.020
Dorsal attention A	0.051	0.041	0.062	0.015	0.054	0.003	**0.180**
Dorsal attention B	0.008	0.038	0.006	0.006	0.071	0.053	0.123
Limbic A	0.000	0.001	0.002	0.014	0.002	0.002	0.011
Limbic B	0.001	0.007	0.015	0.004	0.009	0.005	0.002
Ventral attention A	0.042	0.012	0.023	0.015	0.033	0.124	0.065
Ventral attention B	0.014	0.074	0.001	0.031	0.059	**0.195**	0.039
Somatomotor A	0.022	0.052	0.000	0.039	0.036	0.029	0.028
Somatomotor B	0.000	0.016	0.038	0.009	0.033	0.011	0.015
Temporal parietal	0.001	0.029	0.014	0.118	0.023	0.035	0.034
Central visual	0.022	0.006	0.006	0.038	0.011	0.004	0.123
Peripheral visual	0.025	0.009	0.074	0.020	0.038	0.034	0.037
General semantic cognition	0.032	0.030	0.072	*0.194*	**0.201**	0.092	0.050
Semantic control	0.012	0.036	0.012	0.067	*0.153*	0.091	0.027

Note. The selected network labels for the respective independent components are shown in bold while all cognitive networks that showed a higher similarity coefficient than $J = 0.15$ are shown in italics.

Stronger coupling of default and executive systems predicts intact but less efficient semantic retrieval in older adults

Following rigorous quality control and data-cleaning procedures (Methods), functional brain networks (graphs) were constructed based on the seven networks derived from the ICA. For each participant, a graph consisting of seven nodes each representing one network, as well as a graph with 121 nodes based on significant clusters within each network (see Figure 4a for all 121 nodes) were created. Graphs were then submitted to correlational psychophysiological interaction analyses (cPPI)[38] to extract task-related connectivity for our condition of interest (semantic fluency). In contrast to traditional PPI analysis, cPPI results in undirected, symmetric matrices that can be submitted to network analyses. We tested for statistically significant coupling differences between age groups by means of network-based statistics using permutation testing while controlling for in-scanner head motion (Figure 3a). Overall, the network of older adults showed reduced decoupling compared to young adults. This was especially the case for connectivity across different networks as shown by subsystems of the default network that were less decoupled from attention networks. Significantly stronger positive coupling was found in the graphs of older adults for the networks SEM with VAN-B, CONT-B with VAN-B, and DAN-A with VAN-B. A similar picture of age-related differences emerged for the more fine-grained graphs containing 121 nodes. Here, young adults

generally showed stronger positive coupling within individual networks and between subsystems of
the default network and stronger decoupling between different networks (Figure S2).
We probed the behavioral relevance of the network connection pairs that showed significant
age differences by calculating mixed-effects models for accuracy and response time data (Figure
3b; Table S4-5). These models and all subsequent reported models controlled for years of
education and head motion defined as average framewise displacement (FD) and included random
intercepts for participants and semantic categories. Continuous predictors were always mean-
centered before model estimation. Reported significant effects are based on likelihood-ratio tests.
Results were corrected for multiple comparisons using the Bonferroni-Holm method. For accuracy,
we found significant interactions between age and between-network connectivity for VAN-B with
DMN-A+C (x^2= 12.39, p = 0.002) and DAN-A (x^2= 14.18, p < 0.001). Predicting response time
revealed significant interactions between age and between-network connectivity for VAN-B with
DMN-A+C (x^2= 5.65, p = 0.035), SEM (x^2= 25.75, p < 0.001), and DAN-A (x^2= 28.81, p < 0.001),
and for DAN-A with DMN-B (x^2= 51.76, p < 0.001). For older adults, increased coupling between
default and attention networks predicted high but less efficient performance, while increased
coupling of SEM and VAN-B and between both attention systems (DAN-A and VAN-B) was
associated with faster responses. A different picture emerged in young adults, where stronger
coupling between default and executive systems predicted faster but poorer performance while
increased connectivity between DAN-A and VAN-B was associated with better and faster reactions.
These results suggest that both age groups showed distinct connectivity profiles, with older adults
generally profiting from increased coupling between different cognitive systems and the opposite
pattern for young adults.
263

Figure 3. Functional coupling between task-relevant networks in young and older adults and their behavioral relevance. (a) Chord diagrams display significant results of functional coupling between the ICA-derived networks. Connectivity values are partial correlations. The color intensity and width of a connection indicate its correlational strength. Red indicates coupling and blue indicates decoupling between networks. Chord diagrams of each age group are based on cPPI-derived significance values while age differences were assessed using permutation testing in network-based statistics (cluster-forming threshold at $p = 0.01$, FWE-corrected significance threshold at $p = 0.05$ with 10,000 permutations). (b) Network connections that showed significant age differences were probed for their behavioral relevance. Plots show significant two-way interactions between age and the respective network pair for accuracy and response time data. Connectivity values were mean-centered for interaction analyses. Results were corrected for multiple comparisons using the Bonferroni-Holm method at $p = 0.05$. VAN ventral attention network, DAN dorsal attention network.

Reduced segregation and higher integration of task-relevant networks is associated with better and more efficient performance in older adults

Next, we investigated brain system segregation and integration to get a better understanding of age-related differences in whole-brain dynamics (Figure 4a). Segregation quantifies the presence of densely connected regions that form distinct subnetworks or communities in a global brain network (Figure 4b). In functional connectivity networks, such communities are indicative of functional specialization and segregated neural processing[9,10]. Results of a linear mixed-effects model for global brain system segregation revealed a significant effect of age ($x^2 = 11.23$, $p < 0.001$) with

young adults exhibiting stronger segregation than older adults (Figure 4c; Table S6). Examining the

predictive value of segregation for in-scanner performance and neuropsychological measures

revealed significant interactions between age and segregation for accuracy (x^2 = 9.54, p = 0.002),

response time (x^2 = 71.15, p < 0.001), and a significant correlation of segregation with executive

functions in young adults (r = 0.45, p = 0.013). For all interactions, increasing levels of segregation

predicted better and faster performance in young adults. In contrast, increasing brain-wide

segregation had no effect on accuracy but predicted faster responses in older adults (Figure 4c;

Table S7).

We used the measure of global efficiency to assess network integration. Global efficiency is

calculated as the inverse of the sum of shortest paths between all nodes in a network and is thus a

measure of efficient signal transmission[39]. In brain networks, it is used to assess their capacity for

parallel information transfer and integrated processing[11]. Like most graph theoretical measures, the

calculation of global efficiency requires a sparse graph to represent a biologically plausible network

of functional connectivity[40]. Following recent work on the most reliable and representative

construction of brain networks[33,40,41], we calculated individual OMST based on the weighted

functional connectivity matrices and used the OMST to assess global efficiency. A linear mixed-

effects model indicated higher global efficiency for young adults (x^2 = 21.86, p < 0.001; Figure 4d;

Table S8). Efficiency values were then entered into regression models to assess their predictive

value. Results showed a significant main effect of global efficiency for accuracy (x^2 = 8.79, p =

0.003) and a significant interaction with age for response time (x^2 = 41.79, p < 0.001). While

increasing system-wide efficiency was generally associated with better performance, it also

predicted faster performance in older adults but slower responses in young adults (Figure 4d; Table

S9).

Figure 4. Age-related differences in whole-brain segregation and integration and their behavioral relevance. (a) For each participant, a task-related brain network graph was constructed using 121 nodes. The nodes were based on significant global and local peak maxima of the seven networks derived from the ICA (see Supplementary Table S1 for exact locations of nodes). (b) Spring-embedded graphs depicting age differences in the modular organization of the brain. Graphs are based on average connectivity in each age group. Stronger segregation is reflected by higher within- and lower between-network correlations. In comparison, young adults show stronger segregation than older adults for most networks. For visualization purposes, graphs are displayed at 5% graph density. (c) Brain-wide system segregation was higher for young adults and had distinct

effects on behavior for each age group with young adults profiting from increasing segregation. (d)
A different picture emerged for global efficiency, a measure of network integration. Global efficiency
was calculated for individual orthogonal minimum spanning trees, which were based on weighted
correlation matrices. The graphs of young adults showed stronger global efficiency than older
adults. While increasing global efficiency was associated with better performance in both age
groups, it predicted a slower performance in the group of young adults and a faster performance in
older adults. Note that segregation and global efficiency values were mean-centered for analyses
with behavior.

Brain system segregation predicts age-related differences in behavior as a function of

network type

We next examined whether segregation differed between networks. Previous research showed that

networks exhibit differences in their patterns of age-related changes in segregation[13]. While these

studies focused on a broad distinction of sensorimotor and cognitive association networks, we

investigated segregation and its behavioral relevance for each network individually to explore age-

accompanied differences as a function of system type. Overall, results showed that all networks

were less segregated in older than young adults (x^2 = 47.06, p < 0.001; Figure 5a). However,

networks' increasing segregation differed in their behavioral relevance (Table S11). For accuracy,

we detected significant interactions between age and network segregation (Figure 5b) for DMN-B

(x^2 = 5.76, p = 0.016) and VAN-B (x^2 = 18.22, p < 0.001). For response time (Figure 5c), results

showed significant interactions with age and the networks DMN-A (x^2 = 79.3, p < 0.001), CONT-B

(x^2 = 21.16, p < 0.001), and DAN-A (x^2 = 68.62, p < 0.001). Overall, stronger segregation of different

systems was associated with better and faster performance for young adults and poorer and slower

reactions in older adults. Only increasing segregation of DMN-A predicted slower reactions in young

adults which might point to a different role of this system in semantic cognition. We also explored

the relationship of network segregation with neuropsychological measures (Figure 5d). Results

revealed a significant positive correlation of segregation in the VAN-B with executive measures in

young adults (r = 0.4, p = 0.03) and a negative correlation of DMN-B with semantic memory in older

adults (r = -0.38, p = 0.045).

In summary, exploring brain system integration and segregation in a semantic task revealed

age-specific dynamics where young adults clearly profit from a stronger modular network

organization whereas increasing integration improves efficiency only in the aging brain.

Figure 5. Segregation of individual networks is associated with distinct behavior of older and
young adults as a function of system type. (a) Individual networks' segregation values by age.
All networks showed stronger segregation in young adults. (b) Generalized linear mixed-effects
models for accuracy revealed significant interactions with age and network segregation for two
systems while (c) linear mixed-effects models for response time showed significant interactions for
three networks. For most networks, increasing segregation was associated with better and faster
performance in young adults and worse and slower reactions in older adults. (d) Significant
correlations between network segregation and neuropsychological measures. For young adults, we
detected a positive correlation of increasing segregation of VAN-B with executive functions,
whereas for older adults, a negative correlation of increasing segregation of DMN-B with semantic
memory was found. Note that segregation and global efficiency values were mean-centered for
analyses with behavior. VAN ventral attention network, DAN dorsal attention network.

Stronger system-wide integration of brain networks in older adults is facilitated by additional

connector hubs in frontal and temporal regions

An important characteristic of large-scale brain organization is the presence of regions, or nodes,

that play an important role in facilitating communication between communities of a network. These

nodes, commonly referred to as connector hubs, are defined by a high number of connections

(edges) diversely distributed across communities[42]. Previous work has highlighted their crucial role

for integrative processing in resting- and task-state networks[43]. We explored the existence of

connector hubs via the normalized participation coefficient (PC)[44]. Results revealed connector hubs

in bilateral frontal, parietal, and temporal regions in both age groups (Figure 6a; Table S12-13).

Notably, there were multiple nodes from the subsystems of the default network and CONT-B

identified as connector hubs in the bilateral regions of the inferior parietal lobe and AG.

Furthermore, both age groups had connector hubs in the right MTG and MFG. In older adults,

additional connector hubs were found in the left inferior temporal gyrus and the frontal pole. A linear

model revealed nodes with stronger PC only in the graphs of older adults: in the frontal pole, which

was also identified as a connector hub, STG, and bilateral fusiform gyri (Figure 6b; Table S14).

Figure 6. Topology of network hubs in young and older adults. (a) The normalized participation
coefficient (PC) was calculated for individual orthogonal minimum spanning trees (OMST). Graphs
display the PC of each node for the average OMST in each age group (top). For visualization
purposes, the strongest 5% of connections are shown. Stronger PC values are reflected by color
and node size. The higher the PC, the more a node is connected with nodes from other
communities. The node with the highest PC value in each age group is extracted and displayed with
its neighboring nodes colored by community (middle). Note that these connector hubs are
connected to many different communities. Connector hubs were defined in each age group via PC
values at least 1SD above the mean. In both groups, connector hubs were detected in frontal,
parietal, and temporal regions (bottom). (b) A linear model with age as predictor revealed nodes
with stronger PC only in older adults. The top and middle graphs were plotted using the ForceAtlas2
algorithm. The force-directed layout causes nodes of the same community to cluster together and
diversely connected hubs (connector hubs) to appear in the center of the graph.

Discussion

The neural bases of cognitive aging remain poorly understood. It is especially debated how age-related neural reorganization impacts cognition. However, a better understanding of the neural resources that help to maintain cognitive functions and counteract decline would be mandatory to design more efficient treatment and training protocols. Previous work has largely focused on neural changes in resting-state and during processing of tasks that are primarily affected by age. In the present study, we approached this unresolved issue by investigating the functional brain organization of young and older adults in language, a key domain of human cognition that has been shown to be largely preserved in healthy aging. As a main result, we demonstrate a large-scale age-related reconfiguration of the network architecture even when older adults show intact word retrieval abilities. Overall, networks showed increased integration of task-negative and task-positive networks with age which manifested as increased coupling between functional connectivity networks, reduced segregation of global brain systems, and a larger number of connector hubs in brain graphs of older adults. Associating these age-related differences in network profiles with behavior revealed intact, albeit less efficient, performance for more integrated systems in older adults. These findings shed new light on the frequently reported pattern of declining brain system segregation with age and its impact on cognition[13,22]. Extending previous work from different cognitive domains, our results indicate a compensatory role of increased brain system integration but also reveals its limitations in terms of economical processing.

Using task-based fMRI data and group spatial ICA, we characterized seven higher-order large-scale functional networks relevant to semantic word retrieval across participants. These included default, semantic, frontoparietal control, and attention networks. Notably, our analysis detected two networks associated with semantic processing: a network component showing spatial similarity with an ALE-derived network of general semantic cognition[36] and another component overlapping with the subnetwork DMN-B[35] which has been proposed to facilitate access to semantic knowledge[1,37]. Both networks overlap in key regions of semantic processing, including left IFG, MTG, and AG. However, while the network identified as DMN-B involved bilateral ATL regions, a cross-modal hub of semantic processing[1], the semantic network component showed stronger activity in frontal regions that have been attributed to semantic control processes[36]. The semantic network component also showed strong spatial similarity with a semantic control network and a subnetwork of frontoparietal control. Thus, the networks SEM and DMN-B, which were derived in a data-driven manner for our task, appear to represent complementary aspects of semantic cognition. Moreover, in line with our previous work[29], we detected default as well as executive control and attention systems, thereby lending support to the notion that networks that have been characterized as anti-correlated during resting-state become functionally integrated for successful task processing when controlled access to semantic memory is required[45]. Indeed, exploring task-based functional connectivity within and between these networks in both age groups showed strong positive coupling

not only between subnetworks of the same system, such as the default network, but also between

distinct cognitive networks. Two subnetworks of the default network, DMN-A and DMN-B, were

strongly coupled with the frontoparietal control network. This finding agrees with accumulating

evidence that the default network integrates with control and executive resources during goal-

directed task processing[45,46], especially when complex behavior is supported by knowledge[47], and

thus enables flexible cognition[37].

Our results on age-related differences in network coupling revealed additional integration of

distinct networks with age. Older adults showed stronger positive coupling of SEM, CONT-B, and

DAN-A with VAN-B relative to young adults, suggesting an increased cognitive demand during

semantic processing. In contrast, networks of young adults displayed stronger decoupling of default

systems with attention networks. Previous work indicates a modulation of network integration

through task demand in young adults with more demanding cognitive functions benefiting from a

more integrated brain organization to facilitate information flow across components[43,46,48]. Our

results transfer this observation to the aging brain and demonstrate increased crosstalk between

networks with age. Importantly, when we associated the age-related differences in network coupling

with behavior, we found that enhanced coupling of different cognitive systems like default and

attention networks was associated with consistently high but less efficient performance in older

adults. Conversely, only increased connectivity between subsystems of the attention network

predicted better and more efficient performance in young adults. Our findings offer a new

perspective on the effect of a more integrated network structure in the aging brain on cognitive

function. Consistent with results from the domains of working memory, episodic memory, and

creative thinking[21,24,25,28], we demonstrate that enhanced integration of different cognitive systems in

older adults is associated with high accuracy but at the cost of efficiency. While this network

structure helps older adults to maintain cognitive flexibility, it might not be the most efficient form of

wiring. These results point towards a compensatory response to age-related decline of brain

function during semantic word retrieval.

We gained further insight into age differences in network architecture through the application

of graph-theoretical measures. Exploring integration and segregation on a brain system level

allowed us to investigate age-related changes in organization principles of task-state networks. Our

results revealed global decreases in segregation and efficiency with age. The reduction of

segregation in older adults is in line with previous work from resting-state[13,19,20] and task-based

studies[22,24,25], as well as longitudinal investigations[16–18], and suggests that aging is associated with a

reduced ability for specialized processing within highly connected clusters[10]. This was further

confirmed by our results on segregation of each individual network where young adults generally

showed stronger segregation.

In terms of global efficiency, the majority of resting-state and task-based studies reported

lower global efficiency in older adults[18,20,49], although variability is high, and some have also

reported no changes or even increases with age[13,17,19,50]. These discrepancies might stem from

methodological considerations such as the number of nodes in a brain graph since global efficiency

is based on the length of its edges[51] or different thresholding methods of connectivity matrices like

the commonly applied proportional thresholding, which has been shown to introduce spurious

correlations and inflate group-related differences in graph metrics[34]. To avoid these pitfalls, our

calculation of global efficiency was based on the recently developed OMST[33], a data-driven

approach of individualized graph construction with high reliability[40,41].

Reduced global efficiency implies higher wiring cost and a less efficient information flow

among distributed networks of the global brain system[11]. This is especially relevant for the

processing of complex cognitive functions like semantic word retrieval which require the integration

of distinct networks, as revealed by our functional connectivity analyses. At the neurobiological

level, these changes have been associated with reduced functional connectivity of long-range

connections in older adults[20]. Thus, even though functional networks become more integrated with

age, potentially due to stronger activation of more but less specialized nodes, the efficient

information transfer between different networks is impaired leading to slower processing in aging.

This observation may represent an overall decline of cognitive attention systems in the aging brain,

reflected in slower responses with similar task accuracy, which was already evident at the

behavioral level in our data.

Additional evidence for this interpretation stems from the larger number of connector hubs in

older adults, as revealed by a higher nodal participation coefficient with age. Recent work on the

reconfiguration of networks from resting- to task-state in the young brain has shown an increase of

connector hubs with enhanced task demands to facilitate integration across different networks and

enable better task performance[48,52]. Moreover, studies in healthy aging have found more connector

hubs in older adults also during resting-state, indicating a reduced distinctiveness of network-

specific nodes[18,19,53]. Our work confirms these findings during task processing and allows an

interpretation in light of the semantic nature of our task. Nodes with a higher participation coefficient

in older adults were located in frontal and temporal regions and associated with CONT-B, DAN-A,

and SEM networks. This result underlines the enhanced cognitive demand during semantic word

retrieval with age and provides a mechanistic explanation for the frequently reported pattern of over-

activation of prefrontal control regions during demanding task processing in older adults[54]. A

reduced selectivity in activation of network nodes and hence an over-recruitment of less specialized

brain regions leads to a decline in efficient neural processing between brain regions, and this

process might form the basis of neural dedifferentiation in aging[18,53]. Its effect on cognition, aberrant

or compensatory, depends on the neurocognitive requirements of a task and an individual's neural

resources.

Exploring the topology of task-relevant neural networks as a function of cognitive

performance allowed us to directly link observed age-related differences with behavior. Our results

show that young adults strongly capitalized on a more segregated system during task processing,

as evidenced by improved and more efficient performance during semantic word retrieval and

generally better executive functions. This was true for increasing segregation on a global system

level, but also for most individual networks. In contrast, increasing segregation of the whole brain

graph predicted faster but not better performance in older adults. When zooming into individual

networks, more segregation did not benefit older adults' behavior. Notably, enhanced segregation of

DMN-B correlated negatively with semantic memory functioning in older adults, confirming the

significance of this network for access to semantic memory and its necessary integration with

domain-general default and executive networks for successful word retrieval in aging. Moreover,

increasing global efficiency predicted better performance across groups but faster responses only in

older adults. These findings have important implications for current theories on the behavioral

impact of network reorganization in aging. While a less selective and more integrated network

organization might not be the most efficient system in terms of processing speed, it enables older

adults to maintain high performance. Consistent with previous task-based investigations[21,24,25,28], our

findings thus point towards a compensatory mechanism of age-accompanied reconfiguration in

network topologies. However, our results also reveal the limitations of such compensatory

reorganization processes and demonstrate that a youth-like network architecture in terms of

balanced integration and segregation is associated with more economical processing.

523   In conclusion, our findings provide evidence for age-accompanied large-scale network

reorganization during access to semantic memory even when older adults show intact word retrieval

abilities. In particular, functional networks of older adults were characterized by increased coupling

between different systems, reduced segregation and efficiency, and a larger number of hub regions

relative to young adults. Associating these changes with behavior revealed high, albeit less efficient,

performance for networks in older adults showing stronger dedifferentiation and reduced

distinctiveness. Our results are in line with compensatory accounts of network reconfiguration with

age, but also reveal the limitations of such reorganization processes.

Methods

Participants

Participants consisted of 31 healthy older adults (mean age: 65.5 years, range: 60–69 years) and 30 healthy young adults (mean age: 27.6 years, range: 21–34 years), which is the same sample as described previously[29]. Data of three older participants as well as single runs of six participants had to be excluded due to strong motion during fMRI (>1 voxel size), leading to a final sample size of 28 participants in the older group. Inclusion criteria were native German speaker, right-handedness, normal hearing, normal or corrected-to-normal vision, no history of neurological or psychiatric conditions, and no contraindication to magnetic resonance imaging. Older adults were additionally screened for cognitive impairments with the Mini-Mental State Examination[55] (all ≥26) points and for depression with the Beck Depression Inventory[56] (all ≤14 points). A battery of neuropsychological tests was administered to assess cognitive functioning. Semantic knowledge and verbal executive functions were assessed with the German versions of the spot-the-word test (Wortschatztest)[57], the reading span test[58], and the semantic fluency test, the latter consisting of two 1-min trials of semantic categories (hobbies and surnames) that were not part of the fMRI task (Regensburger Wortflüssigkeitstest)[59]. Non-verbal executive functions were measured with the Digit Symbol Substitution Test[60] and the Trail Making Test[61]. Differences between age groups for neuropsychological measures were determined with two-sample t-tests. Prior to the experiment, participants gave written informed consent. The study was approved by the local ethics committee of the University of Leipzig and conducted in accordance with the Declaration of Helsinki.

Experimental Procedures

The experimental procedure is reported in detail in previous work[29] and briefly summarized here. Participants completed one experimental session which consisted of two runs of the fMRI experiment and neuropsychological tests, and lasted two hours in total. Experimental tasks consisted of a paced overt semantic fluency task and a control task of paced overt counting, which were implemented in a block design in the scanner (Figure 1 in Results). For the semantic fluency task, participants were asked to produce exemplars for 20 semantic categories, which were divided in 10 easy (e.g., colors) and 10 difficult (e.g., insects) categories based on a separate pilot study in healthy young and older adults[29]. Task blocks were 43 s long and separated by rest blocks of 16 s. Each block started with a 2 s visual word cue indicating whether participants were expected to generate category exemplars or count forward (1 to 9) or backward (9 to 1). This was followed by nine consecutive trials of the same category or counting task, respectively. Trials within one block were separated by inter-stimulus intervals of 2-4 s. Participants were instructed to generate one exemplar for a category or one number per trial, which was indicated by a green cross on the screen, and to pause when the cross turned red. They were told not to repeat items and to say

"next" if they could not think of an exemplar for the respective category. Each run contained 10

semantic fluency blocks, divided in easy and difficult categories, and 10 counting blocks, consisting

of forward and backward counting, thus resulting in a total duration of 19.4 min per run. The order of

blocks was counter-balanced and pseudo-randomized across participants. Before the fMRI

experiment, participants received instructions and practiced the task with a separate set of

categories outside the scanner. Stimuli were presented using the software Presentation

(Neurobehavioral Systems, Berkeley, USA; version 18.0). Answers were recorded via a FOMRI III

microphone (Optoacoustics, Yehuda, Israel). After the experiment, response recordings were

analyzed for verbal answers and onset times after being cleaned from scanner noise via Audacity

software (version 2.3.2) and transcribed by three independent raters.

fMRI Data Acquisition and Preprocessing

fMRI data were collected on a 3 T Prisma scanner (Siemens, Erlangen, Germany) with a 32-

channel head coil. For the acquisition of functional images, a multiband dual gradient-echo echo-

planar imaging sequence was used for optimal blood oxygenation level-dependent (BOLD)

sensitivity throughout the entire brain[1,2]. The following scanning parameters were applied: TR =

2000 ms; TE = 12 ms, 33 ms; flip angle = 90°; voxel size = 2.5 x 2.5 x 2.75 mm with an inter-slice

gap of 0.25 mm; FOV = 204 mm; multiband acceleration factor = 2. To increase coverage of

anterior temporal lobe (ATL) regions, slices were tilted by 10° of the AC-PC line. 616 images

consisting of 60 axial slices in interleaved order covering the whole brain were continuously

acquired per run. Additionally, field maps were obtained for later distortion correction (TR = 8000

ms; TE = 50 ms). This study analyzed the data from echo 2 (TE = 33 ms) since preprocessing was

performed using the software fMRIPrep[3], which currently does not support the combination of

images acquired at different echo times. We chose to use results from preprocessing with fMRIPrep

since this pipeline provides state-of-the-art data processing while allowing for full transparency and

reproducibility of the applied methods and a comprehensive quality assessment of each processing

step that facilitates the identification of potential outliers. We also double-checked results from

preprocessing with fMRIPrep with a conventional SPM preprocessing pipeline of both echoes. The

comparison of both pipelines did not reveal big differences in analysis results. A high-resolution, T1-

weighted 3D volume was obtained from our in-house database (if it was not older than two years) or

collected after the functional scans using an MPRAGE sequence (176 slices in sagittal orientation;

TR = 2300 ms; TE = 2.98 ms; flip angle = 9°; voxel size = 1 x 1 x 1 mm; no slice gap; FOV = 256

mm). Preprocessing was performed using fMRIPprep 20.2.3[3] which is based on Nipype 1.6.1[4]. In

short, preprocessing steps included skull stripping, distortion correction, co-registration, slice timing

correction, and calculation of several confounding time-series for each of the two BOLD runs per

participant. Anatomical T1-weighted images were skull-stripped, segmented, and spatially

normalized. For spatial normalization to standard space, the Montreal Neurological Institute (MNI)
ICBM 152 non-linear 6th Generation Asymmetric Average Brain Stereotaxic Registration Model
(MNI152NLin6Asym) was entered as output space in fMRIPrep. For more details on the
preprocessing pipeline, see the section corresponding to workflows in fMRIPrep's documentation
(https://fmriprep.org/en/20.2.3/workflows.html). After preprocessing, 29 volumes from the beginning
of each run were discarded since they were collected for the combination of the short and long TE
images. This yielded 587 normalized images per run which were included in further analyses.

Independent component analysis

We applied group-wise ICA to define spatially independent task-active networks in a data-driven
manner. ICA has been shown to decompose fMRI time series into reliable functionally connected
components with the advantage of simultaneously removing non-neural fluctuations through the
identification of artefactual components[64]. Preprocessed, normalized data were smoothed with a 5
mm^3 FWHM Gaussian kernel and entered into a general linear model for each participant and
session using Statistical Parametrical Mapping software (SPM12; Wellcome Trust Centre for
Neuroimaging), implemented in MATLAB (version 9.10/R2021a). GLMs included regressors for the
task blocks (semantic fluency and counting) as well as nuisance regressors consisting of the six
motion parameters and individual regressors for strong volume-to-volume movement as indicated
by values of framewise displacement > 0.9[65]. Additionally, an individual regressor of no interest was
included in the design matrix if a participant had missed a whole task block during the experiment (n
= 10). Before model estimation, a high-pass filter with a cut-off at 128 s was applied to the data.
Preprocessed, normalized and smoothed data were analyzed using the Group ICA of fMRI
Toolbox (GIFT v4.0c). Dimensions were reduced to 55 using minimum description length
information criteria. Icasso was repeated 50 times to ensure reliability of the decomposition, and
group-level ICs were back-reconstructed to the participant level using the group-information guided
ICA (GICA3) algorithm[66]. We calculated group ICA treating all participants as one group to ensure
that the same components were identified in both groups. We discarded those components related
to banding artifacts and noise after careful visual inspection of the spatial maps according to
established criteria[64] (see Supplementary Figure S1 for an overview of all 55 ICs). Of the remaining
13 non-noise components, seven components of interest were selected. To characterize the spatial
extent of the seven remaining components at the group level, we calculated one-sided t-tests for
participants' spatial maps. A gray matter mask that restricted statistical tests to voxels in the
cerebrum was applied to all group-level analyses. Results were corrected for multiple comparisons
using a peak level threshold at p < 0.05 with the family-wise error (FWE) method and a cluster-
extent threshold of 10 voxels.

Brain network construction

Brain networks were constructed based on the seven selected component maps of the ICA. To determine network labeling of the thresholded maps, we used the Jaccard index (*J*), a measure of spatial similarity[67]. By calculating the ratio of overlapping voxels in two binary spatial network maps relative to all active voxels in either image, the Jaccard index can be used as a measure to assess the fit between a spatial component map (*A*) and a template image (*B*):

$$J = \frac{|A \cap B|}{|A \cup B|}$$

The index ranges from 0 to 1, with a high Jaccard index denoting high similarity of two spatial maps. It has been used previously to assess similarity of brain activation maps with template network parcellations[68,69]. We defined a minimum threshold of $J = 0.15$ to consider a network template for a spatial component mask[69]. Next, if two components were best described by the same network template thereby indicating that the network might have split up in multiple components, we assessed the similarity of the combined component maps to the template. If the combined map reached a higher similarity index than each component individually, the combination was kept as a reflection of the respective network.

As template masks, we used the 17-networks functional connectivity-based parcellation scheme[35] as well as the network masks of general semantic cognition and semantic control defined in a meta-analysis[36]. We included separate template masks for semantic cognition in our analysis to account for the semantic nature of our task. We also probed similarity of Jaccard indices with a 7-networks parcellation scheme[35]. While the results for the 7-networks parcellation generally agreed with the more fine-grained parcellation, the 7-networks parcellation resulted in three components showing high spatial similarity with the default network template. However, differential roles have been reported for subsystems of the default network when access to semantic memory is required[6]. Specifically, the dorsal medial subsystem of the default network ("Default B" in the 17-networks parcellation scheme) has been shown to broadly overlap with a left-lateralized temporal-frontal semantic network[6,7]. Since we were interested in the age-dependent interplay of domain-specific and domain-general networks in semantic cognition, the remaining analyses were based on the 17-networks parcellation scheme.

Based on the results of the Jaccard index, each thresholded component map was inclusively masked by the respective resampled template network. We were interested in the effect of age on the functional connectivity within and between selected networks. In a first step, to explore functional connectivity between networks, we extracted averaged time series across all voxels within one masked component, thus leading to seven time series per participant and run. Second, networks were further parcellated into distinct regions of interest (ROIs) based on peak maxima of activated clusters. ROIs were created for all peak maxima of a significant cluster (up to three ROIs

per cluster) using the MarsBar toolbox[70]. To this end, identified clusters were extracted from the

thresholded and masked component maps, spheres of 5 mm surrounding each maximum

coordinate were created, and, in a last step, both images were combined. In this way, we ensured

that ROIs would only contain voxels that were included in the group-level statistics. Parcellating the

seven network components based on strongest correlation peaks led to 126 cortical ROIs per

participant and run.

Functional time series were extracted for the seven ROIs and 126 ROIs parcellation

schemes from non-smoothed functional data. To account for motion artifacts and other signal

confounds, the following denoising pipeline was applied during time series extraction: 24

realignment parameters (six motion parameters, temporal derivatives, and quadratic terms), global

signal, and top five aCompCor components for white matter and cerebral spinal fluid, respectively.

Censoring included a framewise displacement threshold of 0.9 mm and 18 discrete cosine-basis

regressors to account for signal drifts. All these regressors were combined in a design matrix and

removed from the data in a single step[71,72]. The denoising strategy was based on recent

recommendations[73] that compared the performance of different denoising pipelines for analysis of

task-based functional connectivity. Consistent with previous research on resting-state functional

connectivity[74,75], the authors reported that the inclusion of global signal in a denoising pipeline

markedly reduced global motion artifacts and led to more comparable results across conditions in

task-based functional connectivity data[73]. Further, time series were detrended and demeaned, and

functional images were masked with a subject-specific, resampled gray matter mask before

denoising. During signal extraction for the set of 126 ROIs, the number of voxels per ROI and

participant were extracted. ROIs for which more than 15% of participants did not show any signal

coverage were excluded. The resulting 121 ROIs were used for the remaining analyses.

Functional connectivity matrices

We applied cPPI analyses[38] to obtain connectivity terms that describe task-related interactions

between our networks and regions of interest. In contrast to traditional PPI analyses, cPPI results in

undirected, symmetrical connectivity matrices that are based on pairwise partial correlations

between ROIs. We calculated cPPI for our contrast of interest semantic fluency > counting,

separately for the 7-networks and 121-ROIs parcellations. In brief, the deconvolved time series for

each ROI was multiplied with the task time course from the first-level GLM design matrix and

convolved with a canonical HRF to form a PPI term. Pairwise partial correlations were estimated

between PPI terms of two regions while controlling for the observed BOLD signal in both regions,

the original task regressor and average in-scanner head motion (mean FD). Connectivity matrices

were calculated for each run separately and then averaged, resulting in a 7 x 7 and 121 x 121

correlation matrix per participant. Subsequently, correlation coefficients were Fisher-transformed to
z values.

Network measures

Within- and between-network functional connectivity

Within- and between-network functional connectivity were explored for the 7-networks and 121-

ROIs connectivity matrices in both age groups. Using the connectivity matrices with seven networks

allowed us to investigate the coupling and decoupling between task-relevant networks while the

more fine-grained parcellation provided additional insights into the coupling of regions within distinct

networks. All subsequent network measures were based on the 121-ROIs connectivity matrices.

Brain system segregation

We calculated global segregation as previously implemented by Chan and colleagues[9,13,76], using

the unthresholded, weighted connectivity matrices. In line with previous work on functional

connectivity in healthy aging[18,76], we excluded negative correlations from segregation and

integration analyses by setting them to zero. Excluding negative correlations has been shown to

improve the reliability of graph measures[77] and to help avoid interpretational difficulty, for example

when it comes to concepts like shortest paths[78]. Building upon the network parcellation of our ICA

analysis, each functional network was treated as a distinct system, and segregation was computed

as the difference between mean within-system $(\overline{Z}_w)$ and mean between-system $(\overline{Z}_b)$ correlations

divided by mean within-system correlation as shown in the following equation:

731
$$\text{Brain system segregation} = \frac{\overline{Z}_w - \overline{Z}_b}{\overline{Z}_w}$$

A higher ratio score denotes greater separation of functional systems.

We also calculated segregation values for each functional network individually such that

within-system connectivity $\overline{Z}_w$ represents the mean of all edges (correlations) between pairwise

nodes that belong to the same network and between-system connectivity $\overline{Z}_b$ reflects the mean of all

edges between nodes of the respective network and all other nodes.

Edge filtering

Most graph theoretical measures require some form of filtering to obtain a sparse graph that is more

likely to represent true functional connectivity than a maximally dense graph as produced by a

correlation matrix[78]. While threshold-based filtering methods like proportional or absolute

thresholding are commonly applied in network neuroscience, they are driven by an arbitrary choice

of the respective threshold and suffer from low reliability[40]. To avoid these pitfalls and based on

recent research on the reliability of graph construction in neuroscience[40,41], we calculated the

orthogonalized minimum spanning tree (OMST)[33] on the weighted functional connectivity matrices. Apart from its high reliability, the OMST has several advantages compared to commonly applied threshold-based methods of graph construction: It adheres to the intrinsic topological structure of the brain network by resulting in a fully connected, weighted graph and offers a data-driven method of individualized network construction accounting for each individual's optimal state of economic wiring in terms of cost and efficiency. In contrast to the original minimum spanning tree (MST), the OMST filters connectivity networks until the highest global cost efficiency (GCE) of a graph is reached while including both strong and weak connections and preserving the same mean degree across groups.

The OMST was calculated in three steps as described by Dimitriadis et al. (2017): (a) the MST of a graph is defined; (b) the corresponding edges of the MST are removed from the original graph by setting edge weights to 0; (c) steps (a) and (b) are repeated until the GCE of the graph is optimized. GCE is defined as the global efficiency minus cost, where cost corresponds to the total weights of the selected edges of the OMST divided by the sum of the edges of the original fully weighted graph[12]. The final OMST is constructed by combining all the removed, non-overlapping MSTs. To show that the OMST indeed results in higher GCE than other filtering methods, we compared the GCE for OMST, MST, and a method of proportional thresholding where we used a common range of 5-20% strongest edge weights of a graph (Supplementary Figure S3). To avoid differences in graph measures caused by the number of nodes in a graph, we excluded all nodes where at least one participant had no signal during construction of matrices. This resulted in a 104x104 matrix per participant, which was used for construction of OMST and all subsequent measures.

Brain system integration

We calculated global efficiency as a measure of system-wide integration. It is defined as the average of the inverse shortest path length between all pairs of nodes in a graph and is thus a measure of efficient signal transmission[10,39].

$$\text{Global efficiency} = \frac{1}{N(N-1)} \sum_{i \neq j \in G} \frac{1}{L_{i,j}}$$

Global efficiency was based on the individual OMSTs using the reciprocal edge weights to obtain a distance matrix where high weights signify short paths between nodes.

Global network hubs

We identified hubs via the normalized participation coefficient (PC)[44]. The PC provides insight into the functional role of a node. Specifically, it evaluates whether a node mainly interacts with nodes from its community or multiple communities of a network[79]. In network neuroscience, PC has been applied to define nodes that are important for communication between communities (connector

hubs) and nodes that are central to the communication within communities (provincial hubs)[42,43,52].

Recently, it has been shown that the conventional measure of PC is strongly influenced by the size

and connectedness of its community leading to a reduced interpretational value of this graph

measure[44]. Thus, a normalized version of the PC has been introduced that accounts for these

differences in real-world networks while preserving its meaning. It is calculated similarly to the

original PC as one minus the ratio between the degree k of node i with nodes in its community m

and the degree of node i with all other nodes in the network. However, a normalization factor is

added by subtracting the median degree of this node in a series of random networks:

$$\text{Normalized PC} = 1 - \sqrt{B_0 \sum_{m \in M} \left(\frac{k_i(m) - k_i(m)_{rand}}{k_i} \right)^2}$$

We calculated 100 random networks for each node. Connector hubs were then defined as nodes

with a PC value of at least 1SD above the mean in each age group.

Statistical analysis

Age-related changes for within- and between-network functional connectivity

To assess differences between age groups for within- and between-network connectivity, we ran

two-sample t-tests for each edge of the 7-network and 121-ROIs connectivity matrices within the

Network-Based Statistics toolbox (NBS)[51]. NBS applies cluster-based thresholding to correct for

multiple comparisons using permutation testing. In contrast to more conventional procedures for

controlling the family-wise error rate, such as the false discovery rate, NBS considers connected

components in networks (graphs), which makes it especially suited for network statistics. We set an

initial cluster-forming threshold at $p < 0.01$ (two-sided test; $t = 2.67$) and an FWE-corrected

significance threshold at $p < 0.05$ with 10,000 permutations. To control for the influence of motion

on functional connectivity, the average in-scanner head motion per participant was included as a

covariate. Average head motion was defined as the mean FD based on the calculation of the root

mean square deviation of the relative transformation matrices[80].

Age-related changes for network measures of segregation and integration

Linear mixed-effects models were set up to examine how the dependent variables brain system

segregation, individual network segregation, global efficiency, and nodal participation coefficient

were predicted by age group. We included in-scanner head motion (mean FD) as covariate and a

random intercept for participants. Models were calculated as follows:

$$\text{Network measure} = \beta_0 + \beta_1 \text{Age} + \beta_2 \text{Motion} + (1|\text{Subject}) + \varepsilon$$

Significance values were obtained by likelihood ratio tests of the full model with the effect in
question against the model without the effect in question.
815

Association between network measures and cognitive performance
For those network measures that showed differences between young and older adults, we further
examined their association with participants' cognitive performance for the in-scanner task and the
neuropsychological test battery. Analyses were performed using mixed-effects models with a
logistic regression for accuracy data due to their binomial nature and a linear regression for log-
transformed response time data. We only analyzed response times for correct reactions for the
semantic fluency task since our connectivity values were also based on our contrast of interest
semantic fluency > counting. Models contained fixed effects for the respective mean-centered
network measure (between-network functional connectivity, brain system segregation, individual
network segregation, and global efficiency) and age group as well as their interaction term, and
random intercepts for participants and semantic categories. Further, mean-centered values of mean
FD and education were entered as covariates. Models were set up as shown in the following
equation:

$\text{Cognitive measure} = \beta_0 + \beta_1 \text{Network measure} + \beta_2 \text{Age} + \beta_3 \text{Network measure} \times \text{Age} + \beta_4 \text{Motion} +$
$\beta_5 \text{Education} + (1|\text{Subject}) + (1|\text{Category}) + \varepsilon$

where cognitive measure denotes accuracy and response time, respectively. Significance values
were obtained via likelihood ratio tests. We applied sum coding (ANOVA-style encoding) for all
categorical predictors.
We performed correlation analyses with the neuropsychological tests that had been
assessed outside of the scanner. Due to the collinearity of some neuropsychological tests, we ran
an exploratory factor analysis on the standardized test scores using maximum likelihood estimation
and varimax rotation. Based on the hypothesis test (χ^2 = 14.04, p = 0.081), two factors with an
eigenvalue > 1 were chosen. For subsequent correlations with network measures, participant factor
scores extracted via regression methods were used.
All statistical models except for NBS were performed using R 4.1.0 via RStudio[81] and the
package lme4[82]. Results were visualized using the ggplot2[83] and ggeffects[84] packages. If applicable,
post-hoc comparisons were applied using the package emmeans[85]. The exploratory factor analysis
was calculated with the stats package[81]. OMSTs and all graph theory measures were calculated in
Matlab using the Brain Connectivity toolbox[10] and publicly available scripts for OMST and
normalized PC. Chord diagrams were generated with the circlize package[86], spring-embedded plots
using the igraph package[87], and force-directed plots using the ForceAtlas2 algorithm for R available
on Github (https://github.com/analyxcompany/ForceAtlas2).

Data availability

All behavioral data and raw data of functional connectivity and graph-theoretical measures are available in a public repository at https://gitlab.gwdg.de/functionalconnectivityaging/mdn_lang_networkAnalysis. This repository also holds all self-written code for analyses and figures for this project. Raw neuroimaging data are protected under the General Data Protection Regulation (EU) and can only be made available from the authors upon reasonable request.

Acknowledgments

The authors would like to thank the medical technical assistants of MPI CBS for their support with data acquisition, and Annika Dunau, Caroline Duchow, and Rebekka Luckner for their support with transcriptions of recordings.

Author contributions

S.M. collected, processed, and analyzed the data. K.A.W. contributed to analyses. D.S. contributed to the interpretation of results and the writing of the manuscript. S.M. and G.H. interpreted the results and wrote the paper.

Funding

SM held a stipend by the German Academic Scholarship Foundation (Studienstiftung des deutschen Volkes). DS was supported by the Deutsche Forschungsgemeinschaft (SA 1723/5-1) and the James S. McDonnell Foundation (Understanding Human Cognition, #220020292). GH was supported by the Lise Meitner excellence program of the Max Planck Society and the Deutsche Forschungsgemeinschaft (HA 6314/3-1, HA 6314/4-1).

Competing Interests

The authors declare that no competing interests exist.

References

1. Lambon Ralph, M. A., Jefferies, E., Patterson, K. & Rogers, T. T. The neural and computational bases of semantic cognition. *Nat. Rev. Neurosci.* **18**, 42–55 (2017).
2. Nilsson, L.-G. Memory function in normal aging. *Acta Neurol. Scand. Suppl.* **179**, 7–13 (2003).
3. Nyberg, L., Backman, L., Erngrund, K., Olofsson, U. & Nilsson, L.-G. Age Differences in Episodic Memory, Semantic Memory, and Priming: Relationships to Demographic, Intellectual, and Biological Factors. *J. Gerontol. B. Psychol. Sci. Soc. Sci.* **51B**, P234–P240 (1996).
4. Verhaegen, P., Borchelt, M. & Smith, J. Relation Between Cardiovascular and Metabolic Disease and Cognition in Very Old Age: Cross-Sectional and Longitudinal Findings From the Berlin Aging Study. *Health Psychol.* **22**, 559–569 (2003).
5. Burke, D. M. & Shafto, M. A. Aging and Language Production. *Curr. Dir. Psychol. Sci.* **13**, 21 (2004).
6. Hedden, T. & Gabrieli, J. D. E. Insights into the ageing mind: a view from cognitive neuroscience. *Nat. Rev. Neurosci.* **5**, 87–96 (2004).
7. Meunier, D., Lambiotte, R., Fornito, A., Ersche, K. & Bullmore, E. Hierarchical modularity in human brain functional networks. *Front. Neuroinformatics* **3**, (2009).
8. Power, J. D. *et al.* Functional Network Organization of the Human Brain. *Neuron* **72**, 665–678 (2011).
9. Wig, G. S. Segregated Systems of Human Brain Networks. *Trends Cogn. Sci.* **21**, 981–996 (2017).
10. Rubinov, M. & Sporns, O. Complex network measures of brain connectivity: Uses and interpretations. *NeuroImage* **52**, 1059–1069 (2010).
11. Bullmore, E. & Sporns, O. The economy of brain network organization. *Nat. Rev. Neurosci.* **13**, 336–349 (2012).
12. Bassett, D. S. *et al.* Cognitive fitness of cost-efficient brain functional networks. *Proc. Natl. Acad. Sci.* **106**, 11747–11752 (2009).
13. Chan, M. Y., Park, D. C., Savalia, N. K., Petersen, S. E. & Wig, G. S. Decreased segregation of brain systems across the healthy adult lifespan. *Proc. Natl. Acad. Sci.* **111**, E4997–E5006 (2014).
14. Setton, R. *et al.* Age differences in the functional architecture of the human brain. *Cereb. Cortex* bhac056 (2022) doi:10.1093/cercor/bhac056.
15. Stumme, J., Jockwitz, C., Hoffstaedter, F., Amunts, K. & Caspers, S. Functional network reorganization in older adults: Graph-theoretical analyses of age, cognition and sex. *NeuroImage* **214**, 116756 (2020).
16. Betzel, R. F. *et al.* Changes in structural and functional connectivity among resting-state networks across the human lifespan. *NeuroImage* **102**, 345–357 (2014).
17. Cao, M. *et al.* Topological organization of the human brain functional connectome across the lifespan. *Dev. Cogn. Neurosci.* **7**, 76–93 (2014).
18. Chong, J. S. X. *et al.* Longitudinal Changes in the Cerebral Cortex Functional Organization of Healthy Elderly. *J. Neurosci.* **39**, 5534–5550 (2019).
19. Geerligs, L., Renken, R. J., Saliasi, E., Maurits, N. M. & Lorist, M. M. A Brain-Wide Study of Age-Related Changes in Functional Connectivity. *Cereb. Cortex* **25**, 1987–1999 (2015).
20. Sala-Llonch, R. *et al.* Changes in whole-brain functional networks and memory performance in aging. *Neurobiol. Aging* **35**, 2193–2202 (2014).
21. Deng, L. *et al.* Age-Related Compensatory Reconfiguration of PFC Connections during Episodic Memory Retrieval. *Cereb. Cortex* **31**, 717–730 (2021).

22. Geerligs, L., Maurits, N. M., Renken, R. J. & Lorist, M. M. Reduced specificity of functional
connectivity in the aging brain during task performance. *Hum. Brain Mapp.* **35**, 319–330 (2014).

23. Spreng, R. N., Stevens, W. D., Viviano, J. D. & Schacter, D. L. Attenuated anticorrelation
between the default and dorsal attention networks with aging: evidence from task and rest.
Neurobiol. Aging **45**, 149–160 (2016).

24. Crowell, C. A. *et al.* Older adults benefit from more widespread brain network integration during
working memory. *NeuroImage* **218**, 116959 (2020).

25. Gallen, C. L., Turner, G. R., Adnan, A. & D'Esposito, M. Reconfiguration of brain network
architecture to support executive control in aging. *Neurobiol. Aging* **44**, 42–52 (2016).

26. Capogna, E. *et al.* Whole-brain connectivity during encoding: age-related differences and
associations with cognitive and brain structural decline. *Cereb. Cortex* bhac053 (2022)
doi:10.1093/cercor/bhac053.

27. Pongpipat, E. E., Kennedy, K. M., Foster, C. M., Boylan, M. A. & Rodrigue, K. M. Functional
Connectivity Within and Between n-Back Modulated Regions: An Adult Lifespan
Psychophysiological Interaction Investigation. *Brain Connect.* **11**, 103–118 (2021).

28. Adnan, A., Beaty, R., Silvia, P., Spreng, R. N. & Turner, G. R. Creative aging: functional brain
networks associated with divergent thinking in older and younger adults. *Neurobiol. Aging* **75**,
150–158 (2019).

29. Martin, S., Saur, D. & Hartwigsen, G. Age-Dependent Contribution of Domain-General Networks
to Semantic Cognition. *Cereb. Cortex* **32**, 870–890 (2022).

30. Gordon, J., Young, M. & Garcia, C. Why do older adults have difficulty with semantic fluency?
Aging Neuropsychol. Cogn. **25**, 803–828 (2018).

31. Ferré, P., Jarret, J., Brambati, S. M., Bellec, P. & Joanette, Y. Task-Induced Functional
Connectivity of Picture Naming in Healthy Aging: The Impacts of Age and Task Complexity.
Neurobiol. Lang. 1–24 (2020) doi:10.1162/nol_a_00007.

32. Marsolais, Y., Perlbarg, V., Benali, H. & Joanette, Y. Age-related changes in functional network
connectivity associated with high levels of verbal fluency performance. *Cortex* **58**, 123–138
(2014).

33. Dimitriadis, S. I., Salis, C., Tarnanas, I. & Linden, D. E. Topological Filtering of Dynamic
Functional Brain Networks Unfolds Informative Chronnectomics: A Novel Data-Driven
Thresholding Scheme Based on Orthogonal Minimal Spanning Trees (OMSTs). *Front.*
Neuroinformatics **11**, (2017).

34. van den Heuvel, M. P. *et al.* Proportional thresholding in resting-state fMRI functional
connectivity networks and consequences for patient-control connectome studies: Issues and
recommendations. *NeuroImage* **152**, 437–449 (2017).

35. Yeo, B. T. *et al.* The organization of the human cerebral cortex estimated by intrinsic functional
connectivity. *J. Neurophysiol.* **106**, 1125–1165 (2011).

36. Jackson, R. L. The neural correlates of semantic control revisited. *NeuroImage* **224**, 117444
(2021).

37. Smallwood, J. *et al.* The default mode network in cognition: a topographical perspective. *Nat.*
Rev. Neurosci. **22**, 503–513 (2021).

38. Fornito, A., Harrison, B. J., Zalesky, A. & Simons, J. S. Competitive and cooperative dynamics
of large-scale brain functional networks supporting recollection. *Proc. Natl. Acad. Sci.* **109**,
12788–12793 (2012).

39. Latora, V. & Marchiori, M. Efficient Behavior of Small-World Networks. *Phys. Rev. Lett.* **87**,
198701 (2001).

40. Luppi, A. I. & Stamatakis, E. A. Combining network topology and information theory to construct
representative brain networks. *Netw. Neurosci.* **5**, 96–124 (2021).

41. Jiang, C. *et al.* Toward Reliable Network Neuroscience for Mapping Individual Differences.
2021.05.06.442886 (2021) doi:10.1101/2021.05.06.442886.
42. Bertolero, M. A., Yeo, B. T. T. & D'Esposito, M. The diverse club. *Nat. Commun.* **8**, 1277 (2017).
43. Cohen, J. R. & D'Esposito, M. The Segregation and Integration of Distinct Brain Networks and
Their Relationship to Cognition. *J. Neurosci.* **36**, 12083–12094 (2016).
44. Pedersen, M., Omidvarnia, A., Shine, J. M., Jackson, G. D. & Zalesky, A. Reducing the
influence of intramodular connectivity in participation coefficient. *Netw. Neurosci.* **4**, 416–431
(2020).
45. Krieger-Redwood, K. *et al.* Down but not out in posterior cingulate cortex: Deactivation yet
functional coupling with prefrontal cortex during demanding semantic cognition. *NeuroImage*
141, 366–377 (2016).
46. Vatansever, D., Menon, D. K., Manktelow, A. E., Sahakian, B. J. & Stamatakis, E. A. Default
Mode Dynamics for Global Functional Integration. *J. Neurosci.* **35**, 15254–15262 (2015).
47. Wang, X., Gao, Z., Smallwood, J. & Jefferies, E. Both Default and Multiple-Demand Regions
Represent Semantic Goal Information. *J. Neurosci.* **41**, 3679–3691 (2021).
48. Zhang, W., Tang, F., Zhou, X. & Li, H. Dynamic Reconfiguration of Functional Topology in
Human Brain Networks: From Resting to Task States. *Neural Plast.* **2020**, 8837615 (2020).
49. Gonzalez-Burgos, L. *et al.* Cortical Networks Underpinning Compensation of Verbal Fluency in
Normal Aging. *Cereb. Cortex* **31**, 3832–3845 (2021).
50. Song, J. *et al.* Age-Related Reorganizational Changes in Modularity and Functional Connectivity
of Human Brain Networks. *Brain Connect.* **4**, 662–676 (2014).
51. Zalesky, A., Fornito, A. & Bullmore, E. T. Network-based statistic: Identifying differences in brain
networks. *NeuroImage* **53**, 1197–1207 (2010).
52. Bertolero, M. A., Yeo, B. T. T., Bassett, D. S. & D'Esposito, M. A mechanistic model of
connector hubs, modularity and cognition. *Nat. Hum. Behav.* **2**, 765–777 (2018).
53. Chan, M. Y., Alhazmi, F. H., Park, D. C., Savalia, N. K. & Wig, G. S. Resting-State Network
Topology Differentiates Task Signals across the Adult Life Span. *J. Neurosci.* **37**, 2734–2745
(2017).
54. Davis, S. W., Dennis, N. A., Daselaar, S. M., Fleck, M. S. & Cabeza, R. Que PASA? The
Posterior-Anterior Shift in Aging. *Cereb. Cortex* **18**, 1201–1209 (2008).
55. Folstein, M. F., Folstein, S. E. & McHugh, P. R. "Mini-mental state": A practical method for
grading the cognitive state of patients for the clinician. *J. Psychiatr. Res.* **12**, 189–198 (1975).
56. Beck, A. T., Steer, R. A., Ball, R. & Ranieri, W. Comparison of Beck Depression Inventories -IA
and -II in psychiatric outpatients. *J. Pers. Assess.* **67**, 588–597 (1996).
57. Schmidt, K.-H. & Metzler, P. *WST-Wortschatztest*. (Beltz Test, 1992).
58. Daneman, M. & Carpenter, P. A. Individual differences in working memory and reading. *J.
Verbal Learn. Verbal Behav.* **19**, 450–466 (1980).
59. Aschenbrenner, S., Tucha, O. & Lange, K. W. *Regensburger Wortflüssigkeits-Test*. (Hogrefe,
2000).
60. Wechsler, D. *The measurement of adult intelligence (3rd ed.).* (Williams & Wilkins Co, 1944).
doi:10.1037/11329-000.
61. Reitan, R. M. Validity of the Trail Making Test as an indicator of organic brain damage. *Percept.
Mot. Skills* **8**, 271 (1958).
62. Esteban, O. *et al.* fMRIPrep: a robust preprocessing pipeline for functional MRI. *Nat. Methods*
16, 111–116 (2019).
63. Gorgolewski, K. *et al.* Nipype: A Flexible, Lightweight and Extensible Neuroimaging Data
Processing Framework in Python. *Front. Neuroinformatics* **5**, 13 (2011).

64. Griffanti, L. *et al.* ICA-based artefact and accelerated fMRI acquisition for improved Resting State Network imaging. *NeuroImage* **95**, 232–247 (2014).

65. Siegel, J. S. *et al.* Statistical improvements in functional magnetic resonance imaging analyses produced by censoring high-motion data points. *Hum. Brain Mapp.* **35**, 1981–1996 (2014).

66. Calhoun, V. D., Adali, T., Pearlson, G. D. & Pekar, J. J. A method for making group inferences from functional MRI data using independent component analysis. *Hum. Brain Mapp.* **14**, 140–151 (2001).

67. Jaccard, P. The Distribution of the Flora in the Alpine Zone. *New Phytol.* **11**, 37–50 (1912).

68. Gordon, E. M. *et al.* Default-mode network streams for coupling to language and control systems. *Proc. Natl. Acad. Sci.* (2020) doi:10.1073/pnas.2005238117.

69. Jackson, R. L., Cloutman, L. L. & Lambon Ralph, M. A. Exploring distinct default mode and semantic networks using a systematic ICA approach. *Cortex* **113**, 279–297 (2019).

70. Brett, M., Anton, J.-L., Valabregue, R. & Poline, J.-B. Region of Interest Analysis Using an SPM Toolbox. *Neuroimage* **16**, (2002).

71. Hallquist, M. N., Hwang, K. & Luna, B. The nuisance of nuisance regression: spectral misspecification in a common approach to resting-state fMRI preprocessing reintroduces noise and obscures functional connectivity. *NeuroImage* **82**, 208–225 (2013).

72. Lindquist, M. A., Geuter, S., Wager, T. D. & Caffo, B. S. Modular preprocessing pipelines can reintroduce artifacts into fMRI data. *Hum. Brain Mapp.* **40**, 2358–2376 (2019).

73. Mascali, D. *et al.* Evaluation of denoising strategies for task-based functional connectivity: Equalizing residual motion artifacts between rest and cognitively demanding tasks. *Hum. Brain Mapp.* **42**, 1805–1828 (2021).

74. Ciric, R. *et al.* Benchmarking of participant-level confound regression strategies for the control of motion artifact in studies of functional connectivity. *NeuroImage* **154**, 174–187 (2017).

75. Parkes, L., Fulcher, B., Yücel, M. & Fornito, A. An evaluation of the efficacy, reliability, and sensitivity of motion correction strategies for resting-state functional MRI. *NeuroImage* **171**, 415–436 (2018).

76. Chan, M. Y. *et al.* Long-term prognosis and educational determinants of brain network decline in older adult individuals. *Nat. Aging* **1**, 1053–1067 (2021).

77. Wang, J.-H. *et al.* Graph Theoretical Analysis of Functional Brain Networks: Test-Retest Evaluation on Short- and Long-Term Resting-State Functional MRI Data. *PLOS ONE* **6**, e21976 (2011).

78. Fornito, A., Zalesky, A. & Bullmore, E. T. *Fundamentals of brain network analysis*. (Elsevier/Academic Press, 2016).

79. Guimerà, R. & Nunes Amaral, L. A. Functional cartography of complex metabolic networks. *Nature* **433**, 895–900 (2005).

80. Jenkinson, M., Bannister, P., Brady, M. & Smith, S. Improved Optimization for the Robust and Accurate Linear Registration and Motion Correction of Brain Images. *NeuroImage* **17**, 825–841 (2002).

81. R Core Team. *R: A language and environment for statistical computing*. (R Foundation for Statistical Computing, 2021).

82. Bates, D., Mächler, M., Bolker, B. & Walker, S. Fitting linear mixed-effects models using lme4. *J. Stat. Softw.* **67**, 1–48 (2015).

83. Wickham, H. *ggplot2. Elegant Graphics for Data Analysis*. (Springer International Publishing, 2016). doi:10.1007/978-3-319-24277-4.

84. Lüdecke, D. ggeffects: Tidy Data Frames of Marginal Effects from Regression Models. *J. Open Source Softw.* **3**, 772 (2018).

85. Lenth, R. *emmeans: Estimated Marginal Means, aka Least-Squares Means. R package version*
1.4.8. (2020).
86. Gu, Z., Gu, L., Eils, R., Schlesner, M. & Brors, B. circlize Implements and enhances circular
visualization in R. *Bioinforma. Oxf. Engl.* **30**, 2811–2812 (2014).
87. Csardi, G. & Nepusz, T. The igraph software package for complex network research.
InterJournal **Complex Systems**, 1695 (2006).

1068