Pangenomic genotyping with the marker array

Taher Mun

Johns Hopkins University, USA

Illumina, USA

https://alshai.github.io/

tmun1@jhu.edu

Naga Sai Kavya Vaddadi
Johns Hopkins University, USA

kvaddad1@jhu.edu

Ben Langmead[1]
Johns Hopkins University, USA

http://www.langmead-lab.org

langmea@cs.jhu.edu

— Abstract
We present a new method and softare tool called `rowbowt` that applies a pangenome index to the
problem of inferring genotypes from short-read sequencing data. The method uses a novel indexing
structure called the marker array. Using the marker array, we can genotype variants with respect
from large panels like the 1000 Genomes Project while avoiding the reference bias that results when
aligning to a single linear reference. `rowbowt` can infer accurate genotypes in less time and memory
compared to existing graph-based methods. The method is implemented in the open source software
tool `rowbowt` available at `https://github.com/alshai/rowbowt`.

2012 ACM Subject Classification Applied computing → Computational genomics

Keywords and phrases Sequence alignment indexing genotyping

Digital Object Identifier 10.4230/LIPIcs.Event.2022.

Funding *Taher Mun*: R01HG011392 and R35GM139602 to BL. Also, NSF-135491.
Naga Sai Kavya Vaddadi: R01HG011392 and R35GM139602 to BL
Ben Langmead: R01HG011392 and R35GM139602 to BL. Also, NSF-135491.

1 Introduction

Given DNA sequencing reads from a donor individual, genotyping is the task of determining
which alleles the individual has at polymorphic sites. Genotyping from sequencing data,
sometimes using low-coverage sequencing data together with genotype imputation, is a
common task in human genetics [10] and agriculture [18]. In contrast to variant calling,
genotyping is performed with respect to a catalog of known polymorphic sites. For instance,
genotyping of a human can be performed with respect to the 1000 Genomes Project call set,
which catalogs positions, alleles and allele frequencies for tens of millions of sites [2].

Many existing genotypers start by aligning reads to a single linear reference genome,
e.g. the human GRCh38 reference [26]. Because this reference is simply one example of an
individual's genome, genotyping is subject to reference bias, the tendency to make mistakes
in place where the donor individual differs genetically from the reference. This has been
shown in studies of archaic hominids [17], HLA genotypes [4] and structural variants [28]. A
similar bias exists for methods that extract polymorphic sites along with genomic context,

---

[1] Corresponding author

and search for these sequences in the reads [11, 27]. In particular, the bias remains if the flanking sequences are extracted from the reference and so contain only reference alleles.

Reference bias can be avoided by using a *pangenome* reference instead of a single linear reference. A pangenome can take various forms; it can be (a) a generating graph for combinations of alleles, (b) a small collection of linear references indexed separately, or (c) a larger collection of linear reference indexed together in a compressed way. Pangenome graphs (option a) and small collections of linear references (option b) have been studied in recent literature [23, 8, 15, 7]. Variant graphs are effective for genotyping, but have drawbacks in this context. First, haplotype information is removed when adding variants to the graph. This causes tools like Bayestyper [29] to consider multiple different haplotype paths through the graph during genotyping, increasing running time. Second, variant graphs can grow exponentially – in terms of the number of paths through the graph – as variants are added, leading to a rapid increase in resource usage and likelihood of ambiguous alignments.

We sought a way to avoid reference bias by indexing and querying many linear references at once while keeping index size and query time low. Such an approach can take full advantage of linkage disequilibrium information in the panel, allowing no recombination events except those occurring in the panel. This avoids mapping ambiguity from spurious recombination events between polymorphic sites [23].

We propose a new structure called the *marker array* that replaces the suffix-array-sample component of the r-index with a structure tailored to the problem of collecting genotype evidence. Here we describe the marker array structure in detail. We compare its space usage and query time to those of the standard r-index and explore how accurately both structures are able to capture markers from a sequencing dataset. Finally, we benchmark it using real whole-genome human sequencing data and compare it to existing genotyping tools in terms of both genotyping accuracy and computational efficiency.

2   Background

r-index

The r-index [14] is a compressed repeat-aware text index that scales with the non-redundant content of a sequence collection. It uses $O(r)$ space where r is the number of same-character *runs* in the Burrows-Wheeler Transform (BWT) of the input text. Past work shows that the r-index can efficiently index collections of long-read-derived human genome assemblies [19] as well as large collections of bacterial genomes [1].

While the main contribution of the r-index was its strategy for storing and using a sample of the suffix array [14], even this sample is large in practice. We propose a new *marker array* structure that replaces the suffix array while retaining its ability to deduce when a read-to-pangenome match provides evidence for a particular allele at a polymorphic site. The design of the marker array flows from three observations. First, we can save space by storing auxiliary information about polymorphic sites ("markers") only at the sites themselves. There are often far fewer sites harboring polymorphism than there are BWT runs. Second, pangenome suffixes starting with the same allele tend to group together in the suffix array, which can be exploited to compress the marker array structure. Third, while a suffix array entry is an offset into the pangenome requiring $O(\log n)$ bits, a marker need only distinguish markers and alleles, and so requires just $O(\log M)$ bits where M is the number of polymorphic sites.

3 Methods

Preliminaries

Consider a string S of length n from ordered alphabet Σ. Assume S's last character is lexicographically less than the others. Let F be an array of S's characters sorted lexicographically by the suffixes starting at those characters, and let L be an array of S's characters sorted lexicographically by the suffixes starting immediately after them. The list L is the Burrows-Wheeler Transform [5] of S, abbreviated BWT.

The BWT can function as an *index* of S [13]. Given a pattern P of length $m < n$, we seek the number and location of all occurrences of P in S. If we know the range $\mathsf{BWT}(S)[i..j]$ occupied by characters immediately preceding occurrences of a pattern Q in S, we can compute the range $\mathsf{BWT}(S)[i'..j']$ containing characters immediately preceding occurrences of cQ in S, for any character $c \in \Sigma$, since

$$i' = |\{h : S[h] \prec c\}| + |\{h : S[h] = c, h < i\}| \tag{1}$$

$$j' = |\{h : S[h] \prec c\}| + |\{h : S[h] = c, h \le j\}| - 1. \tag{2}$$

The FM Index is a collection of data structures for executing such queries efficiently. It consists of an array C storing $|\{h : S[h] \prec c\}|$ for each character c, plus a rank data structure for $\mathsf{BWT}(S)$, e.g. a wavelet tree, that can quickly tally the occurrences of a character c up to a position of BWT. To locate the offsets of occurrences of P in S, the FM-index can additionally include a sampled suffix array of S. The full suffix array SA is an array parallel to F containing the offsets of the characters in F. To save space, the FM-index typically keeps a sample of SA, e.g. a subset spaced regularly across SA or across S.

Let $T = \{T_0, T_1, \ldots, T_n\}$ be a collection of n similar texts where T_0 is the *reference sequence*, and $T_1, \ldots, T_n$ are *alternative sequences*. In the scenarios studied here, a T_i represents a human haplotype sequence, with all chromosomes concatenated, and T_0 represents the GRCh38 primary assembly of the human genome. Each T_i with $i > 0$ is an alternate haplotype taken either from the 1000 Genomes project call set [2] or from the HGSVC project [6, 12], each with chromosomes concatenated in the same order as T_0's. We use the terms "haplotype" and "genome" interchangeably here.

We assume that all the T_i's are interrelated through a multiple alignment, e.g. as provided in a Variant Call Format (VCF) file. The multiple alignment is a matrix with genomes in rows and columns representing genomic offsets. The elements are either bases or gaps. We call a column consisting of identical bases and lacking any gaps a *uniform* column. Any other column is a *polymorphic* column. In describing the structure, we make the simplifying assumption that a polymorphic column contains at most two distinct entries. Figure 1 illustrates a multiply-aligned collection of haplotypes and the concatenated text T.

Marker Array

Let the "marker array" M be an array parallel to the concatenated sequence T marking positions that fall in a polymorphic column in the multiple alignment. Each element of M is a tuple recording the offset i with respect to T_0 where the polymorphism begins, as well as the edit operation describing how the sequence differs from the reference at this locus. Distinct edit operations are given distinct integer identifiers, which are decoded using a separate table E. Identifier 0 is the null operation, denoting that the reference allele appears without edits. For example, say $E = \{1 : X \to G\}$, where $X \to G$ denotes a substitution that replaces the reference base with G. Then a marker array record $m = (500, 0)$ marks a locus with no edit

with respect to reference position $T_0[500]$. A record $m' = (500, 1)$ denotes that a substitution
changes that base at $T_0[500]$ to a G. An example is shown in Figure 1 (bottom left).
Consecutive substitutions are collapsed into a single edit in the E table. Insertions and
deletions ("indels" for short) are treated somewhat differently; the offset carrying the "mark"
is the one just preceding the indel (just to its left) in the multiple alignment. Importantly,
the mark covers exactly one position in the genome, even if the insertion/deletion spans
many bases. The marked position must come to the left of the indel to ensure that suffixes
starting at the marked position include the allele itself.
The marker array MA is a permutation of M such that marks appear in suffix-rank order:

▶ **Definition 1.** *The* marker array MA *is the mapping such that* $MA[i] = M[SA[i]]$.

In suffix-rank order, identical $M[i]$'s are often grouped into runs in MA, as seen in Figure 1
(right).

Multiple alignment of reference (R) & haplotypes (H*)	i	SA[i]	Prefix of T[SA[i]...]	BWT[i]	MA[i]
R: GCT**G**ATCG**A**--CTC**G**A	0	148	$GCTGATC	A	Offset w/r/t R
H1: GCT**C**ATCG**G**--CTC**G**A	1	147	A$GCTGAT	T	
H2: GCT**C**ATCG**A**--CTC**T**A	2	96	**AAA**CTCGA	G	(8, 4)
H3: GCT**G**ATCG**AAA**CTC**G**A	3	126	**AAA**CTCGA	G	(8, 4)
H4: GCT**G**ATCG**G**--CTC**T**A	4	80	**AAA**CTCGA	G	(8, 4)
H5: GCT**C**ATCG**AAA**CTC**G**A	5	50	**AAA**CTCGA	G	(8, 4)
H6: GCT**G**ATCG**AAA**CTC**G**A	6	97	AACTCGAG	A	
H7: GCT**C**ATCG**A**--CTC**T**A	7	127	AACTCGAG	A	Index in E table
H8: GCT**G**ATCG**AAA**CTC**G**A			⋮		
H9: GCT**C**ATCG**G**--CTC**T**A					
	35	62	ATCGGCTC	G	
Text (T)	36	75	**C**ATCGAAA	T	(3, 1)
	37	107	**C**ATCGACT	T	(3, 1)
GCTGATCGACTCGAGCTCATCGGCT	38	31	**C**ATCGACT	T	(3, 1)
CGAGCTCATCGACTCTAGCTGATCG	39	17	**C**ATCGGCT	T	(3, 1)
AAACTCGAGCTGATCGGCTCTAGCT	40	137	**C**ATCGGCT	T	(3, 1)
CATCGAAACTCGAGCTGATCGAAAC	41	94	CGAAACTC	T	
TCGAGCTCATCGACTCTAGCTGATC			⋮		
GAAACTCGAGCTCATCGGCTCTA$	87	35	GACTCTAG	C	
	88	102	**G**AGCTCAT	C	(12, 0)
Edit Table (E)	89	26	**G**AGCTCAT	C	(12, 0)
	90	12	**G**AGCTCAT	C	(12, 0)
0 (null edit)	91	132	**G**AGCTCAT	C	(12, 0)
1 (X -> C)	92	86	**G**AGCTGAT	C	(12, 0)
2 (X -> G)	93	56	**G**AGCTGAT	C	(12, 0)
3 (X -> T)			⋮		
4 (X -> AAA)					

■ **Figure 1** Top left: A multiple alignment for a collection of alternate haplotypes (H1–H9), and a reference sequence (R). Marked bases are in bold and alternate alleles are colored. Middle left: The text T, formed by concatenating rows of the multiple alignment (eliding gaps). Bottom left: The edit table E, with alternate-allele coloring. Right: A partial illustration of the marker array in relation to SA, the relevant suffixes themselves (truncated to fit), and the BWT. Colors and bolding highlight where marked bases and alternate alleles end up in the suffixes.

A *marker query* for pattern string q returns all $m \in \mathsf{M}$ overlapped by an occurrence of q in T. We can begin to answer this query using backward search (Equation 1) with $P = q$, giving the maximal SA range $[i..j]$ such that q is a prefix of the suffixes in the range. Having computed $[i..j]$, we know that $\{\mathsf{MA}[i], ..., \mathsf{MA}[j]\}$ contain markers overlapped by q's leftmost character. To recover the markers overlapped by the rest of q's characters, two approaches can be considered, detailed in the following subsections. The FL approach recovers the overlapped markers in a straightforward way but uses $O(|q| \cdot \mathsf{occ})$ time, where occ is the number of times q occurs in T. The heuristic backward-search approach requires only $O(|q|)$ time but is not fully sensitive, i.e. it can miss some overlaps.

FL approach

Say $[i..j]$ is the maximal SA range such that all rows have q as a prefix. We can perform a sequence of FL steps, starting from each row $x \in [i..j]$. An FL step is the inverse of an LF step. That is, if we write an LF mapping step in terms of a rank query

$$i' \;\; = \;\; |\{h \,:\, S[h] \prec c\}| + \mathsf{BWT}.\mathrm{rank}_{\mathsf{BWT}[i]}(i) \tag{3}$$

where $S.\mathrm{rank}_c(i)$ denotes the number of occurrences of c in S up to but not including offset i, then an FL step inverts this using a select query

$$i \;\; = \;\; \mathsf{BWT}.\mathrm{select}_{F[i']}(i' - |\{h \,:\, S[h] \prec F[i']\}|) \tag{4}$$

where $S.\mathrm{select}_c(i)$ returns the offset of the $i+1^{\mathrm{th}}$ occurrence of c in S, i.e. the c of rank i. Whereas LF takes a leftward step with respect to T, FL takes a rightward step.

By starting in each row $x \in [i..j]$ and performing a sequence of $|q| - 1$ FL steps for each, we can visit each offset of T overlapped by an occurrence of q. Checking $\mathsf{MA}[k]$ at each step, where k is the current row, tells us which marker is overlapped, if any. This is slow in practice, both because it requires $O(|q|(j - i + 1))$ FL steps in total, and because each step requires a select query, which is more costly in practice than a rank query.

Heuristic backward-search approach with smearing

Say we perform a backward search starting with the rightmost character of q. At each step we are considering a range $[i..j]$ of SA having a suffix of q as a prefix. Using i and j, we can query $\mathsf{MA}[i..j]$. However, this tells us instances where a *suffix* of q overlaps a marker, whereas our goal is to find where the *whole* query q overlaps a marker. If we report overlaps involving trivially short suffixes of q, many would be false positives. We propose to allow but reduce the number of such false positives by augmenting MA:

▶ **Definition 2.** *The augmented marker array* MA^w *is a multimap such that* $\mathsf{MA}^w[i] = [\mathsf{M}[\mathsf{SA}[i]], \mathsf{M}[\mathsf{SA}[i] + 1], ..., \mathsf{M}[\mathsf{SA}[i] + w]]$

That is, $\mathsf{MA}^w[i]$ is a (possibly empty) list containing markers overlapping any of the positions $T[i..i + w]$. We call this a "smeared" marker array, since the marks are extended (smeared) to the left by w additional positions. Note that a length-w extension can overlap one or more other marked variants to the left. For this reason, MA^w must be a multimap, i.e. it might associate up to w markers with a given position.

Using MA^w, we adjust the backward-search strategy so that instead of querying MA at each step, we query MA^w every w steps. If w is large enough — e.g. longer than the length

at which we see random-chance matches — we can avoid many false positives. More space is
required to represent MA^w compared to MA since it is less sparse. However, we expect MA^w
to remain run-length compressible for the same reason that MA is.

Genotyping a read

Given a sequencing read, we would like to extract as much genotype information as possible
while minimizing computational cost and false-positive genotype evidence. Here we give a
heuristic algorithm (Algorithm 1) that handles entire sequencing reads, querying MA^w during
the backward-search process as proposed in the previous section. The algorithm proceeds
right to left through the read, growing the match by one character if possible. When we can
no longer grow the match (i.e. the range $[i..j]$ becomes empty), we reset the range to the
all-inclusive range $[0..|T|-1]$ and restart the matching process at the next character. We use
the term "extension" to refer to a consecutive sequence of steps that successfully extend a
match. Note that this is a heuristic algorithm that does not exhaustively find all half-MEMs
between the read and the index, as the MONI algorithm does [25].

■ **Algorithm 1** Simplified version of `rowbowt` algorithm for matching query string q and compiling
genotype evidence. C is an array such that $C[c]$ equals $|\{h : T[h] \prec c\}|$, where T is the original text.
N_h is the number of haplotypes in the index. Pseudocode for TallyEvidence and FinalizeEvidence
are not given, but the heuristics they use to further filter genotype evidence is described in the text.

1: **procedure** SIMPLEGENOTYPE(q, w, MA^w, BWT, C, N_h)
2:     $i = 0$, $j = |BWT|$
3:     $\ell = 0$, $k = 0$ ▷ start new extension
4:     $o = |q| - 1$
5:     **while** $o \geq 0$ **do**
6:         $c = q[o]$
7:         $i' = C[c] + \mathsf{BWT}.\mathrm{rank}_c(i)$ ▷ backward search, like equations 1 and 2
8:         $j' = C[c] + \mathsf{BWT}.\mathrm{rank}_c(j)$
9:         $k = k + 1$
10:        **if** $k = w$ and $\ell \geq N_h$ **then**
11:           **for** $x \in [\,i..j\,)$ **do**
12:              **for** $site \in \mathsf{MA}^w[x]$ **do**
13:                 TallyEvidence($site$)   ▷ increment evidence for allele at site
14:              **end for**
15:           **end for**
16:           $k = 0$ ▷ check every w steps
17:        **end if**
18:        **if** $i' = j'$ **then**   ▷ no matching substrings
19:           FinalizeEvidence(ℓ)   ▷ ignore tallied evidence if ℓ is small or evidence conflicts
20:           $i = 0$, $j = |BWT|$, $k = 0$, $\ell = 0$ ▷ start new extension
21:        **end if**
22:        $o = o - 1$
23:     **end while**
24:     FinalizeEvidence(ℓ)   ▷ ignore tallied evidence if ℓ is small or evidence conflicts
25: **end procedure**

As discussed above, the algorithm only checks the marker array every w steps (line 10).
As an additional filter, the algorithm only performs a marker-array query when the the

current suffix-array range size no larger than the number of haplotypes in the index (N_h). A range exceeding that size indicates that we are seeing more than one distinct match in at least one haplotype, meaning that the evidence is ambiguous.

The algorithm tallies evidence as it goes (line 13), but might later choose to ignore that evidence if certain conditions are not satisfied (lines 19 and 24). For example, if the evidence has a conflict — i.e. one match indicates a reference allele at a site but another match found during the same extension finds an alternate allele at that site — then all the evidence is discarded for that extension. Similarly, evidence from an extension is discarded if the sites it observes spans multiple chromosomes. Finally, evidence from extensions failing to match at least 80 bp of the read (adjustable with `--min-seed-length` option) is discarded.

We employ other heuristics to minimize mapping time not shown in Algorithm 1. For instance, we avoid wasted effort spent querying the wrong read strand. Specifically: `rowbowt` randomly selects an initial strand of the read to investigate: forward or reverse complement. If an extension from this strand meets the minimum seed-length threshold (80 by default), then the other strand is not considered and analysis of the read is complete. Otherwise, `rowbowt` then goes on to examine the opposite strand of the read.

Sparse marker encoding

We encode the sparse arrays M, MA and MA^w in the following way. Say that array A consists of empty and non-empty elements. We consider A's non-empty elements as falling into one of x maximal runs of identical (and non-empty) elements. Our sparse encoding for A consists of three structures. S is a length-$|A|$ bit vector with 1s at the positions where a run of identical entries in A begins, and 0s elsewhere. E is a similar bit vector marking the last position of each of the x runs. (This variable E is distinct from the E table defined above in "Marker Array.") To find whether an element $A[i]$ is non-empty, we can ask whether we are between two such marks; that is, $A[i]$ is non-empty if and only if $S.\mathrm{rank}_1(i+1) > E.\mathrm{rank}_1(i)$.

X is a length-x array containing the element that is repeated in each of A's non-empty runs, in the order they appear in A. If $A[i]$ is not empty, the element appearing there is given by $X[E.\mathrm{rank}_1(i)]$.

When encoding M or MA, the elements of X are simply tuples. A complication exists for MA^w, since elements are lists of up to w tuples. In this case, we keep an additional bit-vector B of size $|X|$ where 1s denote left-hand boundaries in X that correspond to runs in A. E and B can be used together to access an element in A (Algorithm 2).

▨ **Algorithm 2** Access the contents of $A[i]$ in the case where entries of A can be lists

---

procedure SPARSEACCESS(S, E, X, B, i)
    if $S.\mathrm{rank}_1(i+1) = E.\mathrm{rank}_1(i)$ **then**
        return $\emptyset$
    end if
    $e = E.\mathrm{rank}_1(i)$
    $j = B.\mathrm{select}_1(e)$
    $k = B.\mathrm{select}_1(e+1)$
    return $\{X[j], ..., X[k-1]\}$
end procedure

Extracting markers from VCF

A Variant Calling Format (VCF) [9] file is used to encode a collection of haplotypes with the variants arranged in order according to a reference genome. In the case of human and other diploid genomes, haplotypes are grouped as pairs. We refer to such a collection of haplotypes as a "panel" and a single haplotype as a "panelist." An VCF entry encodes a variant as a tuple consisting of a chromosome, offset, the allele found in the reference, the alternate allele found in one or more panelists, and a sequence of flags indicating whether each panelist has the reference or alternate version. We start from a VCF file to determine how to populate the marker arrays M, MA and/or MA^w, as well as the edit array E.

A single element of M is a tuple (r, e), where r is an offset in T_0 and e is the edit operation describing how the sequence differs from the reference. As a practical matter, we represent these tuples in a different way that more closely resemble the corresponding VCF records. Specifically, a marker is encoded in a 64-bit word divided into three fields. First, a 12 bit field identifies the chromosome containing the marker. The chromosome ordering is given at the beginning of the VCF file in the "header" section. For example, if "chr1" is the first chromosome in the header, then this chromosome is encoded as `0x000`, and if "chr2" is the second chromosome, it is encoded as `0x001`. Second is a 54 bit field encoding the marker's offset within the chromosome. Third is a 4-bit field storing which version of the variant is present, with 0 indicating the reference allele, 1 indicating the 1st alternate allele, 2 the second alternate allele, etc. This 64-bit representation allows for compact storage of markers and easier random access to the marker array.

Diploid genotyping

In a diploid genome, it is possible for both alleles to occur, i.e. for the genotype to be heterozygous. We use an existing approach [21] to compute genotype likelihoods considering all possible diploid genotypes: homozygous reference (2 reference alleles), homozygous alternate (2 alternate alleles), or heterozygous (1 reference, 1 alternate). Let $g \in \{0, 1, 2\}$ denote the number of reference-allele copies at the marked site; e.g. $g = 1$ corresponds to a heterozygous site and $g = 2$ to a homozygous reference site. Let l be the number of times the reference allele was observed in the reads overlapping a particular marked site and let k be the count of all alleles (reference or alternate) observed. Let ϵ is the sequencing error rate. We calculate the genotype likelihood as follows:

$$\mathcal{L}(g) = \frac{1}{2}^k [(2-g)\epsilon + g(1-\epsilon)]^k [(2-g)(1-\epsilon) + g\epsilon]^{k-l}$$

To choose the most likely genotype g_{max}, we compute:

$$g_{max} = \text{argmax}_{g \in \{0,1,2\}} \mathcal{L}(g)$$

By default, `rowbowt` uses $\epsilon = 0.01$.

Implementation details

The code for constructing the marker array is implemented in the `pfbwt-f` spoftware package, with repository at `https://github.com/alshai/pfbwt-f`. This repository also contains an efficient implementation of the prefix-free-parse BWT construction algorithm [19]. This software is written in C++17, uses the open-source MIT license, and builds on the Succinct Data Structure Library (SDSL) v3.0 [16].

For querying the marker array, we use the `rowbowt` implementation at `https://github.com/alshai/rowbowt`. This repository contains the open source C++17 implementation of `rowbowt`, distributed under the MIT license. It is also a library, containing algorithms for building and querying indexes containing various structures discussed here, including the run-sampled suffix array, marker array, and others.

4   Results

We evaluated the efficiency and accuracy of our marker-array method for compiling genotype evidence. We first generated multiple series of `rowbowt` indexes covering various settings for three parameters: the window size w for the smeared marker array MA^w, the number of haplotypes indexed, and the minimum allele frequency for marked alleles. The `rowbowt` index consisted of three components: the run-length encoded BWT, the run-sampled suffix array, and the marker array. While we build the sampled suffix array for these experiments, the standard marker-array-based method in `rowbowt` does not require this array.

We generated indexes for collections of $200, 400, 800$, or 1000 human chromosome-21 haplotypes from the 1000 Genomes Phase 3 reference panel [2] based on the $GRCh37$ reference. We generated two sets of indexes: one where the marker array marks all polymorphic sites regardless of frequency (denoted "$AF > 0$"), and another where the marker array marks only those sites where the less common allele occurs in at least 1% of haplotypes, i.e. has allele frequency 1% or higher (denoted "$AF > 0.01$"). In all cases, the marker array window size w was set to 19. Each haplotype collection was drawn from a random subset of 500 individuals from the 1000 Genomes Phase 3 panel. The $AF > 0$ panel of 500 haplotypes contains $1,097,388$ polymorphic sites. The $AF > 0.01$ panel of the same haplotypes of contains $193,438$ polymorphic sites with allele frequency over 1%. We also included the GRCh37 reference sequence, consisting of all reference alleles, in each collection, corresponding to the reference sequence called T_0 above.

We generated a series of indexes with window size $w \in \{13, 15, 17, 19, 21, 23, 25\}$. We generated two such series: one with no minimum allele frequency ($AF > 0$) and another with a 1% minimum frequency ($AF > 0.01$). Each index was over the same set of 100 haplotypes.

Index size

We measured the size of the three main components of the `rowbowt` index: the marker array, the run-length encoded BWT (RLE BWT) [3] and the run-sampled suffix array ("r-index SA") [14]. Figure 2 plots this measurement for collections of 200, 400, 800 and 1,000 haplotypes for both $AF > 0$ and $AF > 0.01$. All grow linearly with the number haplotypes grows, as expected. For $AF > 0$, the marker array is consistently larger than the run-sampled suffix array ("r-index SA"). For $AF > 0.01$, the marker array is much smaller, approaching the size of the RLE BWT. The $AF > 0$ marker array is larger because it contains polymorphic sites with infrequent alleles; about 85% of the marked sites in the $AF > 0$ array have allele frequency under 1%. Further, rare alleles are less likely to form long runs in the marker array, negatively affecting its array's run-length size.

In the left portion of Figure 2, the RLE BWT and r-index SA have constant size because the w parameter does not affect those data structures. In the right portion of Figure 2, showing size as a function of number of haplotypes, the marker array is almost always larger than the r-index SA for $AF > 0$ as opposed to $AF > 0.01$, except at $w = 13$. The slope of the marker array size is smaller for $AF > 0.01$ than for $AF > 0$.

313   Overall, both value of w and the number of haplotypes in the index cause the marker
314   array to increase in size, but the inclusion of rare alleles ($< 1\%$ allele frequency) has the
315   largest effect on its size.

■ **Figure 2** Left: Size of `rowbowt` data structures as a function of the number of haplotypes indexed,
and with $w = 19$. Right: Size of `rowbowt` data structures as a function of the "smearing" window
size w, with number of haplotypes fixed at 100. Separate results are shown for when there is no
minimum allowed allele frequency ($AF > 0$) and when the minimum frequency is 1% ($AF > 0.01$).

Query time

We next measured query time for the marker-array strategy versus the locate-query strategy
which uses the run-sampled suffix array. 150bp simulated reads of 25x coverage were generated
for one haplotype of HG01498, an individual that is part of the 1000-Genomes panel, but
which we excluded from all our indexes. We simulated reads using Mason 2 `mason_simulator`
[24] with default options.
In the case of the marker-array strategy, we are measuring the time required to analyze
the reads using the algorithm described above in "Genotyping a read." In the case of the
locate-query strategy, the MA^w query is replaced with a two-step process that first performs
a locate query with respect to the run-sampled suffix array, then performs a lookup in the M
array. To enable this mode, we further augmented the r-index with a representation of M
using the sparse encoding described above. To emphasize: the `rowbowt` strategy does not
require the run-sampled suffix array or the M array; the MA^w effectively replaces them both.
We repeatedly sampled 10,000 simulated reads and recorded the mean query time over
10 trials. As seen in Figure 3 the marker-array method was consistently faster than locate
method. This was true for all allele frequencies and window sizes tested. We found that
the effect of w and allele-frequency cutoff was more pronounced with the larger reference
panel $AF > 0$. For the smaller panel ($AF > 0.01$), query time was mostly invariant to both
window size and allele frequency.

Genotyping accuracy

336   We next measured the accuracy of the genotype information gathered using the marker
337   array. We simulated sequencing reads from one haplotype of HG01498 to an average depth
338   of 25-fold coverage. Individual HG01498 is excluded from the indexes. As our "truth" set
339   for evaluation, we use the variant calls in the 1000 Genomes project callset for the same

Figure 3 Mean time over 10 trials of aligning 10,000 simulated reads from HG01498 against the marker array (marker) and the r-index suffix array (locate). Experiments are repeated for marker collections including all alleles ($AF > 0$) and for alleles having frequency at least 1% ($AF > 0.01$). Left: The experiment is repeated for various window sizes w, and for 100 haplotypes. Right: The experiment is repeated for different numbers of indexed haplotypes, with $w = 19$.

haplotype we simulated from. For simplicity, this experiment treats the genome as haploid. Experiments in the next section will account for the diploid nature of human genomes.

A single marked site can have conflicting evidence, due, for instance, to mismapped reads or sequencing errors. For this evaluation, we make calls simply by finding the frequently observed allele at the site. We ignore any instances of alleles other than the ones noted in the VCF file as the reference and alternate alleles. If the reference and alternate alleles have equal evidence, the reference allele is called.

We calculate precision and recall according to the following formulas. Here, the positive class consists of marked sites that truly have the alternate allele, while the negative class consists of marked sites that truly have the reference allele. We measure:

$$\text{Precision} = \frac{\text{TP}s}{\text{TP}s + \text{FP}s} \qquad \text{Recall} = \frac{\text{TP}s}{\text{TP}s + \text{FN}s}$$

Where TP stands for True Positive, FN stands for False Negative, etc.

Figure 4 shows precision and recall with respect to the number of haplotypes in the index and the minimum allele frequency of the haplotype collection. We observed that the $AF > 0.01$ indexes generally had better precision compared to the $AF > 0$ indexes, though at the expense of recall. Precision and recall generally improve with the addition of more haplotypes to the index. The marker array has similar recall to the locate procedure across all haplotype sizes at the loss of precision. When rare variants are removed from the index ($AF > 0.01$), the gap in precision between the marker array and the locate procedure lessens. This mild (less than 0.1%) loss of precision is expected since algorithm described above in "Genotyping reads" is still prone to some false positives in the earlier part of the extension process.

Diploid genotyping assessment

To assess diploid genotyping accuracy, we data from the Human Genome Structural Variation Consortium (HGSVC) [6, 12]. The HGSVC called both simple and complex genetic variants across a panel of 64 human genomes. Calls were made with respect to the GRCh38 primary assembly [26]. For input reads, we subsampled reads from a 30-fold average coverage PCR-free

■ **Figure 4** Precision (left) and recall (right) of the calls made when querying the marker array using 25x simulated reads from HG01498 against the the marker array (marker) and the *r*-index (locate). Stratified by minimum allowed allele frequency (AF) in the index.

read set provided by the 1000 Genomes Project [2] (accession SRR622457). To create more
challenging scenarios for the genotypers, we randomly subsampled the read sets to make
smaller datasets of 0.01, 0.05, 0.1, 0.5, 1, 2 and 5-fold average coverage.

We assessed three genotyping methods. The first (`bowtie2_bcftools`) used Bowtie 2 [20]
v2.4.2 to align reads to a standard linear reference genome, then used BCFtools v1.13 to call
variants (i.e. genotypes) at the marked sites [21]. The second method used the graph-based
genotyper `bayestyper` v1.5. The third was `rowbowt`.

Prior to applying `bayestyper`, we built a `bayestyper`-compatible VCF file containing
all relevant variants from the HGSVC haplotype panel. For `rowbowt`, we created a `rowbowt`
index from the genomes in the HGSVC haplotype panel. In both cases we excluded NA12878's
haplotypes from the panel prior to building the index.

When evaluating, we stratified variants by complexity: the "snp" category includes
single-nucleotide substitutions, "indel" includes indels no more than 50bp long, and "sv"
includes insertion or deletions longer than 50bp, and "all" includes all variant types. More
complex structural variants like inversions and chromosomal rearrangements are ignored.

We analyzed the accuracy of `rowbowt`'s diploid genotypes in two ways. First we considered
allele-by-allele precision and recall, considering the alternate (ALT) allele calls to be the
positive class. Specifically, every diploid genotype called by a method is considered as a pair
of individual allele calls. If a given allele call is an alternate (ALT) allele and there is at least
one ALT allele present in the true diploid genotype at that site, it counts as a true positive
(TP). If the given allele is a reference allele (REF) and there is at least one REF allele in the
true diploid genotype, this is a true negative (TN). If the given allele is an ALT but the true
genotype is homozygous REF, we count it as a false positive (FP). Finally, if the given allele
is REF but the true genotype is homozygous ALT, this is a a false negative (FN).

Second, we considered precision and recall with respect to sites that were either truly
heterozygous or called heterozygous. If a heterozygous call made by a method is truly
heterozygous, this was counted as a true positive (TP). False positives, false negatives, and
true negatives are defined accordingly.

As seen in Figure 5, `rowbowt`'s ALT and HET precision were generally the highest of all
the methods across all variant categories, though `bayestyper` sometimes achieved higher
ALT/HET precision for indels in the higher-coverage datasets. `rowbowt`'s ALT recall is also
higher than the other methods, except for some of the lower coverage measurements in the

"sv" category, where `bayestyper` achieved higher ALT recall.

Figure 5 Precision and recall for the three tested genotyping methods, both at the level of individual alleles (ALT precision/recall) and at the level of heterozygous variants (HET precision/recall). Note that the bowtie2_bcftools approach is generally unable to align reads across variants in the "sv" category, leading to low precision and recall.

Computational performance

We compared the time and memory usage of each genotyping method, dividing each method into Alignment and Genotyping phases. For each phase, we measured both the wall-clock time elapsed and maximum memory ("maximum resident set") used. Both were measured with the Snakemake tool's `benchmark` directive [22].

Since the tools operate somewhat differently, we define the "Alignment" step differently in each case. For `bowtie2_bcftools`, we define the Alignment step as the process of using `bowtie2` to align sequencing reads to the linear reference genome. For `rowbowt`, we defined the Alignment step as the process of using the `rb_markers` command to genotype the reads using the algorithm described in Methods. For `bayestyper`, we defined the Alignment step as the typical 3-step process of: (a) using the KMC3 software tool to count k-mers in the input reads, (b) using the `bayestyper makeBloom` command to convert k-mer counts to Bloom filters for each sample, and (c) using the `bayestyper cluster` command to identify variant clusters. 16 threads were used during the Alignment phase for `bowtie2_bcftools` and `rowbowt`, while 32 threads were used for `bayestyper`.

For `bowtie2_bcftools`, we define the Genotyping step as the process of using `bcftools call` to call variants from the BAM file output by `bowtie2`. For `rowbowt` We define the Genotyping phase as the process of running the `vc_from_markers.py` script on the output from `rb_markers`. For `bayestyper`, we define the genotyping step as the process of running the `bayesTyper genotype` command. The Genotype phases for both `bowtie2_bcftools` and `rowbowt` do not support multi-threading, so a single thread was used. For the `bayestyper` Genotype phase we used 16 threads.

Figure 6 shows the time taken and peak memory footprint for each method and each phase. We observed that `rowbowt` was consistently faster than the other methods, sometimes by a large margin. We also observed that while `rowbowt` has a higher memory footprint compared to the `bowtie2_bcftools` method, it uses substantially less memory than `bayestyper`, the other pangenome-based method.

5 Discussion

We proposed a family of novel marker array structures, M, MA and MA^w that, together with a pangenome index like the r-index, allow for rapid and memory-efficient genotyping with respect to large pan-genome references. The marker array is smaller and faster to query than the run-sampled suffix array — the usual way to establish where matches fall when querying a run-length compressed index — especially when we limit the set of markers to just alleles at frequency 1% or higher. We further showed that the marker array can replace the sampled suffix array in simple genotyping experiments with moderate sacrifice of precision, and that a marker array based genotyping method outperforms the graph-based Bayestyper method.

Pan-genome indexes allow for rapid analysis of reads while avoiding reference bias. The indexes used in our experiments consisted of many (up to 65) haplotypes, with none having a higher priority over the others, except in the sense that results were expressed in terms of the standard reference. Our approach preserves all linkage disequilibrium information. This is in contrast to some graph-indexing approaches, which might consider all possible combinations of nearby alleles to be "valid," even if most combinations never co-occur in nature.

While we examined only simple structural variants in the form of insertions and deletions longer than 50 bp, the genotyping method is readily extensible to more complex differences as well. Indeed, as long as we can mark the base or bases just to the left of the variant, we can mark any variant in a way that we can later genotype

Figure 6 Time for each phase of the impute-first workflow for three methods of alignment/genotyping

The `rowbowt` method can lead to future methods that use information about genotypes to build a personalized reference genome, containing exactly the genotyped alleles. Alignment to a personalized reference have been shown previously to be the best way to avoid reference bias, even more effective than the best pangenome methods [7, 23].

6 Ackonwledgements

We thank Massimiliano Rossi and Travis Gagie for many helpful discussions. We thank Margaret Gagie for her careful editing.

Part of this research project was conducted using computational resources at the Maryland Advanced Research Computing Center (MARCC).

References

1 O. Ahmed, M. Rossi, S. Kovaka, M. C. Schatz, T. Gagie, C. Boucher, and B. Langmead. Pan-genomic matching statistics for targeted nanopore sequencing. *iScience*, 24(6):102696, Jun 2021.

2 A. Auton, L. D. Brooks, R. M. Durbin, E. P. Garrison, H. M. Kang, J. O. Korbel, J. L. Marchini, S. McCarthy, G. A. McVean, G. R. Abecasis, et al. A global reference for human genetic variation. *Nature*, 526(7571):68–74, Oct 2015.

3 D. Belazzougui, F. Cunial, T. Gagie, N. Prezza, and M. Raffinot. Flexible Indexing of Repetitive Collections. In Jarkko Kari, Florin Manea, and Ion Petre, editors, *Unveiling*

Dynamics and Complexity, volume 10307, pages 162–174. Springer International Publishing, Cham, 2017. Series Title: Lecture Notes in Computer Science.

D. Y. Brandt, V. R. Aguiar, B. D. Bitarello, K. Nunes, J. Goudet, and D. Meyer. Mapping Bias Overestimates Reference Allele Frequencies at the HLA Genes in the 1000 Genomes Project Phase I Data. *G3 (Bethesda)*, 5(5):931–941, Mar 2015.

M. Burrows and D.J. Wheeler. A block sorting lossless data compression algorithm. Technical Report 124, Digital Equipment Corporation, 1994.

M. J. P. Chaisson, A. D. Sanders, X. Zhao, A. Malhotra, D. Porubsky, T. Rausch, E. J. Gardner, O. L. Rodriguez, L. Guo, R. L. Collins, et al. Multi-platform discovery of haplotype-resolved structural variation in human genomes. *Nat Commun*, 10(1):1784, 04 2019.

N. C. Chen, B. Solomon, T. Mun, S. Iyer, and B. Langmead. Reference flow: reducing reference bias using multiple population genomes. *Genome Biol*, 22(1):8, 01 2021.

S. Chen, P. Krusche, E. Dolzhenko, R. M. Sherman, R. Petrovski, F. Schlesinger, M. Kirsche, D. R. Bentley, M. C. Schatz, F. J. Sedlazeck, and M. A. Eberle. Paragraph: a graph-based structural variant genotyper for short-read sequence data. *Genome Biol*, 20(1):291, 12 2019.

P. Danecek, A. Auton, G. Abecasis, C. A. Albers, E. Banks, M. A. DePristo, R. E. Handsaker, G. Lunter, G. T. Marth, S. T. Sherry, et al. The variant call format and VCFtools. *Bioinformatics*, 27(15):2156–2158, Aug 2011.

R. W. Davies, M. Kucka, D. Su, S. Shi, M. Flanagan, C. M. Cunniff, Y. F. Chan, and S. Myers. Rapid genotype imputation from sequence with reference panels. *Nat Genet*, 53(7):1104–1111, 07 2021.

L. Denti, M. Previtali, G. Bernardini, A. Schönhuth, and P. Bonizzoni. MALVA: Genotyping by Mapping-free ALlele Detection of Known VARiants. *iScience*, 18:20–27, Aug 2019.

P. Ebert, P. A. Audano, Q. Zhu, B. Rodriguez-Martin, D. Porubsky, M. J. Bonder, A. Sulovari, J. Ebler, W. Zhou, R. Serra Mari, et al. Haplotype-resolved diverse human genomes and integrated analysis of structural variation. *Science*, 372(6537), 04 2021.

P. Ferragina and G. Manzini. Opportunistic data structures with applications. In *Proceedings of the 41st Annual Symposium on Foundations of Computer Science (FOCS)*, pages 390–398, 2000.

T. Gagie, G. Navarro, and N. Prezza. Optimal-Time Text Indexing in BWT-runs Bounded Space. In *Proceedings of the 29th Annual Symposium on Discrete Algorithms (SODA)*, pages 1459–1477, 2018.

E. Garrison, J. Sirén, A. M. Novak, G. Hickey, J. M. Eizenga, E. T. Dawson, W. Jones, S. Garg, C. Markello, M. F. Lin, B. Paten, and R. Durbin. Variation graph toolkit improves read mapping by representing genetic variation in the reference. *Nat Biotechnol*, 36(9):875–879, 10 2018.

S. Gog, T. Beller, A. Moffat, and M. Petri. From theory to practice: Plug and play with succinct data structures. In *13th International Symposium on Experimental Algorithms, (SEA 2014)*, pages 326–337, 2014.

T. Günther and C. Nettelblad. The presence and impact of reference bias on population genomic studies of prehistoric human populations. *PLoS Genet*, 15(7):e1008302, 07 2019.

C. Kim, H. Guo, W. Kong, R. Chandnani, L. S. Shuang, and A. H. Paterson. Application of genotyping by sequencing technology to a variety of crop breeding programs. *Plant Sci*, 242:14–22, Jan 2016.

A. Kuhnle, T. Mun, C. Boucher, T. Gagie, B. Langmead, and G. Manzini. Efficient Construction of a Complete Index for Pan-Genomics Read Alignment. *J Comput Biol*, 27(4):500–513, 04 2020.

B. Langmead and S. L. Salzberg. Fast gapped-read alignment with Bowtie 2. *Nat Methods*, 9(4):357–359, Mar 2012.

H. Li. A statistical framework for SNP calling, mutation discovery, association mapping and population genetical parameter estimation from sequencing data. *Bioinformatics*, 27(21):2987–2993, Nov 2011.

22 F. Mölder, K. P. Jablonski, B. Letcher, M. B. Hall, C. H. Tomkins-Tinch, V. Sochat, J. Forster, S. Lee, S. O. Twardziok, A. Kanitz, A. Wilm, M. Holtgrewe, S. Rahmann, S. Nahnsen, and J. Köster. Sustainable data analysis with Snakemake. *F1000Res*, 10:33, 2021.

23 J. Pritt, N. C. Chen, and B. Langmead. FORGe: prioritizing variants for graph genomes. *Genome Biol*, 19(1):220, 12 2018.

24 K. Reinert, T. H. Dadi, M. Ehrhardt, H. Hauswedell, S. Mehringer, R. Rahn, J. Kim, C. Pockrandt, J. Winkler, E. Siragusa, G. Urgese, and D. Weese. The SeqAn C++ template library for efficient sequence analysis: A resource for programmers. *J Biotechnol*, 261:157–168, Nov 2017.

25 M. Rossi, M. Oliva, B. Langmead, T. Gagie, and C. Boucher. MONI: A Pangenomic Index for Finding Maximal Exact Matches. *J Comput Biol*, 29(2):169–187, 02 2022.

26 V. A. Schneider, T. Graves-Lindsay, K. Howe, N. Bouk, H. C. Chen, P. A. Kitts, T. D. Murphy, K. D. Pruitt, F. Thibaud-Nissen, D. Albracht, et al. Evaluation of GRCh38 and de novo haploid genome assemblies demonstrates the enduring quality of the reference assembly. *Genome Res*, 27(5):849–864, 05 2017.

27 A. Shajii, D. Yorukoglu, Y. William Yu, and B. Berger. Fast genotyping of known SNPs through approximate k-mer matching. *Bioinformatics*, 32(17):i538–i544, 09 2016.

28 R. M. Sherman, J. Forman, V. Antonescu, D. Puiu, M. Daya, N. Rafaels, M. P. Boorgula, S. Chavan, C. Vergara, V. E. Ortega, et al. Assembly of a pan-genome from deep sequencing of 910 humans of African descent. *Nat Genet*, 51(1):30–35, 01 2019.

29 J. A. Sibbesen, L. Maretty, and A. Krogh. Accurate genotyping across variant classes and lengths using variant graphs. *Nat Genet*, 50(7):1054–1059, 07 2018.