Model metamers illuminate divergences between biological and artificial neural networks

Jenelle Feather[1,2,3], Guillaume Leclerc[4,5], Aleksander Mądry[4,5], Josh H. McDermott[1,2,3,6]

[1] Department of Brain and Cognitive Sciences, Massachusetts Institute of Technology
[2] McGovern Institute, Massachusetts Institute of Technology
[3] Center for Brains Minds and Machines, Massachusetts Institute of Technology
[4] Department of Electrical Engineering and Computer Science, Massachusetts Institute of Technology
[5] Computer Science and Artificial Intelligence Laboratory, Massachusetts Institute of Technology
[6] Speech and Hearing Bioscience and Technology, Harvard University

Abstract

Deep neural network models of sensory systems are often proposed to learn representational transformations with invariances like those in the brain. To reveal these invariances we generated "model metamers" – stimuli whose activations within a model stage are matched to those of a natural stimulus. Metamers for state-of-the-art supervised and unsupervised neural network models of vision and audition were often completely unrecognizable to humans when generated from deep model stages, suggesting differences between model and human invariances. Targeted model changes improved human-recognizability of model metamers, but did not eliminate the overall human-model discrepancy. The human-recognizability of a model's metamers was well predicted by their recognizability by other models, suggesting that models learn idiosyncratic invariances in addition to those required by the task. Metamer recognition dissociated from both traditional brain-based benchmarks and adversarial vulnerability, revealing a distinct failure mode of existing sensory models and providing a complementary benchmark for model assessment.

Introduction

A central goal of neuroscience is to build models that reproduce brain responses and behavior. The hierarchical nature of biological sensory systems (1, 2) has motivated the use of hierarchical neural network models that transform sensory inputs into task-relevant representations (3, 4). As such models have become the top-performing machine perception systems over the last decade, they have also emerged as the leading models of both the visual and auditory systems (5–11).

One hypothesis for why artificial neural network models might replicate computations found in biological sensory systems is that they instantiate invariances that mirror those in such systems (12–14). For instance, visual object recognition must often be invariant to pose, and to the direction of illumination. Similarly, speech recognition must be invariant to speaker identity and to details of the prosodic contour. Sensory systems are hypothesized to build up invariances (15–17) that enable robust recognition. Such invariances plausibly arise in neural network models as a consequence of optimization for recognition tasks or other training objectives.

Although biological and artificial neural networks might be supposed to have similar internal invariances, there are some known human-model discrepancies that suggest the invariances of the two systems do not perfectly match. For instance, model judgments are often impaired by stimulus manipulations to which human judgments are invariant, such as additive noise (18–20) or small translations of the input (21, 22). Another such discrepancy is the vulnerability to adversarial perturbations – small changes to stimuli that alter model decisions despite being imperceptible to humans (23–26). These findings illustrate that current task-optimized models lack some of the invariances of human perception, but leave many questions unresolved. For instance, because the established discrepancies rely on only the model's output decisions, they do not reveal where in the model the discrepancies arise. It also remains unclear whether observed discrepancies are specific to supervised learning procedures that are known to deviate from biological learning. And because the known discrepancies do not point to a general method to assess model invariances in the absence of a specific hypothesis, it remains possible that current models possess many other invariances that humans lack.

In this paper we present a general test of whether the invariances present in computational models of the auditory and visual systems are also present in human perception, and apply this test to a set of contemporary and classical models. Rather than target particular known human invariances, we visualize or sonify model invariances by synthesizing stimuli that produce approximately the same activations in a model. We draw inspiration from human perceptual metamers, which have previously been characterized in the domains of color perception (27, 28), texture (29–31), cue combination (32), Bayesian decision making (33), and visual crowding (34, 35). We call the stimuli we generate "model metamers" because they are metameric for a computational model[1].

We generated model metamers from a variety of state-of-the-art deep neural network models of vision and audition by synthesizing stimuli that yield the same activations in a model stage as particular natural images or speech signals. We then evaluated human recognition of the model metamers. If the model invariances match those of humans, then humans should be able to recognize the model metamer as belonging to the same class as the natural signal to which it is matched.

---

[1] A preliminary version of some of the experiments described here was presented in a conference paper (36).

Across both visual and auditory task-optimized neural networks, metamers from late model stages
were nearly always misclassified by humans, suggesting that many of their invariances are not
present in human sensory systems. The same phenomenon also occurred for networks trained
with unsupervised learning, demonstrating that the model failure is not specific to supervised
classifiers. Model metamers could be made more recognizable to humans with selective changes
to the training procedure or architecture. However, late-stage model metamers remained much
less recognizable than natural stimuli in every model we tested regardless of architecture or
training. Some model changes that produced more recognizable metamers did not improve
conventional neural prediction metrics or evaluations of robustness, demonstrating that the
metamer test provides a complementary tool to guide model improvements. The human-
recognizability of a model's metamers was well predicted by other models' recognition of the same
metamers, suggesting that the discrepancy with humans lies in idiosyncratic model-specific
invariances. Model metamers demonstrate a qualitative gap that remains between current models
of sensory systems and their biological counterparts, and provide a metric for future model
evaluation.
92
Results
General procedure
The goal of our metamer generation procedure (Figure 1a) was to generate stimuli that produce
nearly identical activations at some stage within a model, but that were otherwise unconstrained,
and thus could physically differ in ways to which the model was invariant. We first measured the
activations evoked by a natural image or speech signal at a particular model stage. The metamer
for the natural image or speech signal was then initialized as a white noise signal (either an image
or a sound waveform; white noise was chosen to sample the metamers as broadly as possible
subject to the model constraints, without biasing the initialization towards a specific object class).
The noise signal was then modified to minimize the difference between its activations at the model
stage of interest and those for the natural signal to which it was matched. The optimization
procedure performed gradient descent on the input, iteratively updating the input while holding
the model parameters fixed. Model metamers can be generated in this way for any model stage
constructed from differentiable operations. Because the models we considered are hierarchical,
if the image or sound was matched with high fidelity at a particular stage, all subsequent stages
were also matched (including the final classification stage in the case of supervised models,
yielding the same decision).
110
Experimental logic
The logic of our approach can be related to four sets of stimuli. For a given "reference" stimulus,
there is a set of stimuli for which humans produce the same classification judgment as the
reference (Figure 1b; blue shaded). A subset of these are stimuli that are indistinguishable from
the reference stimulus (i.e., metameric) to human observers (blue circle). If a model performs a
classification task, it will also have a set of stimuli judged to be the same category as the reference
stimulus (orange shaded). However, even if the model does not itself perform classification, it
could instantiate invariances that define model metamers for the reference stimulus at each model
stage (orange circle).
120
In our experiments, we generate stimuli (sounds or images) that are metameric to a model and
present these stimuli to humans performing a classification task (Figure 1c). Because we have
access to the internal representations of the model, we can generate metamers for each stage of
a model (i.e. sampling from the preimage of the reference stimulus activations at each model
stage; Figure 1d). In many models there is limited invariance in the early stages (as is believed to
be true of early stages of biological sensory systems (17)), with model metamers closely
approximating the stimulus from which they are generated (Figure 1d, small orange sets in

leftmost column). But successive stages of a model may build up invariance, producing successively larger sets of model metamers. In a feedforward model, if two distinct inputs map onto the same representation at a given model stage, then any differences in the inputs cannot be recovered in subsequent stages, such that invariance cannot decrease from one stage to the next. If a model replicates a human sensory system, every model metamer from each stage should also be classified as the reference class by human observers (first row of Figure 1d). Such a result does not imply that all human invariances will be shared by the model, but it is a necessary condition for a model to replicate human invariances.

Discrepancies in human and model invariances could result in model metamers that are not recognizable by human observers (second row of Figure 1d). Assessing model metamers from different model stages may provide insight into how the invariances are built up over the model, and where any discrepancies with humans arise within the model.

Our approach differs from classical work on metamers (28) in that we do not directly assess whether model metamers are also metamers for human observers (i.e., indistinguishable). The reason for this is that a human judgment of whether two stimuli are the same or different could rely on any representations within their sensory system that distinguish the stimuli, rather than just those that are relevant to a particular behavior. By contrast, most neural network models of sensory systems are trained to perform a single behavioral task. As a result, we do not expect metamers of such models to be fully indistinguishable to a human observer. But if the model replicates the representations that support a particular behavioral task in humans, its metamers should nonetheless produce the same human behavioral judgment on that task, because they should be indistinguishable to the human representations that mediate the judgment. We thus use a recognition judgment as the behavioral assay of whether model metamers reflect the same invariances that are instantiated in an associated human sensory system. Moreover, if humans cannot recognize a model metamer, they would also be able to discriminate it from the reference stimulus, and the model would also not pass a traditional metamerism test.

We sought to answer several questions. First, we asked whether the learned invariances of commonly used neural network models are shared by human sensory systems. Second, we asked where any discrepancies with human perception arise within models. Third, we asked whether any discrepancies between model and human invariances would also be present in models obtained without supervised learning. Fourth, we explored whether model modifications intended to improve robustness would also make model metamers more recognizable to humans. Fifth, we asked whether metamer recognition identifies model discrepancies that are not evident using other methods of model assessment, such as brain predictions or adversarial vulnerability. Sixth, we asked whether human-discrepant metamers are shared across models.

Figure 1. a) Model metamer generation. Metamers are synthesized by performing gradient descent on a noise signal to minimize the difference between its activations at a model stage and those of a natural signal. The model architecture shown here is that of the CochCNN9 auditory model class used throughout the paper. b) Each reference stimulus has an associated set of stimuli in the space of all possible stimuli that are categorized as the same class by humans (blue) or by models (orange, if models have a classification decision). Metamers for humans and metamers for models are also sets of stimuli in the space of all possible stimuli (subsets of the set of same-class stimuli). In this paper, model metamers are derived for a specific model stage, taking advantage of access to the internal representations of the model at each stage. Because we do not similarly have access to the internal representations of humans, we evaluate the human-consistency of a model's metamers with a behavioral classification judgment. c) General experimental setup. Humans make classification judgements on natural stimuli or model metamers. d) Possible scenarios for how model metamers could relate to human classification decisions. Each square panel depicts sets of stimuli in the input space. The top row depicts a model that passes our proposed behavioral test. The set of metamers for a reference stimulus grows over the course of the model, but even at the deepest stage, all model metamers are classified as the reference category by humans. The second row depicts a model whose invariances diverge from those of humans. By the late stages of the model, many model metamers are no longer recognizable by humans as the reference stimulus class. The metamer test results also constrain the model stage at which model invariances diverge from those of humans. e) Example distributions of activation similarity for pairs of metamers (a natural signal and its corresponding metamer) along with random pairs of natural signals from the training set. The latter provides a null distribution that we used to verify the success of the model metamer generation. The correlation between metamer activations in the model stage used for metamer generation (top left and bottom right) falls outside the null distribution, as intended. When the metamer is generated from an early stage, the activations in a deeper stage are also well matched (top right), as expected given that the model is feedforward and deterministic. By contrast, when metamers are generated from a deep stage, activations in the deep stage are well matched, but those in the early stage are not (bottom left). This is because the

model builds up invariances, such that metamers for the deep stage produce very different activations in an early stage.

Metamer optimization
Because the metamer generation relies on an iterative optimization procedure, it was important
to measure optimization success for each metamer. We considered the metamer generation to
have succeeded only if it satisfied two conditions. First, measures of the match between the
activations for the natural reference stimulus and its model metamer at the matched stage had to
be much higher than would be expected by chance, quantified with a null distribution (Figure 1e,
grey distributions) measured between randomly chosen pairs of examples from the training
dataset. This criterion was adopted in part because it is equally applicable to models that do not
perform a task. Metamers had to pass this criterion for each of three different measures of the
match (Pearson and Spearman correlations, and dB SNR; see Methods). Second, for models that
performed a classification task, the metamer had to result in the same classification decision by
the model as the paired natural signal. In practice we trained linear classifiers on top of all
unsupervised models, such that we were able to apply this second criterion for them as well (to
be conservative).

Figure 1e shows example distributions of the match fidelity (using Spearman's rho in this
example). Activations in the matched model stage have a correlation close to 1, as intended, and
are well outside the null distribution for random pairs of training examples. And as expected given
the feedforward nature of the model, matching at an early stage produces matched activations in
a late stage (Figure 1e, orange distributions, top row). But because the models we consider build
up invariances over a series of feedforward stages, stages earlier than the matched stage need
not have the same activations, and in general differ from those for the original stimulus to which
the metamer was matched (Figure 1e, orange distributions, bottom row). This is particularly true
for model metamers generated from late stages of the model, where many different signals can
yield the same model activations. The match fidelity of this example was typical, and optimization
summaries for each analyzed model are included at
https://github.com/jenellefeather/model_metamers_pytorch.

Metamers for standard visual deep neural networks are unrecognizable to humans
We generated model metamers for multiple stages of five standard visual neural networks trained
to recognize objects (using the ImageNet1K dataset (37)) (Figure 2a). The five network models
spanned a wide range of architectural building blocks and depths: CORnet-S (38), VGG-19 (39),
ResNet50 and ResNet101 (40), and AlexNet (41). These models have been posited to capture
similar features as primate visual representations, and at the time the experiments were run, they
respectively placed 1st, 2nd, 11th, 4th, and 59th on a neural prediction benchmark (38, 42). We
subsequently ran a second experiment on an additional five models pretrained on larger scale
datasets that became available at later stages of the project (ResNet50:CLIP and ViT-B_32:CLIP
(43), ResNet50:SWSL and ResNeXt101-32x8d:SWSL (44), ViT_large_patch-16_224 (45)). To
evaluate human recognition of the model metamers, humans performed a 16-way categorization
task on the natural stimuli and model metamers (Figure 2b) (18). In models with residual
connections, we only generated metamers at stages where all branches converge, which ensured
that all subsequent model stages, and the model decision, remained matched.

Contrary to the idea that the trained neural networks have learned human-like invariances, we
found that human recognition of the model metamers decreased across model stages, reaching
near-chance performance at the deepest stages even though the model metamers remained as
recognizable to the models as the corresponding natural stimuli, as intended (Figure 2c&d). This
reduction in human recognition of model metamers was evident as a main effect of observer and

an interaction between the effect of metamer generation stage and the observer, both of which
were statistically significant for each of the ten models (main effects, CORnet-S: $F(1,42)=424.4$,
$p<0.0001$, $\eta^2_p =0.91$; VGG-19: $F(1,42)=1612.1$, $p<0.0001$, $\eta^2_p =0.97$; ResNet50: $F(1,42)=554.9$,
$p<0.0001$, $\eta^2_p =0.93$; ResNet101: $F(1,42)=1001.7$, $p<0.0001$, $\eta^2_p =0.96$; AlexNet: $F(1,42)=935.4$,
$p<0.0001$, $\eta^2_p =0.96$; ResNet50-CLIP: $F(1,40)= 517.3$, $p<0.0001$, $\eta^2_p=0.93$, ViT-B_32-CLIP:
$F(1,40)= 604.5$, $p<0.0001$, $\eta^2_p=0.94$, ResNet50-SWSL: $F(1,40)= 1159.3$, $p<0.0001$, $\eta^2_p=0.97$,
ResNeXt101-32x3d-SWSL: $F(1,40)=2363.1$, $p<0.0001$, $\eta^2_p=0.98$, ViT_large_patch-16_224:
$F(1,40)=852.01$ $p<0.0001$, $\eta^2_p=0.96$; interactions, CORnet-S: $F(5,210)=293.6$, $p<0.0001$,
$\eta^2_p =0.87$; VGG-19: $F(9,378)=268.4$, $p<0.0001$, $\eta^2_p =0.86$; ResNet50: $F(7,294)=290.2$, $p<0.0001$,
$\eta^2_p =0.87$; ResNet101: $F(7,294)=345.8$, $p<0.0001$, $\eta^2_p =0.89$; AlexNet: $F(8,336)=195.0$, $p<0.0001$,
$\eta^2_p =0.82$;   ResNet50-CLIP: $F(6,240)=181.17$, $p<0.0001$, $\eta^2_p=0.82$,   ViT-B_32-CLIP:
$F(9,360)=110.53$, $p<0.0001$, $\eta^2_p=0.73$, ResNet50-SWSL: $F(7,280)=164.7$, $p<0.0001$, $\eta^2_p=0.80$,
ResNeXt101-32x3d-SWSL: $F(7,280)= 225.93$, $p<0.0001$, $\eta^2_p=0.85$, ViT_large_patch-16_224:
$F(8,320)=158.94$, $p<0.0001$, $\eta^2_p=0.80$).
229
From visual inspection, many of the metamers from late stages resemble noise rather than natural
images (Figure 2e; see Supplementary Figure 1a for examples of metamers generated from
different white noise initializations). Moreover, analysis of confusion matrices revealed that for the
late model stages there was no detectably reliable structure in participant responses
(Supplementary Figure 2). Although the specific optimization strategies we used had some effect
on the subjective appearance of the model metamers, human recognition of the generated stimuli
remained poor regardless of the optimization procedure (Supplementary Figure 3). The poor
recognizability of late-stage metamers was also not explained by optimization difficulties. The
activation matches achieved by the optimization were generally good (e.g. with correlations close
to 1), and what variation we did observe was not predictive of metamer recognizability
(Supplementary Figure 4).
241

a) Generate metamers for each layer

Metamer Generation Layer (Shallow → Deep Layers)

b) *"Identify what you see in the image from the 16 possible categories"*

300ms
300ms
300ms
time

c)

ResNet50
CORnet-S
VGG-19
ResNet101
AlexNet

Proportion Correct

Chance Performance (1/16)
N=22

Metamer Generation Layer (Shallow → Deep Layers)

— Human
-- Network

d)

ResNet50: SWSL
ResNext101-32x8d: SWSL
ViT-B_32: CLIP
ResNet50: CLIP
ViT_large_patch-16_224

Proportion Correct

N=21

Metamer Generation Layer (Shallow → Deep Layers)

— Human
-- Network

e) Example Metamers (Visual Networks)

natural_image   conv1_relu1   layer1   layer2   layer3   layer4   avgpool   final

ResNet50

ResNet50: SWSL

f) about four **million** dollars less

0s   1s   2s

Identify the word spoken in the middle of the clip (i.e. at the one second point)

mil

Dictionary Matches:
family   miles   military   million   similar

g)

CochCNN9
CochResNet50

Proportion Correct

Chance Performance (1/793)
N=20

— Human
-- Network

Metamer Generation Layer (Shallow → Deep Layers)

h) Cochleagrams of Example Metamers (Audio Networks)

CochCNN9   cochleagram   relu0   relu1   relu2   relu3   relu4   avgpool   relufc   final

CochResNet50   cochleagram   conv1_relu1   layer1   layer2   layer3   layer4   avgpool   final

frequency (kHz)
0   time (s)   2

Figure 2 (previous page). Metamers of standard-trained visual and auditory deep neural networks are often unrecognizable to human observers. a) Model metamers are generated from different stages of the model. b) Experimental task used to assess human recognition of visual model metamers. Humans were presented with an image (either a natural image or a model metamer of a natural image) followed by a noise mask. They were then presented with 16 icons representing 16 object categories, and classified each image as belonging to one of these 16 categories by clicking on the icon. c) Human recognition of image model metamers (N=22). For all tested models, human recognition of model metamers declined for late model stages, while model metamers remained recognizable to the model (as expected). Error bars plot SEM across participants (or participant matched stimulus subsets for model curves) d) Human recognition of image model metamers (N=21) trained on larger scale datasets. e) Example metamers from ResNet50 and ResNet50: CLIP trained visual models. f) Experimental task used to assess human recognition of auditory model metamers. Humans classified the word that was present at the midpoint of a two-second sound clip. Participants selected from 793 possible words by typing any part of the word into a response box and seeing matching dictionary entries from which to complete their response. A response could only be submitted if it matched an entry in the dictionary. g) Human recognition of auditory model metamers (N=20). For both tested models, human recognition of model metamers decreased at late model stages. By contrast, model metamers remain recognizable to the auditory models, as expected. When plotted, chance performance (1/793) is indistinguishable from the x-axis. Error bars plot SEM across participants (or participant matched stimulus subsets for model curves). h) Cochleagram visualizations of example auditory model metamers from CochCNN9 and CochResNet50 architectures. Color intensity denotes instantaneous sound amplitude in a frequency channel (arbitrary units)

Metamers for standard auditory deep neural networks are unrecognizable to humans

To investigate whether this phenomenon generalized across modalities, we performed an analogous experiment with two auditory neural networks trained to recognize speech (the word recognition task in the Word-Speaker-Noise dataset (36)). Each model consisted of a biologically-inspired "cochleagram" representation with parameters matched to estimates of the frequency tuning of the human ear (46, 47) followed by a convolutional neural network whose parameters were optimized during training. We tested two model architectures: a ResNet50 architecture (referred to here as CochResNet50) and a model with nine stages (including five convolutional stages) similar to that used in a previously published auditory neural network model (5), referred to here as CochCNN9. Model metamers were generated for clean speech examples from the validation set (Figure 1a). Humans performed a 793-way classification task (5) to identify the word in the middle of either a natural speech example or a model metamer of a speech example generated from a particular model stage (Figure 2e; humans typed responses but were only allowed to enter one of the 793 words from the models' word-recognition task).

As with the image recognition models, human recognition of the auditory model metamers decreased markedly at late model stages for both architectures (Figure 2f). As with the vision models, there was a significant main effect of human vs. model observer (CochCNN9: $F(1,38)=551.9$, $p<0.0001$, $\eta^2_p =0.94$; CochResNet50: $F(1,38)=467.8$, $p<0.0001$, $\eta^2_p =0.92$) and a significant interaction between effect of metamer generation stage and the observer (CochCNN9: $F(9,342)=189.2$, $p<0.0001$, $\eta^2_p =0.83$; CochResNet50: $F(8,304)=227.4$, $p<0.0001$, $\eta^2_p =0.86$). Subjectively, the model metamers from deeper stages sound like noise (and appear noise-like when visualized as cochleagrams; Figure 2g). This result suggests that many of the invariances present in these models are not invariances for the human auditory system.

Overall, these results demonstrate that the invariances of many common visual and auditory neural networks are substantially misaligned with those of human perception, even though these models are currently the best predictors of brain responses in each modality.

Metamers of unsupervised deep network models are also unrecognizable to humans

It is widely appreciated that the learning procedures used to train most contemporary deep neural
networks deviate markedly from the learning that occurs in biological systems (48). Perhaps the
most fundamental difference lies in supervised learning, as biological systems are not provided
with explicit category labels for millions of stimuli during development. Do the divergent
invariances evident in neural network models result in some way from supervised training?
Metamers are well-suited to address this question given that their generation is not dependent on
a classifier, and thus can be generated for any sensory model.
279

Figure 3. Model metamers are unrecognizable to humans even with alternative training procedures. a) Overview of self-supervised learning, adapted from (49). Models were trained to map multiple views of the same image to nearby points in the embedding space. The SimCLR,MoCo_V2, and IPCL models also had an additional training objective that explicitly pushed apart embeddings from different images. b) Example metamers from select stages of ResNet50 supervised and self-supervised models. In all models, late-stage metamers are mostly unrecognizable. c) Human recognition of metamers from supervised and self-supervised models (left, N=21) along with linear evaluation on the ImageNet1K task at each stage of the

models (right). Self-supervised models (SimCLR, MoCo_V2, and BYOL) used a ResNet50 backbone; the comparison supervised model was also a ResNet50. For self-supervised models, model metamers from the "final" stage were generated from a linear classifier trained on the ImageNet1K task on the avgpool representation (intended to validate the representations learned via self-supervision, but included here for completeness). Model recognition curves of model metamers were close to ceiling as in Figure 2, and are omitted here and in later figures for brevity. Here and in d, error bars plot SEM across participants (left) or across three random seeds of model evaluations (right). d) Same as c, but for IPCL self-supervised model and supervised comparison with the same dataset augmentations (N=23). e) Examples of natural and stylized images using the Stylized ImageNet augmentation. Training models on Stylized ImageNet was previously shown to reduce a model's dependence on texture cues for classification. f) Human recognition of model metamers for ResNet50 and AlexNet architectures trained with Stylized ImageNet (N=21). Removing the texture-bias of models by training on Stylized ImageNet does not result in more recognizable model metamers compared to the standard model.

Recent advances in certain types of unsupervised learning have produced neural networks whose
representations support classification tasks without requiring millions of labeled examples during
training (49). The leading such models are self-supervised, being trained with a loss function
favoring representations in which variants of a single training example (different crops of an
image, for instance) are similar while those from different training examples are not (Figure 3a).
To assess whether this unsupervised training produces more human-like invariances compared
to traditional supervised training, we generated model metamers for three such models with a
ResNet50 architecture: SimCLR (49), MoCo_V2 (50) and BYOL (51) (examples shown in Figure
3b), and for one model with an AlexNet architecture with group-normalization: IPCL (52). After
training, we verified that the learned representations were sufficient to support object classification
performance (on ImageNet1K) by training a linear classifier on the final average pooling stage
(without changing any of the model weights; Figure 3c&d show classifier performance for each
stage of each model). We measured human recognition of metamers from these models as well
as those of the same ResNet50 or AlexNet architecture fully trained with supervision (on the
ImageNet1K task).
295
As shown in Figure 3b-d, the unsupervised models (SimCLR, MoCo_V2, BYOL, and IPCL)
produced similar results to those for supervised models: human recognition of model metamers
declined at deeper model stages, approaching chance levels for the final stages. Two of the self-
supervised ResNet50 models had somewhat more recognizable metamers at intermediate
stages, with MoCo_V2 producing the largest boost (significant interaction between model type
and model stage F(21, 420)=16.0, p<0.0001, η^2_p =0.44). The IPCL model also showed a small
but significant improvement in metamer recognizability at intermediate stages (F(9,198)=3.13,
p=0.0018, η^2_p =0.12). However, for both architectures, recognition was low in absolute terms, with
the metamers bearing little resemblance to the original image they were matched to. Overall, the
results suggest that the failure of standard neural network models to pass our metamer test is not
specific to the supervised training procedure. This result also demonstrates the generality of the
metamers method, as it can be applied to models that do not have a behavioral read-out.
308
Making model recognition more shape-dependent does not resolve discrepant metamers
Other observations of recognition discrepancies between deep neural networks and humans have
led to attempts to make model recognition more human-like via changes to the training data. One
commonly highlighted discrepancy is the tendency for models to base their judgments on texture
rather than shape (53–55). Training datasets of "stylized" images have been designed to reduce
this "texture bias" (Figure 3e), and have the effect of increasing a model's reliance on shape cues,
making them more human-like in this respect (53). To assess whether these changes also serve
to make model metamers less discrepant, we generated metamers from two models trained on
Stylized ImageNet. As shown in Fig. 3f, these models had metamers that were just as

unrecognizable to humans as models trained on the standard ImageNet1K training set (no interaction between model type and model stage, ResNet50: $F_{(7,140)}$= 0.225, p= 0.979, η^2_p= 0.011, AlexNet: $F_{(8,160)}$=0.949, p=0.487, η^2_p=0.045). This result suggests that metamer discrepancies are not simply due to texture bias in the models.

Model metamers reveal invariances of classical hierarchical models of sensory systems
As a further demonstration of the generality of the model metamer method, we generated metamers for classical visual and auditory models that were designed by hand based on neuroscience and engineering principles. Although these models do not perform classification tasks as well as contemporary neural network models, their comparative simplicity might be hypothesized to yield more human-like invariances.

The HMAX vision model is a biologically-motivated architecture with cascaded filtering and pooling operations inspired by simple and complex cells in the primate visual system and was intended to capture aspects of biological object recognition (4, 16). We generated model metamers by matching all units at the S1, C1, S2, or C2 stage of the model (Supplementary Figure 5a). Although HMAX is significantly shallower than the neural network models investigated in previous sections, it is evident that by the C2 model stage its model metamers are comparably unrecognizable to humans (Supplementary Figure 5b&c; significant main effect of model stage, $F_{(4,76)}$=351.9, p<0.0001, η^2_p =0.95). This classical model thus also has invariances that differ from those of the human object recognition system.

We performed an analogous experiment on a classical model of auditory cortex, consisting of a set of spectrotemporal filters applied to a cochleagram representation (Spectemp model, (56). We used a version of the model in which the convolutional responses are summarized with the mean power in each filter (5, 57, 58) (Supplementary Figure 5d). Metamers from the first two stages were fully recognizable, and very similar to the original audio, indicating that these stages instantiate few invariances, as expected for overcomplete filter bank decompositions (Supplementary Figure 5e&f). By contrast, metamers from the mean power representation were unrecognizable (significant main effect of model stage $F_{(4,76)}$=515.3, p<0.0001, η^2_p =0.96), indicating that this model stage produces invariances that humans do not share (plausibly because the human speech recognition system retains information that is lost in the averaging stage).

Overall, these results show how metamers can reveal the invariances present in classical models as well as state-of-the-art deep neural networks, and demonstrate that both types of models fail to fully capture the invariances of biological sensory systems.

Adversarial training of visual models increases human recognition of model metamers
A known peculiarity of contemporary artificial neural networks is their vulnerability to small adversarial perturbations designed to change the class label assigned by a model (23–26, 59). Such perturbations are typically imperceptible to humans due to their small magnitude, but can drastically alter model decisions, and have been the subject of intense interest in part due to the security risk they pose for machine systems. One way to reduce this vulnerability is to generate perturbation-based adversarial examples during training and add them to the training set, forcing the model to learn to recognize the perturbed images as the "correct" human-interpretable class (Figure 4a) (60). This procedure has been found to yield models that are less susceptible to adversarial examples for reasons that remain debated (61).

We asked whether reducing adversarial vulnerability in this way would improve human recognition of model metamers. A priori it was not clear what to expect. Perturbation-based adversarial

examples can be viewed as the converse of a model metamer, in that they are generated by
perturbations to which humans are invariant but which cause changes in model decisions. Making
models robust to adversarial perturbations causes them to exhibit more of the invariances of
humans (the shaded orange covers more of the blue outline in Figure 1b), but it is not obvious
that this will reduce the model invariances that are not shared by humans (i.e., to decrease the
orange outlined regions that don't overlap with blue shaded region in Figure 1b). Previous work
visualizing latent representations of visual neural networks suggested that robust training might
make model representations more human-like (62), but human recognition of model metamers
had not been behaviorally evaluated.
378
We first generated model metamers for vision models trained to be adversarially robust
(ImageNet1K-trained ResNet50 and AlexNet architectures) (62). As a control, we also trained
models with equal magnitude perturbations in random, rather than adversarial, directions. Such
random perturbations are typically ineffective at preventing adversarial attacks (59). As intended,
models with adversarial perturbations during training were more robust to adversarial examples
than the standard model or models with random perturbations (Supplementary Figure 6a&b).
385
For both architectures, metamers for the robust models were significantly more recognizable than
those from the standard model (Figure 4b-d; Supplementary Figure 1), evident as a significant
main effect of training type (repeated measures ANOVAs comparing human recognition of
standard and each adversarial model, significant main effect in each of the five models,
$F(1,19)>104.61$, $p<0.0001$, $\eta^2_p>0.85$). Training with random rather than adversarial perturbations
did not yield the same benefit (significant main effect of random vs. adversarial for each
perturbation of the same ε type and size, $F(1,19)>121.38$, $p<0.0001$, $\eta^2_p>0.86$). Model metamers
were more recognizable to humans for some adversarial training variants than others, but all
variants that we tried produced a human recognition benefit. It was nonetheless the case that
metamers from all variants remained less than fully recognizable to humans when generated from
the deep stages. We note that performance is inflated by the use of a 16-way alternative-force-
choice (AFC) task, for which above-chance performance is possible even with severely distorted
images. See Supplementary Figure 7 for an analysis of the consistency of metamer recognition
across human observer, and examples of metamers that are most and least recognizable.
400
Given that metamers from adversarially trained models look less noise-like than those from
standard models, and that standard models may over-represent high spatial frequencies
compared to adversarially robust models (63), we wondered whether their recognition advantage
could be replicated in a standard-trained model by including a smoothness regularizer in the
metamer optimization. Such regularizers are common in neural network visualizations, and
although we view them as side-stepping the goal of human-model comparison, it was nonetheless
of interest to assess their effect. We implemented the regularizer used in a well-known
visualization paper (64) which biases the solution to the metamer optimization to have low total
pixel variation (encouraging smoothness). As shown in Figure 4e, adding smoothness
regularization to the metamer generation procedure for the standard-trained AlexNet model
improved the recognizability of its metamers, but not as much as did adversarial training (and did
not come close to generating metamers as recognizable as natural images; see Supplementary
Figure 8 for examples generated with different regularization coefficients). This result suggests
that a) the benefit of adversarial training is not simply replicated by imposing smoothness
constraints, and b) discrepant metamers more generally cannot be resolved simply with the
addition of a smoothness prior.

Figure 4*.* Adversarial training increases human recognition of visual model metamers. a) Explanation of adversarial training. Adversarial examples are derived at each training step by finding an additive perturbation to the input that moves the classification label away from the training label class (top). These derived adversarial examples are then provided to the model as training examples and used to update the

model parameters (bottom). The resulting model learns to classify the adversarial examples as the training data label, and is subsequently more robust to adversarial perturbations than if standard training were used. As a control experiment, we also trained models with random perturbations to the input rather than adversarial perturbations. b) Human recognition of visual model metamers on a 16-way classification task with metamers generated from ResNet-50 models (N=20) trained with and without adversarial or random perturbations. Here and elsewhere, error bars plot SEM across participants. c) Same as b, but for AlexNet models (N=20). In both ResNet50 and AlexNet models, adversarial training leads to more recognizable metamers at the deep stages of the models, though in both cases the metamers remain less than fully recognizable. d) Example visual model metamers for ResNet50 models trained with and without adversarial or random L_2 perturbations. e) Recognizability of model metamers from standard trained models with and without regularization, compared to that for an adversarially trained model (N=20). Two regularization terms were included in the optimization: a total variation regularizer to promote smoothness, and a constraint to stay within the image range. Two different optimization step sizes were evaluated. f) Example metamers for an adversarially trained AlexNet (top) and a standard AlexNet with (middle) and without (bottom) regularization.

Adversarial training of auditory models increases human recognition of model metamers
To investigate whether adversarial training also leads to more human-like auditory
representations, we trained CochResNet50 and CochCNN9 architectures on the word recognition
task described above, using both standard and adversarial training. Because the auditory models
contain a fixed cochlear stage at their front end, there are two natural places to generate
adversarial examples (they can be added to the waveform or the cochleagram), and we explored
both for completeness.
424
We first investigated the effects of adversarial perturbations to the waveform (Figure 5a,
Supplementary Figure 6c&d). As a control experiment, we again trained models with random,
rather than adversarial, perturbations. As with the visual models, human recognition was generally
better for metamers from adversarially trained models (Figure 5b&c; ANOVAs comparing
standard and each adversarial model, significant main effect in 4/5 cases: $F(1,19)>9.26$,
$p<0.0075$, $\eta^2_p>0.33$; no significant main effect for CochResNet50 with L_2 (ε=1) perturbations:
$F(1,19)=0.29$, $p=0.59$, $\eta^2_p=0.015$). This benefit again did not occur for models trained with random
perturbations (ANOVAs comparing each random and adversarial perturbation model with the
same ε type and size; significant main effect in each case: $F(1,19)>4.76$, $p<0.0444$, $\eta^2_p>0.20$).
The model metamers from the robust models are visibly less noise-like when viewed in the
cochleagram representation (Figure 5d).
436
We also trained models with adversarial perturbations to the cochleagram representation, whose
fixed components enabled norm-based constraints on the perturbation size analogous to those
used for input-based adversarial examples (Figure 5e). Models trained on cochleagram
adversarial examples had significantly more recognizable metamers than both the standard
models and the models adversarially trained on waveform perturbations (Figure 5f&g; ANOVAs
comparing each model trained with cochleagram perturbations vs. the same architecture trained
with waveform perturbations; significant main effect in each case: $F(1,19)>4.6$, $p<0.04$, $\eta^2_p>0.19$;
ANOVAs comparing each model trained with cochleagram perturbations to the standard model;
significant main effect in each case: $F(1,19)>102.25$, $p<0.0001$, $\eta^2_p>0.84$). The effect on metamer
recognition was again specific to adversarial perturbations (ANOVAs comparing effect of training
with adversarial vs. random perturbations with the same ε type and size: $F(1,19)>145.07$,
$p<0.0001$, $\eta^2_p>0.88$).
449
Although the perturbation sizes in the two model stages are not directly comparable, in each case
we chose the size to be large enough that the model showed robustness to adversarial
perturbations while not being so large that the model could not perform the task (as is standard

for adversarial training). Further, training models with perturbations generated at the cochleagram
stage resulted in substantial robustness to adversarial examples generated at the waveform
(Supplementary Figure 6e&f). These results suggest that the improvements from intermediate-
stage perturbations may in some cases be more substantial than those from perturbations to the
input representation. They also highlight the utility of model metamers for evaluating model
modifications, in this case adversarial training with perturbations to intermediate model
representations.
460
461   Overall, these results suggest that training alterations intended to mitigate undesirable
462   characteristics of artificial neural networks (adversarial vulnerability) can cause their invariances
463   to become more like those of humans in both the visual and auditory domain. However,
464   substantial discrepancies remain even with these alterations. In both modalities, many model
465   metamers from deep model stages remain unrecognizable even after adversarial training.
466

Figure 5 (next page). Adversarial training increases human recognition of auditory model metamers. a) Schematic of auditory convolutional neural networks with adversarial perturbations applied to the waveform input. b) Human recognition of auditory model metamers from CochResNet50 (N=20) and c) CochCNN9 (N=20) models with adversarial perturbations generated in the waveform space (models trained with random perturbations are also included for comparison). When plotted here and in f&g, chance performance (1/793) is indistinguishable from the x-axis and error bars plot SEM across participants. L_2 (ε=0.5) waveform adversaries were only included in the CochResNet50 experiment. d) Cochleagrams of example model metamers from CochResNet50 models trained with waveform and cochleagram adversarial perturbations. e) Schematic of auditory convolutional neural networks with adversarial perturbations applied to the cochleagram stage. f) Human recognition of auditory model metamers from models trained with cochleagram adversarial perturbations are more recognizable for CochResNet50 and g) CochCNN9 models compared to those from models trained with waveform perturbations.

Human recognition of metamers dissociates from adversarial vulnerability

Human recognition of metamers dissociates from adversarial vulnerability
Although we found that adversarial training increased human recognizability of model metamers,
the degree of robustness that resulted from the training was not itself predictive of metamer
recognizability. We first examined all the visual models from Figures 2-5, comparing their
adversarial robustness with the recognizability of their metamers from the final model stage (this

stage was chosen as it exhibited considerable variation in recognizability across models). As
shown in Figure 6a, there is a correlation between robustness and metamer recognizability for
visual models (ρ=0.73, p<0.001), but it is mostly driven by the overall difference between two
groups of models: those that were adversarially trained and those that were not.
477
The auditory models showed a similar relationship as the visual models (Figure 6b). When both
standard and adversarially trained models were analyzed together, there was a significant
correlation between metamer recognizability and robustness (ρ=0.63, p=0.004) that was driven
by the overall difference between the two groups of models. This analysis was performed using
intermediate stage metamers (layer4 for CochResNet50, and ReLU4 for CochCNN9) because
the final stage metamer recognizability was sufficiently low overall (because the auditory
recognition task was much harder than the visual task: 793 vs. 16 possible classes) that a floor
effect plausibly explained the absence of a significant correlation for the final stage metamers
(ρ=0.21, p=0.215). As with the visual models, there is no obvious relationship when considering
just the adversarially trained models.
488
To better assess whether variations in robustness produce variation in metamer recognizability,
we compared the robustness of a large set of adversarially trained models (taken from a well-
known robustness evaluation (65)) to the recognizability of their metamers from the final model
stage. As shown in Figure 6c, despite the considerable variation in both robustness and metamer
recognizability, the correlation between these two measures was low and non-significant (ρ=0.31,
p=0.099). Overall, it thus seems that something about the adversarial training procedure leads to
more recognizable metamers, but that robustness per se does not drive the effect.
496
497 Adversarial training is not the only means of making models adversarially robust. But when
498 examining other sources of adversarial robustness, we again found examples where a model's
499 susceptibility to adversarial examples was not predictive of the recognizability of its metamers.
500 Here we present results for two models that had similar adversarial robustness, one of which had
501 much more recognizable metamers than the other.
502
The first model was a CNN that was modified to reduce aliasing (LowpassAlexNet). Because
many traditional neural networks contain downsampling operations (e.g. pooling) without a
preceding lowpass filter, they violate the sampling theorem (36, 66) (Figure 6d). It is nonetheless
possible to modify the architecture to reduce aliasing, and such modifications have been
suggested to improve model robustness to small image translations (21, 22). The second model
was a CNN that contained an initial processing block inspired by primary visual cortex in primates
(67, 68) featuring hard-coded Gabor filters and a stochastic response component present during
training (VOneAlexNet, Figure 6e). The inclusion of this block has been previously demonstrated
to increase adversarial robustness. It was a priori unclear whether either model modification would
improve human recognizability of the model metamers.
513
Both architectures were comparably robust to standard (L_p-bounded) adversarial perturbations
(Figure 6f; no significant main effect of architecture for perturbations, F(1,8)<4.5, p>0.10, η^2_p<0.36
for all perturbation types), and both were more robust than the standard AlexNet (main effect of
architecture for perturbations F(1,8)>137.4, p<0.031, η^2_p>0.94, for all adversarial perturbation
types for both VOneAlexNet and LowPassAlexNet). Both were also more robust than the standard
model to "fooling images" (23) and "feature adversaries" (69), and LowpassAlexNet was not more
robust than VOneAlexNet to these types of adversaries (Supplementary Figure 9). However,
metamers generated from LowpassAlexNet were substantially more recognizable than metamers
generated from VOneAlexNet (Figure 6g,h; main effect of architecture: F(1,19)=71.7, p<0.0001,

$\eta^2{}_p>0.79$; interaction of architecture and model stage: $F(8,152)=21.8$, $p<0.0001$, $\eta^2{}_p>0.53$). This
result further demonstrates that human recognizability of model metamers and susceptibility to
adversarial examples are dissociable. The model metamer test thus provides a complementary
comparison of model invariances that can differentiate models even when adversarial robustness
does not.
528
These adversarial robustness-related results may be understood in terms of the four types of
stimulus sets originally shown in Figure 1b, four configurations of which are depicted in Figure 6i
Adversarial examples are stimuli that are metameric to a reference stimulus for humans but that
are classified differently from the reference stimulus by a model. Adversarial robustness thus
corresponds to a situation where the human metamers for a reference stimulus fall completely
within the set of stimuli that are given the reference class label by a model (blue outline contained
within orange shaded region in 6i, right column). This condition does not imply that all model
metamers will be recognizable to humans (orange outline contained within the blue shaded
region, top row). These theoretical observations motivate the use of model metamers as a
complementary model test, and are confirmed by the empirical observations of this section. The
effect of adversarial training on model metamers (Figures 4&5) thus appears to be somewhat
specific to the training method – a model's adversarial robustness is not always predictive of the
human recognizability of its metamers.
542
Human recognition of metamers also dissociates from other forms of robustness
Neural network models have also been found to be less robust than humans to images that fall
outside their training distribution (e.g. line drawings, silhouettes, high-pass filtered images that
qualitatively differ from the photos that form the basis of the common ImageNet1K training set,
Figure 6j) (18, 70, 71). This type of robustness has been found to be improved by training models
on substantially larger data sets (72). We compared model robustness to such "out-of-distribution"
images to the recognizability of their metamers from the final model stage (the model set included
several models trained on large-scale data sets, taken from Figure 2d, along with all the other
models from Figures 2c, 3 & 4). As shown in Figure 6k, this type of robustness (measured by two
common benchmarks) was again not correlated with metamer recognizability (ImageNet-C: $\rho=-0.16$, $p=0.227$, Geirhos 2021: $\rho=-0.17$, $p=0.215$).
554

a) Visual Models from Figures 2-4

ρ=0.73***

Human Recognition of Final Layer Metamers

Adversarial Robustness

adversarially trained models

b) Audio Models from Figures 2&5

ρ=0.63**

Human Recognition of Final Convolutional Layer Metamers

Adversarial Robustness

adversarially trained models

c) Adversarially Trained Visual Models

ρ=0.31(n.s.)

Human Recognition of Final Layer Metamers

Adversarial Robustness

all models are adversarially trained

d) AlexNet Architecture

input, conv/relu (stride=4), pool (stride=2), conv/relu, pool (stride=2), conv/relu, conv/relu, conv/relu, pool (stride=2), linear/relu, linear/relu, classifier

Convolutional Layers (conv/relu)

Pooling Layers

max()

Standard Network

ReLU

Conv Stride 4

Max Pool Stride 2

Reduced Aliasing "Lowpass" Network

ReLU

Conv Stride 1

Lowpass (Hann Kernel)

Subsample Stride 4

Lowpass (Hann Kernel)

Subsample Stride 2

e) VOneAlexNet Architecture

input, biological filters, stochastic layer, maxpool, conv/relu, maxpool, conv/relu, conv/relu, conv/relu, maxpool, linear/relu, linear/relu, classifier

VOneBlock

f) Model performance with white box adversarial attacks

L_1 Perturbations

L_2 Perturbations

L_∞ Perturbations

Proportion Correct (ImageNet Task)

ε

— Standard AlexNet — LowpassAlexNet — VOneAlexnet

g) Human Recognition of Model Metamers

— Standard AlexNet
— LowpassAlexNet
— VOneAlexnet

N=20

Proportion Correct

Chance Performance (1/16)

natural/relu0 / VOneBlock, relu1, relu2, relu3, relu4, fc0_relu, fc1_relu, final

Metamer Generation Layer

h) Example Metamers

relu1 relu3 fc0_relu

Standard AlexNet

Lowpass-AlexNet

VOneAlexNet

i) **Adversarially Vulnerable:** Model misclassifies some human metamers

Adversarially Robust: Model correctly classifies human metamers

Humans correctly classify model metamers

Humans misclassify some model metamers

◆ Reference stimulus

All stimuli in human class

⃝ Human metamers

All stimuli in model class

⃝ Model metamers

j) Example ImageNet-C Augmentations

snow frost fog

Orignal Image brightness shot_noise contrast

pixelate zoom_blur glass_blur

k) Out-of-Distribution Robustness

ImageNet-C

ρ=-0.16(n.s.)

Human Recognition of Final Layer Metamers

Model Performance

Geirhos 2021

ρ=-0.17(n.s.)

Model Performance

Figure 6 (previous page). Human recognition of model metamers dissociates from adversarial vulnerability. a) Scatter plot of adversarial robustness of visual models vs. human recognizability of final model stage model metamers (N=26 models). Adversarial robustness is quantified as the average robustness to L_2 (ϵ=3) and L_∞ (ϵ=4/255) adversarial examples, normalized by the performance on natural images. Symbols follow Figure 7a. b) Same as a, but for auditory models (N=17 models). Adversarial robustness is quantified as the average robustness to L_2 (ϵ=$10^{-0.5}$) and L_∞ (ϵ=$10^{-2.5}$) adversarial perturbations of the waveform, normalized by the performance on natural audio. Symbols follow Figure 7c. c) Scatter plot of adversarial robustness of a set of visual adversarially trained models vs. human recognizability of the final model stage model metamers (N=25 models). d) Operations included in AlexNet architecture to reduce aliasing. Strided convolutions were replaced with a sequence of four operations: convolution with a learnable kernel using a stride of 1, ReLU, convolution with a fixed lowpass filter, and subsampling with the original convolution stride. Max Pooling was replaced with a sequence of two operations: convolution with a fixed lowpass filter, and subsampling with the original pooling stride. The model with these modified operations more closely obeys the sampling theorem and is referred to as "LowpassAlexNet". e) Schematic of VOneBlock input to AlexNet backbone architecture. The VOneBlock includes a stage of fixed Gabor filters, and a stochastic stage with Gaussian noise. The stochastic stage was turned on for training but turned off for evaluations of adversarial robustness and for metamer generation. f) Adversarial vulnerability, assessed via recognition accuracy on 1000-way ImageNet classification task with adversarial perturbations of different sizes added to the images. LowpassAlexNet and VOneAlexNet both produce a modest increase in adversarial robustness (greater accuracy for large adversarial perturbations) compared to the standard-trained AlexNet model. Error bars plot SEM across five subsets of training images. g) Human recognition of model metamers generated from LowpassAlexNet, VoneAlexNet and standard AlexNet models on the 16-way classification task (N=20). LowpassAlexNet has substantially more recognizable model metamers than the VOneNet, demonstrating a dissociation between human recognition of model metamers and a model's susceptibility to adversarial examples. Error bars plot SEM across participants. h) Example model metamers from experiment in (d). i) Human-recognizability of model metamer is dissociable from adversarial robustness. Adversarial examples are cases where a model misclassifies stimuli that are metameric to humans (left row). This schematic depicts a reference stimulus for which the model gives the correct class label, such that the adversarial perturbation induces a classification error. Model metamers may be unrecognizable to humans even if the model is robust to adversarial examples (bottom right). Tests involving model metamers are thus complementary to those involving adversarial examples. j) Example augmentations applied to images in tests of out-of-distribution robustness. k) Scatter plot of out-of-distribution robustness vs. human recognizability of final stage model metamers (N=26 models). Large-scale training often produces improved robustness (models denoted with ★ symbols), but not an improvement in metamer recognizability. Symbols follow Figure 7a.

Current model-brain comparisons do not capture metamer differences between models

Are the differences between models shown by the metamer test similarly evident when using standard brain comparison benchmarks? To address this question, we used such benchmarks to evaluate the visual and auditory models described above in Figures 2-5. For the visual models, we used the Brain-Score platform to measure the similarity of model representations to neural benchmarks for visual areas V1, V2, V4 and IT (38, 42). The platform's similarity measure combines a set of model-brain similarity metrics, primarily measures of variance explained by regression-derived predictions. For each model, the score was computed for each visual area using the model stage that gave highest similarity in held-out data for that visual area. We then compared this neural benchmark score to the recognizability of the model's metamers from the same stage used to generate the neural predictions. This analysis showed modest correlations between the two measures for V4 and IT (Figure 7b; V1: ρ=0.10, p=0.62; V2: ρ=0.13, p=0.51; V4: ρ=0.40, p=0.04; IT: ρ=0.45, p=0.02). We note that none of these would survive Bonferroni correction, and that these correlations were well below the presumptive noise ceiling (given the split-half reliability of both the metamer recognizability scores and the model-brain similarity scores (73), the noise ceiling of the correlation was ρ=0.92 for IT). Thus, most of the variation in metamer recognizability was not captured by standard model-brain comparison benchmarks.

We performed an analogous analysis for the auditory models, using a large data set of human
auditory cortical responses (74) (fMRI responses to a large set of natural sounds) that had
previously been used to evaluate neural network models of the auditory system (5, 75). We
analyzed voxel responses within four regions of interest in addition to all of auditory cortex, in
each case again choosing the best-predicting model stage, measuring the variance it explained
in held-out data, and comparing that to the recognizability of the metamers from that stage (Figure
7b). The correlation between metamer recognizability and explained variance in the brain
response was not significantly different from 0 when all voxels were considered (ρ=0.06, p=0.81;
Figure 7c). We did find a modest correlation within one of the ROIs (tonotopic: ρ=-0.13, p=.63;
pitch: ρ=-0.31, p=.22; music: ρ=-0.19, p=.47; speech: ρ=0.58, p=.016), but it was again well below
the presumptive noise ceiling (which ranged from ρ=0.78 to ρ=0.87, depending on the ROI), and
would not survive Bonferroni correction.
585
586 We conducted analogous analyses using representational similarity analysis instead of
587 regression-based explained variance to evaluate model-brain similarity, with similar conclusions
588 (Supplementary Figure 10). Overall, the results indicate that the metamer test is complementary
589 to traditional metrics of model-brain fit.
590

Figure 7. Human recognition of model metamers dissociates from model predictions of brain responses. a) Scatter plots of the human recognizability of a model's metamers vs. the model-brain similarity for four areas of the ventral stream as assessed by a commonly used set of benchmarks (38, 42). The benchmarks mostly consisted of the neurophysiological variance explained by model features via regression. A single model stage was chosen for each model and brain region that produced highest similarity in a test data set. Graph plots metamer recognizability and model-brain similarity for this stage. b) To obtain auditory brain predictions, 165 natural sounds presented to humans in an fMRI experiment (74) were also presented to neural network models. The model's time-averaged unit responses in each stage were used to predict each auditory cortical voxel's response by a linear mapping fit to the responses to a subset of the sounds with ridge regression. For each neural network model, the best-predicting stage was selected for each participant using independent data. Model predictions were evaluated on a set of held-out sounds. Schematic of procedure is reproduced from (5). c) Average voxel response variance explained by the best-

predicting stage of each auditory model from Figures 2 and 5, plotted against the metamer recognizability for that model stage. We performed this analysis across all voxels in auditory cortex (left) as well as within a selection of auditory functional ROIs (right). The variance explained (R^2) was measured for the best-predicting stage of the neural network models, chosen individually for each participant and each voxel subset. For each participant, the other participants' data was used to choose the stage that yielded the best predictions, and then the R^2 from this stage for the held-out participant was included in the average. Error bars on each data point plot SEM across participants.

Human recognition of a model's metamers is predicted by their recognizability to other models

Are one model's metamers recognizable by other models? We addressed this issue by taking all the models we trained for one modality, holding one model out as the "generation" model, and then presenting its metamers to each of the other models ("recognition" models), measuring the accuracy of their class predictions (Figure 8a). We repeated this procedure with each model as the generation model. Accuracy for all combinations of recognition and generation models is shown in Supplementary Figures 11 and 12. As a summary measure for each generation model, we averaged the accuracy across the recognition models (Figure 8a, right). Because we had trained the ResNet50 and CochResNet50 architectures with several variants of self-supervised and adversarial training in addition to standard supervised training, we performed further analysis of these architectures (Figure 8b&c).

In the vision models, metamers from deep stages of the standard supervised trained ResNet50 were generally not recognized by other models (Figure 8b, blue), suggesting that many of the invariances in this model are not present in the other models. A similar trend held for the models trained with self-supervision (Figure 8b, orange). By contrast, metamers from the adversarially trained models were more recognizable to other models (Figure 8b, green). We saw an analogous metamer transfer boost from the model with reduced aliasing (LowPassAlexNet), for which metamers for intermediate stages were more recognizable to other models (Supplementary Figure 12). Similar results held for auditory models (Figure 8c), though metamers from the standard supervised CochResNet50 transferred better to other models than did those for the supervised vision model, perhaps due to the shared cochlear representation present in all auditory models, which could increase the extent of shared invariances.

These results suggest that models tend to contain idiosyncratic invariances, in that their metamers vary in ways that render them unrecognizable to other models. The results also clarify the effect of adversarial training. Specifically, they suggest that adversarial training is removing some of the idiosyncratic invariances of standard-trained deep neural networks, rather than learning new invariances that are not shared with other models (in which case their metamers would not have been better recognized by other models). The architectural change that reduced aliasing had a similar effect, albeit limited to the intermediate model stages.

The average model recognition of metamers generated from a given stage of another model is strikingly similar to human recognition of the metamers from that stage (compare Figures 8b and 8c to Figures 3, 4, and 5, and Supplementary Figure 13 to Figure 6d). To quantify this similarity, we plotted the average model recognition for metamers from each stage of each generating model against human recognition of the same stimuli, revealing a strong correlation for both visual (Figure 8d) and auditory (8e) models. This result suggests that the human-model discrepancy revealed by model metamers reflects invariances that are often idiosyncratic properties of a specific neural network, leading to impaired recognition by both other models and human observers. One consequence of this result is that a collection of other models may be a reasonable proxy for a human observer -- rather than running a new psychophysical experiment

634 any time there is a new model to evaluate, one could test the model's metamers on a set of other
635 models, facilitating the automation of searches for better models of perception.

Figure 8. Human recognition of a model's metamers is correlated with their recognition by other models. a) Model metamers were generated for each stage of a "generation" model (one of the models from Figures 2c-d, 3, 4, and 6g for visual model analysis, and from Figures 2f and 5 for auditory model analysis). The associated metamers are input into "recognition" models (all other models from Figures 2c-d, 3, 4, and 6g for visual model analysis, and from Figures 2f and 5 for auditory model analysis). We measured recognition of the generating model's metamers by each recognition model, averaging the accuracy over all recognition models (excluding the generation model). This analysis is shown here for a standard-trained ResNet50 image model. Error bars are SEM over recognition models. b) Average model recognition of metamers generated from the standard ResNet50, the three self-supervised ResNet50 models, and the three ResNet50 models trained with adversarial perturbations. In model groups with multiple generating models, we averaged each recognition model's accuracy curve across all of the generating models, then averaged these curves across the recognition models. Error bars are the SEM over recognition models. Model metamers from deep stages tend to be unrecognizable to other models, but models trained with adversarial perturbations have metamers that are more recognizable by other models. c) Same as b, but for auditory models, with metamers generated from the standard CochResNet50, three CochResNet50 models with waveform adversarial perturbations, and two CochResNet50 models with cochleagram adversarial perturbations. Chance performance is 1/794 for the models because (unlike the human experimental participants) they had a "null" (no speech) class label as a possible prediction in addition to the 793 word labels. d, e) Correlation between human and model recognition of another model's metamers for visual (d) and auditory (e) models. The abscissa of each data point plots the average human recognition accuracy of metamers generated from one stage of a model. The ordinate of each data point plots the average recognition by other models of those metamers. In both modalities, human recognition of a model's metamers is highly correlated with the accuracy of other models at recognizing those same model metamers (quantified by Spearman rank-ordered correlation coefficient).

Discussion

We used model metamers to reveal invariances of deep artificial neural networks, and compared these invariances to those of humans by measuring human recognition of visual and auditory model metamers. We found that metamers of standard deep neural networks are dominated by invariances that are absent from human perceptual systems, in that metamers from deep model stages are typically completely unrecognizable to humans. This was true across modalities (both visual and auditory) and across training methods (supervised vs. self-supervised training). We identified ways to make model metamers more human-recognizable in both the auditory and visual domains, including a new type of adversarial training for auditory models using perturbations at an intermediate model stage. Although there was a substantial effect on metamer recognizability from one common training method to reduce adversarial vulnerability, we found that metamers could reveal model differences that were not evident by measuring adversarial vulnerability alone. Moreover, the model improvements revealed by model metamers were not obvious from standard brain prediction metrics. These results show that metamers provide a model comparison tool that complements the standard benchmarks that are in widespread use.

Even though some models produced significantly more recognizable metamers than others, metamers generated from late model stages remained less recognizable than natural images or sounds in all cases we tested, suggesting that substantial further improvements are needed to align model representations with those of biological sensory systems. The fact that one model generally cannot recognize another model's metamers indicates that the discrepancy is at least partially caused by invariances that are idiosyncratic to a model (being absent in both humans and other models). Might humans analogously have their own invariances that are specific to an individual? This possibility is difficult to explicitly test given that we cannot currently sample human metamers (model metamer generation relies on having access to the model's parameters and responses, which are currently beyond reach for biological systems). If idiosyncratic invariances were present in humans as well, the phenomenon we have described here might not represent a human-model discrepancy, and could instead be a general property of recognition systems. The main argument against this interpretation is that several model modifications motivated by engineering considerations – different forms of adversarial training, and architectural modifications to reduce aliasing – substantially reduced the idiosyncratic invariances present in standard deep neural network models. These results suggest that idiosyncratic invariances are not unavoidable in a recognition system. Moreover, the set of modifications explored here was far from exhaustive, and we see no reason why the idiosyncratic model invariances could not be further alleviated with alternative training or architecture changes in the future.

Relation to previous work

The methods we use to synthesize model metamers are not new. Previous neural network visualizations have also used gradient descent on the input to visualize representations (76), in some cases matching the activations at individual stages as we do here (64). However, the significance of these visualizations for evaluating neural network models of biological sensory systems has received relatively little attention. One contributing factor may be that model visualizations have often been constrained by added natural image priors or other forms of regularization (77) that help make model visualizations look more natural, but mask the extent to which they otherwise diverge from a perceptually meaningful stimulus. For this reason, we intentionally avoided priors or other regularization when generating model metamers, as they defeat the purpose of the metamer test. When we explicitly measured the benefit of regularization, we found that it did boost recognizability somewhat, but that it was not sufficient to render model metamers fully recognizable, or to reproduce the benefits of model modifications that improve metamer recognizability (Figure 4e).

Another reason the discrepancies we report here have not been widely discussed within
neuroscience is that most studies of neural network visualizations have relied on small numbers
of examples rather than systematically measuring recognizability to human observers (in part
because these visualizations are primarily reported within computer science, where such
experiments are not the norm). By contrast, our work used human perceptual experiments to
quantify the divergence between human and model invariances, revealing a widespread
mismatch between humans and current state-of-the-art computational models. We found
controlled experiments to be essential. Prior to running full-fledged experiments we always
conducted the informal exercise of generating examples and evaluating them subjectively.
Although the largest effects were evident informally, the variability of natural images and sounds
made it difficult to predict with certainty how an experiment would turn out. It is thus critical to
substantiate informal observation with controlled experiments in humans.
700
Metamers are also related to a type of adversarial example generated by adding small
perturbations to an image from one class such that the activations of a classifier match those of
a reference image from a different class. These "invariance-based adversarial examples" yield
the same model activations at the classification stage (sometimes referred to as "feature
adversaries" (69) or "feature collisions" (78)), but are seen as different classes by humans (albeit
again tested informally with a small number of examples rather than a systematic experiment)
(79, 80). Our method differs in probing the model invariances without any explicit bias to cause
the metamers to appear different to humans, but our results may reflect some of the same
properties evident in these alternative adversarial stimuli. We innovate on this prior work by
quantifying human recognition with experiments, in probing invariances across model stages, by
exploring a diverse set of models (e.g. those trained with self-supervision), by showing that the
relevant phenomena generalize across auditory and visual domains, and by identifying many non-
human invariances as model-specific. The finding that models tend to learn idiosyncratic
invariances may be related to findings that the representational dissimilarity matrices for natural
images can vary between individual neural network models (81).
716
Metamers have previously been used to validate models of visual and auditory texture (30, 82),
and visual crowding (34, 35, 83, 84). A related type of model-matched stimulus has been used to
test whether models can account for brain responses (58). In these previous lines of work the
models instantiated hypotheses about specific types of invariances that may be present in human
sensory systems, and the experiments assess human perception or brain responses to test the
hypotheses. Our work differs in that the models are learned, and could in principle instantiate
many different types of invariances (which are a priori unknown).
724
Our work also differs from prior work on metamers in that our test of model metamers is a
recognition test rather than a same/different metamerism test that has classically been used for
evaluating models of early sensory stages (measuring the ability to discriminate two stimuli). We
view the recognition test as most appropriate for current deep neural network models that are
typically trained on one or two tasks at most and that model components of high-level sensory
perception, such as object or speech recognition. A same/different discrimination judgment might
be performed using any representations in the observer's perceptual system, rather than just
those that are relevant for a particular task. There is thus no reason to expect that metamers for
representations that support a particular task would be completely indistinguishable in every
respect to a human (in contrast to metamers of color vision, for instance, for which the entire
visual system is constrained by the cone inputs). The classical metamer test is thus likely to be
too sensitive for our purposes – models may fail the test even if they succeeded in capturing the
invariances of a particular task. We note that because an unrecognizable metamer would

obviously be distinguishable from the natural image or sound to which its activations are matched,
a failure in our recognition test also implies a failure in the classical test of metamerism.
740
Effects of unsupervised training
One common criticism of task-optimized models is that supervised training on classification tasks
is inconsistent with biological learning (48). Recent advances in unsupervised learning have
enabled useful representations to be learned from large quantities of natural data without explicit
labels, potentially providing a more biologically plausible computational theory of learning (52, 85,
86). A priori it seemed plausible that the invariances of deep neural network models could be
strongly dependent on supervised training for classification tasks, in which case models trained
without supervision might be substantially more human-like according to the metamers test.
However, we found that the invariances learned from self-supervised learning also diverged from
the invariances of human perceptual systems.
751
The metamer-related model discrepancies we saw for self-supervised models are particularly
striking because these models are trained with the goal of invariance, being explicitly optimized
to become invariant to the augmentations performed on the input. But the metamers of these
models reveal that they nonetheless encode invariances that diverge from those of human
perception. This finding is consistent with evidence that the classification errors of self-supervised
models are no more human-like than those of supervised models (87). We also found that the
divergence with human recognition had a similar dependence on model stage irrespective of
whether models are trained with or without supervision. These findings raise the possibility that
factors common to supervised and unsupervised neural networks underlie the divergence with
humans.
762
Differences in metamers across stages
The metamer test differs from some other model metrics (e.g. behavioral judgments of natural
images or sounds, or measures of adversarial vulnerability) in that metamers can be generated
from every stage of a model, with the resulting discrepancies associated with particular model
stages. Because invariances reflect information that is discarded, and because information that
is discarded at one stage of a feedforward system cannot be recovered, the set of metamers for
a reference stimulus cannot shrink from one model stage to the next. But apart from this constraint
it is otherwise not obvious how discrepancies might develop across stages, and we observed
variation from model to model.
772
One application of this stage-specificity is to characterize intermediate model stages. In some
cases metamers revealed that intermediate stages were more human-like in some models than
others. For example, the effects of reducing aliasing produced large improvements in the human-
recognizability of metamers from intermediate stages (Figure 6g), consistent with the idea that
biological systems also avoid aliasing. By contrast, metamers from the final stages showed little
improvement. This result indicates that this model change produces intermediate representations
with more human-like invariances despite not resolving the discrepancy introduced at the final
model stages.
781
For most models, the early stages produced model metamers that were fully recognizable, but
that also resemble the original image or sound they were matched to. By contrast, metamers from
late stages physically deviated from the original image or sound but for some models nonetheless
remained recognizable. This difference highlights two ways that a model's metamers can pass
the recognition test used here – either by being perceptually indistinguishable to humans, or by
being recognizable to humans as the same class despite being perceptually distinct. This

distinction could be quantified in future work by combining a traditional metamer test with our
recognition test.
790
791 Across all the models we considered, the final model stages tended to produce metamers that
792 were less recognizable than natural images to humans as well as to other models. This was true
793 irrespective of how the models were trained. This result highlights these deep stages as targets
794 for model improvements (55).
795

Limitations
Although a model that fails our metamer test is ruled out as a description of human perception,
passing the test, on its own, reveals little. For instance, a model that instantiates the identity
mapping would pass our test despite not being able to account for human perceptual abilities.
Traditional metrics thus remain critical, but on their own are also insufficient (as shown in Figures
6 and 7). Failing the test also does not imply that the model representations are not present in the
brain, only that they are not sufficient to account for the recognition behavior under consideration.
For instance, there is considerable evidence for time-averaged auditory statistics in auditory
perception (30, 88) even though they do not produce human-recognizable metamers for speech
(Supplementary Figure 5f). We thus argue that a large suite of test metrics, including but not
limited to the model metamer test, is needed for model comparison.
807
Model metamers are generated via iterative gradient-based optimization of a non-convex loss
function, and only approximately reproduce the activations of the natural stimulus to which they
are matched. We attempted to improve on previous neural network visualization work (64, 76) by
setting explicit criteria for the optimization success. For models that perform classification tasks,
we verified that the model metamer produced the same class label as the reference stimulus to
which it was matched. Failures of the metamer test represent an unambiguous dissociation of
model and human behavior for such models. We also verified that the residual error between the
metamer and reference activations was much smaller than would be expected by chance, and
that the residual error did not predict metamer recognizability (Supplementary Figure 4). However,
the reliance on optimization may be a limitation in some contexts and with some models.
818
The metamer optimization process is also not guaranteed to sample uniformly from the set of a
model's metamers. Non-uniform sampling cannot explain the human-model discrepancies we
observed, but could in principle contribute to differences between the magnitude of discrepancies
for some models compared to others. For instance, the greater human-recognizability of
metamers from some models could in principle be caused by differences in the optimization
landscape that make it less likely that the metamer generation process samples along a model's
idiosyncratic invariances. We are not aware of any reason to think that this might be the case, but
it is not obvious how to fully exclude this possibility.
827

Adversarial training reduces idiosyncratic invariances
Why does adversarial training produce models with more recognizable metamers? One
interpretation is that it prevents models from "cheating" on tasks by using data set artifacts to
make decisions (61) and as a consequence develops more human-like invariances. This
interpretation is supported by findings that adversarial examples often transfer across models (60,
89). Our results suggest that the effect of adversarial training on metamers likely has a distinct
explanation. First, we found that not all model changes that improve adversarial robustness have
comparable effects on metamer recognizability (Figure 6). In addition, robustness differences
between different adversarially trained models did not predict recognizability differences between
their metamers. These two findings suggest that it is the adversarial training procedure, rather
than adversarial robustness per se, that underlies the increased human recognizability of model

metamers. Second, metamers from standard-trained models generally did not transfer across
models trained on the same data set (unlike adversarial examples). Metamers from adversarially
trained models were more recognizable to humans but also transferred substantially better to
other models. This finding suggests that adversarial training serves to avoid the model-specific
invariances that are otherwise learned by deep neural network models. This set of results
highlights the relationship between adversarial robustness and model metamers as a promising
direction for future study.
846
Future directions
The underlying causes of the human-model discrepancies demonstrated here seem important to
understand, in part because we will not fully understand biological sensory systems until we can
replicate them in a model, and deep neural networks are currently the most promising candidates.
In addition, many otherwise promising model applications, such as model-based signal
enhancement (90, 91), are likely to be hindered by human-discrepant model invariances.
853
The supervised models we explored here were trained on a single speech or image recognition
task. It is possible that the use of a single task causes models to discard information that is
preserved by biological sensory systems. One possibility is that biological sensory systems do
not instantiate invariances per se, in the sense of mapping multiple different inputs onto the same
representation (92, 93). Instead, they might learn representations that untangle behaviorally
relevant variables. For instance, a system could represent word labels and talker identity, or object
identity and pose, via independent directions in a representational space. Such a representational
scheme could enable invariant classification without invariant representations. Some model
architectures may be able to address this hypothesis, for instance by factoring out different latent
variables that, once combined, can reconstruct the input representation. But as of yet we lack
methods for building such models that can support human-level recognition at scale. Training on
multiple tasks could be another approach that would serve this goal. The results of Figure 8 –
showing that the recognition judgments of a set of models for another model's metamers are
predictive of human recognition – suggest a way to efficiently test any model for discrepant
metamers, which should facilitate evaluation of these and any other model class.
869
The discrepancies shown here for model metamers contrast with a growing number of examples
of human-model similarities for behavioral judgments of natural stimuli. Models optimized for
object recognition (94), speech recognition (5), sound localization (95), and pitch recognition (96)
all exhibit qualitative and often quantitative similarities to human judgments when run in traditional
psychophysical experiments with natural or relatively naturalistic stimuli. Neural network models
trained in naturalistic conditions thus often match human behavior for signals that fall within their
training distribution, but not for some signals derived from the model that fall outside the
distribution of natural sounds and images.
878
Current deep neural network models are overparametrized, such that training produces one of
many functions consistent with the training data. From this perspective it is unsurprising that
different systems can perform similarly on natural signals while exhibiting different responses to
signals outside the training distribution of natural images or sounds. And yet we nonetheless
found that sensible engineering modifications succeeded in bringing models into better alignment
with human invariances. These results demonstrate that divergence between human and model
invariances is not inevitable, and show how metamers can be a useful metric to guide and
evaluate the next generation of brain models.

METHODS

Model training and evaluation
Models were trained and evaluated with the PyTorch deep learning library (97), and the Robustness library (98), modified to accommodate metamer generation and auditory model training. Model code and instructions for downloading checkpoints are available online at https://github.com/jenellefeather/model_metamers_pytorch. Model architecture descriptions are provided as Supplemental Information. All models were trained on the OpenMind computing cluster at MIT using NVIDIA GPUs with a minimum of 11GB memory. In the methods sections that follow we often refer to model stages as "layers", to be consistent with how they are named in PyTorch. "Stage" and "layer" should be taken as synonymous.

Image training dataset
Unless otherwise noted, all visual neural network models were trained on the ImageNet1K Large Scale Visual Recognition Challenge dataset (37). This classification task consists of 1000 classes of images with 1,281,167 images in the training set and 50,000 images in the validation set. All classes were used for training the neural network models. Accuracy on ImageNet1K task and additional training parameters are reported in Table 1.

ImageNet1K model training and evaluation
Unless otherwise described below, visual models trained on ImageNet1K consisted of publicly available checkpoints. Standard supervised models used the pretrained PyTorch checkpoints from torchvision.models (documentation https://pytorch.org/vision/stable/models.html, referred to as "pytorch" in Table 1). Visual model performance was evaluated as the model accuracy on the ImageNet1K validation set, implemented by resizing the images so the smallest dimension was 256 pixels (or 250 in the case of HMAX) and taking a center crop of 224x224 (or 250 in the case of HMAX) pixels of the image. Train, test, and metamer images were all normalized by subtracting channel means and dividing by channel standard deviations before being passed into the first stage of the neural network backbone (except in the case of HMAX, where this normalization was not applied). Channel means were set to [0.485, 0.456, 0.406] and channel standard deviations were set to [0.229, 0.224, 0.225] unless otherwise noted for the architecture. ImageNet1K model training used data-parallelization to split batches across multiple GPUs.

Visual models trained on large-scale datasets
We also tested five visual models that were pretrained on datasets larger than the ImageNet1K dataset described above. Two of these were the visual encoders from Contrastive Language-Image Pre-Training (CLIP) models (one with a ResNet50 visual encoder and one with a ViT-B_32 visual encoder), obtained from the publicly available checkpoints at https://github.com/openai/CLIP (referred to as "clip" in Table 1) (43). CLIP models were trained on a dataset of 400 million (image, text) pairs collected from the internet. ImageNet1K performance from the CLIP models is evaluated with a zero-shot prediction using the list of prepared 80 image template prompts and modified ImageNet labels from (43). We found empirically that we could not synthesize metamers from this classifier, and so only included model stages from the visual encoder in our experiments. CLIP models used a custom channel mean of [0.48145466, 0.4578275, 0.40821073] and a channel standard deviation of [0.26862954, 0.26130258, 0.27577711]. The third and fourth of these models were Semi-Weakly Supervised (SWSL) ImageNet models (ResNet50 and ResNeXt101-32x8d architectures), obtained from the publicly available checkpoints at https://github.com/facebookresearch/semi-supervised-ImageNet1K-models (referred to as "swsl" in Table 1) (44). SWSL Models are pre-trained on 940 million public images with 1.5K hashtags matching with the 1000 synsets in the ImageNet dataset, followed by fine-tuning on the ImageNet1K training images described above. The fifth model was

938 a Vision Transformer (ViT_large_patch-16_224, (45)), obtained from the publicly available
939 checkpoint at https://github.com/rwightman/pytorch-image-models (referred to as "timm" in Table
940 1). ViT_large_patch-16_224 was pre-trained on the ImageNet-21K dataset, consisting of
941 approximately 14 million images with about 21000 distinct object categories, and then fine-tuned
942 on the ImageNet1K training images described above.
943
Self-supervised ResNet50 vision models
Self-supervised ResNet50 models were downloaded from the OpenSelfSup Model Zoo, and the
training details that follow are taken from the documentation (https://github.com/open-
mmlab/OpenSelfSup, referred to as "openselfsup" in Table 1). Three models, each with a
ResNet50 architecture, were used: MoCo_V2, SimCLR and BYOL. MoCo_V2 self-supervised
training had a batch size of 256, with data augmentations consisting of random crop (224x224
pixels), random horizontal flip (probability=0.5), random color jitter (brightness=0.4, contrast=0.4,
saturation=0.4, hue=0.1, probability=0.8, all values uniformly chosen), random greyscale
(probability=0.2), and random gaussian blur (sigma_min=0.1, sigma_max=0.2, probability=0.5).
SimCLR self-supervised training had a batch size of 256, with augmentations consisting of
random crop (224x224 pixels), random horizontal flip (probability=0.5), random color jitter
(brightness=0.8, contrast=0.8, saturation=0.8, hue=0.2, probability=0.8, all values uniformly
chosen), random greyscale (probability=0.2), and random gaussian blur (sigma_min=0.1,
sigma_max=0.2, probability=0.5). BYOL self-supervised training had a batch size of 4096, with
augmentations consisting of random crop (224x224 pixels), random horizontal flip
(probability=0.5), random color jitter (brightness=0.4, contrast=0.4, saturation=0.2, hue=0.1,
probability=0.8, all values uniformly chosen), random greyscale (probability=0.2), and random
gaussian blur (sigma_min=0.1, sigma_max=0.2, probability=0.5). For all self-supervised
ResNet50 models, a linear readout consisting of a fully connected layer with 1000 units applied
to the average pooling layer of the model was trained using the same augmentations used for
supervised training of the other ImageNet1K-trained models described above. The linear readout
was trained for 100 epochs of ImageNet1K (while the model backbone up to avgpool remained
unchanged). For MoCo_V2 and SimCLR models, the accuracy was within 1% of that reported on
the OpenSelfSup (BYOL average pooling evaluation was not posted at the time of training). The
linear readout served as a check that the downloaded models were instantiated correctly, and
was used to help verify the success of the metamer generation optimization procedure, as
described below. Linear evaluations from each model stage were obtained by training a fully
connected layer with 1000 units and a softmax classifier applied to a random subsample of 2048
activations. If the number of activations was less than or equal to 2048 all activations were
maintained.
974
Self-supervised IPCL AlexNetGN models
A model trained with Instance-Prototype Contrastive Learning (IPCL) and a supervised model
with the same augmentations were downloaded from the IPCL github (https://github.com/harvard-
visionlab/open_ipcl, referred to as "ipcl" in Table 1) (52). Both models used an AlexNet
architecture with group-normalization layers. As described in the original publication (52), the
models were trained with a batch size of 128x5 (128 images with 5 augmentations each), for 100
epochs, with data augmentations consisting of a random resize crop (random crop of the image
resized with a scale range of [0.2,1] and aspect ratio [3/4,4/3], and resized to 224x224 pixels),
random horizontal flip (probability=0.5), random grayscale conversion (probability=0.2), random
color jitter (brightness=0.6, contrast=1, saturation=0.4, and hue +/- 144 degrees).
985
Using the procedure described in (52), a linear readout consisting of a fully connected layer with
1000 units was used to evaluate each model stage. The readout was trained using a batch size
of 256, with input augmentations of a random resize crop (random crop of the image resized with

a scale range of [0.08,1] and aspect ratio [3/4,4/3], and resized to 224x224 pixels) and a random
horizontal flip (probability=0.5). The linear readout was trained for 10 epochs with the one-cycle
learning rate policy (99), with cosine annealing to vary the learning rate from 0.00003, increasing
to a maximum of .3 after 3 epochs, then decreasing with a cosine annealing function toward zero
(3e-09) by 10 epochs.
994

Models trained on Stylized ImageNet
Models trained on a "Stylized" ImageNet were downloaded from publicly available checkpoints
(https://github.com/rgeirhos/texture-vs-shape, referred to as "texture-vs-shape" in Table 1) and
training details that follow are taken from the documentation (53). Stylized ImageNet is
constructed by taking the content of an ImageNet1K image and replacing the style of the image
with that of a randomly selected painting using AdaIN style transfer (100). A single stylized version
of each image in the ImageNet1K training dataset was used for training. The models were trained
with a batch size of 256 for 60 epochs, with input augmentations of a random resize crop (random
crop of the image resized with a scale range of [0.08,1] and aspect ratio [3/4,4/3], and resized to
224x224 pixels) and a random horizontal flip (probability=0.5).
1005

HMAX vision model
The hand-engineered HMAX vision model was based off of a publicly availably implementation in
PyTorch (https://github.com/wmvanvliet/pytorch_hmax) which follows the model documented in
a previous publication (4). A gaussian activation function was used, and boundary handling was
added to match the MATLAB implementation provided by the original HMAX authors
(https://maxlab.neuro.georgetown.edu/hmax.html). For full comparison to the other models, we
trained a linear classifier consisting of 1000 units to perform the ImageNet1K recognition task on
the final C2 output of the HMAX model. This fully connected layer was trained for 30 epochs of
the ImageNet1K training dataset, and the learning rate was dropped after every 10 epochs. Inputs
to HMAX during the classifier training consisted of random crops (250x250 pixels), random
horizontal flip (p=0.5), random color jitter (brightness=0.1, contrast=0.1, saturation=0.1,
probability=1, all values uniformly chosen), and lighting noise (alpha standard deviation of 0.05,
an eigenvalue of [0.2175, 0.0188, 0.0045], and channel eigenvectors of [[-0.5675, 0.7192,
0.4009], [-0.5808, -0.0045, -0.8140], [-0.5836, -0.6948, 0.4203]]). HMAX performance was
evaluated by measuring the model accuracy on the ImageNet1K validation set after resizing the
images so that the smallest dimension was 250 pixels, taking a center crop of 250x250 pixels of
the image, converting to greyscale, and multiplying by 255 to scale the image to the 0-255 range.
As expected, the performance on this classifier was low, but it was significantly above chance
and could thus be used for the metamer optimization criteria described below.
1025

Adversarial training – vision models
Adversarially trained ResNet50 models were obtained from the robustness library
(https://github.com/MadryLab/robustness, referred to as "robustness" in Table 1). Adversarially
trained AlexNet architectures and the random perturbation ResNet50 and AlexNet architectures
were trained for 120 epochs of the ImageNet1K dataset, with image pixel values scaled between
0-1, using data parallelism to split batches across multiple GPUs. Learning rate was decreased
by a factor of 10 after every 50 epochs of training. During training, data augmentation consisted
of random crop (224x224 pixels), random horizontal flip (probability=0.5), color jitter
(brightness=0.1, contrast=0.1, saturation=0.1, probability=1, all values uniformly chosen), and
lighting noise (alpha standard deviation of 0.05, an eigenvalue of [0.2175, 0.0188, 0.0045], and
channel eigenvectors of [[-0.5675, 0.7192, 0.4009], [-0.5808, -0.0045, -0.8140], [-0.5836, -0.6948,
0.4203]]). An adversarial or random perturbation was then added. All adversarial examples were
untargeted, such that the loss used to generate the adversarial example pushed the input away
from the original class by maximizing the cross-entropy loss, but did not push the prediction

towards a specific target class. For the L_2-norm ($\epsilon = 3$) model, adversarial examples were
generated with a step size of 1.5 and 7 attack steps. For the L_∞-norm ($\epsilon = 8/255$) model,
adversarial examples were generated with a step size of 4/255 and 7 attack steps. For both
ResNet50 and AlexNet random-perturbation L_2-norm models, a random sample on the L_2 ball with
width $\epsilon = 3$ was drawn and added to the input, independently for each training example and
dataset epoch. Similarly, for both Resnet50 and AlexNet random perturbation L_∞-norm models, a
random sample on the corners of the L_∞ ball was selected by randomly choosing a value of ±8/255
to add to each image pixel, independently chosen for each training example and dataset epoch.
After the adversarial or random perturbation was added to the input image, the new image was
clipped between 0-1 before being passed into the model.
1050
VOneAlexNet vision model
The VOneAlexNet architecture was downloaded from the VOneNet GitHub repository
(https://github.com/dicarlolab/vonenet) (67). Modifications were then made to use Gaussian noise
rather than Poisson noise as the stochastic component, as in (68), and to use the same input
normalization as in our other models (rather than a mean of 0.5 and standard deviation of 0.5 as
used in (67)). The VOneAlexNet architecture was trained for 120 epochs using the same data
augmentations and training procedure described for the adversarially trained AlexNet model (but
without adversarial or random perturbations). The model was trained with stochastic responses
(Gaussian noise with standard deviation of 4) in the "VOne" model stage, but for the purposes of
metamer generation we fixed the noise by randomly drawing one noise sample when loading the
model and using this noise sample for all metamer generation and adversarial evaluation.
Although "fixing" the noise reduces the measured adversarial robustness compared to when a
different sample of noise is used for each iteration of the adversarial example generation, the
model with a single noise draw was still significantly more robust than a standard model, and
allowed us to perform the metamer experiments without having to account for the stochastic
representation during metamer optimization.
1067
LowpassAlexNet vision model
The LowpassAlexNet architecture was trained for 120 epochs using the same augmentations and
training procedure described for the adversarially trained AlexNet models (but without adversarial
or random perturbations). To approximately equate performance on natural stimuli with the
VOneNetAlexNet, we chose an early checkpoint that was closest, but did not exceed, the Top 1%
performance of the VOneAlexNet model (to ensure that the greater recognizability of the
metamers from LowpassAlexNet could not be explained by higher overall performance of that
model). This resulted in a comparison model trained for 39 epochs of the ImageNet1K dataset.
1076
AlexNet vision model, early checkpoint
We trained an AlexNet architecture for 120 epochs using the same augmentations and training
procedure described for the adversarially trained AlexNet models (but without adversarial or
random perturbations). After training, to approximately equate performance on natural stimuli with
the VOneNetAlexNet and LowpassAlexNet, we chose an early checkpoint that was closest, but
not lower than, the performance of the VOneAlexNet model. This resulted in a comparison model
trained for 51 epochs of the ImageNet1K dataset.
1084
Pre-trained adversarially robust models for final stage evaluation
To compare the relationship between metamer recognizability and adversarial robustness of
adversarially trained models (Figure 6c), we evaluated a large set of adversarially trained models.
We evaluated all of the models included in a well-known robustness evaluation as of November
2022 – these comprised the ImageNet- L_∞ evaluation of robustbench (65) (8 models), as well as
additional models from each of the repositories from which these models were chosen (17

additional models), for a total of 25 models. Five of these models were from
https://github.com/dedeswim/vits-robustness-torch (101), and were trained with L_∞-norm, $\epsilon =$
$4/255$, (ViT-XCiT-L12, ViT-XCiT-M12, ViT-XCit-S12, ConvNeXt-T, and GELUResNet-50).
Another 16 of these models were from https://github.com/microsoft/robust-models-transfer (102),
with 3 trained with L_∞-norm, $\epsilon = 4/255$, (ResNet18, ResNet50, and Wide-ResNet-50-2), 3 trained
with L_∞-norm, $\epsilon = 1/255$, (ResNet18, ResNet50, and Wide-ResNet-50-2), and 10 trained with L_2-
norm, $\epsilon = 3.0$, (ResNet18, ResNet50, Wide-ResNet-50-2, Wide-ResNet-50-4, DenseNet,
MNASNET, MobileNet-v2, ResNeXt50_32x4d, ShuffleNet, VGG16_bn). Another 3 models were
ResNet50 architectures from https://github.com/MadryLab/robustness (98); one was trained on
L_∞-norm, $\epsilon = 4/255$, one was trained on L_∞-norm, $\epsilon = 8/255$, and was one trained on L_2-
norm , $\epsilon = 3.0$). Lastly, 1 model was the ResNet50 checkpoint available from
https://github.com/locuslab/fast_adversarial (103). Only the final layer was used for metamer
generation for these models. These models are omitted from Table 1 as they were used for only
a single analysis (that of Figure 6b).
1105
Adversarial evaluation -- visual models
The adversarial robustness of visual models was evaluated with white-box untargeted adversarial
attacks (i.e., in which the attacker has access to the model's parameters when determining an
attack that will cause the model to classify the image as any category other than the correct one).
All 1000 classes of ImageNet1K were used for the adversarial evaluation. Attacks were computed
with L_1, L_2, and L_∞ maximum perturbation sizes (ε) added to the image, with 64 gradient steps
each with size ε/4 (pilot experiments suggested that this step size and number of steps were
sufficient to produce adversarial examples for most models). We randomly chose images from
the ImageNet1K evaluation dataset to use for adversarial evaluation, applying the evaluation
augmentation described above (resizing so that the smallest dimension was 256 pixels, followed
by a center crop of 224x224 pixels). Five different subsets of 1024 stimuli were drawn to compute
error bars.
1118
For the detailed investigation of adversarial vulnerability shown in Supplemental Figure 9, we
measured robustness to two additional types of white-box adversarial attacks. "Fooling Images"
(23) were constructed by first initializing the input image as a sample from a normal distribution
with standard deviation of 0.05 and a mean of 0.5. We then randomly chose a target label from
the 1000 classes of ImageNet1K and derived a perturbation to the image that would cause the
noise to be classified as the target class. Performance was evaluated as the percent of perturbed
images that had the target label. Attacks were computed with L_1, L_2, and L_∞ maximum perturbation
sizes (ε) added to the image, with 64 gradient steps each with size ε/4. Error bars were computed
using five different random samples of 1024 target labels. "Feature Adversaries" (69) were
constructed by deriving small perturbations to a natural "source" image to yield model activations
(at a particular model stage) that are close to those evoked by a different natural "target" image,
by minimizing the L_2 distance between the perturbed source image activations and the target
activations. The source and target images were randomly selected from the ImageNet1K
validation dataset. Evaluation was performed by measuring the percent of perturbed images that
had the same label as the target image. Attacks were computed with L_1, L_2, and L_∞ maximum
perturbation sizes (ε) added to the image, with 128 gradient steps each with size ε/16. Error bars
were computed using five different subsets of 1024 "source" and "target" stimuli.
1136
For the statistical comparisons between the adversarial robustness of architectures for Figure 6f
we performed a repeated measure ANOVA with within-group factors of architecture and
perturbation size ϵ. A separate ANOVA was performed for each adversarial attack type. The

values of ϵ included in the ANOVA were constrained to a range where the VOneAlexNet and
LowPassAlexNet showed robustness over the standard AlexNet (four values for each attack type,
$\epsilon_{L_1} \in \{10^{1.5}, 10^2, 10^{2.5}, 10^3\}$, $\epsilon_{L_2} \in \{10^{-1}, 10^{-0.5}, 10^0, 10^{0.5}\}$, $\epsilon_{L_\infty} \in \{10^{-3.5}, 10^{-3}, 10^{-2.5}, 10^{-2}\}$), so
that any difference in clean performance did not affect the comparisons. We computed statistical
significance for the main effect of architecture by a permutation test, randomly permuting the
architecture assignment, independent for each subset of the data. We computed a p-value by
comparing the observed F-statistic to the null distribution of F-statistics from permuted data (i.e.,
the p-value was one minus the rank of the observed F-statistic divided by the number of
permutations). In cases where the maximum possible number of unique permutations was less
than 10,000, we instead divided the rank by the maximum number of unique permutations.
1150
We performed the same type of ANOVA analysis for the statistical comparisons in Supplementary
Figure 9, using adversarial attack strengths for which VOneAlexNet and LowPassAlexNet showed
robustness over the standard AlexNet for the specific attack being evaluated. For the "Fooling
Images" in Supplementary Figure 9a we used attack strengths of $\epsilon_{L_1} \in \{10^{1.5}, 10^2, 10^{2.5}, 10^3\}$,
$\epsilon_{L_2} \in \{10^{-1}, 10^{-0.5}, 10^0, 10^{0.5}\}$, $\epsilon_{L_\infty} \in \{10^{-3.5}, 10^{-3}, 10^{-2.5}, 10^{-2}\}$, and for the feature adversaries in
Supplementary Figure 9b we used attack strengths of $\epsilon_{L_1} \in \{10^{2.5}, 10^3, 10^{3.5}, 10^4\}$, $\epsilon_{L_2} \in$
$\{10^0, 10^{0.5}, 10^1, 10^{1.5}\}$, $\epsilon_{L_\infty} \in \{10^{-2.5}, 10^{-2}, 10^{-1.5}, 10^{-1}\}$).
1158
1159 *Out of distribution evaluation – visual models*
1160 We evaluated model performance on out of distribution images using two publically available
1161 benchmarks. For both benchmarks, we utilized the BrainScore (42) implementations of the
1162 behavioral benchmarks for the models.
1163
1164 The ImageNet-C benchmark (70) measures model top 1 accuracy on distorted images derived
1165 from the ImageNet test set, using the labels for the original image. The accuracy is averaged over
1166 stimulus sets consisting of the following distortions: Gaussian noise, shot noise, impulse noise,
1167 defocus blur, frosted glass blur, motion blur, zoom blur, snow, frost, fog, brightness, contrast,
1168 elastic, pixelate, and JPEG compression.
1169
The Geirhos 2021 benchmark (72) measures whether the model gets the same stimuli correct as
human observers (error consistency), using 16-way recognition decisions from human observers
for comparison. The error consistency is averaged over stimulus sets consisting of the following
stimulus manipulations: colour/grayscale, constrast, high-pass, low-pass (blurr), phase
scrambling, power equalization, false colour, rotation, Eidolon I, Eidolon II, Eidonlon III, uniform
noise, sketch, stylized, edge, silhouette, and texture-shape cue conflict.
1176
1177

Model	Learning Rate (at Start)	Batch Size	Accuracy Top 1	Accuracy Top 5
AlexNet Standard	(pretrained, pytorch)	(pretrained)	56.518	79.070
AlexNet L_2-norm ($\epsilon = 3$)	0.01	256	41.882	65.018
AlexNet random L_2-norm ($\epsilon = 3$)	0.01	256	57.978	79.986
AlexNet L_∞-norm ($\epsilon = 8/255$)	0.01	256	29.702	51.034
AlexNet random L_∞-norm ($\epsilon = 8/255$)	0.01	256	57.738	79.996
ResNet50 Standard	(pretrained, pytorch)	(pretrained)	76.130	92.862

ResNet50 L_2-norm ($\epsilon = 3$)	(pretrained, robustness)	(pretrained)	57.900	80.706
ResNet50 random L_2-norm ($\epsilon = 3$)	0.1	256	76.600	93.136
ResNet50 L_∞-norm ($\epsilon = 4/255$)	(pretrained, robustness)	(pretrained)	62.424	84.060
ResNet50 L_∞-norm ($\epsilon = 8/255$)	(pretrained, robustness)	(pretrained)	47.906	72.484
ResNet50 random L_∞-norm ($\epsilon = 8/255$)	0.1	256	73.062	91.366
ResNet101 Standard	(pretrained, pytorch)	(pretrained)	77.374	93.546
VGG-19 Standard	(pretrained, pytorch)	(pretrained)	72.376	90.876
CORnet-S Standard	(pretrained, cornet)	(pretrained)	73.020	91.116
ResNet50-BYOL	(pretrained, openselfsup) / 30 linear eval	(pretrained) / 256 linear eval	68.706	88.090
ResNet50-MOCO_V2	(pretrained, openselfsup) / 30 linear eval	(pretrained) / 256 linear eval	67.832	88.322
ResNet50-SIMCLR	(pretrained, openselfsup) / 30 linear eval	(pretrained / 256 linear eval	59.204	81.304
HMAX	0.1 linear eval	256	6.101	15.070
VOneAlexNet	0.01	256	47.84	71.57
LowpassAlexNet	0.01	256	47.620	72.416
AlexNet (EarlyCheckpoint)	0.01	256	52.536	76.446
CLIP-ResNet50	(pretrained, clip) / zero-shot eval	(pretrained)	59.822	86.568
CLIP-ViT-B-32	(pretrained, clip) / zero-shot eval	(pretrained)	63.360	88.820
SWSL-ResNet50	(pretrained, swsl)	(pretrained)	81.180	95.986
SWSL-ResNeXt50	(pretrained, swsl)	(pretrained)	84.294	97.174
ViT_large_patch-16_224	(pretrained, timm)	(pretrained)	84.374	97.232
AlexNetGN IPCL Primary Model	(pretrained, ipcl) / cosine annealing (0.00003 to 0.03)	(pretrained) / 256 linear eval	40.288	63.622
AlexNetGN IPCL Supervised Comparison	(pretrained, ipcl)	(pretrained)	60.988	82.786
AlexNet Stylized ImageNet Trained	(pretrained, texture-vs-shape)	(pretrained)	40.012	64.178

ResNet50 Stylized ImageNet Trained	(pretrained, texture-vs-shape)	(pretrained)	60.184	82.616

1178 **Table 1:** Vision architecture training parameters and ImageNet1K accuracy.

1179

Audio training dataset

All auditory neural network models were trained on the Word-Speaker-Noise (WSN) dataset. This
dataset was first presented in (36) and was constructed from existing speech recognition and
environmental sound classification datasets. The dataset is approximately balanced to enable
performance of three tasks on the same training exemplar: (1) recognition of the word at the
center of a two second speech clip (2) recognition of the speaker and (3) recognition of
environmental sounds, that are superimposed with the speech clips (serving as "background
noise" for the speech tasks while enabling an environmental sound recognition task). Although
the dataset is constructed to enable all three tasks, the models described in this paper were only
trained to perform the word recognition task. The speech clips used in the dataset were excerpted
from the Wall Street Journal (104) (WSJ) and Spoken Wikipedia (105) (SWC).

1191

To choose speech clips, we screened WSJ, TIMIT (106) and a subset of articles from SWC for
appropriate audio clips (specifically, clips that contained a word at least four characters long and
that had one second of audio before the beginning of the word and after the end of the word, to
enable the temporal jittering augmentation described below). Some SWC articles were left out of
the screen due to a) potentially offensive content for human listening experiments; (29/1340 clips),
b) missing data; (35/1340 clips), or c) bad audio quality (for example, due to computer generated
voices of speakers reading the article or the talker changing mid-way through the clip; 33/1340
clips). Each segment was assigned the word class label of the word overlapping the segment
midpoint and a speaker class label determined by the speaker. With the goal of constructing a
dataset with speaker and word class labels that were approximately independent, we selected
words and speaker classes such that the exemplars from each class spanned at least 50 unique
cross-class labels (e.g., 50 unique speakers for each of the word classes). This exclusion fully
removed TIMIT from the training dataset. We then selected words and speaker classes that each
contained at least 200 unique utterances, and such that each class could contain a maximum of
25% of a single cross-class label (e.g., for a given word class, a maximum of 25% of utterances
could come from the same speaker). These exemplars were subsampled so that the maximum
number in any word or speaker class was less than 2000. The resulting training dataset contained
230,356 unique clips in 793 word classes and 432 speaker classes, with 40,650 unique clips in
the test set. Each word class had between 200 and 2000 unique exemplars. A "null" class was
used as a label when a background clip was presented without the added speech.

1212

The environmental soundtrack clips that were superimposed on the speech clips were a subset
of examples from the AudioSet dataset (a set of annotated YouTube video soundtracks) (107).
To minimize ambiguity for the two speech tasks, we removed any sounds under the "Speech" or
"Whispering" branch of the AudioSet ontology. Since a high proportion of AudioSet clips contain
music, we achieved a more balanced set by excluding any clips that were only labeled with the
root label of "Music", with no specific branch labels. We also removed silent clips by first discarding
everything tagged with a "Silence" label and then culling clips containing more than 10% zeros.
This screening resulted in a training set of 718,625 unique natural sound clips spanning 516
categories. Each AudioSet clip was a maximum of 10 seconds long, from which a 2-second
excerpt was randomly cropped during training (see below).

1223

Auditory model training

During training, the speech clips from the Word-Speaker-Noise dataset were randomly cropped
in time and superimposed on random crops of the AudioSet clips. Data augmentations during
training consisted of 1) randomly selecting a clip from AudioSet to pair with each labeled speech
clip, 2) randomly cropping 2 seconds of the AudioSet clip and 2 seconds of the speech clip,
cropped such that the labeled word remained in the center of the clip (due to training pipeline
technicalities, we used a pre-selected set of 5,810,600 paired speech and natural sound crops
which spanned 25 epochs of the full set of speech clips and 8 passes through the full set of
AudioSet clips), 3) superimposing the speech and the noise (i.e., the AudioSet crop) with a Signal-
to-Noise-Ratio (SNR) sampled from a uniform distribution between -10dB SNR and 10dB SNR,
augmented with additional samples of speech without an AudioSet background (i.e. with infinite
SNR, 2464 examples in each epoch) and samples of AudioSet without speech (i.e. with negative
infinite SNR, 2068 examples in each epoch) and 4) setting the root-mean-square (RMS)
amplitude of the resulting signal to 0.1. Evaluation performance is reported on one pass through
the speech test set (i.e., one crop from each of the 40,650 unique test set speech clips)
constructed with the same augmentations used during training (specifically, variable SNR and
temporal crops, paired with a separate set of AudioSet test clips, same random seed used to test
each model such that test sets were identical across models). Audio model training used data-
parallelization to split batches across multiple GPUs.
1243
1244 Each auditory model was trained for 150 epochs (where an epoch is defined as a full pass through
1245 the set of 230,356 speech training clips). The learning rate was decreased by a factor of 10 after
1246 every 50 epochs (see Table 2).
1247
Auditory model cochlear stage
The first stage of the auditory models produced a "cochleagram" – a time-frequency
representation of audio with frequency tuning that mimics the human ear, followed by a
compressive nonlinearity (47). This stage consisted of the following sequence of operations. First,
the 20kHz audio waveform passed through a bank of 211 bandpass filters with center frequencies
ranging from 50Hz to 10kHz. Filters were zero-phase with frequency response equal to the
positive portion of a single period of a cosine function, implemented via multiplication in the
frequency domain. Filter spacing was set by the Equivalent Rectangular Bandwidth (ERB$_N$) scale
(46). Filters perfectly tiled the spectrum such that the summed squared response across all
frequencies was flat (four low-pass and four high-pass filters were included in addition to the
bandpass filters in order to achieve this perfect tiling). Second, the envelope was extracted from
each filter subband using the magnitude of the analytic signal (via the Hilbert transform). Third,
the envelopes were raised to the power of 0.3 to simulate basilar membrane compression. Fourth,
the compressed envelopes were lowpass-filtered and downsampled to 200Hz (1d convolution
with a Kaiser-windowed Sinc filter of size 1001 in the time domain, applied with a stride of 100
and no zero padding, i.e. "valid" convolution), resulting in a final "cochleagram" representation of
211 frequency channels by 390 time points. The first stage of the neural network "backbone" of
the auditory models operated on this cochleagram representation. Cochleagram generation was
implemented in PyTorch such that the components were differentiable for metamer generation
and adversarial training. Cochleagram generation code will be released upon acceptance of the
paper.
1269
Spectemp model
The hand-engineered Spectro-Temporal filter model (Spectemp) was based on a previously
published model (56). Our implementation differed from the original model in specifying spectral
filters in cycles/ERB rather than cycles/octave (because our implementation operated on a
cochleagram generated with ERB-spaced filters). The model consisted of a linear filter bank tuned
to spectro-temporal modulations at different frequencies, spectral scales, and temporal rates. The

filtering was implemented via 2D convolution with zero padding in frequency (211 samples) and
time (800 samples). Spectro-temporal filters were constructed with spectral modulation center
frequencies of [0.0625, 0.125, 0.25, 0.5, 1, 2] cycles/ERB and temporal modulation center
frequencies of [0.5, 1, 2, 4, 8, 16, 32, 64] Hz, including both upward and downward frequency
modulations (resulting in 96 filters). An additional 6 purely spectral and 8 purely temporal
modulation filters were included for a total of 110 modulation filters. This filterbank operated on
the cochleagram representation (yielding the 'filtered_signal' stage in Figure 4d-f). We squared
the output of each filter response at each time step ('power') and took the average across time
for each frequency channel ('average'), similar to previous studies (5, 57, 74). To be able to use
model classification judgments as part of the metamer generation optimization criteria (see
below), we trained a linear classifier after the average pooling layer (trained for 150 epochs of the
speech training set with a learning rate that started at 0.01 and decreased by a factor of 10 after
every 50 speech epochs, using the same data augmentations as for the neural networks).
Although performance on the word recognition task for the Spectemp model was low, it was
significantly above chance, and thus could be used to help verify the success of the metamer
generation optimization procedure.
1292
Adversarial training – auditory models – waveform perturbations
CochResNet50 and CochCNN9 were adversarially trained with perturbations in the waveform
domain. We also included a control training condition in which random perturbations were added
to the waveform. For both adversarial and random waveform perturbations, after the perturbation
was added, the audio signal was clipped to fall between -1 and 1. As with the adversarially trained
vision models, all adversarial examples were untargeted. The L_2-norm ($\epsilon = 0.5$ and $\epsilon = 1.0$)
model adversarial examples were generated with a step size of 0.25 and 0.5, respectively, and 5
attack steps. L_∞-norm ($\epsilon = 0.002$) model adversarial examples in the waveform space were
generated with a step size of 0.001 and 5 attack steps. For random perturbation L_2-norm models
(both CochResNet50 and CochCNN9), a random sample on the L_2 ball with width $\epsilon = 1.0$ was
selected and added to the waveform, independently for each training example and dataset epoch.
Similarly, for random perturbation L_∞-norm models, a random sample on the corners of the L_∞ ball
was selected by randomly choosing a value of ±0.002 to add to each image pixel, chosen
independently for each training example and dataset epoch.
1307
1308 We estimated the SNR_{dB} for the perturbations of the waveform using:

1309
$$\text{SNR}_{dB} = 20 \log_{10} \frac{||x||}{||\xi||}$$

where x is the input waveform and ξ is the adversarial perturbation. As described above, the input
waveforms, x, to the model were RMS normalized to 0.1, and thus $||x|| = 0.1 * \sqrt{n}$, where n is
the number of samples in the waveform (40,000). For L_2-norm perturbations to the waveform, the
norm of the perturbation is just the ϵ value, and so $\epsilon = 0.5$ and $\epsilon = 1.0$ correspond to $||\xi|| = $
0.5 and $||\xi|| = 1$, resulting in SNR_{dB} values of 32.04 and 26.02, respectively. For L_∞-norm
perturbations, the worst case (lowest) SNR_{dB} is achieved by a perturbation that maximally
changes every input value. Thus, an L_∞ perturbation with $\epsilon = 0.002$ has $||\xi|| = \sqrt{\sum_{n=1}^{40,000}(0.002^2)}$,
corresponding to a SNR_{dB} value of 33.98. These SNR_{dB} values do not guarantee that the
perturbations were always fully inaudible to humans, but they confirm that the perturbations are
relatively minor and unlikely to be salient to a human listener.
1320
Adversarial training – auditory models – cochleagram perturbations
CochResNet50 and CochCNN9 were adversarially trained with perturbations in the cochleagram
domain. We also included a control training condition in which random perturbations were added

to the cochleagram. Adversarial or random perturbations were added to the output of the
cochleagram stage, after which the signal was passed through a ReLU so that no negative values
were fed into the neural network backbone. All adversarial examples were untargeted. The L_2-
norm ($\epsilon = 0.5$ and $\epsilon = 1.0$) model adversarial examples were generated with a step size of 0.25
and 0.5 respectively, and 5 attack steps. For random perturbation L_2-norm models (both
CochResNet50 and CochCNN9), a random sample on the L_2 ball with width $\epsilon = 1.0$ was selected,
independently for each training example and dataset epoch.

1331

1332   We estimated the $\mathrm{SNR_{dB}}$ of the cochleagram perturbations using the average cochleagram from
1333   the test dataset, whose L_2-norm was 40.65. Using this value with the $\mathrm{SNR_{dB}}$ equation yielded
1334   estimates of 38.20 and 32.18 dB for cochleagram perturbation models trained with $\epsilon = 0.5$
1335   and $\epsilon = 1.0$, respectively. We again cannot guarantee that the perturbations are inaudible to a
1336   human, but they are fairly low in amplitude and thus unlikely to be salient.

1337

Adversarial evaluation – auditory models
As in visual adversarial evaluation, the adversarial vulnerability of auditory models was evaluated
with untargeted white-box adversarial attacks. Attacks were computed with *L_1, L_2, and L_∞*
maximum perturbation sizes (ε) added to the waveform, with 64 gradient steps each with size ε/4
(pilot experiments and previous results (68) suggested that this step size and number of steps
were sufficient to attack most auditory models). We randomly chose audio samples from the WSN
evaluation dataset to use for adversarial evaluation, including the evaluation augmentations
described above (additive background noise augmentation with SNR randomly chosen between
-10 to 10 dB SNR, and RMS normalization to 0.1). Five different subsets of 1024 stimuli were
drawn to compute error bars.

1348

Model	Learning Rate (at Start)	Batch Size	Accuracy Top 1	Accuracy Top 5
CochCNN9 Standard	0.01	128	66.672	83.129
CochCNN9 waveform L_2-norm ($\epsilon = 1$)	0.01	128	48.091	67.240
CochCNN9 random waveform L_2-norm ($\epsilon = 1$)	0.01	128	65.710	82.376
CochCNN9 waveform L_∞-norm ($\epsilon = 0.002$)	0.01	128	60.440	78.278
CochCNN9 random waveform L_∞-norm ($\epsilon = 0.002$)	0.01	128	66.283	82.952
CochCNN9 cochleagram L_2-norm ($\epsilon = 1$)	0.01	128	48.002	66.089
CochCNN9 cochleagram L_2-norm ($\epsilon = 0.5$)	0.01	128	57.198	75.001
CochCNN9 random cochleagram L_2-norm ($\epsilon = 1$)	0.01	128	66.706	83.087
CochResNet50 Standard	0.1	256	86.797	95.360
CochResNet50 waveform L_2-norm ($\epsilon = 0.5$)	0.1	256	78.130	90.536
CochResNet50 waveform L_2-norm ($\epsilon = 1$)	0.1	256	70.546	85.474
CochResNet50 random waveform L_2-norm ($\epsilon = 1$)	0.1	256	85.916	94.871
CochResNet50 waveform L_∞-norm ($\epsilon = 0.002$)	0.1	256	83.491	93.658
CochResNet50 random waveform L_∞-norm ($\epsilon = 0.002$)	0.1	256	86.367	95.090
CochResNet50 cochleagram L_2-norm ($\epsilon = 1$)	0.1	256	71.392	85.149
CochResNet50 cochleagram L_2-norm ($\epsilon = 0.5$)	0.1	256	80.435	91.444
CochResNet50 random cochleagram L_2-norm ($\epsilon = 1$)	0.1	256	86.556	95.144
Spectemp (linear eval)	0.01 (linear eval)	128 (linear eval)	5.743	13.780

1349   **Table 2:** Auditory model architecture training parameters and word classification accuracy.

1350
1351 ***Metamer generation***
1352 *Optimization of metamers*
1353 Gradient descent was performed to minimize the normalized squared error between all activations
1354 at a particular model stage (for instance, each *x, y,* and *channel* value from the output of a
1355 convolutional layer) for the model metamer and the corresponding activations for a natural signal:

1356
$$\frac{||A - A'||}{||A||}$$

where *A* represents the activations from the natural signal and *A'* represents the activations from
the model metamer. The weights of the model remained fixed during the optimization.
Optimization was performed with gradient descent on the input signal, which was otherwise
unconstrained. Each step of gradient descent was constrained to have a maximum L_2 norm of η,
where η was initialized at 1 and was dropped by a factor of 0.5 after every 3000 iterations.
Optimization was run for a total of 24000 steps for each generated metamer. For all vision models
other than HMAX, the input signal was initialized as a sample from a normal distribution with
standard deviation of 0.05 and a mean of 0.5 (natural inputs to the models were scaled between
0-1). The size of the input stimuli, range of pixel values, and normalization parameters were
matched to the test data for the model. For all auditory models other than the spectrotemporal
model, the input signal was initialized from a random normal distribution with standard deviation
of 10^{-7} and a mean of zero. The perturbation *s* was initialized to 0. Normalization that occurred
after data augmentation in the visual models (subtracting channel means and dividing by channel
standard deviations) was included as a model component during metamer generation (i.e.,
gradients from these operations contributed to the metamer optimization along with all other
operations in the model).
1373
The two hand-engineered models (HMAX and the Spectemp model) had different initialization
settings. For the HMAX model, whose inputs were scaled to fall between 0-255, metamers were
initialized with a random normal distribution with a mean of 127.5 and standard deviation of 10.
For the Spectemp model, metamers were initialized with a random normal distribution with a mean
of zero and standard deviation of 10^{-5}. Empirically, we found that both of these models contained
stages that were difficult to optimize with the same strategy used for the neural networks. For both
models, we maintained the learning rate schedule of 24000 total optimization steps with learning
rate drops of 0.5 after every 3000 iterations (initialized at a learning rate of 1). However, in both
cases we found that optimization was aided by selectively optimizing for subsets of the units
(channels) in the early iterations of the optimization process. For the HMAX model, the subsets
that were chosen depended on the model stage. For the S1 stage, we randomly choose
activations from a single Gabor filter channel to include in the optimization. For the C1 stage, we
randomly selected a single scale. And for the S2 and C2 stages we randomly chose a single patch
size. The random choice of subset was changed after every 50 gradient steps. This subset-based
optimization strategy was used for the first 2000 iterations at each learning rate value. All units
were then included for the remaining 1000 iterations for that learning rate value.
1390
For the Spectemp model, we observed that the higher frequency modulation channels were
hardest to optimize. We set up a coarse-to-fine optimization strategy by initially only including the
lowest frequency spectral and temporal modulation filters in the loss function, and adding in the
filters with the next lowest modulation frequencies after every 400 optimization steps (with 7 total
sets of filters defined by center frequencies in both temporal and spectral modulation, and the
remaining 200/3000 steps continuing to include all of the filters from the optimization). The
temporal modulation cutoffs for each of the 7 sets were [0, 0.5, 1, 2, 4, 8, 16] Hz and the spectral
modulation cutoffs were [0, 0.0625, 0.125, 0.25, 0.5, 1, 2] cycles/ERB; a filter was included in the

n^{th} set if it had either a temporal or spectral scale that was equal to or less than the n^{th} temporal
or spectral cutoff, respectively. This strategy was repeated for each learning rate.

1401

Criteria for optimization success
Because metamers are derived via a gradient descent procedure, the activations that they
produce approach those of the natural signal used to generate them, but never exactly match. It
was thus important to define criteria by which the optimization would be considered sufficiently
successful for the result to be considered a model metamer and included in the behavioral
experiments.

1408

The first criterion was that the models had to produce the same class label for the model metamer
and natural signal. For visual models, the model metamer had to result in the same 16-way
classification label as the natural signal to which it was matched. For the auditory models, the
model metamer had to result in the same word label (out of 794 possible labels, including "null")
as the natural speech signal to which it was matched. For models that did not have a classifier
stage (the self-supervised models, HMAX, and the spectrotemporal filter model), we trained a
classifier as described above for this purpose. The classifier was included to be conservative, but
in practice could be omitted in future work, as very few stimuli pass the matching fidelity criterion
but not the classifier criterion.

1418

1419   The second criterion was that the activations for the model metamer had to be matched to those
1420   for the natural signal better than would be expected by chance. We measured the fidelity of the
1421   match between the activations for the natural stimulus and its model metamer at the matched
1422   model stage using three different metrics: Spearman ρ, Pearson R^2, and the Signal-To-Noise
1423   Ratio:

1424
$$\mathrm{SNR_{dB}} \;=\; 10 \log_{10} \frac{\sum (x^2)}{\sum ((x-y)^2)}$$

where *x* is the activations for the original sound when comparing metamers, or for a randomly
selected sound for the null distribution and *y* is activations for the comparison sound (the model
metamer or another randomly selected sound). We then ensured that for each of the three
measures, the value for the model metamer fell outside of a null distribution measured between
1,000,000 randomly chosen image or audio pairs from the training dataset. Metamers that did not
pass the null distribution test for any of the Spearman ρ, Pearson R^2, or Signal-To-Noise Ratio
measured at the stage used for the optimization were excluded from the set of experimental
stimuli. The only exception to this was the HMAX model, for which we only used the Signal-To-
Noise Ratio for the matching criteria (we found empirically that after the S2 stage of the HMAX
model, activations from pairs of random images became strongly correlated due to the different
offsets and scales in the natural image patch set, such that the correlation measures were not
diagnostic of the match fidelity).

1437

Handling gradients through the ReLU operation
Many neural networks use the ReLU nonlinearity, which yields a partial derivative of zero if the
input is negative. We found empirically that it was difficult to match ReLU layers due to the
initialization producing many activations of zero. To improve the optimization when generating a
metamer for activations immediately following a ReLU, we modified the derivative of the metamer
generation layer ReLU to be 1 for all input values, including values below zero (36). ReLU layers
that were not the metamer generation layer behaved normally, with a gradient of 0 for input values
below zero.

1446

Metamer generation with regularization

To investigate the effects of regularization on metamer recognizability, in one experiment we
generated metamers with additional constraints on the optimization procedure. We followed the
procedures of an earlier paper by Mahendran and Vedaldi (64). Two regularization terms were
included: (1) a total variation (TV) regularizer, and (2) an α-norm regularizer.

The resulting objective function minimized to generate metamers was:

1455
$$\frac{||A - A'||}{||A'||} + \lambda_\alpha R_\alpha(x) + \lambda_{TV} R_{TV}(x)$$

1457   using the 6-norm for the alpha-norm regularizer:
1458
$$R_\alpha(x) = \left|\left|x - \bar{x}\right|\right|_6$$
1459   and using the TV regularizer:
1460
$$R_{TV}(x) = \sum_{i,j} \left(\left((x - \bar{x})_{i,j+1} - (x - \bar{x})_{i,j}\right)^2 + \left((x - \bar{x})_{i+1,j} - (x - \bar{x})_{i,j}\right)^2\right)$$

where A are the activations evoked by the natural signal at the generation layer, A' are the
activations evoked by the model metamer at the generation layer, λ_α and λ_{TV} are scaling
coefficients for the regularizers, and $\bar{x}$ is the mean of the input signal x (x is normalized according
to the typical normalization for the model, ie subtracting the dataset mean and dividing by the
dataset standard deviation for each channel).

For the TV regularizer we generated metamers for 3 different coefficient values with
λ_{TV_1}=0.000005, λ_{TV_2}=10λ_{TV_1}, and λ_{TV_3}=100 λ_{TV_1}. As was also observed by Mahendran and
Vedaldi (64), we found that larger TV regularizers impaired optimization at early model stages,
with resulting stimuli often not passing our metamer optimization success criteria (for instance,
only 2/400 metamers generated from relu_0 of AlexNet passed this criteria for the largest
regularizer coefficient value). Thus, for the behavioral experiments that we ran, we chose
separate coefficient values for each model stage. Specifically, in AlexNet we used λ_{TV_1} for relu_0,
and relu_1, λ_{TV_2} for relu_2 and relu_3 and λ_{TV_3} for relu_4, fc_0, fc_1, and final (this is exactly
what was done in (64) except that the lambda values are different due to differences in how the
input is normalized, 0-255 in (64) compared to 0-1 in our models).

For the α-norm regularizer, we followed the methods used in (64), with α=6, and using a single
coefficient of λ_α =0.005 for all stages. This coefficient was chosen based on the logic proposed
in (64) for the starting value, with a small sweep around the values for a small number of examples
(10x up and 10x down), in which we subjectively judged which value produced the largest visual
recognizability benefit.

We also observed that when these regularizers were used, the default step sizes (initial learning
rate $\eta = 1$) used in our metamer generation method resulted in stimuli that looked qualitatively
more "gray" than expected, i.e. stayed close to the mean. Thus, to maximize the chances of
seeing a benefit from the regularization, in a separate condition we increased the initial step size
for metamer generation to be 16x the default value (initial $\eta = 16$).

We note that regularization typically interferes with the generation of metamers. We found
empirically that there was a tradeoff between satisfying the goal of matching the metamer
activations and of minimizing the regularization term. Imposing the regularization generally
resulted in worse metamer optimization. As described above, it was necessary to hand-tune the

regularization weights to obtain something that met our convergence criteria, but even when these
criteria were met, metamers generated with regularization tended to have worse activation
matches than metamers generated without regularization. This observation is consistent with the
idea that there is not an easy fix to the discrepancies revealed by metamers that simply involves
adding an additional term to the optimization. And in some domains (such as audio) it is not
obvious what to use for a regularizer. While the use of additional criteria to encourage the
optimization to stay close to the manifold of "natural" examples is an interesting direction to
explore further (and likely has useful applications), we emphasize that it is at odds with the goal
of testing whether a model on its own replicates the properties of a biological sensory system.
1504
1505
Online behavioral experiments
All behavioral experiments presented in the main text were run on Amazon Mechanical Turk. To
increase data quality, Amazon Turk qualifications were set to relatively stringent levels: the "HIT
Approval Rate for all Requesters' HITs" had to be at least 97% and the "Number of HITs
Approved" had to exceed 1000. Example code to run the online experiments is available at
https://github.com/jenellefeather/model_metamers_pytorch. All experiments with human
participants (both online and in-lab) were approved by the Committee On the Use of Humans as
Experimental Subjects at the Massachusetts Institute of Technology and were conducted with the
informed consent of the participants.
1515
Stimuli - image experiments
Each stimulus belonged to one of the 16 entry-level MS COCO (Microsoft Common Objects in
Context) categories. We used a mapping from these 16 categories to the corresponding
ImageNet1K categories (where multiple ImageNet1K categories can map onto a single MS COCO
category), used in a previous publication (18). For each of the 16 categories, we selected 25
examples from the ImageNet1K validation dataset for a total of 400 natural images that were used
to generate stimuli. A square center crop was taken for each ImageNet1K image (with the smallest
dimension of the image determining the size) and the square image was rescaled to the necessary
input dimensions for each ImageNet1K trained model. Metamers were generated for each of the
400 images to use for the behavioral experiments.
1526
Stimuli - auditory experiments
A set of two-second speech audio excerpts with no background noise was used to generate
stimuli. These clips were randomly chosen from the test set of the Word-Speaker-Noise dataset
described above, constrained such that only the WSJ corpus was used. We further ensured that
the clips were taken from unique sources within WSJ, and that the sounds were cropped to the
middle two seconds of the training set clip such that the labeled word was centered at the one-
second mark. To reduce ambiguity about the clip onset and offset (which were helpful in judging
whether a word was centered on the clip), we also screened the chosen clips to ensure that the
beginning 0.25s or end 0.25s of the clip was no more than -20dB quieter than the full clip. 400
clips were chosen subject to these constraints and such that each clip contained a different
labeled word. Metamers were generated for each of the 400 clips to use for the behavioral
experiments.
1539
Image behavioral experiment
We created a visual experiment in JavaScript similar to that used in a previous publication (18).
Participants were tasked with classifying an image into one of 16 presented categories (airplane,
bear, bicycle, bird, boat, bottle, car, cat, chair, clock, dog, elephant, keyboard, knife, oven, truck).
Each category had an associated image icon that participants chose from during the experiment.
Each trial began with a fixation cross at the center of the screen for 300ms, followed by a natural

image or a model metamer presented at the center of the screen for 300ms, followed by a pink noise mask presented for 300ms, followed by a 4x4 grid containing all 16 icons. Participants selected an image category by clicking on the corresponding icon. To minimize effects of internet disruptions, we ensured that the image was loaded into the browser cache before the trial began. We note that the precise timing of the image presentation for web experiments via JavaScript is less controlled compared to in-lab experiments, but any variation in timing should be similar across conditions and should average out over trials. To assess whether any timing variation in the online experiment set up might have affected overall performance, we compared recognition performance on natural images to that measured during in-lab pilot experiments (with the same task but different image examples) reported in an earlier conference paper (36). The average online performance across all natural images was on par or higher than that measured in-lab (in-lab proportion correct = 0.888 ± 0.0240) for all experiments.

The experimental session began with 16 practice trials to introduce participants to the task. There was one trial for each category, each presenting a natural image pulled from the ImageNet1K training set. Participants received feedback for these first 16 trials which included their answer and the correct response. Participants then began a 12-trial demo experiment which contained some natural images and some model metamers generated from the ImageNet1K training set. The goal of this demo experiment was two-fold – first, to introduce participants to the types of stimuli they would see in the main experiment and second, to be used as a screening criterion to remove participants who were distracted, misunderstood the task instructions, had browser incompatibilities, or were otherwise unable to complete the task. Participants were only allowed to start the main experiment if they correctly answered 7/12 correct on the demo experiment, which was the minimum that were correctly answered for these same demo stimuli by 16 in-lab participants in a pilot experiment (36). 341/417 participants passed the demo experiment and chose to move onto the main experiment.

There were 6 different main image experiments, each including a set of conditions (model stages) to be compared. The stimuli for each main experiment were generated from a set of 400 natural images. Participants only saw one natural image or metamer for each of the 400 images in the behavioral stimulus set. Participants additionally completed 16 catch trials. These catch trials each consisted of an image that exactly matched the icon for one of the classes. Participant data was only included in the analysis if the participant got 15/16 of these catch trials correct (270/341 participants were included). Of these participants, 125 self-identified as female, 143 as male, and 2 did not report; mean age= 42.1, minimum age=20, maximum age=78. For all but the HMAX experiment, participants completed 416 trials – one for each of the 400 original images, plus the 16 catch trials. The 400 images were randomly assigned to the experiment conditions subject to the constraint that each condition had approximately the same number of trials. Specifically, each condition was initially allocated ceiling(400/N) trials, and then trials were removed at random until the total number of trials was equal to 400. In addition, if the stimulus for a condition did not pass the metamer optimization criteria (and thus, had to be omitted from the experiment), the natural image was substituted for it as a placeholder, and analyzed as an additional trial for the natural condition. These two constraints resulted in the number of trials per condition varying somewhat across participants (see table below). The resulting 416 total trials were then presented in random order across the conditions of the experiment. The HMAX experiment used only 200 of the original 400 images, for a total of 216 trials. The experiment was run with a smaller number of stimuli than other experiments because it contained only 6 conditions (metamer optimization was run for all 400 stimuli and a subset of 200 images was randomly chosen from the subset of the 400 images for which metamer optimization was successful in every stage of the model). HMAX metamers were black and white, while all metamers from all other models were in color.

1597 Model performance on this 16-way classification task was evaluated by measuring the predictions
1598 for the full 1000-way ImageNet classification task and finding the maximum probability for a label
1599 that was included in the 16-class dataset (231 classes).
1600

Experiment	Models	Total Number of conditions (Includes Natural Image)	Number of trials per condition per participant Average (min, max)	Number of Participants
Visual Experiment 1 (Standard Models)	CORnet-S VGG-19 ResNet50 ResNet101 AlexNet	37	10 (8, 14)	22
Visual Experiment 2 (Large-Scale Dataset Models)	ResNet50: CLIP ViT-B_32: CLIP ResNet50: SWSL ResNeXt101-32_8d: SWSL ViT_large_patch-16_224	39	10 (7,13)	21
Visual Experiment 3 (Self-Supervised ResNet50 Models)	ResNet50 Standard Supervised ResNet50 SimCLR ResNet50 MoCo_V2 ResNe50 BYOL	29	13 (11, 20)	21
Visual Experiment 4 (IPCL AlexNetGN)	IPCL Primary Model IPCL Supervised Comparison	19	21 (18, 24)	23
Visual Experiment 5 (Stylized-ImageNet Trained Models)	ResNet50 Standard ImageNet Trained ResNet50 Stylized ImageNet Trained AlexNet Standard ImageNet Trained AlexNet Stylized ImageNet Trained	31	12 (11, 16)	21
Visual Experiment 6 (HMAX)	HMAX	6	33 (31, 34)	20
Visual Experiment 7 (ResNet50 Adversarially Robust)	ResNet50 Standard Supervised ResNet50 L_2-norm ($\epsilon = 3$) ResNet50 random L_2-norm ($\epsilon = 3$) ResNet50 L_∞-norm ($\epsilon = 4/255$) ResNet50 L_∞-norm ($\epsilon = 8/255$) ResNet50 random L_∞-norm ($\epsilon = 8/255$)	43	9 (6, 13)	20

Visual Experiment 8 (AlexNet Adversarially Robust)	AlexNet Standard Supervised AlexNet L_2-norm ($\epsilon = 3$) AlexNet random L_2-norm ($\epsilon = 3$) AlexNet L_∞-norm ($\epsilon = 8/255$) AlexNet random L_∞-norm ($\epsilon = 8/255$)	41	9 (7, 14)	20
Visual Experiment 9 (AlexNet with Regularized Metamers)	AlexNet Standard with No Regularization AlexNet Standard with Regularization (Small Step) AlexNet Standard with Regularization (Large Step) AlexNet Adversarially Trained L_2-norm ($\epsilon = 3$)	33	12 (8, 18)	20
Visual Experiment 10 (Single Image Consistency Experiment)	Natural Image AlexNet random perturbation L_2-norm ($\epsilon = 3$) – ReLU2 AlexNet random perturbation L_2-norm ($\epsilon = 3$) – Final Stage AlexNet adversarial perturbation L_2-norm ($\epsilon = 3$) – Final Stage	4	100 (96, 103)	40
Visual Experiment 11 (Adversarially Trained Models Final Stage)	Adversarially Trained Models (see Methods Section XX)	27	14 (12, 17)	21
Visual Experiment 12 (Lowpass AlexNet and VOneAlexNet)	AlexNet Standard Supervised Lowpass AlexNet VOneAlexNet	25	16 (14, 20)	20

Table 3: Conditions and number of trials included in each visual experiment.

Auditory behavioral experiment

We developed an auditory experiment in JavaScript that was similar to an experiment used in earlier publications from our lab (5, 36). Each human participant listened to a two-second audio clip and had to choose one of 793 word-labels corresponding to the word in the middle of the clip (centered at the one-second mark of the clip). Each trial began with the participant hearing the audio clip and typing the word they thought they heard into a response box. As participants typed, words matching the letter string they were typing appeared below the response box to help participants identify words that were in the response list. Once a word was typed that matched one of the 793 responses, participants could move onto the next trial.

To increase data quality, participants first completed a short experiment (six trials) that screened for the use of headphones (108). If participants scored 5/6 or higher on this screen (224/377 participants), they moved onto a practice experiment consisting of 10 natural audio trials with feedback (drawn from the training set), designed to introduce the task. This was followed by a demo experiment of 12 trials without feedback. These 12 trials contained both natural audio and model metamers, using the same set of 12 stimuli as in a demo experiment used for earlier in-lab experiments (36). As with the visual demo experiment, the goal of the audio demo experiment was to introduce participants to the type of stimuli they would hear in the main experiment and to screen out poorly performing participants. A screening criteria was set at 5/12, which was the minimum for 16 in-lab participants in earlier work (36). 154/224 participants passed the demo experiment and chose to move onto the main experiment. We have repeatedly found that online auditory psychophysical experiments qualitatively and quantitatively reproduce in-lab results, provided that steps such as these are taken to help ensure good audio presentation quality and attentive participants (109–112). The average online performance on natural stimuli was comparable to in-lab performance reported in (36) on natural stimuli using the same task with different audio clips (in-lab proportion correct = 0.863 ± 0.0340).

There were 6 different main auditory experiments, each including a set of conditions (multiple models and multiple model stages) to be compared. The design of these experiments paralleled the image experiments. The stimuli for each main experiment were generated from the set of 400 natural speech behavioral stimuli described above. Participants only heard one natural speech or metamer stimulus for each of the 400 excerpts in the behavioral stimulus set. Participants additionally completed 16 catch trials. These catch trials each consisted of a single word corresponding to one of the classes. Participant data was only included in the analysis if the participant got 15/16 of these trials correct (this inclusion criterion removed 8/154 participants). As the auditory experiment was long, some participants chose to leave the experiment early and their data was excluded from analysis (23/154). An additional 3 participants were excluded due to self-reported hearing loss, for a total of 120 participants across all auditory experiments. Of these participants, 45 self-identified as female, 68 as male, and 7 chose not to report; mean age=39.0, minimum age=22, maximum age=77. For all but the Spectemp experiment, participants completed 416 trials – one for each of the 400 original excerpts, plus the 16 catch trials. The 400 excerpts were randomly assigned to the experiment conditions subject to the constraint that each condition had approximately the same number of trials. As in the visual experiments, each condition was initially allocated ceiling(400/N) trials, and then trials were removed at random until the total number of trials was equal to 400. If the model stage selected for an image produced a metamer that did not pass the metamer optimization criteria (and thus, was omitted from experiment stimuli), the natural audio was used instead, but was not included in the analysis. As in the visual experiments, these two constraints resulted in the number of trials per condition varying somewhat across participants (see Table 4). The resulting 416 total trials were then presented in random order across the conditions of the experiment. The Spectemp experiment used only 200 of the original 400 excerpts, for a total of 216 trials. This experiment was run with a smaller number of stimuli because it contained only 6 conditions (metamer optimization was run for all 400 stimuli and a subset of 200 was randomly chosen from the subset of the 400 original excerpts for which metamer optimization was successful in every stage of the model). We collected online data in batches until we reached the target number of participants for each experiment.

Experiment	Models	Total Number of conditions (Includes	Number of trials per condition per participant	Number of Participants

		Natural Audio)	Average (min, max)	
Auditory Experiment 1 (Standard Models)	CochResNet50 Standard CochCNN9 Standard	18	22 (18, 23)	20
Auditory Experiment 2 (Spectemp Model)	Spectemp Model	6	33 (30, 34)	20
Auditory Experiment 3 (CochResNet50 Waveform Adversarial Training)	CochResNet50 Standard Supervised CochResNet50 waveform L_2-norm ($\epsilon = 0.5$) CochResNet50 waveform L_2-norm ($\epsilon = 1$) CochResNet50 random waveform L_2-norm ($\epsilon = 1$) CochResNet50 waveform L_∞-norm ($\epsilon = 0.002$) CochResNet50 random waveform L_∞-norm ($\epsilon = 0.002$)	49	8 (5, 9)	20
Auditory Experiment 4 (CochCNN9 Waveform Adversarial Training)	CochCNN9 Standard Supervised CochCNN9 waveform L_2-norm ($\epsilon = 1$) CochCNN9 random waveform L_2-norm ($\epsilon = 1$) CochCNN9 waveform L_∞-norm ($\epsilon = 0.002$) CochCNN9 random waveform L_∞-norm ($\epsilon = 0.002$)	46	8 (6, 9)	20
Auditory Experiment 5 (CochResNet50 Cochleagram Adversarial Training)	CochResNet50 Standard Supervised CochResNet50 cochleagram L_2-norm ($\epsilon = 0.5$) CochResNet50 cochleagram L_2-norm ($\epsilon = 1$) CochResNet50 random cochleagram L_2-norm ($\epsilon = 1$)	41	9 (7, 10)	20

	CochResNet50 waveform L_2-norm ($\epsilon = 1$)			
Auditory Experiment 6 (CochCNN9 Cochleagram Adversarial Training)	CochCNN9 Standard Supervised CochCNN9 cochleagram L_2-norm ($\epsilon = 0.5$) CochCNN9 cochleagram L_2-norm ($\epsilon = 1$) CochCNN9 random cochleagram L_2-norm ($\epsilon = 1$) CochCNN9 waveform L_2-norm ($\epsilon = 1$)	46	8 (6, 9)	20

Table 4: Conditions and number of trials included in each auditory experiment.

Statistical tests – difference between human and model recognition accuracy
All human recognition experiments involving neural network models were analyzed by comparing human recognition of a generating model's metamers to the generating model's recognition of the same stimuli (its own metamers). Each human participant was run on a distinct set of model metamers; we presented each set to the generation model and measured its recognition performance for that set. Thus, if N human participants performed an experiment, we obtained N model recognition curves. We ran mixed model repeated measures ANOVAs with a within-group factor of metamer generation model stage and a between-group factor of observer (human or model observer), testing for both a main effect of observer and an interaction between observer and model stage. Data were non-normal due to a prevalence of values close to 1 or 0 depending on the condition, and so we evaluated statistical significance non-parametrically, using permutation tests in which we compared the observed F-statistic to that obtained after randomly permuting the data labels. To test for main effects, we permuted observer labels (model vs. human). To test for interactions of observer and model stage, we randomly permuted both the observer labels and the model stage labels, independently for each participant. In each case we used 10,000 random permutations and computed a p value by comparing the observed F-statistic to the null distribution of F-statistics from permuted data (i.e., the p value was one minus the rank of the observed F-statistic divided by the number of permutations).

Because the classical models did not themselves perform recognition judgments, rather than comparing human and model recognition as in the experiments involving neural network models, we instead tested for a main effect of model stage on human observer recognition. We performed a single-factor repeated measure ANOVA using a within-group factor of model stage, again evaluating statistical significance non-parametrically. We randomly permuted the model stage labels of the recognition accuracy data, independently for each participant (with 10,000 random permutations).

Statistical tests – difference between human recognition of metamers generated from different models
To compare human recognition of metamers generated from different models, we ran a repeated measures ANOVA with within-group factors of model stage and generating model. This type of comparison was only performed in cases where the generating models had the same architecture (so that the model stages were shared between models). We again evaluated statistical

significance non-parametrically, by comparing the observed F-statistic to a null distribution of F-
statistics from permuted data (10,000 random permutations). To test for a main effect of
generating model, we randomly permuting the generating model label, independently for each
participant. To test for an interaction between the generating model and model stage, we
permuted both the generating model label and the model stage label, independently for each
participant.
1701
Power analysis to determine sample sizes
We planned to run ANOVAs examining the interaction between human performance and model
performance, the interaction between model and stage, the interaction between standard models
and adversarially trained models, the interaction between different types of adversarial training,
and the interaction between standard supervised models and self-supervised models. To estimate
the number of participants necessary to be well powered for these analyses, we ran a pilot
experiment comparing the standard versus adversarially trained ResNet50 and CochResNet50
models, as this experiment included the largest number of conditions and we expected that the
differences between different types of adversarially trained models would be subtle, and would
put an upper bound on the sample sizes that would be needed across experiments.
1712
For the vision experiment, we ran 10 participants in a pilot experiment on Amazon Mechanical
Turk. The format of the pilot experiment was identical to that of the main experiments in this paper,
with the exception that we used a screening criteria of 8/12 correct for the pilot, rather than the
7/12 correct used for the main experiment. In this pilot experiment, the smallest effect size out of
those we anticipated analyzing in the main experiments was the comparison between the L_∞-
norm ($\epsilon = 8/256$) adversarially trained ResNet50 and the L_2-norm ($\epsilon = 3$) adversarially trained
Resnet50, with a partial eta squared value of 0.10 for the interaction. A power analysis was
performed with g*power (113); 18 participants were needed to have a 95% chance of seeing an
effect of this size at a p<.01 significance level. We thus set a target of 20 participants for each
main vision experiment.
1723
For the auditory experiments we ran 14 participants in a pilot experiment on Amazon Mechanical
Turk. The format of the pilot experiment was identical to that of the main experiments in this paper
with the exception that 8 of the 14 participants only received 6 original audio trials with feedback,
while in the main experiment 10 trials with feedback were used. As in the vision pilot experiment,
in this pilot the smallest effect size of interest was that for the comparison between the L_∞-norm
($\epsilon = 0.002$) adversarially trained CochResNet50 and the L_2-norm ($\epsilon = 1$) waveform adversarially
trained CochResNet50, yielding a partial eta squared value of 0.37 for the interaction. A power
analysis was performed with g*power; this indicated that 12 participants were needed to have a
95% change of seeing an effect for this size at a p<0.01 significance level. To match the image
experiments, we set a target of 20 participants for each main auditory experiment.
1734
Split-Half Reliability Analysis of Metamer Confusion Matrices (Supplementary Figure 2)
To assess whether human participants had consistent error patterns, particularly in metamer
conditions with poor recognizability, we compared confusion matrices from split halves of
participants. Each row of the confusion matrix (corresponding to a category label) was normalized
by the number of trials for that label. We then computed the Spearman correlation between the
confusion matrices from each split and compared this correlation to that obtained from confusion
matrices from permuted participant responses for the condition. We computed the correlation for
1000 random splits of participants (splitting the participants in half) and using a different
permutation of the response for each split. We counted the number of times that the difference

between the true split-half correlation and the shuffled correlation was less than or equal to 0
($n_{overlap}$), and the p-value was computed as:

1746
$$\frac{1 + n_{overlap}}{1000}$$

1747
1748   *Experiment testing effect of optimization algorithm (Supplementary Figure 3)*
An in-lab visual experiment was conducted to analyze whether differences in the optimization
strategy would have an effect on the human-recognizability of model metamers. This experiment
used one example visual model (a ResNet50 architecture). The optimization code and techniques
used for this small in-lab experiment differed from any of the experiments described in the main
text of this paper (they followed the methods used in our previous work (36)) but showed a similar
main effect of model stage for standard neural network models, where model metamers
generated from late stages of ImageNet1K task-optimized ResNet50 models were
unrecognizable to humans.

1757
1758   *Visual models included in the experiment*
1759   The models and metamer generation for this experiment were implemented in TensorFlow v1.12
1760   (114). For these experiments, we converted the ResNet50 model available via the PyTorch Model
1761   Zoo to TensorFlow using ONNX (version 1.6.0).

1762
The experiment was run together with an unrelated pilot experiment comparing four other models,
the data for which are not analyzed here. To reduce the number of conditions, the stage
corresponding to ResNet50 "layer1" was not included in metamer generation or in the experiment
(from ad-hoc visual inspection of a few examples, the model metamers for conv1_relu1, layer1,
and layer2 looked similar enough to the natural image that we expected ceiling performance for
all conditions).

1769
1770   *Model metamer optimization*
1771   Metamers were optimized using TensorFlow code based on that used for a previous conference
1772   paper (36). Unless otherwise noted the methods were identical to those used in the main
1773   experiments of this paper.

1774
We tested two different optimization schemes for generating model metamers. The first used
stochastic gradient descent with 15000 iterations, where each step of gradient descent was
constrained to have an L_2 norm of 1. The second method used the Adam optimizer (115), which
uses an adaptive estimation of first and second order moments of the gradient. Metamers were
generated with 15000 iterations of the Adam optimizer with an exponentially decaying learning
rate (initial learning rate of 0.001, 1000 decay steps, and a decay rate of 0.95).

1781
Stimuli – Image dataset for optimization strategy experiment
Similar to the other visual experiments in this paper, each stimulus belonged to one of the 16
entry-level MS COCO categories. For each of the 16 categories, we randomly selected 16
examples from the ImageNet1K training dataset using the list of images provided by (18) for a
total of 256 natural images that were used to generate stimuli. Metamers were generated for
each of the 256 images to use for the behavioral experiments.

1788
In-lab visual experiment
The experimental setup was the same as the experiment described for our main experiments (but
implemented in MATLAB Psychotoolbox rather than JavaScript), in which participants had to
classify an image into one of the 16 presented categories. Each trial began with a fixation cross
at the center of the screen for 300ms, followed by a natural image or a model metamer presented

at the center of the screen for 200ms, followed by a pink noise mask presented for 200ms,
followed by a 4x4 grid containing all 16 icons. Stimuli were presented on a 20" ACER LCD (backlit
LED) monitor with a spatial resolution of 1600x900 and a refresh rate of 60Hz. Stimuli spanned
256x256 pixels and were viewed at a distance of approximately 62 cm (set by the chair position,
which was fixed; participants were free to position themselves in the chair as was most
comfortable, which introduced minor variation in viewing distance).
1800
1801 Before the experiment, each participant was shown a printout of the 16 category images with
1802 labels and the experimenter pointed to and read each category. This was followed by a demo
1803 experiment with 12 trials without feedback (same stimuli as in the main experiments, but
1804 performance was not used to exclude participants).
1805
1806 Each participant saw 6 examples from each condition, chosen such that each natural image or
1807 metamer was from a unique image from the 256-image behavioral set. Ten participants completed
1808 the experiment.
1809
Human consistency of errors for individual stimuli (Supplementary Figure 7)
In the experiment to evaluate the consistency of errors for individual stimuli (Supplementary
Figure 7), we only included four conditions in order to collect enough data to analyze performance
on individual images: natural images, metamers from the ReLU2 and final stages for the random
perturbation trained AlexNet L_2-norm ($\epsilon = 1$) model, and metamers from the final stage of the
adversarial perturbation trained AlexNet L_2-norm ($\epsilon = 1$) model. The rationale for the inclusion of
these stages was that the ReLU2 stage of the Random perturbation AlexNet and the Final stage
of the Adversarial perturbation AlexNet had similarly recognizable metamers (Figure 4c), whereas
metamers from the Final stage of the Random perturbation AlexNet were recognized no better
than chance by humans.
1820
To first assess the reliability of the recognizability of individual stimuli (Supplementary Figure 7a),
we measured the Spearman correlation of the recognizability (proportion correct) of each stimulus
across splits of participants, separately for each of the four conditions. We averaged this
correlation over 1000 random splits of participants. P-values were computed non-parametrically
by shuffling the participant responses for each condition and each random split, and computing
the number of times the true average Spearman ρ was lower than the shuffled correlation value.
We only included images in the analysis that had at least 4 trials in each split of participants, and
when there were more than 4 trials in a split, we only included four of the trials, randomly selected,
in the average, to avoid having some images exert more influence on the result than others.
1830
Most and least recognizable images
To analyze the consistency of the "most" and "least" recognizable metamers in each condition
(Supplementary Figure 7b), we used one split of participants to select 50 images that had highest
recognition score and 50 images with lowest recognition score. We then measured the
recognizability of these images in the second split of participants, and assessed whether the
"most" recognizable images had a higher recognition score than the "least" recognizable images.
P-values for this comparison were computed by using 1000 splits of participants and measuring
the proportion of splits in which the difference between the two scores was greater than 0.
1839
To select examples of the most and least recognizable images (Supplementary Figure 7c&d) we
only included example stimuli with at least 8 responses for both the natural image condition and
the model metamer stage under consideration, and which had 100% correct responses on the
natural image condition. From this set we selected the "most" recognizable images (as those with

scores of 100% correct for the considered condition) and the "least" recognizable images (as
those with scores of 0% correct).
1846
Model-Brain Comparison Metrics for Visual Models
We utilized the Brain-Score (42) platform to obtain metrics of neural similarity in four visual cortical
areas of the macaque monkey brain: V1, V2, V4, and IT. For each model considered, we analyzed
only the stages that were included in our human metamer recognition experiments. We note that
some models may have had higher brain similarity scores had we analyzed all stages. Each of
these model stages was fit to a public data split for each visual region, with the best-fitting stage
for that region selected for further evaluation. The match of this model stage to brain data was
then evaluated on a separate set of evaluation data for that region. Evaluation data for V1
consisted of the average of 23 benchmarks: 22 distribution-based comparison benchmarks from
(116) and the V1 partial-least-squares regression (PLS) benchmark from (117). Evaluation data
for V2 consisted of the V2 PLS benchmark from (117). Evaluation data for V4 consisted of the
average of four benchmarks: the PLS V4 benchmark from (118), the PLS V4 benchmark from
(119), the PLS V4 benchmark from (120), and the PLS V4 benchmark from (121). Evaluation data
for IT consisted of the average of 4 benchmarks: the PLS IT benchmark from (118), the PLS IT
benchmark from (119), the PLS IT benchmark from (120), and the PLS IT benchmark from (121).
When comparing the metamer recognizability to the Brain-Score results, we used the human
recognition of metamers from the model stage selected as the best match for each visual region.
1864
1865 We used Spearman correlations to compare metamer recognizability to the Brain-Score results.
1866 We note that the analogous Pearson correlations were lower, and that none reached statistical
1867 significance. We report Spearman correlations on the grounds that the recognizability was
1868 bounded by 0 and 1, and to be conservative with respect to our conclusion that metamer
1869 recognizability is not explained by standard model-brain comparison metrics.
1870
We estimated the noise ceiling of the correlation between Brain-Score results and human
recognizability of model metamers as the geometric mean of the reliabilities of each quantity. To
estimate the reliability of the metamer recognizability, we split the participants for an experiment
in half and measured the recognizability of metamers for each model stage used to obtain the
Brain-Score results (i.e., the best-predicting stage for each model for the brain region under
consideration). We then calculated the Spearman correlation between the recognizability for the
two splits, and Spearman-Brown corrected to account for the 50% reduction in sample size from
the split. This procedure was repeated for 1000 random splits of participants. We then took the
mean across the 1000 splits as an estimate of the reliability. This estimated reliability was 0.917
for V1, 0.956 for V2, 0.924 for V4, and 0.97 for IT. As we did not have access to splits of the
neural data used for Brain-Score, we estimated the reliability of the Brain-Score results as the
Pearson correlation of the score for two sets of neural responses to the same images, Spearman-
Brown corrected, reported in (73). This estimated reliability was only available for IT (r=0.87), but
we assume that the reliability would be comparable for other visual areas.
1885
Model-Brain Comparison Metrics for Auditory Models
The auditory fMRI analysis closely followed that of a previous publication (5) using the fMRI
dataset collected in another previous publication (74).The key components of the dataset and
analysis methods are replicated here, but for additional details see (5, 74). The text from sections
"*fMRI data acquisition and preprocessing*" and "*Voxel and ROI selection"* is replicated from a
previous publication with minor edits (5).
1892
1893 *Natural sound stimuli*

The stimulus set was composed of 165 two-second natural sounds spanning eleven categories (instrumental music, music with vocals, English speech, foreign speech, non-speed vocal sounds, animal vocalization, human-non-vocal sound, animal non-vocal sound, nature sound, mechanical sound, or environment sound). The sounds were presented in a block design with five presentations of each two-second sound. To prevent sounds from being played at the same time as scanner noise, a single fMRI volume was collected following each sound presentation ("sparse scanning"). This resulted in a 17-second block. Blocks were grouped into 11 runs with 15 stimuli each and four blocks of silence. Silence blocks were the same duration as the stimulus blocks and were used to estimate the baseline response. Participants performed a sound-intensity discrimination task to increase attention. One sound in the block of five was presented 7dB lower than the other four (the quieter sound was never the first sound) and participants were instructed to press a button when they heard the quieter sound. Sounds were presented with MR-compatible earphones (Sensimetrics S14) at 75 dB SPL for the louder sounds and 68dB SPL for the quieter sounds.

fMRI data acquisition and preprocessing
MR data was collected on a 3T Siemens Trio scanner with a 32-channel head coil at the Athinoula A. Martinos Imaging Center of the McGovern Institute for Brain Research at MIT. Data was first published in (74), and was re-analyzed for this paper. Each functional volume consisted of fifteen slices oriented parallel to the superior temporal plane, covering the portion of the temporal lobe superior to and including the superior temporal sulcus. Repetition time (TR) was 3.4 s (acquisition time was only 1 s due to sparse scanning), echo time (TE) was 30 ms, and flip angle was 90 degrees. For each run, the five initial volumes were discarded to allow homogenization of the magnetic field. In-plane resolution was 2.1 x 2.1 mm (96 x 96 matrix), and slice thickness was 4 mm with a 10% gap, yielding a voxel size of 2.1 x 2.1 x 4.4 mm. iPAT was used to minimize acquisition time. T1-weighted anatomical images were collected in each subject (1mm isotropic voxels) for alignment and surface reconstruction.

Functional volumes were preprocessed using FSL and in-house MATLAB scripts. Volumes were corrected for motion and slice time. Volumes were skull-stripped, and voxel time courses were linearly detrended. Each run was aligned to the anatomical volume using FLIRT and BBRegister. These preprocessed functional volumes were then resampled to vertices on the reconstructed cortical surface computed via FreeSurfer, and were smoothed on the surface with a 3mm FWHM 2D Gaussian kernel to improve SNR. All analyses were done in this surface space, but for ease of discussion we refer to vertices as "voxels" in this paper. For each of the three scan sessions, we estimated the mean response of each voxel (in the surface space) to each stimulus block by averaging the response of the second through the fifth acquisitions after the onset of each block (the first acquisition was excluded to account for the hemodynamic lag). Pilot analyses showed similar response estimates from a more traditional GLM (74). These signal-averaged responses were converted to percent signal change (PSC) by subtracting and dividing by each voxel's response to the blocks of silence. These PSC values were then downsampled from the surface space to a 2mm isotropic grid on the FreeSurfer-flattened cortical sheet.

Voxel and ROI selection
We used the same voxel selection criterion as Norman-Haignere et al. (2015), selecting voxels with a consistent response to sounds from a large anatomical constraint region encompassing the superior temporal and posterior parietal cortex. Specifically, we used two criteria: (1) a significant response to sounds compared with silence (p < 0.001); and (2) a reliable response to the pattern of 165 sounds across scans. The reliability measure was as follows:

$$r = 1 - \frac{||v_{12} - proj_{v_3}v_{12}||^2}{||v_{12}||^2}$$

$$proj_{v_3}v_{12} = \left(\frac{v_3^T}{||v_3||^2}v_{12}\right)v_3$$

where v_{12} is the response of a single voxel to the 165 sounds averaged across the first two scans (a vector), and v_3 is that same voxel's response measured in the third. The numerator in the second term in the first equation is the magnitude of the residual left in v_{12} after projecting out the response shared with v_3. This "residual magnitude" is divided by its maximum possible value (the magnitude of v_{12}). The measure is bounded between 0 and 1, but differs from a correlation in assigning high values to voxels with a consistent response to the sound set, even if the response does not vary substantially across sounds. We found that using a more traditional correlation-based reliability measure excluded many voxels in primary auditory cortex because some of them exhibit only modest response variation across natural sounds. We included voxels with a value of this modified reliability measure of 0.3 or higher, which when combined with the sound responsive t-test yielded a total of 7694 voxels across the eight participants (mean number of voxels per subject: 961.75; range: 637-1221).

We localized four regions of interest (ROIs) in each participant, consisting of voxels selective for (1) frequency (i.e., tonotopy), (2) pitch, (3) speech, and (4) music. In each case we ran a "localizer" statistical test and selected the top 5% most significant individual voxels in each subject and hemisphere (including all voxels identified by the sound-responsive and reliability criteria described above). We excluded voxels that were identified in this way by more than one localizer. The frequency, pitch, and speech localizers required acquiring additional imaging data, and were collected either during extra time during the natural sound stimuli scan sessions or on additional sessions on different days. Scanning acquisition parameters were identical to those used to acquire the natural sounds data. Throughout this paper we refer to voxels chosen by these criteria as "selective," for ease and consistency. There were a total of 379 voxels in the Tonotopic ROI, 379 voxels in the pitch ROI, 393 voxels in the music ROI and 379 voxels in the speech ROI.

To identify frequency-selective voxels, we measured responses to pure tones in six different frequency ranges (center frequencies: 200, 400, 800, 1600, 3200, 6400 Hz) (122, 123). For each voxel, we ran a one-way ANOVA on its response to each of these six frequency ranges and selected voxels that were significantly modulated by pure tones (top 5% of all selected voxels in each subject, ranked by p values). Although there was no spatial contiguity constraint built into our selection method, in practice most selected voxels were contiguous and centered around Heschl's gyrus.

To identify pitch-selective voxels, we measured responses to harmonic tones and spectrally-matched noise (123). For each voxel we ran a one-tailed t-test evaluating whether the response to tones was greater than that to noise. We selected the top 5% of individual voxels in each subject that had the lowest p values for this contrast.

To identify speech-selective voxels, we measured responses to German speech and to temporally scrambled ("quilted") speech stimuli generated from the same German source recordings (124). We used foreign speech to identify responses to speech acoustical structure, independent of linguistic structure. Note that two of the participants had studied German in school and for one of these participants we used Russian utterances instead of German. The other subject was tested

1990 with German because the Russian stimuli were not available at the time of the scan. For each
1991 voxel we ran a one-tailed t-test evaluating whether responses were higher to intact speech than
1992 to statistically matched quilts. We selected the top 5% of all selected voxels in each subject.
1993
1994 To identify music-selective voxels, we used the music component derived by (74). We inferred
1995 the "voxel weights" for each voxel to all six of the components from its response to the 165
1996 sounds:

$$w = C'v$$

1998 where w contains the inferred voxel weights (a vector of length 6), C' is the Moore-Penrose
1999 pseudoinverse of the "response components" (a 6 by 165 matrix), and v is the measured
2000 response of a given voxel (vector of length 165). We assessed the significance of each voxel's
2001 music component weight via a permutation test. During each iteration, we shuffled all the
2002 component elements, recomputed this new matrix's pseudoinverse, and recomputed each voxel's
2003 weights via the matrix multiply above. We performed this procedure 10,000 times, and fit a
2004 Gaussian to each voxel's null distribution of music weights. We then calculated the likelihood of
2005 the empirically observed voxel weight from this null distribution, and took the top 5% of voxels
2006 with the lowest likelihood under this null distribution.
2007
2008 *Voxelwise encoding analysis*
2009 Each of the 165 sounds from the fMRI experiment was resampled to 20,000Hz (the sampling rate
2010 of the training dataset) and passed through each auditory model. We measured the model
2011 response at each model stage for each sound. To compare the model responses to the fMRI
2012 response we averaged over the time dimension for all units that had a temporal dimension (all
2013 model stages except fully connected layers).
2014
2015 In the CochCNN9 architecture, this resulted in the following number of regressors for each stage:
2016 cochleagram (211), relu0 (6818), relu1 (4608), relu2 (4608), relu3 (9216), relu4 (4608), avgpool
2017 (2560), relufc (4096), final (794). In the CochResNet50 architecture, this resulted in the following
2018 number of regressors for each stage: cochleagram (211), conv1_relu1 (6784), layer1 (13568),
2019 layer2 (13824), layer3 (14336), layer4 (14336), avgpool (2048), final (794).
2020
2021 We used the features sets extracted from model stages to predict the fMRI response to the natural
2022 sound stimuli. Each voxel's time-averaged responses were modeled as a linear combination of a
2023 stage's time-averaged unit responses. Ten random train-test splits (83/82) were taken from the
2024 165 sound dataset. For each split we estimated a linear mapping using L2-regularized ("ridge")
2025 linear regression using RidgeCV from the scikit learn library version 0.23.1 (125). Ridge
2026 regression places a zero-mean gaussian prior on the regression coefficients, corresponding to
2027 solving the regression problem given by:

$$w = (X^T X + n\lambda I)^{-1} X^T y$$

2029 where n is the number of stimuli used for estimation (here equal to 83), w is the d-length column
2030 vector the length of the regressors (number of extracted features for the model stage), y is an n-
2031 length column vector containing the voxels response to each sound (length n), X is a matrix
2032 containing the regressors (n stimuli by d regressors, the extracted features for each sound), I is
2033 the identity matrix, and λ is the ridge regression regularization parameter. The mean of each
2034 column was subtracted from the regressor matrix before fitting.
2035
2036 The best ridge regression parameter for each voxel was independently selected using leave-one-
2037 out cross validation across the 83 training sounds in each split sweeping over 81 logarithmically
2038 spaced values (each power of 10 between $10^{-40} - 10^{40}$). For each held-out sound in the training
2039 set, the mean squared error of the prediction was computed using regression weights from the
2040 other 82 training set sounds, for each of the regularization coefficients. The regularization

2041 parameter that minimized the mean squared error on the held-out sounds was used to fit a linear
2042 mapping between model responses to all 83 training set sounds and the voxel responses. This
2043 mapping was used to predict the voxel response to the held-out 82 test sounds and fitting fidelity
2044 was evaluated with the squared Pearson correlation (r^2) as a metric of explained variance of the
2045 predicted voxel response and the observed voxel response.

2046

2047 This measured explained variance was corrected for the effects of measurement noise by
2048 computing the reliability of the voxel responses and of the predicted voxel response. We use the
2049 correction for attenuation (126), which estimates the correlation between two variables
2050 independent of measurement noise, resulting in an unbiased estimator of the correlation
2051 coefficient that would be observed from noiseless data. The corrected variance explained is:

2052
$$r_{v,\hat{v}}^{2*} = \frac{r(v_{123}, \hat{v}_{123})^2}{r_v' r_{\hat{v}}'}$$

2053 where v_{123} is the voxel response to the 82 test sounds averaged across all three scans, $\hat{v}_{123}$ is
2054 the predicted response to the 82 test sounds using the 83 training sounds to learn the regression
2055 weights, r is a function that computes the Pearson correlation coefficient, r_v' is the correction for
2056 reliability of the voxel responses, and $r_{\hat{v}}'$ is the correction for reliability of the predicted voxel
2057 response. r_v' is computed as the median Spearman-Brown corrected Pearson correlation
2058 between the 3 pairs of scans (scan 0 with scan 1, scan 1 with scan 2, scan 0 with scan 2), where
2059 the Spearman-Brown correction accounts for increased reliability expected from tripling the
2060 amount of data (127). $r_{\hat{v}}'$ is similarly computed by using the training data each of the three pairs
2061 of scans to predict the test data from the same scan, and calculating the median Spearman-Brown
2062 corrected correlation for the predicted voxel responses. If voxels and/or predictions are very
2063 unreliable, this can lead to large corrected variance explained measures (128). We set a minimum
2064 value of 0.182 for r_v' (corresponding to the value at which the correlation of two 83-dimensional
2065 random variables reaches significance at a threshold of p<.05; 83 being the number of training
2066 data values) and a minimum value of 0.183 for $r_{\hat{v}}'$ (the analogous value for 82-dimensional random
2067 variables, corresponding to the number test data values).

2068

The above computation of corrected variance explained was computed for each voxel using each
stage response for each of 10 train/test splits of data. We took the median variance explained
across the 10 splits of data. To provide one summary metric across each of the ROIs (all auditory
voxels, tonotopic voxels, pitch voxels, music voxels, speech voxels) we chose the best stage for
each ROI using a hold-one-participant out analysis. (Figure 7c) A summary measure for each
participant and model stage was computed by taking the median across all voxels of the voxel-
wise corrected variance explained values within the ROI. Holding out one participant, we
averaged across the remaining participant values to find the stage with the highest variance
explained within the given ROI. We measured the corrected variance explained for this stage in
the held-out participant, recorded the stage that was used as the "best" model stage, and repeated
the procedure holding out one participant at a time. This cross validation avoids issues of non-
independence when selecting the best stage. We report the mean corrected variance explained
across the participants. Metamer recognition was measured from the model stage most frequently
chosen as the best predicting model stage across participants (in practice, nearly all participants
had the same "best" model stage). When plotting the variance explained for each model stage
(Figure 7d) we took the median variance explained across the 10 splits of data, and then took the
median across all participants.

2086

2087 *Statistical tests – fMRI predictions*
2088 One-sided paired sample t-tests were performed to test for a difference in the variance explained
2089 summary metrics between different models. Significance values were computed by constructing

2090   a null-distribution of t-statistics by randomly permuting the model assignment independently for
2091   each participant (10,000 permutations). The p-value is reported as one minus the rank of the
2092   observed t-statistic divided by the number of permutations. In cases where the maximum possible
2093   number of unique permutations was less than 10,000, we instead divided the rank by the
2094   maximum number of unique permutations
2095
Noise ceiling estimates for correlation between metamer recognizability and fMRI metrics
We estimated the noise ceiling of the correlation between auditory fMRI predictivity and human
recognizability of model metamers as the geometric mean of the reliabilities of each quantity. To
estimate the reliability of the metamer recognizability, we split the participants for an experiment
in half and measured the recognizability of metamers for the model stage that was most frequently
chosen (across all participants) as the best-predicting stage for the ROI under consideration (i.e.,
the stages used for Figure 7c). We then calculated the Spearman correlation between the
recognizability for the two splits, and Spearman-Brown corrected to account for the 50% reduction
in sample size from the split. This procedure was repeated for 1000 random splits of participants.
We then took the mean across the 1000 splits as an estimate of the reliability. This estimated
reliability of the metamer recognizability was 0.811 for the best predicting stage of all auditory
voxels, 0.829 for the best predicting stage of the tonotopic ROI, 0.819 for the best predicting stage
of the pitch ROI, 0.818 for the best predicting stage of the music ROI, and 0.801 for the best
predicting stage of the speech ROI. To estimate the reliability of the fMRI prediction metric, we
took two splits of the fMRI participants and calculated the mean variance explained for each model
using the stage for which recognizability was measured. We then computed the Spearman
correlation between the explained variance for the two splits and Spearman-Brown corrected the
result. We then repeated this procedure for 1000 random splits of the participants in the fMRI
study, and took the mean across the 1000 splits as the estimated reliability. This reliability of fMRI
predictions was 0.923 for all auditory voxels, 0.768 for the tonotopic ROI, 0.922 for the pitch ROI,
0.796 for the music ROI, and 0.756 for the speech ROI.
2117
Representational similarity analysis (Supplementary Figure 10)
To construct the model representational dissimilarity matrix (RDM) for a model stage, we
computed the dissimilarity (1 minus the Pearson correlation coefficient) between the model
activations evoked by each pair of the 165 sounds for which we had fMRI responses. Similarly,
to construct the fMRI RDM, we computed the dissimilarity in voxel responses (1 minus the
Pearson correlation coefficient) between all ROI voxel responses from a participant to each pair
of sounds. Before computing the RDMs from the fMRI or model responses, we z-scored the voxel
or unit responses. As a measure of fMRI and model similarity, we computed the Spearman
correlation coefficient between the fMRI RDM and the model RDM.
2127
To compute the RDM similarity for the model stage whose RDM best matched that of an ROI
(Supplementary Figure 10a), we first generated 10 randomly selected train/test splits of the 165
sound stimuli into 83 training sounds and 82 test sounds. For each split, we computed the RDMs
for each model stage and for each participant's fMRI data for the 83 training sounds. We then
chose the model stage that yielded the highest Spearman ρ measured between the model stage
RDM and the participant's fMRI RDM. Using this model stage, we measured the model and fMRI
RDMs from the test sounds and computed the Spearman ρ. We repeated this procedure ten
times, once each for 10 random train/test splits, and took the median Spearman ρ across the ten
splits. We performed this procedure for all participants and computed the mean Spearman ρ
across participants for each model. When comparing the RDM similarity from the best matching
stage to metamer recognizability, we measured metamer recognizability from the model stage
that was most frequently chosen as the best matching model stage across participants.

2140
The representational similarity analysis is limited by measurement noise in the fMRI data. As an
estimate of the upper bound for the RDM correlation that could be reasonably expected to be
achieved between a model RDM and a single participant's fMRI RDM, we calculated the
correlation between one participant's RDM and the average of all the other participant's RDM.
We held out one participant and averaged the RDMs across the remaining participants. The
RDMs were measured from the same 10 train/test splits of the 165 sounds described in the
previous paragraph, using the 82 test sounds for each split. We then calculated the Spearman ρ
between the RDM from the held-out participant and the average participant RDM. We took the
median Spearman ρ across the 10 splits of data to yield a single value for each participant. This
procedure was repeated holding out each participant, and the upper bound shown in
Supplementary Figure 10 is the mean across the measured value for each held out participant.
This corresponds to the "lower bound" of the noise ceiling used in prior work (13). We plotted this
upper bound on the results graphs rather than noise-correcting the human-model RDM correlation
to be consistent with prior modeling papers that have used this analysis (13).
2155
2156 ***Model recognition of metamers generated from other models***
2157 To measure the recognition of a model's metamers by other models, we took the generated image
2158 or audio that was used for the human behavioral experiments, provided it as input to a
2159 "recognition" model, and measured the 16 way image classification (for ImageNet1K models) or
2160 the 763-way word classification (for the auditory models).
2161
The plots in Figure 8b show the average recognition by other models of metamers generated from
a particular type of ResNet50 model. We used one "Standard" generation model (the standard
supervised ResNet50). This curve is the average across all other vision recognition models (as
shown in Figure 9a). The curve for self-supervised models shows results averaged across the
three self-supervised generation models (SimCLR, MoCo_V2, and BYOL); the curve for
adversarially trained models shows results averaged across the three adversarially trained
ResNet50 models (trained with L_2-norm ($\epsilon = 3$), L_∞-norm ($\epsilon = 4/255$), and L_∞-norm ($\epsilon = 8/255$)
perturbations, respectively). For these latter two curves, we first computed the average curve for
each recognition model across all three generation models, omitting the recognition model from
the average if it was the same as the generation model (in practice, this meant that there was one
fewer value included in the average for the recognition models that are part of the generation
model group). We then averaged across the curves for each recognition model. The error bars are
on the resulting curves are the SEM computed across the recognition models.
2175
Figure 8c was generated in an analogous fashion. We used one "Standard" generation model
(the standard supervised CochResNet50). The curve for the waveform adversarially trained
models shows results averaged across the three such CochResNet50 models (trained with L_2-
norm ($\epsilon = 0.5$), L_2-norm ($\epsilon = 1$), and L_∞-norm ($\epsilon = 0.002$) perturbations, respectively). The curve
for the cochleagram adversarially trained models shows results averaged across the two such
CochResNet50 models (trained with L_2-norm ($\epsilon = 0.5$), and L_2-norm ($\epsilon = 1$) perturbations,
respectively). The group averages and error bars were computed as in Figure 8b.
2183
Data availability statement
Human data (auditory and visual human recognition performance and summarized fMRI data),
and trained model checkpoints are available at
https://github.com/jenellefeather/model_metamers_pytorch. The same repository also includes
an interface to view/listen to the generated metamers used in the human recognition experiments.
The Word-Speaker-Noise training dataset is available from the authors upon request.

2190
Code availability statement
Code for generating metamers, training models, and running online experiments is available at https://github.com/jenellefeather/model_metamers_pytorch. Auditory front-end (cochleagram generation) code is available at https://github.com/jenellefeather/chcochleagram.

Acknowledgements
We thank Ray Gonzalez for help constructing the Word-Speaker-Noise dataset used for training. We also thank Ray Gonzalez and Alex Durango for help running in-lab experiments, Joel Dapello for guidance on the VOneNet models, and Martin Schrimpf for help with Brain-Score evaluations. We thank Andrew Francl and Mark Saddler for advice on model training and evaluation, Alex Kell and Sam Norman-Haignere for help with the fMRI data analysis, and Malinda McPherson for help with Amazon Turk experiment design and statistics decisions. This work was supported by NSF grant no. BCS-1634050 to J.H.M., National Institutes of Health grant no. R01DC017970 to J.H.M., a DOE CSGF fellowship under grant no. DE-FG02-97ER25308 to J.F., and a Friends of the McGovern Institute Fellowship to J.F.

References

2206

1.   D. H. Hubel, T. N. Wiesel, Receptive fields and functional architecture in two nonstriate
visual areas (18 and 19) of the cat. *J. Neurophysiol.* **28**, 229–289 (1965).

2.   D. J. Felleman, D. C. Van Essen, Distributed hierarchical processing in the primate
cerebral cortex. *Cereb. Cortex* **1**, 1–47 (1991).

3.   K. Fukushima, Neocognitron: a self organizing neural network model for a mechanism of
pattern recognition unaffected by shift in position. *Biol. Cybern.* **36**, 193–202 (1980).

4.   T. Serre, A. Oliva, T. Poggio, A feedforward architecture accounts for rapid categorization.
Proc. Natl. Acad. Sci. U. S. A. **104**, 6424–6429 (2007).

5.   A. J. E. Kell, D. L. K. Yamins, E. N. Shook, S. V. Norman-Haignere, J. H. McDermott, A
task-optimized neural network replicates human auditory behavior, predicts brain
responses, and reveals a cortical processing hierarchy. *Neuron* **98**, 630-644.e16 (2018).

6.   N. Kriegeskorte, Deep neural networks: A new framework for modeling biological vision
and brain information processing. *Annu. Rev. Vis. Sci.* **1**, 417–446 (2015).

7.   D. L. K. Yamins, J. J. DiCarlo, Using goal-driven deep learning models to understand
sensory cortex. *Nat. Neurosci.* **19**, 356–365 (2016).

8.   D. G. Barrett, A. S. Morcos, J. H. Macke, Analyzing biological and artificial neural
networks: challenges with opportunities for synergy? *Curr. Opin. Neurobiol.* **55**, 55–64
(2019).

9.   A. H. Marblestone, G. Wayne, K. P. Kording, Toward an integration of deep learning and
neuroscience. *Front. Comput. Neurosci.* **10**, 94 (2016).

10.   Y. Xu, M. Vaziri-Pashkam, Limits to visual representational correspondence between
convolutional neural networks and the human brain. *Nat. Commun.* **12**, 2065 (2021).

11.   B. M. Lake, T. D. Ullman, J. B. Tenenbaum, S. J. Gershman, Building machines that learn
and think like people. *Behav. Brain Sci.* **40**, e253 (2017).

12.   A. Tacchetti, L. Isik, T. A. Poggio, Invariant recognition shapes neural representations of
visual input. *Annu. Rev. Vis. Sci.* **4**, 403–422 (2018).

13.   S.-M. Khaligh-Razavi, N. Kriegeskorte, Deep supervised, but not unsupervised, models
may explain IT cortical representation. *PLoS Comput. Biol.* **10**, e1003915 (2014).

14.   I. Goodfellow, H. Lee, Q. Le, A. Saxe, A. Ng, Measuring Invariances in Deep Networks in
Advances in Neural Information Processing Systems, Y. Bengio, D. Schuurmans, J.
Lafferty, C. Williams, A. Culotta, Eds. (Curran Associates, Inc., 2009), pp. 646–654.

15.   J. J. DiCarlo, D. D. Cox, Untangling invariant object recognition. *Trends Cogn. Sci.* **11**,
333–341 (2007).

16.   M. Riesenhuber, T. Poggio, Hierarchical models of object recognition in cortex. *Nat.*
Neurosci. **2**, 1019–1025 (1999).

17.   N. C. Rust, J. J. Dicarlo, Selectivity and tolerance ("invariance") both increase as visual
information propagates from cortical area V4 to IT. *J. Neurosci.* **30**, 12978–12995 (2010).

18.   R. Geirhos, C. R. M. Temme, J. Rauber, Generalisation in humans and deep neural
networks. *Adv. Neural Inf. Process. Syst.* (2018).

19.   A. Berardino, J. Ballé, V. Laparra, E. P. Simoncelli, Eigen-Distortions of Hierarchical
Representations. *arXiv [cs.CV]* (2017).

20. H. Jang, D. McCormack, F. Tong, Noise-trained deep neural networks effectively predict
human vision and its neural responses to challenging images. *PLoS Biol.* **19**, e3001418
(2021).

21. R. Zhang, Making convolutional networks shift-invariant again. *arXiv [cs.CV]* (2019).

22. A. Azulay, Y. Weiss, Why do deep convolutional networks generalize so poorly to small
image transformations? *arXiv [cs.CV]* (2018).

23. A. Nguyen, J. Yosinski, J. Clune, Deep neural networks are easily fooled: High confidence
predictions for unrecognizable images in *2015 IEEE Conference on Computer Vision and*
Pattern Recognition (CVPR), (IEEE, 2015) https:/doi.org/10.1109/cvpr.2015.7298640.

24. C. Szegedy, *et al.*, Intriguing properties of neural networks in *2nd International Conference*
on Learning Representations, ICLR 2014, (2014) (February 9, 2022).

25. B. Biggio, *et al.*, Evasion Attacks against Machine Learning at Test Time in *Machine*
Learning and Knowledge Discovery in Databases, (Springer Berlin Heidelberg, 2013), pp.
387–402.

26. N. Carlini, D. Wagner, Audio Adversarial Examples: Targeted Attacks on Speech-to-Text
in *2018 IEEE Security and Privacy Workshops (SPW)*, (2018), pp. 1–7.

27. B. A. Wandell, *Foundations of vision* (Sinauer Associates, 1995).

28. G. Wyszecki, W. S. Stiles, *Color science* (Wiley New York, 1982).

29. B. Julesz, Visual Pattern Discrimination. *IEEE Trans. Inf. Theory* **8**, 84–92 (1962).

30. J. H. McDermott, M. Schemitsch, E. P. Simoncelli, Summary statistics in auditory
perception. *Nat. Neurosci.* **16**, 493–498 (2013).

31. C. M. Ziemba, E. P. Simoncelli, Opposing effects of selectivity and invariance in peripheral
vision. *Nat. Commun.* **12**, 4597 (2021).

32. J. M. Hillis, M. O. Ernst, M. S. Banks, M. S. Landy, Combining sensory information:
mandatory fusion within, but not between, senses. *Science* **298**, 1627–1630 (2002).

33. H. Sohn, M. Jazayeri, Validating model-based Bayesian integration using prior–cost
metamers. *PNAS* (2021) (March 20, 2022).

34. B. Balas, L. Nakano, R. Rosenholtz, A summary-statistic representation in peripheral
vision explains visual crowding. *J. Vis.* **9**, 13.1-18 (2009).

35. J. Freeman, E. P. Simoncelli, Metamers of the ventral stream. *Nat. Neurosci.* **14**, 1195–
1201 (2011).

36. J. Feather, A. Durango, R. Gonzalez, J. McDermott, Metamers of neural networks reveal
divergence from human perceptual systems in *Advances in Neural Information Processing*
Systems, (2019) (March 16, 2021).

37. J. Deng, *et al.*, ImageNet: A large-scale hierarchical image database in *2009 IEEE*
Conference on Computer Vision and Pattern Recognition, (IEEE, 2009)
https:/doi.org/10.1109/cvpr.2009.5206848.

38. M. Schrimpf, *et al.*, Brain-Score: Which Artificial Neural Network for Object Recognition is
most Brain-Like? *bioRxiv* (2018) https:/doi.org/10.1101/407007.

39. K. Simonyan, A. Zisserman, Very Deep Convolutional Networks for Large-Scale Image
Recognition. *arXiv [cs.CV]* (2014).

40.   K. He, X. Zhang, S. Ren, J. Sun, Identity mappings in deep residual networks. *arXiv*
2290   *[cs.CV]* (2016).

2291   41.   A. Krizhevsky, I. Sutskever, G. E. Hinton, ImageNet classification with deep convolutional
2292   neural networks in *Advances in Neural Information Processing Systems*, (2012), pp.
2293   1097–1105.

2294   42.   M. Schrimpf, *et al.*, Integrative benchmarking to advance neurally mechanistic models of
2295   human intelligence. *Neuron* **108**, 413–423 (2020).

2296   43.   A. Radford, *et al.*, Learning Transferable Visual Models From Natural Language
2297   Supervision in *Proceedings of the 38th International Conference on Machine Learning*,
2298   Proceedings of Machine Learning Research., M. Meila, T. Zhang, Eds. (PMLR, 18--24 Jul
2299   2021), pp. 8748–8763.

2300   44.   I. Z. Yalniz, H. Jégou, K. Chen, M. Paluri, D. Mahajan, Billion-scale semi-supervised
2301   learning for image classification. *arXiv [cs.CV]* (2019).

2302   45.   A. P. Steiner, *et al.*, How to train your ViT? Data, Augmentation, and Regularization in
2303   Vision Transformers. *Transactions on Machine Learning Research* (2022) (January 8,
2304   2023).

2305   46.   B. R. Glasberg, B. C. J. Moore, Derivation of auditory filter shapes from notched-noise
2306   data. *Hear. Res.* **47**, 103–138 (1990).

2307   47.   J. H. McDermott, E. P. Simoncelli, Sound texture perception via statistics of the auditory
2308   periphery: evidence from sound synthesis. *Neuron* **71**, 926–940 (2011).

2309   48.   G. W. Lindsay, Convolutional Neural Networks as a Model of the Visual System: Past,
2310   Present, and Future. *J. Cogn. Neurosci.*, 1–15 (2020).

2311   49.   T. Chen, S. Kornblith, M. Norouzi, G. Hinton, A Simple Framework for Contrastive
2312   Learning of Visual Representations in *Proceedings of the 37th International Conference
2313   on Machine Learning*, Proceedings of Machine Learning Research., H. D. Iii, A. Singh,
2314   Eds. (PMLR, 13--18 Jul 2020), pp. 1597–1607.

2315   50.   X. Chen, H. Fan, R. Girshick, K. He, Improved Baselines with Momentum Contrastive
2316   Learning. *arXiv [cs.CV]* (2020).

2317   51.   J.-B. Grill, *et al.*, Bootstrap your own latent: A new approach to self-supervised Learning.
2318   *arXiv [cs.LG]* (2020).

2319   52.   T. Konkle, G. A. Alvarez, A self-supervised domain-general learning framework for human
2320   ventral stream representation. *Nat. Commun.* **13**, 491 (2022).

2321   53.   R. Geirhos, *et al.*, ImageNet-trained CNNs are biased towards texture; increasing shape
2322   bias improves accuracy and robustness in *International Conference on Learning
2323   Representations*, (2019).

2324   54.   K. Hermann, T. Chen, S. Kornblith, The Origins and Prevalence of Texture Bias in
2325   Convolutional Neural Networks in *Advances in Neural Information Processing Systems*,
2326   H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, H. Lin, Eds. (Curran Associates, Inc.,
2327   2020), pp. 19000–19015.

2328   55.   J. J. D. Singer, K. Seeliger, T. C. Kietzmann, M. N. Hebart, From photos to sketches - how
2329   humans and deep neural networks process objects across different levels of visual
2330   abstraction. *J. Vis.* **22**, 4 (2022).

56.   T. Chi, P. Ru, S. A. Shamma, Multiresolution spectrotemporal analysis of complex sounds.
J. Acoust. Soc. Am. **118**, 887–906 (2005).

57.   R. Santoro, *et al.*, Encoding of natural sounds at multiple spectral and temporal resolutions
in the human auditory cortex. *PLoS Comput. Biol.* **10**, e1003412 (2014).

58.   S. V. Norman-Haignere, J. H. McDermott, Neural responses to natural and model-
matched stimuli reveal distinct computations in primary and nonprimary auditory cortex.
PLoS Biol. **16**, e2005127 (2018).

59.   I. Goodfellow, J. Shlens, C. Szegedy, Explaining and Harnessing Adversarial Examples
in *3rd International Conference on Learning Representations, ICLR 2015, San Diego, CA,*
USA, May 7-9, 2015, Conference Track Proceedings, Y. Bengio, Y. LeCun, Eds. (2015).

60.   A. Madry, A. Makelov, L. Schmidt, D. Tsipras, A. Vladu, Towards deep learning models
resistant to adversarial attacks. *arXiv [stat.ML]* (2017).

61.   A. Ilyas, *et al.*, Adversarial examples are not bugs, they are features. *arXiv [stat.ML]*
(2019).

62.   L. Engstrom, *et al.*, Adversarial robustness as a prior for learned representations. *arXiv*
[stat.ML] (2019).

63.   N. C. L. Kong, E. Margalit, J. L. Gardner, A. M. Norcia, Increasing neural network
robustness improves match to macaque V1 eigenspectrum, spatial frequency preference
and predictivity. *PLoS Comput. Biol.* **18**, e1009739 (2022).

64.   A. Mahendran, A. Vedaldi, Understanding deep image representations by inverting them
in *2015 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, (IEEE,
2015) https:/doi.org/10.1109/cvpr.2015.7299155.

65.   F. Croce, *et al.*, RobustBench: a standardized adversarial robustness benchmark in *Thirty-*
Fifth Conference on Neural Information Processing Systems Datasets and Benchmarks
Track, (2021).

66.   O. J. Hénaff, E. P. Simoncelli, Geodesics of learned representations in *4th International*
Conference on Learning Representations, ICLR 2016, San Juan, Puerto Rico, May 2-4,
2016, Conference Track Proceedings, Y. Bengio, Y. LeCun, Eds. (2016).

67.   J. Dapello, *et al.*, Simulating a primary visual cortex at the front of CNNs improves
robustness to image perturbations. *Adv. Neural Inf. Process. Syst.* **33**, 13073–13087
(2020).

68.   J. Dapello, *et al.*, Neural population geometry reveals the role of stochasticity in robust
perception. *Adv. Neural Inf. Process. Syst.* **34** (2021).

69.   S. Sabour, Y. Cao, F. Faghri, D. J. Fleet, Adversarial Manipulation of Deep
Representations in *4th International Conference on Learning Representations, ICLR*
2016, San Juan, Puerto Rico, May 2-4, 2016, Conference Track Proceedings, Y. Bengio,
Y. LeCun, Eds. (2016).

70.   D. Hendrycks, T. Dietterich, Benchmarking Neural Network Robustness to Common
Corruptions and Perturbations in *International Conference on Learning Representations*,
(2018).

71.   S. Dodge, L. Karam, A study and comparison of human and deep learning recognition
performance under visual distortions in *2017 26th International Conference on Computer*
Communication   and   Networks   (ICCCN),   (IEEE,   2017)
https:/doi.org/10.1109/icccn.2017.8038465.

72. R. Geirhos, *et al.*, Partial success in closing the gap between human and machine vision in *Advances in Neural Information Processing Systems*, 34., (2021).

73. J. Kubilius, *et al.*, Brain-Like Object Recognition with High-Performing Shallow Recurrent ANNs in *Advances in Neural Information Processing Systems*, (Curran Associates, Inc., 2019).

74. S. Norman-Haignere, N. G. Kanwisher, J. H. McDermott, Distinct cortical pathways for music and speech revealed by hypothesis-free voxel decomposition. *Neuron* **88**, 1281–1296 (2015).

75. G. Tuckute, J. Feather, D. Boebinger, J. H. McDermott, Many but not all deep neural network audio models capture brain responses and exhibit hierarchical region correspondence. *bioRxiv*, 2022.09.06.506680 (2022).

76. C. Olah, A. Mordvintsev, L. Schubert, Feature Visualization. *Distill* **2** (2017).

77. J. Yosinski, J. Clune, A. Nguyen, T. Fuchs, H. Lipson, Understanding neural networks through deep visualization. *arXiv [cs.CV]* (2015).

78. A. Shafahi, *et al.*, Poison Frogs! Targeted Clean-Label Poisoning Attacks on Neural Networks in *Advances in Neural Information Processing Systems*, (Curran Associates, Inc., 2018).

79. J.-H. Jacobsen, J. Behrmann, R. Zemel, M. Bethge, Excessive Invariance Causes Adversarial Vulnerability in *7th International Conference on Learning Representations, (ICLR)*, (2019).

80. J.-H. Jacobsen, J. Behrmannn, N. Carlini, F. Tramèr, N. Papernot, Exploiting excessive invariance caused by norm-bounded adversarial robustness. *arXiv [cs.LG]* (2019).

81. J. Mehrer, C. J. Spoerer, N. Kriegeskorte, T. C. Kietzmann, Individual differences among deep neural network models. *Nat. Commun.* **11**, 5725 (2020).

82. J. Portilla, E. P. Simoncelli, A Parametric Texture Model Based on Joint Statistics of Complex Wavelet Coefficients. *Int. J. Comput. Vis.* **40**, 49–70 (2000).

83. A. Deza, A. Jonnalagadda, M. Eckstein, Towards Metamerism via Foveated Style Transfer in *International Conference on Learning Representations*, (2019) (March 16, 2021).

84. T. S. Wallis, *et al.*, Image content is more important than Bouma's Law for scene metamers. *Elife* **8** (2019).

85. C. Zhuang, *et al.*, Unsupervised Neural Network Models of the Ventral Visual Stream. *Cold Spring Harbor Laboratory*, 2020.06.16.155556 (2020).

86. K. R. Storrs, B. L. Anderson, R. W. Fleming, Unsupervised learning predicts human perception and misperception of gloss. *Nat Hum Behav* **5**, 1402–1417 (2021).

87. R. Geirhos, *et al.*, On the surprising similarities between supervised and self-supervised models. *arXiv [cs.CV]* (2020).

88. R. McWalter, J. H. McDermott, Adaptive and Selective Time Averaging of Auditory Scenes. *Curr. Biol.* **28**, 1405-1418.e10 (2018).

89. F. Tramèr, N. Papernot, I. Goodfellow, D. Boneh, P. McDaniel, The Space of Transferable Adversarial Examples. *arXiv [stat.ML]* (2017).

90. N. A. Lesica, *et al.*, Harnessing the power of artificial intelligence to transform hearing healthcare and research. *Nature Machine Intelligence* **3**, 840–849 (2021).

91.   M. R. Saddler, A. Francl, J. Feather, J. H. McDermott, Speech Denoising with Auditory
Models in *Interspeech 2021*, (unknown, 2021), pp. 2681–2685.

92.   H. Hong, D. L. K. Yamins, N. J. Majaj, J. J. DiCarlo, Explicit information for category-
orthogonal object properties increases along the ventral stream. *Nat. Neurosci.* **19**, 613–
622 (2016).

93.   S. Thorat, G. Aldegheri, T. C. Kietzmann, Category-orthogonal object features guide
information processing in recurrent neural networks trained for object categorization in
SVRHM 2021 Workshop @ NeurIPS, (2021).

94.   R. Rajalingham, K. Schmidt, J. J. DiCarlo, Comparison of object recognition behavior in
human and monkey. *J. Neurosci.* **35**, 12127–12136 (2015).

95.   A. Francl, J. H. McDermott, Deep neural network models of sound localization reveal how
perception is adapted to real-world environments. *Nat Hum Behav* **6**, 111–133 (2022).

96.   M. R. Saddler, R. Gonzalez, J. H. McDermott, Deep neural network models reveal
interplay of peripheral coding and stimulus statistics in pitch perception. *Nat. Commun.*
12, 7278 (2021).

97.   A. Paszke, *et al.*, "PyTorch: An Imperative Style, High-Performance Deep Learning
Library" in *Advances in Neural Information Processing Systems 32*, H. Wallach, *et al.*, Eds.
(Curran Associates, Inc., 2019), pp. 8024–8035.

98.   L. Engstrom, A. Ilyas, H. Salman, S. Santurkar, D. Tsipras, Robustness (Python Library)
(2019).

99.   L. N. Smith, Cyclical Learning Rates for Training Neural Networks in *2017 IEEE Winter
Conference on Applications of Computer Vision (WACV)*, (2017), pp. 464–472.

100.   X. Huang, S. Belongie, Arbitrary style transfer in real-time with adaptive instance
normalization in *2017 IEEE International Conference on Computer Vision (ICCV)*, (IEEE,
2017) https:/doi.org/10.1109/iccv.2017.167 (January 11, 2023).

101.   E. Debenedetti, V. Sehwag, P. Mittal, A Light Recipe to Train Robust Vision Transformers
(2022) https:/doi.org/10.48550/ARXIV.2209.07399.

102.   H. Salman, A. Ilyas, L. Engstrom, A. Kapoor, A. Madry, Do adversarially robust imagenet
models transfer better? *Adv. Neural Inf. Process. Syst.* **33**, 3533–3545 (2020).

103.   E. Wong, L. Rice, J. Z. Kolter, Fast is better than free: Revisiting adversarial training in
International Conference on Learning Representations, (2020).

104.   D. B. Paul, J. M. Baker, The design for the wall street journal-based CSR corpus in
Proceedings of the Workshop on Speech and Natural Language - HLT '91, (Association
for Computational Linguistics, 1992) https://doi.org/10.3115/1075527.1075614.

105.   A. Köhn, F. Stegen, T. Baumann, Mining the Spoken Wikipedia for Speech Data and
Beyond in *Proceedings of the Tenth International Conference on Language Resources
and Evaluation (LREC 2016)*, N. C. (conference Chair), *et al.*, Eds. (European Language
Resources Association (ELRA), 2016).

106.   V. W. Zue, S. Seneff, "Transcription and alignment of the TIMIT database" in *Recent
Research Towards Advanced Man-Machine Interface Through Spoken Language*,
(Elsevier, 1996), pp. 515–525.

107. J. F. Gemmeke, *et al.*, Audio Set: An ontology and human-labeled dataset for audio events
in *2017 IEEE International Conference on Acoustics, Speech and Signal Processing*
(ICASSP), (IEEE, 2017) https:/doi.org/10.1109/icassp.2017.7952261 (January 31, 2022).

108. K. J. P. Woods, M. H. Siegel, J. Traer, J. H. McDermott, Headphone screening to facilitate
web-based auditory experiments. *Atten. Percept. Psychophys.* **79**, 2064–2072 (2017).

109. K. J. P. Woods, J. H. McDermott, Schema learning for the cocktail party problem. *Proc.*
Natl. Acad. Sci. U. S. A. **115**, E3313–E3322 (2018).

110. M. J. McPherson, J. H. McDermott, Time-dependent discrimination advantages for
harmonic sounds suggest efficient coding for memory. *Proc. Natl. Acad. Sci. U. S. A.* **117**,
32169–32180 (2020).

111. J. Traer, S. V. Norman-Haignere, J. H. McDermott, Causal inference in environmental
sound recognition. *Cognition* **214**, 104627 (2021).

112. M. J. McPherson, R. C. Grace, J. H. McDermott, Harmonicity aids hearing in noise. *Atten.*
Percept. Psychophys. (2022) https:/doi.org/10.3758/s13414-021-02376-0.

113. F. Faul, E. Erdfelder, A.-G. Lang, A. Buchner, G*Power 3: a flexible statistical power
analysis program for the social, behavioral, and biomedical sciences. *Behav. Res.*
Methods **39**, 175–191 (2007).

114. M. Abadi, *et al.*, TensorFlow: A system for large-scale machine learning. *arXiv [cs.DC]*
(2016).

115. D. P. Kingma, J. Ba, Adam: A Method for Stochastic Optimization. *arXiv [cs.LG]* (2014).

116. T. Marques, M. Schrimpf, J. J. DiCarlo, Multi-scale hierarchical neural network models that
bridge from single neurons in the primate primary visual cortex to object recognition
behavior. *bioRxiv*, 2021.03.01.433495 (2021).

117. J. Freeman, C. M. Ziemba, D. J. Heeger, E. P. Simoncelli, J. A. Movshon, A functional
and perceptual signature of the second visual area in primates. *Nat. Neurosci.* **16**, 974–
981 (2013).

118. N. J. Majaj, H. Hong, E. A. Solomon, J. J. DiCarlo, Simple Learned Weighted Sums of
Inferior Temporal Neuronal Firing Rates Accurately Predict Human Core Object
Recognition Performance. *J. Neurosci.* **35**, 13402–13418 (2015).

119. S.　　　Sanghavi,　　　J.　　　J.　　　DiCarlo,　　　Sanghavi2020　　　(2022)
https:/doi.org/10.17605/OSF.IO/CHWDK.

120. S.　Sanghavi,　K.　M.　Jozwik,　J.　J.　DiCarlo,　SanghaviJozwik2020　(2022)
https:/doi.org/10.17605/OSF.IO/FHY36.

121. S.　Sanghavi,　N.　Apurva　Ratan　Murty,　J.　J.　DiCarlo,　SanghaviMurty2020　(2022)
https:/doi.org/10.17605/OSF.IO/FCHME.

122. C. Humphries, E. Liebenthal, J. R. Binder, Tonotopic organization of human auditory
cortex. *Neuroimage* **50**, 1202–1211 (2010).

123. S. Norman-Haignere, N. Kanwisher, J. H. McDermott, Cortical pitch regions in humans
respond primarily to resolved harmonics and are located in specific tonotopic regions of
anterior auditory cortex. *J. Neurosci.* **33**, 19451–19469 (2013).

124. T. Overath, J. H. McDermott, J. M. Zarate, D. Poeppel, The cortical analysis of speech-
specific temporal structure revealed by responses to sound quilts. *Nat. Neurosci.* **18**, 903–
911 (2015).

125. F. Pedregosa, *et al.*, Scikit-learn: Machine Learning in Python. *J. Mach. Learn. Res.* **12**,
2825–2830 (2011).

126. C. Spearman, The proof and measurement of association between two things. *Am. J.*
Psychol. **15**, 72–101 (1904).

127. C. Spearman, Correlation calculated from faulty data. *Br. J. Psychol.* **3**, 271–295 (1910).

128. A. G. Huth, W. A. de Heer, T. L. Griffiths, F. E. Theunissen, J. L. Gallant, Natural speech
reveals the semantic maps that tile human cerebral cortex. *Nature* **532**, 453–458 (2016).

129. D. Tsipras, S. Santurkar, L. Engstrom, A. Turner, A. Madry, Robustness may be at odds
with accuracy. *arXiv [stat.ML]* (2018) (March 16, 2022).

130. A. Dosovitskiy, *et al.*, An Image is Worth 16x16 Words: Transformers for Image
Recognition at Scale in *International Conference on Learning Representations*, (2021).

131. S. Xie, R. Girshick, P. Dollar, Z. Tu, K. He, Aggregated residual transformations for deep
neural networks in *2017 IEEE Conference on Computer Vision and Pattern Recognition*
(CVPR), (IEEE, 2017) https:/doi.org/10.1109/cvpr.2017.634.
2515