Accurate pan-cancer tumor purity estimation from gene expression data

Egor Revkov[1,2], Tanmay Kulshrestha[2], Ken Wing-Kin Sung[1,2], Anders Jacobsen Skanderup[1,2,3*]

[1]National University of Singapore, School of Computing, 119077, Singapore

[2]Genome Institute of Singapore, 138672, Singapore

[3]National Cancer Centre Singapore, Division of Medical Oncology, 169610, Singapore

*skanderupamj@gis.a-star.edu.sg

Abstract

Tumors are complex masses composed of malignant and non-malignant cells. Variation in tumor purity (proportion of cancer cells in a sample) can both confound integrative analysis and enable studies of tumor heterogeneity. Here we developed PUREE, which uses a weakly supervised learning approach to infer tumor purity from a tumor gene expression profile. PUREE was trained on gene expression data and genomic consensus purity estimates from approximately 8000 solid tumor samples. PUREE predicted purity with high accuracy across distinct solid tumor types and generalized to tumor samples from unseen tumor types and cohorts. Gene features of PUREE were further validated using single-cell RNA-seq data from distinct tumor types. In a comprehensive benchmark, PUREE outperformed existing transcriptome-based purity estimation approaches. Overall, PUREE is a highly accurate and versatile method for estimating tumor purity and interrogating tumor heterogeneity from bulk tumor gene expression data.

Keywords

Bioinformatics, cancer, gene expression, machine learning, tumor microenvironment, tumor purity

Introduction

Cancerous tumors are complex mixtures of malignant and non-malignant cells shaping the tumor microenvironment (TME). The composition and relative proportions of malignant cells and non-malignant components (comprising stromal, epithelial, and infiltrating immune cells) can display substantial variation across tumors (1–4). The composition of the TME is also associated with the disease stage and treatment response (5). The proportion of malignant cancer cells in the tumor mass, herein referred to as tumor purity, also impacts genomic analysis such as estimation of clonal composition (6) and tumor mutation burden (7), critical for predicting treatment outcomes and selecting patients for immunotherapy. Moreover, tumor purity can guide tumor transcriptome deconvolution and the estimation of gene expression profiles for malignant and non-malignant cell populations inside tumors (8,9), enabling new insights on TME biology (10) and its impact on clinical treatment response.

Traditionally, the cancer cell proportion has been estimated by pathologists inspecting nuclei in hematoxylin and eosin (H&E)-stained tissue slides. However, such estimates may often be imprecise, as demonstrated by the noticeable variation in estimates when the same sample is evaluated by different pathologists (11). More recent computational approaches to estimate tumor purity are based on DNA sequencing data where variation in allele frequencies of somatic DNA mutations or copy-number alterations (CNAs) are used to infer the malignant cell proportion (5,12). DNA-based purity estimation methods, despite differences in underlying statistical models and input data, have been shown to produce concordant estimates of tumor purity (9,13).

Tumor purity can also be estimated from the tumor gene expression profile (14), which has been used to derive clinically relevant molecular subtypes (15–18), perform quality control of tumor samples (19,20), and analyze treatment responses after immunotherapy (21). Existing methods that estimate tumor purity from a tumor gene expression profile adopt different analytical strategies. ESTIMATE calculates a combined enrichment score for infiltrating immune and stromal cells followed by training of a supervised model (22). EPIC uses constrained least square optimization in combination with non-malignant cell-type reference profiles to perform cell type proportion deconvolution (23). DeMixT uses probabilistic modeling to infer proportions of stromal and cancer-cell components from a set of input samples, comprising both tumor and normal-tissue samples (8). LinSeed constructs an undirected weighted linearity network of genes to determine mutually linear features followed by simplex-based deconvolution (24). CIBERSORTx defines a cell-type signature matrix followed by support vector regression to infer the proportions of cell types in each sample (25,26). However, due to the inherent modeling assumptions, these methods might not always capture all the biological variation between stroma and cancer cells, required to predict require malignant cells proportions. Additionally, while these methods show convincing results in their own benchmarks, it is not clear how accurate they are when applied to distinct cancer types and compared with each other.

Our goal was to develop an accurate reference-free method for predicting tumor purity from a tumor gene expression profile. To reduce the modeling limitations of existing approaches, we utilized minimal prior modeling assumptions and instead relied on a statistical learning approach to infer gene expression patterns related to stroma and cancer components. We used a weakly supervised learning strategy, training a machine learning model using gene expression data from 8000 tumors and 20 solid cancer types (27) in combination with consensus genomics-based tumor purity estimates. The resulting method, PUREE, is able to robustly predict purity values with high correlation and low root mean squared error (RMSE),

outperforming existing deconvolution methods both on TCGA (45% increase in correlation and 53% decrease in RMSE compared to the respective second best approaches) and three external validation datasets of lung and colorectal cancers.

Results

Overview of approach

Our goal was to develop an accurate method for estimating tumor purity from a tumor gene expression profile. Such a method should be able to generalize across different solid cancer types and exhibit high concordance with orthogonal purity estimates derived from tumor DNA data (Fig. 1a). We therefore assembled a training dataset comprising matched genomic and gene expression profiles from 7864 tumors spanning 20 solid cancer types from TCGA (27) (Suppl. Tab. 1). The "pseudo" ground truth purity label of each tumor was estimated using the tumor genomic profile, using the consensus of four existing algorithms that generally displayed high concordance (mean Pearson r=0.66, Methods, Suppl. Fig. S1). Next, we adopted a weakly supervised learning strategy to train a model that could predict tumor purity labels from the matched gene expression profiles. Gene expression profiles were log-rank transformed to provide robustness to variation in scale and normalization of different gene expression datasets and platforms (e.g. FPKM, TPM; Methods). From the 60,000 transcripts profiled in TCGA, we further selected and focused on 10,000 (10K) highly expressed protein-coding genes for model development (Methods). We explored the performance of a range of machine learning methods (Suppl. Fig. S3). In particular, given the regression task of predicting the bounded continuous tumor purity value, we tested both a range of linear and non-linear machine learning architectures. This comparison showed that a regularized linear regression (Lasso) model could achieve optimal accuracy using only a limited set of gene expression features (Suppl. Fig. S3). PUREE was therefore developed using a Lasso regression and weakly supervised learning strategy to enable accurate estimation of tumor purity from a solid tumor gene expression profile (Fig. 1b).

Figure 1: Overview of PUREE. a) PUREE is trained using a weakly supervised learning approach. Consensus genomics-based purity estimates are used as pseudo ground-truth labels, and a predictive model is trained on log-rank transformed gene expression profiles from 7864 tumor samples spanning 20 solid tumor types (80/20% train/test split). **b)** For a new solid tumor sample, PUREE infers the purity from the corresponding tumor gene expression profile.

Feature selection to account for cancer type and tumor purity imbalance

The TCGA training dataset showed strong cancer type and purity range imbalance (Fig. 2a, Suppl. Tab. 1). To reduce the impact of this imbalance during model training, we adopted a two-step feature selection strategy (Methods). Briefly, the first step consisted of selecting features which could predict purity at both lower and higher purity ranges (Fig. 2b). The second step further filtered this feature set to identify the genes most predictive across the entire purity range, resulting in 170 features (Fig. 2c).

We further explored the properties of the resulting reduced feature set. Using gene set enrichment analysis, the 170 genes were enriched in pathways relating to angiogenesis, inflammatory response and epithelial-mesenchymal transition (Methods, Suppl. Fig. S2). Genes positively correlated with purity showed enrichment in cancer-related pathways and processes such as cell cycle coupled E2F targets (CBX5, MXD3, LMNB1), genes involved in the G2/M checkpoint (LMNB1, FANCC), and genes downregulated by KRAS activation (PDK2). Genes negatively correlated with purity showed enrichment in stroma-related processes such as

inflammatory response (CSF3R, STAB1, MSR1, NFKBIA) and genes involved in epithelial-mesenchymal transition (FSTL1, BASP1, CXCL12, TGFBI). Overall, this confirmed the original hypothesis of the PUREE model separating cancer and stroma-related genes by assigning positive and negative weights to them respectively.

Figure 2: Feature selection to account for cancer type and tumor purity imbalance. a) top: genomic-based tumor purity across 20 cancer types from TCGA, blue and red lines marking the bottom/top 20% purity samples; bottom: genomic-based tumor purity separated into low, medium, and high purity ranges. **b)** the first step of the feature selection strategy: lasso feature selection was performed separately on low-mid and mid-high purity range samples, the two feature sets were intersected resulting in 191 genes. **c)** the second step of the feature selection strategy: using the features from the first step, lasso feature selection was performed across all samples, cross-validated on cancer types as folds, resulting in 170 gene features in the final model.

Comparing the performance of pan-cancer and cancer-type specific models

As an alternative to PUREE's pan-cancer tumor purity prediction model, we explored whether models trained for a specific cancer type could more accurately predict purity. To test this, we trained cancer-type specific models (Methods) and compared their performance with PUREE

across all cancer types. Interestingly, PUREE showed comparable and often improved performance, with higher median correlation (0.79 vs 0.76, *P*=0.1, Wilcoxon signed-rank test, two-tailed) and lower median RMSE (0.10 vs. 0.09) with the ground-truth purity estimates (Fig. 3a, Suppl. Fig. S5,S6a). Overall, this confirmed that PUREE's pan-cancer feature selection and training approach provided a robust and accurate prediction across all individual cancer types.

Figure 3: PUREE versus cancer type-specific architectures and unseen cancer types. a) Performance (correlation and RMSE) of PUREE as compared to 20 cancer-type specific models on the test split of the TCGA dataset; **b)** Performance (correlation and RMSE) of PUREE when predicting on a cancer type included in training data versus when the same cancer type was excluded from the training data. Differences were evaluated with the Wilcoxon signed-rank test (two-tailed), and delta is the mean absolute difference between the two metric distributions.

Next, we evaluated the ability of PUREE to predict purity in cancer types absent from the training data (Methods). We compared performance metrics for PUREE and versions of PUREE where one cancer type was removed from the training data. This comparison showed only a minor decrease in correlation (median 0.794 vs 0.79, P=0.08, Wilcoxon signed-rank test, two-tailed) and increase in RMSE (0.092 vs 0.096, P=0.001) when the cancer type was absent from the training data (Fig. 3b, Suppl. Fig. S6b). This demonstrated that PUREE is robust and can generalize to solid tumor types not included in the training data.

Benchmarking of methods on independent datasets

We evaluated PUREE's performance on the withheld test sets from the TCGA dataset. We compared PUREE with five existing gene expression-based deconvolution and purity estimation methods (Methods).

Here, PUREE consistently demonstrated higher correlation and lower RMSE with consensus purity labels than the existing deconvolution methods (Fig. 4a,b, Suppl. Fig. S7). PUREE had the highest median correlation (r=0.83), followed by ESTIMATE (0.63) and CIBERSORTx (0.55). Similarly, PUREE had the lowest median RMSE of all methods (0.09), 53% lower than the next-best method (CIBERSORTx, 0.19), and PUREE displayed the lowest RMSE in each cancer type. PUREE also showed less variation in performance across cancer types as compared to the other methods, with an inter-quartile range for correlation and RMSE of 0.12 and 0.015, respectively.

Next, we compared PUREE's performance on two additional independent public lung cancer cohorts (29,30) as well as an independent colorectal cancer cohort (Methods). Similar to the TCGA cohort, ground-truth tumor purity estimates in these cohorts were estimated from tumor DNA sequencing data (Methods). In all three cohorts, PUREE demonstrated both higher correlation and lower RMSE with the DNA-based tumor purity estimates (Fig. 5a,b, Suppl. Fig. S8). We additionally compared PUREE's resource usage against the other methods in terms of memory (RAM) and compute time. This evaluation showed that PUREE uses less memory to run, in addition to consistently being the fastest method (Fig. 5c).

Figure 4: Comparing PUREE and existing methods on TCGA data. a,b,c) Comparison of PUREE and 5 existing transcriptome deconvolution methods. Pearson's correlation (a) and RMSE (b) of methods when compared with genomic tumor purity estimates on the TCGA test data split (1500 samples).

Figure 5: Benchmarking of methods on independent datasets. Comparing the purity estimates of PUREE and 5 existing transcriptome deconvolution methods. The predictions from each method were compared with genomic tumor purity estimates across 4 cohorts: the TCGA test set, lung cancer samples from Chen et. al (29), lung cancer samples from Chua et. al (30), and al colorectal cancer cohort (CRC-GIS). **a, b)** Mean correlation and RMSE for all methods and cohorts. **c)** Time-memory benchmark of all methods. DeMixT could not be run on the Chua et al. and CRC-GIS cohorts due to the absence of normal samples there.

Exploring the PUREE feature set using single-cell RNA-seq data

We performed orthogonal analysis and validation of the 170 gene-features in the PUREE model using single-cell RNA-seq data. We used published scRNA-seq data from head and neck cancer (32) (5902 cells total, 2539 classified as malignant, 3363 as non-malignant) and melanoma (31) (4513 cells total, 3256 classified as malignant, 1257 as non-malignant). We computed mean cell-wise z-scores of the expression of the genes with positive and negative purity-expression correlation. Interestingly, these genes showed noticeable expression differences between malignant and non-malignant cells in both tumor types (Fig. 6a,b, Mann-Whitney P<1e-200; Suppl. Fig. S9). Genes with positive purity-expression correlation had markedly higher expression in malignant cells as compared to non-malignant cells. In contrast, genes with negative purity-expression correlation were upregulated in non-malignant cells. . This result further confirmed that the gene feature set used by PUREE has the ability to distinguish between and quantify the proportion of cancer and non-cancer cells in the tumors.

Figure 6: Validation of PUREE's features using single-cell RNA-seq data. Comparing the expression of PUREE gene features in malignant and non-malignant cells in **a)** head and neck cancer cells from Puram et al. (32) and **b)** melanoma cells from Tirosh et al. (31). Malignant and non-malignant cell labels were obtained from the original publications. Genes were separated in groups of positive (>0.15) and negative (<-0.15) purity-vs-expression correlation in TCGA data.

Discussion and Conclusions

We developed a novel method, PUREE, that can predict the proportion of cancer cells in a sample (tumor purity) from a bulk tumor gene expression profile. The method adopts a machine learning-based feature selection strategy in combination with a linear regression architecture. The model is trained using weak supervision and consensus tumor purity labels obtained from tumor DNA sequencing data spanning 20 solid tumor types. Compared with existing transcriptome deconvolution methods, we demonstrate that PUREE has superior accuracy across multiple independent test cohorts. Additionally, PUREE is fast and user friendly as the underlying model is pre-trained in advance.

PUREE adopts a stringent feature selection strategy, with which we were able to reduce the initial feature set of around 10,000 genes to 170 predictive genes. Combined with a pan-cancer training strategy, we demonstrate that this sparse model can generalize well to unseen tumor types and cohorts. We also show that PUREE's pan-cancer architecture has comparable accuracy to cancer-type specific models. This suggests that the model is able to capture expression signatures of cancer and stromal cells conserved across solid tumor types, and that cancer-type specific expression signatures do not provide additional discriminatory information for tumor purity estimation. We found that these pan-cancer conserved feature genes were enriched for known cancer and stromal cell specific processes such as cell cycle and immune cell activity.

The gene feature set used by PUREE also demonstrated a remarkable ability to distinguish between malignant and non-malignant cells in single-cell RNA-seq data. This provides orthogonal validation of our feature selection and pan-cancer training strategy as well as further confirming the predictive power of the selected gene set. This result also suggests that a modified version of our approach could potentially be repurposed to classify malignant and non-malignant cells in single-cell RNA-seq data. Finally, due to its supervised machine learning approach, PUREE has some limitations stemming from the composition of the training data. Specifically, the method has only been trained and tested on solid tumor samples and will therefore likely have suboptimal performance if applied to other non-solid cancer types

In summary, we have shown that PUREE is a highly accurate and efficient method for purity estimation from a tumor gene expression profile, enabling robust and accurate interrogation of tumor purity and heterogeneity from bulk tumor gene expression data.

Methods

Availability of data and materials

TCGA transcript-level expression TPM data, quantified by Kallisto, was downloaded through the UCSC Xena Hub (28). The lung cancer validation cohorts used in the external benchmark were obtained from the publication by Chen et al. (29) and Chua et al. (30). The colorectal cancer cohort used in the external benchmark (CRC-GIS) is an unpublished dataset comprising matched WGS and transcriptome data from ~150 patients. The head and neck cancer single-cell cohort used in the feature set validation was taken from the publication by Tirosh et al. (Gene Expression Omnibus ID GSE72056) (31). The melanoma single-cell cohort used in the feature set validation was obtained from the publication by Puram et al. (Gene Expression Omnibus ID GSE103322) (32). ABSOLUTE tumor purity estimates for TCGA samples were obtained from the NCI Genomic Data Commons (GDC) database (33).

PUREE is available as a web service and Python software package. Validation experiments were done on an Amazon EC2 r5.2xlarge instance with 64 GiB memory and 8 vCPUs.

Genomics-based tumor purity estimates

For TCGA samples, genomic-based consensus tumor purities were computed as a mean of predictions from ABSOLUTE (34), AbsCNSeq (35), ASCAT (36) and PurBayes (37) following the approach reported in Ghoshdastider et al.(9). AbsCNSeq and PurBayes estimates are based on mutation variant allele frequency data, and ASCAT and ABSOLUTE on SNP-array data. Briefly, samples with extremely low (<0.1) and extremely high (>0.98) purity estimates from individual methods were flagged as missing data, as recommended by Ghoshdastider et al. These missing data values were instead imputed using an iterative principal component analysis approach (38). Quantile normalization was used to standardize and average the tumor purity distributions of different algorithms per cancer type. Finally, consensus purity estimates were finally estimated as the sample-wise means of the normalized purity estimates from individual methods.

In the first lung cancer validation dataset from Chen et. al (29), genomic purity estimates were computed by Sequenza and obtained from the respective publication. In the second lung cancer validation dataset, Chua et al (30), genomic purity estimates were based on ASCAT and Sequenza methods and taken from the respective publication. In the colorectal cancer validation cohort (CRC-GIS), consensus purity values were computed as a mean of THetA2 (39), TitanCNA (40), AbsCNSeq and PurBayes methods.

TCGA training and test set construction

The TCGA dataset consisted of 7864 samples from 20 solid cancer types. 80% of samples were selected for model training and 20% for testing. The training and test sets were randomly sampled so they had comparable cancer-type and purity distributions. The initial gene expression feature matrix was filtered to only include protein-coding genes. Genes with low expression (median TPM<1) and low variance (variance<1) in all cancer types were further

filtered, leaving ~10,000 gene expression features for subsequent steps (referred to as the 10K features set below).

Gene expression data pre-processing

Gene expression data was log-rank normalized (sample-wise) and z-score standardized (gene/feature-wise). The log-rank normalization allows for generalization across different gene expression platforms (e.g. RNA-seq, microarray) and measurement units (e.g. Transcripts Per Million (TPM), Fragments Per Kilobase Million (FPKM)). Briefly, genes were ranked based on their expression rank within a sample and the logarithm of each rank was computed. Z-score standardization is a common technique used in machine learning, ensuring that features are measured on the same relative scale. Briefly, feature values (log-rank expression) were transformed by subtracting sample means and dividing by sample standard deviations from the training data. Whenever the underlying regression model of PUREE is applied, features are z-score transformed using the training set distribution.

Construction of machine learning models

All machine learning models (Elastic Net, Gradient Boosting, Support Vector Regression, Lasso and Linear Regression models, as well as Iterative Imputer for missing values imputation) were trained using the Scikit-Learn Python package (41). A fully connected Neural Net consisting of a variable number of relu-activated fully-connected hidden layers, depending on the feature size of the input data, was constructed using the Keras submodule of the Tensorflow Python package (42).

Feature selection

We used Lasso regression to reduce the number of input features in PUREE. During the first step, we selected features relevant to both low and high purity ranges. Two lasso regression models, cross-validated using cancer types as folds, were trained on all training data except the bottom and top-20% purity values, respectively. These two resulting feature sets were intersected, resulting in 191 genes. Next, we further iteratively selected features equally relevant to all cancer types by training a Lasso model (cross-validated with cancer type as folds) on a balanced subset of the full TCGA training set comprising all purity ranges. This resulted in 170 genes with non-zero weights, which serve as the input features for the final PUREE model. Correlations of the genes' expression with genomic-based tumor purity were computed on the train portion of TCGA as means per each cancer type averaged across all cancer types.

Predicting on unseen samples

The PUREE pipeline consists of three parts: log-rank normalization, missing values imputation and Lasso model inference. During the first step, log-ranks of the overlap of the genes in the input data and the 10K genes are computed. The data is further reduced to the 170 PUREE input genes. During the second step, the resulting dataset is standardized feature-wise using z-score values computed on the TCGA train set and if there are any missing values in the 170

selected genes, they are imputed using an iterative imputation procedure based on the values of the TCGA train set. During the third step, the pre-trained Lasso model is applied to the resulting data in order to predict purity values.

Cancer-type specific models and test experiments

For experiments with cancer type-specific models, we constructed training/test sets comprising the 10k features for each individual cancer type. We used 5-fold cross-validation to train models on these cancer-type specific training sets. For experiments where individual cancer types were excluded during model training, we constructed a pan-cancer training set (170 features) comprising all cancer types except the cancer type being withheld, followed by lasso regression and 5-fold cross-validation as described for the main pan-cancer PUREE model.

Gene set enrichment analysis

Gene set enrichment analysis was evaluated using the GSEApy Python package, which is based on Enrichr (43) and Gene Set Enrichment Analysis (GSEA) (44) (see Supplementary Materials for details).

Running other gene expression-based methods for purity prediction

CIBERSORTx was run using the web interface provided by the authors. DeMixT, EPIC, ESTIMATE and Linseed were run using their respective R packages (see Supplementary Material for details).

List of abbreviations

FPKM - Fragments Per Kilobase Million

GSEA - Gene Set Enrichment Analysis

H&E - Hematoxylin and Eosin

RMSE - Root Mean Square Error

TCGA - The Cancer Genome Atlas

TME - Tumor Microenvironment

TPM - Transcripts Per Million

Declarations

Ethics approval and consent to participate

Not applicable

Consent for publication

Not applicable

Funding

This research is supported by the Singapore Ministry of Health's National Medical Research Council under its OF-IRG program (OFIRG18may-0075), and Agency for Science, Technology and Research (A*STAR) under its CDAP program (grant no. 1727600057).

Author contributions

A.J.S. and E.R. conceived the idea and the experiments, E.R. conducted the experiments, developed the method, and wrote the manuscript. T.K. developed the web service and the python package. A.J.S. and K.S. supervised the method development and reviewed the manuscript.

Acknowledgments

E.R. is a student funded by the SINGA-A*STAR scholarship and is grateful for the provided financial support for the research above. The authors would also like to express gratitude to Sim Ngak Leng for the help with relevant bioinformatics analysis, Kiran Krishnamachari for the extensive discussion on the manuscript, Sinem Kadioglu and Yu Amanda Guo for testing the method and members of the Skanderup lab for other helpful inputs and overall support of the project.

Competing interests

The authors declare no competing interests.

Bibliography

1. Fridman WH, Pagès F, Sautès-Fridman C, Galon J. The immune contexture in human tumours: impact on clinical outcome. Nat Rev Cancer. 2012 Apr;12(4):298–306.
2. Egeblad M, Nakasone ES, Werb Z. Tumors as Organs: Complex Tissues that Interface with the Entire Organism. Dev Cell. 2010 Jun;18(6):884–901.
3. Avila Cobos F, Vandesompele J, Mestdagh P, De Preter K. Computational deconvolution of transcriptomics data from mixed cell populations. Bioinformatics. 2018;34(11):1969–79.
4. Joyce JA, Pollard JW. Microenvironmental regulation of metastasis. Nat Rev Cancer. 2009;9(4):239–52.
5. Aran D, Sirota M, Butte AJ. Systematic pan-cancer analysis of tumour purity. Nat Commun. 2015 Dec;6(1):8971.
6. Roth A, Khattra J, Yap D, Wan A, Laks E, Biele J, et al. PyClone: Statistical inference of clonal population structure in cancer. Nat Methods. 2014 Apr;11(4):396–8.
7. Anagnostou V, Niknafs N, Marrone K, Bruhm DC, White JR, Naidoo J, et al. Multimodal genomic features predict outcome of immune checkpoint blockade in non-small-cell lung cancer. Nat Cancer. 2020 Jan;1(1):99–111.
8. Wang Z, Cao S, Morris JS, Ahn J, Liu R, Tyekucheva S, et al. Transcriptome Deconvolution of Heterogeneous Tumor Samples with Immune Infiltration. iScience. 2018 Nov;9:451–60.
9. Ghoshdastider U, Rohatgi N, Naeini MM, Baruah P, Revkov E, Guo YA, et al. Pan-Cancer Analysis of Ligand-Receptor Cross-talk in the Tumor Microenvironment. 2021; Available from: http://cancerres.aacrjournals.org/
10. Rohatgi N, Ghoshdastider U, Baruah P, Jacobsen Skanderup A. A pan-cancer metabolic atlas of the tumor microenvironment. bioRxiv. 2020 Oct;2020.10.16.342519.
11. Smits AJJ, Kummer JA, De Bruin PC, Bol M, Van Den Tweel JG, Seldenrijk KA, et al. The estimation of tumor cell percentage for molecular testing by pathologists is not accurate. Mod Pathol. 2014 Feb;27(2):168–74.
12. Dentro SC, Wedge DC, Van Loo P. Principles of Reconstructing the Subclonal Architecture of Cancers. Cold Spring Harb Perspect Med. 2017 Aug;7(8):a026625.
13. Haider S, Tyekucheva S, Prandi D, Fox NS, Ahn J, Xu AW, et al. Systematic Assessment of Tumor Purity and Its Clinical Implications. JCO Precis Oncol. 2020 Nov;(4):995–1005.
14. Wang Y, Mashock M, Tong Z, Mu X, Chen H, Zhou X, et al. Changing Technologies of RNA Sequencing and Their Applications in Clinical Oncology. Front Oncol. 2020 Apr;10:447.
15. Ceccarelli M, Barthel FP, Malta TM, Sabedot TS, Salama SR, Murray BA, et al. Molecular Profiling Reveals Biologically Discrete Subsets and Pathways of Progression in Diffuse Glioma. Cell. 2016 Jan 28;164(3):550–63.
16. Bailey P, Chang DK, Nones K, Johns AL, Patch A-M, Gingras M-C, et al. Genomic analyses identify molecular subtypes of pancreatic cancer. Nature. 2016 Mar;531(7592):47–52.
17. Guinney J, Dienstmann R, Wang X, de Reyniès A, Schlicker A, Soneson C, et al. The consensus molecular subtypes of colorectal cancer. Nat Med. 2015 Nov;21(11):1350–6.
18. Moffitt RA, Marayati R, Flate EL, Volmar KE, Loeza SGH, Hoadley KA, et al. Virtual microdissection identifies distinct tumor- and stroma-specific subtypes of pancreatic ductal adenocarcinoma. Nat Genet. 2015 Oct;47(10):1168–78.
19. Mertins P, Mani DR, Ruggles KV, Gillette MA, Clauser KR, Wang P, et al. Proteogenomics connects somatic mutations to signalling in breast cancer. Nature. 2016 Jun;534(7605):55–62.
20. Dudley JC, Gurda GT, Tseng L-H, Anderson DA, Chen G, Taube JM, et al. Tumor Cellularity as a

Quality Assurance Measure for Accurate Clinical Detection of BRAF Mutations in Melanoma. Mol Diagn Ther. 2014 Aug;18(4):409–18.

21. Riaz N, Havel JJ, Makarov V, Desrichard A, Urba WJ, Sims JS, et al. Tumor and Microenvironment Evolution during Immunotherapy with Nivolumab. Cell. 2017 Nov 2;171(4):934-949.e16.

22. Yoshihara K, Shahmoradgoli M, Martínez E, Vegesna R, Kim H, Torres-Garcia W, et al. Inferring tumour purity and stromal and immune cell admixture from expression data. Nat Commun. 2013 Dec;4(1):2612.

23. Racle J, Gfeller D. EPIC: A tool to estimate the proportions of different cell types from bulk gene expression data. In: Methods in Molecular Biology [Internet]. Humana Press Inc.; 2020. p. 233–48. Available from: https://pubmed-ncbi-nlm-nih-gov.ejproxy.a-star.edu.sg/32124324/

24. Zaitsev K, Bambouskova M, Swain A, Artyomov MN. Complete deconvolution of cellular mixtures based on linearity of transcriptional signatures. Nat Commun. 2019;10(1):1–16.

25. Newman AM, Steen CB, Liu CL, Gentles AJ, Chaudhuri AA, Scherer F, et al. Determining cell type abundance and expression from bulk tissues with digital cytometry. Nat Biotechnol. 2019 Jul;37(7):773–82.

26. Newman AM, Liu CL, Green MR, Gentles AJ, Feng W, Xu Y, et al. Robust enumeration of cell subsets from tissue expression profiles. Nat Methods. 2015 May;12(5):453–7.

27. The Cancer Genome Atlas Program - National Cancer Institute [Internet]. [cited 2021 Jun 23]. Available from: https://www.cancer.gov/about-nci/organization/ccg/research/structural-genomics/tcga

28. Goldman MJ, Craft B, Hastie M, Repečka K, McDade F, Kamath A, et al. Visualizing and interpreting cancer genomics data via the Xena platform. Nat Biotechnol. 2020 Jun;38(6):675–8.

29. Chen J, Yang H, Teo ASM, Amer LB, Sherbaf FG, Tan CQ, et al. Genomic landscape of lung adenocarcinoma in East Asians. Nat Genet. 2020 Feb;52(2):177–86.

30. Chua KP, Teng YHF, Tan AC, Takano A, Alvarez JJS, Nahar R, et al. Integrative Profiling of T790M-Negative EGFR-Mutated NSCLC Reveals Pervasive Lineage Transition and Therapeutic Opportunities. Clin Cancer Res. 2021 Nov 1;27(21):5939–50.

31. Tirosh I, Izar B, Prakadan SM, Wadsworth MH, Treacy D, Trombetta JJ, et al. Dissecting the multicellular ecosystem of metastatic melanoma by single-cell RNA-seq. Science. 2016 Apr 8;352(6282):189–96.

32. Puram SV, Tirosh I, Parikh AS, Patel AP, Yizhak K, Gillespie S, et al. Single-Cell Transcriptomic Analysis of Primary and Metastatic Tumor Ecosystems in Head and Neck Cancer. Cell. 2017 Dec 14;171(7):1611-1624.e24.

33. Grossman RL, Heath AP, Ferretti V, Varmus HE, Lowy DR, Kibbe WA, et al. Toward a Shared Vision for Cancer Genomic Data [Internet]. https://doi.org/10.1056/NEJMp1607591. Massachusetts Medical Society; 2016 [cited 2022 Jan 23]. Available from: https://www.nejm.org/doi/10.1056/NEJMp1607591

34. Carter SL, Cibulskis K, Helman E, McKenna A, Shen H, Zack T, et al. Absolute quantification of somatic DNA alterations in human cancer. Nat Biotechnol. 2012 May;30(5):413–21.

35. Bao L, Pu M, Messer K. AbsCN-seq: A statistical method to estimate tumor purity, ploidy and absolute copy numbers from next-generation sequencing data. Bioinformatics. 2014;30(8):1056–63.

36. Van Loo P, Naume B, Sun W, Weigman VJ, Marynen P, Borresen-Dale A-L, et al. Allele-specific copy number analysis of tumors. Proc Natl Acad Sci. 2010;107(39):16910–5.

37. Larson NB, Fridley BL. PurBayes: Estimating tumor cellularity and subclonality in next-generation sequencing data. Bioinformatics. 2013;29(15):1888–9.

38. Josse J, Husson F. missMDA: A Package for Handling Missing Values in Multivariate Data

Analysis. J Stat Softw. 2016 Apr 4;70:1–31.

39. Oesper L, Satas G, Raphael BJ. Quantifying tumor heterogeneity in whole-genome and whole-exome sequencing data. Bioinformatics. 2014 Dec 15;30(24):3532–40.

40. Ha G, Roth A, Khattra J, Ho J, Yap D, Prentice LM, et al. TITAN: inference of copy number architectures in clonal cell populations from tumor whole-genome sequence data. Genome Res. 2014 Nov;24(11):1881–93.

41. Pedregosa F, Michel V, Grisel O, Blondel M, Prettenhofer P, Weiss R, et al. Scikit-learn: Machine Learning in Python. J Mach Learn Res. 2011;12:2825–30.

42. Martín Abadi, Ashish Agarwal, Paul Barham, Eugene Brevdo, Zhifeng Chen, Craig Citro, et al. TensorFlow: Large-Scale Machine Learning on Heterogeneous Systems [Internet]. 2015. Available from: https://www.tensorflow.org/

43. Xie Z, Bailey A, Kuleshov MV, Clarke DJB, Evangelista JE, Jenkins SL, et al. Gene Set Knowledge Discovery with Enrichr. Curr Protoc. 2021;1(3):e90.

44. Barbie DA, Tamayo P, Boehm JS, Kim SY, Moody SE, Dunn IF, et al. Systematic RNA interference reveals that oncogenic KRAS-driven cancers require TBK1. Nature. 2009 Nov;462(7269):108–12.