The effects of data quantity on performance of temporal response function analyses of natural speech processing

Juraj Mesik[1*] and Magdalena Wojtczak[1]

[1] Department of Psychology, University of Minnesota, Minneapolis, MN, USA

* Correspondence:
Juraj Mesik
mesik002@umn.edu

Abstract
In recent years, temporal response function (TRF) analyses of non-invasive recordings of neural activity evoked by continuous naturalistic stimuli have become increasingly popular for characterizing response properties within the auditory hierarchy. However, despite this rise in TRF usage, relatively few educational resources for these tools exist. Here we use a dual-talker continuous speech paradigm to demonstrate how a key parameter of experimental design, the quantity of acquired data, influences TRF analyses fit to either individual data (subject-specific analyses), or group data (generic analyses). We show that although model performance monotonically increases with data quantity, the amount of data required to achieve significant prediction accuracies can vary substantially based on whether the fitted model contains densely (e.g., acoustic envelope) or sparsely (e.g., lexical surprisal) spaced features, especially when the goal of the analyses is to capture the aspect of neural responses uniquely explained by specific features. Moreover, we demonstrate that generic models can exhibit high performance on small amounts of test data (2-8 min), if they are trained on a sufficiently large data set. As such, they may be particularly useful for clinical and multi-task study designs with limited recording time. Finally, we show that the regularization procedure used in fitting TRF models can interact with the quantity of data used to fit the models, with larger training quantities resulting in systematically larger TRF amplitudes. Together, demonstrations in this work should aid the learning process of new users of TRF analyses, and in combination with other tools, such as piloting and power analyses, may serve as a detailed reference for choosing acquisition duration in future studies.

Keywords: electroencephalography; temporal response function (TRF); regularized linear regression; forward modeling; generic model; continuous speech processing; cortical tracking of speech; envelope processing; semantic processing

1. Introduction

Characterizing how acoustic and linguistic features are encoded in human cortex is a key goal of auditory cognitive neurosciences and neurolinguistics. In recent years, substantial progress has been made in utilizing noninvasive electroencephalographic (EEG) and magnetoencephalographic (MEG) responses to continuous speech in order to uncover a diverse set of neural signatures associated with different aspects of language processing. These range from responses to relatively low-level features associated with the speech envelope (e.g., Ding and Simon, 2012; Power et al., 2012; Kong et al., 2014), mid-level features implicated in phonemic processing (e.g., Di Liberto et al., 2015, 2019; Brodbeck et al., 2018), and higher-order linguistic features associated with semantic and syntactic processing (e.g., Broderick et al., 2018; Weissbart et al., 2019; Donhauser and Baillet, 2020; Mesik et al., 2021; Heilbron et al., 2022).

An important catalyst for this work has been the popularization of regularized linear regression methods for mapping the relationship between features in the stimulus space and the brain response (Lalor and Foxe, 2010; Crosse et al., 2016). This relationship can be characterized in both the *forward* direction, mapping from the stimulus to the brain response, and the *backward* direction, specifying how to reconstruct stimulus features from patterns of brain activity. The forward modeling approach models the continuous M/EEG data as a convolution between a set of to-be-estimated feature-specific impulse responses, known as the *temporal response functions* (TRFs), with the known time courses of the corresponding features (e.g., acoustic envelope, lexical surprisal, etc.). These analyses contrast with the more traditional event-related potential (ERP) method, which relies on averaging of hundreds of identical trials in order to estimate the stereotypical neural response for a given stimulus (e.g., Luck, 2005; Woodman, 2010). Unlike ERP methods, which rely on repetition, the TRF approach allows for analyzing brain responses to naturalistic time-varying stimuli, including continuous speech and music.

While the popularity of TRF methods has increased substantially, there remains a relative lack of literature exploring how these methods perform in the context of EEG and MEG analyses under various constraints, such as the type of features utilized (e.g., temporally sparse vs. dense) or the quantity of the data to which the models are applied. This information resource gap has more recently received some attention (Sassenhagen, 2019; Crosse et al., 2021), but published work has provided a broader overview of issues in TRF research (e.g., effects of correlated variables, missing features, preprocessing choices, etc.) without a more thorough examination of any one issue. As such, there is a continued need for further methodological resources aiding researchers interested in adopting TRF techniques to learn using these methods, and to optimize their experimental design for their efficient use.

One of the most fundamental decisions in study design is the choice of how much data to collect (i.e., number of subjects and acquisition duration per subject). This decision has broad consequences affecting the cost of the study, complexity of applicable models, data quality (due to fatigue / comfort level changes over the course of long experimental sessions), and others. With respect to TRF modeling, understanding how analysis outcomes are influenced by

data quantity is important for making decisions about duration of data acquisition. Specifically,
at the low end of the spectrum (small amounts of data), TRF models may be unable to isolate
neural responses of interest due to poor data signal-to-noise ratio (SNR) and/or limited
sampling of the stimulus feature space used in the analysis. At the upper end of the spectrum
(large amounts of data), model performance may saturate, making additional data wasteful
both in research costs and subject discomfort. Understanding these tradeoffs is particularly
important for studies of special populations, such as the elderly or clinical patients, who may
not tolerate longer experimental sessions.
To date, majority of work exploring effects of data quantity on analyses of speech-
evoked EEG data have focused on attention decoding, especially with *backward* models (e.g.,
Mirkovic et al., 2015; O'Sullivan et al., 2015; Fuglsang et al., 2017; Wong et al., 2018). However,
because the driving force behind the interest in attention decoding is innovation in hearing aid
technologies, much of this work has focused on the performance of trained models on
decoding attention using limited amount of data. In other words, majority of this work has
explored the effects of data quantity at the level of model *evaluation*, rather than on the model
training itself (but see Mirkovic et al., 2015)*.* In the context of forward modeling, the effect of
training data quantity on model performance has only received a limited amount of attention.
Di Liberto and Lalor (2017) explored the impact of data acquisition duration on the
performance of TRF models of phonemic processing, to assess whether small amounts of data
can reliably support detection of phonemic responses in individuals. They showed that although
models trained on data from individual participants required 30+ min to detect these signals,
generic models derived from data from multiple participants could detect signals related to
phonemic processing with as little as 10 min of data per participant. More recently, in their
overview of TRF methods, Crosse et al. (2021) used simulations to demonstrate the impact of
noise and data quantity on a single-feature TRF prediction accuracies and the fidelity of the
derived TRFs. However, beyond these works, a more thorough exploration of TRF forward
model performance in the context of more realistic listening scenarios, with a more diverse set
of modelled speech features has not been performed thus far.
The goal of the present work is to provide a detailed, practical demonstration of how
data quantity and model feature sparsity affect the outcome of TRF analyses in the context of
real noninvasive EEG responses to a dual-talker continuous speech paradigm (Mesik et al.,
2021). In a series of analyses, we repeatedly fit TRF models to progressively larger segments of
the data, estimating both individual subject models, as well as generic models based on data
pooled across multiple subjects. For each analysis, we demonstrate how data quantity
influences TRF estimates, overall model prediction accuracy, and prediction accuracy
attributable to individual features. Additionally, we show the effect of the interplay between
data quantity and regularization on the amplitudes of resulting TRF estimates. Given the unique
nature of each auditory study (design, analyses, etc.) and the rapid innovation in the TRF
methods, we caution readers against taking our work as a sole prescription for how much data
should be collected in future TRF studies, or how the resulting data should be analyzed. Instead,
we believe our work should serve as a detailed demonstration of general patterns of TRF model

performance as a function of data quantity, and a reference that should be carefully used in
conjunction with other tools and sources of information (e.g., piloting and power analyses) for
informing study design and the subsequent analyses.
127
128 **2. Materials and Methods**
129 EEG data used in the present manuscript was acquired and previously analyzed to investigate
130 age effects in cortical tracking of word-level features in competing speech (Mesik et al., 2021).
131 Extensive description of the details associated with the experiment and the data are openly
132 accessible in the original manuscript. For brevity, we highlight key aspects of this data below.
133
2.1 Participants
Data from 41 adult participants (18-70 years old, mean ± SD age: 41.7±14.3 years; 15 male, 26
female) was used in the present study. The broad age range was utilized to assess age effects
on speech-driven EEG responses in the original study. Consequently, a subset of participants (n
= 18) had mild-to-moderate hearing loss (HL), largely concentrated in the high-frequency region
(≥ 4 kHz), which was compensated for via amplification. All participants provided a written
informed consent and received either course credit or monetary compensation for their
participation. The procedures were approved by the Institutional Review Board of the
University of Minnesota.
143
2.2 Stimuli
Stimuli were four public-domain short-story audiobooks (*Summer Snow Storm* by Adam Chase;
Mr. Tilly's Seance by Edward F. Benson; *A Pail of Air* by Fritz Leiber; *Home Is Where You Left It*
by Adam Chase; source: LibriVox.org) read by two male speakers (2 stories per speaker). Each
story had a duration of approximately 25 minutes. Stories were pre-processed to truncate silent
gaps exceeding 500 ms to 500 ms, and the levels in each one-minute segment were root-mean-
square normalized and scaled to 65 dB SPL. In participants with HL, the audio was then
amplified to improve audibility at frequencies affected by HL (see Mesik et al., 2021 for details
of amplification). Stimuli were presented using ER1 Insert Earphones (Etymotic Research, Elk
Grove Village, IL).
154
2.3 Experimental procedure
Participants completed two experimental runs in which they listened to pairs of simultaneously
presented audiobooks narrated by different male talkers. The stories were presented at equal
levels (i.e., 0 dB SNR) and were spatially co-located (i.e., diotic presentation of same stimuli to
the two ears). One story was designated as the target story and participants were instructed to
attend to the target talker for the duration of the experimental run, while ignoring the other
talker. Runs were divided into 1-minute blocks, each of which was followed by a series of four
multiple-choice comprehension questions about the target story, along with several questions
about the subjects' state of attentiveness and story intelligibility. This behavioral data was not
analyzed in the context of the present manuscript. In the second experimental run, participants

listened to a new pair of stories spoken by the same two talkers, with the to-be-attended and
to-be-ignored talker designations switched, to eliminate talker-specific effects in the analysis
results. The order of the story pairs as well as the to-be-attended talker designations were
counter-balanced across participants. All experimental procedures were implemented via the
Psychophysics Toolbox (Brainard, 1997; Pelli, 1997; Kleiner et al., 2007) in MATLAB (Mathworks,
Natick, MA, United States; version R2019a).
171
2.4 EEG procedure
Data were acquired using a non-invasive 64-electrode BioSemi ActiveTwo system (BioSemi B.V.,
Amsterdam, The Netherlands), sampled at 4096 Hz. Electrodes were placed according to the
international 10-20 system. Additional external electrodes were used to obtain activity at
mastoid sites, as well as a vertical electro-oculogram. Data from these external electrodes were
not analyzed in the present study.
178
2.5 EEG preprocessing
Here we include a brief overview of pre-processing steps applied to the data. For more detailed
description of pre-processing, see Mesik et al. (2021). Unless otherwise stated, pre-processing
steps were implemented using the EEGLAB toolbox (Delorme and Makeig, 2004; version
14.1.2b) for MATLAB. To reduce computational load, raw data were downsampled to 256 Hz
and band-pass filtered using *pop_eegfiltnew* function between 1 and 80 Hz using a zero-phase
Hamming windowed sinc FIR filter (846[th] order, 1 Hz transition band width). Next, the data
were pre-processed using the PREP pipeline (Bigdely-Shamlo et al., 2015), in order to reduce
the impact of noisy channels on the referencing process. This procedure involved three stages:
1) power line noise removal via multi-taper regression, 2) iterative referencing procedure to
detect noisy channels based on abnormally high signal amplitude, abnormally low correlations
with neighboring channels, poor predictability of channel data based on surrounding channels,
and excessive amount of high-frequency noise, and 3) spherical-interpolation of the noisy
channels detected in stage 2. For this procedure, we used the default parameters outlined in
Bigdely-Shamlo et al. (2015). Following up to 4 iterations of stages 2-3 (or until no further noisy
channels were identified), the cleaned estimate of global mean activation was used to
reference the dataset.
Subsequently, we epoched all 1-minute blocks and applied independent component
analysis (ICA; Jutten and Herault, 1991; Comon, 1994) to remove components of data
corresponding to muscle artifacts and other sources of noise. ICA decomposes EEG signal into a
set of statistically independent components that reflect various underlying contributors to the
channel data (e.g., eye blinks, different aspects of cognitive processing, etc.), allowing for
removal of components driven largely by nuisance factors such as muscle activity.
The data were then band-pass filtered between 1 and 8 Hz using a Chebyshev type 2
filter (80 dB attenuation below 0.5 Hz and above 9 Hz, with 1 dB band-pass ripple), applied with
the *filtfilt* function in MATLAB. This was done given the existing evidence that cortical speech
processing mechanisms track speech predominantly via low-frequency dynamics in the 1-8 Hz

range (e.g., Ding and Simon, 2012; Zion Golumbic et al., 2013). Finally, the data were
transformed into z-scores to account for variability in overall response amplitudes due to inter-
subject variability in nuisance factors such as skull thickness. Data from the first block of each
run were excluded from analysis due to a small subset of participants accidentally confusing the
attended and ignored speakers in the initial block (this became apparent during behavioral task
following the first block, which pertained to the to-be-attended story).
212
2.6 TRF analyses
The time courses of speech-evoked responses, or TRFs, were extracted from the pre-processed
EEG data using regularized linear regression (i.e., ridge regression), implemented via the mTRF
Toolbox (Crosse et al., 2016, version 2.3). Briefly, TRFs are estimated by regressing a set of n
time-lagged copies of the time series of a given speech feature (e.g., acoustic envelope) against
the EEG time course at m channels. This results in m separate TRFs, each representing how the
response at a given electrode site is affected at the n time lags relative to that feature's
presentation times. This procedure can be simultaneously applied to multiple features (see
section 2.6.3 for details of features used in our analyses), enabling the decomposition of EEG
signals into contributions from different stages of speech processing (e.g., acoustic vs. semantic
processing). Due to the non-white spectral content of speech signals, the TRF estimation
procedure is prone to high degree of variance in the resulting TRFs (Crosse et al., 2016).
Regularized (ridge) regression introduces a "smoothing" bias into TRF estimation by penalizing
large regression coefficients, resulting in the reduction of this (undesirable) variance. Note that
other methods of TRF estimation procedures, such as "boosting" (David et al., 2007; Brodbeck
et al., 2021), rely on alternative approaches to regularization. These alternative methods were
beyond the scope of this work, although recent work directly comparing these methods
suggests that they typically produce highly similar results (Kulasingham and Simon, 2022).
To minimize overfitting, the regression procedure was implemented using leave-one-
trial-out cross-validation in which all-but-one (training) trials or subjects (see sections 2.6.1 and
2.6.2 for details) were used to estimate the TRFs, and the remaining held-out (test) trial/subject
was used to evaluate the prediction accuracy of the estimated model parameters. In the fitting
stage of each cross-validation loop, the data were first used to select the optimal regularization
(ridge) parameter λ. This was done via a separate leave-one-out cross-validation loop utilizing
only the training trials. In each of these cross-validation folds, the model was fit using a range of
different λ parameter values and evaluated by predicting the data from the left-out trial. The
prediction accuracies for each λ value were then averaged across all cross-validation folds and
electrodes. The λ corresponding to the highest average prediction accuracy was used in the
final fit to the entire training set. The resulting fit was then evaluated on the held-out "test"
trial or subject to determine the ability of the TRF model to predict EEG responses to speech.
The Pearson's correlation between the predicted and the actual data represents the prediction
accuracy. This procedure was repeated j-times, where j denotes the number of trials or
subjects, each time holding out data from a different trial/subject, resulting in j sets of TRF
estimates and prediction accuracies.

In addition to overall model prediction accuracies, we further estimated the degree to
which each feature contributed to the model performance. Briefly, this was done by comparing
the full model's prediction accuracy to "reduced" model prediction accuracies, which were
obtained by fitting models in which individual features were excluded. For example, to estimate
contribution of feature "A" in a model containing features "A" and "B", we computed the
prediction accuracy difference between model containing both features, to model containing
only the feature "B". In other words, the additional predictive power of a full model over a
reduced model can be interpreted as reflecting the contribution of the extra feature present in
the full model. In the remainder of this manuscript, these differentials are referred to as
feature-specific model contributions.
The main goal of the present work was to explore how estimates of cortical responses
to a range of speech features are influenced by the quantity of EEG data included in the
analysis. To explore this question, we iteratively applied identical sets of analyses to
progressively larger amounts of the pre-processed EEG data. This was done via two distinct
analysis approaches: 1) subject-specific analyses, where data from each participant was fit
independently, and 2) generic analyses, where data from multiple subjects were fit jointly.
Below we provide details of each analysis approach.
264
2.6.1 Subject-specific analyses
The subject-specific analyses involved repeated TRF estimation using data from individual
subjects with progressively larger amounts of their data. Cross-validated fitting procedure was
repeated with 11 distinct data quantities (3, 4, 6, 8, 10, 14, 18, 24, 30, 36, and 42 min of data),
with data in each analysis selected in chronological order to reflect real constraints of data
collection. While this may potentially bias analysis outcomes via temporally systematic
phenomena such as fatigue or adaptation, such order effects are a natural aspect of most
experiments and thus reflect realistic data acquisition scenarios. The data quantities in this, as
well as generic analyses (see section 2.6.2), were chosen to be spaced quasi-logarithmically to
more densely sample changes in model performance at relatively low data quantities, under
the assumption that at larger data quantities performance would begin to saturate. Group-level
analyses were performed using each subject's average TRFs and prediction accuracies across all
cross-validation folds (see section 2.6.4).
278
2.6.2 Generic subject analyses
In generic subject analyses, we repeatedly estimated TRFs using data pooled across
progressively larger number of subjects. Cross-validated model fitting was again repeated with
11 distinct numbers of subjects (3, 4, 6, 8, 10, 14, 18, 24, 30, 36, and 41 subjects) at three
distinct data acquisition durations per subject (2, 4, and 8 min), yielding 33 unique analysis
outputs per model. The data per subject was constrained both because of memory limitations
for analyses involving larger numbers of subjects, but also to explore the extent to which small
amount of data per subject can support accurate TRF estimation and robust prediction
accuracies.

A notable limitation of generic analyses, as implemented here, is that all of the data is
utilized within a single cross-validation procedure, resulting in a single set of average prediction
accuracy and TRF estimates. While individual subject prediction accuracies from cross-
validation can be used for group level statistics, these statistics are highly susceptible to noise
from outlier data when utilizing small numbers of subjects. As such, to assess the central
tendencies of generic analysis performance more accurately as a function of subject count, we
utilized a resampling approach to obtain distributions of model performances for each sample
size. Briefly, for each analysis (i.e., sample size), we randomly resampled, with replacement,
participant data 20 times, and used leave-one-subject-out cross-validation procedure to fit each
such resampled data set with a TRF model. We then used the mean TRFs and prediction
accuracies across the cross-validation folds for further analyses, yielding 20 sets of TRFs and
prediction accuracies for each sample size, model, and per-subject data quantity. Note that the
20 resamplings were performed independently at each sample size, rather than being done in a
dependent manner via incremental sampling (with increasing sample size) of more participants
into the to-be-analyzed data pool. To obtain maximally comparable full and reduced model
performances for estimating feature-specific model contributions (see section 2.6, paragraph
3), we utilized identical sets of resampling indices (i.e., same participant data) for full and
reduced models.
To aid statistical evaluation of the analyses (see section 2.7.2) we corrected the model
prediction accuracies using estimates of the noise floor, i.e. range of prediction accuracies that
may be expected by chance, by mismatching regressor-data pairings and computing their
corresponding prediction accuracies. This was done at the level of each cross-validation fold
(i.e., held-out subject), where we computed prediction accuracies for each 1-min data segment
for all mismatched regressor-data pairings. Each subject's true prediction accuracy was then
noise-floor corrected by subtracting the average mismatched prediction accuracy. Results of
the 20 resampling analyses were then interpreted as a distribution of mean TRFs and prediction
accuracies expected for a given sample size. Because each of the 20 iterations corresponded to
5% of the analyses, results in which all 20 analyses showed consistent results (e.g., same sign of
prediction accuracies) were interpreted as statistically significant (albeit at a level uncorrected
for multiple comparisons). Note that to allow for more reliable statistical inference, bootstrap-
based analyses such as these are typically performed ≥1000 times in order to more precisely
estimate the degree of overlap between the distributions of parameter estimates for different
conditions. However, because the goal of this work was to demonstrate general behavior of TRF
analyses rather than to draw strong statistical conclusions about our data, and the
computational load of running ≥1000 resamplings for each of the 66 analyses (2 models x 11
subject counts x 3 data quantities/subject) would have been very high, we chose to perform the
more modest bootstrap procedure with 20 iterations.
325
2.6.3 Modelled speech features
To explore effects of feature choice on subject-specific and generic model performance, each
modeling approach was evaluated using two distinct models of *attended* speech processing

that emphasized features with different levels of sparseness. In the denser "envelope" model
we included a continuously varying log-transformed acoustic envelope, along with a sparse
word-onset regressor intended to capture responses to acoustic onsets and lexical
segmentation. The sparser "surprisal and SNR_{word}" model included lexical surprisal for each
word, SNR of each attended word against the to-be-ignored speaker, and the word-onset
regressors. While lexical surprisal has been shown to be robustly tracked by cortical language
processing mechanisms (e.g., Weissbart et al., 2019; Heilbron et al., 2022), SNR_{word} is a
relatively unexplored feature in the context of TRF literature. We chose to include it to reflect
the fact that the attended talker's intelligibility fluctuated on a moment-to-moment basis due
to the independent variations in the relative attended and ignored talkers' speech intensities.
The "glimpsing" models of speech understanding have proposed that in speech-on-speech
masking scenarios, time periods with relatively high SNR (i.e. "glimpses") may serve a privileged
role in speech perception, with information from glimpsed periods being used to fill-in
information from masked portions of speech (e.g., Cooke, 2006).
Word-onset regressors were included in both models primarily to help account for
onset-driven neural activity, which is known to have particularly large amplitudes. While speech
signals generally contain numerous onsets beyond those found at word onsets, these occur
largely at faster rates (up to 50 Hz; e.g., Stone et al., 2010) than the 1-8 Hz range analyzed here.
As such, we abstained from utilizing envelope onset regressors (e.g., half-wave rectified
envelope derivative), as they would fall outside the passband of low-rate envelope
representations, and thus would not contribute to model prediction accuracies. This was
confirmed in a supplemental analysis, where envelope onset representations did not provide
additional predictive power in the 1-8 Hz frequency band (results not shown).
Besides their level of sparseness, the two feature sets also differed in terms of the
modelled response latencies, as envelope responses have previously been shown to occur
largely at relatively low latencies < ~300 ms (e.g., Power et al., 2012; Kong et al., 2014; Fiedler
et al., 2019), while responses to sparser, higher-order features occur at longer latencies (e.g.,
Weissbart et al., 2019; Mesik et al., 2021). Responses to features in the denser model were
therefore modelled using time intervals between -100 to 350 ms relative to feature onsets,
while responses to the features in the sparser model were modelled between -100 to 800 ms
relative to feature onset. Consequently, fitting the denser model to signal recorded by a
particular electrode resulted in estimation of 234 model beta coefficients (2 features × 117
samples, corresponding to the time lags above), whereas the sparser model resulted in 696
beta coefficients (3 features × 232 samples).
Across the two models, the four features were estimated as follows. The word onset
regressors contained unit-amplitude impulses time-aligned to the onset of each word. The low
frequency acoustic envelopes were extracted by half-wave rectifying the speech stimuli and
lowpass filtering this representation below 8 Hz. This representation was then log-transformed
to more closely approximate encoding of sound level in the human auditory system. Lexical
surprisal regressors were the negative logarithm of each word's probability given the multi-
sentence preceding context, as estimated using the GPT-2 artificial neural network (Radford et

al., 2019). SNR$_{word}$ regressors were obtained by computing the ratio of each word's root-mean-
square (RMS) of its acoustic waveform and the RMS of background speaker's acoustic
waveform. This was motivated by the increased importance of momentary glimpses of high
broadband SNR for speech understanding at low target-to-masker ratios (Best et al., 2019). As
with envelopes, these ratios were log-transformed to more closely mimic sound level encoding
in the human auditory system. Features in both surprisal and SNR$_{word}$ regressors utilized the
same timing as word-onset regressors, as prior work has shown that onset timing results in
reasonable characterization of responses to higher-order speech features (e.g., Broderick et al.,
2018; Weissbart et al., 2019; Mesik et al., 2021). Finally, non-zero regressor values for all
features were RMS scaled to have an RMS value of 1. This was done to make TRFs for different
features more similar in amplitudes in order to optimize regularization performance. With the
exception of the acoustic envelope, a more detailed description of the derivation of these
features can be found in Mesik et al. (2021).
Note that different features were separated into the denser and sparser models for the
practical purpose of exploring how performances of models with distinct levels of sparseness
vary as a function of data quantity used in fitting. However, outside of this context, pooling
features into larger models (e.g., containing both acoustic and linguistic features) can generally
be advantageous, especially for more accurate estimation of feature-specific model
contributions (e.g., Gillis et al., 2021; see section 4.4.5).
389
2.6.4 Regions of interest
Due to the relatively low spatial resolution of EEG data and for simplicity of analysis result
presentation, we chose to limit the spatial dimensionality of the results to two regions of
interest (ROIs), the frontal and parietal ROIs. These ROIs were chosen based on the peak
locations of activation for the two models. Both ROIs contained 13 electrodes, which
symmetrically surrounded electrode Fz in the frontal ROI (i.e., AF3, AFz, AF4, F3, F1, Fz, F2, F4,
FC3, FC1, FCz, FC2, and FC4), and electrode Pz in the parietal ROI (i.e., CP3, CP1, CPz, CP2, CP4,
P3, P1, Pz, P2, P4, PO3, Poz, and PO4). ROI-specific TRFs and prediction accuracies were
computed by averaging TRF analysis results from these sets of electrodes. All statistical analyses
were performed on these ROI-averaged results. Note that the choice of ROI-based analyses was
driven primarily by the simplicity of data presentation, for educational purposes. TRFs of
individual features may potentially perform better at specific electrode sites not directly
analyzed here.
403
2.7 Statistical analysis
2.7.1 Statistical analyses of Subject-specific models
The primary goal of this work was to describe general patterns of TRF model behavior as a
function of data quantity used in model fitting. For subject-specific analyses, to test whether a
given quantity of data was sufficient for the derived TRF to yield prediction accuracies that were
significantly greater than zero, we utilized either t-tests or Wilcoxon signed-rank test, based on
the outcome of the Anderson-Darling test of normality. These tests were conducted at the

group level, using all 41 individual prediction accuracies. To normalize the distribution of
correlation coefficients, their values were Fisher z-transformed prior to conducting the
statistical tests. Note that statistics were not corrected for multiple comparisons, as we treated
the analysis of each data quantity as a quasi-independent experiment, emulating the scenario
where only that amount of data was acquired. Because analyses on different data quantities
were not independent due to utilizing partially overlapping data, we abstained from direct
pairwise comparisons of model prediction accuracies, and instead focused on more general
description of model performance patterns (e.g., trajectory of mean model performance and
between-subject variance) as a function of data quantity. However, in order to provide a
statistical description of linear changes in model performance as a function of data quantity, we
fit linear mixed effects models (LMM) to the prediction accuracy results (as well as each
feature's unique model fit contributions), with a fixed effects of training data quantity, ROI, and
a random effect of participant identification number. In all LMM analyses, training data
quantity was treated as a continuous numeric variable, while ROI was treated as a categorical
variable. Significance of these models were assessed using LMM ANOVA (type 3) and
Satterthwaite approximation for degrees of freedom.
We additionally used the subject-specific model fits to explore the relationship between
the size of participant pool and the data quantity per subject required to achieve statistically
reliable detection of cortical tracking of attended speech for different significance levels. To do
this, we utilized subject pool sizes ranging from 2 to 41 subjects, and for each pool size, we
resampled with replacement the prediction accuracies from analyses of each training data
quantity (i.e., minutes of data per participant) 10,000 times. Within these samples, we
conducted t-tests on results derived from each of the 11 data quantities per subject, searching
for the minimum data quantity for which at least 80% of the 10,000 analyses exceeded the t-
score thresholds corresponding to $p < 0.05$, $p < 0.01$, and $p < 0.001$. For these analyses we used
parametric statistics, although non-parametric tests resulted in similar patterns of results.
437
2.7.2 Statistical analyses of generic models
For generic analyses, we estimated prediction accuracy noise floors as described in section
2.6.2. Within each cross-validation fold of each resampling analysis, we computed the
difference between the true prediction accuracy and the "mismatched" prediction accuracy
estimated using mismatched regressor-data pairings for the held-out participant. Thus, the
distribution of these corrected prediction accuracies across resampling analyses reflects the
proportion of times in which the true regressor-data pairings enabled more accurate data
predictions than mismatched-pairings. Given that our analyses included 20 resamplings, only
analyses where all data points exceeded the 0-point were deemed to be significant (i.e., since
1/20 corresponds to 5%). Note that noise floor correction in generic analyses was motivated by
the possibility that very small positive prediction accuracies could occur by chance, making it
difficult to determine the proportion of analyses with reliably elevated prediction accuracies.
This correction was particularly important given our use of only 20 resampling analyses. In
principle, this approach could also be used in subject-specific analyses. However, we abstained

from the use of noise floors in subject-specific analyses because of their greater statistical
power (i.e., more independent data points), our use of cross-validation, and the observation
that in generic analyses, noise floor prediction accuracies were concentrated around zero.
To test for linear increase in prediction accuracy as a function of number of participants
used in generic analyses, we fit linear functions to the patterns of generic model prediction
accuracies. Due to the dependent nature of the 20 resampled estimates of prediction
accuracies at each training data quantity, we used a separate bootstrap analysis approach to
establish the likelihood of observing a positive slope relating training data quantity and
prediction accuracies. Specifically, on each bootstrap iteration we randomly selected one result
from the pool of resampling analyses for each training data quantity, and fit a two-parameter
linear function (slope and intercept) to the obtained series of 11 prediction accuracies. We
repeated this procedure 1000 times, each time storing the slope of the linear fit. Finally, we
deemed the result of each such analysis significant if >95% of obtained slopes were greater
than zero. This procedure was done separately for noise floor-corrected overall prediction
accuracies at each training data quantity per subject, as well as the corresponding feature-
specific model contributions, of both the denser and sparser models.
For each model type and feature set, we assessed the similarity of TRFs derived using
different data quantities by computing pairwise Pearson's correlations between time courses of
the TRFs. Additionally, we assessed the extent to which subject-specific and generic analyses
resulted in estimation of morphologically similar TRFs by computing Pearson's correlations
between these TRFs. For these analyses, we focused on models that utilized the greatest
amounts of minutes (subject-specific analyses) and subjects (generic analyses). Because edge
artifacts are commonly observed in beginning and end TRF samples, all TRFs were trimmed by
25-ms at each end when computing TRF similarities, as well as for visualization purposes.
476
3. Results
We explored the effects of training data quantity on performance of TRF models trained and
evaluated on data from individual subjects (section 3.1), or trained on aggregate data of
multiple subjects and evaluated on different subjects (section 3.2). Below we discuss each
modeling approach in terms of its prediction accuracies, feature-specific model contributions,
and the recovered TRFs.
483
3.1 Subject-specific analyses
In subject-specific analyses, each participant's data was fit individually using each of the two
models and evaluated on held-out data from the same participant. Group-level pattern of
overall model prediction accuracies as a function of data quantity is depicted in Fig 1 for the
denser (Fig 1A) and sparser (Fig 1B) models. In general, increases in training data quantity
resulted in monotonic increases in performance for both models (LMM ANOVA: effect of data
quantity at $p < 0.001$ for both models; See Supplementary Table 1), along with reductions in
inter-subject variability in prediction accuracies. With 41 participants used in these analyses,
both models reached high degree of statistical significance with as little as 5 minutes of data

per participant. However, at low training data quantities (e.g., < 10 min), a subset of
participants exhibited prediction accuracies (i.e., correlations between the predicted and actual
EEG data) that did not exceed 0. At larger data quantities (e.g. > 20 min), prediction accuracy
distributions were elevated and largely did not span the value of zero.
497
498

499
Figure 1. Overall subject-specific model prediction accuracies for the denser (A; onset and
envelope features) and sparser (B; onset, surprisal, and SNR_{word} features) models displayed as a
function of training data quantity (data acquisition duration). The violin plots depict the
distribution of these values for all 41 participants, with a box plot depiction (interquartile range)
shown within each violin. Red circles denote median values of the distributions. The

uncorrected significance levels of each statical comparison against zero are displayed at the top
of each plot: * p < 0.05, ** p < 0.01, *** p < 0.001
507
Although overall prediction accuracy is a key metric in evaluating TRF model
performance, it does not reflect the extent to which individual features in the model uniquely
contribute to this accuracy. To assess the unique contributions from individual features, we
compared the full model prediction accuracies to those estimated using reduced models
containing all-but-one feature. Model fit contributions from individual features (i.e., change in
prediction accuracy due to adding a given feature) as a function of training data quantity are
depicted in Fig 2 for the denser and Fig 3 for the sparser models, respectively. In contrast to
overall prediction accuracies, feature-specific contributions showed a less pronounced increase
as a function of data quantity used in model fitting (see Supplementary Table 2), especially in
the case of the sparser model, although generally models trained with more data allowed for
more robust detection of unique contributions of individual features. Notably, the dense
envelope feature (Fig 2, bottom) had substantially higher model prediction accuracies than
either the onset feature in the dense model, or any of the sparse features (Fig 3). Accordingly,
highly significant detection of unique contribution of acoustic envelope was possible with mere
minutes of data. In the sparser model, highly significant model fit contributions were observed
only at relatively large training data quantities (> ~17 min) for the word onset feature frontally,
and lexical surprisal parietally. For SNR_{word}, weakly significant contributions were observed
sporadically, with no systematic relation to data quantity. In fact, at very low data quantities,
inclusion of SNR_{word} in the model led to a small decrease in prediction accuracies, likely due to
the full model having too many parameters relative to the training data quantity. As such, with
the available data quantity and the chosen method for estimating feature-specific model
contributions, we were only able to detect reliable model contributions for two out of three
features of the sparser model.
In addition to prediction accuracies, a key output of TRF models are the TRFs
themselves: the impulse responses to each of the modelled features. Fig 4 shows TRFs for the
denser model and Fig 5 shows TRFs for the sparser model. Mirroring the high prediction
accuracies and feature-specific model contributions, the denser model TRFs (Fig 4) showed a
high degree of morphological similarity across the different data amounts, albeit with a
systematic increase in amplitudes seen with increasing data quantity (for easier comparison
across data quantities, see Supplementary Fig S1). In line with its lower feature-specific model
contributions, the sparser model TRFs (Fig 4; Supplementary Fig S2) generally exhibited greater
noisiness at low data quantities, with TRFs reaching stable form once substantial data quantity
(> 17 min) was used in model fitting. These qualitative observations were supported using
correlational comparisons of TRF time courses derived using different training data quantities
(see Supplementary Figs S3-4 for correlation matrices for denser and sparse models,
respectively). While there was a trend for lower TRF amplitudes with increasing data quantity,
this pattern is opposite to that seen for the denser model and generally appears less systematic
than that seen in Fig 4. Additionally, for both the denser and sparser models, RMS amplitudes

of the TRFs showed significant positive correlations with the feature-specific model
contributions, particularly in models trained on large data quantities (data not shown). This
supports the often assumed association between larger TRF amplitudes reflecting higher
predictive power.
The systematic increase in TRF amplitudes seen in Fig 4 could, in principle, reflect a
genuine neural phenomenon related to the chronological inclusion of data into models trained
on more data. For example, it could reflect improved neural tracking of the target audiobook
over the course of the study session. However, examination of the regularization parameter
(Fig 6A), which controls the penalty assigned to large TRF values during the fitting procedure,
indicates a systematic decrease in this parameter with increasing data quantity. In other words,
models fitted to greater data quantity penalized large TRF amplitudes less, likely resulting in the
systematic increase in their amplitudes seen in Fig 4. This interpretation was supported by a
supplemental analysis (not shown), in which we fit the denser TRF model using a 6-min moving
window to assess whether the TRF amplitude changes over the course of the study session. This
analysis revealed virtually identical TRF amplitudes in all analysis windows, lending support to
the effect in Fig 4 being entirely technical in nature. Regularization parameter of the sparser
model (Fig 6B) showed a similar systematic decrease with increasing data quantity without the
corresponding increase in TRF amplitudes (Fig 5). This may reflect the overall greater noisiness
in these TRFs at low data quantities (see Supplementary Fig S4), as well as greater similarity in
general TRF amplitudes across the three features (in contrast to the larger amplitude
discrepancy between onset and envelope TRFs seen in Fig 4).
Although utilization of data from all participants for analyses in Figs 1-6 provides the
most accurate estimates of the average model performance for different training data
quantities, it is less informative about the statistical performance of our TRF models with more
limited samples. To provide a more complete description of how subject-specific models
perform under more limited sample sizes, we performed a resampling analysis using subsets of
participant from our 41-subject pool. More specifically, for each participant pool ranging from
2-41 participants, we resampled (with replacement) the subject-specific result pool 10,000-
times at each of the data quantities and determined how many minutes of data per participants
were required to reach significance in at least 80% of analyses at three commonly used
significance thresholds ($p < 0.05$, 0.01, and 0.001). The results of these analyses are shown in
Fig 7 for overall prediction accuracy, and Fig 8 for feature-specific model contributions. These
results show the expected downward sloping pattern whereby larger participant pools require
smaller amount of data per participant. Additionally, these results mirror those in Figs 1-3 in
that the sparser model generally requires more data per participant, and capturing significant
feature-specific model contributions requires both more participants and more data per
participant. In fact, across the features in the sparse model, resampling analyses revealed that
model contributions could only be reliably detected for the word onset feature frontally, and
for lexical surprisal frontally and parietally (Fig 8B; note that frontal surprisal contributions are
not shown, as these were only detectable with 40+ participants at 17+ min of data, at the
lowest significance level of $p < 0.05$). Finally, while patterns of minimum data per participant

required to reach significance from Figs 1-3 (i.e., when n = 41) are similar to those in Figs 7-8
(rightmost data points in each plot), in some cases the exact minutes per participants (or
significance levels) don't match between the two, since the true participant sample in Figs 1-3
corresponded to just one data point within the larger bootstrap distribution used for Figs 7-8.

591
Figure 2. Feature-specific model fit contributions as a function of training data quantity for the
denser model. Model fit contributions reflect the unique contribution of each feature to the
overall prediction accuracy of the full model, compared to reduced models in which those
features were excluded. Note the different scales of the contributions for the Onset (upper
row) and Envelope (lower row) features, with the latter fit contributions being about an order
of magnitude larger than the former. To facilitate visualization of the central portion of the
distributions, upper and lower limits of some of the violin plots for the "Onset" feature are
truncated. Asterisks denote significance levels as in Fig 1.
600

601
602 Figure 3. Feature-specific model fit contributions as a function of training data quantity for the
603 sparser model. The data presentation and significance markers are as in Fig 2.

Figure 4. Group-averaged TRF time courses of model beta coefficients for onset (top row) and
envelope (bottom row) features from the denser model in frontal (left column) and parietal
(right column) ROIs. TRFs estimated using different amounts of data are depicted in different
colors (see legend above the lower right plot). The small sharp deflections in envelope response
around t = 0 ms reflect mild leakage of electrical artifact from earphones into the EEG signal.
See also heatmap depiction of the TRFs in Supplementary Fig S1 for easier comparison across
different data quantities, and Fig S3 for correlation matrices comparing TRF morphologies
across different data quantities.

Figure 5. Group-averaged TRF time courses of model beta coefficients for onset (top row),
surprisal (middle row), and SNR$_{word}$ (bottom row) features from the sparser model in frontal
(left column) and parietal (right column) ROIs, as a function of training data quantity (see
legend in bottom right). Note that these TRFs contain a broader range of latencies than those in
Fig 3 due to these features engaging higher-order processing, reflected in key TRF features such
as the N400 response seen in parietal ROI. See also heatmap depiction of the TRFs in
Supplementary Fig S2 for easier comparison across different data quantities, and Fig S4 for
correlation matrices comparing TRF morphologies across different data quantities.

624
Figure 6. Distributions of subject-specific regularization parameters, lambda, from the denser
(A) and sparser (B) models, as a function of training data quantity. Red horizontal lines within
each box represent the median value while the lower and upper bounds of the blue boxes
depict the 25th and 75th percentiles of the distributions. To aid the visualization of where bulk of
the data points were, unusually large parameters (for a given data quantity) were marked as
outliers with red "+" symbols. Note: "a.u." denotes arbitrary units.
631

Figure 7. The amount of training data per participant required to reach significant overall prediction accuracy as a function of participant sample size for the denser (A) and sparser (B) TRF models in frontal (left column) and parietal (right column) ROIs. Different line colors represent different significance levels (see legend in lower right). For visualization purposes, minutes of data are shown on a log axis. The discrete steps along the y-axis stem from the fact that subject-specific analyses were run using 11 discrete data quantities per subject, the results of which were used in this resampling analysis. Therefore, values on the plots represent approximate threshold data quantities needed for each sample size.

Figure 8. Amount of training data per participant required to reach significant feature-specific contributions to model prediction accuracies, as a function of participant sample size for the denser (A) and sparser (B) TRF models in frontal (left column) and parietal (right column) ROIs. Note that for the sparser model, only feature-ROI combinations where significant feature-specific model contributions could be achieved are shown (except for surprisal in the frontal ROI, where $p < 0.05$ could be achieved with 40+ participants at 17+ min of data). Line colors represent different significance levels (see legend in lower right).

3.2 Generic analyses

In the second set of analyses, we explored the effects of subject count on performance of *generic* analyses using the same two models (with denser and sparser features; section 2.6.3) used for subject-specific analyses (section 3.1). In contrast to subject-specific analyses, generic models are simultaneously fit to data from multiple participants and evaluated on their ability to predict data of held-out participants. Due to the higher computational load of fitting models to multiple subjects simultaneously, these models were tested on 2, 4 and 8 minutes of data per participant. Figures 9-14 depict results of generic analyses analogous to those shown in Figures 1-6 for subject-specific analyses. Note that the two sets of results are not directly comparable, as the latter results depict distributions over, and averages of, the central tendency of 20 resampled generic analyses, rather than distributions of individual subject results. The lower variability in these analyses is therefore not directly indicative of generic analyses performing better than subject-specific analyses. The resampling approach used here was important due to inherent noisiness and strong influence of outlier data in analyzing small subject counts (see section 2.6.2).

Qualitatively, the generic model prediction accuracies (Fig 9) as well as model fit contributions (Figs 10-11) both exhibited apparent monotonically increasing performance and decreasing variability as the number of participants used to train the model increased. Because these plots depict distributions of average performances across 20 resampling analyses, only subject counts for which the entire distribution is elevated above zero can be deemed as reliably achieving significant non-zero performance. Quantitatively, however, bootstrap analyses of the linear relationship between the subject pool size used in model fitting and prediction accuracies (see section 2.7.2) only revealed a significant linear increase in overall prediction accuracies of the sparser model. None of the feature-specific model contributions in any ROI showed a significant relationship with the subject pool size. This is likely driven by the high variance of prediction accuracies with small numbers of participants. Nevertheless, it is evident from Figs 9-11 that model performance did improve with increasing participant pool, since significant prediction accuracies and feature-specific contributions were more consistently seen with increasing participant pools. Depending on the ROI, about 5-7 participants were needed to achieve reliably elevated overall model prediction accuracy, while substantially greater number of participants were needed to observe elevated feature-specific model contributions for different features in the denser and sparser models, respectively. A notable divergence between subject-specific and generic results was that in the former

683   analyses, feature-specific contribution of surprisal but not SNR_{word} reached significance (Fig 3),
684   whereas in the latter (Fig 11), SNR_{word} exhibited significant model contributions that were
685   detected in a greater number of analyses than contributions of surprisal.

686   Interestingly, comparisons of 2-, 4- and 8-min of data per subject used in model fitting
(different boxplot fill colors in each plot) made only a modest difference in performance, with
the models trained on more data per participant generally producing tighter performance
distributions, and reaching significance with fewer participants. However, it is noteworthy that
the prediction accuracies and feature-specific contributions of the sparse model (Fig 9B, and Fig
11, respectively) exhibited a trend of decreasing peak prediction accuracies with increasing per-
subject amount of training data (e.g., 8-min/subject models had slightly lower mean
performance than 2-min/subject models, especially with larger participant pools). The cause of
this is unclear and may warrant future exploration via analyses of different data (and feature)
sets.

696   TRFs derived from denser generic models, averaged across the 20 resampling analyses,
are depicted in Fig 12 (for easier comparison across data quantities, see heatmaps in
Supplementary Figs S5-7). These TRFs were highly stereotypical across different subject pool
sizes and the three per-subject data quantities (see supplementary Figs S11-S13 for correlation
matrices of pairwise comparisons of TRFs). In line with subject-specific analyses, there was
some evidence of increasing TRF amplitudes as the overall amount of data used to fit the model
increased (i.e., with increasing number of subjects; see TRFs depicted by different colors in each
subplot), although for envelope TRFs this effect diminished with increasing per-subject data
quantities. This general patterns of increasing TRF amplitudes was again accompanied by a
systematic decrease in the regularization parameters (Fig 14A). Notably, because most generic
models were trained on greater total amount of data than any of the subject-specific models
(for n > 20, n > 10, and n > 5, in models using 2-min, 4-min, and 8-min of data per subject,
respectively), the upper bound of regularization parameter values seen in generic analyses was
substantially lower than those seen in subject-specific analyses. These differences likely account
for the slightly weaker envelope TRF amplitude increases as a function of training data quantity
in generic analyses, compared to subject-specific analyses.

712   TRFs from the sparser model (Fig 13; Supplementary Figs S8-10) also exhibited a high
degree of similarity for models trained on different amounts of data, although they generally
show slightly higher degree of noisiness across different sample sizes than those derived using
the denser model (except for dense model's parietal onset TRFs; see supplementary Figs S14-
S16). Mirroring the slight decrease in prediction accuracies with increasing per-subject data
quantity (Fig 9B, Fig 11), there was an analogous decrease in TRF amplitudes (Fig 13, left vs right
pairs of columns). At the same time, we also observed a pattern of slight increases in TRF
amplitudes for models trained on more participants (i.e., different plot colors in each subplot of
Fig 13; see heatmaps in Supplementary Figs S8-10), mirroring the decreasing amplitudes of
regularization parameters in these analyses (Fig 14B). We speculate that this apparently
paradoxical discrepancy between effects of more data per participant vs more participants
could reflect tradeoff between phenomena driven by cognitive (e.g., waning attention or

increased adaptation) vs technical (i.e., decreasing regularization parameter with more data)
factors.
726
727
728

729
Figure 9. Noise floor-corrected generic model prediction accuracy distributions as a function of
training subject pool size, for denser (A) and sparser (B) models with 2-min, 4-min, and 8-min of
training data per subject (violin color; see legend in the lower left plot). The distributions
depicted by violin plots represent collection of mean prediction accuracies across 20 resampling
analyses (instead of across-subject variability seen in Figs 1-2). As such, only subject counts with
distributions with no overlap with zero are deemed to be significant at $p < 0.05$ (uncorrected).
Note that for each triplet of violins, the training subject pool is fixed with a value indicated by
the x-tick label below the central violin of the triplet.
738

739
Figure 10. Feature-specific generic model contributions as a function of training subject pool
size, for the denser model, with 2-min, 4-min, and 8-min of training data per subject (violin
color; see legend in the upper left plot).

Figure 11. Feature-specific generic model contributions as a function of training subject pool
size, for the sparser model, with 2-min, 4-min, and 8-min of training data per subject (violin
color; see legend in the lower left plot).

Figure 12. Average generic model TRF time courses for onset (top row) and envelope (bottom
row) features from the denser model trained with 2-min (left pair of columns), 4-min (middle
pair of columns), and 8-min (right pair of columns) of data per subject. TRFs estimated using
different amounts of data are depicted in different colors (see legend in the upper right plot).
Note that the sharp deflections in envelope response around t = 0 ms reflect mild leakage of
electrical artifact from earphones into the EEG signal.

Figure 13. Average generic model TRF time courses for onset (top row), surprisal (middle row),

and SNR_word (bottom row) features from the sparser model trained with 2-min (left pair of

columns), 4-min (middle pair of columns), and 8-min (right pair of columns) of data per subject.

TRFs estimated using different amounts of data are depicted in different colors (see legend

above the upper right plot).

Figure 14. Distributions of generic model regularization parameters, lambda, from the denser (A) and sparser (B) models, as a function of training data quantity. Details of visualization are as in Fig 6.

3.3 Similarity between subject-specific and generic TRFs

While subject-specific and generic analyses produced qualitatively similar TRFs (Figs 4 and 5 vs Figs 12 and 13), we sought to assess this similarity quantitatively using a correlation analysis (Fig 15). To this end, we focused on TRFs derived from the largest quantity of data in each analysis (including generic TRFs based on each of 2-min, 4-min and 8-min of data per subject), as these TRFs most accurately capture the underlying neural responses to each of the features. For each feature, we computed the Pearson's correlation between TRFs derived in subject-specific and generic analyses. This analysis confirmed that in vast majority of cases, the two analyses produce highly similar TRFs, only seldom deviating below r = 0.75, predominantly for sparser features in ROIs with relatively low TRF amplitudes (e.g., parietal onset and frontal

780 surprisal responses). These results demonstrate that at least for features modelled here,
781 subject-specific and generic analyses enable extraction of highly similar neural responses.
782

783
Figure 15. Similarity between average TRFs derived using subject-specific and generic analyses
for features in the sparser (A) and denser (B) models. For generic analyses, both the results
from analyses utilizing 2-min (left column), 4-min (middle column), and 8-min (right column)
per subject are shown. Different bar colors represent the frontal and parietal ROIs (see legend
in lower left plot). Note that these analyses utilized TRFs derived using models trained on
largest amounts of data in each type of analysis, i.e., most data per subject for subject-specific
analyses, and most subjects for generic analyses.
791

4. Discussion
4.1 Summary of goals and findings
TRF analyses (Lalor and Foxe, 2010; Crosse et al., 2016) of EEG and MEG data are increasingly
popular in studies of cortical responses to continuous, naturalistic stimuli such as speech (e.g.,
Di Liberto et al., 2015; Broderick et al., 2018; Weissbart et al., 2019) and music (e.g., Di Liberto
et al., 2020; Marion et al., 2021). However, relatively few informational and educational
resources demonstrating the behavior of these analyses under various constraints exist. Such
resources allow researchers who are new to TRF analyses or considering adopting them to gain

key intuition and insight to guide their study design. The goal of the present work was to
demonstrate how quantity of collected data, a key parameter in experimental design,
influences TRF analyses of attended speech representations in the context of a dual-talker
continuous speech paradigm. We addressed this question using a previously collected dataset
(Mesik et al., 2021) using two types of analyses: 1) Subject-specific analyses in which TRF
models are independently fit to each participant's data, and 2) Generic analyses in which data
from multiple participants is jointly used to fit a TRF model. For each analysis type we fit two
different models, one of which had temporally denser features (acoustic envelope model),
while the other had temporally sparser features (surprisal and SNR_{word} model). These models
were fit repeatedly to explore how the amount of data per participant and number of
participants influence model prediction accuracies in subject-specific and generic analyses,
respectively. Finally, we used correlation analysis to compare the similarity of the TRFs derived
in the two analysis approaches.
It is unsurprising that fitting models to more data resulted in monotonically improving
prediction accuracies and more reliable TRF estimates. However, a closer examination of our
results revealed several noteworthy phenomena. First, across both types of analyses, significant
prediction accuracies could be achieved with just minutes of data per participant (Figs 1 and 9),
although the denser model with envelope features had on average higher prediction accuracies
than the sparser model with word-level features. Second, in analyses of feature-specific
contributions to the overall prediction accuracies (Figs 2-3 and 10-11), we observed a marked
dissociation between denser and sparser models. Specifically, feature-specific model
contributions were generally much smaller for sparser features, and capturing these model
contributions required much greater amount of training data. However, it is noteworthy that in
generic analyses, even 2-4 minutes of data per participant were, in some feature-ROI
combinations, enough to reveal these feature-specific model contributions (Fig 11). This
demonstrates that signals related to sparse features may have sufficient signal-to-noise ratio to
be detected even with relatively small amounts of data, provided that the model is trained on a
sufficiently large dataset. Third, although TRFs derived with different amounts of data generally
showed a high degree of time-domain consistency, we observed a systematic increase in TRF
amplitudes with increasing data quantity (Figs 4-5, and 12-13). This pattern was mirrored by
systematic decreases in the regularization parameter (Figs 6 and 14), which reflects the degree
to which larger TRF amplitudes are penalized during model fitting. Finally, TRF patterns derived
using subject-specific and generic analyses were highly similar (Fig 15), demonstrating that the
two analyses reveal largely identical signatures of cortical speech processing.
834
4.2 Relationship to past literature
While most existing works utilizing TRF methods have used these tools to address specific
questions about the nature of speech and music processing, only a handful of studies have
explored the methodology itself. In general, the latter works focused on bigger picture
overview of TRF methods and their utility in speech processing (Crosse et al., 2016;
Sassenhagen, 2019), as well as on best practices in utilizing these methods in studies of special

and clinical populations (Crosse et al., 2021). Additionally, Wong et al. (2018) explored
performance of a range of regularization approaches for fitting forward and backward models
in the context of a growing body of attention decoding literature.
Most closely related to the present work, Di Liberto and Lalor (2017) investigated the
effect of data quantity on performance of subject-specific and generic forward models in the
context of phoneme-level speech processing. Similar to our results, Di Liberto demonstrated
that the ability of subject-specific models to capture responses related to the phonemic
processing improved with greater amount of data, with models requiring about 30 minutes of
data to do so reliably. Their generic model derived via averaging of subject-specific models was
able to capture phonemic responses with 10-min of data, with no further improvement when
more data per subject was used. While the prediction accuracies of our generic models
improved with increasing subject pool, our results are consistent with those of Di Liberto in that
we observed neither strong evidence of increases in generic model performance with
increasing amount of data per participant, nor substantial increases in the mean feature-
specific prediction accuracies with increasing subject pool. Nevertheless, utilizing larger training
subject pools did result in decreased variance in the estimates of these contributions, and
hence increased statistical power for their detection. Overall, our results agree with those of Di
Liberto in that generic models can provide significant predictive power even when they are
trained and evaluated on relatively small amounts of data per participant (2-/4-min and 10-min
in our and Di Liberto's studies, respectively).
861
4.3 Utility of subject-specific and generic TRF analyses
Given that generic analyses demonstrated superior performance to subject-specific analyses
when small amounts of data per participant was available, it is important to consider the
scenarios for which each analysis approach may be appropriate. Despite requiring more data
per participant, subject-specific analyses have been overwhelmingly more popular than generic
analyses in studies of speech and music processing. A key advantage of these analyses is that
for each participant, subject-specific fits provide independent estimates of both prediction
accuracies, and the TRFs themselves, allowing for traditional approaches to group-level
statistics. Additionally, subject-specific modelling is critically important for studies seeking to
characterize individual differences within a population, and/or their relationship to behavioral
performance or other subject-level characteristics.
Conversely, while cross-validation used during generic model fitting also provides
independent prediction accuracies for all participants, the TRFs from different cross-validation
folds are non-independent. Moreover, the interpretation of prediction accuracies for individual
subjects in the context of generic analyses differs from subject-specific approach, as they reflect
the predictability of a given participant's neural representations by a generic model, as opposed
to the overall strength of speech representations in that participant. In other words, it may be
the case that due to individual differences (e.g., due to anatomical variability) a particular
participant's data may be poorly predicted by a generic model even if their individual model
could perform substantially better. However, by capturing the shared aspects of neural

processing within a larger group, generic analyses may be particularly useful for categorizing
participants, or their mental states, which may have important applications both in clinical
diagnostics, and for practical tools such as neuro-steered hearing aid devices. Indeed, several
studies utilizing *backward* models to decode attention have demonstrated the utility of generic
models, albeit with a performance deficit relative to subject-specific models (e.g., Mirkovic et
al., 2015; O'Sullivan et al., 2015). The potential of generic models for clinical applications is
further supported by the key observation in the present work that they can achieve substantial
predictive power on highly limited amounts of data per participant. However, as pointed out by
Di Liberto and Lalor (2017), generic models implicitly assume within-group homogeneity in
neural representations, which may be particularly questionable within clinical populations (e.g.,
Levy et al., 1997; Happé et al., 2006). As such, researchers need to be cognizant about this
limitation. Finally, on a practical note, one disadvantage of generic analyses, as implemented in
the present work, is that fitting them to large datasets requires large amounts of computational
resources and time, especially when utilizing a resampling approach to fitting. However,
efficient use of resources (e.g., downsampling and reducing data dimensionality via methods
such as multiway canonical component analysis, MCCA; de Cheveigné et al., 2018), and
alternative model estimation approaches, such as averaging of subject-specific models (e.g., Di
Liberto & Lalor, 2017) or models fitted to subsets of participants, can mitigate these technical
challenges.
Finally, it should be noted that in the broader context of their neuroscientific
applications, TRF analyses have been utilized predominantly for discovery of scientific
knowledge. However, due to their ability to extract complex neural responses to arbitrary
stimulus features from M/EEG activity evoked by continuous, naturalistic stimuli, TRF analyses
have potential for applications beyond basic science. As noted above, such applications may
include clinical diagnostics of deficits in speech and music processing, as well as evaluation of
interventions, such as hearing aids or sensory training. For example TRF analyses could aid in
diagnosis speech perception deficits that are difficult to capture via traditional audiological
tests (e.g., Tremblay et al., 2015), as well as perceptual consequences of cochlear synaptopathy
(i.e., hidden hearing loss; see review by Liberman and Kujawa, 2017). Notably, backward
models have recently started to show promise in revealing group-level effects of hearing aids
on cortical representations of speech (e.g., Alickovic et al., 2020, 2021). However, while
exploration of TRF methods for clinical uses in individual patients is an important future
direction, significant methodological progress will be needed before such methods become
viable in practice.
916
4.4 Limitations and methodological caveats
While the present work provides a detailed exploration of TRF model performance as a function
of training data quantity, caution should be taken in generalizing our results to other TRF
studies. Choices in the experimental design, data pre-processing, modelled feature space, and
statistical analyses could all influence the performance and interpretation of TRF analyses (for a
broader, more detailed overview of associated issues, see Crosse et al., 2021). Moreover, as

TRF methods are growing in popularity, "best/recommended" analysis methods are likely to
become outperformed as new and improved analysis and statistical methods emerge. Below
we highlight a number of methodological choices made within this study that could have
influenced our results, and briefly discuss alternative choices available to experimenters.
927
4.4.1 Study design considerations
This work utilized a dataset obtained using a challenging dual-talker paradigm from a
participant sample spanning a wide range of ages (18-70). Alternative stimulus choices, such as
different talkers (e.g., male vs female; single vs multi-talker), types of noise (e.g., speech-
shaped noise, multi-talker babble, etc.), spatial configuration of sound sources, and task can
alter the overall prediction accuracies, and TRF amplitudes. For example, neural
representations of unattended speech are generally substantially weaker (e.g., Ding and Simon,
2012; Mesgarani and Chang, 2012), or even absent in the case of higher-order features related
to phonetic (Teoh et al., 2022) and semantic processing (Broderick et al., 2018). It is notable
that most existing speech TRF studies utilized single-talker paradigms. It is likely that for a
model with fixed complexity, these paradigms require appreciably lower data quantities to
achieve significant prediction accuracies, given their high speech intelligibility. Indeed, in the
context of subject-specific models, several single-talker works have reported significant feature-
specific contributions for higher-order features with as little as 12 minutes of data (e.g.,
Broderick et al., 2021; Gillis et al., 2022b). We chose to use a dual-talker paradigm in part
because studies exploring neural correlates of speech perception difficulties are increasingly
popular, making the present analyses more relevant to these investigators. Finally, despite
using a dual-talker paradigm, it is likely that the TRFs obtained here are representative of TRFs
one may derive in single-talker paradigms, as similar TRFs have previously been observed using
both paradigms (e.g., Kong et al., 2014; Broderick et al., 2018).
In terms of participant sample, prior work has shown amplified cortical tracking of
speech in older (e.g., Presacco et al., 2016; Decruy et al., 2019; Zan et al., 2020; Mesik et al.,
2021, but see Gillis et al., 2022b) and hearing-impaired populations (Decruy et al., 2020;
Fuglsang et al., 2020; Gillis et al., 2022a). As such, the inclusion of older participants in our data
set may have resulted in slightly higher prediction accuracies and hence a need of somewhat
less data to reach a criterion level of model performance, relative to what one may expect from
data obtained only from younger adults. Note that we chose to utilize the combined data set
given that in our previous work (Mesik et al., 2021) younger and older adults exhibited similar
temporal morphologies of word-level TRFs, and hence it is likely that these groups' speech-
driven responses vary along a continuum, rather than reflecting categorically different speech
processing (the latter of which would make combined analysis of the two sets of participants
invalid). Lastly, we caution the reader that the present results are likely less applicable to
special populations, such as clinical patients or children, whose speech processing may be
immature or otherwise altered relative to the healthy adult population studied here.
962
4.4.2 Pre-processing considerations

Pre-processing operations applied to data in order to improve its SNR, likewise, can have
substantial impact on TRF analyses. Filtering is one of the most common pre-processing
operations, allowing researchers to isolate a subset of frequencies thought to contain the
neural signals of interest, while removing contributions of noise sources. While some filtering is
usually desirable, we caution the reader that different types of filters can introduce systematic
distortions into the data, which can negatively impact the interpretability of the extracted
neural signals, such as ERPs or TRFs. We refer the reader to a detailed overview of issues
related to filtering by de Cheveigné and Nelken (2019). In the present work, data was filtered to
isolate the neural dynamics in the low-frequency delta (1-4 Hz) and theta (4-8 Hz) bands of
cortical responses to speech. Although this was largely motivated by previous findings that
speech processing mechanisms track predominantly the low-frequency dynamics of speech
signals (e.g., Zion Golumbic et al., 2013), auditory cortex is known to phase-lock to acoustics
features at rates up to 100 Hz (e.g., Holmes et al., 2018). Thus, depending on the nature of
studied feature representations, different filter cutoffs than those used here may be required.
Besides temporal filtering, of particular interest to TRF analyses are more sophisticated
denoising algorithms, such as the denoised source separation (DSS; de Cheveigné and Simon,
2008), and multiway canonical correlation analysis (MCCA; de Cheveigné et al., 2018). DSS is a
dimensionality reduction technique that can isolate components of neural activity most
strongly related to a particular stimulus representation, such as the acoustic envelope, thus
providing improved SNR for subsequent TRF analyses. This technique may be used to improve
SNR in subject-specific analyses, likely achieving significant predictive power with lower
amounts of data. Similarly, MCCA is a technique that isolates components of neural activity
shared across subjects within a data set, which allows researchers to factor out subject-level
sources of variability, such as differences in anatomy. MCCA, therefore, is particularly relevant
for generic analyses that fit models to multiple participants simultaneously. In present work,
generic analyses assumed anatomical alignment of neural activity at the level of EEG sensors.
Differences in anatomy may have therefore contributed to lower prediction accuracies than
could likely be achieved with MCCA.
992
4.4.3 Modelled feature spaces
One of the key aspects of TRF analysis is the choice of the modelled feature space. Here we fit
two separate models emphasizing denser and sparser features in order to compare the relative
performance of these types of feature sets. However, it is important to highlight that this
separation of features into distinct models served a demonstrative role, rather than being
methodologically necessary (but see discussion of banded ridge regression in section 4.4.4).
Fitting of models with smaller subsets of features can be particularly problematic when the
scientific question concerns whether a given feature appears to explain unique variance in
cortical responses. Specifically, it may be the case that variance explained by one feature can be
explained similarly or better by other, correlated features that were not included in the model.
By using a more complete feature representation, researchers can gain greater (albeit not
complete) certainty about the unique explanatory power of different features in the model.

Indeed, several recent studies have brought into question unique cortical tracking of higher-
order features, such as phonemic categories (Daube et al., 2019; but see Teoh et al., 2022) and
semantic dissimilarity (Gillis et al., 2021), when more complete representations of stimulus
acoustics were included in the model. In this regard, we acknowledge that the present work
does not conclusively establish that the modelled features per se were uniquely tracked in our
data.
Finally, while most existing TRF studies have modelled responses to researcher-defined
stimulus features, a notable emerging approach relies on passing stimuli through pre-trained
artificial neural networks (e.g., deep neural networks; DNNs), and deriving feature sets from the
abstract representations that emerge within these networks. This approach has been
successfully used in functional magnetic resonance imaging (fMRI) studies (e.g., Güçlü and van
Gerven, 2015; Kell et al., 2018), and given its promise, it will likely become increasingly popular
in TRF analyses as well. However, while fitting more complex models can generally account for
greater amount of variance, they introduce several challenges that researches need to deal
with. First, a practical issue is that larger models require larger amounts of data, in order to
more thoroughly sample the feature space included in the model. As such, the quantities of
data that were sufficient to fit our relatively small models may be insufficient for adequate
fitting of substantially larger models, such as ones with feature spaces based on activation
patterns of DNNs. Second, uninformative features may be particularly common in large models,
which can lead to overfitting of the training data set and poorer test performance. Pruning (i.e.,
systematic elimination) of uninformative features is therefore especially important with these
larger models. Finally, while larger models can more accurately predict brain responses, they
also tend to be more challenging to interpret, particularly when their features are derived using
artificial neural networks. A major challenge in the interpretation of larger models is
determining what cognitive processes (or neural computations) does tracking of various
abstract features reflect.
1031
4.4.4 TRF analysis methods
The TRF estimation methods themselves offer researchers several options that may affect the
performance of TRF analyses. In the present work, we fit TRF models using regularized linear
regression, while other existing methods include boosting (David et al., 2007; for boosting-
based toolbox for M/EEG analyses, see Brodbeck et al., 2021), normalized reverse correlation
(Theunissen et al., 2001), as well as a method for TRF estimation in the neural source space
(Das et al., 2020). Although these alternative methods are beyond the scope of the present
work, we note that Kulasingham and Simon (2022) showed that with a fixed amount of training
data, regularized linear regression and boosting algorithms result in highly similar TRF
estimates, making it likely that most of the patterns observed in the present work would also
apply to boosting-based analyses. However, since boosting does not utilize a regularization
parameter, it is unclear whether similar dependence of TRF amplitudes on training data
quantity would be observed with boosting.

With respect to regularization methods used in the present work, it is notable that each
analysis utilized a single ridge parameter, meaning that the fitting procedure penalized
regression (beta) coefficients of all features included in the model to the same extent.
However, because different features may have substantially different predictive powers, and
may correlate with one another to different extents, single regularization parameter may be
insufficient to allow for accurate TRF estimation of all features in a model (Nunez-Elizalde et al.,
2019). To account for this issue, banded ridge regression methods have recently been
introduced, which apply individualized ridge parameters to different features in a model
(Nunez-Elizalde et al., 2019; Dupré la Tour et al., 2022). This method was not used in the
present work, as we chose to build our analysis pipelines using publicly available tools (i.e.,
mTRF toolbox), which did not have this functionality implemented, yet (but see Crosse et al.,
2021 for the description of forthcoming banded ridge regression functionality). Given our use of
relatively small feature sets, it is unlikely that banded ridge regression would lead to substantial
improvements in the performance of our analyses. Nevertheless, exploration of the effects of
training data quantity on banded ridge regression performance is a useful future direction.
Estimation of feature-specific model contributions is another aspect of TRF analysis with
multiple existing methods. Here we utilized perhaps the most common approach, which
computes feature-specific contributions as the difference in prediction accuracies between full
and reduced models containing all but one feature (e.g., Di Liberto et al., 2015; Gillis et al.,
2021). Another approach utilizes comparisons of full and "null" models with equal
dimensionality, where regressors of individual features are shuffled to disrupt their temporal
relationship with the stimulus (e.g., Brodbeck et al., 2018). In certain cases, performances of
these types of null models have been computed from full model's TRF estimates (Broderick et
al., 2021; Mesik et al., 2021), although potential biases this may introduce in fit contribution
estimates have not been thoroughly assessed. The partial correlation approach for estimating
feature-specific model contributions relies on comparisons of predictions of models utilizing
individual feature representations (e.g., Prinsloo and Lalor, 2022; Teoh et al., 2022). Lastly,
feature-specific contributions can also be estimated by subtracting (i.e., partialling out)
predictions of an all-but-one feature model from the EEG data, and then fitting this residual
signal with a model containing the left-out feature (O'Sullivan et al., 2021). In general, we
anticipate that most of these methods result in correlated estimates of model contributions,
albeit more work will be needed to assess their relative performances.
Finally, we reiterate that the ROI-based statistical analyses in the present work were
used partly to highlight general locations where the two models performed well, and partly to
simplify the presentation of results. As such, it is possible that different subsets of electrodes,
identified using, e.g., cluster-based permutation tests (Maris and Oostenveld, 2007), could be
more sensitive for detection of significant prediction accuracies and feature-specific model
contributions. Use of these methods could, likewise, lead to increased statistical power, and
consequently lower required training data quantity.
1084
4.5 Conclusions

The goal of this work was to develop an informational resource for the growing field of TRF
analyses of continuous speech processing, demonstrating the behavior of TRF analyses as a
function of data quantity used in TRF fitting. In the context of relatively simple models of lower-
level envelope processing, as well as higher-order processing of word-level features, we
demonstrate that given a large-enough participant pool, small amounts of data (< 5 min) can be
sufficient to train subject-specific models that predict significant variance in EEG responses to
speech-masked speech. At the same time, substantially more data (15+ min) may be needed to
capture feature-specific model contributions of individual word-level features. On the other
hand, generic models can support significant prediction accuracy even for feature-specific
variance with as little as 2-min of data per participant, while providing highly similar TRF
estimates to those seen in subject-specific analyses. As such, despite their infrequent use,
generic models have potential to be particularly useful for applications in clinical diagnostics,
and multi-task studies with low per-task time budgets. While the present work is not, on its
own, intended to be prescriptive about experimental duration, it may be a useful resource for
informing selection of experimental duration, especially in conjunction with other tools, such as
simulations and piloting.
1102

1103 **Data availability**
1104 Data and analysis scripts will be made available upon reasonable request. Requests should be
1105 directed to JM, mesik002@umn.edu, or MW, wojtc001@umn.edu.
1106

1107 **Ethics statement**
1108 The Institutional Review Board of the University of Minnesota approved the procedures in this
1109 study. All participants provided written informed consent to participate.
1110

1111 **Author contributions**
1112 JM and MW designed the original experiment, analyzed the data, and wrote the manuscript. JM
1113 implemented experimental procedures and collected the data. All authors commented on the
1114 manuscript and approved the submitted version.
1115

1116 **Funding**
1117 Financial support for this work was provided by NIH grants R01 DC015462 to MW, and R21
1118 DC020788 to JM.
1119

1120 **Acknowledgments**
1121 We thank Lucia Ray for help with carrying out the original study that yielded the data used in
1122 the present work.
1123

1124 **Conflict of Interest Statement**
1125 The authors declare no conflicts of interest.
1126

References

Alickovic, E., Lunner, T., Wendt, D., Fiedler, L., Hietkamp, R., Ng, E. H. N., et al. (2020). Neural representation enhanced for speech and reduced for background noise with a hearing aid noise reduction scheme during a selective attention task. *Front. Neurosci.* 14, 846. doi:10.3389/fnins.2020.00846.

Alickovic, E., Ng, E. H. N., Fiedler, L., Santurette, S., Innes-Brown, H., and Graversen, C. (2021). Effects of hearing aid noise reduction on early and late cortical representations of competing talkers in noise. *Front. Neurosci.* 15. doi:10.3389/fnins.2021.636060.

Best, V., Roverud, E., Baltzell, L., Rennies, J., and Lavandier, M. (2019). The importance of a broad bandwidth for understanding "glimpsed" speech. *J. Acoust. Soc. Am.* 146, 3215–3221. doi:10.1121/1.5131651.

Bigdely-Shamlo, N., Mullen, T., Kothe, C., Su, K.-M., and Robbins, K. A. (2015). The prep pipeline: standardized preprocessing for large-scale eeg analysis. *Front. Neuroinform.* 9, 1–20. doi:10.3389/fninf.2015.00016.

Brainard, D. H. (1997). The psychophysics toolbox. *Spat. Vis.* 10, 433–436. doi:10.1163/156856897X00357.

Brodbeck, C., Das, P., Kulasingham, J. P., Bhattasali, S., Gaston, P., Resnik, P., et al. (2021). Eelbrain : a python toolkit for time-continuous analysis with temporal response functions. *bioRxiv*, 1–30. Available at: https://doi.org/10.1101/2021.08.01.454687.

Brodbeck, C., Hong, L. E., and Simon, J. Z. (2018). Rapid transformation from auditory to linguistic representations of continuous speech. *Curr. Biol.* 28, 3976-3983.e5. doi:10.1016/j.cub.2018.10.042.

Broderick, M. P., Anderson, A. J., Di Liberto, G. M., Crosse, M. J., and Lalor, E. C. (2018). Electrophysiological correlates of semantic dissimilarity reflect the comprehension of natural, narrative speech. *Curr. Biol.* 28, 803-809.e3. doi:10.1016/j.cub.2018.01.080.

Broderick, M. P., Liberto, G. M. Di, Anderson, A. J., Rofes, A., and Lalor, E. C. (2021). Dissociable electrophysiological measures of natural language processing reveal differences in speech comprehension strategy in healthy ageing. *Sci. Rep.* 11, 4963. doi:10.1038/s41598-021-84597-9.

Comon, P. (1994). Independent component analysis, a new concept? *Signal Processing* 36, 287–314. doi:10.1016/0165-1684(94)90029-9.

Cooke, M. (2006). A glimpsing model of speech perception in noise. *J. Acoust. Soc. Am.* 119, 1562–1573. doi:10.1121/1.2166600.

Crosse, M. J., Di Liberto, G. M., Bednar, A., and Lalor, E. C. (2016). The multivariate temporal response function (mtrf) toolbox: a matlab toolbox for relating neural signals to continuous stimuli. *Front. Hum. Neurosci.* 10, 1–14. doi:10.3389/fnhum.2016.00604.

Crosse, M. J., Zuk, N. J., Di Liberto, G. M., Nidiffer, A. R., Molholm, S., and Lalor, E. C. (2021).

Linear modeling of neurophysiological responses to speech and other continuous stimuli:
methodological considerations for applied research. *Front. Neurosci.* 15.
doi:10.3389/fnins.2021.705621.

Das, P., Brodbeck, C., Simon, J. Z., and Babadi, B. (2020). Neuro-current response functions: a
unified approach to meg source analysis under the continuous stimuli paradigm.
Neuroimage 211, 116528. doi:10.1016/j.neuroimage.2020.116528.

Daube, C., Ince, R. A. A., and Gross, J. (2019). Simple acoustic features can explain phoneme-
based predictions of cortical responses to speech. *Curr. Biol.* 29, 1924-1937.e9.
doi:10.1016/j.cub.2019.04.067.

David, S. V., Mesgarani, N., and Shamma, S. A. (2007). Estimating sparse spectro-temporal
receptive fields with natural stimuli. *Netw. Comput. Neural Syst.* 18, 191–212.
doi:10.1080/09548980701609235.

de Cheveigné, A., Di Liberto, G. M., Arzounian, D., Wong, D. D. E., Hjortkjær, J., Fuglsang, S. A.,
et al. (2018). Multiway canonical correlation analysis of brain data. *Neuroimage* 186, 728–
740. doi:10.1016/j.neuroimage.2018.11.026.

de Cheveigné, A., and Nelken, I. (2019). Filters: when, why, and how (not) to use them. *Neuron*.
doi:10.1016/j.neuron.2019.02.039.

de Cheveigné, A., and Simon, J. Z. (2008). Denoising based on spatial filtering. *J. Neurosci.*
Methods 171, 331–339. doi:10.1016/j.jneumeth.2008.03.015.

Decruy, L., Vanthornhout, J., and Francart, T. (2019). Evidence for enhanced neural tracking of
the speech envelope underlying age-related speech-in-noise difficulties. *J. Neurophysiol.*
122, 601–615. doi:10.1152/jn.00687.2018.

Decruy, L., Vanthornhout, J., and Francart, T. (2020). Hearing impairment is associated with
enhanced neural tracking of the speech envelope. *Hear. Res.* 393, 107961.
doi:10.1016/j.heares.2020.107961.

Delorme, A., and Makeig, S. (2004). EEGLAB: an open source toolbox for analysis of single-trial
eeg dynamics including independent component analysis. *J. Neurosci. Methods* 134, 9–21.
doi:10.1016/j.jneumeth.2003.10.009.

Di Liberto, G. M., and Lalor, E. C. (2017). Indexing cortical entrainment to natural speech at the
phonemic level: methodological considerations for applied research. *Hear. Res.* 348, 70–
77. doi:10.1016/j.heares.2017.02.015.

Di Liberto, G. M., O'Sullivan, J. A., and Lalor, E. C. (2015). Low-frequency cortical entrainment to
speech reflects phoneme-level processing. *Curr. Biol.* 25, 2457–2465.
doi:10.1016/j.cub.2015.08.030.

Di Liberto, G. M., Pelofi, C., Bianco, R., Patel, P., Mehta, A. D., Herrero, J. L., et al. (2020).
Cortical encoding of melodic expectations in human temporal cortex. *Elife* 9, 1–26.
doi:10.7554/eLife.51784.

Di Liberto, G. M., Wong, D., Melnik, G. A., and de Cheveigné, A. (2019). Low-frequency cortical
responses to natural speech reflect probabilistic phonotactics. *Neuroimage* 196, 237–247.
doi:10.1016/j.neuroimage.2019.04.037.

Ding, N., and Simon, J. Z. (2012). Neural coding of continuous speech in auditory cortex during
monaural and dichotic listening. *J. Neurophysiol.* 107, 78–89. doi:10.1152/jn.00297.2011.

Donhauser, P. W., and Baillet, S. (2020). Two distinct neural timescales for predictive speech
processing. *Neuron* 105, 385-393.e9. doi:10.1016/j.neuron.2019.10.019.

Dupré la Tour, T., Eickenberg, M., Nunez-Elizalde, A. O., and Gallant, J. L. (2022). Feature-space
selection with banded ridge regression. *Neuroimage* 264, 119728.
doi:10.1016/j.neuroimage.2022.119728.

Fiedler, L., Wöstmann, M., Herbst, S. K., and Obleser, J. (2019). Late cortical tracking of ignored
speech facilitates neural selectivity in acoustically challenging conditions. *Neuroimage* 186,
33–42. doi:10.1016/j.neuroimage.2018.10.057.

Fuglsang, S. A., Dau, T., and Hjortkjær, J. (2017). Noise-robust cortical tracking of attended
speech in real-world acoustic scenes. *Neuroimage* 156, 435–444.
doi:10.1016/j.neuroimage.2017.04.026.

Fuglsang, S. A., Märcher-Rørsted, J., Dau, T., and Hjortkjær, J. (2020). Effects of sensorineural
hearing loss on cortical synchronization to competing speech during selective attention. *J.*
Neurosci. 40, 2562–2572. doi:10.1523/JNEUROSCI.1936-19.2020.

Gillis, M., Decruy, L., Vanthornhout, J., and Francart, T. (2022a). Hearing loss is associated with
delayed neural responses to continuous speech. *Eur. J. Neurosci.* 55, 1671–1690.
doi:10.1111/ejn.15644.

Gillis, M., Kries, J., Vandermosten, M., and Francart, T. (2022b). Neural tracking of linguistic
speech representations decreases with advancing age. *bioRxiv*.
doi:10.1101/2022.07.29.501978.

Gillis, M., Vanthornhout, J., Simon, J. Z., Francart, T., and Brodbeck, C. (2021). Neural markers of
speech comprehension: measuring eeg tracking of linguistic speech representations,
controlling the speech acoustics. *J. Neurosci.* 41, JN-RM-0812-21.
doi:10.1523/jneurosci.0812-21.2021.

Güçlü, U., and van Gerven, M. A. J. (2015). Deep neural networks reveal a gradient in the
complexity of neural representations across the ventral stream. *J. Neurosci.* 35, 10005–
10014. doi:10.1523/JNEUROSCI.5023-14.2015.

Happé, F., Ronald, A., and Plomin, R. (2006). Time to give up on a single explanation for autism.
Nat. Neurosci. 9, 1218–1220. doi:10.1038/nn1770.

Heilbron, M., Armeni, K., Schoffelen, J.-M., Hagoort, P., and de Lange, F. P. (2022). A hierarchy
of linguistic predictions during natural language comprehension. *Proc. Natl. Acad. Sci.* 119,
2020.12.03.410399. doi:10.1073/pnas.2201968119.

Holmes, E., Purcell, D. W., Carlyon, R. P., Gockel, H. E., and Johnsrude, I. S. (2018). Attentional
modulation of envelope-following responses at lower (93–109 hz) but not higher (217–233
hz) modulation rates. *J. Assoc. Res. Otolaryngol.* 19, 83–97. doi:10.1007/s10162-017-0641-
9.

Jutten, C., and Herault, J. (1991). Blind separation of sources, part i: an adaptive algorithm
based on neuromimetic architecture. *Signal Processing* 24, 1–10. doi:10.1016/0165-
1684(91)90079-X.

Kell, A. J. E., Yamins, D. L. K., Shook, E. N., Norman-Haignere, S. V., and McDermott, J. H. (2018).
A task-optimized neural network replicates human auditory behavior, predicts brain
responses, and reveals a cortical processing hierarchy. *Neuron* 98, 630-644.e16.
doi:10.1016/j.neuron.2018.03.044.

Kleiner, M., Brainard, D. H., and Pelli, D. G. (2007). What's new in psychtoolbox-3. in *Perception*
36 ECVP Abstract Supplement.

Kong, Y. Y., Mullangi, A., and Ding, N. (2014). Differential modulation of auditory responses to
attended and unattended speech in different listening conditions. *Hear. Res.* 316, 73–81.
doi:10.1016/j.heares.2014.07.009.

Kulasingham, J. P., and Simon, J. Z. (2022). Algorithms for estimating time-locked neural
response components in cortical processing of continuous speech. *IEEE Trans. Biomed.*
Eng., 1–9. doi:10.1109/tbme.2022.3185005.

Lalor, E. C., and Foxe, J. J. (2010). Neural responses to uninterrupted natural speech can be
extracted with precise temporal resolution. *Eur. J. Neurosci.* 31, 189–193.
doi:10.1111/j.1460-9568.2009.07055.x.

Levy, F., Hay, D. A., McStephen, M., Wood, C., and Waldman, I. (1997). Attention-deficit
hyperactivity disorder: a category or a continuum? genetic analysis of a large-scale twin
study. *J. Am. Acad. Child Adolesc. Psychiatry* 36, 737–44. doi:10.1097/00004583-
199706000-00009.

Liberman, M. C., and Kujawa, S. G. (2017). Cochlear synaptopathy in acquired sensorineural
hearing loss: manifestations and mechanisms. *Hear. Res.* 349, 138–147.
doi:10.1016/j.heares.2017.01.003.

Luck, S. J. (2005). *An introduction to the event-related potential technique*. MIT Press.

Marion, G., Di Liberto, G. M., and Shamma, S. A. (2021). The music of silence. part i: responses
to musical imagery encode melodic expectations and acoustics. *J. Neurosci.* 41, JN-RM-
0183-21. doi:10.1523/JNEUROSCI.0183-21.2021.

Maris, E., and Oostenveld, R. (2007). Nonparametric statistical testing of eeg- and meg-data. *J.*
Neurosci. Methods 164, 177–190. doi:10.1016/j.jneumeth.2007.03.024.

Mesgarani, N., and Chang, E. F. (2012). Selective cortical representation of attended speaker in
multi-talker speech perception. *Nature* 485, 233–236. doi:10.1038/nature11020.

Mesik, J., Ray, L., and Wojtczak, M. (2021). Effects of age on cortical tracking of word-level
features of continuous competing speech. *Front. Neurosci.* 15, 1–21.
doi:10.3389/fnins.2021.635126.

Mirkovic, B., Debener, S., Jaeger, M., and De Vos, M. (2015). Decoding the attended speech
stream with multi-channel eeg: implications for online, daily-life applications. *J. Neural*
Eng. 12. doi:10.1088/1741-2560/12/4/046007.

Nunez-Elizalde, A. O., Huth, A. G., and Gallant, J. L. (2019). Voxelwise encoding models with
non-spherical multivariate normal priors. *Neuroimage* 197, 482–492.
doi:10.1016/j.neuroimage.2019.04.012.

O'Sullivan, A. E., Crosse, M. J., Di Liberto, G. M., de Cheveigné, A., and Lalor, E. C. (2021).
Neurophysiological indices of audiovisual speech processing reveal a hierarchy of
multisensory integration effects. *J. Neurosci.* 41, 4991–5003.
doi:10.1523/JNEUROSCI.0906-20.2021.

O'Sullivan, J. A., Power, A. J., Mesgarani, N., Rajaram, S., Foxe, J. J., Shinn-Cunningham, B. G., et
al. (2015). Attentional selection in a cocktail party environment can be decoded from
single-trial eeg. *Cereb. Cortex* 25, 1697–1706. doi:10.1093/cercor/bht355.

Pelli, D. G. (1997). The videotoolbox software for visual psychophysics: transforming numbers
into movies. *Spat. Vis.* 10, 437–442. doi:10.1163/156856897X00366.

Power, A. J., Foxe, J. J., Forde, E.-J., Reilly, R. B., and Lalor, E. C. (2012). At what time is the
cocktail party? a late locus of selective attention to natural speech. *Eur. J. Neurosci.* 35,
1497–1503. doi:10.1111/j.1460-9568.2012.08060.x.

Presacco, A., Simon, J. Z., and Anderson, S. (2016). Effect of informational content of noise on
speech representation in the aging midbrain and cortex. *J. Neurophysiol.* 116, 2356–2367.
doi:10.1152/jn.00373.2016.

Prinsloo, K. D., and Lalor, E. C. (2022). General auditory and speech-specific contributions to
cortical envelope tracking revealed using auditory chimeras. *J. Neurosci.* 42, JN-RM-2735-
20. doi:10.1523/JNEUROSCI.2735-20.2022.

Radford, A., Wu, J., Child, R., Luan, D., Amodei, D., and Sutskever, I. (2019). Language models
are unsupervised multitask learners. *OpenAI Blog*. Available at:
https://cdn.openai.com/better-language-
models/language_models_are_unsupervised_multitask_learners.pdf.

Sassenhagen, J. (2019). How to analyse electrophysiological responses to naturalistic language
with time-resolved multiple regression. *Lang. Cogn. Neurosci.* 34, 474–490.
doi:10.1080/23273798.2018.1502458.

Stone, M. A., Füllgrabe, C., and Moore, B. C. J. (2010). Relative contribution to speech
intelligibility of different envelope modulation rates within the speech dynamic range. *J.*
Acoust. Soc. Am. 128, 2127–2137. doi:10.1121/1.3479546.

Teoh, E. S., Ahmed, F., and Lalor, E. C. (2022). Attention differentially affects acoustic and
phonetic feature encoding in a multispeaker environment. *J. Neurosci.* 42, 682–691.
doi:10.1523/JNEUROSCI.1455-20.2021.

Theunissen, F. E., David, S. V., Singh, N. C., Hsu, A., Vinje, W. E., and Gallant, J. L. (2001).
Estimating spatio-temporal receptive fields of auditory and visual neurons from their
responses to natural stimuli. *Netw. Comput. Neural Syst.* 12, 289–316. doi:10.1088/0954-
898X/12/3/304.

Tremblay, K. L., Pinto, A., Fischer, M. E., Klein, B. E. K., Klein, R., Levy, S., et al. (2015). Self-
reported hearing difficulties among adults with normal audiograms: the beaver dam
offspring study. *Ear Hear.* 36, e290–e299. doi:10.1097/AUD.0000000000000195.

Weissbart, H., Kandylaki, K. D., and Reichenbach, T. (2019). Cortical tracking of surprisal during
continuous speech comprehension. *J. Cogn. Neurosci.*, 1–12. doi:10.1162/jocn_a_01467.

Wong, D. D. E., Fuglsang, S. A., Hjortkjær, J., Ceolini, E., Slaney, M., and de Cheveigné, A. (2018).
A comparison of regularization methods in forward and backward models for auditory
attention decoding. *Front. Neurosci.* 12, 531. doi:10.3389/fnins.2018.00531.

Woodman, G. F. (2010). A brief introduction to the use of event-related potentials in studies of
perception and attention. *Atten. Percept. Psychophys.* 72, 2031–2046.
doi:10.3758/APP.72.8.2031.

Zan, P., Presacco, A., Anderson, S., and Simon, J. Z. (2020). Exaggerated cortical representation
of speech in older listeners: mutual information analysis. *J. Neurophysiol.* 124, 1152–1164.
doi:10.1152/jn.00002.2020.

Zion Golumbic, E. M., Ding, N., Bickel, S., Lakatos, P., Schevon, C. A., McKhann, G. M., et al.
(2013). Mechanisms underlying selective neuronal tracking of attended speech at a
"cocktail party." *Neuron* 77, 980–991. doi:10.1016/j.neuron.2012.12.037.

1336