1   **MARSY: A multitask deep learning framework for prediction of drug combination synergy**

2   **scores**

3   Mohamed Reda El Khili[1], Safyan Aman Memon[1], and Amin Emad[1,2,3,*]

[1] Department of Electrical and Computer Engineering, McGill University, Montreal, QC,

Canada

[2] Mila, Quebec AI Institute, Montréal, QC, Canada

[3] The Rosalind and Morris Goodman Cancer Institute, Montréal, QC, Canada

5   * Corresponding Author:

6   Amin Emad

7   755 McConnell Engineering Building

8   3480 University Street, Montreal, Quebec, Canada, H3A 0E9

9   Email: amin.emad@mcgill.ca

Abstract

Combination therapies have emerged as a treatment strategy for cancers to reduce the probability of drug resistance and to improve outcome. Large databases curating the results of many drug screening studies on preclinical cancer cell lines have been developed, capturing the synergistic and antagonistic effects of combination of drugs in different cell lines. However, due to the high cost of drug screening experiments and the sheer size of possible drug combinations, these databases are quite sparse. This necessitates the development of transductive computational models to accurately impute these missing values. Here, we developed MARSY, a deep learning multi-task model that incorporates information on gene expression profile of cancer cell lines, as well as the differential expression signature induced by each drug to predict drug-pair synergy scores. By utilizing two encoders to capture the interplay between the drug-pairs, as well as the drug-pairs and cell lines, and by adding auxiliary tasks in the predictor, MARSY learns latent embeddings that improve the prediction performance compared to state-of-the-art and traditional machine learning models. Using MARSY, we then predicted the synergy scores of 133,722 new drug-pair cell line combinations, which we have made available to the community as part of this study. Moreover, we validated various insights obtained from these novel predictions using independent studies, confirming the ability of MARSY in making accurate novel predictions.

Introduction

Cancers are complex diseases that involve various pathways and are regulated by a multitude of different genes [1,2]. Despite the emerging understanding of cancers, the development of effective treatments remains a prevailing challenge. Combination therapies, in which multiple treatments are administered simultaneously, have emerged as an alternative to monotherapies [2-4]. By simultaneously targeting multiple genes, proteins, and pathways, they can reduce the probability of drug resistance while improving treatment's efficacy [3,5-7], and allow for the reduction of necessary dosage per drug, reducing the risk of drug toxicity and adverse effects [5,7,8].

Due to the distinct molecular and clinical characteristics of cancer types, it is necessary to evaluate the response of cancer cells to different treatments and treatment strategies in each cancer type. The curation of molecular profiles of cancer cell lines (CCLs) and their response to monotherapies in large databases such as the Cancer Cell Line Encyclopedia (CCLE) [9] and Genomics of Drug Sensitivity in Cancer (GDSC) [10] initiated the development of various computational models for prediction of single drug response in CCLs [11,12] and patient tumours [13,14]. More recently, large databases of synergy scores of drug combinations (mainly drug-pairs) in CCLs such as DrugComb [15] have been curated based on results of many high-throughput drug screening studies. These databases include different synergy scores to quantify the observed effectiveness of a drug combination compared to its expected effectiveness if they are not interacting [16]. In spite of these efforts, the sheer size of possible (drug combination, CCL) tuples and the cost of drug screening experiments have resulted in sparse datasets with many missing

values. Computational models that can accurately predict the synergy scores of drug

combinations and impute these datasets can have a significant impact in this domain.

Various models have been proposed to achieve this goal. In one study [17], the authors used

various machine learning (ML) models and obtained their best predictive performance using

Random Forests (RF) and Extreme Gradient Boosting (XGB) models. Other studies have also

explored ML models such as linear regression, Support Vector Machine (SVM), LASSO, RF, XGB,

Extremely Randomized Trees, and TreeCombo (which is an extreme gradient boosted tree-

based approach) [18-20]. In addition to these traditional ML models, several deep learning (DL)

models have been proposed. One of the earliest methods, DeepSynergy [21], used a fully

connected neural network composed of two hidden layers and showed significant

improvement compared to then state-of-the-art ML models such as RF and XGB. A more recent

model, MatchMaker [8], showed that learning two distinct representations for each drug-CCL

pair in a combination can improve the performance.

Here we present MARSY, a multitask DL model that predicts the level of synergism between

drug-pairs tested on CCLs. Using gene expression to characterize CCLs and drug-induced

signatures to represent each drug, MARSY learns a distinct set of embeddings to obtain multiple

views of the input features. Precisely, a representation of the entire combination and a

representation of the drug-pair are learned in parallel. These embeddings are then fed to a

multitask network that predicts the synergy score of the drug combination alongside single

drug responses. A thorough evaluation of MARSY revealed its superior performance compared

to various state-of-the-art and traditional computational methods. A detailed analysis of the

design choices of our framework demonstrated the predictive contribution of the learned

embeddings by this model. Using MARSY, we then predicted the synergy scores of 133,722 new

drug-pair CCL combinations, which can be used to guide future drug screening and

pharmacogenomics studies. Moreover, we validated various insights obtained from these novel

predictions using independent studies, confirming the ability of MARSY in making accurate

novel predictions.

METHODS

Prediction of drug-pair synergy scores and single drug response using MARSY

MARSY (Multitask drug pAiR Synergy) is a DL-based model that seeks to learn latent

representations (embeddings) capable of predicting the synergy score of two drugs in a CCL. As

input, it receives feature vectors of two candidate drugs and a feature vector of a CCL (Figure

1). The architecture includes two parallel and separately parameterized encoders with a

bottleneck layer, and one multi-task predictor. The first encoder (ENC_{Pair}) receives the

concatenation of the feature vectors of the drug-pair to learn a (drug 1, drug2)-specific

embedding, while the second encoder (ENC_{Triple}) receives all three feature vectors to learn a

(drug1, drug2, CCL)-specific embedding. These embeddings are then concatenated and

provided as input to the predictor, which predicts the synergy score of the two drugs, along

with the single drug response of each drug in that CCL (performing three tasks simultaneously).

The inclusion of single drug response predictors as auxiliary tasks ensures that the

representations learned by the two encoders are constrained to capture biologically and

chemically important information corresponding to each drug, improving its generalizability

and performance.

ENC_{Pair} accepts a drug-pair's signature (a vector of length 3912) as input and consists of two

fully connected hidden layers of width 1024 and 2048. ENC_{Triple} accepts a vector of length 8551

corresponding to the concatenation of a drug-pair's signatures and a CCL's gene expression

profile as input and consists of two fully connected hidden layers of width 2048 and 4096. The

first hidden layer of both encoders is a bottleneck layer to perform dimensionality reduction,

while the second hidden layer has a larger width to increase the capacity of the model. The

relative width of layers in these two encoders are chosen to approximately match the length of

inputs to each encoder. A linear activation function is used for the first layer, while a Rectified

Linear Unit (ReLU) function is used for the second layer of both encoders. Both encoders use

dropout regularization with a probability of 0.2. The embeddings obtained from these two

encoders are concatenated and provided as input to the predictor ($PRED_{Resp}$). $PRED_{Resp}$ consists

of two fully connected hidden layers of width 4096 and 1024 and an output layer of width 3 to

predict the synergy score of the drugs and their individual drug response. A ReLU activation

function is used for the first two layers while a linear activation function is selected for the

output layer, given the regression nature of the prediction task. Finally, a dropout

regularization with a probability of 0.5 is used for the predictor. Details of hyperparameter

tuning and training are discussed below.

Figure 1: The overview of MARSY's architecture. A) The drug features and CCL gene expression profile are provided as input to the two encoders. Separately parameterized encoders obtain representations corresponding to the drug-pair and to the drugs and CCL triple. B) Both representations are concatenated and used as inputs to a multi-task predictor. C) The predictor predicts the synergy score of the drug combination, along with the single drug response of each drug (three outputs).

Training and hyperparameter tuning

Both encoders (ENC_{Triple} and ENC_{Pair}) and the predictor ($PRED_{Resp}$) were trained in an end-to-end

fashion using a mean squared error (MSE) loss function and the Adamax optimizer [22] with the

default learning rate of 0.001 and early stopping. The dropout probabilities and the activation

function used on the input layer of both encoders were considered hyperparameters to be

tuned using an independent validation set. All possible combinations of the probabilities 0.2

and 0.5 were assessed for both the encoders and the predictor. Furthermore, this assessment

was performed alternating between a ReLU and a linear activation function for the input layer

of the encoders. The reason we considered a linear activation function as an option for the first

layer is its ability to improve and simplify the optimization process. These hyperparameters

were evaluated on a small validation set (~1100 samples) that was excluded from the main

dataset used for cross-validation evaluation, in order to ensure that no data leakage occurs.

The rest of MARSY's architecture followed the design choices detailed above. The best

performing combination of hyperparameters (as evaluated on the independent validation set)

was used to finalize the design of the MARSY framework.

Datasets and data cleaning

In this study, the feature vector of each CCL corresponded to its baseline gene expression

profile (before administration of any drug), as measured in CCLE [9]. We downloaded the

$log_2(RPKM + 1)$ normalized RNA-seq profile of 1019 untreated CCLs (catalogued in the CCLE

study) from the CellMiner database [23,24]. We removed lowly expressed genes whose

$log_2(RPKM + 1)$ value was lower than 1 in more than 75% of all CCLs. Additionally, we

calculated the variance of genes across all CCLs and excluded those that had a variance smaller

than 0.8, which resulted in a set of 4639 features (Figure 2). Finally, a z-score normalization was

performed to the expression of each gene over all the CCLs, one gene at a time.

154
155
156
157

To represent drugs (as inputs to the model) we used their signatures corresponding to the

differential gene expression profile of two CCLs (MCF7 and PC3) measured 24 hours after

treatment with that drug with the dosage of $10\ \mu M$. We downloaded level 5 signatures from

the Library of Integrated Network-Based Cellular Signatures (LINCS) [25], and only used

experimentally measured values corresponding to 978 landmark genes. The two CCLs, the time

after treatment, and the drug dosage were selected to maximize the number of samples in our

study. In instances where replicate signatures existed for the same CCL, same drug, same

dosage, and same time-point, we calculated their mean to obtain a consensus signature. We

concatenated the MCF7 and PC3 signatures of each drug, resulting in a vector of length 3912

to represent each drug-pair (Figure 2).

We obtained drug synergy scores (and single drug responses) from the DrugComb database

(v1.5) [15]. DrugComb is one of the largest publicly available datasets for drug synergy scores with

a total of 739,964 drug combinations obtained from 8397 unique drugs. We downloaded data

corresponding to triples of (drug1, drug2, CCL) for which we had both drug signatures (from

LINCS) and CCL gene expression profiles (from CCLE). In this work, we focused on two measures

of synergism, Zero Interaction Potency ("ZIP") and "S_{mean}". ZIP calculates the synergism of a

drug-pair under the assumption that there is no potency between the single drug responses [26].

On the other hand, S_{mean} calculates synergism of a drug-pair assuming that the single drug effect

is equivalent to the average of the single drug responses [27]. As opposed to ZIP, S_{mean} is not

calculated for each combination of dosages; instead, a drug sensitivity measure is computed

directly from the dose response curve of each drug and used as the drug-pair's response. Thus,

S_{mean} serves not only as a measure of drug-pair synergy but also of its sensitivity, which aims to

illustrate the actual response of a CCL [27], and hence is more biologically informative.

Since DrugComb contains (sometimes inconsistent) replicates, it is important to carefully

process such cases. To identify samples with inconsistent replicates, we used two conditions.

First, we only kept samples for which at least 60% of the replicates had the same synergy score

sign. Second, we only kept the samples for which the standard deviation of the synergy score

over replicates did not exceed 0.1. Finally, to obtain a single consensus synergy score for each

sample, we calculated the replicates' median score. The final dataset, comprised of samples

that were present in all three datasets above and passed the filtering steps, contained 43,181

(drug1, drug2, CCL) triple samples corresponding to 670 unique drugs, 2353 unique drug-pairs

and 75 unique CCLs. Finally, in order to ensure that the trained model is invariant to the order

of the drugs in its input space, for each triple sample we constructed a new sample by changing

the order of the drugs (Figure 2), resulting in a total of 86,362 triple samples. It is important to

note that the samples with known synergy scores above only correspond to 0.128% of all

possible combinations of 670 drugs and 75 CCLs, further emphasizing the importance of

transductive computational models to complete this sparse 3-dimensional tensor.

We used relative inhibition (RI), available in DrugComb, as the response of each drug in a CCL.

RI represents the normalized area under the dose-response curve after a log_{10} transformation

[28]. More precisely, RI is the proportion of this area under the dose-response curve to the

maximal area that one drug can achieve at the same range of dosages. This metric represents

the overall inhibition effect of a drug and has shown to be a robust way to represent drugs'

sensitivity [29]. Additionally, the RI metric allows the comparison of drug responses obtained

using different dose ranges [28].

Baseline models

We considered several baseline models for benchmarking the performance of MARSY. Off-the-

shelf models included LASSO, ElasticNet, Support Vector Machine Regression (SVM), Random

Forests (RF) and a multi-layer perceptron (MLP) with the same depth and width as MARSY.

State-of-the-art algorithms, developed by others for the same task, included TreeCombo [19],

DeepSynergy [21], and MatchMaker [8]. All models were trained on the same dataset (with identical

folds across models) and evaluated similarly to ensure a fair comparison. Hyperparameters of

these models were tuned using the same independent validation set used to tune MARSY's

hyperparameters. The model that performed best on the validation set was used for cross-

validation analysis on the main dataset. In addition to the baselines above, we performed an

extensive ablation study to assess the effect of each component of MARSY's architecture on its

performance. The details of the ablation study are provided in Results.

Cross-validation, data splitting, and evaluation metrics

The performance of MARSY (and other methods) was evaluated using a five-fold cross

validation (CV) approach combined with two data splitting strategies. The main dataset

described above was randomly divided into five folds (based on each data split strategy

described below); four folds were used to train each model using the hyperparameters

obtained from the independent validation set (not used as part of these folds) and the

remaining fold was used for performance evaluation. This was repeated five times so that each

fold is set as the test set once. The mean and standard deviation of performance metrics on

these test sets were used for evaluation.

Two data splitting strategies were used corresponding to the transductive setup of this study:

leave-triple-out and leave-pair-out. In the former strategy, random triples (drug-pair and CCL)

were selected randomly to construct the five folds. In the latter strategy, the folds were

randomly selected based on drug-pairs, to ensure that the pairs of drugs are not seen together

in the training set. To ensure a fair comparison, we used the exact same folds for all models

and evaluated them in a similar manner. We evaluated the performance of MARSY and other

methods in predicting the continuous-valued drug synergy scores using Root Mean Squared

Error (RMSE), Spearman's Rank Correlation Coefficient (SCC), and Pearson Correlation

Coefficient (PCC). Additionally, we converted drug synergy scores to binary classes (synergistic

or antagonistic) using different thresholds (0, ±1, ±5, ±10 and ±20), and used area under the

receiver operating characteristic (AUROC) to evaluate the performance. For a threshold t,

synergy scores above $+t$ were considered synergistic and values below $-t$ were considered

antagonistic.

RESULTS

Performance of MARSY in prediction of drug synergy scores in a leave-triple-out data split

As the first evaluation study, we focused on the five-fold CV with leave-triple-out setup,

discussed in Methods (Table 1). MARSY outperformed all baseline models using all

performance metrics. In particular, MARSY achieved a Pearson correlation coefficient of PCC =

0.886 on ZIP and PCC = 0.864 on S_{mean}. The substantial difference between the performance of

MARSY and the MLP with a similar depth and width, reveals the importance of learning

separate representations for input pairs and triples, and using a multi-task predictor to

constraint these representations using single drug priors. In this evaluation, all state-of-the-art

algorithms outperformed off-the-shelf methods, yet did not achieve MARSY's performance.

Table1: The performance of MARSY and baseline methods using 5-fold leave-triple-out
evaluation. The folds are the same across different models for a fair comparison. Best
performance values are in bold-face and underlined. The mean and standard deviations are
calculated across the folds. Models are sorted based on their ZIP PCC values.

Model	ZIP			S$_{mean}$		
	SCC	PCC	RMSE	SCC	PCC	RMSE
MARSY	**0.780** (±0.010)	**0.886** (±0.005)	**5.36** (±0.19)	**0.836** (±0.002)	**0.864** (±0.003)	**8.42** (±0.09)
MatchMaker	0.742 (±0.004)	0.873 (±0.006)	6.11 (±0.319)	0.810 (±0.003)	0.840 (±0.005)	9.84 (±0.23)
TreeCombo (XGBoost)	0.737 (±0.004)	0.870 (±0.003)	5.73 (±0.17)	0.817 (±0.002)	0.852 (±0.002)	8.77 (±0.06)
DeepSynergy	0.701 (±0.003)	0.869 (±0.004)	5.78 (±0.18)	0.803 (±0.003)	0.843 (±0.002)	9.14 (±0.12)
MLP	0.675 (±0.002)	0.840 (±0.004)	6.30 (±0.15)	0.781 (±0.011)	0.817 (±0.009)	9.72 (±0.24)
SVM	0.689 (±0.004)	0.783 (±0.006)	7.65 (±0.19)	0.766 (±0.005)	0.779 (±0.004)	10.67 (±0.07)
Random Forests	0.419 (±0.003)	0.646 (±0.016)	9.04 (±0.21)	0.619 (±0.006)	0.640 (±0.005)	12.98 (±0.05)
LASSO	0.342 (±0.009)	0.433 (±0.013)	10.41 (±0.21)	0.561 (±0.011)	0.525 (±0.013)	14.22 (±0.14)
Elastic Net	0.342 (±0.009)	0.432 (±0.012)	10.42 (±0.21)	0.562 (±0.011)	0.525 (±0.013)	14.22 (±0.15)

Next, we sought to determine the ability of MARSY (and other models) in predicting the

synergistic and antagonistic drugs in each CCL (a binary classification task). Since the ZIP scores

and S$_{mean}$ are continuous values, we used five thresholds (0, ±1, ±5, ±10 and ±20) with an

increasing degree of strictness to binarize these values. For a specific threshold $\pm t$, a score (ZIP

or S$_{mean}$) of a triple (two drugs and a CCL) larger than $+t$ was considered to be synergistic,

smaller than $-t$ was considered to be antagonistic, and values between these two thresholds

were considered low-confidence and were discarded. Figure 3A and Table S1 show the AUROC

of MARSY and other baselines models as a function of these thresholds, revealing the superior

performance of MARSY in prediction of ZIP score in a classification formulation.

Figure 3: Performance of MARSY and its embeddings in identifying highly antagonistic and synergistic drugs. Panels A) and B) show classification performance of different methods in terms of AUROC for ZIP score for leave-triple-out and leave-pair-out five-fold cross validation, respectively. Panels C) and D) show principal component analysis (PCA) of synergistic and antagonistic drug-pairs for different thresholds (t) for SK-MEL-28 cell line based on their triple representations (panel C) and their pair representations (panel D) learned by MARSY.

Performance of MARSY in prediction of drug synergy scores in a leave-pair-out data split

Next, we sought to evaluate the performance of MARSY, when folds in the five-fold CV are determined only based on drug-pair identities (i.e., a drug-pair in the test set is never observed in the training set). Similar to the leave-triple-out framework, MARSY outperformed all other models (Table 2), reaching a Pearson correlation coefficient value of PCC = 0.875 for prediction of ZIP score and PCC = 0.841 for prediction of S_{mean}. Similar to the leave-triple-out, MatchMaker, TreeCombo and DeepSynergy were the best performing models after MARSY. Figure 3B and Table S1 show the AUROC of different models for different thresholds, further demonstrating the superior performance of MARSY for the majority of the thresholds.

Table2: The performance of MARSY and baseline methods using 5-fold leave-pair-out evaluation. The folds are the same across different models for a fair comparison. Best performance values are in bold-face and underlined. The mean and standard deviations are calculated across the folds. Models are sorted based on their ZIP PCC values.

Model	ZIP			S_{mean}		
	SCC	PCC	RMSE	SCC	PCC	RMSE
MARSY	**0.749** (±0.011)	**0.875** (±0.005)	**5.62** (±0.15)	**0.809** (±0.007)	**0.841** (±0.011)	**9.06** (±0.45)
MatchMaker	0.720 (±0.006)	0.864 (±0.007)	6.23 (±0.12)	0.788 (±0.009)	0.816 (±0.015)	10.34 (±0.46)
TreeCombo (XGBoost)	0.689 (±0.005)	0.856 (±0.006)	6.00 (±0.15)	0.775 (±0.010)	0.815 (±0.011)	9.69 (±0.37)
DeepSynergy	0.676 (±0.006)	0.860 (±0.008)	5.95 (±0.16)	0.762 (±0.004)	0.804 (±0.011)	10.17 (±0.42)
MLP	0.642 (±0.030)	0.822 (±0.023)	6.68 (±0.45)	0.744 (±0.029)	0.752 (±0.091)	11.36 (±0.24)
SVM	0.649 (±0.008)	0.773 (±0.012)	7.79 (±0.14)	0.737 (±0.011)	0.752 (±0.013)	11.15 (±0.42)
Random Forests	0.413 (±0.005)	0.650 (±0.012)	9.02 (±0.17)	0.608 (±0.016)	0.627 (±0.013)	13.14 (±0.33)
LASSO	0.333 (±0.019)	0.430 (±0.007)	10.43 (±0.17)	0.555 (±0.013)	0.519 (±0.012)	14.29 (±0.39)

Elastic Net	0.333 (±0.018)	0.429 (±0.008)	10.44 (±0.18)	0.555 (±0.013)	0.512 (±0.019)	14.29 (±0.40)

Detailed evaluation of MARSY's architecture

One aspect of MARSY's architecture is its multitask predictor. We replaced this predictor with

a single-task predictor that only predicts drug synergy scores. This modification resulted in a

lower performance based on all three measures and both data split strategies (Supplementary

Table S2). For example, MARSY had a 6.12% higher SCC in leave-triple-out and a 5.05% higher

SCC in leave-pair-out 5-fold CV for prediction of ZIP score. These results further demonstrate

the importance of including a multi-task predictor in the architecture of MARSY. In fact,

changing the predictor of DL baseline models also improved their performance (Supplementary

Table S2).

Next, we sought to determine the role of input representations and encoders' architecture

(Figure 1A) on MARSY's performance. Figure 3C and 3D (visually) show that both triple and pair

representations are able to separate the synergistic and antagonistic drug-pairs. To

systematically evaluate their role, we implemented six alternative architectures in which the

predictor was identical to MARSY's multitask predictor, but the latent embeddings were

learned using different number and types of encoders. Supplementary Figures S1-S6 show the

architecture of these models and Table 3 shows their performance. These results show that

overall, MARSY's choice of encoders is superior compared to these alternatives. In particular,

using both Triple and Pair encoders is superior to only using the Triple encoder (Model1) or

replacing the Triple or Pair encoders with a CCL encoder (Models 2 and 3). Similarly, it performs

better compared to using separate encoders for each drug (Models 4-6).

Table 3: The performance of different combination of embeddings using 5-fold leave-pair-out CV. Folds are the same across different models for a fair comparison. Best performance values are in bold-face and underlined. The mean and standard deviations are calculated across the folds. Architecture of the models are provided in Figure 1 and Supplementary Figures S1-S6.

Model	Num. Encoders	Encoder Type	ZIP			S_{mean}		
			SCC	PCC	RMSE	SCC	PCC	RMSE
MARSY	2	Pair, Triple	**0.741** (±0.018)	**0.871** (±0.009)	5.70 (±0.14)	**0.808** (±0.010)	**0.840** (±0.008)	**9.07** (±0.35)
Model1	1	Triple	0.679 (±0.024)	0.848 (±0.011)	6.22 (±0.18)	0.762 (±0.007)	0.801 (±0.012)	10.17 (±0.44)
Model2	2	CCL, Pair	0.706 (±0.018)	0.857 (±0.009)	6.52 (±0.13)	0.793 (±0.010)	0.826 (±0.007)	10.85 (±0.34)
Model3	2	CCL, Triple	0.734 (±0.017)	0.867 (±0.012)	5.77 (±0.18)	0.804 (±0.011)	0.837 (±0.007)	9.17 (±0.35)
Model4	3	Drug1, Drug2, CCL	0.714 (±0.019)	0.861 (±0.008)	6.26 (±0.15)	0.793 (±0.009)	0.828 (±0.007)	10.72 (±0.34)
Model5	3	Drug1, Drug2, Triple	0.737 (±0.013)	**0.871** (±0.008)	5.80 (±0.15)	0.798 (±0.008)	0.830 (±0.009)	9.94 (±0.44)
Model6	4	Drug1, Drug2, CCL, Pair	0.736 (±0.016)	0.870 (±0.008)	**5.69** (±0.14)	0.800 (±0.010)	0.833 (±0.005)	9.38 (±0.31)

Effect of hyperparameters and input features on MARSY's performance

As described in Methods, several aspects of MARSY's architecture were design choices selected a priori without hyperparameter tuning. To assess how these choices influence MARSY's performance, we conducted a study based on leave-pair-out 5-fold CV in which we ran MARSY with 576 different combinations of multiple hyperparameters to predict the ZIP score. These hyperparameters and their options included the learning rate (0.01, 0.001, 0.0001), the

optimizer (Adam, Adamax), the input activation function (Linear, ReLU), the batch size (64,

128), the dropout (with or without) and the width and depth of the encoders and the predictor

(see Supplementary Table S3 in Supplementary File S1 for the specific choices).

Our analysis revealed that a large learning rate (0.01) results in poor performance with Adamax

(Figure 4A) and also results in non-convergence of the Adam optimizer. However, the two

smaller learning rates do not suffer from the same issue. When the learning rate is selected

appropriately (the default 0.001 or 0.0001), the effects of other hyperparameters are relatively

small (Figure 4B and 4C). In particular, other than the learning rate, number of encoder layers

and the choice of optimizer had the largest effect, where 2 encoder hidden layers resulted in

1.4% higher median SCC (0.3% higher median PCC) compared to 3 hidden layers and Adamax

resulted in 1.1% higher median SCC (0.5% higher median PCC) compared to Adam (Figure 4C

and Supplementary Figure S7). In conclusion, learning rate seems to have the most effect

(consistent with our experience in other related studies [12]), but when large learning rates are

excluded, the results are not too sensitive to the choice of hyperparameters. However, if

computational complexity is not an issue, marginal improvements can be achieved using

hyperparameter tuning based on an independent validation set.

Figure 4: The effect of hyperparameters on performance of MARSY for prediction of ZIP score in leave-pair-out 5-fold CV. In boxplots, red circle represents MARSY, solid horizontal yellow line shows the median and dashed green line shows the mean. A) Effect of learning rate on the performance of MARSY with Adamax optimizer. B) The histogram of performance metrics based on different hyperparameter options, excluding a learning rate of 0.01. C) The boxplots show the distribution of SCC for different hyperparameter options. Runs with a learning rate of 0.01 are excluded due to the large number of non-converging runs.

MARSY uses LINCS drug signatures to represent each drug. We next asked how the performance of MARSY changes, if alternative drug signatures (e.g., based on their chemical structure) is used instead. We obtained the chemical representations of drugs from the DrugBank database [30] and used the RDKit python library [31] to extract two types of chemical feature representations: "Morgan fingerprints" and "molecular descriptors". To make the evaluation consistent, we only conserved samples from DrugComb for which we could obtain both chemical feature representations and LINCS drug signatures, along with the gene

expression of the CCLs, resulting in 73,768 samples. Table 4 shows the performance of MARSY

with different drug features using this dataset. Considering all three metrics on the two

evaluation setups, LINCS signature performed better compared to Morgan fingerprint and

molecular descriptor. We also concatenated different features to provide a combination of

them as input to the model. Combination of Morgan fingerprints and molecular descriptors

performed better than each of them individually in leave-triple-out, but its performance was

inferior to Morgan fingerprints in leave-pair-out. Additionally, combining all three types of

representations performed slightly better than LINCS signature alone (and the other

representation choices), however one shortcoming of this combination is that it requires

availability of multiple type of representations for each drug, which sometimes limits the

number of datapoints for analysis (as was the case in our study).

Table 4: The performance of MARSY using distinct types of drug features. Evaluation is
performed using 5-fold leave-triple-out and 5-fold leave-pair-out on the prediction of the ZIP
synergy score. Best performance values are in bold-face and underlined. The mean and
standard deviations are calculated across the folds.
379

Drug Features	Leave-Triple-Out			Leave-Pair-Out		
	SCC	PCC	RMSE	SCC	PCC	RMSE
Molecular descriptors	0.702 (±0.014)	0.849 (±0.005)	5.57 (±0.12)	0.676 (±0.016)	0.841 (±0.009)	5.67 (±0.35)
Morgan fingerprints	0.739 (±0.001)	0.858 (±0.007)	5.24 (±0.13)	**0.729** (±0.011)	0.854 (±0.009)	5.36 (±0.21)
Molecular descriptors & Morgan fingerprints	0.746 (±0.003)	0.861 (±0.007)	5.16 (±0.15)	0.714 (±0.016)	0.846 (±0.012)	5.42 (±0.35)
LINCS signature	0.756 (±0.007)	0.869 (±0.005)	5.02 (±0.11)	0.725 (±0.012)	0.857 (±0.009)	**5.22** (±0.29)
All features combined	**0.757** (±0.005)	**0.870** (±0.005)	**5.01** (±0.13)	0.727 (±0.010)	**0.858** (±0.008)	**5.22** (±0.28)

Prediction of drug synergy scores for new triples not present in DrugComb

Next, we used our trained model to predict the ZIP synergy scores of 133,722 new (drug-pair,

CCL) triples that were not present in DrugComb. These triples correspond to all possible

combinations of 69 unique drugs that appeared in at least 10% of the drug-pairs in our training

set (Supplementary Table S4). Given these synergy scores, we first asked which drug-pairs show

a synergistic effect on all 75 CCLs. We identified seven drug-pairs that had a minimum ZIP score

larger than 2 across all CCLs. The majority of these corresponded to the combination of

vincristine (a chemotherapy agent) with other drugs. In particular, two of these combinations

corresponded to tyrosine kinase inhibitors (TKI) lapatinib (mean ZIP = 28.6) and imatinib (mean

ZIP = 17.9) combined with vincristine. Several independent studies have shown the synergistic

effect of these drugs. For example, these two TKIs sensitized KBV20C oral cancer cells to

vincristine, and their combination up-regulated apoptosis and reduced cell viability [32]. In

addition, lapatinib significantly increased the efficacy of vincristine in epidermoid carcinoma C-

A120 cells that overexpress multidrug resistance–associated protein 1 (MRP1) [33]. Another

noteworthy combination corresponded to docetaxel (chemotherapy) and veliparib (a PARP

inhibitor), (mean ZIP = 16.3). The siRNA knockdown of PARP1 in PC3 cell lines has been shown

to enhance docetaxel activity [34], and MARSY predicted the ZIP score of docetaxel and PARP-

inhibitor veliparib in PC3 to be 9.8 (reflecting synergism).

Next, we sought to identify drug combinations that show synergistic effect in a tissue-specific

manner. For this purpose, we focused on breast tissue, since it had the highest number of CCLs

in our cohort (n = 26). To identify breast cancer-specific synergistic combinations, we required

a drug-pair to not be antagonistic in any of the CCLs of breast cancer (minimum ZIP in the tissue

> 0) and then ranked the remaining drug-pairs based on the difference between their mean ZIP

score in CCLs of breast cancer and the mean ZIP score of CCLs of other tissues (Supplementary

Table S5). The top-ranked drug-pair corresponded to combination of paclitaxel (a

chemotherapy widely used in treating breast cancer) and ruxolitinib (a selective JAK1/2 kinase

inhibitor). A one-sided Mann Whitney U test also showed this difference to be statistically

significant (Benjamini-Hochberg false discovery rate = 7.76E-3). Ruxolitinib has been shown to

enhance the efficacy of paclitaxel in a synergistic manner in ovarian cancer cells [35]. Recent

studies of triple negative breast cancer (TNBC) samples has shown that inhibition of JAK1/2 by

ruxolitinib sensitizes cancer cells to paclitaxel, both *in-vitro* and *in-vivo* [36,37]. A phase I clinical

trial of the combination of these two drugs in HER2-negative metastatic breast cancer patients

was recently completed and showed these two drugs to be well tolerated by the participants

[38]. Following these results, a phase II randomized clinical trial is currently undergoing for the

combination of these two drugs in TNBC patients [38]. Our results also showed that TNBC CCLs in

our cohort have a higher mean ZIP score for this drug combination compared to other subtypes

of breast cancer (difference mean ZIP = 1.4).

These examples illustrate the utility of MARSY to suggest synergistic drug combination

candidates for follow-up drug screening experiments.

Discussion and Conclusion

In this study, we proposed MARSY, a novel deep multi-task learning method for prediction of

synergy scores of drug-pairs in difference cancer cell lines. Extensive evaluations using four

different metrics and two methods of data splitting for cross-validation revealed the superior

performance of MARSY compared to various computational models designed for this task.

MARSY's architecture was designed to learn distinct embeddings that capture different and

complimentary views of the input features and are informative not just for drug synergy score

prediction, but also enable single drug response prediction. Given the gene expression profile

of CCLs as well as the LINCS signatures of each drug, the two encoders of MARSY learn different

views of the input features, capturing the interplay of the drugs, as well as the drugs and the

CCL. Our ablation study confirmed that incorporating both of these encoders is beneficial to

the performance of the model. Moreover, the predictor of MARSY utilizes auxiliary tasks of

single drug prediction to enhance the synergy score prediction performance, by enhancing the

embeddings learned during the end-to-end training of the model. We also observed that these

auxiliary tasks can be helpful to other DL-based baseline models.

Unlike many previous models that utilize drug molecular profiles, we used the signatures of

each drug representing the changes in the expression profiles of two cancer cell lines after

administration of the drug. While replacing these signatures with chemical and molecular

information of drugs resulted in a lower performance, integrating them together slightly

improved the results, showcasing the complimentary information available in each of these

data modalities.

In this study, our focus was on developing a transductive model to impute the missing values

in our dataset. As such, we used MARSY to predict the synergy scores of 133,722 new (drug-

pair, CCL) triples that were not present in DrugComb and validated some of these predictions

and insights obtained from them using independent datasets. However, one of the remaining

challenges in this domain is developing models that can predict the synergy scores for unseen

CCLs. Currently, the main challenge in achieving this goal is data availability. For example, after

data cleaning, pre-processing and quality control, we ended up with only 75 CCLs that were

usable for method development in this study. Such small numbers do not allow deep learning

model development that generalizes well to unseen CCLs. However, as new data becomes

available, we expect that this shortcoming of current datasets will be resolved and accurate

models that can generalize to unseen CCLs can be developed.

Funding

This work was supported by the Government of Canada's New Frontiers in Research Fund

(NFRF) [NFRFE-2019-01290] (AE), by Natural Sciences and Engineering Research Council of

Canada (NSERC) grant RGPIN-2019-04460 (AE), and by McGill Initiative in Computational

Medicine (MiCM) (AE). This work was also funded by Génome Québec, the Ministère de

l'Économie et de l'Innovation du Québec, IVADO, the Canada First Research Excellence Fund

and Oncopole, which receives funding from Merck Canada Inc. and the Fonds de Recherche du

Québec – Santé (AE). This research was enabled in part by support provided by Calcul Québec

(www.calculquebec.ca) and Compute Canada (www.computecanada.ca).

Data and Code Availability

All data generated as part of this study are provided as supplementary files. An implementation

of MARSY in python is freely available at: https://github.com/Emad-COMBINE-lab/MARSY.

Supplementary Files

Supplementary File S1: This file contains Supplementary Figures S1-S7, Supplementary Table

S3, and the caption of Supplementary Tables S1, S2, S4, and S5, which are provided as separate

xlsx files.

REFERENCES

1   Li, J., Tong, X.-Y., Zhu, L.-D. & Zhang, H.-Y. A Machine Learning Method for Drug
Combination Prediction. *Frontiers in Genetics* **11**, doi:10.3389/fgene.2020.01000
(2020).
2   Sun, Y. *et al.* Combining genomic and network characteristics for extended capability
in predicting synergistic drugs for cancer. *Nature Communications* **6**, 8481,
doi:10.1038/ncomms9481 (2015).
3   Bayat Mokhtari, R. *et al.* Combination therapy in combating cancer. *Oncotarget* **8**,
38022-38043, doi:10.18632/oncotarget.16723 (2017).
4   Madani Tonekaboni, S. A., Soltan Ghoraie, L., Manem, V. S. K. & Haibe-Kains, B.
Predictive approaches for drug combination discovery in cancer. *Brief Bioinform* **19**,
263-276, doi:10.1093/bib/bbw104 (2018).
5   Li, H., Li, T., Quang, D. & Guan, Y. Network Propagation Predicts Drug Synergy in
Cancers. *Cancer Research* **78**, 5446-5457, doi:10.1158/0008-5472.Can-18-0740 (2018).
6   Li, H., Hu, S., Neamati, N. & Guan, Y. TAIJI: approaching experimental replicates-level
accuracy for drug synergy prediction. *Bioinformatics* **35**, 2338-2339,
doi:10.1093/bioinformatics/bty955 (2018).
7   Li, S. *et al.* Prediction of Synergistic Drug Combinations for Prostate Cancer by
Transcriptomic and Network Characteristics. *Frontiers in Pharmacology* **12**,
doi:10.3389/fphar.2021.634097 (2021).
8   Kuru, H. I., Tastan, O. & Cicek, E. MatchMaker: A Deep Learning Framework for Drug
Synergy Prediction. *IEEE/ACM Trans Comput Biol Bioinform* **Pp**,
doi:10.1109/tcbb.2021.3086702 (2021).
9   Barretina, J. *et al.* The Cancer Cell Line Encyclopedia enables predictive modelling of
anticancer drug sensitivity. *Nature* **483**, 603-607, doi:10.1038/nature11003 (2012).
10   Yang, W. *et al.* Genomics of Drug Sensitivity in Cancer (GDSC): a resource for
therapeutic biomarker discovery in cancer cells. *Nucleic Acids Res* **41**, D955-961,
doi:10.1093/nar/gks1111 (2013).
11   Costello, J. C. *et al.* A community effort to assess and improve drug sensitivity
prediction algorithms. *Nat Biotechnol* **32**, 1202-1212, doi:10.1038/nbt.2877 (2014).
12   Hostallero, D. E., Li, Y. & Emad, A. Looking at the BiG picture: Incorporating bipartite
graphs in drug response prediction. *bioRxiv*, 2021.2008.2011.455993,
doi:10.1101/2021.08.11.455993 (2022).
13   Huang, E. W., Bhope, A., Lim, J., Sinha, S. & Emad, A. Tissue-guided LASSO for
prediction of clinical drug response using preclinical samples. *PLoS Comput Biol* **16**,
e1007607, doi:10.1371/journal.pcbi.1007607 (2020).
14   Hostallero, D. E., Wei, L., Wang, L., Cairns, J. & Emad, A. A Deep Learning Framework
for Prediction of Clinical Drug Response of Cancer Patients and Identification of Drug
Sensitivity Biomarkers using Preclinical Samples. *bioRxiv*, 2021.2007.2006.451273,
doi:10.1101/2021.07.06.451273 (2021).
15   Zagidullin, B. *et al.* DrugComb: an integrative cancer drug combination data portal.
Nucleic Acids Res **47**, W43-w51, doi:10.1093/nar/gkz337 (2019).

16   Amzallag, A., Ramaswamy, S. & Benes, C. H. Statistical assessment and visualization of
synergies for large-scale sparse drug combination datasets. *BMC Bioinformatics* **20**, 83,
doi:10.1186/s12859-019-2642-7 (2019).
17   Sidorov, P., Naulaerts, S., Ariey-Bonnet, J., Pasquier, E. & Ballester, P. J. Predicting
Synergism of Cancer Drug Combinations Using NCI-ALMANAC Data. *Frontiers in*
Chemistry **7**, doi:10.3389/fchem.2019.00509 (2019).
18   Jeon, M., Kim, S., Park, S., Lee, H. & Kang, J. In silico drug combination discovery for
personalized cancer therapy. *BMC Syst Biol* **12**, 16, doi:10.1186/s12918-018-0546-1
(2018).
19   Janizek, J. D., Celik, S. & Lee, S.-I. Explainable machine learning prediction of
synergistic drug combinations for precision cancer medicine. *bioRxiv*, 331769,
doi:10.1101/331769 (2018).
20   Celebi, R., Bear Don't Walk, O., Movva, R., Alpsoy, S. & Dumontier, M. In-silico
Prediction of Synergistic Anti-Cancer Drug Combinations Using Multi-omics Data.
Scientific Reports **9**, 8949, doi:10.1038/s41598-019-45236-6 (2019).
21   Preuer, K. *et al.* DeepSynergy: predicting anti-cancer drug synergy with Deep Learning.
Bioinformatics **34**, 1538-1546, doi:10.1093/bioinformatics/btx806 (2017).
22   Kingma, D. P. & Ba, J. Adam: A method for stochastic optimization. *arXiv preprint*
arXiv:1412.6980 (2014).
23   Reinhold, W. C. *et al.* CellMiner: A Web-Based Suite of Genomic and Pharmacologic
Tools to Explore Transcript and Drug Patterns in the NCI-60 Cell Line Set. *Cancer*
Research **72**, 3499-3511, doi:10.1158/0008-5472.Can-12-1370 (2012).
24   Shankavaram, U. T. *et al.* CellMiner: a relational database and query tool for the NCI-
60 cancer cell lines. *BMC Genomics* **10**, 277, doi:10.1186/1471-2164-10-277 (2009).
25   Subramanian, A. *et al.* A Next Generation Connectivity Map: L1000 Platform and the
First 1,000,000 Profiles. *Cell* **171**, 1437-1452.e1417, doi:10.1016/j.cell.2017.10.049
(2017).
26   Yadav, B., Wennerberg, K., Aittokallio, T. & Tang, J. Searching for Drug Synergy in
Complex Dose–Response Landscapes Using an Interaction Potency Model.
Computational and Structural Biotechnology Journal **13**, 504-513,
doi:https://doi.org/10.1016/j.csbj.2015.09.001 (2015).
27   Malyutina, A. *et al.* Drug combination sensitivity scoring facilitates the discovery of
synergistic and efficacious drug combinations in cancer. *PLOS Computational Biology*
15, e1006752, doi:10.1371/journal.pcbi.1006752 (2019).
28   Zheng, S. *et al.* DrugComb update: a more comprehensive drug sensitivity data
repository and analysis portal. *Nucleic Acids Research* **49**, W174-W184,
doi:10.1093/nar/gkab438 (2021).
29   Douglass, E. F. *et al.* A community challenge for a pancancer drug mechanism of action
inference from perturbational profile data. *Cell Reports Medicine* **3**, 100492,
doi:https://doi.org/10.1016/j.xcrm.2021.100492 (2022).
30   Wishart, D. S. *et al.* DrugBank 5.0: a major update to the DrugBank database for 2018.
Nucleic Acids Res **46**, D1074-d1082, doi:10.1093/nar/gkx1037 (2018).
31   Landrum, G.   (Academic Press Cambridge, 2013).

32   KIM, J. Y., KIM, H. S. & YOON, S. Tyrosine Kinase Inhibitors Imatinib and Erlotinib
Increase Apoptosis of Antimitotic Drug-resistant KBV20C Cells Without Inhibiting P-gp.
Anticancer Research **39**, 3785-3793, doi:10.21873/anticanres.13527 (2019).

33   Ma, S.-l. *et al.* Lapatinib antagonizes multidrug resistance-associated protein 1-
mediated multidrug resistance by inhibiting its transport function. *Mol Med* **20**, 390-
399, doi:10.2119/molmed.2014.00059 (2014).

34   Wu, W. *et al.* Inhibition of PARP1 by small interfering RNA enhances docetaxel activity
against human prostate cancer PC3 cells. *Biochemical and Biophysical Research*
Communications **442**, 127-132, doi:https://doi.org/10.1016/j.bbrc.2013.11.027 (2013).

35   Han, E. S. *et al.* Ruxolitinib synergistically enhances the anti-tumor activity of paclitaxel
in human ovarian cancer. *Oncotarget* **9** (2018).

36   Lian, B. *et al.* Truncated HDAC9 identified by integrated genome-wide screen as the
key modulator for paclitaxel resistance in triple-negative breast cancer. *Theranostics*
10, 11092-11109, doi:10.7150/thno.44997 (2020).

37   Han, J. *et al.* JAK2 regulates paclitaxel resistance in triple negative breast cancers.
Journal of Molecular Medicine **99**, 1783-1795, doi:10.1007/s00109-021-02138-3
(2021).

38   Lynce, F. *et al.* Phase I study of JAK1/2 inhibitor ruxolitinib with weekly paclitaxel for
the treatment of HER2-negative metastatic breast cancer. *Cancer Chemotherapy and*
Pharmacology **87**, 673-679, doi:10.1007/s00280-021-04245-x (2021).