PHAT: interpretable prediction of peptide secondary structures using

hypergraph multi-head attention network and transfer learning

Yi Jiang[1,2#], Ruheng Wang[1,2#], Jiuxin Feng[1,2], Junru Jin[1,2], Sirui Liang[1,2], Zhongshen Li[1,2],

Yingying Yu[1,2], Anjun Ma[3], Ran Su[4], Quan Zou[5], Qin Ma[3*] and Leyi Wei[1,2*]

[1]School of Software, Shandong University, Jinan, China

[2]Joint SDU-NTU Centre for Artificial Intelligence Research (C-FAIR), Shandong University,

Jinan, China

[3]Department of Biomedical Informatics, College of Medicine, The Ohio State University,

Columbus, OH, 43210, USA

[4]College of Intelligence and Computing, Tianjin University, Tianjin, China

[5]Institute of Fundamental and Frontier Sciences, University of Electronic Science and

Technology of China, Chengdu, China

[#]These authors contributed equally to this work as first authors.

*Corresponding authors:

Q.M: Qin.Ma@osumc.edu

L.W: weileyi@sdu.edu.cn

Abstract

Peptides have recently emerged as therapeutic molecules against various diseases, and the secondary structure of peptides is a crucial determinant of their bioactivity. However, accurately predicting peptide secondary structures remains a challenging task due to the lack of peptide sequence data and low prediction efficiency caused by limitations in feature engineering. Therefore, we developed PHAT, a deep learning framework based on a hypergraph multi-head attention network and transfer learning for the prediction of peptide secondary structures. Comparative results demonstrated the outstanding performance and robustness of PHAT. In particular, PHAT automatically learns a set of biologically meaningful knowledge on secondary sub-structures, overcoming the limitations of "black-box" in deep learning-based models and providing good interpretability. Additionally, we demonstrated that the structure information derived from PHAT significantly improved the performance of downstream tasks such as the prediction of peptide toxicity and protein-peptide binding sites. Importantly, we further explored the applicability of PHAT for contact map prediction, which can aid in the reconstruction of peptide 3-D structures, thus highlighting the versatility of our model. To facilitate the use of PHAT, we establish an online server which is accessible via https://server.wei-group.net/PHAT/. We expect our work to assist in the design of functional peptides and contribute to the advancement of structural biology research.

Keywords: peptide secondary structure, hypergraph network, downstream task, interpretability of deep learning.

Introduction

Peptides have recently emerged as potential therapeutic molecules against various diseases, and have garnered increasing attention due to their many advantages, including high specificity, high penetration, low production cost, and ease of manufacturing and modification [1]. Various disease-specific functional peptides have entered the global market, including antiviral peptides (AVPs), antimicrobial peptides (AMPs), and anticancer peptides (ACPs) [2-4]. Specifically, a family of peptides known as cell-penetrating peptides (CPPs) has shown enormous success in the cellular uptake of therapeutic molecules [5]. Currently, over 40 cyclic peptide drugs are in clinical use, and approximately one new cyclic peptide drug is approved for clinical use each year on average [6]. Furthermore, predicting the secondary structure of bioactive peptides can provide key insights into the functional mechanisms of peptides and could serve as a basis for designing peptides with desired functions [1]. Predicting the secondary structure of peptides is an intermediate step in predicting three-dimensional (3D) or tertiary structures, all of which are essential determinants of peptide bioactivity [7]. Therefore, reliable and accurate computational methods for predicting the secondary structures of peptides are urgently needed.

Many efforts have been made to predict the secondary structure of proteins through
computational approaches, most of which are based on machine learning algorithms. For
instance, Heffernan *et al.* developed a multi-task deep learning model [8] in which a long- and
short-term memory bidirectional regression neural network (LSTM-BRNNS) was constructed
to capture both short-term and long-term residue interaction relationships [9]. Li *et al.*
developed the diffusion convolutional recurrent neural network (DCRNN), a hybrid neural
network that alleviates the local features derived from convolutional neural networks (CNNs)
and the global features captured from stacked bi-directional gated recurrent units (BIGRU) to
predict the secondary structures of proteins [10]. Similarly, Busia *et al.* integrated CNN and
residual connections to predict the secondary structures of peptides and achieved good
performance, demonstrating the importance of the primary protein sequence information in
secondary structure prediction [11]. In addition to the above methods, there are many other
protein secondary structure predictors, such as DeepCNF, JPRED, PROTEUS2, RaptorX, and
MUfold-SSW, among others [12-17]. However, these methods are designed for the prediction
of protein structures and are not applicable for secondary structure prediction due to the
inherent structural differences between peptides and proteins. For example, evolutionary
information is frequently integrated and used for model training in the prediction of protein
secondary structures, and potential biases might be introduced when designing peptide
secondary structure models due to the short length of peptides. Additionally, previous studies
have demonstrated that even for identical segments of residues in proteins and peptides, their
secondary structures might be quite different [1]. One possible reason is that proteins have
more complex tertiary structures, which presumably leads to changes in secondary structures.
Particularly, hydrophobic collapse is a major force responsible for a well-defined tertiary
structure. However, this phenomenon is only applicable to proteins and not peptides [18].
Therefore, developing a peptide-specific secondary structure prediction method is urgently
needed.
84
Singh *et al.* [1] proposed PEP2D, the first peptide-specific secondary structure predictor that
trains a random forest (RF) model with peptide sequential and evolutionary data and achieves
good performance. Recently, Cao *et al.* [19] designed PSSP-MVIRT (**P**eptide **S**econdary
Structure **P**rediction based on **M**ulti-**V**iew **I**nformation, **R**estriction and **T**ransfer learning) for
the prediction of peptide secondary structures, employing CNNs and BIGRU to learn
high-latent features and introducing transfer learning to overcome the lack of training data. In
addition to the aforementioned methods, there are several other peptide structure prediction
methods, such as PEP-FOLD [20]. However, existing methods have several limitations.
Particularly, most of them rely heavily on feature engineering to design handcrafted features,
the quality of which might greatly impact the predictive performance because the feature
design is based on the researchers' prior knowledge. Additionally, existing protein-specific
secondary structure prediction methods focus on long-distance dependence of sequences
with hundreds of residues rather than local fragments, whereas peptide-specific methods
focus more on neighborhood information among residues, thus easily ignoring global
information. Ultimately, although deep learning has been successfully used in secondary

structure prediction, the current methods still follow a "black box" model and lack good
interpretability. These shortcomings limit our ability to predict the relationships between
peptide primary sequences and their secondary structures.

In this study, we propose an innovative deep learning model called PHAT to predict peptide
secondary structures. Importantly, our proposed model incorporates several novel features: (*i*)
we introduce a powerful pre-trained protein language model [21] to transfer semantic
knowledge from large-scale proteins to peptides and learn high-latent and long-term features
of peptide residues. (*ii*) Considering the local continuity and diversity of peptide secondary
structures [22, 23], we propose a novel HyperGMA (**Hyper G**raph **M**ulti-head **At**tention
network), in which we can encode peptide residues with multi-semantic secondary structural
information while capturing contextual features from consecutive regions using multi-level
attention mechanisms. Additionally, our constructed hypergraph effectively prevents
over-smoothing, which is a common issue in conventional graph networks (*e.g.*, GCN [24],
GAT [25]). (*iii*) To reveal the predicting mechanisms of PHAT, the transition and emission
matrices were visualized in conditional random fields (CRFs) that can automatically learn a set
of biologically meaningful knowledge on secondary sub-structures. This overcomes the
limitations of "black-box" approaches in deep learning-based models to some extent and
provides good interpretability of our PHAT model. (*iv*) We also demonstrated that the structural
predictions obtained from our model can assist in peptide-related downstream tasks, such as
the prediction of peptide toxicity [26], T-cell receptor (TCR) interactions with MHC (major
histocompatibility complex)-peptide complexes [27], and protein-peptide binding sites. (*v*) A
case study demonstrated that our PHAT can also accurately predict distance map and contact
map matrices, which can be further used for the reconstruction of peptide 3-D structures.
Benchmarking results indicated that the proposed PHAT significantly outperforms the
state-of-the-art methods in either 3-state or 8-state secondary structure prediction,
demonstrating the superiority and robustness of our model. To facilitate the use of our method,
we established a code-free, interactive, and non-programmatic web interface of PHAT at
https://server.wei-group.net/PHAT/, which can lessen the programming burden for biological
and biomedical researchers.

Materials and methods

Datasets

To evaluate the effectiveness of our model, we used the same benchmark dataset commonly
used as a "gold standard" dataset in several studies [19, 28]. The dataset contains 5,772
secondary structures of protein data with three structural states: Helix (H), Strand (E), and Coil
(C). The dataset processing process is illustrated in **Figure 1A**. Specifically, the protein
structures are derived from X-ray crystallography, and this process is executed with a
resolution of at least 2.5 Å, with no chain breaks and less than five unknown amino acids. The
sequence similarity in this dataset is reduced to 25% to ensure a fair performance evaluation.

Additionally, there are some sequences containing the "X" symbol, representing unnatural

residues in this dataset. Following the same data pre-processing in [19], we removed the

unnatural sequences including the "X" symbol, and 4,542 protein and peptide sequences were

retained. Afterward, among the remaining sequences, we selected the sequences with <100

residues lengths, finally yielding 1,285 peptide sequences as our three-structure-state dataset.

The length of the sequences ranged from 30 to 99 residues. Moreover, previous studies have

demonstrated that the secondary structures of protein and peptides can also be defined with

eight states, including H (alpha-helix), G (3_{10}helix), I (π-helix), E (extended beta-strand), B

(isolated beta-strand), T (turns), S (bend), and others (C) [8, 29, 30]. To account for this

scenario, we further constructed a new dataset of 1,060 peptide sequences, derived from the

DSSP (Dictionary of Protein Secondary Structure) structure database [31].

Training and testing datasets

To account for the characteristics of short peptide sequences and fairly evaluate the

performance of the methods, the dataset was divided into two categories: >50 residue

sequences and ≤50 residue sequences. The sequences with ≤50 residues consisting of 257

peptide sequences (with H of 5,294, E of 1,119, and C of 3,733) were used as the test set. The

remaining 1,028 peptide sequences were used as the training dataset. For model training, we

randomly selected 10% peptide sequences as our validation set from the training dataset to

adjust the parameters of our model. Additionally, the training and testing datasets were labeled

with the three-state secondary structures, with the sequence length of peptides ranging from

30 to 100. For the eight-structure-state dataset, we also collected 1,060 sequences to re-train

and test our model. The details of the datasets are summarized in **Supplementary Table 1**

and **Supplementary Table 2**.

Architecture of the proposed PHAT model

The overall network architecture of the PHAT model is illustrated in **Figure 1B** with three main

modules: (*i*) knowledge transfer module, (*ii*) hypergraph embedding module, and (*iii*) feature

fusion and classification module. Specifically, our PHAT model only takes peptide sequences

as input. In module (*i*), to address the scarcity of peptides, our model employs and fine-tuned

and pre-trained large-scale protein language model called ProtT5 for the analysis of our

peptide datasets. By doing so, we can transfer rich contextual information from large-scale

protein sequences to our model and learn discriminative feature embeddings of peptide

sequences. In module (*ii*), we propose a HyperGMA (**Hyper G**raph **M**ulti-head **A**ttention

network) to learn local and global features. Specifically, given a peptide sequence, our model

first exploits the graph extractor to divide the peptide sequence into fragments with particular

lengths as hyperedges and residue groups as hypernodes. Then, by using the hyperedges

and hypernodes, we construct the hypergraph structure and pass it to the HyperGMA to

integrate the sequence information of different scales in the hypergraph structure. Our model

can capture both local and global features at the residue group level and peptide fragment

level through the multi-scale hypergraph attention mechanism. Afterward, in module (*iii*), we

integrate the feature embeddings from the above two channels (knowledge transfer module

and hypergraph embedding module) through an element-wise multiplication strategy.

Furthermore, our model adopts Bi-LSTM (Bidirectional Long Short-Term Memory Networks)

[32] to improve and optimize the feature representation ability and exploits CRFs to learn

useful correlations among the sub-secondary structures. Finally, PHAT takes the resulting

features from module (*iii*) as the input of a Viterbi algorithm and predicts the structural state to

which each peptide residue belongs.

Figure 1. The workflow and framework of PHAT. **(A)** Dataset processing. We extracted the

benchmark datasets from SCRATCH-1D, where the protein and peptide structures were

derived with X-ray crystallography and operated with a resolution of at least 2.5 angstroms, for

three-state and eight-state secondary structures. **(B)** Framework of PHAT. The framework

consists of three modules: *(i)* Knowledge transfer module, *(ii)* Hyper Graph embedding module,

and *(iii)* Fusion and classification module. In Knowledge transfer module, the original

sequences are encoded by a pretrained protein model to gain the features of peptide residues.

In Hyper Graph embedding module, the peptide sequences are constructed into hypergraph

structures and embedded by HyperGMA. In Fusion and classification module, the outputs of

Knowledge transfer module and the Hyper Graph embedding module are firstly fused through

the element-wise multiplication and better integrated by the Bi-LSTM. Then the output of
Bi-LSTM is inputted into the CRF layer, and as a result, the secondary structure of related
residues can be predicted. **(C)** illustrates the details of Hyper Graph embedding module. In the
part of graph extractor, peptide sequences are firstly sliced into fragments with specific length
and constructed as hyperedges of the hypergraph structure. Then the hyperedges are cut into
residue groups to be built as hypernodes in the hypergraph structure. Next, the hypergraph
structure from graph extractor is inputted into HyperGMA to capture the multi-scale
relationships in view of residue groups and peptide fragments by the multi-scale attention
mechanism. **(D)** Online service. Our web server of PHAT is freely available to provide
researchers with peptide details in three-state or eight-state secondary structures, statistical
analysis, and position analysis. The predictions of our model can be applied in many
downstream tasks as in Downstream Analysis.

Feature embedding from the pre-trained model ProtT5

Although there are some differences between proteins and peptides in terms of structure, they
are similar in many aspects such as the transcription process and residue sequence
composition. Therefore, we used the pre-trained model ProtT5 based on the t5-3b model [33],
which was pre-trained using the UniRef50 database [34] (i.e., a database consisting of 45
million protein sequences), in a self-supervised manner to transfer semantic knowledge from
proteins to peptides. Its weight was pre-trained with a BERT-like mask language model
denoising objective using raw protein sequences without labeling. The model can fully learn
the semantic information and generate different residue features belonging to multiple
expressions in different context scenarios.
223
224 The original peptide sequences are fed into ProtT5, and the output vectors are extracted from
225 many encoder blocks that are dependent on the self-attention mechanism. Each encoder
226 block calculates the attention for each residue with all residues in the sequence, aiming to
227 obtain the relevance and importance between every two residues. The calculation formula of
228 the self-attention mechanism is as follows:

$$\mathrm{Attention}(Q, K, V) = \mathrm{softmax}\left(\frac{QK^{T}}{\sqrt{d_{Key}}}\right) \tag{1}$$

229
where Q, K, and V are the query vector, key vector, and value vector of the corresponding
individual residues in the peptide sequence, respectively, and d_{Key} is the dimension of the
input key vector.

Hypergraph multi-head attention networks

Inspired by the previous studies for hypergraphs in natural language processing [35], we
constructed a hypergraph structure by taking the peptide residue groups as nodes and the
peptide fragments as edges. Based on this structure, we proposed a novel HyperGMA. **Figure**

1C shows the hypergraph construction process and HyperGMA architecture. (*i*) The peptide
sequence was inputted into the graph extractor, which takes a particular length as the sliding
window size and moves the sliding window to select the sequence fragments with cross
residues. (*ii*) The sequence fragment is divided into smaller residue groups in a similar way as
in step (*i*) but with a smaller sliding window size. The residue groups are regarded as
hypernodes and the peptide fragments are taken as the hyperedges. (*iii*) The structure of the
hypergraph is constructed using the hyperedges and hypernodes generated from steps (*i*) and
(*ii*). (*iv*) Then, the hypergraph structure is inputted into HyperGMA to extract the graph
embeddings of the peptide sequence.

The context of residues in a peptide sequence describes the language characteristics of local
co-occurrence among residues, and its function in sequence representation learning has also
been proved to be effective. In our model, we established two residues as a group, based on
which we identified 400 types of groups. Moreover, a set of residue groups is regarded as a
hyperedge, which is a sequence fragment with a specific length. This enables our model to
simultaneously capture structural information both at the residue group level and peptide
fragment level. Specifically, a hypergraph is defined as $G = (\nu, \varepsilon)$, where $\nu = \{v_1, v_2, \dots, v_n\}$
represents a set of n nodes in the graph, and $\varepsilon = \{e_1, e_2, \dots, e_m\}$ represents a set of m
hyperedges. Moreover, the model can connect two or more nodes for any hyperedge e_j.

Residue group-level multi-head attention

$$(f_j^l)_m = \sigma\left(\sum_{v_k \in e_j} \alpha_{jk} W_m h_k^{l-1}\right) \tag{2}$$

where k represents the index of the residue group (hypernode) in the fragment (hyperedge)
e_j, j indicates the index of the fragment in edge set ε, $v_k \in e_j$ indicates that v_k is contained
in fragment e_j, h_k^l is the representation of residue group (hypernode) v_k at layer l, σ is the
activation function $LeakyReLU$, W_{m} is the weight matrix trained in the m-head attention, and
m represents the head number of multi heads. α_{jk} is the attention coefficient of the residue
group v_k in the fragment e_j, which can be computed by:

$$\alpha_{jk} = \frac{exp\ (a_m^T u_k)}{\sum_{v_p \in e_j} exp\ (a_m^T u_p)} \tag{3}$$

264 where a_m^T is a weight vector for measuring the importance of residue groups in the m-head
265 attention, $v_p \in e_j$ represents that residue group v_p is contained in fragment e_j, and T
266 means "transpose." u_k represents v_k on the hypergraph defined as:

$$u_k = LeakyReLU(W_m h_k^{l-1}) \tag{4}$$

268 The expression $(f_j^l)_m$ represents hyperedge e_j from m-head attention at layer l. We
269 constructed the multi-head attention mechanism, connected it, and compressed it to the
270 desired dimension after the layer was fully connected. This structure is aimed to capture

271 residue context information. The output f_j^l represents the connected representation of
272 hyperedge e_j at layer l.
273

Peptide fragment-level attention

275 With the representations of all peptide fragments (hyperedges) as $\{f_j^l | \forall e_j \in \varepsilon_i\}$ connecting to
276 residue group v_i, we introduce the fragment level attention mechanism to capture the
277 structural information of peptide fragments with distance interval for learning the next-layer
278 representation of residue group v_i, which is expressed as follows:

$$h_i^l = \sigma(\sum_{e_j \in \varepsilon_i} \beta_{ij} W_{fragment} f_j^l) \tag{5}$$

279 where h_i^l is the output representation of residue group (hypernode) v_i $(v_i \in v)$ at layer l, i
280 represents the index of the residue group (hypernode) in the node set v, all the hyperedges
281 containing residue group v_i are in ε_i, and $W_{fragment}$ is a weight matrix. e_j is a fragment
282 (hyperedge) divided at a fixed length from peptide sequence, and ε_i is the set of fragments of
283 the peptide.
284
285 β_{ij} shows the attention interaction of peptide fragment (hyperedge) e_j on residue group
286 (hypernode) v_i. The computing process is described below:

$$\beta_{ij} = \frac{exp\ (a_{fragment}^T V_j)}{\sum_{e_p \in \varepsilon_i} exp\ (a_{fragment}^T V_p)} \tag{6}$$

287
288 where $a_{fragment}^T$ is a weight vector similar to a_m^T but for measuring the importance of peptide
289 fragments

$$W_{residue} = (||_{i=1}^m W_i) \cdot W_d \tag{7}$$

$$V_j = LeakyReLU([W_{fragment} f_j^l || W_{residue} h_i^{l-1}]) \tag{8}$$

291
292 || represents the concatenation operation, · is matrix multiplication, and W_d is a trainable
293 matrix for dimensional reduction.

Bidirectional long short-term memory and conditional random field

The secondary structural information in peptide sequences is often related to the residues in
the forward and backward peptide fragments. Therefore, we implemented Bi-LSTM
(Bidirectional Long Short-Term Memory Networks) to extract information from two directions in
the peptide sequence. Additionally, the previously learned features from ProtT5 and
HyperGMA are fused in the form of element-wise multiplication, which may introduce
redundant information. Therefore, we added a layer of Bi-LSTM to better integrate them and

provide a sequence-level view for the CRF layer. Bi-LSTM is a deep-learning architecture with
two LSTM layers in different directions, which can capture the dependence of long-distance
residues, and selectively learn and forget information with corresponding importance through
training [36]. Moreover, LSTM has three gate structures (inputting gate, forgetting gate, and
outputting gate) and a Cell State's hiding state. In LSTM, the inputting gate is responsible for
processing the input of the current sequence position, whereas the forgetting gate controls
whether the hidden cell state of the upper layer must be forgotten based on probability. The
results of the forgetting gate and inputting gate will act on the cell state. Then, information from
the previous sequence, the current sequence, and the cell state will be combined with the
activation function and weights to obtain the output. Therefore, the model can better capture
semantic information of peptide sequences and the prediction can more accurately select
Bi-LSTM, as shown in **Supplementary Figure 1**.
313
To the best of our knowledge, our model is the first to determine the probability of each residue
belonging to specific secondary structures by adding a linear layer with the softmax function
behind the Bi-LSTM, after which the label with the highest probability can be obtained.
However, this will ignore the correlation among secondary structures and decrease the
prediction performance. Alternatively, we chose the CRF approach, which is widely used in
named entity recognition to predict secondary structures, while exploring the context-related
interactions between secondary structures and residue level contributions to all secondary
structures.
322
CRFs consist of emission matrices including the probability of residues occupying different
secondary structure states and transition matrices including the likelihood of transferring one
secondary sub-structure state to another. During the training process, the model uses the
forward and backward algorithms to infer the conditional probability of the secondary
structures at each position of the sequence and finally predict the secondary structure by the
scoring matrices. The specific calculation process is described below.
329
330 There are two kinds of feature functions. The first is referred to as the emission function, which
331 is only related to the current position i in the peptide sequence:

$$e_l(y_i, x, i) \quad l = 1, 2, ..., L \tag{9}$$

332 where x represents all residues of the peptide, y_i represents the secondary structure at
333 position i, and L indicates the number of all secondary structures.
334
335 The second function is defined in the context of secondary structures and is referred to as the
336 transition function, which is related to the current structure y_i and the previous structure y_{i-1}:

$$t_k(y_{i-1}, y_i, x, i) \quad k = 1, 2, ..., K \tag{10}$$

337 where K indicates the number of all permutations of two secondary structure states, which is
338 9 for 3-state secondary structures and 64 for 8-state secondary structures.
339

340   Assuming that we have K_1 transition functions and K_2 emission functions, there are a total of

341   K_1+K_2 feature functions. We then used the formula $f_k(y_{i-1}, y_i, x, i)$ to express them:

$$f_k(y_{i-1}, y_i, x, i) = \begin{cases} t_k(y_{i-1}, y_i, x, i) & k = 1,2, \dots K_1 \\ e_l(y_i, x, i) & k = K_1 + l, \quad l = 1,2, \dots, K_2 \end{cases} \tag{11}$$

342   We also unified the weight coefficient $f_k(y_{i-1}, y_i, x, i)$ with w_k:

$$w_k = \begin{cases} \lambda_k, & k = 1,2, \dots K_1 \\ \mu_l, & k = K_1 + l, \quad l = 1,2, \dots, K_2 \end{cases} \tag{12}$$

343   where λ_k represents the weight coefficient of the k-th transition function and μ_l represents

344   the weight l-th coefficient of the emission function.

346   The parametric form is simplified as:

$$P(y|x) = \frac{1}{Z(x)} exp \sum_{k=1}^{K_1+K_2} w_k f_k(y, x) \tag{13}$$

347    $Z(x)$ is the normalization factor:

$$Z(x) = \sum_{y} exp \sum_{k=1}^{K_1+K_2} w_k f_k(y, x) \tag{14}$$

In the traditional CRF, we find that the only global transition matrix is easily affected by the

noise from datasets, resulting in unstable prediction results. To solve this problem, we first

arranged the outputs from Bi-LSTM into linear layers, transferring the outputs to local transition

matrices with the same dimension as the global transition matrix. Then, we connected them to

the global transition matrix, as using the fused transition matrices can improve the ability of our

model to assess different datasets. The details of our CRF architecture are shown in

Supplementary Figure 2.

Model training and predicting process

Training process

We introduced the Bi-LSTM-CRF layer to fuse features and predict the secondary structure of

peptides. In Bi-LSTM-CRF, the secondary structure label paths are constructed with the

emission and transition matrices. The loss function of our model consists of two parts, the

score of the real label path and the total score of all paths, with different secondary structure

label combinations. The score of the real path should be the highest in all paths and the goal of

our optimization is to minimize the gap between the predicted score and the real score.

If a certain path is a real path and the secondary structure label sequence is the correct

prediction result, then it should have the highest score of all possible paths. According to the

following loss function, the parameters of our model will be updated continuously with every

iteration of the training process, making the ratio of the score of the real path to the total score

larger.

$$Loss = -\log\left(\frac{S_{real\,path}}{S_{total}}\right) \tag{15}$$

Assuming that the score of each possible path is S_i, and there are *n* paths in total, then the total score of all paths is (where e is Euler number):

$$S_{total} = e^{S_1} + e^{S_2} + \dots + e^{S_n} \tag{16}$$

Next, the composition of S_k can be expressed as follows:

$$S_k = EmissionScore + TransitionScore \tag{17}$$

$$EmissionScore = e_{1(x_1 \to y_1)} + e_{2(x_2 \to y_2)} + \dots + e_{n(x_n \to y_n)} \tag{18}$$

The $e_{i(x_i \to y_i)}$ is the score function resulting in a probability to predict the current residue x_i as the secondary structure y_i.

$$TransitionScore = t_{(start \to y_1)} + t_{(y_1 \to y_2)} + \dots + t_{(y_n \to end)} \tag{19}$$

where $t_{i(y_i \to y_j)}$ is the score function in support of generating the probability of transferring the secondary structure y_i to y_j.

Prediction process

In the prediction process, the Viterbi algorithm [37] is used to obtain the secondary structure prediction. The Viterbi algorithm is a dynamic programming algorithm that uses the start and end states and the recurrence formula to gain the secondary structure labels. The input of the Viterbi algorithm consists of K feature functions of the model, K weights related to the functions, the observation peptide sequence $x = (x_1, x_2, \dots, x_n)$, and the number of secondary structure states m. The output of this calculation is the optimal prediction secondary structure label sequence $y^* = (y_1^*, y_2^*, \dots, y_n^*)$. The details of the prediction process of the Viterbi algorithm are described below.

First, the start recursive algorithm is initialized as:

$$\delta_1(l) = \sum_{k=1}^{K} w_k f_k(y_0 = start, y_1 = l, x, i), l = 1,2, \dots, L \tag{20}$$

$$\psi_1(l) = start, l = 1,2, \dots, L \tag{21}$$

where L is the number of secondary structure labels.

For $i = 1,2, \dots, n-1$, the recursion formula is performed as follows:

$$\delta_{i+1}(l) = \max_{1 \le j \le L}\left\{\delta_i(j) + \sum_{k=1}^{K} w_k f_k(y_i = j, y_{i+1} = l, x, i)\right\}, l = 1,2, \dots, L \tag{22}$$

$$\psi_{i+1}(l) = arg\max_{1 \le j \le L}\left\{\delta_i(j) + \sum_{k=1}^{K} w_k f_k(y_i = j, y_{i+1} = l, x, i)\right\}, l = 1,2, \dots, L \tag{23}$$

398   When the following condition occurs, program recursion is stopped:

$$y_n^* = arg \max_{1 \leq j \leq L} \delta_n(j) \tag{24}$$

399   Through the backtracking algorithm, we obtain the final prediction structure:

$$y_i^* = \psi_{i+1}(y_{i+1}^*), i = n-1, n-2, ..., 1 \tag{25}$$

400   In the end, the prediction is:

$$y^* = (y_1^*, y_2^*, ..., y_n^*) \tag{26}$$

Performance metrics

The performance of our proposed PHAT is evaluated by the accuracy and SOV (segment
overlap measure) for each secondary structure state. Acc_i, F1-score$_i$ {i represents the
secondary structure element [H(Helix), E(Sheet) or C(Coil) for 3-state and H(alpha-helix),
G(3_{10}helix), I(π-helix), E(extended beta-strand), B(isolated beta-strand), T (turns), S (bend)
and others (C) for 8-state]}, the accuracy in all states (hereinafter referred to as Acc), and SOV
are calculated as follows:

$$Acc_i = \frac{A_{ii}}{A_i} \tag{27}$$

$$Acc = \sum \alpha_i \frac{\sum_{i \in \{structure\ element\}} A_{ii}}{\sum_{i \in \{structure\ element\}} A_i} \tag{28}$$

$$F1 - score_i = \frac{2P_i R_i}{P_i + R_i} \tag{29}$$

$$Macro - F1 = \frac{\sum_{i \in \{structure\ element\}} F1 - score_i}{n} \tag{30}$$

$$SOV = \frac{\sum_{i \in \{structure\ element\}} \sum_{si} \frac{min\ ov(s1, s2) + \delta(s1, s2)}{max\ ov(s1, s2)} \cdot len(s1)}{N} \tag{31}$$

where A_i is the sum of correctly predicted residues in each state; A_{ii} is the number of
correctly predicted residues in state i; α_i is the proportion of state i in the entire test set; P_i
indicates the proportion of residues correctly predicted to be i among those predicted to be i;
R_i is the proportion of residues correctly predicted to be i among residues with the actual i;
$s1$ and $s2$ are segments corresponding to actual and predicted secondary structures; $len(s1)$
represents the number of residues defining the segment $s1$; $max\ ov(s1, s2)$ is the maximum
length overlap of $s1$ and $s2$ for which either of the segments has a residue in state i;
$min\ ov(s1, s2)$ represents the length overlapping $s1$ segments and $s2$ segments. $\delta(s1, s2)$ is
calculated as follows:

$$\delta(s1,s2) = min \begin{cases} (\max ov(s1,s2) - \min ov(s1,s2)) \\ (\min ov(s1,s2)) \\ \left(\dfrac{int(len(s1))}{2}\right) \\ \left(\dfrac{int(len(s2))}{2}\right) \end{cases} \tag{32}$$

420 The normalization value N is a sum of $N(i)$ over the entire set of conformational states:

$$N = \sum_{i \in \{structure\ element\}} N(i) \tag{33}$$

SOV was introduced because the segment overlap measure treats H, E, and C on an equal
basis (eight-state assignment is the same). There are no arbitrary cutoffs on segment length,
thus ensuring a consecutive and threshold-free assessment of prediction accuracy.

Results

PHAT outperforms existing methods when analyzing an independent testing set

To evaluate the performance of the proposed PHAT model, we compared it with four
state-of-the-art methods: PROTEUS2 [14], RaptorX [16], Jpred [12], and PSSP-MVIRT [19].
The first three were designed for protein secondary structure prediction whereas the other is
for peptide secondary structure prediction. To ensure a fair comparison, the models were
executed and evaluated using the same independent test set. As shown in **Supplementary**
Table 3, PHAT achieved the best performance among all of the tested methods, with an Acc of
84.07%, Acc_H of 89.08%, Acc_E of 71.76%, Acc_C of 80.66%, and SOV of 79.78%. Specifically,
compared to other existing methods, our method delivered 1.39% to 19.26% higher SOV
values (see **Figure 2A and Supplementary Table 3**), which is an important metric at the
segment level and evaluates the overall performance of the methods. The superior SOV
performance of our proposed model might be related to the context information of the peptide
sequences extracted by the Bi-LSTM-CRF layer and multi-scale features captured by the
hypergraph multi-head attention network. Furthermore, all methods exhibited a relatively low
accuracy in the prediction of the structural state E compared to the other two states (H and C).
This was due to the low proportion of E in the dataset (see **Figure 2B and Supplementary**
Table 1). Therefore, the existing models capture more information for the H and C states,
rather than E, during model training. Nevertheless, our PHAT achieved the highest accuracy at
E among all of the evaluated methods. This was likely because our multi-head attention
mechanism is capable of capturing a more informative structural representation of E.
Additionally, the comparison results in the dataset of the eight-state secondary structure
shown in **Supplementary Table 9** also demonstrate the outstanding performance of our
method. Therefore, we concluded that our method is more effective than Jpred, PSSP-MVIRT,

PROTEUS2, and RaptorX in the prediction of peptide secondary structures, especially for

Acc_E, Acc, and SOV.

Figure 2. The performances of our method and existing methods on independent test subsets, comparison of different encoding strategies, and visualization of different methods on one peptide: (**A**) SOV, macro-F1, and F1-score_H are used as the evaluation metrics; (**B**) F1-scores under three sub-structures are used as the evaluation metrics. (**C**) SOV of four methods at the different length intervals. (**D–G**) represent PCA visualization results of individual features of ProtT5, HyperGMA, and the fusion features in multiplication or additive respectively; (**H, J, K**) represent the comparison between multiplication fusion strategy and other three strategies. (**I**) represents performance comparison between HyperGMA and TextCNN. (**L**) The visualization of predictions by our method and other two methods for the peptide with PDB ID: 2w25.

Length preference investigation for peptide secondary structure prediction

Previous studies have demonstrated that the functionality of peptides (e.g., affinity) is easily
affected by the length of sequences, with most bioactive peptides being normally less than 40
residues long[19, 38, 39] . To investigate if our model had length biases for peptide secondary
structure prediction, we further explored whether peptide length affected the performance of
our model. We first divided the test set into four subsets with different length intervals ([30, 35],
(35, 40], (40, 45], and (45, 50]), then separately evaluated our model and existing methods
using the subsets. **Figure 2C** and **Supplementary Figure 3** show the SOV, Acc, and F1-score
of the different methods for the prediction of peptide secondary structures using the
aforementioned subsets. As illustrated in **Supplementary Figure 3,** the performance of all of
the tested methods clearly decreased as the length of the sequences declined, which indicates
that shorter sequences are more difficult to predict as their contextual information is less.
Furthermore, as illustrated in **Figure 2C**, the SOV score of our method was higher than that of
the other methods in almost all ranges of peptide sequence lengths. Particularly, our PHAT
model exhibited an outstanding performance, with average Acc, SOV, and F1-score values up
to 7.02%, 6.21%, and 3.33% higher than the runner-up PSSP-MVIRT in different sequence
length intervals. These results demonstrate that our method is better at the prediction of
shorter peptides.

Exploration of the optimal architecture of our model

To investigate the performances of our model using different encoding strategies, we
compared the prediction results of different encoding strategies including the two individual
feature extractors (HyperGMA and ProtT5) and their different fusion combinations.
Supplementary Table 4 shows that our final element-wise multiplication strategy achieves an
Acc of 84.07%, Acc_H of 89.08%, Acc_E of 71.76%, Acc_C of 80.66%, and SOV of 79.78%,
outperforming the Acc and SOV of ProtT5 by 1.77% and 5.79% and the fused extractor in the
additive strategy by 1.36% and 5.64%, respectively. Furthermore, although ProtT5 performed
better than HyperGMA, the model performed better than the individual extractors and the
fused extractor in the additive strategy after fusing the features from HyperGMA and ProtT5
with the element-wise multiplication fusion strategy. This indicated that the different
information is complementary to each other in the fusion strategy, thus effectively improving
the predictive performance of the model. Moreover, it can be seen from **Figure 2H-2K** that the
element-wise multiplication fusion strategy of HyperGMA and ProtT5 achieved better
performance than the fusion strategies of TextCNN and ProtT5 in terms of Acc and SOV.
498
To further illustrate the effect of different encoding strategies more intuitively, we visualized the
distribution of feature representations in the test set, which reveals the discriminability of
features for distinguishing different secondary sub-structure states through dimension

reduction. In the principal component analysis (PCA) [40] in **Figure 2D-2G**, each point

represents a site in the peptide sequence and different colors are used to distinguish the Helix

(H), Strand (E), and Coil (C) secondary structures. Compared with the two fusion strategies,

the distribution of the site samples belonging to different classes in the feature space from the

individual ProtT5 and HyperGMA are almost connected, making it difficult to distinguish the

region for each secondary sub-structure class. Regarding the two fusion strategies, the site

samples of three classes are more clearly distributed in the feature space of the multiplication

fusion strategy (**Figure 2F**) than in the feature space of the additive fusion strategy (**Figure**

2G). Furthermore, to avoid biases between different dimension reduction methods, we also

applied another non-linear method T-SNE [41] for dimension reduction, and similar results can

be seen in **Supplementary Figure 3**. In conclusion, our results demonstrate that our PHAT

model with the multiplication fusion strategy can capture more discriminative and high-quality

features.

The PHAT model has good interpretability in terms of extracting multi-scale features

and making classifications

To verify the effect of the Bi-LSTM-CRF layer in our model, we compared the performance of

our model under two training strategies (Cross Entropy loss function and Bi-LSTM-CRF), and

the results are shown in **Supplementary Table 5**. Clearly, our model with Bi-LSTM-CRF layer

performed better (especially in terms of SOV) than the model using the Cross-Entropy loss

function. To explain how the Bi-LSTM-CRF efficiently predicts the secondary structure at each

site in the peptide sequence, we randomly selected and predicted the secondary structures of

the peptide sequence with PDB ID 1edm chain B (Protein Data Bank Identity). Afterward, we

chose several sites of this peptide and visualized the corresponding weights of the transition

matrix and emission matrices from our model in **Figure 3A**. As illustrated in **Figure 3A**, the

secondary structure labels corresponding to the highest values in the emission matrices match

the real secondary structures of the residues. Moreover, the probability of transferring the

labels of the current residues to the real labels of the adjacent residues was the highest in the

transition matrices.

To further explore the role HyperGMA of in our model, we visualized and analyzed the

attention matrices from HyperGMA in **Figure 3**. The HyperGMA includes two main steps, the

residue group level attention encoding and the peptide fragment level attention encoding. In

the first step, the feature representations of peptide fragments are aggregated from the

contained residue groups through the residue group level multi-head attention mechanism.

The contribution of each residue group to corresponding peptide fragments is shown in **Figure**

3B. Moreover, **Figure 3C** illustrates that the peptide fragments are more likely to reflect the

characteristics of specific residue groups, meaning that the peptide fragments are more

strongly influenced by local information. In the second step, the feature representation of the

residue group is encoded by the peptide fragments where it exists through the fragment level
attention mechanism. The contribution of the peptide fragment to corresponding residue
groups is shown in **Figure 3C**, which indicates that a given residue group can aggregate the
information from different fragments where it exists. Therefore, our model can better capture
the local and global information by collecting secondary structure information at the residue
group level and peptide fragment level using HyperGMA.

Figure 3. The Interpretability of our model. (**A**) Visualization of the weights of transition
matrix and emission matrix in Bi-LSTM-CRF layer. The emission matrix and transition matrix
are calculated by our model. The emission matrix shows the possibilities of current site in
different classes and the transition matrix indicates the possibility of the secondary structure
transformation in adjacent positions. (**B-C**) Visualization of the attention matrices in
hypergraph multi-head attention network, where **B** represents the attention of peptide
fragments to residue groups and **C** represents the attention of residue groups to peptide
fragments. Darker color means stronger attention.

Application of our PHAT model in three peptide related downstream tasks

Several experiments were conducted to verify that the secondary structures predicted by our
method can be useful for downstream tasks. **Figure 4A-4C** shows the results of prediction of
peptide toxicity, prediction of T-cell receptor interactions with MHC-peptide complexes, and
prediction of protein-peptide binding sites, respectively. In **Figure 4**, it can be seen that when
fused with the structure predictions of our PHAT model, the evaluated methods (ATSE,
NetTCR-2.0, and PepBCL) achieve higher performance in terms of most metrics than without

the PHAT predictions. Similar results were observed with the methods fused with structure

predictions from PROTEUS2 and PSSP-MVIRT in the corresponding task.

Figure 4. Comparative results for three downstream tasks. (A) shows the results on the

task of prediction of peptide toxicity. **(B)** shows the results on the task of prediction of T-cell

receptor interactions with MHC-peptide complexes. **(C)** shows the results on the task of

prediction of protein-peptide binding sites. **(D)** shows ROC curve and Precision-Recall cure of

comparison experiment in ATSE. **(E)** and **(F)** show density of positive and negative examples

under different confidence in prediction of peptide toxicity. **(G)** shows ROC curve and

Precision-Recall cure of comparison experiment in NetTCR-2.0. **(H)** and **(I)** show density of

positive and negative examples under different confidence in prediction of TCR interactions

with MHC-peptide complexes.

PHAT has an outstanding performance for aiding in predicting peptide toxicity

We first used the methods (PSSP-MVIRT, PROTEUS2, and PHAT) to predict the secondary

structures of the dataset in ATSE [26], a peptide toxicity predictor, and add the secondary

structures from the three methods to ATSE. As shown in **Figure 4D** and **Supplementary**

Table 6, ATSE with our PHAT model achieved an SN of 95.06%, SP of 93.4%, Acc of 94.74%,

MCC of 89.62%, AUC of 96.7% (the definition of these metrics can be found in Supplementary

metrics), which constituted a 0.17%, 0.18%, 0.43%, 0.5%, and 1.1% higher performance than

ATSE with PROTEUS2, and a 0.25%, 0.37%, 0.88%, 1.87%, and 0.8% higher performance

than ATSE with PSSP-MVIRT, respectively. Additionally, **Figure 4E-4F** shows PHAT had an

outstanding performance for the prediction and classification of ATSE, and there was also a

general improvement over the original method. These results demonstrate the efficiency of our
model to predict secondary structures to assist in peptide toxicity prediction. Particularly, the
higher SOV of our method reveals that our model can more accurately capture the integrity
and continuity of secondary structures, which may explain the superior performance of our
method.
591
Secondary structure is an important determinant of toxicity [42]. However, few studies have
used the secondary structure of peptides to predict peptide toxicity. Predicting the secondary
structures of peptides by various methods can compensate for these limitations and build a
bridge between peptide secondary structure and peptide toxicity.

PHAT achieves superior performance for the prediction of T-cell receptor interactions

with MHC-peptide complexes

Our prediction of the secondary structure of peptides can also be applied to the study of T-cell
receptor interactions with MHC-peptide complexes. Here, we used the NetTCR-2.0 method
[27], which has a CNN architecture, to predict the interactions between the α/β TCR and
MHC-peptide sequences and assess the effect of adding secondary structures predicted from
the three methods (PSSP-MVIRT, PROTEUS2, and our PHAT). As indicated in **Figure 4G**
and **Supplementary Table 7**, analysis of the NetTCR-2.0 dataset with PHAT achieved an
average Acc of 94.04%, a precision of 45.54%, a recall of 78.6%, an F1-score of 57.29%, and
an AUC of 92.7%, which was higher than the original method by 0.61%, 3.52%, 2.61%, and
2.4%, respectively. Furthermore, our model outperformed the Acc, Precision, F1-score, and
AUC of PSSP-MVIRT by 0.38%, 1.61%, 1.28%, and 1%, as well as PROTEUS2 by 0.59%,
2.29%, 1.82%, and 1.3%, respectively. Moreover, **Figure 4H-4I** shows that PHAT achieved a
better prediction of NetTCR-2.0 classification.
610
Additionally, we found that two groups of α/β TCR sequences, which have similar sequences
but different secondary structures, cannot be classified correctly using NetTCR-2.0 without
adding secondary structures. Fortunately, they were accurately predicted after introducing the
secondary structure features from our PHAT model. In **Supplementary Figure 4**, we
visualized the secondary structures of the two peptide sequences predicted by our method.
Therefore, our findings demonstrated that the secondary structures predicted by our method
provide useful biochemical information and improve the performance of NetTCR-2.0. In
conclusion, the above results can prove that our prediction of peptide secondary structures
has a positive effect on promoting the accuracy of TCR tasks and provide a new direction for
TCR research.

PHAT exhibited competitive performance for assisting in the prediction of

protein-peptide binding sites

Protein-peptide interactions are involved in various fundamental cellular functions and are crucial for designing new peptide drugs. To explore the effect of the secondary structures from our model in the prediction of protein-peptide binding sites, comparison experiments with the PepBCL model were conducted [43]. Specifically, we first combined our structure predictions with the features from the PepBCL model. Then, protein-peptide binding site predictions were conducted based on a random forest machine learning method [44]. In a previous study that used the PepBCL model [36], the secondary structure from SPOT-1D-Single was introduced to generate structural features, which we generated in the same way. In this context, the efficiency of our prediction can be verified by comparing secondary structures from several different sources (**Supplementary Table 8**). Our findings indicated that the application of peptide secondary structures predicted by our PHAT achieves significantly better performance than other methods. Some researchers have already incorporated secondary structures into their predictions. Moreover, the prediction of more accurate and continuous secondary structures may enhance the efficiency of site mining. As illustrated in **Figure 4C**, the features from PepBCL combined with the prediction of PHAT can achieve higher AUC and MCC than using peptide secondary structures from other methods.

The visualization of two cases demonstrated that our proposed PHAT method performs

better than existing methods

To intuitively assess the performance of existing methods, we first randomly selected two peptide chains (PDB ID: 2w25A and 1ejbA) with experimental secondary structures, and applied different methods (PHAT, RaptorX, PSSP-MVIRT, PROTEUS2, and Jpred) for the prediction of the secondary structure of two peptides. As illustrated in **Figure 2L and Supplementary Figure 5**, the secondary structures from different methods were mapped into the tertiary structures, where the red area represents Helix (H), the yellow area represents Strand (E), and the green area represents Coil (C). The differences between the structures predicted by our method and the experimental ones were smaller than those of the predictions of the other methods described above. In **Figure 2L**, our model achieved more correct Helix (H) and Strand (E) predictions, whereas the other methods were more likely to identify the Helix (H) and Strand (E) structures as a Coil (C). Furthermore, in **Supplementary Figure 5**, the other four methods (RaptorX, PSSP-MVIRT, PROTEUS2, and Jpred) tended to predict the Coil (C) as Helix (H), whereas our method made more correct predictions in local consecutive sequence regions. In conclusion, our method can achieve better performance in terms of continuity and accuracy compared to the existing methods.

The proposed PHAT model facilitates the construction of 3-D peptide structures

To explore the potential of PHAT in capturing 3-D structure information of peptides, we used

our model to predict the distance map and contact map matrices, which is an essential

process in protein 3-D structure prediction. The workflow of exploration is shown in **Figure 5A**.

Specifically, our PHAT model was first trained using a secondary structure dataset to capture

the 2-D structure information of the peptide. Then, a fully connected network was added to our

model and fine-tuned using the contact map dataset (the details are shown in **Supplementary**

Table 10) to obtain the distance information of the 3-D structure. Next, we calculated the

distance of each amino acid pair to construct the distance map and contact map of the peptide

sequence. Compared with the experimental results from the test set, our model achieved an

average variation of less than 1 Å for each amino acid pair in terms of distance map prediction.

To intuitively assess the performance of our model, we visualized and compared our

predictions with the state-of-the-art method trRosetta [45-47] based on the experimental

results from a randomly selected peptide with PDB ID 7ve4 (**Figure 5B**). Our predicted contact

map is more accurate in terms of contacting amino acid pairs than the one obtained with

trRosetta. Additionally, our predicted distance map is closer to the experimental result than the

trRosetta-generated map, indicating that our model can more accurately capture the distance

between amino acids. With our predicted contact maps and distance maps, the 3-D structures

of corresponding peptides can be reconstructed more realistically by folding algorithms [48-50].

In this case, we extended our prediction of the secondary structure to the contact map and

distance map, thus aiding in the prediction of the peptide 3-D structure. Therefore, our PHAT

model has the potential to promote the development of therapeutic molecules against various

diseases, as well as the design of functional peptides [40].

Figure 5. The exploration in constructing 3-D structure of peptide with our method. (A)
The workflow of assisting in building 3-D peptide structure with our predicted contact and
distance map matrices. **(B)** The visualization of contact map and distance map matrices of
experimental results, trRosetta prediction and our prediction for the peptide with PDB ID: 7ve4.

Discussion and Conclusion

In this study, we developed PHAT, a deep learning-based method for peptide secondary
structure prediction, and systematically evaluated it using benchmark datasets. Compared
with other methods designed for protein secondary structure prediction, our model achieved
superior performance in most metrics, especially Acc_E and SOV. The conventional methods
designed for the prediction of protein structure might be biased toward extracting long-distance
dependence within protein sequences with hundreds of residues. However, the peptides in our
dataset are significantly shorter than most proteins, and therefore the neighborhood
information in peptides may not be easily captured by these methods. In contrast, our method
can capture more contextual information of peptide sequences through the hypergraph
multi-head attention network, and can thus make more correct predictions in local consecutive

sequence regions, as demonstrated by the visualization of our predictions for two peptides
(PDB ID: 2w25A and 1ejbA).

Similar results can be seen when comparing the peptide-specific secondary structure
predictors (e.g., PSSP-MVIRT) with our method. This is likely because previous methods
designed for peptides focus more on neighborhood information of peptide residues and
therefore tend to ignore long-term information. In contrast, in addition to being capable of
capturing contextual information, our method can obtain long-term and bio-semantic
knowledge for peptide sequences by using ProtT5, a model pre-trained with millions of protein
sequences, thus achieving a good prediction performance. The peptide length preference
experiments for secondary structure prediction illustrated that although the prediction
performance of the tested methods decreased as the length of the sequences declined, our
method achieved better performance than other existing methods when analyzing shorter
peptide sequences. This indicated that our model can integrate contextual information and
long-term knowledge to make predictions.

Moreover, to reveal the feature extraction and prediction mechanisms of our PHAT model, we
visualized matrices of a hypergraph multi-head attention network (HyperGMA) and
Bi-LSTM-CRF, which provide good interpretability while achieving an outstanding prediction
performance. Specifically, the visualization of attention matrices in HyperGMA demonstrated
that our model can effectively capture the local and global features of peptides at the residue
group-level and the peptide fragment-level, thus providing insights into its attention
mechanisms. Similarly, the visualization of the classification layer in Bi-LSTM-CRF illustrates
that CRFs can guide our model to efficiently predict the secondary structure for each site in the
peptide sequences.

Furthermore, to verify the accuracy of the secondary structures predicted by our model in
downstream tasks, we applied our predicted structural information to the prediction of peptide
toxicity, T-cell receptor interactions with MHC-peptide complexes, and identification of
protein-peptide binding sites. Using the secondary structures predicted by our model
enhanced the performances of these tasks, which indicated that our predicted structural
information can assist in predicting more accurate properties and is complementary to
sequential and evolutionary features in peptide-related downstream tasks. Additionally, to
explore the potential of PHAT in capturing 3-D structural information of peptides, we applied
our model to predict distance map and contact map matrices and achieved an outstanding
performance, thus demonstrating that our model can help in the reconstruction of peptide 3-D
structures. We also developed an online service (the workflow is shown in **Figure 1D**) to
implement our PHAT, thus saving researchers the need to write programs or scripts. We hope
that this online tool will be helpful to the research community.

Although our PHAT model achieves improved performances for predicting peptide secondary
structure, there is still room for improvement. For example, PHAT is meant to be used for

general peptide secondary structure prediction, and therefore we focused particularly on
sequences with lengths <50. However, for datasets with peptide sequences longer than 50, we
cannot ensure that our method will have the same performance. Moreover, when interacting
with other targets (e.g., protein, DNA, RNA, *etc.*), peptide sequences remain the same, but the
secondary structure of the peptides may change considerably. However, our PHAT makes its
predictions based on the sequence patterns and thus cannot make adjustments to account for
potential molecular interactions. Therefore, we are planning to incorporate additional data
such as interaction information with other targets to further improve the prediction of peptide
secondary structures in different interacting scenarios.

Data Availability

The authors declare that the data supporting the findings of this study are available within the
article and its supplementary information files. Besides, the benchmarking datasets and our
source code were also available for downloading at https://server.wei-group.net/PSSPHAT/.
752

753 **Funding**

754 The work was supported by the Natural Science Foundation of China (Nos. 62071278 and
755 62072329), and Natural Science Foundation of Shandong Province (ZR2020ZD35).
756

757 **Conflict of Interest**

758 The authors declare that they have no competing interests.
759

References

1. Singh, H., S. Singh, and G.P.S. Raghava, *Peptide secondary structure prediction*
using evolutionary information. BioRxiv, 2019: p. 558791.
2. Chowdhury, A.S., et al., *Better understanding and prediction of antiviral peptides*
through primary and secondary structure feature importance. 2020. **10**(1): p. 1-8.
3. He, W., et al., *Learning embedding features based on multisense-scaled attention*
architecture to improve the predictive performance of anticancer peptides.
Bioinformatics, 2021. **37**(24): p. 4684-4693.
4. Huan, Y., et al., *Antimicrobial peptides: classification, design, application and research*
progress in multiple fields. Frontiers in microbiology, 2020: p. 2559.
5. Habault, J. and J.-L. Poyet, *Recent advances in cell penetrating peptide-based*
anticancer therapies. Molecules, 2019. **24**(5): p. 927.
6. Zorzi, A., K. Deyle, and C. Heinis, *Cyclic peptide therapeutics: past, present and future.*
Current opinion in chemical biology, 2017. **38**: p. 24-29.

7.   Ward, K.B., W.A. Hendrickson, and G. KLIPPENSTEIN, *Quaternary and tertiary*
structure of haemerythrin. Nature, 1975. **257**(5529): p. 818-821.
8.   Heffernan, R., et al., *Improving prediction of secondary structure, local backbone*
angles and solvent accessible surface area of proteins by iterative deep learning.
Scientific reports, 2015. **5**(1): p. 1-11.
9.   Heffernan, R., et al., *Capturing non-local interactions by long short-term memory*
bidirectional recurrent neural networks for improving prediction of protein secondary
structure, backbone angles, contact numbers and solvent accessibility. Bioinformatics,
2017. **33**(18): p. 2842-2849.
10. Li, Z. and Y. Yu, *Protein secondary structure prediction using cascaded convolutional*
and recurrent neural networks. arXiv preprint arXiv:.07176, 2016.
11. Busia, A. and N.J.a.p.a. Jaitly, *Next-step conditioned deep convolutional neural*
networks improve protein secondary structure prediction. 2017.
12. Cole, C., J.D. Barber, and G.J.J.N.a.r. Barton, *The Jpred 3 secondary structure*
prediction server. 2008. **36**(suppl_2): p. W197-W201.
13. Fang, C., et al., *MUFold-SSW: a new web server for predicting protein secondary*
structures, torsion angles and turns. 2020. **36**(4): p. 1293-1295.
14. Montgomerie, S., et al., *PROTEUS2: a web server for comprehensive protein*
structure prediction and structure-based annotation. Nucleic acids research, 2008.
36(suppl_2): p. W202-W209.
15. Rost, B., C. Sander, and R. Schneider, *PHD-an automatic mail server for protein*
secondary structure prediction. Bioinformatics, 1994. **10**(1): p. 53-60.
16. Wang, S., et al., *RaptorX-Property: a web server for protein structure property*
prediction. Nucleic acids research, 2016. **44**(W1): p. W430-W435.
17. Wang, S., et al., *Protein secondary structure prediction using deep convolutional*
neural fields. Scientific reports, 2016. **6**(1): p. 1-11.
18. Bradley, P., et al., *Rosetta predictions in CASP5: successes, failures, and prospects*
for complete automation. Proteins: Structure, Function, Bioinformatics, 2003. **53**(S6):
p. 457-468.
19. Cao, X., et al., *PSSP-MVIRT: peptide secondary structure prediction based on a*
multi-view deep learning architecture. 2021. **22**(6): p. bbab203.
20. Maupetit, J., P. Derreumaux, and P. Tuffery, *PEP-FOLD: an online resource for de*
novo peptide structure prediction. Nucleic acids research, 2009. **37**(suppl_2): p.
W498-W503.
21. Elnaggar, A., et al., *ProtTrans: towards cracking the language of Life's code through*
self-supervised deep learning and high performance computing. 2020.
22. Maity, I., et al., *Self-programmed nanovesicle to nanofiber transformation of a*
dipeptide appended bolaamphiphile and its dose dependent cytotoxic behaviour.
Journal of Materials Chemistry B, 2014. **2**(32): p. 5272-5279.
23. Metrano, A.J., et al., *Diversity of secondary structure in catalytic peptides with*
β-turn-biased sequences. Journal of the American Chemical Society, 2017. **139**(1): p.
492-516.

24.   Kipf, T.N. and M. Welling, *Semi-supervised classification with graph convolutional*
networks. arXiv preprint arXiv:.02907, 2016.
25.   Velickovic, P., et al., *Graph attention networks.* stat, 2017. **1050**: p. 20.
26.   Wei, L., et al., *ATSE: a peptide toxicity predictor by exploiting structural and*
evolutionary information based on graph neural network and attention mechanism.
Briefings in Bioinformatics, 2021. **22**(5): p. bbab041.
27.   Montemurro, A., et al., *NetTCR-2.0 enables accurate prediction of TCR-peptide*
binding by using paired TCRα and β sequence data. Communications biology, 2021.
4(1): p. 1-13.
28.   Magnan, C.N. and P. Baldi, *SSpro/ACCpro 5: almost perfect prediction of protein*
secondary structure and relative solvent accessibility using profiles, machine learning
and structural similarity. Bioinformatics, 2014. **30**(18): p. 2592-2597.
29.   Fang, C., et al., *MUFOLD-SS: new deep inception-inside-inception networks for*
protein secondary structure prediction. 2018. **86**(5): p. 592-598.
30.   Torrisi, M., M. Kaleel, and G. Pollastri, *Deeper profiles and cascaded recurrent and*
convolutional neural networks for state-of-the-art protein secondary structure
prediction. Scientific reports, 2019. **9**(1): p. 1-12.
31.   Kabsch, W. and C. Sander, *Dictionary of protein secondary structure: pattern*
recognition of hydrogen-bonded and geometrical features. Biopolymers: Original
Research on Biomolecules, 1983. **22**(12): p. 2577-2637.
32.   Graves, A. and J. Schmidhuber, *Framewise phoneme classification with bidirectional*
LSTM and other neural network architectures. Neural networks, 2005. **18**(5-6): p.
602-610.
33.   Raffel, C., et al., *Exploring the limits of transfer learning with a unified text-to-text*
transformer. arXiv preprint arXiv:.10683, 2019.
34.   Suzek, B.E., et al., *UniRef clusters: a comprehensive and scalable alternative for*
improving sequence similarity searches. Bioinformatics, 2015. **31**(6): p. 926-932.
35.   Ding, K., et al., *Be more with less: Hypergraph attention networks for inductive text*
classification. 2020.
36.   Frishman, D. and P. Argos, *Incorporation of non-local interactions in protein*
secondary structure prediction from the amino acid sequence. Protein Engineering,
Design Selection, 1996. **9**(2): p. 133-142.
37.   Forney, G.D., *The viterbi algorithm.* Proceedings of the IEEE, 1973. **61**(3): p. 268-278.
38.   O'Brien, C., D.R. Flower, and C. Feighery, *Peptide length significantly influences in*
vitro affinity for MHC class II molecules. Immunome research, 2008. **4**(1): p. 1-7.
39.   Roberts, P.R., et al., *Effect of chain length on absorption of biologically active peptides*
from the gastrointestinal tract. Digestion, 1999. **60**(4): p. 332-337.
40.   Abdi, H. and L.J.J.W.i.r.c.s. Williams, *Principal component analysis.* 2010. **2**(4): p.
433-459.
41.   Van der Maaten, L. and G. Hinton, *Visualizing data using t-SNE.* Journal of machine
learning research, 2008. **9**(11).

42.   Hideji, T. and H. Kazuo, *Structure-toxicity relationship of acrylates and methacrylates.*
Toxicology letters, 1982. **11**(1-2): p. 125-129.

43.   Wang, R., et al., *Predicting protein-peptide binding residues via interpretable deep*
learning. Bioinformatics, 2022.

44.   Qi, Y., *Random forest for bioinformatics*, in *Ensemble machine learning*. 2012,
Springer. p. 307-323.

45.   Yang, J., et al., *Improved protein structure prediction using predicted interresidue*
orientations. Proceedings of the National Academy of Sciences, 2020. **117**(3): p.
1496-1503.

46.   Du, Z., et al., *The trRosetta server for fast and accurate protein structure prediction.*
Nature protocols, 2021. **16**(12): p. 5634-5651.

47.   Su, H., et al., *Improved Protein Structure Prediction Using a New Multi-Scale Network*
and Homologous Templates. Advanced Science, 2021: p. 2102592.

48.   Aszódi, A., M. Gradwell, and W. Taylor, *Global fold determination from a small number*
of distance restraints. Journal of molecular biology, 1995. **251**(2): p. 308-326.

49.   Skolnick, J., A. Kolinski, and A.R. Ortiz, *MONSSTER: a method for folding globular*
proteins with a small number of distance restraints. Journal of molecular biology, 1997.
265(2): p. 217-241.

50.   Vendruscolo, M., E. Kussell, and E. Domany, *Recovery of protein structure from*
contact maps. Folding Design, 1997. **2**(5): p. 295-306.

877