DIVE: a reference-free statistical approach to diversity-generating & mobile genetic element discovery

J. Abante[1,2]**, P.L. Wang**[1,3]**, and J. Salzman**[1,3,4] ✉

[1]Biomedical Data Science, Stanford University, 1265 Welch Rd, Palo Alto, CA 94305
[2]Center for Computational, Evolutionary and Human Genomics, Stanford University, 327 Campus Drive, Stanford, CA 94305
[3]Department of Biochemistry, Stanford University, 279 Campus Drive, Stanford, CA 94305
[4]Department of Statistics, Stanford University, 390 Serra Mall, Stanford, CA 94305

Diversity-generating and mobile genetic elements are paramount to microbial and viral evolution and result in evolutionary leaps conferring novel phenotypes, such as antimicrobial resistance. State-of-the-art algorithms to detect these elements have many limitations, including reliance on reference genomes, assemblers, and heuristics, resulting in computational bottlenecks and limiting the scope of biological discoveries. Here we introduce DIVE, a new reference-free approach to overcome these limitations. We show that DIVE has improved detection power compared to existing reference-based methods using simulations and real data. We use DIVE to rediscover and characterize the activity of known and novel elements and generate new biological hypotheses about the mobilome. Using DIVE we rediscover CRISPR and identify novel repeats, and we discover unannotated genetic hyper-variability hotspots in *E. coli* and *V. cholerae*. Building on DIVE, we develop a reference-free framework for *de novo* discovery of mobile genetic elements, not currently available to our knowledge, and we use it to rediscover the majority of known transposons in *M. tuberculosis*, the causative agent of *Tuberculosis*.

Recent estimates predict the existence of 1 trillion microbial species subject to large intraspecies variation (1, 2). This genetic diversity results from multiple processes, such as point mutations, but is increasingly appreciated to be driven by mobile genetic elements (MGEs). These elements abruptly modify the genome and rapidly provide new phenotypes (3). The rapid spread of these elements is causing a surge of antibiotic resistance, considered an urgent public health crisis (4). In addition, diversity-generating mechanisms (DGMs), such as diversity-generating retroelements (DGRs) and CRISPR-Cas systems, further contribute to microbial diversity. These mechanisms allow pathogens to adapt rapidly to changing environmental conditions and acquire resistance against bacteriophages. Nevertheless, current estimates point to $> 40\%$ of sequenced bacteria lacking annotated CRISPR systems (5), suggesting other DGMs remain to be discovered.

State-of-the-art algorithms (6–11) to detect MGEs or DGMs have many limitations, including reliance on reference genomes, assemblers, and heuristics, resulting in bottlenecks and limiting the breadth of biological discoveries. Reference genomes are only available for relatively few organisms which are, in turn, constantly evolving. Assembly algorithms are computationally expensive, especially in the metagenomic setting, and fail to capture the inherent complexity in the bacterial and viral world (12). Lastly, commonly used heuristics embedded in these algorithms impose assumptions that may not hold in general, such as the existence of target site duplications (11).

Alignment-free methods have shown great promise in several genomics problems, including transcript abundance estimation (13) and association mapping (14). However, their applications have been limited and have not been used to discover genomic variation. We reasoned that reference-free methods could have much broader discovery power in this setting. This realization led us to develop DIVE, a novel reference-free algorithm designed to identify sequences that cause genetic diversification (e.g., CRISPR repeat or transposon insertions), as well as MGE integration hotspots in the genome, such as tRNA loci (Fig. 1). DIVE operates directly on sequencing reads and does not rely on a reference genome. We designed DIVE from a simple observation: a mobile genetic element such as a transposon is defined by its bounding sequence or transposon arms A. These arms mechanistically enable mobility, but they also define the element in an algorithmic sense: the constant sequence A will be flanked by a highly diverse set of sequences if A is indeed the arm of an MGE (Fig. 1). This principle applies to MGE magnets and other constant/variable sequence assemblies, such as CRISPR arrays. Thus, we reasoned it should be possible to discover such elements by identifying sequences A with highly diverse neighboring sequences.

DIVE makes the preceding logic into a statistical algorithm. We define k-mers *anchor* and *target*, both sequences of a predefined length k. DIVE aims to find anchors with neighboring (upstream or downstream) statistically highly diverse (target) sequences. DIVE processes each read sequentially using a sliding window to construct *target* dictionaries for each *anchor* encountered in each read (Fig. 1). For each anchor, DIVE uses the number of target clusters C_N, constructed using the Jaccard similarity, to compute the probability that the observed target diversity is due to background variability, resulting in a set of p-values that are corrected for multiple hypothesis testing (Methods). Lastly, anchors are clustered to reduce redundancies in the output, and

a representative anchor (RA) maximizing the effect size $\alpha \equiv \log(C_N/E[C_N|N])$ in each direction is picked (Supplementary Information). Notably, α is a relative measure of the observed diversity compared to the expected diversity for a given coverage. This quantity can be used to prioritize actively diversifying CRISPR arrays over less active ones or highly mobilized over ancestral MGEs (Methods). Annotation and references are not used during any step of DIVE except as a post-facto option for interpretation. Lastly, DIVE anchors can be extended using any assembly algorithm producing longer sequences which can be subsequently used to perform protein domain homology search and classification (Methods). Together, this enables reference-free *de novo* MGE discovery, which is critical and currently unavailable to our knowledge.

We first evaluated the dependence of DIVE's effect size α on the abundance of a k-mer in the reads by correlating it with the number of observations N, a proxy for the abundance of a k-mer. The lack of correlation indicates that k-mer prevalence alone does not predict diversifying sequences as expected (Fig. S1). We then used whole-genome sequence (WGS) data from *E. coli* and *V. cholerae* to compare the proportion of annotated RAs between DIVE and a naive algorithm that randomly picks anchors based on prevalence (Methods, Table S1, S2). RAs reported by DIVE were strongly enriched relative to the naive algorithm for mapping to known elements (Table S3), showing DIVE's sensitivity is not a function of k-mer abundance.

Next, we performed a set of simulations to systematically evaluate DIVE's ability to identify MGE termini in two different scenarios. We considered the case where an MGE is not active and has multiple copies, and the case where a single copy of an active element has been active within a single sample (Supplementary Information; Fig. S2). DIVE achieved an area under the curve (AUC) of >99% in all scenarios with coverage > 30X (Fig. 1, S3, S4), even when the genomic divergence in the genome was considerable. We also compared the discovery power of DIVE to that of MGEfinder, a *de novo* MGE detection tool that outperformed the state of the art in a recent benchmark (11). MGEfinder heavily relies on heuristics, an assembly step involving all the reads, and requires a reference genome, which affects the algorithm's sensitivity (Supplementary Information). MGEfinder outperformed DIVE when $C_N \leq 5$ and the mutation and indel rate (MIR) was the lowest considered. Nevertheless, DIVE showed higher sensitivity than MGEfinder in all other scenarios involving different coverages, element activity, copy number, and genome variability levels (Supplementary Information; Fig. S5, S6). We also compared the two algorithms using real *N. gonorrhoeae* isolate WGS data using reads not mapping to the reference used by the authors (Supplementary Information). DIVE reported RAs mapping to over 100 known TEs (15) using data from 200 isolates (Fig. 2, Table S4), whereas MGEfinder reported 28 unique TEs (891 isolates), consistent with the lower sensitivity observed in our simulations. In addition to known TEs, DIVE reported RAs mapping to known CRISPR direct repeats and other MGEs.

We next tested whether DIVE could identify CRISPR repeats *de novo* in *E. coli* using purely statistical features. Three hundred one of the RAs identified by DIVE mapped to known CRISPR repeats, with their associated targets mapping to 774 known spacers in the CRISPR-Cas++ database (8) (Methods). In particular, of the 59 known *E. coli* repeats present in the data and meeting the minimum sample size ($N_{\min} = 25$), DIVE detected 50 (85%). Additionally, DIVE detected eight repeats not annotated in *E. coli* (seven known in Enterobacteria and one in Proteobacteria) (Table S5). Of all categories, RAs mapping to CRISPR repeats showed the largest median effect size (Fig. S1). They were further distinguishable from other RAs in that they belonged to anchor clusters with bidirectional significance, showed large effect size ($0.5(\alpha_u + \alpha_d) \geq 3.5$) and appeared more than once within a read. Imposing these requirements restricted to ten RAs, perfectly mapping to six known *E. coli* CRISPR repeats (Table S6), achieving 100% specificity. This observation suggests that these criteria may be used to identify CRISPR repeats *de novo*. Using these criteria, we identified a novel CRISPR repeat in human gut metagenomic samples (Fig. 2). This repeat was related but not identical to a known CRISPR repeat, forming an array with spacers (many mapping to known phages) adjacent to *Cas* genes (Supplementary Information). We also used these criteria to identify six novel repeats in microbiota metagenomic samples (Methods). This set of repeats included five with 1-5 mismatches to the closest repeat on CRISPR-Cas++ and one that did not match any known repeat (Fig. S7). Three of the six repeats completely aligned to at least one bacterial genome on NCBI (BLAST). These repeats had varying copy numbers in the genomes, ranging from 1 to 12. In addition, we found annotated CRISPR *Cas* and *Csd* proteins nearby for two of the repeats. Interestingly, the array consisted of just 1-2 repeats in these cases, constituting mini-CRISPR arrays. This result shows that DIVE permits the discovery of CRISPR arrays lacking *Cas* genes in *cis* since it does not rely on heuristics such as nearby known *Cas* proteins, as well as arrays with low numbers of repeats.

DIVE provides additional information about CRISPR repeats beyond discovering them *de novo*, establishing a framework to estimate spacer diversity in CRISPR arrays as a function of available covariates when multiple samples are available. The target clusters produced by DIVE for a given anchor can be compared across different environments or conditions and statistically modeled using a binomial generalized linear model to identify covariates driving the differences in target diversity (Methods). In the *E. coli* dataset, five RAs mapped to *E. coli* CRISPR repeats with spacer (target) diversity being a function of the isolation source (Fig. 2, S8, S9). In addition to CRISPR, several other loci had high target diversity, including 77 RAs mapping to lambdoid phages, ICEs, TEs, and non-coding RNA (ncRNA), where target diversity varied as a function of the isolation source (Fig. S8, S10, S11). Thus, this framework can enable the study of genetic diversity as a function of available covariates beyond CRISPR arrays.

Next, we investigated whether DIVE could rediscover the role that non-coding RNA (ncRNA) loci play in the genome as insertion hotspots for MGEs (16, 17) (Supplementary Information). For example, regions coding for tRNA genes are common

insertion sites for phages and plasmids (18). DIVE found substantial target diversity among RAs mapping to ncRNAs, including several examples where the target variability was a function of available covariates (Fig. S11). In *E. coli*, DIVE called 712 unique RAs mapping to 84 different Rfam accessions annotated as tRNA genes (BLAST e<0.01), aligning to the ends of the genes (Table S7). DIVE RAs also mapped to 82 Rfam accessions annotated as nucleoid-associated noncoding RNA 4 (naRNA4) genes (Table S8). These genes are encoded in repetitive extragenic palindrome (REP) regions, which have been previously observed at the recombination junctions of lambda phages and described as hotspots for transposition events (19, 20). DIVE also identified 264 RAs mapping (BLAST e<0.01) to 26 Rfam accessions annotated as antisense RNA 5 (asRNA5) among *V. cholerae* isolates, four of which have a target diversity significantly associated with available covariates, including date, country, and isolation environment (Table S9).

To illustrate DIVE's application to reference-free *de novo* MGE discovery we analyzed a subsample of seventy-five *M. Tuberculosis* isolates from the CRyPTIC consortium (21) and focused on *de novo* discovery of transposon sequences (Fig. 3). Using the RAs reported by DIVE, we reconstructed transposons by performing seed-based assembly on the RAs and subsequent protein homology analysis, allowing us to identify contigs with transposon-associated domains in each isolate (Fig. 3; Methods). We clustered the contigs using CD-HIT-EST (22) to collapse similar sequences from different isolates (>90% identity), producing 48 clusters, of which 38 were singletons with sizes ranging from 236 to 20,000 bp (Fig. 3). To evaluate whether the assembly step produced valid sequences, we used BLAST to align one sequence in each cluster to all *M. Tuberculosis* sequences available on NCBI. All the contigs produced complete alignments with $> 99\%$ identity, suggesting the seed assembly step produced valid sequences. To test whether the contigs consisted of transposons, we aligned one contig in each cluster to the insertion sequence database ISfinder (23). Nine clusters matched *IS6110* (BLAST evalue<0.01), a well-known transposon in *M/ Tuberculosis* commonly used to type strains. When we aligned the input seeds in the assembly step onto this element, we found they accumulated on the ends as expected (Fig. 3). Eleven other clusters matched nine known transposon sequences in *Mycobacteria*, among which we completely assembled the sequences of *ISMt1-3*, *IS1553* and *IS1538* (Table S10). The proposed approach reconstructed *de novo* seven known transposons in *M. Tuberculosis* from 19 contig clusters, whereas the other 28 clusters produced partial short matches on ISfinder but did not fully contain an annotated IS. Twenty of these clusters have at least one entry with multiple alignments in at least one *M. Tuberculosis* genome on NCBI, some with up to 55 copies in a single genome (BLAST $e - value < 0.01$). The high copy number and the fact that these contigs contain TE-associated domains point to a potential set of previously unreported transposons in TB. To our knowledge, such a reference-free approach for *de novo* discovery of MGEs is not currently available.

State-of-the-art methods do not attempt to discover within-MGE variability, which is known to have a significant phenotypic impact (24). We hypothesized that DIVE could discover hotspots of genetic rearrangements within MGEs. As an example, integrative and conjugative elements (ICEs) confer various properties to their hosts through cargo genes, such as phage and antibiotic resistance (25). In *V. cholerae*, SXT ICEs determine phage resistance, and deletion of hotspot five in SXT ICEs leads to susceptibility to ICP1 phage infection (24). We hypothesized that DIVE could recognize the boundaries of cargo gene hotspots in SXT ICEs in *V. cholerae* isolates. To test this hypothesis, we looked at the concentration of anchors around known SXT cargo hotspots. DIVE's RAs clustered around the edges of cargo gene hotspots in five SXT ICE variants and a putative hotspot in an unannotated SXT ICE (Fig. 2, Supplementary Information). Extension of these anchors through an assembly algorithm could enable the study of differences in antibiotic resistance gene composition.

DIVE also discovered a large number of unannotated genetic hyper-variable regions in well-studied organisms like *E. coli* and *V. cholerae*. We filtered the unannotated RAs with at least a median $\alpha \geq 2$ and a sample prevalence $> 5\%$, resulting in a shortlist of 5 anchors among *E. coli* isolates and 29 among *V. cholerae* isolates (Table S11), and here we highlight two examples (Supplementary Information). In each case, raw reads containing the corresponding RA were multiple-sequence aligned (26) showing a sudden decay in consensus nucleotide composition on one end of the RA consistent with DIVE's output (Fig. 4). In the *E. Coli* example, the RA produces a unique match in the *E. coli* O157 reference proximal to the 3' end of isomerase Arabinose 5-phosphate isomerase (kdsD), an intramolecular oxidoreductase that interconverts aldoses and ketoses, with target diversity that results in downstream non-synonymous mutations and indels in the enzyme. In *V. cholerae*, the RA produced a single match in at least one hundred NCBI *V. cholerae* accessions, mapping to the intergenic region between tRNA-Cys and the artP gene (arginine ABC transporter ATPase), with the former being in the direction of more target diversity. The target diversity observed was not well represented on the reference genomes available on NCBI, with $> 30\%$ of targets not blasting to any genome in either case. Furthermore, the sequence variability extended well beyond the range of the target sequence, spanning over 100 nt, including substitutions and indels altering the protein sequence. These unannotated hyper-variable regions warrant further investigation to identify the mechanism and functional consequences of their sequence variability.

DIVE offers a new reference-free paradigm for studying genetic bacterial and viral evolution. It is a theoretically guided, has high precision in simulation, and is reference-free, and efficient to perform *de novo* detection of MGEs and DGMs. DIVE also enables the characterization of MGE and DGM activity levels as a function of available covariates and the study of within-element variability. More importantly, given the generality of the principle used, DIVE could enable the discovery of entirely novel biological mechanisms that diversify genomes.

Methods

DIVE configuration. Here we defined the k-mer size k to be 27, striking a balance between the memory requirements and the specificity of the sequence. DIVE also allows the user to introduce a gap in between the anchor and the targets of an arbitrary distance g, which here we set at $g = 0$. We defined the minimum and the maximum number of targets per anchor to be $N_{\min} = 25$ and $N_{\max} = 75$, respectively. Finally, to strike a balance between power and computational resources, we decided to limit the number of FASTQ records processed per sample to 2.5M.

Clustering targets on the fly. Upon observing a target k-mer, DIVE checks whether the k-mer produces a Jaccard similarity (JS) larger than a given threshold (0.2) with any of the previously observed targets. If so, the counter of that key is increased by one, and, with a probability of 50%, the key is replaced by the newly observed target sequence. If no such target sequence exists in the dictionary, a new key is created, and its counter is initialized at one. To calculate the JS between two targets of length $k = 27$, DIVE splits each one into smaller k-mers of length seven and computes the JS similarity between the two using

$$\text{JS}(\mathcal{X}_1, \mathcal{X}_2) = \frac{\mathcal{X}_1 \cap \mathcal{X}_2}{\mathcal{X}_1 \cup \mathcal{X}_2} \tag{1}$$

where $\mathcal{X}_i$ is the set of 7-mers in the i-th target sequence.

Minimum and maximum N. For each anchor, DIVE requires a minimum number of targets observed $N_{\min}$ to proceed with the downstream statistical analysis. In addition, since it might not be necessary to keep all the targets observed exhaustively, DIVE also imposes a maximum number of targets $N_{\max}$ to be observed for each anchor. This allows the algorithm to skip anchors for which it has already observed $N_{\max}$ targets in each direction and move faster along the FASTQ file. Here we set these parameters to $N_{\min} = 25$ and $N_{\max} = 75$.

Minimum sample size prediction. To manage the memory burden and make the algorithm more efficient, we impose a minimum number $N_{\min}$ of targets to be observed by the end of the FASTQ file. We let the total number of FASTQ records in the file be L and the number of observed records so far be l. Then, letting $p_{\min = N_{\min}/L}$ be the probability that we will observe a target sequence for any given anchor in a single read at least once, we compute the probability that, after l records observed, we have observed zero instances using

$$P[N = 0; l] = (1 - p_{\min})^l \tag{2}$$

When this probability becomes smaller than 0.01 this implies that the rate we are observing targets for the anchor is too slow for us to observe $N_{\min}$ by the end with 99% probability. Thus, DIVE does not accept new anchors into the anchor dictionary DA past this point. This condition allows us to discard new anchors that appear late in the FASTQ file, which will likely not produce enough data to test for hyper-variability, reducing an unnecessary burden for dictionary $\mathcal{D}_A$. Past the point where DIVE does not accept new anchors, DIVE also anticipates the number of targets that will be observed for each anchor remaining in the dictionary to decide whether a given anchor should remain in the dictionary $\mathcal{D}_A$. More precisely, the oracle used by DIVE computes the probability that we will observe at least $N_{\min}$ targets by the end of the FASTQ file. Letting L be the total number of FASTQ reads, x the number of targets observed, and l the number of FASTQ reads processed so far, we can compute

$$P[N \geq N_{\min}; x, l] = \sum_{n = N_{\min}}^{L} \binom{L}{n} \left(\frac{x}{l}\right)^n \left(1 - \left(\frac{x}{l}\right)\right)^{L-n} \tag{3}$$

where *x/l* is an empirical estimate of the probability of observing a target sequence for the given anchor at least once in a single read. However, we use the normal approximation to the binomial distribution for efficiency to compute this probability. The anchor is conserved in the dictionary $\mathcal{D}_A$ if this probability is larger than 50%. Otherwise, the anchor is removed to reduce the size of the dictionary and speed up the algorithm.

Target sequence hyper-variability. We let X_n be a binary random variable indicating whether we created a new key in the target sequence dictionary upon observing the n-th target sequence for a given anchor and direction. Let C_n be the total number of keys target sequence clusters (keys) formed after observing the n-th target sequence. Then, assuming that X_n is independent and distributed according to a Bernoulli distribution with success probability p_n, we have that $C_N \sim \text{PoissBin}(p_1, \ldots, p_N)$. Upon observing a set of trajectories $\{C_1, C_2, \ldots, C_M\}$, the success probabilities $\{p_n\}$ can be estimated from the data by simply computing

$$\hat{p}_n = \frac{\sum_{m=1}^{M} x_{m,n}}{\sum_{m=1}^{M} 1\{N_m \geq n\}} \tag{4}$$

This follows from the fact that we can assume that most of the anchors will not be nearby hyper-variable regions. Nevertheless, the following test will be more conservative if we happen to include anchors adjacent to hyper-variable regions by chance. For a given $C_N = c$, we can compute the probability under the null hypothesis that the observed value c can be explained by the background biological (e.g., point mutations) and technical variability (e.g., sequencing errors) using

$$P_{H_0}[C_N \geq c] = \sum_{k=C_N}^{N} \frac{1}{N+1} \sum_{l=0}^{N} R^{-lk} \prod_{n=1}^{N} \left(1 + \left(R^l - 1\right)\hat{p}_n\right) \tag{5}$$

The resulting p-values are corrected using the Benjamini-Hochberg (BH) correction, resulting in a list of q-values that allow us to perform false discovery rate (FDR) control.

Efficient Benjamini-Hochberg correction. To correct for multiple hypothesis testing, we DIVE implements a memory-efficient version of the Benjamini-Hochberg (BH) correction. DIVE records the total number of statistical tests performed m and drops non-significant cases ($p > 0.1$). Then, it adjusts the remaining m' p-values by using the following procedure. First, it ranks the remaining m' p-values $\{p_i\}$ in ascending order $\{p^{(1)}, p^{(2)}, \ldots, p^{(m')}\}$. Then, it computes the adjusted p-value using $q^{(i)} = p^{(i)}m/i$, and it reports the anchors for which $q < 0.1$. Note that p-values computed for overlapping k-mers will be positively correlated. Nevertheless, the BH correction can still control the FDR under that form of dependence (27).

Clustering of anchors. Once the BH correction is applied to the computed p-values, DIVE uses DBSCAN (Levenshtein edit distance) to cluster the anchor sequences to avoid redundancies in the output. This is done using the function DBSCAN from the python package sklearn with parameters `eps=2` and `min_samples=1`. For each anchor cluster, a representative anchor is chosen for each direction (upstream and downstream) by picking the anchor that maximizes the effect size.

Effect size computation. The effect size is quantified using the log-fold change between the observed number of clusters c_N and the expected number of clusters for a given number of observed targets, as quantified by N, and it is given by

$$\alpha(c_N) = \log_2 \frac{c_N}{E[C_N \mid N]} \tag{6}$$

This quantity can be used to rank the results in terms of effect size and allows the user to filter out positives with small effect size and thus little biological interest. ***Annotation of DIVE's output.*** To validate our results, we used blastn-short 2.11.0 (28) to align the detected k-mers to a set of sequence databases stored in FASTA format comprised of CRISPR direct repeats (CRISPR-Cas++ (8)), transposable elements (Dfam (29); TnCentral (15)), mobile genetic elements (ACLAME (30)), internal transcribed spacers 1 and 2 (ITSoneDB (31), ITS2 (32)), integrative and conjugative elements (ICEberg (33)), and RNA sequence families of structural RNAs (Rfam (34)). Furthermore, we cross-referenced our results with Illumina adapter (obtained from TrimGalore) and UniVec sequences (NCBI) to remove technical artifacts. We classified each k-mer as unannotated if no BLAST produced $e \leq 0.25$, questionable if $0.01 \leq e < 0.25$, and annotated if the lowest $e \leq 0.01$ with the corresponding annotation. Here we chose this comprehensive set of annotation files. Nevertheless, DIVE can take an arbitrary number of annotation files as input, and thus this step can be adjusted depending on the application.

Enrichment analysis of positive controls. A total of 100,000 27-mers were chosen at random among the entire *E. coli* dataset, allowing for repetition. We used BLAST to align this set of random anchors to the set of annotation files we used during our analysis. Then, we deemed anchors as unannotated and annotated if their BLAST e-values were *e>0.25* and *e<0.01*, respectively. Then, we used the function fisher_exact python's scipy package to perform a two-sided Fisher's exact test comparing the proportions of annotated to unannotated between this set of random anchors and the set of DIVE anchors.

Binomial regression. To find associations between the target variability and a set of covariates given by $\mathbf{x}$, we use a binomial regression model such that $C \sim \text{Binomial}(N; p(\mathbf{x}))$, such that

$$p(\mathbf{x}) = \frac{1}{1 + e^{-\boldsymbol{\beta}^T \mathbf{x}}} \tag{7}$$

For *E. coli* isolates, we used the isolation source as a covariate, whereas for *V. cholerae* isolates we used the environment, date, country, as well as first-order interactions.

A posteriori clustering of targets. To cluster the targets across samples *a posteriori*, we used a greedy clustering approach. We rank the targets based on their total count across the entire dataset. Starting from the most prevalent target, we recruit all targets for which the JS>0.2 and eliminate these from the list. We proceed with the most prevalent target sequence remaining in the list the same way, and we repeat this procedure until no sequences are left. The number of times we repeat this procedure defines the number of across-sample target sequence clusters.

Anchor extension and protein domain homology. DIVE anchors can be extended using an assembly algorithm to produce a longer sequence of interest. To that end, we used SSAKE (v4.0) in the seed mode iteratively (-p 1 -m 20 -o 1 -c 1 -w 5 -r 0.51 -i 0). In each iteration, SSAKE produced a set of contigs that where used in the next iteration as seeds. In our analysis, we performed ten iterations. This process results in a set of extended anchors that can be used as input to protein domain homology search algorithms. To that end, we used HMMER (v3.3.2) in conjunction with Pfam35 in the default setting.

Availability of data and materials. The data sets analyzed in this paper are publicly available and published. The *E. coli* isolate sequencing data used was generated by the GenomeTrakr Project, US Food and Drug Administration (PRJNA230969). We used 514 samples encompassing 62 different isolation sources (Table S12). The *V. cholerae* sequencing data was downloaded from SRA (PRJNA723557). We used all the 247 *V. cholerae* isolates sequenced as part of this project (Table S13). The rotavirus

metagenomics sequencing data was downloaded from SRA (PRJNA729919). We used 102 in our analysis (Table S14). Finally, the *N. gonorrhoeae* data was downloaded from SRA (PRJNA298332), from which we used 200 samples in our analysis (Table S14).

Code availability. The code used in this work is available at https://github.com/jordiabante/biodive.

Authors' contributions. J.A. and J.S. developed the computational method. J.A. developed the software. J.A., P.W. and J.S. analyzed the data. J.S. conceived and supervised the project. J.A. and J.S. wrote the paper with the assistance of P.W..

Funding. J.A. is partially supported by the Stanford Center for Computational, Evolutionary and Human Genomics Post-doctoral Fellowship. J.S. is supported by the Stanford University Discovery Innovation Award, National Institute of General Medical Sciences grant nos. R35 GM139517 and the National Science Federation Faculty Early Career Development Program Award no. MCB1552196.

Conflict of interest. The authors declare no competing interests.

Acknowledgements. We would like to thank Ruth Timme, David Lipman, Andrew Fire, Kaitlin Chuang, Roozbeh Dehghannasiri, Elisabeth Meyer, Tavor Baharav and Ivan Zheludev for their comments and suggestions. We would also like to thank Kaitlin Chuang for her help processing part of the data used in this paper.

Bibliography

1. Kenneth J Locey and Jay T Lennon. Scaling laws predict global microbial diversity. *Proceedings of the National Academy of Sciences*, 113(21): 5970–5975, 2016.
2. Ruiting Lan and Peter R Reeves. Intraspecies variation in bacterial genomes: the need for a species genome concept. *Trends in microbiology*, 8 (9):396–401, 2000.
3. Chitra Dutta and Archana Pan. Horizontal gene transfer and bacterial diversity. *Journal of biosciences*, 27(1):27–33, 2002.
4. Rachel A Smith, Nkuchia M M'ikanatha, and Andrew F Read. Antibiotic resistance: a primer and call to action. *Health communication*, 30(3): 309–314, 2015.
5. Rotem Sorek, Victor Kunin, and Philip Hugenholtz. Crispr—a widespread system that provides acquired resistance against phages in bacteria and archaea. *Nature Reviews Microbiology*, 6(3):181–186, 2008.
6. Aaron E Darling, Bob Mau, and Nicole T Perna. progressivemauve: multiple genome alignment with gene gain, loss and rearrangement. *PloS one*, 5(6):e11147, 2010.
7. Abraham G Moller and Chun Liang. Metacrast: reference-guided extraction of crispr spacers from unassembled metagenomes. *PeerJ*, 5:e3788, 2017.
8. David Couvin, Aude Bernheim, Claire Toffano-Nioche, Marie Touchon, Juraj Michalik, Bertrand Néron, Eduardo PC Rocha, Gilles Vergnaud, Daniel Gautheret, and Christine Pourcel. Crisprcasfinder, an update of crisrfinder, includes a portable version, enhanced performance and integrates search for cas proteins. *Nucleic acids research*, 46(W1):W246–W251, 2018.
9. Panisa Treepong, Christophe Guyeux, Alexandre Meunier, Charlotte Couchoud, Didier Hocquet, and Benoit Valot. panisa: ab initio detection of insertion sequences in bacterial genomes from short read sequence data. *Bioinformatics*, 34(22):3795–3800, 2018.
10. Alexander Mitrofanov, Omer S Alkhnbashi, Sergey A Shmakov, Kira S Makarova, Eugene V Koonin, and Rolf Backofen. Crispridentify: identification of crispr arrays using machine learning approach. *Nucleic acids research*, 49(4):e20–e20, 2021.
11. Matthew G Durrant, Michelle M Li, Benjamin A Siranosian, Stephen B Montgomery, and Ami S Bhatt. A bioinformatic analysis of integrative mobile genetic elements highlights their role in bacterial adaptation. *Cell host & microbe*, 27(1):140–153, 2020.
12. Izaak Coleman and Tal Korem. Embracing metagenomic complexity with a genome-free approach. *Msystems*, 6(4):e00816–21, 2021.
13. Rob Patro, Stephen M Mount, and Carl Kingsford. Sailfish enables alignment-free isoform quantification from rna-seq reads using lightweight algorithms. *Nature biotechnology*, 32(5):462–464, 2014.
14. Atif Rahman, Ingileif Hallgrímsdóttir, Michael Eisen, and Lior Pachter. Association mapping from sequencing reads using k-mers. *Elife*, 7:e32920, 2018.
15. Karen Ross, Alessandro M Varani, Erik Snesrud, Hongzhan Huang, Danillo Oliveira Alvarenga, Jian Zhang, Cathy Wu, Patrick McGann, and Mick Chandler. Tncentral: a prokaryotic transposable element database and web portal for transposon analysis. *MBio*, 12(5):e02060–21, 2021.
16. Rolf Marschalek, Thomas Brechner, Elfi Amon-Böhm, and Theodor Dingermann. Transfer rna genes: landmarks for integration of mobile genetic elements in dictyostelium discoideum. *Science*, 244(4911):1493–1496, 1989.
17. Thomas H Eickbush and Danna G Eickbush. Finely orchestrated movements: evolution of the ribosomal rna genes. *Genetics*, 175(2):477–485, 2007.
18. Allan M Campbell. Chromosomal insertion sites for phages and plasmids. *Journal of bacteriology*, 174(23):7495–7499, 1992.
19. Michiyo Kumagai and Hideo Ikeda. Molecular analysis of the recombination junctions of λ bio transducing phases. *Molecular and General Genetics MGG*, 230(1):60–64, 1991.
20. Raquel Tobes and Eduardo Pareja. Bacterial repetitive extragenic palindromic sequences are dna targets for insertion sequence elements. *BMC genomics*, 7(1):1–12, 2006.
21. Timothy M Walker, Paolo Miotto, Claudio U Köser, Philip W Fowler, Jeff Knaggs, Zamin Iqbal, Martin Hunt, Leonid Chindelevitch, Maha R Farhat, Daniela Maria Cirillo, et al. The 2021 who catalogue of mycobacterium tuberculosis complex mutations associated with drug resistance: a genotypic analysis. *The Lancet Microbe*, 3(4):e265–e273, 2022.
22. Limin Fu, Beifang Niu, Zhengwei Zhu, Sitao Wu, and Weizhong Li. Cd-hit: accelerated for clustering the next-generation sequencing data. *Bioinformatics*, 28(23):3150–3152, 2012.
23. Patricia Siguier, Jocelyne Pérochon, L Lestrade, Jacques Mahillon, and Michael Chandler. Isfinder: the reference centre for bacterial insertion sequences. *Nucleic acids research*, 34(suppl_1):D32–D36, 2006.
24. Kristen N LeGault, Stephanie G Hays, Angus Angermeyer, Amelia C McKitterick, Fatema-tuz Johura, Marzia Sultana, Tahmeed Ahmed, Munirul Alam, and Kimberley D Seed. Temporal shifts in antibiotic resistance elements govern phage-pathogen conflicts. *Science*, 373(6554):eabg2166, 2021.

25. Rachel AF Wozniak and Matthew K Waldor. Integrative and conjugative elements: mosaic mobile genetic elements enabling dynamic lateral gene flow. *Nature Reviews Microbiology*, 8(8):552–563, 2010.

26. Julie D Thompson, Toby J Gibson, and Des G Higgins. Multiple sequence alignment using clustalw and clustalx. *Current protocols in bioinformatics*, (1):2–3, 2003.

27. Yoav Benjamini and Daniel Yekutieli. The control of the false discovery rate in multiple testing under dependency. *Annals of statistics*, pages 1165–1188, 2001.

28. Christiam Camacho, George Coulouris, Vahram Avagyan, Ning Ma, Jason Papadopoulos, Kevin Bealer, and Thomas L Madden. Blast+: architecture and applications. *BMC bioinformatics*, 10(1):1–9, 2009.

29. Jessica Storer, Robert Hubley, Jeb Rosen, Travis J Wheeler, and Arian F Smit. The dfam community resource of transposable element families, sequence models, and genome annotations. *Mobile DNA*, 12(1):1–14, 2021.

30. Raphael Leplae, Gipsi Lima-Mendez, and Ariane Toussaint. Aclame: a classification of mobile genetic elements, update 2010. *Nucleic acids research*, 38(suppl_1):D57–D61, 2010.

31. Monica Santamaria, Bruno Fosso, Flavio Licciulli, Bachir Balech, Ilaria Larini, Giorgio Grillo, Giorgio De Caro, Sabino Liuni, and Graziano Pesole. Itsonedb: a comprehensive collection of eukaryotic ribosomal rna internal transcribed spacer 1 (its1) sequences. *Nucleic Acids Research*, 46(D1): D127–D132, 2018.

32. Christian Selig, Matthias Wolf, Tobias Müller, Thomas Dandekar, and Jörg Schultz. The its2 database ii: homology modelling rna structure for molecular systematics. *Nucleic acids research*, 36(suppl_1):D377–D380, 2007.

33. Meng Liu, Xiaobin Li, Yingzhou Xie, Dexi Bi, Jingyong Sun, Jun Li, Cui Tai, Zixin Deng, and Hong-Yu Ou. Iceberg 2.0: an updated database of bacterial integrative and conjugative elements. *Nucleic acids research*, 47(D1):D660–D665, 2019.

34. Ioanna Kalvari, Eric P Nawrocki, Nancy Ontiveros-Palacios, Joanna Argasinska, Kevin Lamkiewicz, Manja Marz, Sam Griffiths-Jones, Claire Toffano-Nioche, Daniel Gautheret, Zasha Weinberg, et al. Rfam 14: expanded coverage of metagenomic, viral and microrna families. *Nucleic Acids Research*, 49(D1):D192–D200, 2021.

Figures

Fig. 1. DIVE algorithm and simulations. a. Transposable elements (TEs), CRISPR arrays, and sequences near hotspot boundaries in integrative and conjugative elements (ICE) contain a diverse set of neighboring sequences. Sequencing adapters do as well and serve as technical positive controls. **b.** Flow diagram of DIVE's logic while parsing a FASTQ file. **c.** Cluster formation process based on Jaccard similarity (JS) for a given anchor (downstream case). **d.** DIVE processes reads sequentially through a sliding window that moves along the sequencing reads, recording for each anchor the upstream and downstream k-mers (targets). **e.** DIVE takes a FASTQ file as input and stores the output in two output files. The anchor significance file contains information about each anchor (e.g., statistics, p-values). DIVE also produces an anchor-target pair file which contains information about the stored target sequences in the dictionary, the direction and the count for each anchor. **f.** The sensitivity of DIVE in detecting MGE termini is higher than that of MGEfinder for both active and ancestral elements with multiple copies for various coverages, copy number, and activity level.

Fig. 2. DIVE quantifies activity of MGE and DGMs. **a.** Number of distinct transposable elements (TEs) detected by each method and number of reads containing an anchor mapping to TE detected by DIVE among unaligned reads in *N. gonorrhoeae* data from Durrant et. al 2020. Tn3 transposons TnXc5, TnTsp1, and TnArsp6 were most prevalent, whereas TnXAj417 and Tn3434 showed the largest median effect size. **b.** Boxplot of the ratio of number of clusters to the number of observation (C/N) of the anchor sequence GTGTTCCCCGCGCCAGCGGGGATAAAC called by DIVE in E. coli. The target diversity in four environments (shown in blue) is significantly larger than that of the rest of environments (Methods). **c.** Putative direct repeat TAGTGTAAATCTATAAGGTAGTAAAAC detected by DIVE in the Rotavirus dataset. The anchor reported by DIVE is two substitutions away from a known CRISPR direct repeat, and maps to an assembly (ctAYv1) containing a phage (orange) and a genomic segment (gray) having a canonical CRISPR array, derived from *R. bromii*. **d.** Alignment of all significant anchors from the *V. cholerae* analysis to the six available sequences of integrative and conjugative elements (ICEs) in the ICEberg database. The annotated genes for each SXT ICE are shown above the plot (yellow genes: integrases; red genes: antibiotic resistance). Below the ICE, a heatmap shows the coverage of anchors with respect to the element. Anchors cluster in the neighborhood of known antibiotic resistance genes in all but ICEVchBan8, where they overlap with a known transposase.

Fig. 3. De novo discovery of transposons. **a.** DIVE anchors with variability in a single direction are chosen as putative TE termini that can be used as seeds in an seeded assembly step. The resulting contigs are translated to produce amino acid sequences. Lastly, protein domain homology can be performed on the resulting protein sequences to identify putative transposable elements, as well as other elements of interest. **b.** Pile up of anchors in *IS6110* concentrating on the ends of the insertion sequence, which has a length of 1354 bp. **c.** Histogram of the number of alignment loci for each contig in at least a *M. tuberculosis* genome in the NCBI nucleotide database. **d.** BLAST alignment of contig104 against a *M. tuberculosis* genome, mapping to two copies of the element inserted in opposite directions. This contig corresponds to the insertion sequence *IS6110*. **e.** BLAST alignment of contig2 against a *M. tuberculosis* genome. This contig corresponds to the insertion sequence *ISMt1*.

Fig. 4. DIVE discovers unexplained hyper-variability in *E. coli* and *V. cholerae*. a. The anchor CCGCCATATCACCTCCGTGATG-GTTGC showed the largest median effect among unannotated anchors in *E. coli* (α=4.22, prevalence=5.28%). The anchor produces a unique match in *E. coli* O157 overlapping isomerase Arabinose 5-phosphate isomerase (kdsD). The multiple sequence alignment (CLUSTALW) of a random selection of 20 reads containing the unannotated anchor (below). The sequence consensus (black bars) is approximately 100% upstream of the anchor (light blue), whereas downstream of the anchor the sequences found across the reads diverge significantly and introduce substitutions and indels. **b.** The unannotated anchor CCGCCATATCACCTCCGTGATGGTTGC showed the largest median effect size among unannotated anchors in *V. cholerae* (α=3.47, prevalence=5.17%). The anchor produced a single match in at least one hundred NCBI accessions, all *V. cholerae* strains, mapping to the intergenic region between tRNA-Cys and the artP gene (arginine ABC transporter ATPase), with the former being in the direction of more target diversity. The multiple sequence alignment (CLUSTALW) of a random selection of 20 reads containing the unannotated anchor (below). The sequence consensus (black bars) is approximately 100% upstream of the anchor (light blue), whereas downstream of the anchor the sequences found across the reads diverge significantly and introduce substitutions and indels.