Exploration of DPP-IV inhibitory peptide design rules assisted by deep learning pipeline that identifies restriction enzyme cutting site

Changge Guan[1]*[†], Jiawei Luo[2†], Shucheng Li[1†], Zheng Lin Tan[3†], Yi Wang[1], Haihong Chen[4,5], Naoyuki Yamamoto[3], Chong Zhang[1,6], Yuan Lu[1], Junjie Chen[2], and Xin-Hui Xing[1,4,5,6]*

[1] Key Laboratory for Industrial Biocatalysis, Ministry of Education of China, Department of Chemical Engineering, Tsinghua University, Beijing, China.
[2] Department of Computer Science and Technology, Harbin Institute of Technology, Shenzhen, China.
[3] School of Life Science and Technology, Tokyo Institute of Technology, Yokohama, Japan.
[4] Institute of Biopharmaceutical and Health Engineering, Tsinghua Shenzhen International Graduate School, Shenzhen, China.
[5] Institute of Biomedical Health Technology and Engineering, Shenzhen Bay Laboratory, Shenzhen, China.
[6] Center for Synthetic and Systems Biology, Tsinghua University, Beijing, China.
[†] These authors contributed equally to this work.

Keywords

DPP-IV inhibitory peptide, peptide language model, DPP-IV cleavage site, dipeptide repeat unit

Abstract

Mining of anti-diabetic dipeptidyl peptidase IV (DPP-IV) inhibitory peptides (DPP-IV-IPs) is

currently a costly and laborious process. Due to the absence of rational peptide design rules, it relies

on cumbersome screening of unknown enzyme hydrolysates. Here, we present an enhanced deep

learning (DL) model called BERT-DPPIV, specifically designed to classify DPP-IV-IPs and

exploring their design rules to discover potent candidates. The end-to-end model utilizes a fine-

tuned bidirectional encoder representations (BERT) architecture to extract structural/functional

information from input peptides and accurately identify DPP-IV-Ips from input peptides.

Experimental results in benchmark dataset showed BERT-DPPIV yielded state-of-the-art accuracy

of 0.894, surpassing the 0.797 obtained by sequence-feature model. Furthermore, we leverage the

attention mechanism to uncover that our model could recognize restriction enzyme cutting site and

specific residues that contribute to the inhibition of DPP-IV. Moreover, guided by BERT-DPPIV,

proposed design rules of DPP-IV inhibitory tripeptides and pentapeptides were validated and they

can be used to screen potent DPP-IV-IPs.

1 Introduction

Due to the side effects and the requirement of injection of commercial dipeptidyl peptidase IV

(DPP-IV) inhibitors, which are used to treat approximately 537 million patients with type II

diabetes, it is crucial to develop new DPP-IV inhibitory drugs and functional foods[1,2,3]. Peptides

with DPP-IV inhibitory activities are a promising class of oral hypoglycemic without adverse

effects, which are derived from products of enzymatically hydrolyzed edible animal, plant, and

macroalgal proteins[1].

Current approaches for the discovery of DPP-IV inhibitory peptides (DPP-IV-IPs) are known to be

labor- and cost-intensive. For instance, conventional enzymatic hydrolysate screening method

requires extensive separation and purification, mass spectrometric identification and revalidation of

peptide synthesis[2,3]. In addition, the lack of design rules and effective characterization methods

make it challenging to design DPP-IV-IPs and synthesis peptide libraries for DPP-IV-IPs screening[4].

These problems have limited the discovery of efficient DPP-IV-IPs. Therefore, it is an important

task to develop a high-throughput method capable of rapidly identifying effective DPP-IV-IPs that

can be used in functional foods or medicine innovation[1,2,5].

Recently, powered by artificial intelligence, large language models (LLMs) based on natural

language processing (NLP) have been successful used to solve biological problems. Therefore,

computation tools complement experimental studies in DPP-IV-IPs discovery process. Over the

past decade, several computational approaches have been used for the discovery of DPP-IV-IPs

including quantitative structure-activity relationship method[6–9] and machine learning (ML)[7,10–13].

The ML methods mainly include support vector machine and random forest[14–16]. However, such

methods reported to date have some major limitations leading to poor performance: (1) the

performance of these models is heavily dependent on the quality of the features extracted by feature

engineering, (2) they are poorly able to represent amino acid sequences, and (3) they fail to capture

information hidden in the amino acid sequence itself, which renders these models inefficient.

Furthermore, classifiers for DPP-IV-IPs developed to date have not been verified experimentally

due to low accuracy of model which will result in high cost of experimental verification.

Deep neural networks with advanced architecture can overcome these limitations, and have a

capability of automating feature learning to extract discriminating feature representations with

minimal human effort[17]. In particular, DL methods, e.g., long-short term memory, which is based on

NLP and regarded amino acid sequence as natural language, is a promising method in identifying

functional peptides for extraction of discriminative feature representation, such as anti-microbial

peptides[18–21]. However, DL-based models have been criticized for their interpretability and

unexplainable characteristics, which are referred to as a 'black box'. Moreover, limited volume of

data is a great challenge to training DL models from scratch.

In this article, we present a novel peptide language model (PLM)-based DL model, named BERT-

DPPIV, to offer a promising solution to address the challenges of DPP-IV-IPs screening and design.

BERT-DPPIV combines a pre-training process based on unlabeled protein data and a NLP BERT

model with an attention mechanism to identify DPP-IV-IPs. By learning the discrimination task,

BERT-DPPIV was trained to automatically learn the characteristics and features contained in the

original peptide sequences and to distinguish and represent amino acid sequences in high-

dimensional spaces, and achieved state-of-the-art.

Benefiting from the attention mechanism, BERT-DPPIV has good interpretability, which is more

advantageous than existing ML algorithms for DPP-IV-IPs identification. According to the attention

analyses, we have found that our model can learn tertiary structure property of peptide except for

physicochemical properties. Particularly, we have found that BERT-DPPIV can identify cleavage

sites of DPP-IV enzymes on the substrate polypeptides, which was first reported, and suggested that

NLP DL model may be used to analysis enzyme cleavage site.

The accuracy of BERT-DPPIV was validated by wet laboratory experiment based on measurement

of half maximal inhibitory concentration (IC_{50}) of synthetic peptides predicted to be DPP-IV-IPs by

BERT-DPPIV, and the result suggest that the prediction accuracy is in align with experimental data,

thus extending the computational model to practical applications. By combining both the PLM

model and biological assays, we have proposed a novel DPP-IV inhibitory pentapeptide design

strategy based on the dipeptide repeat unit X-proline to provide a new idea for the design of DPP-

IV-IPs. This design strategy has addressed the bottleneck in DPP-IV-IP discovery and demonstrated

that *in silico* evaluation method can aid peptide drug development.

Results

Overview of BERT-DPPIV

BERT-DPPIV is a PLM-based DL framework designed for mine novel DPP-IV-IPs based on their

amino acid sequence (Fig 1). To realize this, the framework consists of four main components: pre-

training, fine tuning, analysis, and model validation and application. During the pre-training

procedures, a total of 556,603 protein sequences from databases including UniProt, SWISS-PROT,

TrEMBL, and PIR-PSD were used to pre-trained 12 layer of BERT-based language models. We

employed three different word segmentation approaches, i.e., kmer = 1, kmer = 2, kmer = 3 to

generate three pre-trained BERT models. Two major tasks, i.e., masked language model (MLM)

and next sentence prediction (NSP) involved in the pre-training procedures for capturing word-level

and sentence-level representations and learning the common features of protein sequences. The

fine-tuning process aimed to construct PLM model specifically for the task of identifying DPP-IV-

IPs.

Fig. 1 Schematic representation of study workflow. We first collected sequences to pre-train a BERT model

(upper left). We then used the DPP-IV-IP dataset for fine-tuning the pre-trained BERT model to obtain three

kinds of PLMs. The three models were combined to construct the BERT-DPPIV (upper middle). To

determine what the model had learned, we analyzed and visualized the model's attention (upper right, analysis

module). We then used BERT-DPPIV to screen tripeptides that may inhibit DPP-IV to illustrate the

performance of our model inhibition (upper right, model validation module). After the model screening, the

functional peptides screened out by the model were verified by biological experiments (lower right). Having

demonstrated the practical applicability of our model, we proposed a design strategy for DPP-IV-IPs based on

dipeptide repeat units and demonstrated the feasibility of this strategy using models and experiments (lower

left).

The framework's analysis component involved evaluating the performance and capabilities of

BERT-DPPIV. Various metrics were conducted to assess the model's ability to predict and identify

DPP-IV-IPs accurately. Three models with different kmers in the test set showed the highest

accuracy (Acc) of 0.891 was achieved for kmer = 1, followed by 0.887 for kmer = 2, and 0.842 for

kmer = 3 and BERT-DPPIV combining three models achieved state-of-the-art, which resulted in an

improved Acc of 0.894 (Supplementary Table. 1).

Our models (kmer=1, kmer=2, and kmer=3) outperform the first sequence-based iDPPIV-SCM

model, as evidenced by significant improvements in Acc and Matthews correlation coefficient

(MCC) respectively (Supplementary Table. 1). These results highlight the ability of our models to

extract more valuable information from peptide sequences. To further compared with sequence-

based physicochemical property SVM model and the sequence- and structure-based StackDPPIV

model. Our model (kmer=1) achieves the same accuracy as the best model StackDPPIV and BERT-

DPPIV outperforms it. These results suggest that our models are able to extract physicochemical

properties or structure information and BERT-DPPIV can make good use of information from

different models. Moreover, the visualization of the model demonstrated these findings further.

Finally, the model was validated and applied to real-world scenarios, providing a tool for mining

and discovering novel DPP-IV-IPs based on their amino acid sequences. Overall, we demonstrate

the capability of BERT-DPPIV to predict important parameters for DPP-IV-IPs to guide DPP-IV-

IPs screening, i.e., (1) inhibitory activity of peptides, (2) physicochemical properties of peptides

sequences, (3) structural properties from peptide sequences, and (4) capture cleavage site

information. Furthermore, we have also shown the application of BERT-DPPIV in guiding the

design of DPP-IV-IPs in addition to peptides screening. Pentapeptides were designed, and their

DPP-IV inhibitory activity was predicted and verified.

Sequence representation and its properties learned by BERT-DPPIV

To investigate the information captured by our models, we selected kmer = 1 that exhibit the

highest Acc among our three kmer models for further study. First, we analyzed the representation of

the peptide sequences learned by the pretrained BERT, as prior studies have shown that BERT

models can effectively learn the representation of the sequence[18–21]. The vector representations of

the peptide sequences during the training process of the model were extracted and projected to 2D

by t-distributed stochastic neighbor embedding (t-SNE) for visualization (Supplementary Fig. 1),

which showed that the model was able to identify DPP-IV-IPs by learning the vector representation

of peptides.

In addition, we have illustrated the ability of our model to learn physicochemical properties of

peptides by visualizing the distribution of amino acid and peptide representations. The vector

representation learned by the model was well able to distinguish amino acids with different

properties (Fig. 2a). We then used the modlAMP package[22] to extract 10 kinds of physicochemical

property information from peptide sequences. Based on peptide sequence physicochemical

properties, the vector representation of it was then analyzed. The vector representations learned by

the model were able to distinguish among sequences with different physical and chemical properties

(Fig. 2b,c, Supplementary Fig. 2). To this point, we have shown that the PLM can learn the

physicochemical properties of the peptide sequences.

Fig. 2 Sequence representation visualization and attention visualization of structural information learned by the model. A vector representation of the peptide sequence and of individual amino acids was extracted from the model and analyzed by t-SNE. The amino acid representation learned by the model (a) and physicochemical properties contained in model-learned representations of peptide sequences (b and c) are shown. Here, we show how the inner workings of the model's attention heads can be used to analyze a single peptide in more detail. Each attention head performs internally an all-against-all comparison to compute weighted sums for each token relative to all other tokens in the sequence. High scores indicate that the model learned to put more weight on certain residue pairs (upper left, lower left, and lower right). The structure of the peptide shows that Ser-3 can interact with Phe-1, Gln-6, and Gln-7 and that Gln-14 can interact with His-18. When visualizing the attention weights for these sites, we observed that some of the attention heads can capture this interaction information.

Capturing the structural information and attention patterns generated by the

models

The attention mechanism provides a way to reveal 'black-box' of DL models and features learned

by it[23,24]. In this section, we investigated the capability of our model to learn structural information

about peptide sequences with the help of an attention mechanism, which is a technology that

mimics cognitive attention. First, the structure of the peptides with a length ≥ 5 amino acids from

positive samples was predicted by APPTEST software[25], and 12 kinds of peptides with α-helix

secondary structure were found (Supplementary Fig. 3). Three peptides were randomly selected

from among these peptides for further structural confirmation using AlphaFold2[26]. The presence of

α-helical structures was confirmed.

Then, the attention of the model for each head at each layer of the model was visualized (12 layers,

12 heads per layer) (Supplementary Fig. 4). As shown in Fig. 1, Fig. 2d, and Supplementary Fig. 5,

we observed that the attentions focus on the interacting sites of peptides, suggesting that this model

was able to capture the structural information of peptide sequences. Furthermore, analysis of 144

attention mechanisms (Supplementary Fig. 4) showed that several learning mechanisms existed in

the model, which include previous-word attention patterns (Supplementary Fig. 6a), next-word

attention patterns (Supplementary Fig. 6b), delimiter-focused attention patterns (Supplementary Fig.

6c), specific-word attention patterns (Supplementary Fig. 6d,e), and related-word attention patterns

(Supplementary Fig. 6f).

Attentions of BERT-DPPIV divert to DPP-IV cleavage sites and proline

In most cases, the attention learned by BERT-DPPIV focused on the second and third positions of the N

terminus of the polypeptide sequences (Supplementary Fig. 6d-g), which are the cleavage sites

of DPP-IV[4]. This result suggested that our model can capture information about DPP-IV

cleavage sites by learning the sequence of polypeptide substrate.

To further illustrate the capability of cleavage site prediction, we statistically analyzed the attention

sites of the sequences of training set (Fig. 3a, b). These results suggested that the attention of our

model focused on the cleavage sites of DPP-IVs. Furthermore, a comparison of the changes in

attention positions of the model before and after fine-tuning have supported that our model could

capture cleavage site information of DPP-IVs.

Fig. 3 Visualization of the position and importance of amino acid species. To study the importance of position

and amino acid species, attention to positions and amino acids was statistically analyzed. BERT-BASE and

BERT-DPPIV represent the models before and after fine-tuning, respectively. The statistical importance of

the position of peptide sequence according to the attention of the model is shown (a and b). The statistical

importance of amino acid species according to the attention of the model is shown (c and d). The attention of

the model to proline and cysteine in the peptide sequence was visualized (e, f, g, and h).

We have further investigated the capability of our model to analyze the importance of each amino

acid in the sequences. Statistical analyses have suggested that proline is the amino acid of major

concern in our model, whereas cysteine is of the least concern. Increase in attention toward proline

and decrease in attention toward cysteine were observed (Fig. 3c, d).

To investigate the importance of proline and cysteine in these amino acid sequences, we have

visualized the attention of our model for each amino acid in a randomly selected sequence from α-

lactalbumin, "QNPHSSNICN". We observed differences in all amino acids after training, which

suggested that the model had directed its attention toward important amino acids, e.g., proline

(which is an important amino acid for DPP-IV inhibition), whereas less important amino acids, e.g.,

cysteine, received less attention (Fig. 3e-h). To illustrate the accuracy of this result, we have

statistically analyzed the proportion of our model's attention that was focused on each of the 20

standard amino acids (Fig.4) and compared it to the proportion of pre-train model's attention

(Supplementary Table 2). These results demonstrated that our model efficiently captured the amino

acid types that play important roles in the amino acid sequences of a peptide.

Fig. 4 Percentage of each attention head that is focused on the 20 natural amino acids.

Application of BERT-DPPIV for DPP-IV inhibitory tripeptide screening

To illustrate the usefulness of BERT-DPPIV in mining of DPP-IV-IPs which can be used as anti-diabetic drugs, we applied our model for the screening of DPP-IV inhibitory tripeptides. Prior work conducted by one of the authors (C.G.) classified DPP-IV inhibitory dipeptides into five classes, and, from one class of peptides, represented by VPX and IPX (where X represents one of the 20

amino acids), isolated nine tripeptides with efficient human DPP-IV (hDPP-IV) inhibitory activity[27].

However, it was unknown whether other kinds of tripeptides can efficiently inhibit hDPP-IV. In this

section, one class of tripeptides that contains WPX, WAX, WRX, and WVX from five classes

previously classified was selected for screening.

We predicted the DPP-IV inhibitory activity of the 80 kinds of tripeptides with our models and

found that all these tripeptides are expected to possess DPP-IV inhibitory activity (Supplementary

Table 3). Then, these tripeptides were chemically synthesized, and the inhibitory activity was

verified experimentally based on the IC_{50}, which is inversely correlated to inhibitory activity. IC_{50}

were detected from 72 out of the 80 kinds of tripeptides, and the DPP-IV inhibitory activity of each

of these tripeptides was confirmed (Table 1). The Acc achieved in this study was 90%, which is

consistent with our prediction (Supplementary Table 1). The top three tripeptides for DPP-IV

inhibitory activity were WAW, WAY, and WPN with IC_{50} of 103.66 µM, 117.40 µM, and 128.59

µM, respectively. This result demonstrated that our model could predict DPP-IV-IPs with 90%

accuracy.

A proposed strategy to design DPP-IV-IPs based on the repeating dipeptide

unit X-proline

Recently, the development of protein synthesis technology has enabled screening of DPP-IV

inhibitory activity among chemically synthesized peptides. These studies were conducted based on

the property of preferential cleaving of X-proline or X-alanine from the N terminus of peptides by

DPP-IV. However, the feasibility of designing the repeating dipeptide unit X-proline remained

unclear. To address this problem, we used our model to investigate the potential of this design

strategy.

As VPI has the highest hDPP-IV inhibitory activity[27], the dipeptide unit VP was selected for further

study. A library of 20 pentapeptides containing two VP repeats (VPVPX) was designed, and the

inhibitory activity of these 20 kinds of pentapeptides were predicted by our model. In addition,

IPIPI and IPVPI were also predicted by our model, as IPI has the highest porcine DPP-IV inhibitory

activity[27]. The model predicted that 14 out of 22 pentapeptides exhibit inhibitory activity against

DPP-IV, which has provided us with new insights into the properties of pentapeptides capable of

inhibiting DPP-IV (Supplementary Table 4).

To verify the properties of the peptides predicted, these peptides were chemically synthesized, and

their IC_{50} were measured (Fig. 5, Supplementary Table 5). Eight pentapeptides were identified as

false negatives, whereas the IC_{50} for the other peptides were correctly predicted. The top three

peptides with the highest IC_{50} were IPIPI, VPVPH, and VPVPC, which were 47.47 µM, 51.11 µM,

and 54.77 µM, respectively. Inhibitory activity of IPIPI was 2.18-fold higher than WAW, which is

the tripeptides with highest inhibitory activity detected in this study. This result indicates that

pentapeptides with the repeating dipeptide unit VP exhibit higher DPP-IV inhibitory activity as

compared with tripeptides and thus suggests that designing peptides with repeating units is a more

efficient strategy.

Fig. 5 Characteristics of the activity of DPP-IV inhibitory pentapeptides. The pentapeptides were characterized by (a) IC_{50} and (b) binding affinity.

To understand the DPP-IV inhibitory activity of these pentapeptides, their binding energy, which is inversely proportional to inhibitory activity, was analyzed with MDockPeP[28]. We calculated the binding affinities of pentapeptides to hDPP-IV and found that VPVPW, VPVPR, and VPVPY had the lowest affinity. However, a difference was observed in their ranking with respect to binding affinity relative to that for IC_{50} (Supplementary Table 5). This difference might have resulted from (1) the docking method, which reflects only the first step of the interaction between the polypeptide and DPP-IV and cannot reflect the subsequent two consecutive VP cleavage steps, or (2) the docking affinity being calculated based on DPP-IV in the static state, which thus did not consider the dynamic of DPP-IV.

These results suggested that a design strategy based on repeating X-proline units is effective and

feasible, although the efficiency of peptides with repeating units of X-alanine should be investigated.

Discussion

In this study, we have successfully built a PLM-based model BERT-DPPIV for mining novel DPP-

IV-IPs and applied it to guide biological experiments for screening and design. Our model, BERT-

DPPIV, had demonstrated Acc of 0.894, which is higher than those previously reported, e.g.,

StackDPPIV[16]. Furthermore, this model can also capture more biologically relevant information

from peptide sequences, notably the cleavage site information of DPP-IV and structure information

of peptide sequences (Fig. 2, Supplementary Fig. 5). Our model can automatically capture

information from various aspects of sequence, structural feature information from the peptide

sequence, and the specific cleavage site features from the peptide dataset. This renders our model

more advantageous than StackDPPIV, which has been the best model described to date, as the latter

must extract sequence and structure feature information by feature engineering.

Although our model has achieved good performance, there is room for further improvement. As

BERT models that use the word segmentation method with overlap, e.g., DNABERT[29], typically

show higher accuracy than those that do not, our model which is based on the non-overlapping

word segmentation method, can be further improved by using an overlapping segmentation method.

The attention-based BERT model adopted in this study overcomes poor interpretability of DL

methods. Visualizing the model's attention during learning revealed what the model learned and

how this model had changed during training. Through this strategy, we discovered that our model

can capture cleavage site information for DPP-IV in addition to the physicochemical properties and

structural information of the peptide sequence (Fig. 2, Supplementary Fig. 5), which had not

1   **Table. 1** Experimental characterization of tripeptides that inhibit DPP-IV

Peptide	IC_{50}, μM	Peptide	IC_{50}, μM	Peptide	IC_{50}, μM	Peptide	IC_{50}, μM
WRM	896.67	WPE	353.02	WAC	282.79	WPQ	196.18
WRP	741.50	WAG	352.16	WRH	277.20	WVE	192.50
WPC	739.03	WVD	343.00	WVV	275.33	WAH	189.55
WAR	664.68	WVA	341.25	WAA	274.53	WVF	188.33
WRW	603.14	WVG	340.63	WRG	269.85	WPW	182.96
WPS	588.31	WVT	335.63	WRS	265.09	WRE	160.15
WRT	555.60	WVK	331.38	WAL	260.10	WAF	153.32
WRV	541.17	WRI	330.4	WRF	257.07	WRL	150.75
WRA	534.67	WAM	329.85	WVH	256.86	WPG	134.98
WPV	511.47	WVM	317.00	WAV	249.79	WPN	128.59
WPD	480.61	WPH	314.57	WVS	247.00	WAY	117.40
WAE	461.79	WRN	313.20	WVW	238.63	WAW	103.66
WPL	461.32	WPY	303.79	WVC	231.78	WPI	-
WAP	440.97	WPP	303.49	WPM	218.75	WPK	-
WPT	435.08	WAN	301.78	WVY	214.88	WAK	-
WAD	432.65	WRY	296.50	WRC	209.64	WAS	-
WVP	402.00	WAT	296.33	WPR	208.94	WRK	-
WVL	398.88	WAQ	289.19	WPA	206.01	WRR	-
WVN	372.88	WPF	285.91	WRD	203.64	WVI	-
WVQ	366.00	WRQ	285.50	WAI	198.88	WVR	-

2   IC_{50} : half maximal inhibitory concentration.

3   - : not detected within 1

1 previously been reported as a classifier. This is the first use of the PLM BERT to discover enzyme

2 cleavage site information from substrate information, and this model should be extremely helpful in

3 understanding the biological implications of DPP-IV. Apparently, this feature can be extended to

4 other enzymes after pre-training with respective databases, and it should be applicable to

5 understanding the functions of different enzymes and to mining the cleavage site information of

6 enzymes.

7 In contrast with the previous classifiers for inhibiting DPP-IV peptides[14–16] that were tested only on

8 a dataset and were not verified by actual screening experiments, we used the proposed model to

9 screen tripeptides with DPP-IV inhibitory activity and showed experimentally that our model had

10 an accuracy of 90%. DPP-IV inhibitory activity was identified in 72 out of 80 tripeptides predicted

11 (Table 1). This result suggested that our model can be used to aid in the screening of functional

12 peptides that inhibit DPP-IV.

13 The number of reported DPP-IV inhibitory polypeptides is still limited due to the absence of

14 strategies for designing DPP-IV inhibitory polypeptide libraries. Therefore, we have also proposed

15 a new peptide design strategy to design polypeptides that inhibit DPP-IV based on repeating

16 dipeptide units to accelerate mining of DPP-IV inhibitory polypeptides. This design strategy has

17 been verified and shown to be feasible through the predictions of our model and subsequent

18 biological assays. Twenty-two pentapeptides containing VP or IP were discovered to inhibit DPP-

19 IV efficiently. This design strategy can help researchers to efficiently explore peptides that inhibit

20 DPP-IV. The accuracy of the model for pentapeptide prediction was 63.6% despite the lack of

21 sequences with repeating dipeptide units in the training dataset. It is likely that the model can be

22 improved by increasing the availability of data through biological assays. Verification of the

23 efficiency of the model in predicting long peptide sequences is in progress.

In conclusion, we have constructed the first PLM-based DPP-IV classifier and have verified its

performance experimentally. Furthermore, based on the assistance of the classifier, 72 peptides

were revealed to inhibit DPP-IV. A novel design strategy for peptides with DPP-IV inhibitory

activity was proposed and verified, based on which 22 pentapeptides were discovered to have DPP-

IV inhibitory effects.

In conclusion, we have proposed BERT-DPPIV, a PLM model which is very effective in DPP-IV-

IPs mining. This model could aid screening and design of DPP-IV-IPs, which will greatly accelerate

the process and reduce the cost of anti-diabetic drug development.

Methods

Database

The pre-trained protein data were downloaded from UniProt and can be accessed on Google Drive

at

https://drive.google.com/file/d/1QeXWV5_OIKgms7u5ShNfvPEKPBLOC3UT/view?usp=sharing.

This dataset contains 556,603 protein sequences[30]. The dataset used for fine-tuning was previously

described and was used to train and test our proposed model[14]. The benchmark dataset includes 532

DPP-IV-IPs and the same number of peptides with no inhibitory activity against DPP-IV. The

number of IPs and non-inhibitory peptides in the independent dataset was 133 peptides each.

Reagents and peptides

hDPP-IV (>200 U/ml) was obtained from the ATGen company (South Korea). Gly-Pro *p*-

nitroanilide (Gly-Pro-pNA) was obtained from the Cayman Chemical Company (Michigan, US).

Peptides containing VPVPX, WPX, WAX, WRX, and WVX (where X represents any one of 20

amino acids) with purity > 95% were synthesized by Gen-Script (Suzhou, China).

Training of the PLM

BERT[31] is a pre-trained language model developed by Google for natural language text applications

and achieves state-of-the-art results on downstream NLP tasks through transfer learning. We pre-

trained 12-layer BERT-based language models on 556,603 protein sequences from the UniProt

dataset[30].

To adapt our model to different sequence lengths, we used different word segmentation lengths,

kmer = 1, kmer = 2, and kmer = 3, to generate three pre-trained BERT models. The pre-training

process consisted of two pre-training tasks: masked language model (MLM) and next sentence

prediction (NSP), so that our pre-trained BERT models could capture word-level and sentence-level

representations and learn the common features of protein sequences. MLM is able to model

complex relationships between amino acids and capture the evolutionary information of proteins[32].

During the MLM task, 15% of the tokens among the original protein sequence were randomly

masked to obtain the masked sequence, and a special token [MASK] was used to replace the

masked token 80% of the time, a random token was used 10% of the time, and the selected token

was unchanged 10% of the time. The model then predicted the masked tokens based on the context

of the unmasked sequence for language modeling. For training, we minimized the negative log

likelihood of the true amino acid at each of the masked positions using equation (1),

$$L_{\mathrm{MLM}} = - \sum_{\hat{x} \in m(x)} \log q\left(\hat{x} \,|\, x_{\backslash m(x)}\right) \#(1)$$

Where L_{MLM} is the loss function of MLM, $m(x)$ and $x_{\backslash m(x)}$ denote the masked tokens from the

protein sequences x and the remaining tokens, respectively. During the NSP task, the data were

randomly divided into two equal parts A and B: choosing the protein sequence segments A and B

for each pretraining example, 50% of the time B is the actual next sentence that follows A (labeled

as IsNext), and 50% of the time it is a random sentence from the corpus (labeled as NotNext).

BERT was trained by identifying whether these protein sequence segment pairs were continuous.

The loss function of the NSP task, L_{NSP} was described as equation (2),

$$L_{\text{NSP}} = -\log p(t \mid x, y) \#(2)$$

6 where $t = 1$ if x and y are continuous protein segments from protein corpus.

7 Then MLM and NSP were trained together, with the goal of minimizing the combined loss function

8 of the two strategies as defined in Eq. (3).

$$L = L_{\text{MLM}} + L_{\text{NSP}} \#(3)$$

The pre-training hyperparameters included train steps of 10 million times, a learning rate of $2 \times$

10^{-5} and a batch size of 32 to train the BERT model[30]. After the pre-training process, we obtained

three pre-trained BERT models. To construct the PLM for a specific downstream task that identifies

and predicts DPP-IV-IPs, we modified the pre-trained BERT model**s** by adding a classification

layer on top of the BERT output for the [CLS] token. We fine-tuned the pre-trained model on a

benchmark dataset containing DPP-IV-IPs without major architectural modifications. For the fine-

tuning hyperparameters, we used a learning rate of 2×10^{-6}, a batch size of 32, a warm-up

proportion of 0.1, and an average training of 50 epochs.

Performance evaluation of the model

We used four general quantitative indicators to evaluate our model: Acc, sensitivity (Sn), specificity

(Sp), and the MCC, each of which is defined by equation (4), equation (5), equation (6), and

equation (7), respectively. TP (true positive) is the number of correctly predicted DPP-IV-IPs, FN

(false negative) is the number of DPP-IV-IPs that were in fact predicted to be non-DPP-IV-IPs, TN

(true negative) is the number of correctly predicted non-DPP-IV-IPs, and FP (false positive) is the

number of non-DPP-IV-IPs that were in fact predicted to be DPP-IV-IPs.

$$\text{Acc} = \frac{\text{TP} + \text{TN}}{(\text{TP} + \text{FP} + \text{TN} + \text{FN})} \#(4)$$

$$\text{Sn} = \frac{\text{TP}}{(\text{TP} + \text{FN})} \#(5)$$

$$\text{Sp} = \frac{\text{TN}}{(\text{TN} + \text{FP})} \#(6)$$

$$\text{MCC} = \frac{\text{TP} \times \text{TN} - \text{FP} \times \text{FN}}{\sqrt{(\text{TP} + \text{FP}) \times (\text{TN} + \text{FN}) \times (\text{TP} + \text{FN}) \times (\text{TN} + \text{FP})}} \#(7)$$

Sn and Sp reflect the model's ability to recognize DPP-IV-IPs and non-DPP-IV-IPs, respectively,

and Acc embodies the overall prediction effect of the model. The value range of the three is [0,1],

and the larger the value, the more accurate the model's prediction. MCC is usually considered a

balanced indicator and can be used even if the sample is not balanced. Its value is between –1 and

+1, reflecting the correlation between the true label of the sample in the testing set and the predicted

result. The higher value indicates a greater correlation. When the value is close to +1, the

classification performance of the model is excellent; when it is close to –1, the prediction result of

the model is the opposite of the actual result; and when it is close to 0, the prediction result of the

model is similar to a random prediction. In addition, the area under the receiver operating

characteristic (AUC) was used as another statistical metric. Considering these five evaluation

indicators, the performance of the classification models can be better evaluated.

Visualization of the Model

Representation visualization was used to analyze the learning capacity of the model. To the original

protein sequence, $x = [x_1, \ldots, x_n]$ will, we added the special start and end tokens, CLS and SEP,

respectively, and got the final input sequence $x' = [\text{CLS}, x_1, \ldots, x_n, \text{SEP}]$. The resulting sequence

representation h_i was obtained from hidden states in the i^{th} layer of BERT-DPPIV.

Analyzing the information contained in the representation learned by the model, we used the vector

corresponding to CLS in each layer of BERT-DPPIV to represent the analytical sequence and

analyzed the representation at the residue level and sequence level by t-SNE. At the residue level,

amino acids were divided into six categories, consisting of aromatic (W, F, Y), aliphatic (M, L, I, A,

V), positive (R, H, K), negative (D, E), polar neutral (Q, N, S, T), and special-case (G, P, C)

residues. At the sequence level, 10 kinds of physicochemical property information were obtained

from the modlAMP package[22].

Attention visualization was used to analyze the information about which the model was specifically

concerned and provide interpretable analysis. Each attention head in a model layer produces an

attention matrix, α, which indicates the degree of correlation between token pairs. For example, $\alpha_{i,j}$

indicates the attention from token i to token j, and the weight of token i for all tokens is 1, as shown

in equation (8).

$$\sum_{j=1}^{n} \alpha_{i,j} = 1 \#(8)$$

We analyzed attention through a multiscale visualization tool for the Transformer model[24]. The

attention-head view in this tool expresses the self-attention matrix α in the form of connected lines

and displays the attention patterns generated by one or more attention heads in a given layer. The

lines in the head view indicate how much of the hidden state information of the attending token

(right) will flow to the attended token (left) (Fig. 2d). The different colors of the lines indicate

different attention heads, whereas the color depth of the line is related to the attention weight. The

model view in the tool provides a global view of attention patterns across all layers and heads of the

model. We then use a slightly simplified version of AlphaFold[26] to obtain the structure information

of the polypeptide sequences and explore the relationship between sites of interaction in

polypeptide structures and model attention patterns.

We then used the attention matrix to calculate the importance of each token, d_j, in the peptide

sequence as shown in equation (9).

$$d_j = \sum_{i=1}^{n} \alpha_{i,j} \#(9)$$

We carried out a statistical analysis of 144 attention patterns including all layers and all heads of

each layer. We removed sequences of less than or equal to three amino acids. Then we calculated

the importance of all tokens including the special tokens (CLS, SEP) and selected the three most

important tokens from each sequence for each attention pattern. We counted the distribution of the

top three most important tokens across the different patterns for each sequence with respect to their

position and amino acid type. We also selected a specific residue in the sequence and calculated the

importance of this residue in 144 attention patterns and visualized the results using a heatmap. We

then investigated the interaction between attention and particular amino acids[24]. We used equation

(10) for amino acids and defined an indicator function, $f(i,j)$, that returns a value of 1 if this amino

acid was present in the token j (e.g., if token j is a proline).

$$p_\alpha(f) = \frac{\sum_{x \in X} \sum_{i=1}^{|x|} \sum_{j=1}^{|x|} f(i,j) \cdot 1_{\alpha_{i,j} > \theta}}{\sum_{x \in X} \sum_{i=1}^{|x|} \sum_{j=1}^{|x|} 1_{\alpha_{i,j} > \theta}} \#(10)$$

where $p_\alpha(f)$ equals the proportion of attention that is directed to the amino acid. We computed the

proportion of attention for the fine-tuned model and the pre-trained model directed toward each of

the 20 standard amino acids.

DPP-IV Inhibitory Assay

DPP-IV inhibitory activity was measured according to a slightly modified version of the method

described previously[8]. hDPP-IV was used for the triplicate measurements. Peptide solution (20 µl);

substrate solution, consisting of 2 mM Gly-Pro-pNA (20 µl); and Tris-HCl buffer (pH 8.0; 20 µl)

were pre-mixed in a 96-well microplate. The reaction was initiated by adding 40 µl of hDPP-IV

(final concentration, 0.025 U/ml) in 100 µl of the above mixture. The samples were then incubated

at 37°C for 60 min. Absorbance at 405 nm was measured using a microplate reader. The negative

control mixture included Tris-HCl buffer (pH 8.0), Gly-Pro-pNA, hDPP-IV, and phosphate

buffered saline (pH 7.4). The hDPP-IV inhibitory ratio of the sample was calculated according to

equation (11),

$$\text{Inhibition ratio} = \frac{A_{\text{Control}} - A_{\text{Sample}}}{A_{\text{Control}}} \#(11)$$

where A_{Control} is the absorbance of the control sample with PBS and A_{Sample} is the absorbance of

the peptide sample.

Data and Software Availability

The code used in this work is publicly available and can be accessed at

https://github.com/guanchangge/BERT-DPPIV. The data used in this work will be

made available upon reasonable request and completion of technology transfer

agreement.

Declarations

The authors declare no competing interests

Corresponding Author

5   Xin-Hui Xing

6   xhxing@mail.tsinghua.edu.cn

7   Changge Guan

8   Changge.Guan@Pennmedicine.upenn.edu

Present Address

11   Changge Guan

12   Perelman School of Medicine, University of Pennsylvania, Philadelphia, PA, 19104, United

13   States

Author Contributions

X.-H.X., N.Y., Y.L., and C.G. conceived the project and designed the study. C.G.

designed the tripeptide and pentapeptide screening experiments; J.C. and C.G.

designed the model construction and analysis; C.G. and S.L. performed the

tripeptide and pentapeptide screening experiments; C.G. and J.Luo performed

model construction; C.G. conducted wet experiments; C.G., J.Luo, and Z.L.T.

performed data analysis and interpretation. C.G., J.Luo, J.C., and Z.L.T. drafted

and revised the paper. J.Li, Z.W., H.C., Y.W. and C.Z. provided consultation for

the project. All authors contributed to the revision of the paper.

Funding Sources

5 This work was funded by Shenzhen Science and Technology Innovation Commission

6 (KCXFZ20201221173207022), Natural Science Foundation of China (62102118).

References

(1) Barnett, A. DPP-4 Inhibitors and Their Potential Role in the Management of Type 2 Diabetes:

DPP 4 INHIBITORS AND MANAGEMENT OF TYPE 2 DIABETES. *Int. J. Clin. Pract.*

2006, *60* (11), 1454–1470. https://doi.org/10.1111/j.1742-1241.2006.01178.x.

(2) Nongonierma, A. B.; FitzGerald, R. J. Features of Dipeptidyl Peptidase IV (DPP-IV)

Inhibitory Peptides from Dietary Proteins. *J. Food Biochem.* **2019**, *43* (1), e12451.

https://doi.org/10.1111/jfbc.12451.

(3) Wang, Y.; Li, S.; Guan, C.; He, D.; Liao, X.; Wang, Y.; Chen, H.; Zhang, C.; Xing, X.-H.

Functional discovery and production technology for natural bioactive peptides. *Chin. J.*

Biotechnol. **2021**, *37* (6), 2166–2180. https://doi.org/10.13345/j.cjb.210047.

(4) Mulvihill, E. E.; Drucker, D. J. Pharmacology, Physiology, and Mechanisms of Action of

Dipeptidyl Peptidase-4 Inhibitors. *Endocr. Rev.* **2014**, *35* (6), 992–1019.

https://doi.org/10.1210/er.2014-1035.

(5) Duez, H.; Cariou, B.; Staels, B. DPP-4 Inhibitors in the Treatment of Type 2 Diabetes.

Biochem. Pharmacol. **2012**, *83* (7), 823–832. https://doi.org/10.1016/j.bcp.2011.11.028.

(6) Nongonierma, A. B.; FitzGerald, R. J. An in Silico Model to Predict the Potential of Dietary

Proteins as Sources of Dipeptidyl Peptidase IV (DPP-IV) Inhibitory Peptides. *Food Chem.*

2014, *165*, 489–498. https://doi.org/10.1016/j.foodchem.2014.05.090.

(7) Nongonierma, A. B.; Mooney, C.; Shields, D. C.; FitzGerald, R. J. In Silico Approaches to

Predict the Potential of Milk Protein-Derived Peptides as Dipeptidyl Peptidase IV (DPP-IV)

Inhibitors. *Peptides* **2014**, *57*, 43–51. https://doi.org/10.1016/j.peptides.2014.04.018.

(8) Nongonierma, A. B.; FitzGerald, R. J. Structure Activity Relationship Modelling of Milk

Protein-Derived Peptides with Dipeptidyl Peptidase IV (DPP-IV) Inhibitory Activity.

Peptides **2016**, *79*, 1–7. https://doi.org/10.1016/j.peptides.2016.03.005.

(9) Nongonierma, A. B.; Paolella, S.; Mudgil, P.; Maqsood, S.; FitzGerald, R. J. Identification of

Novel Dipeptidyl Peptidase IV (DPP-IV) Inhibitory Peptides in Camel Milk Protein

Hydrolysates. *Food Chem.* **2018**, *244*, 340–348.

https://doi.org/10.1016/j.foodchem.2017.10.033.

(10) Nongonierma, A. B.; FitzGerald, R. J. Learnings from Quantitative Structure–Activity

Relationship (QSAR) Studies with Respect to Food Protein-Derived Bioactive Peptides: A

Review. *RSC Adv.* **2016**, *6* (79), 75400–75413. https://doi.org/10.1039/C6RA12738J.

(11) Shoombuatong, W.; Prathipati, P.; Owasirikul, W.; Worachartcheewan, A.; Simeon, S.;

Anuwongcharoen, N.; Wikberg, J. E. S.; Nantasenamat, C. Towards the Revival of

Interpretable QSAR Models. In *Advances in QSAR Modeling*; Roy, K., Ed.; Challenges and

Advances in Computational Chemistry and Physics; Springer International Publishing: Cham,

2017; Vol. 24, pp 3–55. https://doi.org/10.1007/978-3-319-56850-8_1.

(12) Hellberg, S.; Sjoestroem, M.; Skagerberg, B.; Wold, S. Peptide Quantitative Structure-

Activity Relationships, a Multivariate Approach. *J. Med. Chem.* **1987**, *30* (7), 1126–1135.

https://doi.org/10.1021/jm00390a003.

(13) Basith, S.; Manavalan, B.; Hwan Shin, T.; Lee, G. Machine Intelligence in Peptide Therapeutics: A Next‐generation Tool for Rapid Disease Screening. *Med. Res. Rev.* **2020**, *40* (4), 1276–1314. https://doi.org/10.1002/med.21658.

(14) Charoenkwan, P.; Kanthawong, S.; Nantasenamat, C.; Hasan, Md. M.; Shoombuatong, W. IDPPIV-SCM: A Sequence-Based Predictor for Identifying and Analyzing Dipeptidyl Peptidase IV (DPP-IV) Inhibitory Peptides Using a Scoring Card Method. *J. Proteome Res.* **2020**, *19* (10), 4125–4136. https://doi.org/10.1021/acs.jproteome.0c00590.

(15) Zou, H.; Yin, Z. Identifying Dipeptidyl Peptidase-IV Inhibitory Peptides Based on Correlation Information of Physicochemical Properties. *Int. J. Pept. Res. Ther.* **2021**, *27* (4), 2651–2659. https://doi.org/10.1007/s10989-021-10280-2.

(16) Charoenkwan, P.; Nantasenamat, C.; Hasan, M. M.; Moni, M. A.; Lio', P.; Manavalan, B.; Shoombuatong, W. StackDPPIV: A Novel Computational Approach for Accurate Prediction of Dipeptidyl Peptidase IV (DPP-IV) Inhibitory Peptides. *Methods* **2022**, *204*, 189–198. https://doi.org/10.1016/j.ymeth.2021.12.001.

(17) Janiesch, C.; Zschech, P.; Heinrich, K. Machine Learning and Deep Learning. *Electron. Mark.* **2021**, *31* (3), 685–695. https://doi.org/10.1007/s12525-021-00475-2.

(18) Almagro Armenteros, J. J.; Tsirigos, K. D.; Sønderby, C. K.; Petersen, T. N.; Winther, O.; Brunak, S.; von Heijne, G.; Nielsen, H. SignalP 5.0 Improves Signal Peptide Predictions Using Deep Neural Networks. *Nat. Biotechnol.* **2019**, *37* (4), 420–423. https://doi.org/10.1038/s41587-019-0036-z.

(19) Youmans, M.; Spainhour, C.; Qiu, P. Long Short-Term Memory Recurrent Neural Networks for Antibacterial Peptide Identification. In *2017 IEEE International Conference on Bioinformatics and Biomedicine (BIBM)*; IEEE: Kansas City, MO, 2017; pp 498–502. https://doi.org/10.1109/BIBM.2017.8217697.

(20) Yan, J.; Bhadra, P.; Li, A.; Sethiya, P.; Qin, L.; Tai, H. K.; Wong, K. H.; Siu, S. W. I. Deep-

AmPEP30: Improve Short Antimicrobial Peptides Prediction with Deep Learning. *Mol. Ther.*

- Nucleic Acids **2020**, *20*, 882–894. https://doi.org/10.1016/j.omtn.2020.05.006.

(21) Wu, C.; Gao, R.; Zhang, Y.; De Marinis, Y. PTPD: Predicting Therapeutic Peptides by Deep

Learning and Word2vec. *BMC Bioinformatics* **2019**, *20* (1), 456.

https://doi.org/10.1186/s12859-019-3006-z.

(22) Müller, A. T.; Gabernet, G.; Hiss, J. A.; Schneider, G. ModlAMP: Python for Antimicrobial

Peptides. *Bioinformatics* **2017**, *33* (17), 2753–2755.

https://doi.org/10.1093/bioinformatics/btx285.

(23) Vaswani, A.; Shazeer, N.; Parmar, N.; Uszkoreit, J.; Jones, L.; Gomez, A. N.; Kaiser, Ł.;

Polosukin, I. Attention Is All You Need. In *NIPS'17: Proceedings of the 31st International*

Conference on Neural Information Processing Systems; Long Beach, USA, 2017; pp 6000–

6010. https://doi.org/10.5555/3295222.3295349.

(24) Vig, J. A Multiscale Visualization of Attention in the Transformer Model. In *Proceedings of*

the 57th Annual Meeting of the Association for Computational Linguistics: System

Demonstrations; Association for Computational Linguistics: Florence, Italy, 2019; pp 37–42.

https://doi.org/10.18653/v1/P19-3007.

(25) Timmons, P. B.; Hewage, C. M. APPTEST Is a Novel Protocol for the Automatic Prediction

of Peptide Tertiary Structures. *Brief. Bioinform.* **2021**, *22* (6), bbab308.

https://doi.org/10.1093/bib/bbab308.

(26) Jumper, J.; Evans, R.; Pritzel, A.; Green, T.; Figurnov, M.; Ronneberger, O.;

Tunyasuvunakool, K.; Bates, R.; Žídek, A.; Potapenko, A.; Bridgland, A.; Meyer, C.; Kohl, S.

A. A.; Ballard, A. J.; Cowie, A.; Romera-Paredes, B.; Nikolov, S.; Jain, R.; Adler, J.; Back, T.;

Petersen, S.; Reiman, D.; Clancy, E.; Zielinski, M.; Steinegger, M.; Pacholska, M.;

Berghammer, T.; Bodenstein, S.; Silver, D.; Vinyals, O.; Senior, A. W.; Kavukcuoglu, K.; Kohli, P.; Hassabis, D. Highly Accurate Protein Structure Prediction with AlphaFold. *Nature* **2021**, *596* (7873), 583–589. https://doi.org/10.1038/s41586-021-03819-2.

(27) Guan, C.; Iwatani, S.; Xing, X.; Yamamoto, N. Strategic Preparations of DPP-IV Inhibitory Peptides from Val-Pro-Xaa and Ile-Pro-Xaa Peptide Mixtures. *Int. J. Pept. Res. Ther.* **2021**, *27* (1), 735–743. https://doi.org/10.1007/s10989-020-10122-7.

(28) Xu, X.; Yan, C.; Zou, X. MDockPeP: An *Ab□initio* Protein–Peptide Docking Server. *J. Comput. Chem.* **2018**, *39* (28), 2409–2413. https://doi.org/10.1002/jcc.25555.

(29) Ji, Y.; Zhou, Z.; Liu, H.; Davuluri, R. V. DNABERT: Pre-Trained Bidirectional Encoder Representations from Transformers Model for DNA-Language in Genome. *Bioinformatics* **2021**, *37* (15), 2112–2120. https://doi.org/10.1093/bioinformatics/btab083.

(30) Zhang, Y.; Lin, J.; Zhao, L.; Zeng, X.; Liu, X. A Novel Antibacterial Peptide Recognition Algorithm Based on BERT. *Brief. Bioinform.* **2021**, *22* (6), bbab200. https://doi.org/10.1093/bib/bbab200.

(31) Devlin, J.; Chang, M.-W.; Lee, K.; Toutanova, K. BERT: Pre-Training of Deep Bidirectional Transformers for Language Understanding. In *Proceedings of the 2019 Conference of the North*; Association for Computational Linguistics: Minneapolis, Minnesota, 2019; pp 4171–4186. https://doi.org/10.18653/v1/N19-1423.

(32) Elnaggar, A.; Heinzinger, M.; Dallago, C.; Rehawi, G.; Wang, Y.; Jones, L.; Gibbs, T.; Feher, T.; Angerer, C.; Steinegger, M.; Bhowmik, D.; Rost, B. ProtTrans: Towards Cracking the Language of Lifes Code Through Self-Supervised Deep Learning and High Performance Computing. *IEEE Trans. Pattern Anal. Mach. Intell.* **2021**, 1–1. https://doi.org/10.1109/TPAMI.2021.3095381.

1   **Table of Contents graphic**