Modeled grid cells aligned by a flexible attractor

Sabrina Benas[1]*, Ximena Fernandez[2]* and Emilio Kropff[1]

[1] Leloir Institute – IIBBA/CONICET, Buenos Aires, Argentina

[2] Department of Mathematics, Durham University, UK

*These authors contributed equally.

ABSTRACT

Entorhinal grid cells implement a spatial code with hexagonal periodicity, signaling the position of the animal within an environment. Grid maps of cells belonging to the same module share spacing and orientation, only differing in relative two-dimensional spatial phase, which could result from their participation in a two-dimensional attractor. Such an architecture, however, has the drawbacks of being complex to construct and rigid, allowing no degrees of freedom for grid cells to deviate from the hexagonal pattern, as happens under a variety of experimental manipulations. Here we show that a simpler one-dimensional architecture is enough to align grid cells equally well. Using topological data analysis, we show that the resulting population activity is a sample of a torus, while the ensemble of maps preserves features of the network architecture. The flexibility of this low dimensional attractor allows it to negotiate with the feedforward inputs the geometry of the representation manifold, rather than imposing it, finding a number of equally viable configurations. Our results represent a proof of principle against the intuition that the architecture and the representation manifold of an attractor are the same topological object, with implications to the study of attractor networks across the brain.

INTRODUCTION

Grid cells in the medial entorhinal cortex and other brain areas provide a representation of the spatial environment navigated by an animal, through maps of hexagonal periodicity that have been compared to a system of Cartesian axes (Buzsáki & Moser, 2013; Fyhn, Molden, Witter, Moser, & Moser, 2004; Moser, Kropff, & Moser, 2008). While different mechanisms have been proposed as the basis to make a neuron develop a collection of responsive fields distributed in space with hexagonal periodicity, the alignment of axes of symmetry between neighboring, co-modular neurons in most computational models occurs through direct excitatory communication between them (Burak & Fiete, 2009; Burgess, Barry, & O'keefe, 2007; Couey et al., 2013; Kropff & Treves, 2008). In general, the network responsible for this communication can be thought of as a two-dimensional continuous attractor (Knierim & Zhang, 2012).

Attractor networks are among the clearest examples of unsupervised self-organization in the brain. Point-like attractors emerge naturally in a network with dense recurrent connectivity

equipped with Hebbian plasticity, and can be used to store and retrieve discrete pieces of information (Hopfield, 1982). If a number of point-like attractors is set close enough to each other along some manifold, a continuous attractor emerges. One-dimensional ring attractors have been used to model head direction cells (Redish, Elga, & Touretzky, 1996; Zhang, 1996), while two dimensional attractors have been used to model coherent maps of space such as those of place cells or grid cells (Battaglia & Treves, 1998; Burak & Fiete, 2009; Gardner et al., 2022). A common underlying assumption is that the dimensionality of the network architecture mimics that of the space that is being represented, which explains why the word 'dimensionality' applied to an attractor is indistinctly used to refer to one or the other. However, the network activity does not only depend on recurrent connections, but also on inputs, and the potential interplay between these two sources has so far received little attention. Grid cells have been modeled using two-dimensional attractors because they represent two-dimensional space, but a number of reasons call for the exploration of alternatives. First, grid cells are also capable of representing one dimensional variables such as space, time or the frequency of a sound, or three dimensional space, in which case they exhibit poor to no spatial periodicity (Aronov, Nevers, & Tank, 2017; Ginosar et al., 2021; Grieves et al., 2021; Hafting, Fyhn, Bonnevie, Moser, & Moser, 2008; Kraus et al., 2015; Yoon, Lewallen, Kinkhabwala, Tank, & Fiete, 2016). Second, two dimensional attractors impose a rather rigid constraint on the activity of neurons, but grid maps can suffer global or local modifications in response to different experimental manipulations (Barry, Hayman, Burgess, & Jeffery, 2007; Boccara, Nardin, Stella, O'Neill, & Csicsvari, 2019; Butler, Hardcastle, & Giocomo, 2019; Krupic, Bauza, Burton, Barry, & O'Keefe, 2015; Krupic, Bauza, Burton, & O'Keefe, 2018; Sanguinetti-Scheck & Brecht, 2020; Yoon et al., 2013). Third, the mechanisms behind the formation and maintenance of such a complex and fine-tuned network are far from understood, and theoretical proposals tend to involve as a prerequisite an independent functional representation of two-dimensional space to serve as a tutor (Si & Treves, 2013; Widloski & Fiete, 2014). Fourth, a recent experiment shows that when animals are trained to navigate deprived from sensory and vestibular feedback, entorhinal cells tend to develop a surprising ring (1D) rather than toroidal (2D) population dynamic (Gonzalo Cogno et al., 2022).

Here we explore the possibility that grid cells are aligned by simpler, one-dimensional attractors, which, as we show, have the potential to flexibly organize the population activity into a configuration that is negotiated with the inputs rather than pre-defined. Crucially, we show for the first time with mathematical rigor that the architecture and representational space of an attractor network can be two different topological objects. This proof of principle broadens the spectrum of potential candidates for the recurrent architecture interconnecting grid cells, opening the possibility of variability along animal development and maturation, or across the multiple brain areas where grid cells have been described.

RESULTS

Grid maps aligned by a one-dimensional attractor

To understand if grid maps can be aligned by an architecture of excitatory recurrent collateral connections simpler than a two-dimensional attractor, we trained a model in which grid maps are obtained from spatial inputs through self-organization (Kropff & Treves, 2008). In this model, a layer of spatially stable inputs projects through feedforward connections equipped with Hebbian plasticity to a layer of grid cells (Fig. 1a). Two factors, all-to-all inhibition and adaptation, force neurons in the grid cell layer to take turns to get activated. This promotes the specialization of entorhinal cells, which only strengthen their feedforward synapses to co-active inputs, different across cells. As a virtual animal navigates an open-field environment, modeled entorhinal cells self-organize, acquiring maps with hexagonal symmetry as a result of this Hebbian sculpting of the feedforward connectivity matrix. Previous work has shown that these maps are not naturally aligned unless excitatory recurrent collaterals are included (Kropff & Treves, 2008; Si & Treves, 2013).

We performed 100 simulations of a simplified version of this self-organizing network (Methods), including 225 input cells and $N_{EC} = 100$ grid cells, in two otherwise identical setups (Fig. 1b). In the first scenario (2D), we added to the grid cell layer a classical architecture of recurrent collateral connections shaped as a torus. In the second scenario (1D), we used instead a much simpler ring attractor architecture. At the end of the learning process, maps in both types of simulation had hexagonal symmetry (Fig. 1c). The average of autocorrelograms also had hexagonal symmetry, indicating that individual maps within the network shared spacing and orientation (Fig. 1d), which was further confirmed by the clustering into 6 well defined groups of first order autocorrelogram maxima for the pool of all cells (Fig. 1e). This was true not only for the 2D architecture, which was constructed in an *ad hoc* way to align grid maps, but also for the much simpler 1D architecture.

Figure 1 - Attractors with a 2D or 1D architecture align grid maps. a, Schematics of the network model, including an input layer with place cell-like activity (purple), feedforward all-to-all connections with Hebbian plasticity and a grid cell layer (green) with global inhibition and a set of excitatory recurrent collaterals of fixed structure. **b**, Schematics of the recurrent connectivity from a given cell (orange) to its neighbors (green) in a 2D (top) or 1D (bottom) setup. **c**, Representative examples of maps belonging to the same 2D (top) or 1D (bottom) network at the end of training. **d**, Average of all autocorrelograms in the same two simulations, highlighting the 6 maxima around the center (black circles). **e**, Superposition of the 6 maxima around the center (as in **d**) for all individual autocorrelograms in the same two simulations.

For a quantitative comparison of grid cell properties, we incorporated two additional conditions, one with a stripe-like linear attractor, with no periodic boundaries ($1D_L$), and one with no recurrent collaterals (No), in setups otherwise identical to those of 1D and 2D. We compared across conditions the hexagonality of maps (through a gridness index), the spacing between neighboring fields and the angular spread in axes of symmetry across the population, indicative of alignment (Fig. 2a). In general, we found marked differences only between the No condition and the other three. Gridness was highest for 1D, followed closely by 2D and $1D_L$, while the No condition exhibited distinctly lower values. Spacing and spread were lowest for the 2D condition, followed by a small margin by 1D and $1D_L$, with the No condition again presenting the largest differences with the rest. These results suggest that attractor connectivity of all investigated types not only aligns grid cells similarly but also has the effect of lowering the spacing of maps. To visualize how individual maps varied across categories, we plotted the distribution of pooled maxima (as in Fig. 1e) relative to the main axis of the corresponding autocorrelogram, i.e. the one presenting the highest correlation value (Fig. 2b).

To address differences in the self-organization dynamics, we next inspected maps along the learning process (Fig. 2c). We found that the mean gridness exhibited by individual cells initially increased at a similar pace for all conditions, saturating early in this process only for the No condition. Further increase in gridness was an emergent property only allowed by attractor dynamics, which in the 2D condition took a slightly slower start compensated later by an elbow toward plateauing behavior at higher gridness values. For simulations with attractors, population gridness (or the gridness of the average autocorrelogram), while always lower than mean individual gridness, increased steadily, with 2D exhibiting slightly higher values most of the time. In the No condition, no substantial increase was observed in the population gridness despite a parallel increase in individual gridness, indicative of the absence of alignment between maps. The asymptotic behavior for both individual and population gridness was similar for all conditions with attractors. Individual spacing in maps with attractors showed a decrease throughout most of the learning process, more pronounced in the 2D condition, while the No condition evidenced a steady increase toward an asymptote. A combination of progressive increase in gridness and

decrease in spacing has been observed in animals familiarizing with a novel environment (Barry et al., 2007). Our results, although only qualitatively exhibiting similar trends, point to the efficiency of excitatory collaterals in imposing constraints to the population activity as a possible mechanism. This compression of maps resulting from experience was less evident in the mean population spacing, obtained from average autocorrelograms, indicating that, at least in our simulations, this phenomenon has a strong driver in the deviation of individual cells from the coordinated population behavior, which would explain why the contraction is more marked for the most rigid constraint (2D). Despite these subtle differences, gridness, spacing and spread looked overall very similar across conditions with attractors, and markedly different in the No condition.

Figure 2 - Quantification of the alignment and contraction of grid maps by different attractor architectures. a, Distribution of gridness (left), spacing (center) and spread (right) at the end of the learning process across conditions (quartiles; identical simulations except for the architecture of recurrent collaterals). **b,** Smoothed distribution of maxima relative to the main axis of the corresponding autocorrelogram. **c,** Mean evolution of gridness (top) and spacing (bottom) in transient maps along the learning process, calculated from individual (left) or average (right) autocorrelograms.

Toroidal topology of the population activity space

Classical features such as gridness and spacing looked similar in maps obtained with different attractor geometry. We next asked, more generally, if the topology of the population activity was also the same for different conditions. Every pixel in the arena where the virtual animal runs is

associated with a vector containing the mean activity of each neuron in that position. These vectors, which are the columns of the population matrix P (where the element P_{ij} is the mean activity of the i^{th} neuron in the j^{th} pixel), form a point cloud of size equal to the number of pixels in a space of dimension N_{EC} (the number of grid cells). It is commonly understood, given the symmetry of grid maps, that this cloud should be a sample of a low dimensional structure represented by a twisted torus and embedded in a high dimensional space (Knierim & Zhang, 2012) (see Methods; Fig. S1), as experimental data suggests (Gardner et al., 2022).

The topology of an object that a point cloud is a sample of can in some cases be completely determined through a series of methods in topological data analysis. The theorem of classification of closed surfaces states that if a geometric object (i) is locally two-dimensional, (ii) has neither boundary nor singularities and (iii) is orientable, then its topology is determined by its homology (Hatcher, 2002) (see Methods).

To understand whether and when this is true in our simulations, we first studied the local dimension of the population activity space (i) for the different conditions. To avoid irregularities sometimes found at the perimeter of the environment, we used for all further analyses the 60 cm wide central square of each 1 m wide map. For every data point, we extracted the principal components of a local neighborhood around it (Fig. S1). We defined the local dimension at this point as the number of principal components for which an elbow in the rate of explained variance in the local neighborhood was found. In all conditions, more than 90 % of the data points had a local dimensionality equal to 2, with eventual outliers that had some impact on the mean but not on the median (Fig. 3a). To understand if these deviations were the result of noise or, in contrast, had a structure in the physical space, we next plotted individual maps of local dimensionality (Fig. 3b) and their average across simulations of the same condition (Fig. 3c). We only observed a structure in the No condition, where mean values close to 3 were concentrated at the corners of the reduced map. These results suggest that the population activity in all conditions with attractors is concentrated around a structure with a local dimension of 2.

Next, to understand if the data had boundary or singularities (ii), we studied the local homology of the underlying space by estimating the first Betti number β_1 in an annulus neighborhood around each data point (Stolz, Tanner, Harrington, & Nanda, 2020) (Fig. 3d). In a sample of a locally 2-dimensional manifold with neither boundary nor singularities, the data inside the annulus neighborhood is expected to form a ring, with local $\beta_1 = 1$, while points in the boundary are characterized by $\beta_1 = 0$ and singularities by $\beta_1 > 1$ (Fig. S1d). We observed that most of the data points had $\beta_1 = 1$, which was the case for more than 90 % of data in each of the conditions with attractors and for 70 % of the data in the No condition. The No condition had not only the lowest fraction of data with $\beta_1 = 1$, but also the lowest deviation in the distribution, pointing to a systematic decrease in β_1. This could be explained by examining individual maps of local β_1 (Fig. 3e) and averages across simulations (Fig. 3f). The conditions with attractors exhibited no structure in eventual deviations from $\beta_1 = 1$, but the average for the No condition had a value

$\beta_1 = 0$ in the pixels close to the perimeter of the reduced map, indicating a (non-empty) boundary set in the population activity.

Put together, these results suggest that the population activity for simulations with attractors is locally 2-dimensional, without boundary or singularities, forming a closed surface. In contrast, data clouds in the No condition do not meet the first two conditions of the theorem of classification of closed surfaces, and are compatible with a two-dimensional sheet exhibiting a boundary along the edge of the space selected for analysis.

Figure 3 - The population activity in all attractor conditions is locally 2-dimensional, with no boundary or singularities. a, Distribution across conditions of the fraction of the data with local dimensionality of 2 (quartiles). **b**, Distribution of local dimensionality across physical space in representative examples of 1D and 2D conditions. **c**, Average distribution of local dimensionality for all conditions (same color code as in **b**). **d-f**, As **a-c** for but exploring deviations of the local homology H_1 from a value of 1, the value expected away from borders and singularities.

We next studied the orientability (iii) of the population activity space for the conditions with attractors. For each simulation we obtained and compared persistence diagrams in Z_2 and Z_3. The pooled distribution of such diagrams and the averages across 100 simulations of each type (Methods) were almost identical for conditions 1D, 2D (Figs. 4a,b) and $1D_L$ (Fig. S2), indicating that the population activity in all cases is an orientable manifold.

Given that for simulations with attractors the three conditions posed by the theorem of classification of closed surfaces were met, we were able to conclude that the topology of the population activity is determined by its Betti numbers. From the average diagrams for all

conditions with attractors, Betti numbers could be qualitatively estimated as those of a torus: β_0 = 1, β_1 = 2 and β_2 = 1 (Fig. 4a). This was the case not only for average of persistence diagrams, but also for most of the individual simulations, as shown in the plots of the distribution across simulations of the difference in lifetime of consecutive generators ordered from largest to smallest (Fig. 4c). When quantifying the Betti numbers for individual simulations using a common cutoff value (Methods), 82 (out of 100) were classified as [1, 2, 1] in the 1D condition and 76 in the 2D condition (Fig. 4d), with small deviations compatible with a noisy scenario for the rest of the simulations.

In summary, our analyses show that different attractor architectures (torus, ring, stripe) similarly constrain the population activity into a torus embedded in a high dimensional space. This is not surprising for the 2D condition, where the architecture has itself the topology of a torus, but is an unprecedented result in the case of the 1D and $1D_L$ conditions, given that these simpler attractors were not tailored to represent two-dimensional neighboring relations.

Figure 4 - For 1D and 2D architectures, the population activity is an orientable manifold with the homology of torus. a, Smoothed density of pooled data (colored areas) and average across simulations (circles) of persistence diagrams with coefficients in Z_2 for H_0 (grey), H_1 (blue) and H_2 (red) corresponding to simulations in the 1D (top) and 2D (bottom) conditions. **b**, As **a** but with coefficients in Z_3. Similarity with **a** implies that population activity lies within an orientable surface. **c**, Distribution across simulations of lifetime difference between consecutive generators ordered for each simulation from longest to shortest lifetime for 1D (left) and 2D (right). The position of maxima coincides with Betti numbers. **d**, Pie plot and table indicating the number of simulations (out of 100 in each condition) classified according to their Betti numbers using common cutoff values.

Features of network architecture in the spatial maps

Our analyses showed that all conditions with attractors had a population activity with the topology of a torus, irrespective of the architecture of recurrent connections. We next asked if similar tools could be used to qualitatively unveil differences between conditions, following the intuition that the network architecture could perhaps be reflected in the geometry of map similarity relationships across neurons. We computed Betti numbers for the point cloud given by spatial maps of individual neurons, represented by a set of N_{EC} = 100 points (the number of neurons) in a 625-dimensional space (the number of pixels in the reduced map) (Fig. 5). This is equivalent to what was done in the previous section, but this time with the transpose of the matrix P.

For the 2D condition, the mean diagram could be described as having the Betti numbers of a torus [1,2,1], which was also apparent in the difference between consecutive ordered lifetimes (Fig. 5a,b). However, in individual persistence diagrams only 27 simulations had Betti numbers [1,2,1], while 69 had Betti numbers [1,2,0] where the cavity could not be correctly identified (Fig. 5c). The reason for this discrepancy, or the failure to find the cavity in individual diagrams, is possibly related to the low number of datapoints used in this analysis (100 vs. 625 in the previous case), taking the signal-to-noise ratio close to the limit of no detection. In contrast, 1D simulations had an average persistence diagram similar to the majority of individual diagrams (86 %), characterized by the Betti numbers of a ring [1,1,0], while for $1D_L$ simulations the average diagram and 97 % of individual diagrams had Betti numbers [1,0,0] compatible with a stripe.

In summary, the analysis of the matrix P showed that all conditions with attractors had a population activity embedded in a torus, while the same analysis applied to its transpose showed qualitative differences across conditions, where often the homology recapitulated that of the architecture of recurrent connections.

Figure 5 – Features of the attractor architecture observed in the persistent homology of neural activity. a, From top to bottom, diagrams as in Figure 4a but for the point cloud formed by the collection of individual maps, in conditions 1D, 2D and $1D_L$. Each panel shows smoothed density of pooled data (colored areas) and average (circles) persistence diagrams for H_0 (gray), H_1 (blue) and H_2 (red) with coefficients in Z_2. **b**, As in Figure 4c, distribution of the difference between consecutive generators ordered for each simulation from longest to shortest lifetime. **c**, Pie plots showing the percentage of simulations in which each combination of Betti numbers was found.

Flexibility of one-dimensional attractors

Given that one-dimensional attractors are not constructed in an *ad hoc* way to guarantee the correct organization of the population activity into a pre-defined configuration, we next asked what kind of geometrical arrangement was found by our self-organizing model to allow covering two-dimensional space with a one-dimensional arrangement of neurons. To visualize the population activity in space, we colored neurons in the 1D ring attractor according to hue, so that connected neurons along the ring were assigned similar colors. We then assigned to each pixel in the virtual space the color that best described the mean population activity associated with it. This allowed us to plot for each simulation a map in which color represented the mean population activity (Fig. 6a). While all individual colors in these maps had hexagonal periodicity, as expected from a population of aligned grid maps, the geometry of the attractor layout in physical space allowed for a classification into 4 orders (O_0 to O_3) with different prevalence (Fig. 6b). A way to understand these configurations is to imagine a cycle along the attractor. The cycle begins and ends in the same color, but since in physical space any given color is constrained to have hexagonal periodicity, the end has to lie either in the same position as the beginning (O_0) or

in an n-order neighboring field (in our case n = 1 to 3; Fig. 6c). This conceptualization implies that, although we only found 4 configurations for aligning grid cells with a 1D attractor, the constraint imposed by hexagonal symmetry is compatible with a countably infinite number of them (as many as orders of neighbors in a hexagonal grid), provided attractors are able to stretch enough in physical space. We speculate that the number of neurons in the grid cell layer (N_{EC}) could play a critical role in determining to what extent the attractor can stretch and which configurations can be achieved in practice by a given network. Simulations of the $1D_L$ condition were classified into categories following the same logic, by assessing the distance between the two extremes of the attractor (colored black and white) in terms of neighboring order in a hexagonal grid (Figs. 6b and 6d).

These results show that the weak constraint imposed by one-dimensional flexible attractors allows for many possible solutions to co-exist as local minima of the self-organization energy landscape.

Figure 6 - Multiple configurations for the alignment of grid maps by one-dimensional attractors. **a**, Top: Population map for 4 representative examples of 1D simulations with increasing configuration order (indicated) from left to right. Color indicates the region of the ring attractor best describing the mean population activity at each position. Schematics of some of the frontiers, defined by abrupt changes in color (black), and hexagonal tiles maximally coinciding with these frontiers (semi-transparent white) are included for visualization purposes. Bottom: Schematic representation of the order of the solution as the minimum number of colors traversing the perimeter of the hexagonal tile or, equivalently, the minimum number of hexagonal tiles whose perimeter is traversed by one cycle of the attractor. **b**, Table indicating the number of simulations out of 100 in which each configuration order was found. **c**, Schematic

representation of the ring attractor extending in space from a starting point to different order neighbors in a hexagonal arrangement. **d**, As **a** but for the 1D$_L$ condition. Gray scale emphasizes the lack of connections between extremes of the stripe attractor.

Visualization of the twisted torus

Dimensionality reduction techniques are a popular way of visualizing high dimensional data, such as the population activity in our simulations. It should be noted, however, that in general they provide no guarantee of preserving the topology of the data cloud in the original high dimensional space. For our data, three-dimensional Isomap projections (Tenenbaum, Silva, & Langford, 2000) allowed for the visualization of the twisted torus in two distinct ways for all conditions with attractors. In many simulations, the three-dimensional reduction of the population activity looked like a tetrahedron (Fig. 7a). If data were grouped using k-means clustering (k = 4) in the reduced Isomap space and colored accordingly, the representation of the same data in physical space took the form of a four-color checkerboard. The minimal tile containing all four colors was a square in which one pair of opposite sides had simple periodicity while the other had a periodicity with a 180° twist, which is the basic representation for the twisted torus (Fig. S1). Other times the same reduction technique, with identical parameters, produced directly a torus-like shape, squeezed at two opposite sides (Fig. 7b,c). While extreme solutions looked either like the tetrahedron or the torus, intermediate cases were also found which could not be clearly interpreted as one or the other. The fact that the same procedure produced so different visualizations calls for a cautious approach to interpreting the geometry of reduced data when using non-linear dimensionality reduction methods such as Isomap. This technique does not aim to preserve the global geometry of the original point cloud, but instead the relative distance between data points.

In summary, our results show that there are multiple ways in which continuous attractors can align grid cells, including simple architectures such as ring or stripe attractors. The resulting population activity is equivalent (homeomorphic), despite differences in the topology of the architecture or in projections obtained through dimensionality-reduction techniques.

Figure 7 - Two different visualizations of the twisted torus obtained with Isomap. a, Top: Representative examples of dimensionality reduction into a structure resembling a tetrahedron for different conditions (indicated). Data points are colored according to the distance to one of the four cluster centers obtained with k-means (each one close to tetrahedron vertices; k = 4). Bottom: Same data and color code but plotted in physical space. The white square indicates the minimal tile containing all colors, with correspondence between edges, indicated by arrows, matching the basic representation of the twisted torus. **b**, Representative examples of dimensionality reduction into a torus structure squeezed at two points, obtained in other simulations using identical Isomap parametrization. Hue (color) and value (from black to bright) indicate angular and radial cylindrical coordinates, respectively. **c**, For the same two examples (indicated), three dimensional renderings. To improve visualization of the torus cavity, color is only preserved for data falling along the corresponding dashed lines in **b**.

DISCUSSION

Our main result is that the alignment of hexagonal axes in a model of grid cells can result from interactions between neurons following a simple one-dimensional architecture, not

constructed *ad hoc* for representation of two-dimensional spaces. This possibility has not been assessed before in modeling because a common assumption is that recurrent collateral architecture perfectly defines the geometry of the manifold that an attractor constrains the population activity to be embedded in. We show for the first time that this seemingly reasonable assumption is wrong, providing two counter-examples in which the representational space is a torus but the architecture, either a ring or a stripe, has a different topology and even lower dimensionality. Crucially, if the attractor is not active, grid maps obtained under otherwise identical conditions exhibit markedly lower levels of hexagonal symmetry and do not align, failing to constrain the population activity into a torus. Our results open the way to considering the potential of simple flexible attractors for a wide spectrum of modeling applications, given their capability of enacting on the population activity a negotiated constraint, as opposed to rigid attractors with no such degrees of freedom.

Grid cells were originally described in superficial layers of the medial entorhinal cortex, but were later found also in other entorhinal layers and even in an increasing number of other brain areas (Boccara et al., 2010; Long, Deng, Cai, Chen, & Zhang, 2021; Long & Zhang, 2021). Our work points to the possibility that organizational principles simpler than previously thought could act in some of these areas to structure grid cell population activity. In addition, given that grid cell properties change substantially during the early life of rodents (Langston et al., 2010; Wills, Cacucci, Burgess, & O'Keefe, 2010), flexible attractors could be taken into account as a potential intermediate stage toward the formation of more complex architectures. Advantages of flexible attractors are versatility and simplicity in network design. Grid cells, for example, represent multiple geometries with individual characteristics in each case. Two-dimensional maps of familiar environments are highly symmetric and periodic, but this is not the case for other dimensionalities. In one- and three-dimensional spatial tasks they exhibit multiple fields, as they do in two-dimensional navigation, but with larger and more irregular spacing (Ginosar et al., 2021; Grieves et al., 2021; Hafting et al., 2008; Yoon et al., 2016). In other one-dimensional tasks, involving the representation of frequency of a sound or time, they much more often develop single response fields (Aronov et al., 2017; Kraus et al., 2015). To properly model this collection of scenarios with rigid attractors, one should consider a number of them embedded on the same network architecture, each specialized for a single purpose, and a mechanism to select the attractor best suited for every situation. Alternatively, the same could perhaps be achieved with a single architectonic principle. One-dimensional attractors are simple enough to emerge independently of experience, as suggested by coherent head direction cells in rats prior to eye-opening (Bjerknes, Langston, Kruge, Moser, & Moser, 2015) or internally generated sequences in the hippocampus (Pastalkova, Itskov, Amarasingham, & Buzsaki, 2008). Future computational explorations should include a wider range of architectures to assess whether even simpler configurations than the ones used here, such as a collection of short fragmented sequences with

minimal deviation from a random architecture (Rajan, Harvey, & Tank, 2016), could align grid cells in a similar way.

Most grid cell models are focused on path integration, or the capacity of spatial maps to persist in the absence of spatial inputs based on self-motion information (Burak & Fiete, 2009; Burgess et al., 2007; Widloski & Fiete, 2014). Experiments in which animals navigate in the dark support this functionality for hippocampal and entorhinal maps, and it has been recently shown that the path integrator can be recalibrated in an almost online fashion (Jayakumar et al., 2019). However, although from a theoretical perspective grid cells are ideal candidates to implement path integration, the involvement of some or all grid cells in this operation still needs to find direct experimental proof. In contrast, a growing corpus of evidence suggests that grid cells can exhibit behaviors that deviate from pure path integration. This includes local and global distortions of the two-dimensional grid map in response to a variety of experimental manipulations (Barry et al., 2007; Boccara et al., 2019; Butler et al., 2019; Krupic et al., 2015; Krupic et al., 2018; Sanguinetti-Scheck & Brecht, 2020), as well as the progressive refinement in symmetry and decrease in spacing observed along days of familiarization to a novel environment (Barry, Ginzberg, O'Keefe, & Burgess, 2012; Yoon et al., 2013). In our model, this last result could be understood as a consequence of the interplay between feedforward and collateral inputs, where the efficiency of the attractor constraint progressively increases as feedforward synaptic weights are modified and individual deviation from the collective behavior decreases. More generally, understanding how this heterogeneous set of experimental results could emerge from interactions between path integration and landmark navigation is a challenge for future work in which the concept of flexible attractors could prove useful. Path integration is an operation that needs to be computed in the direction of movement, which is at a given instant a one-dimensional space. This reduction of the two-dimensional problem to a one-dimensional one underlies many path integration models, which can be thought of as employing several overlapping two-dimensional attractors, each specialized in one direction of movement, to achieve path integration in all directions (Burak & Fiete, 2009), a task that one-dimensional attractors might be naturally suited for without loss of flexibility.

In a recent experiment, mice were trained to run head-fixed at a free pace on a rotating wheel, in complete darkness and with no other sensory or behavioral feedback (Gonzalo Cogno et al., 2022). It could be expected that in such a situation the population activity deprived of inputs is influenced to a greater extent by its internal dynamics, offering a window, however imperfect, into the architecture of the attractor. The experimenters observed that the entorhinal population dynamic engaged in cycles, with a period of tens of seconds to minutes. These cycles, naturally occurring here but not in other areas of the brain, point to the possibility of one-dimensional attractor arrangements, modelled by either our 1D or $1D_L$ conditions, as a prevailing organizational principle of the entorhinal cortex. Future efforts should focus on whether or not a

relationship exists between the organization of grid cells within entorhinal cycles and their relative spatial phases in two-dimensional open field experiments, contrasting the population map with configurations shown in Figure 6.

Given that many aspects of behavior are intrinsically low-dimensional, topological data analysis can be extremely useful to understand both the architecture and the representational manifold of different brain networks. As persistent homology is being increasingly used to describe the activity of neural populations, it is important to note that it does not univocally determine geometry. We have implemented it here in the context of the theorem of classification of closed surfaces, which adds mathematical rigor to an otherwise qualitative characterization. Unfortunately, not all topological objects can be classified in this way. A greater involvement of topologists in the study of the brain would help to establish reasonable criteria and develop tools to understand neural datasets of increasing complexity.

Our work shows that attractor networks have capabilities that so far have not been exploited in modeling. Addressing the dimensionality of an attractor network, as is common practice to describe it, becomes challenging from the perspective of our results, given that a single network architecture can organize population activity into manifolds of diverse geometry, and the same geometry can be achieved by architectures of different dimensionality. This bridging across dimensions is analogous to proposals regarding the semantization of episodic memories in the hippocampus (Buzsáki, 2005), and as implemented by flexible attractors could shed light on the way we map a world of unknown complexity through our limited one-dimensional experience.

ACKNOWLEDGEMENTS

This work was supported by Human Frontiers Science Program grant RGY0072/2018 (E.K.).

METHODS

The model is inspired in a previous work that describes extensively the mechanism and reasons why Hebbian learning sculpts hexagonal maps through self-organization (Kropff & Treves, 2008). We here describe the main ingredients of the model and small modifications aimed to make it simpler and computationally less expensive.

The network has an input layer of N_I = 225 neurons projecting to a layer of N_{EC} = 100 cells. While the model works with arbitrary spatially stable inputs (Kropff & Treves, 2008), for simplicity we use place cell like inputs. Input cells had Gaussian response fields with a standard deviation of 5.4 cm centered at preferred positions uniformly distributed across the 1 m arena.

The total field h received by grid cell i at time t is given by two terms. The first one includes the contributions of the feedforward connections from input cells. The second one includes recurrent contributions

$$h_i(t) = \sum_{j=1}^{N_I} W_{i,j}^I \, r_j^I(t) + \sum_{k=1}^{N_{EC}} W_{i,k}^{EC} \, r_k^{EC}(t),$$

where $r_j^I(t)$ and $r_k^{EC}(t)$ are the firing rate of input cell j and grid cell k, respectively. The feedforward synaptic weight matrix W^I is equipped with Hebbian plasticity, while for the purposes of this paper the recurrent synaptic weigh W^{EC} is fixed (see next section).

The field of the cell is inserted into a set of two equations with two internal variables, h_{act} and h_{inact} and a parameter β aimed to mimic adaptation or neural fatigue within the cell,

$$h_{act}(t) = h(t) - h_{inact}(t)$$
$$h_{inact}(t) = h_{inact}(t) + \beta h_{act}(t).$$

Once the value of h_{act} is obtained for all grid cells, a threshold linear transfer function with gain G is applied. A threshold T mimicking inhibition is established so that only the fraction A of cells with highest h_{act} values has non-zero firing rate, while a normalization, acting as an effective gain, ensures that Hebbian plasticity does not get stuck at the beginning of the learning process due to low post-synaptic activity. The activity of each cell is obtained as

$$r_i^{EC}(t+1) = G \frac{|h_{act}(t) - T|_{>0}}{\langle |h_{act}(t) - T|_{>0} \rangle},$$

where the operation $|\ldots|_{>0}$ represents a rectifying linear transformation and $\langle\ldots\rangle$ denotes averaging across all cells. This normalization is effectively equivalent to controlling the sparseness of the network (Kropff & Treves, 2008) but is much more efficient computationally.

The update of the feedforward synaptic weight $W_{i,j}^I$ is given by de Hebbian rule

$$W_{i,j}^I(t+1) = W_{i,j}^I(t) + \varepsilon \left(r_j^I(t) \, r_k^{EC}(t) - \overline{r_j^I r_k^{EC}} \right),$$

where ε is a learning parameter and the computationally efficient temporal average operation

$$\bar{r}(t+1) = \bar{r}(t)(1-\delta) + r(t)\delta$$

is used. Negative values of W^I are set to zero and the vector of all presynaptic weights entering a given postsynaptic grid cell is divided by its Euclidean norm to ensure that it remains inside a hypersphere.

In our hands, the condition 2D was the one with the greatest sensibility to model parameters. For this reason, they were fine-tuned using the 2D recurrent architecture, with the aim of being able to use the lowest possible number of cells and thus optimize the computational cost. This was achieved by reducing the grid cell layer to 100 cells, a number below which self-organization of the population activity into a torus ceased to be consistent. We noticed that including a greater number of neurons in the input layer had a substantial impact on the speed and stability of the learning process, which led us to include 225 input cells. Once the 2D architecture simulations were optimized, the other conditions were run using

the same values for all parameters and initial conditions, except for the parameters describing the recurrent collateral architecture itself. The following are some important model parameters. The first few ensure that the magnitude of recurrent and feedforward inputs is similar throughout the learning process.

- Gain for otherwise normalized recurrent inputs: 2.
- Gain for otherwise normalized feedforward inputs: 2.
- Peak value for r^I: 20.
- Gain G: 0.1
- Grid cells allowed to have non-zero activity at any given time: 60 %.
- Learning parameter ε: $5\ 10^{-4}$
- Adaptation parameter β: 0.04.
- Averaging parameter δ: 0.5
- Side of the square arena: 1 m.
- Input field standard deviation: 5.4 cm.
- Distance traveled in one simulation step: 0.6 cm.
- Variation in direction at each step: normal distribution with 0º mean and 17º s.d.
- Overall number of steps per simulation $2\ 10^7$.

Recurrent collateral architectures

Toroidal architecture

For the purpose of designing the 2D architecture of recurrent collaterals, each neuron in a given simulation was assigned a position, uniformly covering the virtual arena. The strength of connectivity between a given pair of cells k and l was set to depend on their relative position $\mathbf{x} = [x_k - x_l, y_k - y_l]$, through a function f($\mathbf{x}$) that was defined as the sum of three cosine functions in directions $\mathbf{k}_i$, 120⁰ and 240⁰ from each other, i.e. an ideal grid map (Kropff & Treves, 2008),

$$f(x) = 1 + \frac{2}{3}\sum_{i=1}^{3}\cos(k_i x)$$

The spacing of this imaginary grid map (inverse to the modulus of $\mathbf{k}$) could be varied along a wide range of values without noticeable consequences on the simulations. For simulations included in this paper it was arbitrarily set to 60 cm.

Ring architecture

For the 1D condition, neurons were uniformly distributed along an imaginary ring, spaced by 3.6⁰. The connection strength between any pair of neurons was defined as proportional to a 7.2⁰ standard deviation Gaussian function of the minimum angle between them.

Stripe architecture

For the 1D$_L$ condition, neurons were uniformly distributed along an imaginary stripe. The connection strength between any pair of neurons was defined as proportional to Gaussian function of the distance between them, with standard deviation equal to twice the distance between consecutive neurons.

Rate Maps

Mean rate for each pixel in space was obtained from the instantaneous rate of each neuron observed during visits to the pixel. To optimize memory usage, at any given time the pixel currently traversed by the rat was identified and its mean rate for each neuron j, m_j updated as

$$m_j = m_j (1 - \tau) + r_j(t)\tau$$

where r_j is the instantaneous firing rate and τ is 0.03. The rest of the pixels of the map were not modified at this step.

Autocorrelograms were obtained by correlating two copies of each map displaced relatively to one another in all directions and magnitudes. To reduce the absolute value close to the borders, where correlations can reach extreme values with poor statistical power, a 1 m circular hamming window was applied to each autocorrelogram. Mean population autocorrelograms were obtained by averaging the autocorrelogram across all neurons in a given simulation.

Quantification of grid properties

Spacing:

Autocorrelograms were interpolated to a Cartesian grid in polar coordinates, so that correlation could be analyzed for all angles at any fixed radius. Spacing was defined as the radius with maximal 6-period Fourier component modulation of the autocorrelation across angles.

Gridness:

For the radius that defined spacing, gridness was defined as the mean autocorrelation at the six 60-degree spaced maxima minus that at the six 60-degree spaced minima.

Angular spread:

For each cell in a given simulation, the six maxima around the center of the autocorrelogram were identified. A k-means clustering algorithm was applied to the pool of all maxima in the simulation (MATLAB *kmeans()* function, with k = 6, otherwise default parameters and 10 repetitions to avoid local minima). The spread was defined as the mean absolute angle difference between pairs of points belonging to the same cluster.

Metric Structure of the Population Activity

To study the topology of the population activity (Fig. 4), the central 60 cm of each map in a simulation was considered. The population activity thus determines point clouds of 625 points — the size of the arena, i.e., 25x25 — in $R^{N_{EC}}$, where N_{EC} = 100 is the number of simulated grid cells. For the purpose of capturing the intrinsic geometry of the underlying space determined by these point clouds, and to avoid the effects of the 'curse of dimensionality', we endowed each point cloud with an estimator of the *geodesic distance*. This estimator, known as the *kNN-distance*, is defined as the length of the shortest path along the *k-nearest neighbors graph*, a graph with an edge between every data point and each of its k-nearest neighbors with respect to the ambient Euclidean distance. We set the value k = 10 for all our analyses but similar results could be obtained for a range of similar values of k.

To obtain features of the network architecture (Fig. 5) the activity of each cell represents a vector in R^{625} with the average activity on each pixel of the arena. The simultaneous activity of all the cells in the module is a point cloud of size N that, we observed, shares features with the architecture of the underlying neural network. To study the connectivity patterns of the network, we endowed this point cloud with the metric structure given by the *correlation distance* between the vectors of spatial activity.

Persistent Homology

We aimed to robustly recover geometric information, such as the number of connected components, cycles and holes of different dimensions, from the simulated data. To do so we computed the *persistent homology* (Boissonnat, Chazal, & Yvinec, 2018; Edelsbrunner & Harer, 2008; Edelsbrunner, Letscher, & Zomorodian, 2000; Zomorodian & Carlsson, 2005) of each point cloud endowed with its respective metric structure. As output we obtained *persistence diagrams*, graphical representations of the evolution of the generators of the *homology groups* associated to each point cloud, for different parameter scales (Fig. S1c). Each generator is described as a point whose first coordinate represents its *birth* and the second coordinate, its *lifetime*. Generators with long lifetime indicate topological features, while the ones with short lifetime are linked to noise. In all cases, the lifetime of the only generator for H_0 was set to an arbitrary value to facilitate visualization, given that its value is infinite. To summarize the information of the persistent homology over *all* simulations, we computed both the average of the persistence diagrams as its *Frechet mean* (Mileyko, Mukherjee, & Harer, 2011; Turner, Mileyko, Mukherjee, & Harer, 2014), as well as the density associated with the distribution of points in the diagrams (Fig. 4).

All the computations of persistence diagrams, related to both the population activity and the cross-cell similarities, were performed with the Ripser package (Bauer, 2021), while the Frechet mean or barycenter of persistence diagrams was obtained using the corresponding library in GUDHI (Maria, Boissonnat, Glisse, & Yvinec, 2014).

Automated quantification of individual persistence diagrams

Betti numbers are typically assessed from persistence diagrams in a qualitative way. Profiting from the fact that we had 100 similar persistence diagrams for every condition, we designed an automated procedure to determine cutoff values for each homology group and condition. A histogram of lifetime with 100 bins between 0 and the maximum value was obtained for the pool of all cycles in all simulations belonging to the condition. The histogram was smoothed with a 3-bin standard deviation gaussian window. Locations of minima in this smoothed histogram were identified and the one representing the greatest fall from the previous maximum was set as the cutoff lifetime value. Persistence diagrams for individual simulations were analyzed by counting how many cycles had a lifetime greater than the corresponding cutoff value.

Local Principal Component Analysis

Local *Principal Component Analysis (PCA)* is a well-established procedure to detect the local dimension of point clouds (Fukunaga & Olsen, 1971). It is based on the popular method PCA of linear dimensionality reduction, applied to local k-nearest neighborhoods of each data point (Fig. S1b). We employed local neighborhoods of size k = 70 for all simulations of population activity with attractors and k = 20 for the ones in the No condition. These values were determined as the center of a range of k values with stable outcomes.

For every local neighborhood, we computed the evolution of the *rate of explained variance* after adding each principal component (in decreasing eigenvalue-order). An estimator of the local dimension at a point is the number of dimensions at which there is a drop off (or 'elbow') in the curve of explained variances (Fig S1b). For elbow detection we used the Python package kneed (Satopaa, Albrecht, Irwin, & Raghavan, 2011).

Local Persistent Homology

Persistent homology can also be used to capture the topological structure *around* each data point. Even though homology does not distinguish among local neighborhoods of different dimensions (and hence, it is not useful to identify local dimensions), it is an appropriate method to detect anomalies such as points in the *boundary* or *singularities*. The main idea is to identify

the shape of the region *surrounding* each point, by studying the persistent homology of an annular neighborhood (Stolz et al., 2020).

We defined the *annular local neighborhood* of a point x as the set of points in the point cloud (ordered according to the Euclidean distance to x) between the $k_1{}^{th}$ and the $k_2{}^{th}$ nearest neighbors, with k_1 = 50, k_2 = 100 for the simulations with attractor, and k_1 = 10 , k_2 = 30 for the ones in the No condition (Fig. S1d).

Orientability

Orientability is the geometric property that ensures a consistent local coordinate system in a manifold. In the special case of *closed* manifolds (compact connected manifolds without boundary) this homeomorphism invariant can be detected by its homology.

We computed the persistent persistence diagrams of the point clouds obtained from 100 simulations of the population activity of grid cells in all conditions, using coefficients in both Z_2 and Z_3 (Fig. S1e). A summary of the persistent homology over all the simulations (for every coefficient field) was presented via the Frechet mean and the density of the distribution of the generators in the persistent diagrams.

Notice that for *any* closed manifold M of dimension 2, $H_2(M, Z_2) \neq 0$. This is consistent with salient generator in the (Frechet mean) persistence diagram for H_2 that we can detect in all conditions with attractors (Fig. 4). We also observe that the Frechet mean of persistence diagrams remains unaltered after the change of coefficients from Z_2 to Z_3. This proves the orientability of the underlying surfaces in all cases. If the sample belonged to a non-orientable surface, the salient generator of the persistent diagram representing $H_2(M, Z_2)$ should disappear when compared with $H_2(M, Z_3)$ (Fig. S1e). This should also be accompanied by the disappearance of a salient generator of $H_1(M, Z_2)$ when contrasted with $H_1(M, Z_3)$. This phenomenon of simultaneous changes in homology is explained by the independence of the Euler characteristic on the choice of field of coefficients.

Dimensionality Reduction

Among the most popular techniques in manifold learning are the procedures for *dimensionality reduction*, that aim to project high-dimensional point clouds into a low-dimensional space while preserving some properties of the original data.

Isomap is a celebrated (non-linear) dimensionality reduction method that assumes the data is a sample of a low dimensional manifold embedded in a high dimensional Euclidean space. It reduces the dimensionality by mapping the original data into a lower dimensional Euclidean space while preserving geodesic distances on the manifold subjacent in the data. Since the intrinsic distance in the underlying manifold is unknown, it estimates the geodesic distance by

the kNN graph distance, where the parameter k represents the number of nearest neighbors used in the construction of the graph.

We performed Isomap projections of the population activity in all conditions 2D, 1D, $1D_L$ and No condition, with a parameter value of k = 10 (although comparable results are obtained for a range of similar values). We employed the method Isomap from the Python library sklearn.manifold.

We remark that, even though dimensionality reduction procedures may serve as a useful tool for data visualization and feature extraction as part of a machine learning pipeline, they do not provide guarantee a priori to preserve the topology of the underlying manifold, so they do not constitute in general a proof of structure of the original data neither an accurate preprocessing method for a subsequent rigorous geometric analysis.

Figure S1 – Methods in topological data analysis and examples. a, Basic representation of different geometries (indicated) and their corresponding Betti numbers. **b**, Local dimensionality of a sphere (i) and a subset of it (ii), computed by obtaining its local principal components (iii)

and finding and elbow on the rate of explained variance (iv). **c**, Left, top: Birth and death of a generator in H_1 (a cycle) for the same collection of datapoints and increasing radius. Left, bottom: barcode diagram indicating the birth and death of all generators. Right: Lifetime diagram indicating the length of bars in **b**, indicating relevant generators and noise. **d**, Local homology in different locations of a locally two-dimensional object. Deviations from $H_1 = 1$ can indicate borders ($H_1 = 0$) or singularities ($H_1 > 1$) as exemplified. **e**, Orientable (top, torus) and non-orientable (bottom, Klein bottle) objects with Betti numbers [1, 2, 1] in Z_2 but different Betti numbers in Z_3 (indicated).

Figure S2 – Persistent homology and Betti numbers for condition 1D_L. a, Smoothed density of pooled data (colored areas) and average across simulations (circles) of persistence diagrams with coefficients in Z_2 for H_0 (grey), H_1 (blue) and H_2 (red) corresponding to simulations in the $1D_L$ condition. **b**, as **a** but in Z_3. **c**, Distribution across simulations of lifetime difference between consecutive generators ordered for each simulation from longest to shortest lifetime. **d**, Pie plot and table indicating the number of simulations (out of 100) classified according to their Betti numbers.

References

Aronov, D., Nevers, R., & Tank, D. W. (2017). Mapping of a non-spatial dimension by the hippocampal–entorhinal circuit. *Nature, 543*(7647), 719-722.

Barry, C., Ginzberg, L. L., O'Keefe, J., & Burgess, N. (2012). Grid cell firing patterns signal environmental novelty by expansion. *Proceedings of the national academy of sciences, 109*(43), 17687-17692.

Barry, C., Hayman, R., Burgess, N., & Jeffery, K. J. (2007). Experience-dependent rescaling of entorhinal grids. *Nature neuroscience, 10*(6), 682-684.

Battaglia, F. P., & Treves, A. (1998). Attractor neural networks storing multiple space representations: a model for hippocampal place fields. *Physical Review E, 58*(6), 7738.

Bauer, U. (2021). Ripser: efficient computation of Vietoris–Rips persistence barcodes. *Journal of Applied and Computational Topology, 5*(3), 391-423.

Bjerknes, T. L., Langston, R. F., Kruge, I. U., Moser, E. I., & Moser, M.-B. (2015). Coherence among head direction cells before eye opening in rat pups. *Current Biology, 25*(1), 103-108.

Boccara, C. N., Nardin, M., Stella, F., O'Neill, J., & Csicsvari, J. (2019). The entorhinal cognitive map is attracted to goals. *Science, 363*(6434), 1443-1447.

Boccara, C. N., Sargolini, F., Thoresen, V. H., Solstad, T., Witter, M. P., Moser, E. I., & Moser, M.-B. (2010). Grid cells in pre-and parasubiculum. *Nature neuroscience, 13*(8), 987-994.

Boissonnat, J.-D., Chazal, F., & Yvinec, M. (2018). *Geometric and topological inference* (Vol. 57): Cambridge University Press.

Burak, Y., & Fiete, I. R. (2009). Accurate path integration in continuous attractor network models of grid cells. *PLoS computational biology, 5*(2), e1000291.

Burgess, N., Barry, C., & O'keefe, J. (2007). An oscillatory interference model of grid cell firing. *Hippocampus, 17*(9), 801-812.

Butler, W. N., Hardcastle, K., & Giocomo, L. M. (2019). Remembered reward locations restructure entorhinal spatial maps. *Science, 363*(6434), 1447-1452.

Buzsáki, G. (2005). Theta rhythm of navigation: link between path integration and landmark navigation, episodic and semantic memory. *Hippocampus, 15*(7), 827-840.

Buzsáki, G., & Moser, E. I. (2013). Memory, navigation and theta rhythm in the hippocampal-entorhinal system. *Nature neuroscience, 16*(2), 130-138.

Couey, J. J., Witoelar, A., Zhang, S.-J., Zheng, K., Ye, J., Dunn, B., . . . Roudi, Y. (2013). Recurrent inhibitory circuitry as a mechanism for grid formation. *Nature neuroscience, 16*(3), 318-324.

Edelsbrunner, H., & Harer, J. (2008). Persistent homology-a survey. *Contemporary mathematics, 453*, 257-282.

Edelsbrunner, H., Letscher, D., & Zomorodian, A. (2000). *Topological persistence and simplification.* Paper presented at the Proceedings 41st annual symposium on foundations of computer science.

Fukunaga, K., & Olsen, D. R. (1971). An algorithm for finding intrinsic dimensionality of data. *IEEE Transactions on Computers, 100*(2), 176-183.

Fyhn, M., Molden, S., Witter, M. P., Moser, E. I., & Moser, M.-B. (2004). Spatial representation in the entorhinal cortex. *Science*.

Gardner, R. J., Hermansen, E., Pachitariu, M., Burak, Y., Baas, N. A., Dunn, B. A., . . . Moser, E. I. (2022). Toroidal topology of population activity in grid cells. *Nature*, 1-6.

Ginosar, G., Aljadeff, J., Burak, Y., Sompolinsky, H., Las, L., & Ulanovsky, N. (2021). Locally ordered representation of 3D space in the entorhinal cortex. *Nature, 596*(7872), 404-409.

Gonzalo Cogno, S., Obenhaus, H. A., Jacobsen, R. I., Donato, F., Moser, M.-B., & Moser, E. I. (2022). Minute-scale oscillatory sequences in medial entorhinal cortex. *bioRxiv*.

Grieves, R. M., Jedidi-Ayoub, S., Mishchanchuk, K., Liu, A., Renaudineau, S., Duvelle, É., & Jeffery, K. J. (2021). Irregular distribution of grid cell firing fields in rats exploring a 3D volumetric space. *Nature neuroscience, 24*(11), 1567-1573.

Hafting, T., Fyhn, M., Bonnevie, T., Moser, M.-B., & Moser, E. I. (2008). Hippocampus-independent phase precession in entorhinal grid cells. *Nature, 453*(7199), 1248-1252.

Hatcher, A. (2002). *Algebraic Topology*: Cambridge University Press.

Hopfield, J. J. (1982). Neural networks and physical systems with emergent collective computational abilities. *Proceedings of the national academy of sciences, 79*(8), 2554-2558.

Jayakumar, R. P., Madhav, M. S., Savelli, F., Blair, H. T., Cowan, N. J., & Knierim, J. J. (2019). Recalibration of path integration in hippocampal place cells. *Nature, 566*(7745), 533-537.

Knierim, J. J., & Zhang, K. (2012). Attractor dynamics of spatially correlated neural activity in the limbic system. *Annual review of neuroscience, 35*, 267.

Kraus, B. J., Brandon, M. P., Robinson II, R. J., Connerney, M. A., Hasselmo, M. E., & Eichenbaum, H. (2015). During running in place, grid cells integrate elapsed time and distance run. *Neuron, 88*(3), 578-589.

Kropff, E., & Treves, A. (2008). The emergence of grid cells: Intelligent design or just adaptation? *Hippocampus, 18*(12), 1256-1269.

Krupic, J., Bauza, M., Burton, S., Barry, C., & O'Keefe, J. (2015). Grid cell symmetry is shaped by environmental geometry. *Nature, 518*(7538), 232-235.

Krupic, J., Bauza, M., Burton, S., & O'Keefe, J. (2018). Local transformations of the hippocampal cognitive map. *Science, 359*(6380), 1143-1146.

Langston, R. F., Ainge, J. A., Couey, J. J., Canto, C. B., Bjerknes, T. L., Witter, M. P., . . . Moser, M.-B. (2010). Development of the spatial representation system in the rat. *Science, 328*(5985), 1576-1580.

Long, X., Deng, B., Cai, J., Chen, Z. S., & Zhang, S.-J. (2021). A compact spatial map in V2 visual cortex. *bioRxiv*.

Long, X., & Zhang, S.-J. (2021). A novel somatosensory spatial navigation system outside the hippocampal formation. *Cell research, 31*(6), 649-663.

Maria, C., Boissonnat, J.-D., Glisse, M., & Yvinec, M. (2014). *The gudhi library: Simplicial complexes and persistent homology.* Paper presented at the International congress on mathematical software.

Mileyko, Y., Mukherjee, S., & Harer, J. (2011). Probability measures on the space of persistence diagrams. *Inverse Problems, 27*(12), 124007.

Moser, E. I., Kropff, E., & Moser, M.-B. (2008). Place cells, grid cells, and the brain's spatial representation system. *Annu. Rev. Neurosci., 31*, 69-89.

Pastalkova, E., Itskov, V., Amarasingham, A., & Buzsaki, G. (2008). Internally generated cell assembly sequences in the rat hippocampus. *Science, 321*(5894), 1322-1327.

Rajan, K., Harvey, C. D., & Tank, D. W. (2016). Recurrent network models of sequence generation and memory. *Neuron, 90*(1), 128-142.

Redish, A. D., Elga, A. N., & Touretzky, D. S. (1996). A coupled attractor model of the rodent head direction system. *Network: computation in neural systems, 7*(4), 671.

Sanguinetti-Scheck, J. I., & Brecht, M. (2020). Home, head direction stability, and grid cell distortion. *Journal of Neurophysiology*.

Satopaa, V., Albrecht, J., Irwin, D., & Raghavan, B. (2011). *Finding a" kneedle" in a haystack: Detecting knee points in system behavior.* Paper presented at the 2011 31st international conference on distributed computing systems workshops.

Si, B., & Treves, A. (2013). A model for the differentiation between grid and conjunctive units in medial entorhinal cortex. *Hippocampus, 23*(12), 1410-1424.

Stolz, B. J., Tanner, J., Harrington, H. A., & Nanda, V. (2020). Geometric anomaly detection in data. *Proceedings of the national academy of sciences, 117*(33), 19664-19669.

Tenenbaum, J. B., Silva, V. d., & Langford, J. C. (2000). A global geometric framework for nonlinear dimensionality reduction. *Science, 290*(5500), 2319-2323.

Turner, K., Mileyko, Y., Mukherjee, S., & Harer, J. (2014). Fréchet means for distributions of persistence diagrams. *Discrete & Computational Geometry, 52*(1), 44-70.

Widloski, J., & Fiete, I. R. (2014). A model of grid cell development through spatial exploration and spike time-dependent plasticity. *Neuron, 83*(2), 481-495.

Wills, T. J., Cacucci, F., Burgess, N., & O'Keefe, J. (2010). Development of the hippocampal cognitive map in preweanling rats. *Science, 328*(5985), 1573-1576.

Yoon, K., Buice, M. A., Barry, C., Hayman, R., Burgess, N., & Fiete, I. R. (2013). Specific evidence of low-dimensional continuous attractor dynamics in grid cells. *Nature neuroscience, 16*(8), 1077-1084.

Yoon, K., Lewallen, S., Kinkhabwala, A. A., Tank, D. W., & Fiete, I. R. (2016). Grid cell responses in 1D environments assessed as slices through a 2D lattice. *Neuron, 89*(5), 1086-1099.

Zhang, K. (1996). Representation of spatial orientation by the intrinsic dynamics of the head-direction cell ensemble: a theory. *Journal of Neuroscience, 16*(6), 2112-2126.

Zomorodian, A., & Carlsson, G. (2005). Computing persistent homology. *Discrete & Computational Geometry, 33*(2), 249-274.