Measuring Neuronal Avalanches to inform Brain-Computer Interfaces

Marie-Constance Corsi[1,2,*], Pierpaolo Sorrentino[3,*], Denis Schwartz[4], Nathalie George[1,4], Leonardo L. Gollo[5], Sylvain Chevallier[6], Laurent Hugueville[3], Ari E. Kahn[7], Sophie Dupont[1], Danielle S. Bassett[8], Viktor Jirsa[3,**], Fabrizio De Vico Fallani[1,2,**]

* These authors contributed equally and are listed alphabetically, ** these authors co-supervised equally

[1] Sorbonne Université, Institut du cerveau - Paris Brain Institute - ICM, CNRS, Inserm, APHP, Hôpital de la Pitié Salpêtrière, Paris, France

[2] Inria, Aramis team, Paris, France

[3] Institut de Neuroscience des Systèmes, Aix-Marseille University, Inserm, Marseille, France

[4] Institut du Cerveau - Paris Brain Institute, ICM, Inserm U 1127, CNRS UMR 7225, Sorbonne Université, CENIR, Centre MEG-EEG, Paris, France

[5] The Turner Institute for Brain and Mental Health, School of Psychological Sciences, and Monash Biomedical Imaging, Monash University, Victoria 3168, Australia

[6] LISN-CNRS, Université Paris-Saclay, France

[7] Princeton Neuroscience Institute, Princeton University, USA

[8] University of Pennsylvania, Philadelphia, USA

Abstract

Large-scale interactions among multiple brain regions manifest as bursts of activations called neuronal avalanches, which reconfigure according to the task at hand and, hence, might constitute natural candidates to design brain-computer interfaces (BCI). To test this hypothesis, we used source-reconstructed magneto/electroencephalography, during resting state and a motor imagery task performed within a BCI protocol. To track the probability that an avalanche would spread across any two regions we built an avalanche transition matrix (ATM) and demonstrated that the edges whose transition probabilities significantly differed between conditions hinged selectively on premotor regions in all subjects. Furthermore, we showed that the topology of the ATMs allows task-decoding above the

30 current gold standard. Hence, our results suggest that Neuronal Avalanches might capture interpretable

31 differences between tasks that can be used to inform brain-computer interfaces.

Introduction

Brain-Computer Interfaces (BCIs) constitute a promising tool for establishing direct communication and

control from the brain over external effectors for clinical applications[1,2]. However, the ideal features to

design a BCI are unknown, since the underlying microscopic brain processes, and their reflection on

brain signals, are poorly-understood[3]. As a result, mastering non-invasive BCI systems remains a learned

skill that yields suboptimal performance in ~30% of users, referred to as the "BCI inefficiency"

phenomenon[4]. Measuring the dynamical features that are relevant to the execution of a task and, as a

consequence, may improve BCI performance, remains an open challenge[3]. Electromagnetic imaging

data is dominated by 'bursty' dynamics, with fast, fat-tailed distributed, aperiodic perturbations, called

"neuronal avalanches", traveling across the whole brain[5], which have been recorded using

electro/magnetoencephalography[6,7]. Neuronal avalanches spread preferentially across the white-matter

bundles[8], they are modified by neurodegenerative diseases[9], and they evolve over a manifold during

resting-state, generating rich functional connectivity dynamics[10]. Such rich dynamics are a major

contributor to time-averaged functional connectivity[5,11]. Hence, the spreading of neuronal avalanches

might be a correlate of the functional interactions among brain areas and, as such, we hypothesize that

they could spread differently according to the task at hand, thereby providing a powerful and original

marker to differentiate between behaviors. To test our hypothesis, we compared source-reconstructed

magnetoencephalography (MEG) signals in resting-state (RS) and while performing a motor imagery

(MI) task in a BCI protocol, in order to track the dynamical features related to motor imagery as

compared to rest. We obtained the probabilities of each pair of regions being recruited sequentially in

an avalanche[8], compared these probabilities across MI and RS conditions edge- and subject-wise, and

related the differences between the two conditions to the performance in the BCI task, as measured using

the BCI classification accuracy. Furthermore, we used these features to decode the tasks from source-

reconstructed data.

Results

We used the spatio-temporal spreading of large aperiodic bursts of activations as a proxy for communications between pairs of regions. Within this framework, large-scale, higher-order perturbations are considered to mediate the interactions between brain regions. We tested for differences between the two experimental conditions (i.e. resting-state, RS, and motor imagery, MI) in the probabilities of any such perturbation to propagate across two brain regions. To this end, we built an avalanche transition matrix (ATM) for each subject, containing regions in rows and columns, and the probability that region j would activate at time (t+1), given that region i was active at time t, as the ij[th] entry. The differences in the probability of being sequentially recruited by an avalanche was used to track (subject- and edge-wise) the spatial propagation of the perturbations across the two experimental conditions. To validate the observed differences, for each subject and each edge, we built a null-model (Figure 1A) randomizing the labels of each trial (i.e. RS or MI) 10000 times, so as to obtain a null distribution of the differences expected by chance. These distributions were used to spot, individually, the edges that differed between the two conditions above chance level. The significances were corrected for multiple comparisons across edges using the Benjamini-Hochberg (BH) correction[12]. Following this step, we focused on the edges that were consistently significant across subjects (defined here as "reliable" edges). To achieve this, we randomized 10000 times, in each subject, the statistically significant edges (Figure 1B). This way, we identified the edges which differed significantly between the experimental conditions in a higher number of subjects than expected at chance level (p<0.05, BH corrected across edges). Our results show that there is a set of edges, consistent across most subjects, across which large-scale perturbations propagate differently according to the experimental condition (Figure 2A).

We then checked if the significantly different edges would cluster over specific brain regions. To this end, we computed the expected number of significant edges incident on any region, given a random distribution (with a comparable density), and selected those regions with an above-chance number of significant edges clustered upon them (Figure 1B). Statistics were again corrected using BH, this time across regions. As evident in Figure 2, panel C, to the left, these "reliably different" edges cluster on

premotor regions bilaterally and, particularly, on the caudal middle frontal gyri bilaterally (p<0.0001, BH corrected). We replicated the analysis demonstrating the robustness to the choice of arbitrary parameters (supplementary material 1), and to the methodology and parcellation used (supplementary materials 2). We have also performed the same pipeline as described above, this time using the power spectra and the phase locking-value, both of them in the theta, alpha and beta bands, as features to distinguish the motor imagery from the resting-state (supplementary materials 3). So far, we have classified the trials according to the stimulus presented to the subject. However, if the differences we found were genuinely related to the task execution, one might expect that they would be greater when the trials were successful (i.e. when the subject could control the BCI device), as compared to when the trials were unsuccessful. To test this hypothesis, in each subject, we compared the differences between MI and RS in the successful trials, to the differences between MI and RS in the unsuccessful trials, expecting to see greater differences at the individual level (in the same set of edges) in the former case as compared to the latter. To statistically test this hypothesis, we used a permutation approach, randomizing successful and unsuccessful trials within each subject. As shown in Figure 2, panels C, to the right, we could confirm that the transition probabilities across the previously identified reliable edges differed more, in each subject, between conditions, in successful trials as compared to unsuccessful trials, supporting the hypothesis that the relationship between transition probabilities and task performance is valid and measurable at the individual level.

To explore the performance of neuronal avalanches in the decoding of the task (i.e., resting-state versus motor imagery), we compared the ATMs to the Common Spatial Pattern (CSP) approach[13,14], which is a gold standard for classification in MI-based BCI. We also explored the performance of the power-spectra and of the phase-locking values which both performed, as expected, worse than the CSP (not shown). The CSP and ATM outputs were classified with a Support Vector Machine (SVM), and the results were compared. As it can be seen in Figure 3A and 3D, the classification performance seemed comparable for both methods with MEG (averaged performance of 0.76 for both CSP+SVM and for ATM+SVM) and greater for ATM+SVM than CSP+SVM with EEG (averaged performance of 0.75 and of 0.80 respectively for CSP+SVM and for ATM+SVM). Furthermore, in both MEG and EEG we observed greater inter-subject variability in the case of CSP+SVM (standard deviation= 0.13 and 0.15,

for MEG and EEG, respectively) than with ATM+SVM (standard deviation= 0.11 and 0.10 for MEG

and EEG, respectively).

Then, we moved on to a subject-specific analysis, to explore the applicability of the ATM method in the

context of a BCI training. We aimed to compare the ability of correctly classifying a trial as MI and RS

within each subject. Hence, for each subject, we ran t-tests (and confirmed them with Wilcoxon tests)

to compare the 50 success rates obtained with CSP+SVM to the 50 success rates obtained using

ATM+SVM. This was done under the null hypothesis that CSP+SVM and ATM+SVM would not yield

any statistically different performance in trial classification. We repeated this comparison for every

subject, and corrected the statistical comparisons for multiple comparisons across subjects using the

False Discovery Rate (FDR). We also repeated the analysis for 75 random splits, and the results did not

change, showing that our results reached convergence at 50 splits.

This analysis showed that for the MEG dataset, ATM+SVM yielded significantly higher classification

accuracy than CSP+SVM did for 6 subjects, while the opposite was true for 7 subjects. For the remaining

7 subjects, there was not any statistically significant difference between the decoding performances of

CSP+SVM and ATM+SVM (Fig. 3, panel B). For the EEG data, ATM+SVM yielded better

classification accuracy than CSP+SVM for 12 subjects. In four subjects, CSPs yielded better accuracy

than ATMs (Fig. 3, panel E). In 5 subjects, there was not any statistically significant difference between

the two approaches.

Moreover, we examined the variability of the estimates across the splits. Steady estimates are important

to train online algorithms and high variability might be partly responsible for ineffective training. We

observed marginally higher intra-subject variability in CSP+SVM (median value of 0.07 in both

modalities) as compared to ATM+SVM (median value of 0.06 in both modalities). In particular, the

standard deviation across the split is smaller for the ATMs for most subjects. In Figure 3, panels C and

F for MEG and EEG respectively, we compare the variance (across random splits) of the estimates

obtained with the two pipelines (again, ATM on the x-axis, CSP on the y-axis).

137
138 Finally, we explore the relationship between the magnitude of the differences in the transition

139 probabilities between the two experimental conditions (in each subject, for every edge) to the individual

BCI performance (defined as the proportion of trials in which the subject controlled the BCI device) in the MI task, as measured using the BCI score. Figure 4, panel A shows the edges whose differences between conditions correlate the most with the BCI scores (the color code shows the intensities of the correlations, for visualization purposes only edges with correlations with p-values < 0.05 are shown). Firstly, for nearly every edge we observed a positive correlation. To help interpretation, we clustered all the edges according to functional regions (i.e., executive regions, pre/motor areas, parietal areas, temporal areas, occipital areas, (Figure 1C). That is, we computed the average Spearman's correlation over all the edges connecting any two functional regions (also including self-connections, i.e. edges which are comprised within a functional region). To check if the differences in edges transitions which correlated to task performance clustered over certain functional areas above chance-level, we again built a null-model. To this end, for 10000 times, we randomly allocated edges correlation coefficients to functional areas and, each time, we computed the average. We compared the observed average correlation coefficient to the null distribution to obtain a significance value per functional area. Significance values were then corrected for multiple comparisons across all their combinations (i.e., 5x5, 25 p-values). Our results suggest that edges that significantly relate to BCI task performance hinge pre/motor areas and parietal areas (p<0.0001, See Figure 4, panel B). Since we retrieved nearly exclusively positive correlations, our results capture that perturbations spread more often between premotor/motor areas and parietal areas when the subject is engaged in the motor-imagery task, as compared to the resting-state condition. We replicated these results using different parcellation schemes (supplementary materials 5).

Discussion

In this work, we set out to test if neuronal avalanches can track subject-specific changes induced by the execution of a task (i.e., motor imagery) in the large-scale brain dynamics. The working hypothesis was that meaningful communication among regions on the large-scale is intermittent, and it is best understood and measured in terms of aperiodic perturbations. Neuronal avalanches are inherently aperiodic processes with scale-free fluctuations, whose statistical parameters meet theoretical

predictions from mean-field theory[15–17]. In our data, we confirmed that the measured branching ratio is

compatible with that of a system operating at criticality or near-criticality[18]. We went on from there to

test the basic idea that brain regions interact differently while performing different tasks. We reasoned

that, if avalanches convey interactions occurring between regions, their spreading should also be

modified according to the task at hand. Such context-dependent modifications should then be encoded

in the avalanche transition matrices and, in turn, might be decoded in order to tailor brain-computer

interfaces. More specifically, such information could be considered either as potential predictors of BCI

performance, to conceive tailored training programs, or as alternative features, to improve the

classification performance.

With respect to the encoding framework, we identified, in an unsupervised manner, a number of

functional links (i.e. edges) that are reliably more likely to be dynamically recruited during a motor

imagery task as compared to resting state. The edges cluster over regions typically involved in motor

planning and attention, as expected from a motor imagery task. In fact, premotor areas are involved in

the planning of motor actions, in the imagining of actions, in allocating executive attention[19], as well as

in the selection between competing visual targets[20], while parietal areas are notably involved, among

other things, with the processing of sensitive input. In line with previous findings[21], a premotor-parietal

network was found to be specifically implicated with spatial imagery tasks. Our study of the relationship

between the contrast topology and the success rate revealed that the more the differences in an individual

match the "reliable edges", the better the performance. These results suggest that indeed the localization

of the different edges carries a behavioral meaning.

The ATMs directly track the spreading of activations as they happen (as opposed to quantifying

dependencies over time intervals). Using such straight-forward approach[8], we reliably retrieve

functional information related to the execution of a task at the subject-level, which was not possible

using classical functional metrics[22]. This is based on theoretical underpinnings derived from statistical

mechanics, which posits that higher-order, long-range correlations would appear in a near-critical

dynamical regime[15,18]. In fact, it is important to notice that, by z-scoring each region and using a high-

threshold we selected only very strong coherent activity, which is unlikely to be generated by a linear

process and that, instead, refers to a higher-order phenomenon. In doing so, we discarded most of the available signals. In practice, we have discarded roughly 90% of the data, applying a "spatio-temporal" filter, and only selecting those points in time and space where large-scale aperiodic perturbations were found. To provide a comparison with more standards techniques, we have used the same pipeline based on techniques that assume stationarity (and take the whole data into account), namely the power-spectra (containing local information) and the phase-locking value (estimating bivariate synchronization between brain regions). Importantly, both techniques failed to reproduce any pattern of differences between the two conditions that was replicable at the individual level (see supplementary materials 3). However, in the same dataset, a previous work showed that the power-spectra could show differences at the group-level[22]. The fact that we could find robust individual differences while discarding most data and that we failed to do so when taking the whole data into account suggests that focusing on higher-order perturbations might be useful to capture functionally-relevant processes and, in turn, to apply them to the design of BCIs.

We replicated our results using different thresholds and binnings showing that they are resilient to these choices. Also, they can be replicated using different parcellation schemes, and using EEG signals, which is more widely available than MEG for BCI applications, thereby making our methodology suitable in a wide variety of settings. All in all, extensive replications make it unlikely that our results could be due to arbitrary choices or limited to a specific methodology.

Within the decoding framework, we compared the offline classification performance resulting from the use of the ATM to the gold-standard approach, which relies on spatial filters (i.e., the Common Spatial Patterns). Our results suggest that the integration of periodic and aperiodic features would be a straightforward way to improve task classification. Indeed, the information captured by the two types of feature extraction (namely CSPs and ATMs) and the two modalities (MEG and EEG) are complementary. The ATMs maintain a fairly straightforward interpretability as opposed to CSPs, which operate on large-scale components of the signal that are not as readily interpretable. In particular, the ATMs focus on the strong coherent interactions that intermittently occur on the large-scale. The good performance of the ATMs on the EEG data is relevant to translate our methodology to real-world

scenarios. In this configuration, the classification of ATMs leads to a significant improvement of the

decoding performance with respect to the benchmark in the majority of subjects. Importantly, in both

modalities, we observed a reduced intra and inter-subject variability with our approach as compared to

CSP+SVM. This might help, in real-life experiments, to reduce the BCI inefficiency phenomenon. To

evaluate the feasibility in online applications, we estimated that for an epoch of 5s the time necessary to

extract the features, and to perform the classification, was approximately 25ms for ATM+SVM and

27ms for CSP+SVM. This value is actually compatible with current on-line settings which use similar

time windows and update the feedback every 28 ms. Further investigations are needed to explore the

performance in the context of online classification with shorter time windows. Nevertheless, it is

worthwhile mentioning that this is a first proof-of-concept study of the use of neuronal avalanches as

complementary/alternative features for the design of BCI.

Identifying neural markers associated with BCI performance is crucial to design optimized and tailored

BCI systems[24]. In turn, the most informative markers provide insight into the processes that underpin

the execution of a given task.

Neurophysiological predictors of BCI scores are most commonly associated with power spectra. Indeed,

sensorimotor μ- and α-rhythms or, more recently, time-averaged brain interactions in these frequency

bands have been considered as potential markers[25]. These findings were mainly empirical and, in this

oscillatory perspective, features such as power spectra and/or (static) synchronization measures have

been widely explored to inform the interfaces[25,26]. Furthermore, regional connectivity strength[22] and the

M/EEG multiplex core-periphery[27] of specific associative and somatosensory areas held predictive

power over BCI performance in the same session. However, between 15% and 30% of the subjects do

not learn to control the effector despite extensive training. This might mean that the typical features only

partly capture the processes that lead to the execution of the task. Hence, different markers might be

exploited. Our study contributes, on a practical level, by achieving a differentiation between tasks at

the individual level. From a more theoretical perspective, our results suggest that the spreading of local

synchronization on the large-scale might be intermittent and aperiodic, and that such spreading carries

behavioral relevance. The fact that neuronal avalanches are relevant to the execution of a task might

also have implications on the underlying microscopic dynamics. As such, this would allow the

deployment of complex and solid mathematical tools derived from statistical mechanics to test the

presence of specific microscopic physiological processes.

When relating the differences between MI and RS in the probability of an avalanche consecutively

recruiting two regions to the magnitude of BCI performance we find mostly positive correlations,

indicating that the more avalanches spread between premotor/motor and parietal regions during the task,

the better the control of the BCI. This might suggest that the interactions between pre/motor regions and

parietal ones underpin the execution of the task. These findings are in line with previous studies relying

on MI-based BCI paradigms. In particular, Buch et al[28] showed that the structural integrity of the

frontoparietal networks predict the ability of stroke patients to control a brain computer interface in a

motor imagery task. Using fMRI, Halder et al. showed that the premotor areas participate in executing

voluntary modulation of brain rhythms through a MI-based BCI[29].

Importantly, when interpreting the results in cognitive terms, one should consider that a (BCI) task likely

recruits multiple cognitive processes, beyond those exploited by the BCI classification itself. As such, a

psychophysiological interpretation of the areas involved in the BCI classification is not straightforward.

For example, the right fronto-parietal network dynamics also reflects the allocation of attentional

resources, which are typically engaged in cognitive/motor tasks. It is also known that fronto-medial

activities are one of the main correlates of sustained attention[30]. Thus, although the clustering of the

edges that we found in the fronto-parietal network is consistent with the prominent involvement of this

network in motor imagery tasks, it cannot be mapped uniquely onto one cognitive process. A different

perspective is provided by the analysis of cognitive profiles, since it was shown that spatial abilities

influence BCI performance[31], and in particular mental rotation[32]. As such, training strategies might be

tailored over a subject-specific assessment of such abilities. Intriguingly, mental rotation abilities were

related in turn to increased activity of the premotor cortex, the superior-parietal and the intra-parietal

cortices[33,34]. Furthermore, activations in the right middle frontal gyrus correlated with BCI performance,

which might be interpreted in the light of the role that this region plays in the processing of an observed

movement[29].

In conclusion, in a real-world scenario, multiple mechanisms might be in place. As such, our approach

is not expected to be the only useful framework. However, it might capture part of the processes that

were typically overlooked in a more oscillatory perspective. Our work paves the way to use aperiodic

activities to improve classification performance and tailor BCI training programs.

Methods

Cohort & experiment description & data preprocessing

Participants

The research was conducted in accordance with the Declaration of Helsinki. A written informed consent

was obtained from subjects after explanation of the study, which was approved by the ethical committee

CPP-IDF-VI of Paris. All participants received financial compensation at the end of their participation.

Twenty healthy subjects (27.5 ± 4.0 years old, 12 men), with no medical or psychological disorder, were

recruited. They participated in a BCI experiment where MEG and EEG were simultaneously recorded.

A description of the participants characteristics is provided in the supplementary materials 6.

BCI experiment

We used the dataset from Corsi et al[22]. The BCI task consisted of a standard two-target box task[35], where

the subjects were instructed to modulate their alpha and/or beta band brain activity to control the vertical

position of a moving cursor to hit a gray vertical bar, referred as the target, displayed on the right part

of the screen. To hit the "up-target" the subjects had to perform a sustained motor imagery (MI) of the

right-hand grasping and to hit the "down-target", the subjects were instructed to remain at rest.

During the experiments, the online features were obtained from the estimation of the power spectra via

an autoregressive model that relied on the maximum entropy method[36] every 28ms on a time window

of 0.5s. These features were classified using the Linear Discriminant Analysis (LDA) method. The

feedback provided to the subject, namely the vertical position of the moving cursor, relied on the linear

combination of the computed features via the moving average method[37]. The BCI performance used in

this study refers to the proportion of trials in which the subjects could control the vertical position of the

moving cursor to hit the target.

M/EEG data acquisition and preprocessing

EEG signals were recorded with a 74 EEG-channel system, with Ag/AgCl passive sensors (Easycap,

Germany) placed according to the standard 10-10 montage, with the references placed at the mastoids,

and the ground electrode located at the left scapula. MEG signals were recorded via a system composed

of 102 magnetometers and 204 gradiometers (MEGIN Neuromag TRIUX MEG system). M/EEG signals

were simultaneously recorded in a magnetic shielding room with a bandwidth of 0.01-300Hz and a

sampling frequency of 1kHz. Head positions were digitized via the Polhemus Fastrak digitizer

(Polhemus, Colchester, VT). Three points were used as landmarks to provide co-registration with the

individual anatomical MRI: nasion, left and right pre-auricular points. Individual T1 sequences (256

sagittal slices, TR=2.40ms, TE=2.22ms, 0.80mm isotropic voxels, 300x320 matrix; flip angle=9°) were

acquired with a 3T Siemens Magnetom PRISMA after the BCI experiments. Subjects were instructed

to remain at rest for 15 minutes. Images were preprocessed with the FreeSurfer toolbox[38] and imported

to the Brainstorm toolbox[39] where the digitized locations of the landmarks, and of the EEG electrodes

were aligned with the MRI.

To remove the environmental noise in MEG signals, we applied the temporal extension of the Signal

Space Separation (tSSS) with MaxFilter[40]. To remove ocular and cardiac artifacts, we performed an

Independent Components Analysis (ICA) via the Infomax approach with the Fieldtrip toolbox[41,42]. Only

the components that contained physiological artifacts were removed through a visual inspection of the

signals. Once the data was preprocessed, we cut the recordings into epochs of 7 seconds.

Source reconstruction was performed by the computation of individual head models with the Boundary

Element Method (BEM)[43,44] where the surfaces were obtained from three layers related to the individual

MRI (scalp, inner skull, outer skull) that contained 1922 vertices each. Sources were estimated via the

weighted Minimum Norm Estimate (wMNE)[45,46]. In this work, we used the Desikan parcellation

scheme[47].

For a complete description of the preprocessing steps, please refer to Corsi et al[22].

Data pipeline

Each source-reconstructed signal was z-scored (over time), thresholded, and set to 1 when above

threshold, and to zero otherwise (threshold: $z = |3|^6$). Then, an avalanche was defined as starting when

at least one region is above threshold, and as finishing when no region is active. For each avalanche, we

estimated a transition matrix, structured with regions in rows and columns, and the ij-th edge is defined

as the probability that regions j would be active at time t+1, given region i was active at time $t^{9,48}$. For

each subject, we obtained an average transition matrix (i.e. averaging edge-wise over all avalanches) for

the baseline condition, and an average transition matrix for the motor imagery task. To ensure

appropriate sampling[49], we have binned the data with bins ranging from 1 to 3 (stopping at three to avoid

aliasing). To select the optimal binning, we looked at the branching ratio, since a branching ratio ~ 1

typically indicates a process operating near a critical regime. The branching ratio is calculated as the

geometrically averaged (over all the time bins) ratio of the number of events (activations) between the

subsequent time bin (descendants) and that in the current time bin (ancestors) - eq.1, as:

345
$$\sigma_i = \prod_{j=1}^{N_{bin}-1} \left(\frac{n_{events}\,(j+1)}{n_{events}\,(j)} \right)^{\frac{1}{N_{bin}-1}} \qquad (1)$$

346   and then geometrically averaging it over all the avalanches - eq.2^{15}.

347
$$\sigma = \prod_{i=1}^{N_{aval}} (\sigma_i)^{\frac{1}{N_{aval}}} \qquad (2)$$

where σ_i is the branching parameter of the i-th avalanche in the dataset, N_{bin} is the total amount of bins

in the i-th avalanche, n_{events} (j) is the total number of events active in the j-th bin, and N_{aval} is the total

number of avalanches in each participant's recording.

In branching processes, a branching ratio of $\sigma = 1$ indicates critical processes with activity that is highly

variable and nearly sustained, $\sigma < 1$ indicates subcritical processes in which the activity quickly dies

out, and $\sigma > 1$ indicates supercritical processes in which the activity increases as runaway excitation.

The bin length equal to one sample yielded a $\sigma = 1$, hinting at the avalanches as occurring in the context

of a dynamical regime near operating near criticality, was chosen for subsequent analyses. Importantly,

the other binnings also yielded branching ratios extremely close to 1 (0.995, and 0.978 for binnings 2

and 3, respectively), and the results of the analyses remain unchanged, showing resilience to the details

of the pipeline. However, one should notice that this particular dataset entails rather short epochs and,

as such, it is not best suited for the evaluation of a long tail. This is all the more true considering that a

stimulus was being delivered and, as such, the dynamics was not evolving unperturbed.

In order to compare how the trials are encoded in the data, we provide a comparison with standard

feature extraction techniques, we computed the power spectra, via the Welch method with a window

length of 1 s and a window overlap ratio of 50%, and the phase-locking value, as in Lachaux et al[50].

For these analyses, the classification of the trials as MI or RS was based on the outcome of the

experiment. To explore the robustness of our results to different classification algorithms, we also

classified the trials as MI/RS based on either Linear Discriminant Analysis or a Support Vector Machine.

The results showed that our conclusions are robust to the classification algorithm (see supplementary

material 4).

Statistical analysis

For each subject, we computed the difference in the probability of a perturbation running across a given

edge during resting-state and during the MI task. To statistically validate this, for each individual, we

randomly shuffled the labels of the individual avalanches (i.e. each trial-specific transition matrix was

randomly allocated to either resting-state and motor imagery). We performed this procedure 10000

times, obtaining, for each edge, the distribution of the differences given the null-hypothesis that the

transition matrices would not capture any difference between the two conditions. Note that this approach

does not require normality of the original distributions. We used the null distribution to obtain a

statistical significance for each edge. The retrieved significances were Benjamini-Hochberg-corrected

for multiple comparisons across edges[12]. Following this procedure, we obtained for each patient, a

matrix with the edges that significantly differed from the two conditions. We then looked at the

concordance of such matrices across subjects, as to only focus on the edges that are reliably related to

the task at hand. We have only selected those edges that were significant in a higher-than-chance number

of subjects. Finally, we selected only those nodes that had more significantly different edges incident

upon them, as compared to chance level. This way, we selected the areas whose involvement in large-

scale dynamics is qualitatively different, in multiple subjects, between the two conditions (i.e. RS vs.

MI task), and refer to these as the "task-specific" areas.

Then, we moved on to check what edges differed related to the BCI performance. To this end, we related,

for each edge, the individual differences in the transition probabilities in the two experimental conditions

to the individual BCI performances. We then grouped the edges according to functional areas, namely:

executive areas, pre/motor areas, parietal areas, temporal areas, and occipital areas. To statistically

validate this approach, for 10000 we have randomly allocated the edges to these groups and computed

the average correlation coefficient at each iteration for each group of edges. We used these averages to

build a null-distribution for each functional area, and used to have a statistical significance. Finally,

these significances were corrected across functional regions using the BH correction for multiple

comparison. We have repeated the correlation analysis without grouping the regions into functional

areas but carrying out the correlation analysis for each region separately. In this case, no single region

survived the BH correction (not shown).

Finally, we replicated our results using the Destrieux parcellation scheme[51] and using the

electroencephalogram. Furthermore, we repeated the analysis changing the threshold to define active

regions.

Classification analysis

To assess the extent to which the ATMs might be considered as an alternative feature for BCIs, we

compared the classification performance resulting from a feature extraction approach based respectively

on the ATMs and on spatial filters, namely Common Spatial Patterns (CSP)[13,14]. In addition, as a

preliminary study, we also tested the classification performance associated with other features such as

the power-spectra (of the source-reconstructed time-series) and the phase-locking values. All the

considered features were classified with two different techniques, namely linear discriminant analysis

(LDA) and support vector machines (SVM). We obtained the best classification performance using CSP

followed by the Support Vector Machine (SVM) classifier. Therefore, we selected this framework as

the benchmark against which ATMs were compared.

For each subject, we divided the dataset to include 80% of the trials in the train split and 20% of the

trials in the test split. The SVM was trained using either the CSPs or the ATMs. For each subject, the

CSP method decomposes the source-reconstructed signals using spatial filters, and then selects the n

modes that capture most inter-class variance. Here, we selected eight spatial modes (since they yielded the best classification accuracy) and returned the average power of each. As for the ATMs, for each subject we found the optimal z-score threshold for identifiability. Then, we fed an SVM classifier with either feature (CSP-filtered data or ATM). Finally, we compared the classification performance (i.e. the proportion of correctly labeled trials) for CSP+SVM and ATM+SVM, over 50 random splits of the data. For each subject, we ran t-tests (and confirmed them with Wilcoxon) under the null hypothesis that CSP+SVM and ATM+SVM would not yield a statistically different performance in trial classification. We repeated this comparison for all the subjects and corrected the statistical comparisons for multiple comparisons across subjects using the False Discovery Rate (FDR). To calculate the inter-subject variability, we used the standard deviation of the classification performance across splits and subjects. As per the intra-subject variability, we calculated the standard deviation of the classification accuracy across the 50 splits for each subject. To estimate the computational time required to extract and to classify the features, we used a built-in function in python.

Data availability

Given the personal nature of the data, it cannot be made publicly available. However, the data is available upon request to the corresponding authors for the purpose of replication.

Code availability

The code used to perform the analysis of this study is publicly available at https://github.com/mccorsi/NeuronalAvalanches4BCI.git.

Acknowledgments

The authors acknowledge support from the European Research Council (ERC) under the European Union's Horizon 2020 research and innovation program (grant agreement No. 864729), the program "Investissements d'avenir" ANR-10-IAIHU-06, and the European Union's Horizon 2020 research and

441 innovation programme under grant agreement No. 945539 (SGA3) Human Brain Project,

442 VirtualBrainCloud No.826421.

Author contributions

445 Conceptualization: MCC & PS; Methodology: MCC & PS; Investigation: MCC & PS; Visualization:

446 MCC & PS; Supervision: FDVF & VJ; Data collection and curation: MCC, DS, LH; Data processing:

447 MCC, PS, AEK; Writing—original draft: MCC & PS; Writing—review & editing: MCC, PS, DS, NG,

448 LG, SC, LH, AEK, SD, DSB, VJ, FDVF.

Figure 1 Overview of the analysis. A. Subject-level analysis: to identify, for each subject, the edges that show a significant condition effect. The average of all RS trials was subtracted, edge-wise, from the average of the MI trials. The differences were validated by shuffling the labels (i.e. MI and RS) 10000 times. This way, significantly different edges were identified for each patient. **B. Group level analysis:** we identified the edges that were significantly different in a large number of subjects (as compared to what would be expected by chance) and then performed nodal analysis to identify the regions over which significant differences were clustered. **C. Correlation analysis:** correlation coefficients between individual differences (for each edge) and individual BCI scores were averaged over 5 regions, namely, executive, pre/motor, parietal, temporal and occipital, obtaining one mean correlation between functional areas (i.e. 5 x 5 = 25 values). Then, the correlation coefficients were shuffled 10000 times, and each time surrogate average coefficients were obtained for each group of edges. These nulls were used to check if the edges with differences in transition probabilities that related to task performance clustered in any specific area. All statistical analyses were BH corrected for multiple comparisons, as appropriate.

Figure 2 Reliability analysis. A. Edge-wise differences in transition probability from the ground truth: Reliably different task-based interactions over the subjects (p<0.05, after correction for multiple comparison). **B. Edge-wise differences in transition probability between hit/miss trials:** Reliably different task-based interactions over the subjects (p<0.05, after correction for multiple comparison). The reported edges are the ones where the difference observed between MI and Rest in the "hit" trials was greater than that found in the "miss" trials. **C. Node-wise differences in transition probability - on the left: computed from the trials according to the stimulus presented to the subject ("ground truth"); on the right: from the "hit/miss trials":** the color scale is proportional to the nodal degree derived from the matrix with the group-significant differences (the brighter the color, the more edges that differ between tasks are incident upon that node).

Figure 3 - Classification analysis. **A & D. Group-level classification performance obtained from MEG and EEG data:** for each classification tool (respectively, in purple to the left, CSP+SVM and in salmon to the right, ATM+SVM) each dot corresponds to the accuracy obtained for a given subject and a given split. **B & E. Individual-level classification performance from MEG data and EEG data:** each dot corresponds to the accuracy averaged over the 50 splits obtained from a given subject. The x-axis refers to the accuracy of ATM+SVM, while the y-axis refers to the accuracy of CSP+SVM. The dashed black line represents equal accuracy for both methods. Therefore, the dots below (resp. above) the line represents the subjects for which ATM+SVM performed better (resp. worse) than CSP+SVM. Dots have been color coded accordingly: in salmon, the subjects for whom ATM+SVM were statistically more accurate than the CSP+SVM; in violet, the subjects for whom CSP+SVM were statistically more accurate than the ATM+SVM, and in gray, the subjects where the two methods did not yield statistically different performances. **C & F. Individual-level classification performance variability from MEG data and EEG data:** each dot corresponds to the standard deviation over the 50 splits obtained from a given subject. The dashed black line represents equal variability for both methods. The x- and y-axis have been coded in descending value order so that the dot distribution can be read similarly as in the

previous plots, with dots below (resp. above) the dashed line representing subjects for whom ATM+SVM led smaller (resp. greater) variability than CSP+SVM. The color code is identical to the plots B and E, so that salmon (resp. violet) dots represent the subjects for whom ATM+SVM *accuracy* was significantly better (resp. worse) than the *accuracy* of CSP+SVM. We chose to keep the color code constant to allow for more direct comparison of the performance (accuracy and variability) of both methods.

Figure 4 Correlation analysis. A. Edge-wise correlations: edge-wise correlation with BCI scores. For visualization purposes, only the edges with p-values<0.05 are visualized. The color of the edges is proportional to the correlation coefficient. **B. Node-wise differences in transition probabilities:** the picture shows the functional-areas averaged correlation coefficients. In orange the pre/motor areas, in turquoise the parietal lobe.

References

1. Daly, J. J. & Wolpaw, J. R. Brain-computer interfaces in neurological rehabilitation. *Lancet Neurol.* **7**, 1032–1043 (2008).

2. Chaudhary, U., Birbaumer, N. & Ramos-Murguialday, A. Brain–computer interfaces for communication and rehabilitation. *Nat. Rev. Neurol.* **12**, 513–525 (2016).

3. Thompson, M. C. Critiquing the Concept of BCI Illiteracy. *Sci. Eng. Ethics* (2018) doi:10.1007/s11948-018-0061-1.

4. Allison, B. Z. & Neuper, C. Could Anyone Use a BCI? in *Brain-Computer Interfaces* (eds. Tan, D. S. & Nijholt, A.) 35–54 (Springer London, 2010).

5. Tagliazucchi, E., Von Wegner, F., Morzelewski, A., Brodbeck, V. & Laufs, H. Dynamic BOLD functional connectivity in humans and its electrophysiological correlates. *Front. Hum. Neurosci.* **6**, 339 (2012).

6. Shriki, O. *et al.* Neuronal Avalanches in the Resting MEG of the Human Brain. *J. Neurosci.* **33**, 7079–7090 (2013).

7. Palva, J. M. *et al.* Neuronal long-range temporal correlations and avalanche dynamics are correlated with behavioral scaling laws. *Proc. Natl. Acad. Sci.* **110**, 3585–3590 (2013).

8. Sorrentino, P. *et al.* The structural connectome constrains fast brain dynamics. *eLife* **10**, e67400 (2021).

9. Sorrentino, P. *et al.* Flexible brain dynamics underpins complex behaviours as observed in Parkinson's disease. *Sci. Rep.* **11**, 4051 (2021).

10. Rabuffo, G., Fousek, J., Bernard, C. & Jirsa, V. Neuronal Cascades Shape Whole-Brain Functional Dynamics at Rest. *eNeuro* **8**, ENEURO.0283-21.2021 (2021).

11. Zamani Esfahlani, F. *et al.* High-amplitude cofluctuations in cortical activity drive functional connectivity. *Proc. Natl. Acad. Sci.* **117**, 28393–28401 (2020).

12. Benjamini, Y. & Hochberg, Y. Controlling the False Discovery Rate: A Practical and Powerful Approach to Multiple Testing. *J. R. Stat. Soc. Ser. B Methodol.* **57**, 289–300 (1995).

13. Koles, Z. J., Lazar, M. S. & Zhou, S. Z. Spatial patterns underlying population differences in the background EEG. *Brain Topogr.* **2**, 275–284 (1990).

14. Blankertz, B., Tomioka, R., Lemm, S., Kawanabe, M. & Muller, K. Optimizing Spatial filters for Robust EEG Single-Trial Analysis. *IEEE Signal Process. Mag.* **25**, 41–56 (2008).

15. Bak, P., Tang, C. & Wiesenfeld, K. Self-organized criticality: An explanation of the 1/f noise. *Phys. Rev. Lett.* **59**, 381–384 (1987).

16. Cocchi, L., Gollo, L. L., Zalesky, A. & Breakspear, M. Criticality in the brain: A synthesis of neurobiology, models and cognition. *Prog. Neurobiol.* **158**, 132–152 (2017).

17. Sethna, J. P., Dahmen, K. A. & Myers, C. R. Crackling noise. *Nature* **410**, 242–250 (2001).

18. Moretti, P. & Muñoz, M. A. Griffiths phases and the stretching of criticality in brain networks. *Nat. Commun.* **4**, 2521 (2013).

19. Andersson, M., Ystad, M., Lundervold, A. & Lundervold, A. J. Correlations between measures of executive attention and cortical thickness of left posterior middle frontal gyrus - a dichotic listening study. *Behav. Brain Funct.* **5**, 41 (2009).

20. Germann, J. & Petrides, M. Area 8A within the Posterior Middle Frontal Gyrus Underlies Cognitive Selection between Competing Visual Targets. *eNeuro* **7**, (2020).

21. Sack, A. T. *et al.* Dynamic Premotor-to-Parietal Interactions during Spatial Imagery. *J. Neurosci.* **28**, 8417–8429 (2008).

22. Corsi, M.-C. *et al.* Functional disconnection of associative cortical areas predicts performance during BCI training. *NeuroImage* **209**, 116500 (2020).

23. Schalk, G., McFarland, D. J., Hinterberger, T., Birbaumer, N. & Wolpaw, J. R. BCI2000: a general-purpose brain-computer interface (BCI) system. *IEEE Trans Biomed Eng* **51**, 1034–1043 (2004).

24. Perdikis, S., Leeb, R. & Millán, J. d R. Subject-oriented training for motor imagery brain-computer interfaces. *Conf Proc IEEE Eng Med Biol Soc* **2014**, 1259–1262 (2014).

25. Ahn, M. & Jun, S. C. Performance variation in motor imagery brain–computer interface: A brief review. *J. Neurosci. Methods* **243**, 103–110 (2015).

26. Gonzalez-Astudillo, J., Cattai, T., Bassignana, G., Corsi, M.-C. & Fallani, F. D. V. Network-based brain–computer interfaces: principles and applications. *J. Neural Eng.* **18**, 011001 (2021).

27. Corsi, M.-C. *et al.* BCI learning induces core-periphery reorganization in M/EEG multiplex brain networks. *J. Neural Eng.* **18**, 056002 (2021).

28. Buch, E. R. *et al.* Parietofrontal integrity determines neural modulation associated with grasping imagery after stroke. *Brain* **135**, 596–614 (2012).

29. Halder, S. *et al.* Neural mechanisms of brain-computer interface control. *NeuroImage* **55**, 1779–1790 (2011).

30. Sarter, M., Givens, B. & Bruno, J. P. The cognitive neuroscience of sustained attention: where top-down meets bottom-up. *Brain Res. Rev.* **35**, 146–160 (2001).

31. Jeunet, C., N'Kaoua, B., Subramanian, S., Hachet, M. & Lotte, F. Predicting Mental Imagery-Based BCI

Performance from Personality, Cognitive Profile and Neurophysiological Patterns. *PLoS ONE* **10**, e0143962 (2015).

32. Benaroch, C. Contribution to the understanding of mental task BCI performances using predictive computational models. (Bordeaux, 2021).

33. Ptak, R., Schnider, A. & Fellrath, J. The Dorsal Frontoparietal Network: A Core System for Emulated Action. *Trends Cogn. Sci.* **21**, 589–599 (2017).

34. Zacks, J. M. Neuroimaging studies of mental rotation: a meta-analysis and review. *J. Cogn. Neurosci.* **20**, 1–19 (2008).

35. Wolpaw, J. R., McFarland, D. J., Vaughan, T. M. & Schalk, G. The Wadsworth Center brain-computer interface (BCI) research and development program. *IEEE Trans. Neural Syst. Rehabil. Eng. Publ. IEEE Eng. Med. Biol. Soc.* **11**, 204–207 (2003).

36. Kay, S. M. *Modern spectral estimation: theory and application*. (Prentice-Hall, 1988).

37. Ramoser, H., Wolpaw, J. R. & Pfurtscheller, G. EEG-Based Communication: Evaluation of Alternative Signal Prediction Methods - EEG-basierte Kommunikation: Evaluierung alternativer Methoden zur Signalprädiktion. *Biomed. Tech. Eng.* **42**, 226–233 (2009).

38. Fischl, B. FreeSurfer. *NeuroImage* **62**, 774–781 (2012).

39. Tadel, F., Baillet, S., Mosher, J. C., Pantazis, D. & Leahy, R. M. Brainstorm: A User-Firendly Application for MEG/EEG Analysis. *Comput. Intell. Neurosci.* **2011**, (2011).

40. Taulu, S. & Simola, J. Spatiotemporal signal space separation method for rejecting nearby interference in MEG measurements. *Phys Med Biol* **51**, 1759–1768 (2006).

41. Bell, A. J. & Sejnowski, T. J. An information-maximization approach to blind separation and blind deconvolution. *Neural Comput* **7**, 1129–1159 (1995).

42. Oostenveld, R. *et al.* FieldTrip: Open Source Software for Advanced Analysis of MEG, EEG, and Invasive Electrophysiological Data, FieldTrip: Open Source Software for Advanced Analysis of MEG, EEG, and Invasive Electrophysiological Data. *Comput. Intell. Neurosci. Comput. Intell. Neurosci.* **2011, 2011**, e156869 (2010).

43. Fuchs, M., Wagner, M. & Kastner, J. Boundary element method volume conductor models for EEG source reconstruction. *Clin. Neurophysiol.* **112**, 1400–1407 (2001).

44. Gramfort, A., Papadopoulo, T., Olivi, E. & Clerc, M. OpenMEEG: opensource software for quasistatic bioelectromagnetics. *Biomed. Eng. OnLine* **9**, 45 (2010).

45. Lin, F.-H. *et al.* Assessing and improving the spatial accuracy in MEG source localization by depth-weighted minimum-norm estimates. *NeuroImage* **31**, 160–171 (2006).

46. Gramfort, A. *et al.* MNE software for processing MEG and EEG data. *NeuroImage* **86**, 446–460 (2014).

47. Desikan, R. S. *et al.* An automated labeling system for subdividing the human cerebral cortex on MRI scans into gyral based regions of interest. *NeuroImage* **31**, 968–980 (2006).

48. Polverino, A. *et al.* Flexibility of Fast Brain Dynamics and Disease Severity in Amyotrophic Lateral Sclerosis. *Neurology* **99**, e2395–e2405 (2022).

49. Levina, A. & Priesemann, V. Subsampling scaling. *Nat. Commun.* **8**, 15140 (2017).

50. Lachaux, J.-P., Rodriguez, E., Martinerie, J. & Varela, F. J. Measuring phase synchrony in brain signals. *Hum. Brain Mapp.* **8**, 194–208 (1999).

51. Destrieux, C., Fischl, B., Dale, A. & Halgren, E. Automatic parcellation of human cortical gyri and sulci using standard anatomical nomenclature. *Neuroimage* **53**, 1–15 (2010).