LinAliFold and CentroidLinAliFold: Fast RNA consensus secondary structure prediction for aligned sequences using beam search methods

Tsukasa Fukunaga[a,*], Michiaki Hamada[b,c]

[a]*Waseda Institute for Advanced Study, Waseda University, Tokyo, 1690051, Japan*
[b]*Department of Electrical Engineering and Bioscience, Graduate School of Advanced Science and Engineering, Waseda University, Tokyo, 1698555, Japan*
[c]*Computational Bio Big-Data Open Innovation Laboratory, AIST-Waseda University, Tokyo, 1698555, Japan*

Abstract

RNA consensus secondary structure prediction from aligned sequences is a powerful approach for improving the secondary structure prediction accuracy. However, because the computational complexities of conventional prediction tools scale with the cube of the alignment lengths, their application to long RNA sequences, such as viral RNAs or long non-coding RNAs, requires significant computational time. In this study, we developed LinAliFold and CentroidLinAliFold, fast RNA consensus secondary structure prediction tools based on minimum free energy and maximum expected accuracy principles, respectively. We achieved software acceleration using beam search methods that were successfully used for fast secondary structure prediction from a single RNA sequence. Benchmark analyses showed that LinAliFold and CentroidLinAliFold were much faster than the existing methods while preserving the prediction accuracy. As an empirical application, we predicted the consensus secondary structure of coronaviruses with approximately 30,000 nt in 5 and 76 minutes by LinAliFold and CentroidLinAliFold, respectively. We confirmed that the predicted consensus secondary structure of coronaviruses was consistent with the experimental results. The source code is freely available at https://github.com/fukunagatsu/LinAliFold and https://github.com/fukunagatsu/CentroidLinAliFold .

---

*Corresponding Author. E-mail address: fukunaga@aoni.waseda.jp

Introduction

RNAs play essential roles in various biological processes, such as transcriptional regulation and nucleotide modification ([1, 2]). RNA function is closely related to their structures, and as a result many studies have been conducted to determine RNA structures experimentally ([3]). However, these experiments are too expensive and time-consuming to perform the large-scale RNA structure analysis; therefore, a fast computational structure prediction analysis is widely used as an alternative approach. Although protein tertiary structures can be predicted with high accuracy using AlphaFold2 ([4]), the prediction of RNA tertiary structures with acceptable performance remains a challenge ([5]). Accordingly, RNA secondary structure prediction analyses are frequently performed, and various secondary structure prediction tools have been developed ([6, 7, 8, 9, 10, 11]).

RNA consensus secondary structure prediction from sequence alignments is a powerful approach   for accurate secondary structure prediction ([12, 13, 14, 15, 16]). These methods improve prediction performance by taking advantage of the fact that evolutionarily conserved base-pairs tend to form secondary structures ([17]). The conventional method is RNAalifold, which predicts a consensus minimum free energy (MFE) structure while including sequence covariation scores in the energy model ([12, 14]). Another representative tool is CentroidAlifold, which computes the centroid structure in the probability distribution of candidate structures based on the maximum expected accuracy (MEA) principle ([15]).

These prediction methods are highly accurate and are widely used by experimental biologists. However, they are too computationally expensive to be applied to long sequences, such as viral RNAs and long non-coding RNAs, because the computational complexities are proportional to the cube of the alignment lengths. One solution to this problem is the local folding method, which reduces the computational time by ignoring long-range base-pair interactions ([18, 19, 20, 21]). This approach enables analysis of RNA secondary structures at the transcriptome level ([22, 23]). However, ignored long-range interactions are often found in natural RNAs, some of which have functional roles such as regulation of splicing or transcription ([24, 25]). For example, the SARS-CoV-2 RNA genome forms 29.8-knt spanning long-range base-pairs that are presumed to contribute to genome replication ([26]).

Another approach for long RNA prediction, LinearFold was recently proposed by Huang *et al.* for fast secondary structure prediction from a single RNA sequence. LinearFold accelerates structure prediction by pruning candidate structures using a beam search method ([27]). In other words, by using heuristics to

obtain approximate solutions, LinearFold can predict secondary structures including long-range interactions, within a reasonable amount of time. Despite the use of the heuristics, Huang *et al.* demonstrated the superior prediction accuracy of LinearFold over the conventional prediction tools, RNAfold and CONTRAFold. The beam search-based acceleration technique is currently applied to various RNA secondary structure analyses, including partition function calculation ([28]), structural alignment ([29]), stochastic sampling ([30]), sequence design ([31]), and pseudoknot prediction ([32, 33]).

In the current study, we developed fast RNA consensus secondary structure prediction tools using beam search methods. We implemented two prediction tools, LinAliFold and CentroidLinAliFold, accelerated methods of RNAalifold and CentroidAlifold by beam search methods, respectively. We confirmed that LinAliFold and CentroidLinAliFold showed comparable prediction accuracy to existing programs and that the two programs were much faster than existing programs.

Methods

The LinAliFold algorithm

We first briefly introduce the RNAalifold algorithm, which outputs a consensus MFE structure from the input alignment data under a thermodynamic energy model incorporating sequence covariation scores ([12, 14]). The prediction algorithm is based on dynamic programming (DP), with time and space complexities of $O(SN^3)$ and $O(N^2)$ for a sequence alignment whose the number of sequences is S and the length is N. As a thermodynamic energy model, RNAalifold uses the same neighborhood energy model as RNAfold, which predicts the MFE structure from a single sequence. RNAalifold is unique as it uses sequence covariation scores for structure prediction.

The sequence covariation score $b(i, j)$ is defined for two alignment columns i and j. $b(i, j)$ is designed to have a lower value when there are more base mutations such that base pairing is conserved in the two columns. Conversely, when gaps or two bases that do not form a base-pair are included in the two columns, the value of $b(i, j)$ is designed to be higher. The sequence covariation score was firstly

designed in RNAalifold as follows ([12]) :

$$b(i, j) = b'(i, j) + \sum_{\alpha \in \mathbf{A}} \begin{cases} 0.0 & \text{if } (\alpha_i, \alpha_j) \in \mathbf{B} \\ 0.25 & \text{if } \alpha_i \text{ and } \alpha_j \text{ are gaps} \\ 1.0 & \text{otherwise} \end{cases}$$

$$b'(i, j) = -\frac{1}{2} \sum_{\substack{\alpha, \beta \in \mathbf{A} \\ \alpha \neq \beta}} \begin{cases} h(\alpha_i, \beta_i) + h(\alpha_j, \beta_j) \\ \quad \text{if } (\alpha_i, \beta_i) \in \mathbf{B} \wedge (\alpha_j, \beta_j) \in \mathbf{B}, \\ 0 \quad \text{otherwise} \end{cases}$$

where $\mathbf{A}$ is the set of sequences in the input alignment and $\mathbf{B} = \{(A, U), (U, A), (C, G), (G, C), (G, U), (U, G)\}$ is the set of possible base-pairs. α_i represents the i-th column in the sequence α. $h(a, b)$ is the Hamming distance. Specifically, $h(a, b) = 0$ and 1 if $a = b$ and $a \neq b$, respectively. We refer to this sequence covariation score model as the simple score model. RNAalifold also provides the RIBOSUM score model, a more sophisticated score design learned from an alignment of SSU ribosomal RNAs ([34, 35, 14]).

We also introduce the beam search method in RNA secondary structure analysis ([27]). As an example, consider evaluating the energy score when a column i forms a base-pair with a column on the 5′ side of the column i. In conventional exact approaches, the energy scores of all columns that can form base-pairs are investigated, and all energy scores are retained for subsequent calculations in the DP. In contrast, the heuristic beam search method evaluates only the energy scores of columns whose scores are retained. Subsequently, the method only maintains the energy scores of the top b columns with the lowest energy scores, and discards the energy scores of the other columns. Beam search heuristics was also applied to the evaluation of multi loop formation. LinearFold achieved significant acceleration by pruning the search space with this beam search, and reduced the time and space complexities from $O(N^3)$ and $O(N^2)$ to $O(Nb\log b)$ and $O(Nb)$. b is the beam size and is a user-defined parameter. To perform the beam search efficiently, LinearFold employed a left-to-right DP instead of a bottom-up DP, which is conventionally used in RNA structural analysis ([36, 37]).

LinAliFold is a program that speeds up RNAalifold by using the beam search method. Specifically, the bottom-up DP in RNAalifold was replaced by the left-to-right DP, and the beam pruning was applied to the DP calculation. Compared with RNAalifold, the time complexity is reduced from $O(SN^3)$ to $O(SNb\log b)$. However, because the sequence covariance scores must be stored in the memory, the space complexity is the same $O(N^2)$ as RNAalifold. In addition, we have slightly modified the calculation method of RNAalifold and LinearFold; this is

described in the Supplementary Material.

The CentroidLinAliFold algorithm

We next present an overview of the CentroidAlifold algorithm ([15]). CentroidAlifold was designed from the viewpoint of MEA, which maximizes the expected prediction accuracy under a probability distribution on candidate solutions. In particular, CentroidAlifold utilizes the γ-centroid estimator ([7]), which is theoretically superior to the frequently used ContraFold MEA estimator ([6]).

CentroidAlifold first computes p^*_{ij}, a base pairing probability (BPP) between two columns i and j, for all column pairs, as follows:

$$p^*_{ij} = \frac{w}{S} \sum_{x \in \mathbf{A}} p^{(x)}_{ij} + (1 - w) p^{(A)}_{ij},$$

where $w \in [0, 1]$ is a mixture weight parameter, $p^{(x)}_{ij}$ is the BPP on an individual sequence x, and $p^{(A)}_{ij}$ is the BPP on the input alignment $\mathbf{A}$. Here, $p^{(x)}_{ij}$ and $p^{(A)}_{ij}$ can be computed using the McCaskill algorithm and the extension of RNAalifold with the time complexities $O(N^3)$ and $O(SN^3)$, respectively.

CentroidAlifold then performed Nussinov-style DP using p^*_{ij} as follows ([38]):

$$M_{i,j} = \begin{cases} M_{i+1,j} \\ M_{i,j-1} \\ M_{i+1,j-1} + (\gamma + 1)p^*_{ij} - 1 \\ \max_k[M_{i,k} + M_{k+1,j}], \end{cases}$$

where $M_{i,j}$ denotes the best score for $\mathbf{A}[i..j]$, a subsequence between i and j on alignment $\mathbf{A}$. γ is a user-defined hyperparameter that balances the positive prediction value (PPV) with the sensitivity (SEN). A higher γ value is expected to increase SEN and decrease PPV. The time and space complexities of DP are $O(N^3)$ and $O(N^2)$. entroidAliFold finally predicted the secondary structure by traceback of the DP matrix. Accordingly, the total time and space complexities of CentroidAlifold were $O(SN^3)$ and $O(N^2)$.

CentroidLinAliFold is the software that speeds up CentroidAlifold by applying the beam search method to each step of CentroidAlifold. The calculation method of $p^{(x)}_{ij}$ using beam search has been proposed as LinearPartition ([28]) with a time complexity $O(Nb^2)$, and the algorithm was reimplemented and incorporated into CentroidLinAliFold. In addition, to calculating $p^{(A)}_{ij}$, we developed a novel beam search-based algorithm with time complexity $O(SNb^2)$ by extending

LinAliFold. The beam search method was not applied to the Nussinov-style DP step because this step empirically requires less computational time when using the threshold method. The threshold method is a fast structure prediction method that uses only p^*_{ij} larger than tha threshold in DP recursion. From the third line of the DP algorithm, we can set the threshold to $\frac{1}{\gamma+1}$ without affecting the prediction results.

Datasets and evaluation measures

We evaluated the prediction performance using eight RNA families provided in the RNAStralign dataset: 5S rRNA, 16S rRNA, group I intron, RNase P, SRP RNA, telomerase RNA, tmRNA, and tRNA ([39]). We randomly selected 5, 10, or 20 sequences for each RNA family, and aligned the sequences by mafft-xinsi v7.490, which performs multiple alignments considering RNA secondary structure information ([40, 41]). We then predicted the consensus secondary structures from the alignments, and evaluated the prediction quality of individual RNA sequences using three metrics: PPV, SEN, and the Matthews correlation coefficient (MCC) with respect to base-pairs ([15]). We prepared five datasets for each evaluation experiment, and measured the average values of the evaluation metrics.

The maximum alignment length of the RNAStralign dataset is approximately 1,500 bp for 16S rRNA, and the alignment length is insufficient to evaluate the computation speed of LinAliFold and CentroidLinAliFold. To test the performance on longer sequences, we created artificial alignment datasets by concatenating multiple alignments of 16S rRNAs two to ten times. For each number of concatenations, we evaluated the average computational time and required memory size for the five datasets. Although the number of concatenations is the same, the alignment lengths differed for each dataset. Therefore, we regarded the average alignment lengths as the representative alignment length for the number of concatenations. In this experiment, the computation was conducted on an Intel Core i5 2.4 GHz CPU with 8GB of memory.

For practical application of long RNA sequences, we predicted consensus secondary structures of coronaviruses with sequence lengths of approximately 30,000 nt. We used the coronavirus genome dataset of 25 sequences compiled by Li *et al.* ([29]). The dataset consisted of 16 SARS-CoV-2, five human SARS-CoV-1, and four bat coronavirus genomes. We could not apply mafft-xinsi to the coronavirus dataset owing to the shortage of memory;therefore, we used mafft with default settings for multiple sequence alignments. An experimentally determined reference RNA secondary structure, we used the structure determined by Ziv *et al.* was used, including long-range RNA-RNA interactions ([26]). The computation

was performed on an Intel Xeon Gold 6154 4.0 GHz CPU with 128GB memory in this experiment ([26]).

We compared the performance of LinAliFold and CentroidLinAliFold with those of RNAalifold and CentroidAlifold, respectively. We also used RNAfold and Centroidfold to predict the secondary structure from a single sequence to compare the prediction performance. For the thermodynamic energy parameter, we used Andronescu's BL* parameter owing to its high prediction accuracy ([42]). As in previous studies, we used 100 and 0.5 as the default values of the beam size b and the mixture weight parameter w, respectively ([15],[27]). We also used the simple score model as the default sequence covariation score model.

Results

Evaluation of prediction accuracy

We first evaluated the prediction accuracy of the six RNA structure prediction tools using the RNAStralign dataset. Fig. 1 and Fig. S1 show the average prediction results for all RNA families. MEA-based tools have multiple prediction results depending on γ, and we selected γ from $\{2^k : -1 \leq k \leq 7, k \in \mathbb{N}\}$. We found that the consensus secondary structure prediction tools were superior to the prediction tools from single sequences, and that the MEA-based tools performed better than the MFE-based tools. These results are consistent with previous studies. In addition, we verified that LinAliFold and CentroidLinAliFold have comparable prediction accuracy to RNAalifold and CentroidAlifold, respectively. These results were independent of the number of sequences in the alignments (Fig. S1).

Table 1 and Table S1-8 show the prediction performance of each RNA family. In this analysis, the hyperparameter γ was automatically determined based on the maximization of the pseudo-expected accuracy for the MCC ([43]). We found that the consensus secondary structure prediction tools performed well. However, the prediction from a single sequence was more accurate for some families, such as group I introns and tmRNAs. This result may be due to inaccurate structural alignments. Additionally, we confirmed that LinAliFold and CentroidLinAliFold have equal or better accuracy than RNAalifold and CentroidAlifold, respectively. In particular, CentroidLinAliFold achieved the best prediction performance with an MCC of 0.702 when the sequence size was 20. These results suggest that the beam search heuristics do not have a negative influence on the prediction accuracy of RNA consensus secondary structure prediction.

Evaluation of computational time and required memory size

We next assessed the computational time required by the developed software (Fig. 2 and Fig. S2). We confirmed that LinAliFold and CentroidLinAliFold could perform the prediction in almost linear computational time with respect to the alignment lengths. In addition, LinAliFold and CentroidLinAliFold were considerably faster than RNAalifold and CentroidAlifold when the alignment lengths were long, and the speed efficiency increased as the alignment lengths increased. For example, with an alignment length of 15,600 nt and sequence size of 20, LinAliFold was 7.8 times faster than RNAalifold. As another example, with an alignment length of 4,680 nt and the sequence size of 20, CentroidLinAliFold was 20.9 times faster than CentroidAlifold.

We also investigated the required memory size for the developed software (Fig. 3 and Fig. S3). The results show that RNAalifold and LinAliFold required almost the same amount of memory size, but CentroidLinAliFold was more memory efficient than CentroidAlifold. This result may be due to differences in implementation rather than differences in the algorithms. We further examined the dependencies of computational time and required memory size on sequence size (Tables S9-10). The computational time increased for both LinAliFold and CentroidLinAliFold as the sequence sizes increased; however, the required memory size did not change significantly.

Analysis of the dependence of the performance on the sequence covariation score model and the beam size

We then analyzed the effects of the sequence covariation score model on the prediction accuracy (Table S11). Note that we could not perform the analysis for CentroidAlifold because this tool does not have the option of changing the sequence covariation score model. We found that the RIBOSUM model outperforms the simple score model with any prediction tool, as described in a previous study ([14]). When comparing the prediction performance for each RNA family using the RIBOSUM model, some families improved the prediction accuracy significantly, and no families showed substantial decreases.

We also estimated the influence of the beam size b on the performance of LinAliFold and CentroidLinAliFold. Tables S12-13 show the MCC changes with beam size b. The prediction accuracy monotonically increased with increasing b, but the performance did not improve significantly over $b = 100$. Tables S14-15 show the changes in the computational time and required memory size with the change in beam size b. We found that the computational time increased but the

required memory size did not change significantly as b increased. These results are consistent with the results of the computational complexity analysis.

Prediction of coronavirus RNA consensus secondary structure

We finally predicted the consensus secondary structures of coronaviruses using LinAlifold and CentroidLinAliFold. For comparison, we used LinearTurboFold, a beam search-based structural alignment and structure prediction tool ([29]). Table 2 shows the computational time and required memory size for the prediction. The computational time include the execution time of MAFFT for our tools; however, most of the required computational time is the structure prediction because MAFFT completed the computation in seven seconds. We demonstrated that our tools could predict the secondary structure of coronaviruses much faster and using less memory than LinearTurboFold. In particular, LinAliFold was 227.3 times faster and 9.3 times more memory efficient than LinearTurboFold. It should be note that the purpose of LinearTurboFold is not exactly the same as that of our tools because our tools do not perform structural alignment.

We compared the predicted and experimentally determined structures of canonical 5′-UTRs, which have been well studied. We confirmed that LinAliFold and CentroidLinAliFold produce predictions consistent with the experimental results, with a few exceptions, such as the shortage in the stem structure of the SL6 motif and the lack of the SL5-3 motif, respectively (Fig. 4 and S4). As shown in a previous study, the prediction from a single sequence cannot predict a consistent structure ([29]), these prediction results demonstrated that RNA consensus secondary structure prediction is an effective approach for viral RNA structure prediction.

The region forming the SL3 motif in the 5′-UTR of the coronavirus can form an alternative structure that takes a long-range interaction spanning 29.8 knt. However, most RNA secondary structure prediction tools predict only one of two different structures. For example, while LinearTurboFold predicted a structure with the long-range interaction, our tools predicted the canonical structure. However, prediction methods that calculate BPPs, such as LinearTurboFold and CentroidAliFold, can estimate the possibility that alternative structures form. Therefore, we examined whether CentroidLinAliFold could capture the potential of the long-range interaction by examining BPPs. Specifically, we calculated the average probabilities that the bases constituting the SL3 motif formed the base pairs of each structure. As a result, we found that the probabilities that the region formed the canonical SL3 structure and the long-range interaction were 37% and

7%, respectively. This result indicates that CentroidLinAliFold can capture the long-range interactions in the coronavirus genome.

Discussion

In this study, we developed LinAliFold and CentroidLinAliFold, which adopt beam search methods to accelerate RNA consensus secondary structure prediction. We investigated the prediction performance using the RNAStralign dataset, and verified that LinAliFold and CentroidLinAliFold have comparable accuracy to the existing programs, RNAalifold and CentroidAlifold. However, the computational speeds of LinAliFold and CentroidLinAliFold were much faster than those of the existing programs, especially for longer alignment lengths. In addition, we demonstrated that these two programs could accurately predict the secondary structures of coronaviruses of approximately 30,000 nt lengths in a reasonable amount of time.

We used the same score models for the sequence covariation score model as in the RNAalifold software was used. However, previous benchmarks suggested that the score models do not have high detection performance because the score models ignore the effects of stacking energy and nucleotide frequency distribution ([44], [45]). Rivas *et al.* recently showed that average product corrected (APC) G-test statistics have robust and sensitive performance for sequence covariation detection ([45]). This result suggests that the use of the APC G-test statistics may be effective for consensus secondary structure prediction. However, because the computational time of the APC G-test statistics scale with the square of the alignment lengths, the simple integration of the APC G-test statistics into LinAliFold or CentroidAlifold may result in the loss of the high speed advantage of these tools. We envision the development of a fast computable and sensitive sequence covariation score model.

The beam search method has been used to increase the speed of various RNA structure informatics tools, and the scope of its application should continue to expand. For example, CentroidHomfold ([46]) and CentroidAlign ([47]), which we previously developed for the structure prediction of a single sequence using homologous sequence information and structural alignment, can also be accelerated by beam search methods. The speedup of existing tools based on beam search methods is essential for genome-scale RNA secondary structural analysis in the research area of RNA informatics.

References

[1] Stefani, G. & Slack, F. J. Small non-coding RNAs in animal development. *Nat Rev Mol Cell Biol* **9**, 219–230 (2008).

[2] Statello, L., Guo, C. J., Chen, L. L. & Huarte, M. Gene regulation by long non-coding RNAs and its biological functions. *Nat Rev Mol Cell Biol* **22**, 96–118 (2021).

[3] Ma, H., Jia, X., Zhang, K. & Su, Z. Cryo-EM advances in RNA structure determination. *Signal Transduct Target Ther* **7**, 58 (2022).

[4] Jumper, J. *et al.* Highly accurate protein structure prediction with AlphaFold. *Nature* **596**, 583–589 (2021).

[5] Miao, Z. *et al.* RNA-Puzzles Round IV: 3D structure predictions of four ribozymes and two aptamers. *RNA* **26**, 982–995 (2020).

[6] Do, C. B., Woods, D. A. & Batzoglou, S. CONTRAfold: RNA secondary structure prediction without physics-based models. *Bioinformatics* **22**, e90–98 (2006).

[7] Hamada, M., Kiryu, H., Sato, K., Mituyama, T. & Asai, K. Prediction of RNA secondary structure using generalized centroid estimators. *Bioinformatics* **25**, 465–473 (2009).

[8] Reuter, J. S. & Mathews, D. H. RNAstructure: software for RNA secondary structure prediction and analysis. *BMC Bioinformatics* **11**, 129 (2010).

[9] Lorenz, R. *et al.* ViennaRNA package 2.0. *Algorithms Mol Biol* **6**, 26 (2011).

[10] Singh, J., Hanson, J., Paliwal, K. & Zhou, Y. RNA secondary structure prediction using an ensemble of two-dimensional deep neural networks and transfer learning. *Nat Commun* **10**, 5407 (2019).

[11] Sato, K., Akiyama, M. & Sakakibara, Y. RNA secondary structure prediction using deep learning with thermodynamic integration. *Nat Commun* **12**, 941 (2021).

[12] Hofacker, I. L., Fekete, M. & Stadler, P. F. Secondary structure prediction for aligned RNA sequences. *J Mol Biol* **319**, 1059–1066 (2002).

[13] Kiryu, H., Kin, T. & Asai, K. Robust prediction of consensus secondary structures using averaged base pairing probability matrices. *Bioinformatics* **23**, 434–441 (2007).

[14] Bernhart, S. H., Hofacker, I. L., Will, S., Gruber, A. R. & Stadler, P. F. RNAalifold: improved consensus structure prediction for RNA alignments. *BMC Bioinformatics* **9**, 474 (2008).

[15] Hamada, M., Sato, K. & Asai, K. Improving the accuracy of predicting secondary structure for aligned RNA sequences. *Nucleic Acids Res* **39**, 393–402 (2011).

[16] Tagashira, M. & Asai, K. ConsAlifold: considering RNA structural alignments improves prediction accuracy of RNA consensus secondary structures. *Bioinformatics* **38**, 710–719 (2022).

[17] Puton, T., Kozlowski, L. P., Rother, K. M. & Bujnicki, J. M. CompaRNA: a server for continuous benchmarking of automated methods for RNA secondary structure prediction. *Nucleic Acids Res* **41**, 4307–4323 (2013).

[18] Bernhart, S. H., Hofacker, I. L. & Stadler, P. F. Local RNA base pairing probabilities in large sequences. *Bioinformatics* **22**, 614–615 (2006).

[19] Kiryu, H., Kin, T. & Asai, K. Rfold: an exact algorithm for computing local base pairing probabilities. *Bioinformatics* **24**, 367–373 (2008).

[20] Fukunaga, T. *et al.* CapR: revealing structural specificities of RNA-binding protein target recognition using CLIP-seq data. *Genome Biol* **15**, R16 (2014).

[21] Kawaguchi, R. & Kiryu, H. Parallel computation of genome-scale RNA secondary structure to detect structural constraints on human genome. *BMC Bioinformatics* **17**, 203 (2016).

[22] Agarwal, V., Bell, G. W., Nam, J. W. & Bartel, D. P. Predicting effective microRNA target sites in mammalian mRNAs. *Elife* **4**, e05005 (2015).

[23] Fukunaga, T. & Hamada, M. RIblast: an ultrafast RNA-RNA interaction prediction system based on a seed-and-extension approach. *Bioinformatics* **33**, 2666–2674 (2017).

[24] Raker, V. A., Mironov, A. A., Gelfand, M. S. & Pervouchine, D. D. Modulation of alternative splicing by long-range RNA structures in Drosophila. *Nucleic Acids Res* **37**, 4533–4544 (2009).

[25] Lai, W. C. *et al.* mRNAs and lncRNAs intrinsically form secondary structures with short end-to-end distances. *Nat Commun* **9**, 4328 (2018).

[26] Ziv, O. *et al.* The short- and long-range RNA-RNA interactome of SARS-CoV-2. *Mol Cell* **80**, 1067–1077 (2020).

[27] Huang, L. *et al.* LinearFold: linear-time approximate RNA folding by 5'-to-3' dynamic programming and beam search. *Bioinformatics* **35**, i295–i304 (2019).

[28] Zhang, H., Zhang, L., Mathews, D. H. & Huang, L. LinearPartition: linear-time approximation of RNA folding partition function and base-pairing probabilities. *Bioinformatics* **36**, i258–i267 (2020).

[29] Li, S. *et al.* LinearTurboFold: Linear-time global prediction of conserved structures for RNA homologs with applications to SARS-CoV-2. *Proc Natl Acad Sci U S A* **118**, e2116269118 (2021).

[30] Zhang, H., Zhang, L., Li, S., Mathews, D. H. & Huang, L. LazySampling and LinearSampling: Fast stochastic sampling of RNA secondary structure with applications to SARS-CoV-2. *bioRxiv* (2021).

[31] Zhang, H. *et al.* Algorithm for optimized mrna design improves stability and immunogenicity. *arXiv* (2020).

[32] Zhang, L., Zhang, H., Mathews, D. H. & Huang, L. Threshknot: Thresholded probknot for improved rna secondary structure prediction. *arXiv* (2019).

[33] Sato, K. & Kato, Y. Prediction of RNA secondary structure including pseudoknots for long sequences. *Brief Bioinform* **23**, bbab395 (2022).

[34] Klein, R. J. & Eddy, S. R. RSEARCH: finding homologs of single structured RNA sequences. *BMC Bioinformatics* **4**, 44 (2003).

[35] Wuyts, J., Perrière, G. & Van De Peer, Y. The European ribosomal RNA database. *Nucleic Acids Res* **32**, D101–103 (2004).

[36] Tomita, M. Graph-structured stack and natural language parsing. In *26th Annual Meeting of the Association for Computational Linguistics*, 249–257 (1988).

[37] Huang, L. & Sagae, K. Dynamic programming for linear-time incremental parsing. In *Proceedings of the 48th Annual Meeting of the Association for Computational Linguistics*, 1077–1086 (2010).

[38] Nussinov, R., Pieczenik, G., Griggs, J. R. & Kleitman, D. J. Algorithms for loop matchings. *SIAM Journal on Applied mathematics* **35**, 68–82 (1978).

[39] Tan, Z., Fu, Y., Sharma, G. & Mathews, D. H. TurboFold II: RNA structural alignment and secondary structure prediction informed by multiple homologs. *Nucleic Acids Res* **45**, 11570–11581 (2017).

[40] Tabei, Y., Tsuda, K., Kin, T. & Asai, K. SCARNA: fast and accurate structural alignment of RNA sequences by matching fixed-length stem fragments. *Bioinformatics* **22**, 1723–1729 (2006).

[41] Katoh, K. & Standley, D. M. MAFFT multiple sequence alignment software version 7: improvements in performance and usability. *Mol Biol Evol* **30**, 772–780 (2013).

[42] Andronescu, M., Condon, A., Hoos, H. H., Mathews, D. H. & Murphy, K. P. Computational approaches for RNA energy parameter estimation. *RNA* **16**, 2304–2318 (2010).

[43] Hamada, M., Sato, K. & Asai, K. Prediction of RNA secondary structure by maximizing pseudo-expected accuracy. *BMC Bioinformatics* **11**, 586 (2010).

[44] Lindgreen, S., Gardner, P. P. & Krogh, A. Measuring covariation in RNA alignments: physical realism improves information measures. *Bioinformatics* **22**, 2988–2995 (2006).

[45] Rivas, E., Clements, J. & Eddy, S. R. A statistical test for conserved RNA structure shows lack of evidence for structure in lncRNAs. *Nat Methods* **14**, 45–48 (2017).

[46] Hamada, M., Sato, K., Kiryu, H., Mituyama, T. & Asai, K. Predictions of RNA secondary structure by combining homologous sequence information. *Bioinformatics* **25**, i330–338 (2009).

[47] Hamada, M., Sato, K., Kiryu, H., Mituyama, T. & Asai, K. CentroidAlign: fast and accurate aligner for structured RNAs by maximizing expected sum-of-pairs score. *Bioinformatics* **25**, 3236–3243 (2009).

[48] Darty, K., Denise, A. & Ponty, Y. VARNA: Interactive drawing and editing of the RNA secondary structure. *Bioinformatics* **25**, 1974–1975 (2009).

Acknowledgments

Computations were partially performed on the NIG supercomputer at ROIS National Institute of Genetics and the SHIROKANE supercomputer at human genome center, the Institute of Medical Science, The University of Tokyo.

Funding

This work was supported by the Japan Society for the Promotion of Science (grant numbers JP19K20395, JP20H05582 and JP22H04891 to T.F.).

Figures

Figure 1: Prediction performance of RNA secondary structure on the RNAStralign dataset with 20 sequences. The x-axis and the y-axis represent PPV and SEN, respectively. Symbols and colors used above represent: RNAfold (black crosses), CentroidFold (black squares), RNAalifold (red crosses), CentroidAlifold (red circles), LinAliFold (blue squares), and CentroidLinAliFold (blue triangles).

Figure 2: Evaluation of the computational time for a sequence size of 20. The x- and y-axis represent the alignment lengths (nt) and computational time (s), respectively. The lines represent RNAalifold (red dashed), CentroidAlifold (red solid), LinAliFold (blue dashed), and CentroidLinAliFold (blue solid). The exact computational time was not measured when it exceeded 2 hours.

Figure 3: The required memory size was evaluated for a sequence size of 20. The x- and y-axis represent the alignment lengths (nt) and required memory size (GB), respectively. The lines represent RNAalifold (red dashed), CentroidAlifold (red solid), LinAliFold (blue dashed), and CentroidLinAliFold (blue solid). The required memory size was not measured when computational time exceeded 2 hours.

Figure 4: (A) A predicted RNA consensus secondary structure of coronavirus 5′-UTR by CentroidLinAliFold. (B) An experimentally determined secondary structure of the coronavirus. Graphical views were created using VARNA ([48]).

Tables

Table 1: The MCC results of prediction accuracy for each RNA family when the sequence size was 20

RNA Family	RNAfold	CentroidFold	RNAalifold	LinAliFold	CentroidAlifold	CentroidLinAliFold
5s rRNA	0.729	0.676	0.885	0.898	0.885	**0.903**
16S rRNA	0.434	0.520	0.684	0.656	**0.734**	0.720
group I intron	0.708	**0.752**	0.598	0.632	0.627	0.644
RNaseP	0.568	0.647	0.616	0.596	0.635	**0.654**
SRP RNA	0.643	0.640	0.596	0.645	0.602	**0.649**
telomerase RNA	0.455	0.493	0.436	0.555	0.551	**0.572**
tmRNA	0.512	**0.547**	0.382	0.475	0.460	0.505
tRNA	0.809	0.784	0.962	**0.966**	0.962	**0.966**
average	0.607	0.632	0.645	0.678	0.682	**0.702**

The bold values are the highest scores in each row.

Table 2: The computational time and required memory size for coronavirus secondary structure prediction

software	computational time	required memorory
LinAliFold	4m48s	4.7G
CentroidLinAliFold	1h15m24s	14.9G
LinearTurboFold	18h11m1s	44.1G