Machine learning approaches for classification of *Plasmodium falciparum* life cycle stages using single-cell transcriptomes

Swarnim Shukla, Soham Choudhuri, Bhaswar Ghosh*

Center for Computational Natural Sciences and Bioinformatics
International Institute of Information Technology Hyderabad, 500032, India
e-mail: swarnim.shukla@research.iiit.ac.in, soham.choudhuri@research.iiit.ac.in,
bhaswar.ghosh@iiit.ac.in
*Corresponding author

Abstract

Malaria spread by female anopheles mosquito is a highly fatal disease widespread in many parts of the world, causing 0.4 million deaths globally. Vital gene expressions form the basis in the detection of malaria infection levels. Quantification of malaria parasite infected RBCs and classification of its life cycle stages are done at macroscopic level by experts, for making informed decisions. Off late multiple computational approaches have been proposed to circumvent the problem of dimensionality leading to accurate predicted results. In this work a dimensionality reduction technique based on Genetic Algorithm (GA) is applied on *P. falciparum* single-cell transcriptomics to arrive at an optimized subset of features from the larger dataset. Features are chosen based on their class variants considering increased efficiency and accuracy, to separately transform the selected elements into a lower dimension. For the classification of the life cycle of malaria parasite based on single cell transcriptome data, a three-pronged approach employing the multiclass Support Vector Machine (SVM), Logistic Regression (LR) and Random Forest (RF) techniques is used. Further, we constructed protein interaction networks of the genes identified by the feature selection method and elucidate the role of the proteins in progression of the parasite through it's life cycle. Our approach presents a novel protocol to implement ML techniques on scRNA seq datasets and subsequently harnessing the extracted information for biomarker/drug target detection.

Keywords: malaria, life cycle classification, dimensionality reduction, genetic algorithm,

Introduction

Malaria is a deadly disease caused by the Plasmodium parasite and is transmitted through the bite of a female Anopheles mosquito. This plasmodium attacks the red blood cells (RBCs) and the degree of malaria can be estimated by the quantity of infected RBCs [1]. The complex life cycle of malaria parasites features diverse developmental strategies, each of which is uniquely adapted to thrive in the particular host environment. Six Plasmodium species cause human malaria, with majority of the estimated 0.4 million annual deaths caused by *Plasmodium falciparum* (*P. falciparum*). Blood stage development begins when a newly released, extracellular parasite (a merozoite) invades an erythrocyte, establishing the ring stage of infection, progressing to the trophozoite stage. During this stage the infected erythrocyte is extensively modified to enable parasite proliferation. Thereafter the parasite divides to form a connected group of daughter cells, called schizont, which eventually lyses the host erythrocyte, releasing the newly formed merozoites to invade new erythrocytes. These steps are collectively known as the intraerythrocytic developmental cycle (IDC) [2]. Malaria symptoms include high fever and headache and in some severe cases even seizures and death are caused. Malaria mostly affects the economically weak communities of the world, where medical treatment is not readily available. For a quick and successful recovery of any patient, it is vital to diagnose and treat the malarial infection early. If the malaria life cycle stages are somehow ascertained then the treatment of disease becomes easier. Experienced medical professionals frequently examine a large number of blood films to detect malaria infection. Microscopists normally visualize the thick and thin blood smears to identify a disease or its cause. However, the accuracy depends upon smear quality and the expertise in classifying and counting the parasite and non-parasite cells. It is fairly challenging to number the parasites and infected RBCs manually and needs an expert microscopist for quality diagnosis [3].
Recent advances in single cell RNA-sequencing (sc-RNA)techniques paved new ways to characterize gene expression changes during the development stages of the plasmodium life cycle [4, 5]. Analysis of the gene expression regulation may allow us to identify

new diagnostics marker as well as potential target for a new drug. Indeed, many studies have already been conducted in the last few years by utilizing sc-RNA experiments for plasmodium falciparum. One of the central advantages of employing sc-RNA methods is the scope of exploring cell to cell heterogeneity in the population by uncovering hidden variability in gene expression among single cells [6, 5, 7] . In fact, recent studies have elucidated the role of heterogeneity in enabling a small fraction of plaosmodium population inside the human host to remain ready to enter into the mosquito host by making transition to gametogenesis stage [8]. Similarly, heterogeneity plays crucial role in plasmodium stress response inside the RBC [9]. However, the diagnostics of scRNA-Seq is challenging as its outcome suffers from lack of fit due to high dimensional gene expression data. Advanced computational skills are needed to study and process the massive volume of proteomic and genomic data obtainable freely from several repositories [10, 11] and harness them to reveal new biological insights.

The dataset contains redundant characteristics that behave as noise during model training. As a result, classification performance is degraded and computing time is increased. Dimensionality Reduction (DR) techniques are required to eliminate redundancy and to retrieve irrelevant details that hinder performance. There are two methods for reducing the dimensionality of data: Feature Extraction and Feature Selection. Feature selection is further divided into filter, wrapper, and embedded methods [12]. In the filter method, mathematical measures are used to select the optimal features. Wrapper is a feedback method that uses a machine-learning algorithm to help choose the best features. The embedded approach is a hybrid of the filter and wrapper methods. This paper proposes a wrapper-based feature selection technique using the Genetic Algorithm to select the optimal features and remove the redundant noise in the dataset. In order to evaluate the performance of these features, SVM, LR, and RF classification models are used.

The main objective of our study is to select top-ranked genes from the scRNA-seq profiles at different stages of the plasmodium falciparum life cycle inside infected RBC. We employ supervised learning algorithm coupled with feature selection algorithms to extract most relevant genes in predicting the life cycle stages of plasmodium inside RBC. The first stage of the proposed model is to optimize the quality data from the data set by removing the redundant, noisy, and irrelevant genes (features). From the literature review it can be concluded that genetic algorithm (GA) showed that better performance

than the other selection algorithms and thus, prominently used for feature selection from high dimensional data sets.

Hence, GA is employed in our proposed approach as the search algorithm in the feature selection process. This subset can be further utilized in the second stage of the process, Classification, to produce high classification accuracy. We tested the subsets using three classifiers: SVM, LR, and RF to ensure the investigation is carried out rigorously. The combination of first and second stages of the proposed model will achieve a better identification of the different Malaria Life Cycle stages. Additionally, the feature selection method is able to identify genes which significantly change expression across the life cycle stages. We constructed the protein interaction network of these genes and performed a set of topological analysis to provide hierarchies according to importance of the genes in the network. These genes can be used for diagnosis and drug targets. Our study presents a theoretical framework to select diagnosis markers and drug targets by implementing ML techniques on sc-RNA-seq data.

Results

The single cell RNA-seq dataset utilized here is freely accessible through a user-friendly web interface (www.sanger.ac.uk/science/tools/mca/mca/) [13]. Our dataset has 5066 rows and 6737 columns. Each row corresponds to RNA-seq read counts of a gene and each column corresponds the same for a single cell. We have 5066 feature in our dataset. Additionally, each cell is assigned one label among the four different malaria life cycle stages (early troph, late troph, ring, schizont). Thus, we set out to utilize classification ML algorithms (Material and methods) which would allow us to predict the life cycle stage of a cell based on the gene expression pattern.

Classification without feature selection

We first implement SVM, LR and RF algorithms to classify the cells into the four different stages by including all the genes. In order to calculate the prediction accuracy, we randomly selected 80 % of the cells as training set and 20 % of the cells are chosen for calculating the desired accuracy. Figure 1 shows the accuracy of SVM, LR, and RF. This is the baseline for our experiment. Without Feature selection, SVM performed

best with classification accuracy measured this 91%. The least accurate algorithm was Random Forest (88%) whilst the level of performance of LR (90%) was acceptable.

Figure 1: Classification accuracy of different models without feature selection. The classification accuracy are shown for different machine learning protocols namely SVM, LR and RF

As listed in Table 1, the following best F1 scores were determined: ring 96%, late_troph 94%, early_troph 86% and schizont 80%.

F1 scores(%) Malaria Life Cycle Stage	SVM	LR	RF
early_troph	0.86	0.85	0.79
late_troph	0.94	0.91	0.91
ring	0.94	0.96	0.95
schizont	0.80	0.74	0.77

Table 1: F1 scores of different models of the different classes without Feature Selection

Features selection

From the data set, we observed that there are many genes which do not change expression levels across the life cycle stages. Thus, a feature selection algorithms would drastically reduce the dimension and would allow us to extract important genes, the expression of which are responsible for the life cycle changes. In order to select the features, a genetic algorithm (GA) based– pipeline is implemented (Material and methods for details). The GA pipeline outputs the most optimal features and has removed the redundant features.

Table 2 shows the details of the number of features. The initial number of features was **5066** out of which a subset of size **336** was selected using the GA. The dataset was reduced by **93.3%**.

	Number of Features
Full Dataset	5066
Features Selected after GA pipeline	336

Table 2: Numbers of Features selected

Classification with feature selection

This section shows the detail of the classification results with feature selection stage. Figure 2 shows the accuracy of SVM, LR, and RF. SVM performed best with classification accuracy measured this 91%. RF and LR both gave this 90% accuracy. The sections 5.4.1, 5.4.2, and 5.4.3 shows the test results of the SVM, LR, and RF models respectively.

Figure 2: Classification accuracy of different models with feature selection. The classification accuracy are shown for different machine learning protocols namely SVM, LR and RF after selection of the 336 feature following genetic algorithm.

Using multiclass Support Vector Machine

Table 3 presents the precision, recall, and f1 scores of the SVM model for the four different classes. For late_troph and ring, we have achieved an f1 score of 0.93 and 0.94,

respectively. We got an average f1 score for early_troph at 0.86. Schizont was the worst, at 0.78.

Metric (%) / Malaria life cycle stage	precision	recall	F1-score
early_troph	0.92	0.82	0.86
late_troph	0.91	0.95	0.93
ring	0.90	0.99	0.94
schizont	0.92	0.67	0.78

Table 3: Test results of SVM model with feature selection

Using Logistic Regression

Table 4 presents the precision, recall, and f1 scores of the LR model for the four different classes. For late_troph and ring, we have achieved an f1 score of 0.91 and 0.95, respectively. We got an average f1 score for early_troph at 0.87. Schizont was the worst, at 0.74.

Metric (%) / Malaria Life Cycle Stage	precision	recall	F1-score
early_troph	0.87	0.86	0.87
late_troph	0.90	0.93	0.91
ring	0.95	0.96	0.95
schizont	0.83	0.66	0.74

Table 4: Test results of LR model with feature Selection

Using Random Forest

Table 5 presents the precision, recall, and f1 scores of the RF model for the four different classes. For late_troph and ring, we have achieved an f1 score of 0.92 and 0.95, respectively. We got an average f1 score for early_troph at 0.83. Schizont was the worst at, 0.75.

Metric (%) Malaria life cycle stage	precision	recall	F1-score
early_troph	0.91	0.77	0.83
late_troph	0.88	0.97	0.92
ring	0.93	0.97	0.95
schizont	0.93	0.63	0.75

Table 5: Test results of RF model with feature selection

Confusion matrix of the three models

Figure 3: Confusion matrix of the models. The heatmaps display the confusion matrix in predicting the four different stages as indicated after feature selection for three different models (A) SVM (B) LR (C) RF models

Figure 3 shows the confusion matrix of the three models. The confusion matrix for the SVM model shows that 32 samples were predicted as late_troph which should have been labelled as early_troph. Similarly, 37 samples were predicted as late_troph which were otherwise labelled as schizont. For late_troph class, 15 samples were misclassified as

early_troph. For ring class, 2 samples were misclassified as early_troph.

The confusion matrix for the LR model shows that 25 samples were predicted as late_troph which should have been labelled as early_troph. Similarly, 35 samples were predicted as late_troph which were otherwise labelled as schizont. For late_troph class, 29 samples were misclassified as early_troph. For ring class, 14 samples were misclassified as early_troph.

The confusion matrix for the RF model shows that 54 samples were predicted as late_troph which should have been labelled as early_troph. Similarly, 42 samples were predicted as late_troph which were otherwise labelled as schizont. For late_troph class, 19 samples were misclassified as early_troph. For ring class, 6 samples were misclassified as early_troph. These were some of the common misclassifications in all three models.

A comparison of classification without vs with feature selection.

Figure 4: Classification accuracy with feature selection vs without feature selection.The bar graphs display a comparison between the values of accuracy for the three models and for classification with feature selection and without feature selection as indicated

Figure 4 shows the accuracy of classification without feature selection vs. classification with feature selection. We can see that we have reduced our feature set from 5066 to 336. Using these 336 features, we have achieved an accuracy of 91% in the SVM model, 90% in the LR model, and 90% in the RF model. We have improved the accuracy of the RF

model and have achieved similar results in the SVM and LR models.

For the SVM model, without feature selection, we got a f1 score of 0.86, 0.94, 0.94, and 0.80, where as with feature selection, we got a f1 score of 0.86, 0.93, 0.94, and 0.78 for early_troph, late_troph, ring, and schizont, respectively. For the LR model, without feature selection, we got a f1 score of 0.85, 0.91, 0.96, and 0.74, where as with feature selection, we got a f1 score of 0.87, 0.91, 0.95, and 0.74 for early_troph, late_troph, ring, and schizont, respectively. For the RF model, without feature selection, we got a f1 score of 0.79, 0.91, 0.95, and 0.77, where as with feature selection, we got a f1 score of 0.83, 0.92, 0.95, and 0.75 for early_troph, late_troph, ring, and schizont, respectively. We can see from the results that just by using the 336 features we have achieved similar f1 scores for all the four classes across all three models. This proves the robustness of the features selected from the GA pipeline. For the early_troph class, we have achieved the best f1 score of 0.87 from the LR model. For the late_troph class, we have achieved the best f1 score of 0.93 from the SVM model. For the ring class, we have achieved the best f1 score of 0.95 from both the SVM and RF models. Schizont was the worst, with an f1 score of 0.78 from the SVM model. This could be because less number of instances of the schizont class in the dataset compared to other classes.

We also calculated the mutual information (MI) between the predicted labels and the true labels of the three models using the joint probabilities from confusion matrix (see Subsection). For instance, C(1,1) of the confusion matrix represents the the joint probability P(X,Y) where X= true label of early troph and Y corresponds to correctly predicted early troph. Similarly C(1,2) would reflect the joint probability P(X,Y) where X= true label of early troph while Y= incorrectly predicted to be late troph. Figure 5 shows the comparison of MI with and without feature selection. One of the advantages of displaying the accuracy using mutual information is that the upper limit of the mutual information is exactly known. So, the accuracy of the model can be compared with the ideal case. In our case, since the number of labels is four, the maximum possible mutual information for an error free case is 2 bits, however maximum information acquired by the models is 1.28 bits here.

Figure 5: Mutual information with and without feature selection. The bar graphs display a comparison between the values of mutual information in bits between predicted and actual labels for the three models and for classification with feature selection and without feature selection as indicated

Classification with randomly selecting 336 features

In order to test whether the GA based feature selection algorithm is able to select the features appropriately, We randomly chose 336 features from our dataset and evaluated the prediction accuracy using the SVM, LR, and RF models. We achieved accuracy of 0.83, 0.83, and 0.83 for the models. Table 6shows the f1 scores of the different classes for the three models.

F1 scores Malaria Life Cycle Stage	SVM	LR	RF
early_troph	0.69	0.70	0.68
late_troph	0.86	0.85	0.87
ring	0.89	0.89	0.89
schizont	0.77	0.72	0.75

Table 6: F1 scores of different models of the different classes with randomly selecting 336 features

The accuracy and the f1 scores of this experiment were lower compared to the classification results with feature selection using the GA pipeline. This results demonstrate the legitimacy of the feature selection method.

Construction and analysis of protein-protein interaction network

Understanding protein-protein interactions (PPIs) is critical for cell physiology in normal and pathological states because they are required for practically every process in a cell [14]. Protein-protein interaction networks (PPIN) are graphs of the physical interactions between proteins in a cell. Protein-protein interaction happens in specified binding areas and serves a specific function. The feature selection method provided us with 336 proteins in Plasmodium falciparum. We used the Search Tool for the Retrieval of Interacting Genes/Proteins database (STRING 11.0b) [15] to construct the PPI network associated with these proteins. STRING can then construct a PPI network containing all of these proteins and their connections. Their interactions were generated with high confidence from high-throughput lab experiments and prior information in curated databases (sources: experiments, databases; Scores 0.90). The network construction shows a set of highly connected modules (Figure 6).

The topological analysis of the PPI network

Various topological measures are generally used to evaluate the both global and node characteristics in the PPI networks, including degree (k), between centrality (BC), eccentricity, closeness centrality (CC), eigenvector centrality (EC), and clustering coefficient [16]. Here, highest degree nodes are identified using degree distribution. Additionally, We have used markov clusting algorithm (MCL) to find clusters in the network. Among these clusters, we identified a clusters which also contains the node with highest degree and high betweenss centrality.

This PPIN is composed of of 334 nodes with number of edges: 571, average node degree: 3.42, avg. local clustering coefficient: 0.304, expected number of edges: 519 PPI enrichment p-value: 0.013. We can see that proteins in red cluster has highest degree and high betweenness centrality. So, we can consider red cluster as disease module. We have analysed other topological properties like degree, BC, eccentricity, CC, EC, clustering coefficient, etc of this Red cluster using Gephi [17].

Figure 6: The protein interaction of selected features. The graph shows the protein protein interaction network of the 336 proteins selected by the feature selection method. The different colors indicate different identified clusters.

Proteins name	Degree	betweeness centrality	Description
C6KSS5	27	78.99	conserved Plasmodium protein, unknown function
Q8I2V4	27	73.99	Regulator of chromosome condensation-PP1-interacting protein
C6KSY0	26	124.65	AP2 domain transcription factor, putative(1. regulation of transcription, DNA-templated 2. DNA-binding transcription factor activity)
Q8IKV6	26	65.30	similar to Rhoptry neck protein 2(function unknown)

Q8IIK5	26	36.76	Rhoptry neck protein 4 (Antigen binding)
Q8IEA7	26	35.61	Uncharacterized protein
Q8I3V1	24	106.02	Glideosome-associated protein 40, putative
C0H5C8	24	41.29	Protein kinase domain-containing protein (protein kinase activity and ATP binding)
C0H584	24	30.43	Protein MAM3, putative (magnesium ion homeostasis).

Table 7: Topological analysis of the PPI network of the selected proteins

The proteins in above table from red cluster has high degree and betweeness centrality. In this cluster, we have, number of nodes: 37, number of edges: 272, average node degree: 14.7 avg. local clustering coefficient: 0.79, expected number of edges: 128 PPI enrichment p-value: $< 1.0e\text{-}16$. We can see that this cluster has less node with high interaction and high clustering coefficient. So, this is an small world network. We can see from the above table that C6KSS5, Q8I2V4, C6KSY0 and Q8IKV6 has highest degree with high bc .We considered these four protein as the hubs or bottlenecks as this nodes has high degree (k) and BC. We have chosen 7 more proteins that has high degree and bc to consider them backbone of the PPIN. These proteins are C6KSS5, Q8I2V4, C6KSY0, Q8IKV6, Q8IIK5, Q8IEA7, Q8I3V1, C0H5C8, C0H584. These 9 proteins are highly connected in PPIN and has control over the network. Next we have checked functions of all these proteins.

Expression profile of the selected features

The analysis above provides us a set of proteins which are associated with the progression of the malaria pathogen through different stages of the life cycle. Thus, the expression pattern of these proteins would elicit the identity of the stages. In order to investigate the overall expression pattern of the genes across the different stages, we extracted the

selected 336 features from the dataset. For each feature, we find the average RNA-seq read counts for all the four classes(early_troph, late_troph, schizont and ring). The average values are then transformed into log scale. We observed that genes fall into different clusters according to the expression patterns (Figure 7) and also the expression patterns vary among the stages. For instance, the genes at the bottom have a very low expression in ring phase. Similarly, genes at the top cluster are displaying low expression for all stages. These expression patterns may be harnessed to look for specific markers for different stages.

Figure 7: Expression Profile of the selected genes across the different stages. The heatmap shows the average RNA-count of the selected 336 genes across the different stages as indicated. A hierarchical clustering is performed on the expression levels in order group genes with similar expression patterns indicated by the dendogram.

Discussion and outlook

The present study has proposed a two-stage model for feature selection and classification which has been shown to improve the classification of the different stages of the Malaria Life Cycle. This was achieved by removing the irrelevant features from the total data set considered for analysis. The study's main finding is that using a feature selection procedure before applying a classification algorithm results in more accurate predictions. The use of GA as a feature selection process significantly reduced the number of features included in the dataset.

Various machine learning (ML) approaches have been proposed to yield more accurate results. Karthik and Sudha [18], reviewed ML methods for classifying gene expression model or computational analytical structure for complicated diseases, by identifying several differentially expressed gene techniques. Authors in [19] used the Convolutional Neural Networks (CNNs) based deep learning models for attribute extraction and categorization. For achieving higher categorization accuracy, they selected certain dominating features including size, colour, shape and cell count from the images. Similarly, a more effective two stage approach based on CNNs on a larger dataset was also proposed by [20]. It remains an especially challenging task to distinguish the multiple growth stages of parasites. Seng et al. [21] developed a deep learning approach for the recognition of multi-stage malaria parasites in blood smeared images using a novel deep transfer graph convolutional network (DTGCN). They reported higher accuracy and effectiveness compared to a wide range of state-of-the-art approaches.

Numerous ML approaches have been proposed in the literature to enhance gene expression data classification such as clustering, classification, dimensional reduction, among others [22] . Training of ML models using initial high-dimensional features performs unsatisfactorily in practice and may result in network over-fitting and increased redundant information. This problem was addressed using random forests classifier in [23, 24]. Hossain et al. [25] designed an effective variational quantum circuit (VQC-based) approach to recognize the existence of malaria from RBC images through the classification of optimized feature set extracted from them. Murad et al. [26] used algorithms based on multifilter and hybrid approaches to feature selection leading to accuracy in excess of 90%. Mei et al. [27] suggested a dimensionality reduction method for classifying tumour gene expression data. Arowolo et al. [28] and Li et al. [29] proposed a

dimensionality reduction approach for classifying gene expression.

To overcome the dimensionality problem, Rokach et al. devised a genetic algorithm-based feature selection method. They evaluated the fitness function of several, obvious tree classifiers using a new encoding approach [30]. Zhang et al. proposed a classifier ensemble with feature selection based on GA. The authors of this work created a new hybrid method that combines a multi-objective genetic algorithm with an ensemble of classifiers. The GA-ensemble approach was tested on a variety of datasets and its performance was compared using a variety of classifiers [31]. Cheng-Lung Huang [32] suggested a feature selection method based on GA and SVM optimization. The ultimate goal was to improve the SVM classification accuracy while optimising the feature subset and parameters. Chaung et al. [33] employed a hybrid technique that began with a genetic algorithm with a dynamic variable to pick a sample of genes, which were then ranked using chi square analysis, and the level of accuracy of the selection was assessed using SVM. Shutao et al [34] used Particle Swarm optimisation and GA in order to perform highly accurate classification. The authors in [35] achieved a classification accuracy of 90.32 % using GA for feature selection and a SVM Classifier.

For further research the hybrid methods for feature selection, impact of parameter fine tuning on various algorithms'level and use of other methods including Ensemble Learning may be attempted. Next, we have constructed protein-protein interaction network between our proteins (which we get after using feature selection algorithm) and we have done network analysis on this protein-protein interaction network using STRING 11.0b and Gephi software. Various topological measures are estimated to evaluate the node characteristics in the PPI networks, including degree (k), between centrality (BC), eccentricity, closeness centrality (CC), eigenvector centrality (EC), and clustering coefficient [16]. We found degree and betweeness centrality of each protein though this calculation. Proteins having high degree and betweeness centrality tend to assert more control over the network function. These proteins can be considered as drug targets for future studies.

Material and Methods

Background of the dataset

The data are freely accessible as a processed dataset through a user-friendly web interface (www.sanger.ac.uk/science/tools/mca/mca/) [13]. Our dataset has 5066 rows and 6737 columns. Each row corresponds to single cell and each column corresponds to a gene. We have 5066 feature in our dataset. We have four different malaria life cycle stages (early troph, late troph, ring, schizont).

Tools Utilized

Ada, the High Performance Computing Data Center of International Institute of Information Technology Hyderabad, India was utilized for the computation. It consists of 92 nodes, each equipped with dual Intel Xeon E5-2640 v4 processor, 128 GB RAM, two scratch disks (2 TB SATA and 960 GB SSD SATA) and four Nvidia GTX 1080 Ti / RTX 2080 Ti GPUs. The cluster has a total of 1472512 GPU cores, 3680 CPU cores and 11776 GB RAM. For our experiment we have used 40 cores with maximum memory per CPU as 2 GB on a Linux Ubuntu operating system. The proposed model is implemented using Python with the genetic_selection library for the Genetic Algorithm implementation and the sklearn library for the classification algorithms.

System Design

The proposed classification technique comprises of two stages, namely:

1. Dimensionality Reduction with Feature Selection

2. Classification

Dimensionality Reduction with Feature Selection

The dimensionality of the gene expression dataset is high. The dataset has redundant features which act as noise while training a model. This results in poor classification performance and high computational time. Dimensionality reduction is a technique that removes redundant features that hinder performance. We have used the feature selection [36] dimensionality reduction technique.

Let X be the initial m dimensional set of features, defined by the equation X = x(i)| i = 1,2,...m where x(i) are the defined features and m are the genes. The process of feature selection generates Y(i)|i = 1,2,...,p where Y(i) represents the new subset of features and p is now the number of features in the subset with p <= m. There are three types of feature selection methods - Filter, Wrapper, and Embedded approaches [37, 38] .

Figure 8 shows the the proposed computational model framework. The feature selection stage uses GA for dimensionality reduction.Genetic Algorithm (GA) is a metaheuristic, evolutionary, stochastic optimization algorithm inspired by the process of natural selection. GAs are commonly used to generate optimum solutions to problems employing three biologically inspired operators selection, crossover and mutation.

Figure 8: Proposed computational model framework

Classification

Classification is the process of identification of which of a set of categories or sub-populations an observation belongs to. Usually, the individual observations are grouped into a set of quantifiable properties called features. These features may either be categorical or ordinal or integer or real-valued. In the field of machine learning, the observations are called instances, the variables termed as features are grouped to form a feature vector, and the to be predicted categories are called classes. Figure 9 shows the pseudo code of the entire pipeline. We have used three classification algorithms in our research viz. Support Vector Machines, Logistic Regression and Random Forest.

Support vector machines (SVM) are one of the most popular, robust, non-probabilistic,

binary, linear and non-linear classifier, supervised learning algorithms that analyze data for classification or regression analysis in machine learning. Based on a set of categorized training data, an SVM training model assigns new unseen examples to either of the trained categories, creating the decision boundaries (or hyperplanes) that can segregate n-dimensional space into classes.

Logistic regression (LR) is another powerful supervised ML algorithm used for binary classification problems that can be generalized to multiclass classification. A logistic function is used to model the probability of a discrete outcome based on an input variable. LR is an extensively employed algorithm for classification problems in industry owing to its high simplicity and efficiency particularly for linearly separable classes.

Random forests (RF) are an ensemble learning classification method and work by constructing a multitude of decision trees at training time. For classification jobs, the RF output is the class selected by most trees. Ensemble learning combines many classifiers to provide solutions to complex problems. In machine learning RFs also assist in reducing the training set overfitting by decision trees and also increases precision.

input	: Training Set
	Testing Set
output	: Selected Features
	Classification Accuracy

Begin: General Steps for feature selection using GA

Initialization:
$t \leftarrow 0$
Initialize population P_t randomly from training set.
EVALUATE_FITNESS(P_t)
while *termination condition not met* **do**
    Select individuals from P_t (fitness proportionate)
    Crossover of individuals
    Mutate individuals
    EVALUATE_FITNESS(modified_individuals)
    $P_{t+1} \leftarrow$ newly created individuals
    $t \leftarrow t + 1$
end
$Solution\#1 \leftarrow$ Individuals with maximum fitness

Function EVALUATE_FITNESS(P):
    $clf \leftarrow Random\_Forest\_Classifier()$
    for *each individual $i \in P$* **do**
        $fitness(i) \leftarrow accuracy(clf(i))$
    end

End Feature Selection Process

Begin: Classification Process

Receive the best fitted individuals(Solution#1)
Compute the classification accuracy of the selected features using
different classifiers(SVM, RF and LR)
Return the classification accuracy and evaluation results.

End Classification Process

Figure 9: Psuedocode of the proposed method

Experimentation

The following sections will introduce each of the followed steps in detail. A summary of
the implementation of the entire pipeline is depicted in Figure 10.

Figure 10: Flowchart of entire pipeline

Data Preparation

In order to create an independent test set and improve the classification validity and accuracy, the input data was divided into the training and testing sets in a ratio of 80% and 20% respectively. The training set was created to validate the feature selection while the test set served a similar validation role in the classification process. The training set is then processed through the GA pipeline.

Genetic Algorithm

Genetic Algorithm (GA) is a stochastic evolutionary optimization technique. It starts with an initial randomized set of population of features (500 here) and then creates another population using subsets of the available features whose individuals are evaluated using the Random Forest predictive model for the target task. The tournament selection

technique is used to pick the higher fitness subsets to be carried forward into the next generation for applying the cross-over (updating the winning feature sets with features from the other winners) and mutation (probabilistically introducing or removing some features) genetic operators. The individuals of this subset are stored in the Hall of Fame which is continuously sorted so as to have the first element with maximum fitness value so far. This process is iterated to yield the optimum features for the set termination criteria (maximum generations = 100, if no change in the best-fitted individual for 20 generations). Few other GA modelling parameters used in our research are - uniform crossover probability of 0.5, flip-bit-mutation probability of 0.2.

Classification Process

After the GA has selected the optimal features, these features are then subjected to different classification algorithms (SVM, Random Forest, Logistic Regression) to measure the classification accuracy of the selected feature set. This yields us the classification accuracy of the four different classes viz **early_troph, late_troph, schizont and ring**.

Mutual Information

Mutual Information (MI) is a measure of how much one variable's uncertainty is reduced when the other variable's value is known. It is given by the formula:

$$I(X_1; X_2) = \sum_{X_1} \sum_{X_2} P(X_1, X_2) \log \frac{P(X1, X2)}{P(X_1)P(X_2)}$$

where $P(X_1, X_2)$ is the joint distribution of the two variables. $P(X_1)$ and $P(X_2)$ is the marginal distribution of the two variables. It's a dimensionless quantity that's measured in bits. Each element of confusion matrix represents the conditional probability of predicting a class y' given the true category y - $p(y'|y)$. The joint probability of $P(y, y')$ is equal to the multiplication of probability of true label $P(y)$ and conditional probability $P(y'|y)$. $P(y')$ is given by sum of joint probability over true label y. We have used this to find the $I(y; y')$.

References

[1] Naveed Abbas, Tanzila Saba, Amjad Rehman, Zahid Mehmood, Hoshang Kolivand, Mueen Uddin, and Adeel Anjum. Plasmodium life cycle stage classification based quantification of malaria parasitaemia in thin blood smears. *Microscopy research and technique*, 82(3):283–295, 2019.

[2] Lia Chappell, Philipp Ross, Lindsey Orchard, Timothy J Russell, Thomas D Otto, Matthew Berriman, Julian C Rayner, and Manuel Llinás. Refining the transcriptome of the human malaria parasite plasmodium falciparum using amplification-free rna-seq. *BMC genomics*, 21(1):1–19, 2020.

[3] Mahdieh Poostchi, Kamolrat Silamut, Richard J Maude, Stefan Jaeger, and George Thoma. Image analysis and machine learning for detecting malaria. *Translational Research*, 194:36–55, 2018.

[4] Mtakai Ngara, Mia Palmkvist, Sven Sagasser, Daisy Hjelmqvist, Åsa K Björklund, Mats Wahlgren, Johan Ankarklev, and Rickard Sandberg. Exploring parasite heterogeneity using single-cell rna-seq reveals a gene signature among sexual stage plasmodium falciparum parasites. *Experimental cell research*, 371(1):130–138, 2018.

[5] Juliana M Sa, Matthew V Cannon, Ramoncito L Caleon, Thomas E Wellems, and David Serre. Single-cell transcription analysis of plasmodium vivax blood-stage parasites identifies stage-and species-specific profiles of expression. *PLoS biology*, 18(5):e3000711, 2020.

[6] Adam J Reid, Arthur M Talman, Hayley M Bennett, Ana R Gomes, Mandy J Sanders, Christopher JR Illingworth, Oliver Billker, Matthew Berriman, and Mara KN Lawniczak. Single-cell rna-seq reveals hidden transcriptional variation in malaria parasites. *elife*, 7:e33105, 2018.

[7] Katelyn A Walzer, Hélène Fradin, Liane Y Emerson, David L Corcoran, and Jen-Tsan Chi. Latent transcriptional variations of individual plasmodium falciparum uncovered by single-cell rna-seq and fluorescence imaging. *PLoS genetics*, 15(12):e1008506, 2019.

[8] Asaf Poran, Christopher Nötzel, Omar Aly, Nuria Mencia-Trinchant, Chantal T Harris, Monica L Guzman, Duane C Hassane, Olivier Elemento, and Björn FC Kafsack. Single-cell rna sequencing reveals a signature of sexual commitment in malaria parasites. *Nature*, 551(7678):95–99, 2017.

[9] Mukul Rawat, Ashish Srivastava, Shreya Johri, Ishaan Gupta, and Krishanpal Karmodiya. Single-cell rna sequencing reveals cellular heterogeneity and stage transition under temperature stress in synchronized plasmodium falciparum cells. *Microbiology spectrum*, 9(1):e00008–21, 2021.

[10] Manaswini Pradhan. Evolutionary computational algorithm by blending of ppca and ep-enhanced supervised classifier for microarray gene expression data. *IAES International Journal of Artificial Intelligence*, 7(2):95, 2018.

[11] Divya Jain and Vijendra Singh. An efficient hybrid feature selection model for dimensionality reduction. *Procedia Computer Science*, 132:333–341, 2018.

[12] D Asir Antony Gnana Singh, E Jebamalar Leavline, R Priyanka, and P Padma Priya. Dimensionality reduction using genetic algorithm for improving accuracy in medical diagnosis. *International Journal of Intelligent Systems and Applications*, 8(1):67, 2016.

[13] Virginia M Howick, Andrew JC Russell, Tallulah Andrews, Haynes Heaton, Adam J Reid, Kedar Natarajan, Hellen Butungi, Tom Metcalf, Lisa H Verzier, Julian C Rayner, et al. The malaria cell atlas: Single parasite transcriptomes across the complete plasmodium life cycle. *Science*, 365(6455):eaaw2619, 2019.

[14] Roded Silverbush, Dana Sharan. A systematic approach to orient the human protein–protein interaction network. *Nature Communications*, 2019.

[15] Nastou KC Lyon D Kirsch R Pyysalo S Doncheva NT Legeay M Fang T Bork P Jensen LJ von Mering C. Szklarczyk D, Gable AL. The string database in 2021: customizable protein-protein networks, and functional characterization of user-uploaded gene/measurement sets. *Nucleic Acids Res.*, 49(605-612):91–107, 2021.

[16] Réka Albert and Albert-László Barabási. Statistical mechanics of complex networks. *Reviews of modern physics*, 74(1):47, 2002.

[17] Mathieu Bastian, Sebastien Heymann, and Mathieu Jacomy. Gephi: An open source software for exploring and manipulating networks, 2009.

[18] S Karthik and M Sudha. A survey on machine learning approaches in gene expression classification in modelling computational diagnostic system for complex diseases. *International Journal of Engineering and Advanced Technology*, 8(2):182–191, 2018.

[19] Jaspreet Singh Chima, Abhishek Shah, Karan Shah, and Rekha Ramesh. Malaria cell image classification using deep learning. *International Journal of Recent Technology and Engineering*, 8(6):5553–59, 2020.

[20] Qazi Ammar Arshad, Mohsen Ali, Saeed-ul Hassan, Chen Chen, Ayisha Imran, Ghulam Rasul, and Waqas Sultani. A dataset and benchmark for malaria life-cycle classification in thin blood smear images. *Neural Computing and Applications*, 34(6):4473–4485, 2022.

[21] Sen Li, Zeyu Du, Xiangjie Meng, and Yang Zhang. Multi-stage malaria parasite recognition by deep learning. *GigaScience*, 10(6):giab040, 2021.

[22] Micheal Olaolu AROWOLO, Marion Olubunmi ADEBIYI, Chiebuka Timothy NN-ODIM, Sulaiman Olaniyi ABDULSALAM, and Ayodele Ariyo ADEBIYI. An adaptive genetic algorithm with recursive feature elimination approach for predicting malaria vector gene expression data classification using support vector machine kernels. *Walailak Journal of Science and Technology (WJST)*, 18(17):9849–11, 2021.

[23] Qingwen Li, Benzhi Dong, Donghua Wang, and Sui Wang. Identification of secreted proteins from malaria protozoa with few features. *IEEE Access*, 8:89793–89801, 2020.

[24] Sushil Kumar Mishra. Human malaria detection and stage classification using random forest classifier.

[25] Muhammad Minoar Hossain, Md Abdur Rahim, Ali Newaz Bahar, and Mohammad Motiur Rahman. Automatic malaria disease detection from blood cell images using the variational quantum circuit. *Informatics in Medicine Unlocked*, 26:100743, 2021.

[26] Murad Al-Rajab, Joan Lu, and Qiang Xu. A framework model using multifilter feature selection to enhance colon cancer classification. *Plos one*, 16(4):e0249094, 2021.

[27] Qinglin Mei, Huaxiang Zhang, and Cheng Liang. A discriminative feature extraction approach for tumor classification using gene expression data. *Current Bioinformatics*, 11(5):561–570, 2016.

[28] Micheal O Arowolo, Marion Olubunmi Adebiyi, Ayodele Ariyo Adebiyi, and Olatunji Julius Okesola. A hybrid heuristic dimensionality reduction methods for classifying malaria vector gene expression data. *IEEE Access*, 8:182422–182430, 2020.

[29] Jie Li, Zhun Zhao, Li Zhou, and Yadong Wang. Y-spcr: A new dimensionality reduction method for gene expression data classification. In *2019 IEEE International Conference on Bioinformatics and Biomedicine (BIBM)*, pages 401–408. IEEE, 2019.

[30] Lior Rokach. Genetic algorithm-based feature set partitioning for classification problems. *Pattern Recognition*, 41(5):1676–1700, 2008.

[31] Zili Zhang and Pengyi Yang. An ensemble of classifiers with genetic algorithmbased feature selection. *The IEEE intelligent informatics bulletin*, 9(1):18–24, 2008.

[32] Cheng-Lung Huang and Chieh-Jen Wang. A ga-based feature selection and parameters optimizationfor support vector machines. *Expert Systems with applications*, 31(2):231–240, 2006.

[33] Li-Yeh Chuang, Chao-Hsuan Ke, Hsueh-Wei Chang, and Cheng-Hong Yang. A two-stage feature selection method for gene expression data. *OMICS A journal of Integrative Biology*, 13(2):127–137, 2009.

[34] Shutao Li, Xixian Wu, and Mingkui Tan. Gene selection using hybrid particle swarm optimization and genetic algorithm. *Soft Computing*, 12(11):1039–1048, 2008.

[35] Mohd Saberi Mohamad, Safaai Deris, and Rosli Md Illias. A hybrid of genetic algorithm and support vector machine for features selection and classification of gene expression microarray. *International Journal of Computational Intelligence and Applications*, 5(01):91–107, 2005.

[36] Nada Almugren and Hala Alshamlan. A survey on hybrid feature selection methods in microarray gene expression data for cancer classification. *IEEE access*, 7:78533–78548, 2019.

[37] Almas Jabeen, Nadeem Ahmad, and Khalid Raza. Machine learning-based state-of-the-art methods for the classification of rna-seq data. In *Classification in BioApps*, pages 133–172. Springer, 2018.

[38] Barnali Sahu, Satchidananda Dehuri, and Alok Jagadev. A study on the relevance of feature selection methods in microarray data. *The Open Bioinformatics Journal*, 11(1), 2018.

Acknowledgements

Authors thank the Department of Biotechnology (No. BT/RLF/Re-entry/32/2017), Government of India for funding.

Contributions

B.G. conceived the study. S.S. performed the feature selection and classification experiments. S.C performed the network tolplogy analysis. S.S., S.C. and B.G. wrote the manuscript.

Corresponding author

Correspondence to Bhaswar Ghosh.

Competing interests

The authors declare no competing interests.