`fimpera`: drastic improvement of Approximate Membership Query data-structures with counts

Lucas Robidou [1],*, Pierre Peterlongo [1]

[1] Univ. Rennes, Inria, CNRS, IRISA, Rennes, France.
{lucas.robidou,pierre.peterlongo}@inria.fr

*To whom correspondence should be addressed.

Abstract

Motivation: High throughput sequencing technologies generate massive amounts of biological sequence datasets as costs fall. One of the current algorithmic challenges for exploiting these data on a global scale consists in providing efficient query engines on these petabyte-scale datasets. Most methods indexing those datasets rely on indexing words of fixed length k, called k-mers. Many applications, such as metagenomics, require the abundance of indexed k-mers as well as their simple presence or absence, but no method scales up to petabyte-scaled datasets. This deficiency is primarily due to the fact that storing abundance is expensive. Using counting Approximate Membership Queries (cAMQ) data structures, such as counting Bloom filters, provides a way to index large amounts of k-mers with their abundance, but at the expense of a sensible false positive rate.

Results: We propose a novel algorithm, called `fimpera` that enables the improvement of any cAMQ performance. Applied to counting Bloom filters, our proposed algorithm reduces the false positive rate by two orders of magnitude and it improves the precision of the reported abundances. Alternatively, `fimpera` allows for the reduction of the size of a counting Bloom filter by two orders of magnitude while maintaining the same precision. `fimpera` does not introduce any memory overhead and even reduces the query time.

Availability: https://github.com/lrobidou/fimpera

1 Introduction

Public data banks providing sequencing data or assembled genome sequences are growing at an exponential rate Cummins *et al.* (2022), and faster than computational power. Searching for a sequence of interest among datasets is a fundamental need that enables for instance a better understanding of genetic changes in tumors, offering precious information about the diagnosis and treatment of cancer Tomczak *et al.* (2015), or enabling to study at a large scale the distribution and adaptation of life in oceans Sunagawa *et al.* (2020). However, no method scales to the dozens of petabytes of data already available today. Thus, new computational methods are required to perform a search against datasets.

Querying datasets can be done precisely by aligning genome sequences (e.g. using Blast-like Altschul *et al.* (1990) algorithms). However aligning sequences is computational-resources intensive. Thus, queries on large-scale datasets are usually done through k-mers presence/absence: each dataset is represented by its set of k-mers, and a query is represented by its sequence of k-mers. The ratio of the k-mers in the query and in the dataset over all the k-mers in the query approximates the similarity between the query and the dataset.

The challenge is to index hundreds of billions of distinct k-mers across thousands of datasets. Methodological developments have thus been made to index every k-mer of a dataset. Some methods use Approximate Membership Query data structures (AMQ), e.g. Bloom filters, to store the presence/absence of k-mers, as for instance SBT Solomon and Kingsford (2016) or HowDeSBT Harris and Medvedev (2020); see Marchet *et al.* (2021) for a survey of approaches. However, very few methods tackle the issue of recording the abundance of the indexed k-mers. The information about the abundance is however crucial for many biological applications such as in transcriptomics or in metagenomics analyses. Storing abundance in an AMQ, and turning it into a so-called "counting AMQ", is costly with regard to space consumption; conversely, adding abundance information in an AMQ for the same memory usage increases its false positive rate. As an example, BIGSI Bradley *et al.* (2019) relies on Bloom filters with a high false positive rate, e.g. 25% false positive rate per k-mer query. At constant memory usage, adding the information of abundance would yield an extremely high false positive rate that could reach up to 70%, which is not tolerable. As such, methods storing abundances mostly rely on compression by clustering abundance with neighboring k-mers or across datasets, as Reindeer Marchet *et al.* (2020) or Counting de Bruijn graphs Karasikov *et al.* (2022). Also, these methods do not rely on counting AMQ, but rather on exact data structures.

In this paper, we propose a wrapper to improve any existing counting AMQ. The method we introduce is called `fimpera`. It generalizes a previous contribution called `findere` Robidou and Peterlongo (2021). In short, `fimpera` splits every k-mer into s-mers (with $k \geq s > 0$) and then associates the abundance of a k-mer with its constituent s-mers in a counting AMQ. This allows us to retrieve the abundance of a k-mer at query time via its s-mers count. We show that, when compared

to the original counting AMQ indexing of kmers, `fimpera` improves abundance correctness while lowering the false positive rate by an order of magnitude without generating false-negative calls or underestimating the abundance of a kmer and without requiring additional time for query execution. Alternatively, for a fixed false positive rate value, the `fimpera` strategy allows reducing the size of the `cAMQ` by two orders of magnitude.

The `fimpera` algorithm can be used on top of any query made using any kind of counting AMQ. However, our implementation and tests are proposed on top of a counting Bloom Filter (`cBF`) that uses a unique hash function. This choice is motivated by the fact that `cBF`s are the simplest and are widespread data structures for dealing with billions of elements, and by the fact that state-of-the-art indexing tools based on counting AMQ (Cobs Bingmann *et al.* (2019), HowDeSBT Harris and Medvedev (2020)) impose the usage of a unique hash function.

Additionally, the `fimpera` algorithmic needs led us to propose a novel algorithm for computing the sliding window minima (resp. maxima): the minimal (resp. maximums) values of all sub-arrays of a fixed size over an array of x values. This algorithm runs in $\mathcal{O}(x)$ time and requires no dynamic memory allocation. This contribution may be useful outside the `fimpera` context. Its novelty is that being in place, it uses no additional memory, while other approaches use memory that is linear with the size of the intervals. This makes it the fastest known algorithm to perform this task. It is available at https://github.com/lrobidou/sliding-minimum-windows along with a benchmark comparing it to other solutions.

The `fimpera` contribution is publicly available at https://github.com/lrobidou/fimpera.

2 Methods

2.1 Background

A k-mer is a word of length k over an alphabet Σ. Given a sequence S, $|S|$ denotes the length of S. In the current framework, we consider a dataset to be composed of a multiset of sequences. Given a dataset D, $\mathcal{D}_k$ denotes the multiset of k-mers extracted from D.

The abundance of a k-mer d (the number of times d appears) in $\mathcal{D}_k$ is represented by $abundance(\mathcal{D}_k, d)$. We consider that a k-mer is "present" in $\mathcal{D}$ if $abundance(\mathcal{D}_k, d) > 0$, else $(abundance(\mathcal{D}_k, d) = 0)$ the k-mer is "absent".

A counting AMQ data structure represents a multiset of elements $\mathcal{D}_k$. It can be queried with any element d; the query's response on a counting AMQ, denoted by n, is always either correct or overestimated, i.e. $n \geq abundance(\mathcal{D}_k, d)$. If $n = abundance(\mathcal{D}_k, d)$, the counting AMQ reports the correct abundance, otherwise it reports an overestimation. Note that underestimation is not possible.

In particular, if $abundance(\mathcal{D}_k, d) = 0$ and $n > 0$, then d is found in the counting AMQ even if it is absent from $\mathcal{D}$. This particular case is a false positive call. The false positive rate of a counting AMQ, denoted by FPR_{cAMQ}, is defined by $FPR_{cAMQ} = \frac{\#FP}{\#FP + \#TN}$ with $\#FP$ and $\#TN$ denoting respectively the number of false positive calls and the number of true negative calls ($n = 0$). FPR_{cAMQ} depends on the used counting AMQ strategy and on the amount of space used by this counting AMQ.

There exist several models and implementations of counting AMQ. The simplest being the counting Bloom Filter Fan *et al.* (2000) (`cBF` for short) using a unique hash function, of which a toy example is given in Fig. 1. In a `cBF`, each element is hashed to get a position in a bit vector, at which position its abundance is stored. This requires a few bits per entry for storing this abundance. Collisions are allowed: should a collision occur, the abundance stored is the maximum of the colliding elements. This leads to a non-null probability of overestimation. A `cBF` is a generalization of

Fig. 1. Toy example of a counting Bloom Filter using a unique hash function, with k-mers of length $k = 5$, and $b = 4$ bits per element. Top, indexing: each indexed element (k-mer) is hashed to a slot, and its abundance is stored in that slot. Bottom, querying: queried elements are hashed, and the value of the corresponding slot is returned. Three situations may occur: 1/ true positive (e.g. "ACTGA"), 2/ false positive (e.g. "CTGAC") or 3/ true negative ("TGACA"). A true positive is always either correct or overestimated (in case of a hash collision between two elements with different abundances).

Bloom filters, in which each element is allocated only one bit, recording its presence/absence. Hence, a `cBF` requires more memory than a Bloom filter to achieve the same false positive rate. Equivalently, a `cBF` has a higher false positive rate than a simple Bloom filter with constant memory.

It should be noted that other `cAMQ` exist, such as the counting quotient filters Pandey *et al.* (2017). Despite the fact that the method we propose is applicable to any `cAMQ`, the description presented here, as well as the associated implemented tool, are based on the counting Bloom Filter using a unique hash function.

2.2 Overview of `fimpera`

2.2.1 Core principle

`fimpera`'s objectives are to reduce FPR_{cAMQ} and to improve the precision of the reported abundance of true positive calls. This is achieved using a method based on splitting k-mers into smaller words called s-mers. The s-mers are the elements indexed in the counting AMQ at indexation time. At query time, a k-mer is reported as found if and only if every one of its s-mers is found in the counting AMQ. Thus, a false positive (resp. overestimation) on a k-mer requires $k - s + 1 > 1$ false positives (resp. overestimations) on its s-mers. This emulates having $k - s + 1$ hash functions per k-mer, but requires fewer insertions in the filter while being compatible with tools requiring the use of one hash function per element such as Cobs Bingmann *et al.* (2019) or HowDeSBT Harris and Medvedev (2020) to cite a few. Alternatively, for a fixed FPR_{cAMQ}, the `fimpera` strategy reduces the memory needed by the `cAMQ` up to several orders of magnitudes.

2.2.2 Indexation overview

At indexation time, `fimpera` takes as input a file of counted k-mers, as provided for instance by KMC Kokot *et al.* (2017). `fimpera` splits each k-mer into its $k - s + 1$ constituent s-mers ($k \geq s$). Each s-mer is then stored in a `cAMQ` along with its $s_{abundance}$. The $s_{abundance}$ of a s-mer is formally defined as the maximum of the abundance of the k-mers containing this s-mer. We explain the choice on relying on $s_{abundance}$ instead of the abundance of s-mers and describe its outcomes in the Supplementary Materials, Section 3.3. Using both the $s_{abundance}$ and the abundance of s-mers is supported in the implementation.

In the following, we set $z = k - s$, hence $z \geq 0$.

2.2.3 Query overview

For each queried sequence S, `fimpera` extracts its sequence of s-mers, which is then queried against the `cAMQ`, and the abundance of any k-mer of S is computed as the minimum of $s_{abundance}$ of its s-mers. By default, `fimpera` prints each input sequence along with the abundance of every of its consecutive k-mer. In practice, the input query file is a fasta or a fastq file, possibly gzipped.

2.2.4 False positive calls

Let's consider a k-mer d with an abundance of 0 and each of its s-mer has an $s_{abundance}$ of 0 as well. With `fimpera`, wrongly reporting d as present requires that *every* s-mer of that k-mer are wrongly found as present in the counting AMQ. The probability of such an event is approximately $F(PR_{cAMQ})^{z+1}$, leading to a dramatic decrease in the occurrences of false positive calls with respect to z. For instance, with z=3 (which is a recommended and the default value) and a counting AMQ having a false positive rate of 25%, the false positive rate with `fimpera` for that setting is $\approx 0.4\%$.

The `fimpera` approach may generate a novel kind of false positive. A queried k-mer, absent from the indexed dataset, may be composed of s-mers existing in this indexed set. Querying such a k-mer with `fimpera` returns a non-zero abundance, so generating a false positive, which we call a "construction false positive". These false positives are created by `fimpera`, *independently of the underlying cAMQ*. This event is non-null but it is in practice negligible when using usual k and z values, as shown in the results.

2.2.5 Overestimations

To overestimate the abundance of a queried k-mer with `fimpera`, overestimations are required to happen on the abundance of **every** s-mer that k-mer that has the minimal $s_{abundance}$. The more s-mer per k-mer, the more s-mer abundance overestimations need to happen to overestimate a k-mer abundance. s-mer abundance overestimations can come from two sources:

- a collision occurs in the counting Bloom Filter, leading to the overestimation of the less abundant colliding s-mer; and/or:
- a s-mer is shared among two different k-mers having different abundances. This overestimates the abundance of this s-mer from the least abundant k-mer. This happens no matter the false positive rate of the counting Bloom Filter. We call those overestimations "construction overestimation". This new kind of overestimation is specific to `fimpera`.

Observe a case of interest: consider two k-mers d_0 and d_1 overlapping over $k - 1$ characters. If d_1 has an abundance greater than d_0, then the correct abundance of d_0 is retrievable through a unique s-mer (the unique s-mer of d_0 that does not appear in the k-mer d_1). In such case, d_0 is more likely to be overestimated than d_1.

Consequently, `fimpera`'s overestimations are not uniformly distributed random events. Overestimations are more likely to occur close to a change in abundance along queried sequences than in a random k-mer. In such cases, those overestimations are limited to the abundance of their neighbor k-mers, mitigating their impact. Indeed, in the result section (Section 3), we show that the erroneous abundance calls are closer to the ground truth with `fimpera` compared to those obtained with the original cBF.

We now describe in more detail both the indexing step and the querying step of `fimpera`, as well as one optimization, allowing a query time independent from the z value.

Another optimization enables `fimpera` to perform queries slightly faster than using the original underlying `cAMQ`. This optimization is described in Supplementary Materials, Section 2.2.

2.3 Querying with `fimpera`

`fimpera`'s query consists in querying all consecutive, overlapping k-mers from a sequence of size greater than or equal to k through their constituent s-mers. `fimpera`'s query is a two-step process:

- for every position in the query except the last $s - 1$ ones, s-mers starting at these positions are queried in the counting AMQ and are stored in an array of integers $s_{abundances}$;
- the abundance of any k-mer starting position p is the minimum value of the sub-array of length $(z + 1)$ starting at the position p: $s_{abundances}[p; p + z]$.

A non-optimized version of the `fimpera`'s query algorithm is shown in Supplementary Materials, Section 1.

The first step is improved by avoiding recomputing the minimal value of windows of length $z + 1$ starting at each position p of an array. This optimization is described in the following section.

2.4 Optimisation: sliding window minimum algorithm

The problem, independent of `fimpera`, is as follows: given a vector of values (integers or floats) v and an integer $size\_window$ (with $size\_window \leq |v|$), give an array r such that $\forall i \in [0, |v| - size\_window], r[i] = min(v[i], v[i + 1], ..., v[i + size\_window - 1])$. This is a particular case of a more general problem, the "range minimum query" (RMQ). Given a vector v of element drawn from a totally ordered set and two integers i, j ($0 \leq i < j < |v|$), the RMQ consists in finding $min(v[i], v[i+1], ..., v[j-1]$. Answering RMQ generally relies on some pre-computation beforehand (e.g. pre-computing the whole set of possible queries, but less resource-intensive solutions can be found, such as Durocher and Singh (2019)).

The sliding window minimum problem studied here is a particular case of an RMQ ($j - i$ is fixed and queries consist in every window of that size). Thus, its solutions do not require taking into account other window sizes, effectively allowing to skip pre-computation. The naive approach to solving the sliding minimum problem is to simply search for the minimal value in each window. This algorithm is in $\mathcal{O}(size\_window \times |v|)$ time. Some straightforward faster solutions can be built on top of dynamic heaps. Here, we propose a solution (named "fixed window") that does not rely on any heap allocation (which is slow for most systems). This solution without any dynamic memory allocation is an order of magnitude faster than other $\mathcal{O}(|v|)$ solutions as shown Section 3.1 in the Supplementary Materials.

The main idea of the proposed "fixed window" approach is to split the input vector of values in fixed, non-overlapping windows of size $size\_window$. Then, for each so-called "fixed window", compute two vectors:

- min_left_j: $min\_left\_j[i \% size\_window]$ contains the minimum value encountered in the j-th fixed window up to the position i; ($i \in [i * size\_window * j; i * size\_window * (j + 1) - 1]$
- min_right_j: $min\_right\_j[i \% size\_window]$ contains the minimum value from the position i up to the end of the j-th fixed window.

All min_left_j and min_right_j vectors are then concatenated into two vectors (min_left and min_right). The minimum of a *sliding window* starting at position i, denoted by $min\_sliding[i]$, is thereupon the minimum between:

- $min\_left[i + size\_window - 1]$ (the minimum of the left part of the next fixed window)
- $min\_right[i]$ (the minimum of the right part of the current fixed window)

An example is provided in Table 1.

i	0	1	2	3	4	5	6	7	8	9
v	5	3	7	1	4	5	3	2	2	3
j	0		1		2			3		
min_left	5	3	3	<u>1</u>	1	1	3	2	2	3
min_right	3	<u>3</u>	7	1	4	5	2	2	2	3
$min\_sliding$	3	**<u>1</u>**	1	1	3	2	2	2		

Table 1. Computation example of the $min\_sliding$ vector, with a window of size 3. Tables min_left and min_right are represented for helping comprehension but are not implicitly created in practice. The j row indicates the starting positions of each fixed windows. As an example, the minimal value of the sliding window of size 3 starting position $i = 1$ is $min\_sliding[1] = 1$ (bold underlined value), being equal to $\min(min\_left[1 + 3 - 1], min\_right[1]) = \min(1, 3)$ (underlined values).

Note that, as described previously, this approach would require allocating memory for two vectors per call. This memory need may appear negligible in theory as those vectors are limited by the query size which is a few hundred to few thousand. However, in practice, allocating memory for these vectors is time-consuming, and may increase significantly the practical running time. We overcome this memory need thanks to these three following tricks. **1/** we compute $min\_left[i]$ on the fly (if $i\%size\_window \neq 0$ then $min\_left[i] = min(min\_left[i - 1], v[i])$, else $min\_left[i] = v[i]$). **2/** min_right is computed *directly in the queried vector*. This does not impact the correctness of the algorithm, as $min\_sliding[i] \leq min\_right[i] \leq v[i]$. **3/** the response (minimal value per sliding window) can be stored directly in the input queried vector as well. At the price of modifying the input vector, this allows the algorithm to be run in $\mathcal{O}(size\_query)$ time while avoiding any time-consuming heap allocation.

A complete description of the optimized solution is provided in Supplementary Materials, Section 2.1, algorithm 2, along with a benchmark Section 3.1, Fig. 1.

This algorithm offers a generic solution for computing the minimal value of a sliding window in constant memory and linear time. Its usefulness is not limited to fimpera. As so, we propose an independent implementation https://github.com/lrobidou/sliding-minimum-windows. Note also that it can be straightforwardly modified for computing the maximal value instead of the minimal value of each window.

2.5 Implementation of fimpera

An implementation of fimpera is available at https://github.com/lrobidou/fimpera. This implementation is specialized for genomic data (i.e. with an alphabet consisting of A, T, C, G) and uses a counting Bloom Filter with a unique hash function as cAMQ. A template mechanism allows the use of any other cAMQ provided by the user. Queries consist of fasta or fastq files (gzipped or not), and an option is provided to index and query canonical k-mers only, i.e. the lexicographic minimum between each k-mer and its reverse complements. Indexing options include the k and z values, the size of the filter, and b, the number of bits per element used to store its abundance. As b has a major impact on the final size of the data structure, it is recommended to use low b values (say $b \leq 5$). This limits the maximal stored abundance value to $2^b - 1$ (to prevent overflow, the abundance is capped at $2^b - 1$).

In order to encode large abundance values with few bits per k-mer, instead of storing the first possible $2^b - 1$ distinct abundance values, we propose to discretize any abundance value to user-defined interval ranges. In practice, fimpera can use any surjective function

$$f(x \in [1, \infty]) \rightarrow y \in [0, 2^b - 1],$$

supplied by the user. This can be for instance any intervals. The proposed implementation proposes the usage of $y = \min(\lfloor \log_2(x) \rfloor, 2^b - 1)$, or $y = \min(\lfloor \log_{10}(x) \rfloor, 2^b - 1)$.

Changing the default output (e.g. storing results instead of printing them, computing average abundance per sequence, or printing only sequences whose average k-mer abundances is above a user-defined threshold) is possible.

3 Results

3.1 Experimental setup

To the best of our knowledge, no other tool focuses on reducing the false positive rate of existing cAMQ, thus we compare fimpera results applied on a counting Bloom Filter indexing s-mers with the original counting Bloom Filter results indexing k-mers using a unique hash function. We propose results on biological marine metagenomic data. Parameters used are the default ones: $k = 31$, size of the filter of 3.48×10^9 bits, as discussed in section 3.3, using $b = 5$ bits per abundance count (thus $2 * 10^8$ slots), and abundances are stored as their $\lfloor \log_2 \rfloor$ values. We use the default $z = 3$ parameter (unless otherwise stated).

A list of commands for reproducing the results is available here: https://github.com/lrobidou/fimpera/blob/paper/paper_companion/Readme.md along with a step-by-step explanation of the output. Executions were performed on the GenOuest platform on a node with 4x8cores Xeon E5-2660 2,20 GHz with 200 GB of memory.

3.2 Metagenomic dataset

We used two fastq files from the TARA ocean metagenomic dataset Sunagawa *et al.* (2020) to show the advantages offered by fimpera on metagenomic samples. The index was computed from the 2.38×10^8 distinct 31-mers present at least twice in an arctic station (accession number ERR1726642) and the query sample was the first 3×10^6 reads from a sample in another arctic station (accession number ERR4691696). Canonical k-mers were considered for this experiment.

3.3 Choice of filters parameters

In this experiment, we apply the fimpera approach on top of a counting Bloom Filter designed to have 25% of false positive calls, while using 5 bits per element for storing the abundance of indexed k-mers. For indexing 2.38×10^8 31-mers this structure requires $6.96 * 10^8$ slots (thus 3.48×10^9 bits).

We compare the results of queries made against this raw counting Bloom Filter with the results of queries made using fimpera wrapping that same counting Bloom Filter. As we use $z = 3$, we compare the results of a cBF indexing 31-mers, with results of fimpera used on a cBF with the same sizing, but indexing s-mers of size 28 (31-3).

3.4 Used metrics

To measure the quality of the fimpera results and the cBF results, we propose three metrics:

- the false positive rate, which provides the probability that the method returns an abundance call > 0 for a k-mer absent from the indexed set.

• the proportion of incorrect abundance, that provides the probability
that the method returns the incorrect abundance for a k-mer actually
in the indexed set.
• statistics of responses for incorrect abundances calls, that estimate
the reported abundance of k-mers whose abundance is incorrectly
reported. When comparing any two approaches, we set up a metric
that we call "overestimation score". It is defined as the sum of the
square of errors made on the output of each method.The lower the
overestimation score is, the fewer errors were made. Errors that are
closer to the ground truth are less penalized by this score than errors
distant from it.

3.5 False positive rate analyses

Fig. 2. Proportion of false positive calls without `fimpera` (on a classical counting Bloom Filter) and with `fimpera` ($z = 3$), indexing and querying real metagenomic read datasets.

Results about false positives obtained with the proposed experiment are
shown in Fig. 2. Results about the `cBF` simply confirm the setup and show
a false positive rate of 25%. When applying `fimpera`, the false positive
rate drops to 0.56%. Among all these `fimpera` false positives, 4.8 % are
due to the so-called "construction false positives" (see Section 2.2.3), thus
representing 0.0027% of the total k-mer calls.
It is important to recall that these comparative results were obtained
using the exact same amount of space. Hence the `fimpera` approach
enabled to yield about 45 times fewer false positive calls, with no drawback
and even saving query time (see Table 2).

3.6 Correctness of the reported abundances

In this section, we focus only on true positive calls. Hence, these results
do not concern the 25% false positive calls obtained with the original `cBF`,
nor the 0.56 % ones using `fimpera`.
Results comparing the proportion of calls reported with an incorrect
abundance among the true positives show that 1.54 % of true-positive
calls are overestimated in the `cBF`, while 1.33 % of true-positive calls are
overestimated with `fimpera`. Among the `fimpera` calls estimating an
incorrect abundance among the true positives, 83 % are due to the so-called
"construction overestimation".

3.7 Distribution of errors in overestimated calls

In this section, we focus only on the wrongly estimated calls among true
positives.
Results presented Fig. 3 show that, as stated in Section 2.2.5, the
erroneous abundance calls are closer to the ground truth with `fimpera`
compared to those obtained with the original `cBF`. As seen Fig. 3-bottom,
with `fimpera`, almost all (except for a few outliers) overestimations are
only one value apart from the correct range (the average difference with

Fig. 3. For true-positive calls with an incorrect abundance estimation: reported abundance with respect to the correct abundance. Top: using the original `cBF`, Bottom: using `fimpera`.

387 the correct abundance range is 1.07). With the original `cBF`, as seen Fig. 3-
388 left, overestimations are more important (1.33 range in average from the
389 ground truth).

3.8 Influence of the size of the underlying `cAMQ`.

Because there is a trade-off between space usage and the false positive
rate of a `cAMQ`, `fimpera` can either reduce the false positive rate of the
`cAMQ` without changing its size or reduce its size without changing its
false positive rate. This section focuses on the impact of `fimpera` on this
latter strategy.

This trade-off (with and without `fimpera`) is shown Fig. 4 and Fig. 5.
To be as close as possible to real-life use-case, we consider in this section
the average abundance of k-mer on each read, not the abundance of each
k-mer. For precision requirement, abundances were not stored as their
$\lfloor \log_2 \rfloor$ values, but rather as their original values.

With `fimpera`, achieving a false positive rate of 2% requires $\approx 2.98 *
10^9$ bits ($\approx 3.72 * 10^8$ slots of 8 bits each) (see Fig. 4). Without `fimpera`,
achieving the same false positive rate requires $\approx 65.5 * 10^9$ bits (21 times
more space). The lower the false positive rate, the greater the space gap
between using and not using `fimpera`. Achieving a false positive rate of
0.02% requires about $7.25 * 10^9$ bits with `fimpera`, but $360 * 10^9$ bits
were not enough without `fimpera` (i.e. allocating more than 50 times
the space budget of `fimpera` would be required). In order to take into
account the abundance information, we set up the output of `fimpera` to
be the average of k-mers' abundance for each queried read.

Fig. 5 shows the sum of square of overestimations, with and without
`fimpera`. For an overestimation score (defined Section 3.4) of 200000,
`fimpera` requires $\approx 3.10 * 10^9$ bits ($\approx 3.87 * 10^8$ slots of 8 bits each),
whereas a `cBF` would requires $330.9 * 10^9$ bits (i.e. 100 times more space).

3.8.1 Impact of z

As shown in Table 2, the false positive rate decreases with respect to z and
stays low for a wide range of z values (at least from $z = 3$ to $z = 9$).

Fig. 4. Variation of the false positive rate with respect to the size of the `cBF`, with and without `fimpera` ($z = 3$). As we consider here the average abundance of k-mers on each queried read, a false positive means that the average abundance of a k-mer on a read is strictly positive while it should have been 0.

Fig. 5. Sum of square error with respect to the size of the `cBF`, with and without `fimpera` ($z = 3$). In this experiment, the output of `fimpera` is the average of each input read.

z	0	3	5	7	9	20
False positive rate (%)	25.00	0.56	0.08	0.02	0.03	99.70
Of which: construction FP (%)	0	0.49	9.64	46.32	67.26	99.99
Incorrect abundance calls (%)	1.55	1.33	1.93	2.99	4.27	42.73
Of which: constr. overest. (%)	0	83.02	88.65	94.24	94.34	99.85
Query time (s)	808.31	789.56	784.11	785.09	779.42	1596

Table 2. Influence of the z parameter on the quality of the results and on the computation time. "constr." stands for "construction" and "overest." stands for "overestimation". Results with $z = 0$ are equivalent to those obtained with the original `cBF` results.

When using an extreme z value, for instance, $s = 20$, the false positive rate is increased up to almost 100%. With $z = 20$, as we use $k = 31$, the size of the indexed s-mers is $s = 11$. When indexing as little as a few hundred million characters, each 11-mer has a great probability to appear by chance in the indexed dataset. Indeed, the probability of such event is $1 - (1 - \frac{1}{|\Sigma|^s})^n$, with n being the number of characters. For instance, for $s = 11$ and a sequence as little as $n =$ 20 million characters, the probability of the presence of any 11-mer is $> 99\%$. This quasi-random existence of all s-mers generates a huge amount of construction false positives, as seen in the last column. This has an effect on the running time, which nearly doubles, undoubtedly because all s-mers queried are positives, annihilating the s-mer skipping optimization.

3.8.2 Query time

As mentioned in the Supplementary Materials, section 2.2, the `fimpera` approach does not increase the query execution time. On the contrary, it makes it possible to reduce the running time slightly as z increases. See Table 2.

3.8.3 Discussion

A Bloom filter indexing $2.38 * 10^8$ elements using $2.33 * 10^8$ bits and one hash function would lead to a false positive rate of $\approx 6.61\%$. A counting Bloom Filter indexing the same dataset using the same space with 5 bits per slot (thus 5 times fewer slots) yields a false positive rate of 25%. With `fimpera`, using 5 bits per slot and the same total number of bits, the false positive rate drops to 0.56%. Using the same space as a Bloom filter, `fimpera` allows reducing the false positive rate, while adding count storage and being quicker to query. The only downside may in some cases be the computation of the $s_{abundance}$ from the abundance of counted k-mers. However, this can be skipped altogether with a moderate impact on the result (see Supplementary Materials, Section 3.3).

4 Conclusion

We presented `fimpera`, a novel computational method for reducing the false positive rate and increasing precision in any counting Approximate Membership Query data structure. This is achieved without requiring any changes to the original data structure, with no memory overhead, and even with a slight improvement in query computation time.

Our results showed that when applied on top of a counting Bloom Filter, `fimpera` enabled to yield about 45 times fewer false positive calls than when querying directly a counting Bloom Filter of identical size. Moreover, using `fimpera`, abundance errors were slightly less frequent on true positive calls, and finally, those abundance errors were on average 1.07 apart from the ground truth with `fimpera` while they are on average 1.33 apart from the ground truth with the original `cBF`.

Independently from parameters of the used `cAMQ`, `fimpera` requires setting up a unique parameter, z. Fortunately, results are highly robust with the choice of z, unless extreme values are chosen. Future work will include a formal analysis of the theoretical limits on the choice of z usage ranges.

We provide a C++ implementation of `fimpera` which enabled us to validate the approach. This implementation can also be used as a stand-alone tool for indexing and querying genomic datasets, and it can be tuned with user-defined parameters and ranges of abundances. The provided GitHub project also proposes all necessary instructions and links to genomic data to reproduce the results.

Finally, of independent interest, we proposed a novel algorithm and its implementation for computing the minimal or maximal values of consecutive windows, sliding on an array of integers or floats. To the best of our knowledge, this is the fastest algorithm to perform this task.

Acknowledgements

The authors thank Eric Pelletier for his help regarding the usage of the Tara Ocean data sets. We acknowledge the GenOuest bioinformatics core facility (https://www.genouest.org) for providing the computing infrastructure. The work was funded by ANR SeqDigger (ANR-19-CE45-0008).

References

Altschul, S. F. *et al.* (1990). Basic local alignment search tool. *Journal of molecular biology*, **215**(3), 403–410.

Bingmann, T. *et al.* (2019). Cobs: a compact bit-sliced signature index. In *International Symposium on String Processing and Information Retrieval*, pages 285–303. Springer.

Bradley, P. *et al.* (2019). Ultrafast search of all deposited bacterial and viral genomic data. *Nature biotechnology*, **37**(2), 152–159.

Cummins, C. *et al.* (2022). The european nucleotide archive in 2021. *Nucleic Acids Research*, **50**(D1), D106–D110.

Durocher, S. and Singh, R. (2019). A simple linear-space data structure for constant-time range minimum query. *Theoretical Computer Science*, **770**, 51–61.

Fan, L. *et al.* (2000). Summary cache: a scalable wide-area web cache sharing protocol. *IEEE/ACM transactions on networking*, **8**(3), 281–293.

Harris, R. S. and Medvedev, P. (2020). Improved representation of sequence bloom trees. *Bioinformatics*, **36**(3), 721–727.

Karasikov, M. *et al.* (2022). Lossless indexing with counting de bruijn graphs. In *International Conference on Research in Computational Molecular Biology*, pages 374–376. Springer.

Kokot, M. *et al.* (2017). Kmc 3: counting and manipulating k-mer statistics. *Bioinformatics*, **33**(17), 2759–2761.

Marchet, C. *et al.* (2020). Reindeer: efficient indexing of k-mer presence and abundance in sequencing datasets. *Bioinformatics*, **36**(Supplement_1), i177–i185.

Marchet, C. *et al.* (2021). Data structures based on k-mers for querying large collections of sequencing data sets. *Genome Research*, **31**(1), 1–12.

Pandey, P. *et al.* (2017). A general-purpose counting filter: Making every bit count. In *Proceedings of the 2017 ACM international conference on Management of Data*, pages 775–787.

Robidou, L. and Peterlongo, P. (2021). findere: fast and precise approximate membership query. In *International Symposium on String Processing and Information Retrieval*, pages 151–163. Springer.

Solomon, B. and Kingsford, C. (2016). Fast search of thousands of short-read sequencing experiments. *Nature biotechnology*, **34**(3), 300–302.

Sunagawa, S. *et al.* (2020). Tara oceans: towards global ocean ecosystems biology. *Nature Reviews Microbiology*, **18**(8), 428–445.

Tomczak, K. *et al.* (2015). Review the cancer genome atlas (tcga): an immeasurable source of knowledge. *Contemporary Oncology/Współczesna Onkologia*, **2015**(1), 68–77.

<div align="center">

Supplementary Materials

`fimpera`: drastic improvement of Approximate Membership
Query data-structures with counts

Lucas Robidou and Pierre Peterlongo

</div>

These supplementary materials first propose a detailed description of the proposed query algorithms. We start by providing the simple naive query algorithm (Section 1). Then, we present two optimization approaches (Section 2.1 and 2.2). These supplementary materials also propose additional results showing the advantages of the sliding window algorithm we propose 3.1, showing a comparison between using `fimpera` on a counting AMQ having a unique hash function, or not using `fimpera` on a counting AMQ with $z + 1$ hash functions (Section 3.2), showing the effect of using the abundance of s-mers, instead of their $s\_abundances$ (Section 3.3).

1 Query algorithm: non-optimized version

A non-optimized algorithm of `fimpera`'s query is shown in Algorithm 1. This algorithm takes a queried sequence q, a counting AMQ indexing s-mers, and parameters k and z. It returns a vector of integers called $response$, such that: $\forall i \in [0, |response| - 1]$, $response[i]$ is the abundance of the k-mer starting at position i in the query, for all i in $[0, |q| - k + 1]$.

Algorithm 1 Non optimized `fimpera`'s query

1: **procedure** NON_OPT_QUERY($q \in \Sigma^*$; cAMQ indexing s-mers; k and z in $\mathbb{N}^+$) with $|q| \geq k, z < k$.)
2:     ▷ Store $s_{abundance}$ of all s-mers from q:
3:     $smer\_s_{ab} \leftarrow emptyVector(|q| - s + 1)$
4:     **for** i in $[0; |q| - s + 1]$ **do**
5:         $smer\_s_{ab}[i] \leftarrow get\_s_{ab}(q[i, i + s - 1])$
6:             ▷ get_s_{ab} uses the cAMQ to provide the $s_{abundance}$ of a s-mer
7:     **end for**
8:     ▷ Compute all k-mers abundances from s-mer $s_{abundances}$:
9:     $response \leftarrow emptyVector(|q| - k + 1)$
10:    **for** i in $[0; |q| - k + 1]$ **do**
11:        $response[i] \leftarrow \min_{j \in [i, i+z]}(smer\_s_{ab}[j])$
12:    **end for**
13:    **return** $response$
14: **end procedure**

Algorithm 1 is not optimal. Line 11 computes the minimal value of a range of z consecutive integers taken from a vector of integers. At each iteration of the *for loop* line 10, this range is shifted by one.

2 Optimized query algorithm

We propose two optimizations of the previous algorithm.

- The first one consists in using a minimum sliding window, that provides a way to compute in $O(1)$ the *min* from Line 11 of the non-optimized version of the query algorithm. This

<div align="center">1</div>

optimization is explained at a high level in the main text (Section 2.4). Here, Section 2.1 we provide the associated pseudo-code.

- The second optimization consists in exploiting the fact that for any queried s-mer detected as absent, all k-mers that contain this s-mer are also predicted as absent. Section 2.2 shows how to optimize the queries jumping all k-mer positions that contain an absent s-mer. This section finally proposes the overall optimized query algorithm 3.

2.1 Sliding window minimums

Algorithm 2 details our proposal for computing all minimal values of a sliding window of a vector of integers v in linear time and with zero memory allocation. Note that modifying this algorithm for computing the maximal values instead of minimal values is straightforward. Section 3.1, we propose results showing the advantages of this proposed algorithm.

Algorithm 2 sliding_minimum_window

1: **procedure** SLIDING_MINIMUM_WINDOW(vector v of positive integers; length of window w ($|v| \geq w, w >$ 1))
2:     $nbWin \leftarrow \lfloor size(v)/w \rfloor$
3:     $nb\_elem\_last\_window \leftarrow |v| \mod w$
4:     ▷ Computation of min_left (See Section 2.4 in main text)
5:     $min\_left \leftarrow v[0]$
6:     **for** i in $[0; w-1]$ **do**
7:         $min\_left \leftarrow min(min\_left, v[i])$
8:     **end for**
9:     **for** i in $[0; nbWin - 2]$ **do**   ▷ for every window excluding the last one
10:         $start\_window \leftarrow i * w$
11:         **for** $index$ in $[start\_window + w - 2; start\_window]$ ▷ (decreasing order) **do**
12:             $v[index] \leftarrow min(v[index + 1], v[index])$ ▷ compute min_right, directly in v
13:         **end for**
14:         **for** j in $[0;$ w-1$]$ **do**
15:             ▷ sliding_minimum is min(min_left, $min\_right(=v)$):
16:             $v[start\_window + j] \leftarrow min(v[start\_window + j], min\_left)$
17:             ▷ update min_left (if a new fixed window starts, reset min_left):
18:             **if** $j == 0$ **then**
19:                 $min\_left \leftarrow v[start\_window + w]$
20:             **else**
21:                 $min\_left \leftarrow min(min\_left, v[start\_window + w + j])$
22:             **end if**
23:         **end for**
24:     **end for**
25:     ▷ Computation for the last window is not described here for the sake of simplicity
26:     ▷ remove last $w - 1$ elements from v:
27:     **for** i in $[0; w - 2]$ **do**
28:         $v.pop\_back()$
29:     **end for**
30:     **return** v
31: **end procedure**

2.2 Skip stretches of consecutive absent k-mers

Knowing the absence of a s-mer allows deducing that all k-mers containing this s-mer are absent. This allows inferring the existence of a stretch of consecutive absent k-mers.

We exploit this simple idea further. If one detects that two absent s-mers are $z + 1$ positions away in the query, then any k-mer starting at any position between them is also absent. In the `fimpera` algorithm, if a s-mer is not found during the query, an optimization consists of searching

for the abundance of the s-mer $z + 1$ positions further away in the query. If that s-mer is also absent, there is no need to query any s-mer in between.

Thus, `fimpera` only needs to query one s-mer every $z + 1$ position as long as the queried s-mers are absent in the counting AMQ, effectively saving time.

We can now propose the entire algorithm of `fimpera` (algorithm 3), using the sliding minimal window algorithm and including the optimization of skipping stretches of absent k-mers. The skip optimization occurs line 31: if a negative s-mer is called, the algorithm jumps $z + 1$ position away in the sequence, probing for another absent s-mer. A positive answer triggers line 17, backtracking z positions backward. In this situation, we keep track of the fact that we are skipping s-mers via the *extending_stretch* flag.

Algorithm 3 Optimized `fimpera`'s query

$(q \in \Sigma^*;$ cAMQ indexing s-mers; k and z in $\mathbb{N}^+)$ with $|q| \geq k, z < k$.

1: $s \leftarrow k - z$
2: $response \leftarrow emptyVector(size - K + 1)$
3: $stretchLength \leftarrow 0$
4: $j \leftarrow 0$ ▷ Current position in the query
5: $extending\_stretch \leftarrow true$
6: $previous\_answers \leftarrow emptyVector(0)$
7: **while** $j < |q| - k + 1$ **do**
8:     $smer \leftarrow q[j, j + s - 1]$
9:     $amq\_answer \leftarrow s_{abundance}\_of\_smer\_in\_cAMQ$
10:     **if** $amq\_answer > 0$ **then**
11:         **if** $extending\_stretch$ **then**
12:             $previous\_answers.push\_back(amq\_answer)$
13:             $stretchLength \leftarrow stretchLength + 1$
14:             $j \leftarrow j + 1$
15:         **else**
16:             $extending\_stretch \leftarrow True$
17:             $j \leftarrow j - z$
18:         **end if**
19:     **else**
20:         **if** $stretchLength > z$ **then**
21:             $start\_of\_stretch \leftarrow j - stretchLength$
22:             $offset \leftarrow 0$
23:             **for** $minimum : sliding\_window\_minimum(previous\_answers, z + 1)$ **do**
24:                 $response[start\_of\_stretch + offset] \leftarrow minimum$
25:                 $offset \leftarrow offset + 1$
26:             **end for**
27:         **end if**
28:         $previous\_answers \leftarrow emptyVector(0)$
29:         $stretchLength \leftarrow 0$
30:         $extending\_stretch \leftarrow false$
31:         $j \leftarrow j + z + 1$
32:     **end if**
33: **end while**
34: **if** $stretchLength > z$ **then**
35:     $start\_of\_stretch \leftarrow |q| - k + 1 - stretchLength;$
36:     $offset \leftarrow 0$
37:     **for** $minimum : sliding\_window\_minimum(previous\_answers, z + 1)$ **do**
38:         $response[start\_of\_stretch + offset] \leftarrow minimum$
39:         $offset \leftarrow offset + 1$
40:     **end for**
41: **end if**
42: **return** $response$

---

3 Additional results

In this section we propose additional results, highlighting the advantages of the new algorithm we propose for computing the minimal value of each sliding window (Section 3.1), or studying the connection between using `fimpera` or using a simple bloom filter with $z + 1$ hash functions (Section 3.2). Finally, we propose additional results focused on the effect of using the $s_{abundance}$ instead of the abundance of s-mers (Section 3.3).

3.1 Sliding window minimum benchmark

We propose a benchmark of the following algorithms to compare algorithms that find the minimal value of each sliding window on a vector of integers v:

- "*recomputing*": a naive algorithm, computing naively the minimum in each window. Time: $\mathcal{O}(size\_window \times |v|)$.

- "*recomputing from last min*": keeping a reference to the minimum m in the previous window and recomputing the minimum in the current window only if the element of value m was the first element of the previous sliding window. Simply update m if the new element in the current window is smaller than m. Time: $\mathcal{O}(size\_window \times |v|)$ at worst (if v is an increasing sequence).

- a deque-based approach: the deque contains elements of the input vector. For each element e, the back of the deque is removed if it is strictly smaller than e. Then e is added on the back of the deque and elements that are out of the current window are removed. The minimum of the current window is then the front of the deque. Time: $\mathcal{O}(|v|)$, but requires time consuming memory allocations.

- "*fixed windows*": the approach described in Section 2.4, but allocating new vectors. Time: $\mathcal{O}(|v|)$, but requires time consuming memory heap allocations.

- Our proposal: "***fixed windows in place***": based on the fixed approach we also introduced (previous item), but without heap allocation, as described in algorithm 2. Time: $\mathcal{O}(|v|)$.

We propose various tests, highlighting the behaviors of the presented algorithms in different contexts: v is made up of random integers with either a small (size 9) or a large (size 100) window, and v is made up of increasing integers. In all cases, our proposal is the fastest algorithm. Recall that the implementation, of independent interest, is available at `https://github.com/lrobidou/sliding-minimum-windows` along with a recipe to reproduce and extend this benchmark.

As shown in Fig. 1, when $size\_window$ is set to 9, approaches can be divided into two groups: those with heap allocations and those without. The fixed window approach with heap allocations is slower than keeping the last minimum ($\mathcal{O}(size\_window \times |v|)$ at worst), but once heap allocation is prevented (our proposal), this outperforms any other implementation, including keeping the last minimum by a factor 2. Heap allocations are costly: the differences between approaches in $\mathcal{O}(size\_window \times |v|)$ with heap allocation and in $\mathcal{O}(|v|)$ without them are negligible in practice (as long as $|v|$ is small enough, see Fig. 2).

Results presented Figure 2 show that the naive approach in $\mathcal{O}(size\_window \times |v|)$ is significantly slower than other approaches, even if it does not require heap allocation.

Keeping a reference to the minimum from the previous window is simpler than using a fixed window but it is two times slower. Moreover, if the input vector contains increasing values, it requires recomputing every window. Indeed, in this case, the minimum from any window is its leftmost element, and as it is out of the next window, the next window needs to be recomputed. See Fig. 3, to see the impact on run time. As illustrated in the figure, the strategy of keeping a reference to the minimum of each window is slower than when applied to random values. In any case, the query time of the method we propose is constant regardless of the input vector's content.

Figure 1: Comparison of five approaches for computing sliding window minimum. The input vector is composed of random integers. The size of the window is set to 9 and for each size of the input vector, 10000 instances were tested.

Figure 2: Comparison between 5 approaches for computing sliding window minimum. The input vector is composed of random integers. The size of the window is set to 100.

3.2 Comparing `fimpera` and a counting Bloom filter with multiple hash functions

Splitting k-mers into $z+1$ s-mers and associating each s-mer with a hash value as done in `fimpera` may be seen as a similar strategy as using $H = z+1$ hash functions per k-mer with a bloom filter. There are two obvious observations:

- Canonical indexing methods such as HowDeSBT [1] for instance rely on bloom filters using a unique hash function. These state-of-the-art approaches can thus directly benefit from our proposal, with no modification.

- Indexing and query time grow linearly with the number of hash functions used.

About the result correctness, we compared the reported abundance when indexing k-mers through s-mers compared to indexing k-mers through independent hash functions.

Using the overestimation score defined in Section 3.4 of the main manuscript, it is possible to compare `fimpera` ($z = 3$) using one hash function (ie. using 4 s-mers per k-mers) and using 4 independent hash functions. Using the same memory budget, $z = 3$ allows attaining an overestimation score of 98169 while using 4 independent hash functions allows reaching an overestimation

Figure 3: Comparison between 5 approaches for computing sliding window minimum. The size of the window is set to 9 and the input consists of an array of increasing values.

score of 57967168 (the lower the better). The false positive rate attained by using $z = 3$ is $\approx 0.36\%$ while using 4 independent hash functions leads to a drastic increase of the false positive rate to 99.94%. This is due to the fact that using 4 independent hash functions saturates the filter and most absent k-mers calls lead to false positives.

3.3 Comparison between $s_{abundance}$ and abundance of s-mers

As stated in Section 2.2.2 of the main manuscript, we index the $s_{abundance}$ of each s-mer instead of its abundance in the input dataset. This is motivated by the fact that the $s_{abundance}$ of a s-mer α is lower or equal [1] to the abundance of α in the input dataset. For instance, consider a s-mer α that occurs in two k-mers respectively with an abundance of one and two. Then, the abundance of α is three $(= 1 + 2)$, while the $s_{abundance}$ of α is two $(= \max(1, 2))$. Storing the $s_{abundance}$ of α instead of its abundance lowers the abundance overestimations, as it avoids accumulating the abundances of distinct k-mers it belongs to.

However, computing the $s_{abundance}$ is time-consuming, as it requires parsing all s-mers given an input composed of counted k-mers. Thus, keeping compatibility with most k-mer counter requires either that the indexation step is performed by `fimpera`, or the use of the abundance of s-mers instead of the $s_{abundance}$.

To measure overestimations achieved when indexing the abundance of s-mers instead of their $s_{abundance}$, we provide additional results (same datasets as those used in the main manuscript). In the main manuscript, we indexed the $\lfloor \log_2 \rfloor$ values of abundance for limiting the size of the `cBF`. In this section, we show overestimation results computed on exact abundances stored using 8 bits, and thus bounded to 255. We used $k = 31$ and $s = 28$. This is motivated by the fact that, else, no difference could be seen.

In Fig. 4, we show that overestimations introduced by the use of the abundance of each s-mer instead of $s_{abundance}$ are limited. This can be numerically estimated:

- the overestimation score comparing a raw counting AMQ to the ground truth is $\approx 8.6 * 10^7$;

- the overestimation score comparing `fimpera` to the ground truth is $\approx 10^4$ (three order of magnitude smaller);

- the additional overestimation score comparing the indexing of the abundance of s-mers instead of their $s\_abundance$ with `fimpera` is $\approx 2 * 10^4$ which appears negligible.

---

[1] except in some extremely rare cases with palindromic s-mers as described below

Figure 4: Comparison between the average abundance of k-mers from reads query results.

Extremely counter-intuitive case: the abundance of a s-mer can be smaller than its $s_{abundance}$

Actually, in some rare setups, the abundance of s-mer can be smaller than its $s_{abundance}$, and even lower than the abundance of any k-mer that contains it (which would lead to an underestimation). This is only possible when indexing and querying canonical k-mers. This case happens with s even, when two k-mers having the same canonical form overlap over s characters. On a sequence of size $k + 1$ composed of such overlap of two k-mers having the same canonical form, their canonical abundance in this sequence is 2, whereas the s-mer being the suffix of the first k-mer and the prefix of the second has an abundance of 1, thus smaller than its $s_{abundance} = max(2) = 2$.

For instance, consider the sequence $seq = TACGTA$ and $k = 5, s = 4$. The first k-mer is $TACGT$ and the second k-mer is $ACGTA$. Both have the same canonical form $ACGTA$, whose abundance is then equal to two. The s-mer they share, $ACGT$, exists only once in seq, so its abundance is one, lower than its $s_{abundance}$ equal to two as provided by the abundance of the unique (in this situation) abundance of the canonical k-mer it belongs to.

This setup is rare (541 out of 281032928 s-mers of the indexed TARA dataset, i.e.: 0.000193 % of its s-mers). In practice, this led to zero underestimation of the average of any read. Even if using the abundance of s-mers instead of their $s_{abundance}$, and using their canonical versions breaks the theoretical absence of underestimation, we consider the biological impact of these underestimations as perfectly negligible.

References

[1] Robert S Harris and Paul Medvedev. Improved representation of sequence bloom trees. *Bioinformatics*, 36(3):721–727, 2020.