Droplet-based microfluidics as a media optimization tool for cyanobacteria

Jialan Cao[1†], David A. Russo[2], Ting Xie[1], G. Alexander Groß[1], and Julie A. Z. Zedler[3†]

[1]Ilmenau University of Technology, Institute for Chemistry and Biotechnology, Dept. Physical Chemistry and Microreaction Technology, Weimarerstr. 32, D-98693 Ilmenau, Germany
[2]Friedrich Schiller University Jena, Institute for Inorganic and Analytical Chemistry, Bioorganic Analytics, Lessingstr. 8, D-07743 Jena, Germany
[3]Friedrich Schiller University Jena, Matthias Schleiden Institute for Genetics, Bioinformatics and Molecular Botany, Synthetic Biology of Photosynthetic Organisms, Dornburgerstr. 159, D-07743 Jena, Germany

[†]Correspondence: jialan.cao@tu-ilmenau.de; julie.zedler@uni-jena.de

Keywords: cyanobacteria, dose-response screening, droplet-based microfluidics, salt tolerance, *Synechococcus*, *Synechocystis*

Abstract

The urgent need to increase sustainability in biotechnology has led to an increased interest in photosynthetic production platforms. Cyanobacteria are particularly attractive for their fast photoautotrophic growth and genetic accessibility. However, the lack of systematic strain optimization is holding back progress towards industrialization. To overcome this bottleneck, here we introduce a droplet-based microfluidics platform capable of one- (1D) and two-dimension (2D) screening of key parameters in cyanobacterial cultivation. We successfully grew three different unicellular, biotechnologically relevant cyanobacteria: *Synechocystis* sp. PCC 6803, *Synechococcus elongatus* UTEX 2973 and *Synechococcus* sp. UTEX 3154. Highly-resolved 1D screening of nitrate, phosphate, carbonate, and salt content show that nitrate and/or phosphate can be limiting in standard cultivation media. Finally, we show that 2D screening results from our microfluidic setup translate well to a laboratory scale high-density cultivation setup. This study demonstrates that droplet-based microfluidics by micro segmented-flow are a powerful tool for nanoscale high-throughput optimization of cyanobacterial cultivation.

Introduction

Cyanobacteria have attracted interest for sustainable biotechnology due to their fast photoautotrophic growth, minimal nutritional requirements, and metabolic capacity for heterologous product formation. Transfer of existing systems to an industrial scale is however still rare and yet to come of age. Despite this, the market of cyanobacterial products is rapidly growing and cyanobacteria already account for half of the European algae production[1]. The existing products, however, are largely limited to "Spirulina" (*Arthrospira* spp.) which can be grown in high pH and high salt conditions. To efficiently exploit cyanobacterial diversity, and increase their biotechnological relevance, several challenges need to be solved. One key aspect is strain-specific optimization of growth conditions. To achieve this, high-throughput screening methods that are suitable for studying cyanobacterial chassis are needed. Standard high throughput methods for heterotrophic systems, such as micro-well cultivation and live-cell monitoring systems, are often not compatible with cyanobacteria due to the requirement for controlled light exposure, extended cultivation periods and autofluorescence interference with optical measurements. In addition, increasing of throughput by reducing volume raises new challenges in terms of oxygen supply, evaporation control and homogeneity. Thus, it is of great importance to establish alternative, cost-efficient technologies that are tailored for high-throughput screening and optimization of cyanobacteria.

Microfluidics is an established tool in chemical analytics and micro reaction technology and has played a pivotal role in the development of high-throughput analysis strategies for biological systems. It was first recognized as a promising tool for biological applications more than two decades ago. Starting with micro capillary electrophoresis[2] and micro flow-through PCR[3,4], miniaturized fluidic techniques became of interest for fast and efficient bioanalytical procedures. The ability to miniaturize volumes and multiplex sample handling and analysis then also attracted interest in molecular biology as well as in microbiology. For cultivation, droplet-based microfluidics by micro segmented-flow was first introduced to separate soil microorganisms from complex soil microbial communities[5]. In small droplets, the principle of stochastic confinement applies. In other words, rare individuals and their released molecules can accumulate to high densities, thus, enabling single cell experiments[6,7]. The segmented-flow principle enables an easy screening of sample series with concentration gradients and allows the measurement of organismic responses to stress factors like antibiotics, nanoparticles or heavy metals[8–10] with high resolution. In addition, this approach allows the screening of two and three-dimensional concentration spaces with a very small amount of material in a single experimental run. Thus, opening the possibility of conveniently detecting combinatorial effects of, for example, toxins, pharmaceutical drugs and nutrients[11]. Furthermore, droplet-based microfluidics is in use for detection of antibiotic resistances and for the development of new antibiotics[12]. Besides bacteria, the micro segmented-flow technique has also proven to be suitable for eukaryotic microorganisms such as *Chlorella*[13] or even embryos of multicellular organisms[14] and for the characterization of the concentration-dependent response of complex unknown environmental bacterial communities on toxic substances[15,16]. As applied to cyanobacterial systems, microfluidics is an emerging technology with only a handful of applications. For instance, a microfluidics-based tool for harvesting cyanobacterial biomass was developed for *Synechocystis* sp. PCC 6803[17] (hereafter PCC 6803). In addition, microfluidics have been used for lactate productivity screening in a PCC 6803 CRISPRi library[18] as well as to screen for ethanol production[19].

Here, we established a droplet-based microfluidic setup that allows for high-throughput media composition optimization in biotechnologically relevant cyanobacteria. We tested the compatibility of our system with three different cyanobacterial strains using biomass accumulation as the screening parameter. Our setup allowed for continuous cultivation and analysis of the cells where individual medium parameters such as macronutrient content as well as salt and bicarbonate concentrations were varied in small steps allowing for highly parallel, high-throughput screening. In addition, we demonstrated that our platform can screen two parameters simultaneously to explore the two-dimensional effect space of combined variables. Our data show that this microdroplet setup is a powerful setup to improve medium composition and cultivation conditions in a cost- and time-effective manner to unlock the exploitation of biotechnologically relevant cyanobacterial strains.

Materials and Methods

Strains and Growth Conditions

Three cyanobacterial wild-type strains were used: a non-motile, glucose-tolerant substrain of *Synechocystis* sp. PCC 6803 (originally obtained from Patrik Jones, Imperial College London), *Synechococcus elongatus* UTEX 2973 (originally obtained from Himadri Pakrasi, University of Washington) (hereafter UTEX 2973) and *Synechococcus* sp. UTEX 3154 (a spontaneous mutant of *Synechococcus* sp. PCC 11901[20] which does not require vitamin B_{12} for growth, obtained from the UTEX culture collection) (hereafter UTEX 3154). PCC 6803 and PCC 2973 were grown in BG-11 medium[21] supplemented with 10 mM N-Tris(hydroxymethyl)methyl-2-aminoethanesulphonic acid (TES) buffer (pH 8.0) (BG-11 TES medium). Medium A[22] with D7 micronutrients[23] (AD7 medium) was used for cultivation of UTEX 3154. All cultures were maintained at 30°C with 20 – 50 µmol photons m^{-2} s^{-1} white light (Lumilux cool white L 15W/840 fluorescent lamps (Osram, Germany)) on BG-11 or AD7 medium plates supplemented with 1.5% bacto-agar. Liquid pre-cultures for inoculation of the microfluidic coils were grown in glass tubes bubbled with 3% CO_2-supplemented air at 30°C with approximately 60 µmol photons m^{-2} s^{-1} white light for 3 to 4 days (culture volume: 20 mL).

To test improved nitrogen:phosphorus (N:P) ratios based on 2D screening experiments, standard BG-11 medium and BG-11 medium with adjusted $NaNO_3$ and K_2HPO_4 concentrations were prepared. Liquid cultures were inoculated for PCC 6803 and UTEX 2973 in a high-density cultivation setup (HDC 6.10 starter kit CellDEG, Germany)[24] using 25 mL culture vessels with a culture volume of 10 mL. The cultures were supplemented through a membrane with CO_2 at a partial pressure of approximately 32 mbar (reference T = 20°C) by a carbonate buffer (3 M $KHCO_3$ and 3 M K_2CO_3, ratio 4:1)[24]. The growth setup was placed on a Unimax 1010 orbital shaker (Heidolph Instruments, Germany) and incubated with shaking at 280 rpm at 30°C with 50 µmol photons m^{-2} s^{-1} white light (Lumilux cool white L 15W/840 fluorescent lamps (Osram, Germany)). Main cultures for the growth experiment were inoculated in triplicates from a pre-culture grown in the same medium and conditions to a starting optical density (OD) at 750 nm of 0.3 and monitored for 7 days by measuring OD at 750 nm every 24 hours using a GENESYS 10S UV-Vis Spectrophotometer (Thermo Scientific, Germany). For PCC 6803, the optimized BG-11 medium contained 0.4 mM K_2HPO_4 and 27 mM $NaNO_3$ and for UTEX 2973 0.45 mM K_2HPO_4 and 30 mM $NaNO_3$. All other elements of the medium were kept the same as in the standard BG-11 TES medium.

Microfluidic Cultivation

Microfluidic arrangement

Details on the fluidic devices, the optical detection unit and the applied methods for realizing concentration programs were reported earlier[9]. Here, a similar experimental set-up (Fig. 1) was used for one- and two-dimensional screening of effectors based on a syringe pump with six dosing units (Cetoni GmbH, Germany). The microfluidic segments were generated through a self-developed droplet generator comprising of a 6-port manifold[25] with controlled dosing of effectors, culture medium and cell suspension into a flow of carrier liquid (perfluoromethyldecalin (PP9)). The droplet generator was connected via fluoroethylenepropylene (FEP) tubing (inner diameter 1.0 mm and outer diameter 1.6 mm) to a computer-operated syringe pump, controlling syringes with volumes of 500 µL (effector solution and cell suspension), 1000 µL (culture medium) and 5000 µL (carrier liquid). Generated segments are transported at a constant flow rate of 200 µL min^{-1} through an optical detector unit for the simultaneous measurement of extinction and fluorescence of the droplet content directly through the transparent FEP tubing (Fig.1). Extinction was measured with four light emitting diodes (Agilent, United States) with peak wavelengths of 470, 505, 615 and 750 nm. Measurement of fluorescence induction was carried out with a laser diode with a peak wavelength of 405 nm (Changchun New Industries Optoelectronics, China) with a longpass filter (425 nm) (Laser Components, Germany). The emitted photons were counted by photomultiplier modules (Hamamatsu, Japan). To store and incubate the generated droplet sequences, polytetrafluoroethylene (PTFE) tube coils (inner diameter 0.5 mm and outer diameter 1.6 mm) with a length of four meters for 1D- and seven meters for 2D-screening were used.

Fig. 1 Experimental droplet-based microfluidic setup for 1D and 2D-screening of cultivation parameters used in this study. The illustration on the left shows a 6-channel droplet generator which mixes the aqueous liquids and produces droplets that are separated from the immiscible carrier medium. Droplet size, spacing and composition can be adjusted via the flow rate control program. The generated droplets are monitored with optical micro flow-through detector units directly through the transparent FEP tubing, and the generated droplet sequences are stored in PTFE tube coils.

Experimental Parameters

The flow rate of the fluid was controlled using a LabVIEW program (National Instruments, USA) to adjust the concentration inside the microfluidic segments. To investigate the dose-response relationships for single substances (1D-screening), a LabVIEW program with continuous change of the effector concentration was used (Fig. 2a). In binary mixtures (2D-screening), a stepwise change of the concentration with a resolution of 10% was applied. Two effectors in 11 different concentration steps (0, 10, 20, 30, 40, 50, 60, 70, 80, 90, 100%) were combined in micro fluid segments resulting in 121 different combinations (Fig. 2b). The flow rates of the carrier liquid and the cell suspension were set at 136 µL min^{-1} and 32 µL min^{-1}. The flow rates of the effector solution and cultivation medium were varied within a total flow rate of 32 µL min^{-1}. Therefore, the overall flow rate of the segment generation process was kept constant at 200 µL min^{-1}. An initial cell density of 5000 cells per 500 nL segment (10^7 cells mL^{-1}) was applied. The generation of highly resolved 1D- and 2D-screening sequences required approximately four and nine minutes, respectively, per single experimental run. After droplet formation and initial measurement (t = 0), the droplets were collected in the subsequent connected tube coils, enabling incubation and serial analysis. The tube coils were incubated for 7 days at 30 ± 2°C, 3% CO_2 and under 20 ± 5 µmol photons m^{-2} s^{-1} illumination.

Fig. 2 Syringe pump control program for the generation of 1D- and 2D-gradients. a Highly resolved dose response screening for single substances (1D-screening) and **b** two-dimensional concentration spaces in 11 combinatorial steps, resulting in 121 concentration combinations (2D-screening).

Effector screening concentration range

For effector screening, only the concentrations of our test variables were altered, while the remaining medium components were kept at the same concentrations. Stock solutions with two-fold concentrations for 1D screening and four-fold concentrations for 2D screening of the highest final concentration were prepared. These stocks were then used to generate highly resolved concentration gradients using the setup as shown in Fig. 1 and Fig. 2. In all experiments, PP9 (F2 Chemicals Ltd, Lancashire, UK) was used as an immiscible carrier liquid.

Data processing

Droplet sequences were measured at a 250 Hz sampling rate shortly after formation and after seven days of incubation (for generation of growth curves, daily measurements were taken). The droplets were analyzed offline using a custom LabVIEW program which elucidates droplet-specific data from the spectral sensor raw data: number, size, distance between two

neighboring droplets as well as extinction and fluorescence measurements. A droplet is recognized when the extinction value exceeds the background extinction of the carrier liquid. The droplet size is then determined through the time interval during which the extinction values exceed and, subsequently, return to background levels. Due to the inhomogeneous cell distribution in the droplets, growth behavior was analyzed by calculating the integral of the extinction and fluorescence signal with respect to the droplet size. The autofluorescence intensity I is given by the ratio between the intensity of the measurement value I(fluo) and the reference fluorescence I(ref) of the FEP tube filled with carrier liquid subtracted by 1.

$$I = \frac{I(fluo)}{I(ref)} - 1$$

Statistics and Reproducibility

In general, for each experiment two droplet sequences were generated and analyzed (Supplementary Fig. 1 red circles and black squares). Each dot shows the intensity for individual droplets. The droplets were then grouped into 32 concentration ranges from 0 to 100% of effector concentration (corresponding to a 3.1% concentration resolution). The mean and standard deviation were calculated for these 32 concentrations ranges and the resulting curve was plotted as a dose-response curve (Supplementary Fig. 1 blue triangles). For the growth kinetic experiment, each data point represents the mean and standard deviation of 50 ± 5 droplets across two independent coils. For 1D- and 2D-screening experiments, a total of 440 ± 21 and 814 ± 26 droplets, respectively, were generated per coil. These droplets were then distributed across the chemical gradients and approximately 10 (1D-screening) and 8 (2D-screening) droplets were analyzed per tested concentration. In sum, each data point represents the mean and standard deviation of 20 ± 6 (1D-screening) and 16 ± 6 (2D-screening) droplets. This redundancy was applied in order to validate the reliability of measurements and to control for stochastic effects that can derive from small reaction volumes and cell numbers.

Comparison of final biomass values in the high-density cultivation setup were done with an independent sample Student's t-test with a significance value of $\alpha = 0.05$.

Results and Discussion

In this study we introduce a microfluidics method that allows us to rapidly screen one- and two-dimensional (1D and 2D) culture medium parameters to optimize the growth conditions of industrially relevant cyanobacteria. Our results show that our droplet-based microfluidic approach is well suited to screen culture media conditions in a fast and efficient way, with low material input and a reduced amount of incubator space. In addition, we observed that commonly used medium formulations are not optimized for maximum growth and small changes can result in significantly higher biomass outputs. This method should be widely applicable to a variety of freshwater and saltwater strains and has the potential to facilitate high-throughput strain optimization.

Microdroplet cultivation setup is suitable to grow freshwater and marine unicellular cyanobacteria

To test the applicability of microdroplet cultivation to cyanobacteria we chose three biotechnologically relevant species. PCC 6803 is a freshwater model cyanobacterium that has been extensively characterized and for which many molecular tools exist. UTEX 2973 is a

freshwater fast-growing relative of *Synechococcus elongatus* PCC 7942. Due to their genetic proximity, an average nucleotide identity (ANI) > 99.8%[26], the tools developed for *Synechococcus elongatus* PCC 7942 are largely transferable to UTEX 2973. UTEX 2973 is of particular interest for biotechnological applications because of its fast growth phenotype with doubling times reported as fast as 1.5 hours[27]. As a third strain, we chose a saltwater strain. A recently isolated strain, *Synechococcus* sp. PCC 11901 (hereafter PCC 11901), is genetically tractable and with clear biotechnological potential due to its reported doubling time of approximately 2 hours and the ability to grow at high light intensities and a range of salinities. Under optimized conditions, PCC 11901 can accumulate up to 33 g dry cell weight per liter. Curiously, it has an ANI of 96.76% when compared to the commonly used *Synechococcus* sp. PCC 7002 strain[20]. Therefore, it may be possible to utilize tools previously developed for *Synechococcus* sp. PCC 7002 in PCC 11901. However, this strain is a vitamin B_{12} auxotroph. Hence, we decided to use a closely related, spontaneous mutant of this strain, UTEX 3154, that can grow without an external supply of vitamin B_{12}.

First, we proceeded to test whether these three cyanobacterial strains could grow in the droplet-based microfluidics setup. For the initial screening, sensors detecting autofluorescence (excitation: 405 nm, emission: 425 nm) and optical density (OD) at 470, 505, 615 and 750 nm were tested over a period of 7 days. In our microfluidic setup, OD reflects the reduction of the intensity of transmitted light by use of a microflow-through photometer. OD typically correlates well with the final cell number, however it does not allow to distinguish between live and dead cells. Growth can also be monitored by measuring the endogenous cellular autofluorescence with a micro flow-through fluorimeter. The fluorescence can be used to evaluate the approximate number of physiological active cells and, typically, is a more sensitive parameter than OD. Growth kinetics were observed with all sensor channels (Supplementary Fig. 2, Supplementary Data Table S1) but were best visualized in the OD_{470} (Fig. 3a) and autofluorescence (Fig. 3b) channels. In further experiments, we decided to use the autofluorescence channel to evaluate biomass accumulation. In some cases, biomass accumulation in the droplet storage coils was visible by the naked eye already after 4 days (Fig. 3c). The high cell density was confirmed by the observation of individual droplets by light microscopy (Fig. 3d). The typically reported doubling times for PCC 6803 are in the range of 10 to 12 h[28,29] and approximately 2 h for UTEX 2973[26] and UTEX 3154[20]. In line with this, our data show that PCC 6803 grows significantly slower than UTEX 2973 and UTEX 3154 (Fig. 3a, 3b). Between UTEX 2973 and UTEX 3154 we observed similar exponential growth rates and final biomass values despite the longer lag phase of UTEX 2973. Overall, the individual growth profiles fit with published literature and show that microdroplet cultivation is suitable for unicellular freshwater and saltwater strains.

Fig. 3 Growth of cyanobacteria in microdroplet setup. Growth kinetics of cyanobacterial strains (UTEX 3154, UTEX 2973 and PCC 6803) in microdroplet setup measured with multi-channel photo-fluorimeter device showing **a** absorbance (optical density OD) at 470 nm and **b** autofluorescence (excitation: 405 nm, emission: 425 nm) in the microfluidic setup over a 7 day period. Data points are averages of 50±5 droplets. Error bars represent standard deviation. **c** Example of UTEX 2973 cultivation in microfluidic tube coils. **d** Growth of cyanobacteria PCC 6803, UTEX 2973 and UTEX 3154 in microdroplets observed by light microscopy after 4 days, scale bar: 100 µm.

Microdroplet technology facilitates high-throughput, high resolution dose response screening

Following the successful establishment of PCC 6803, UTEX 2973 and UTEX 3154 in our microdroplet setup, we proceeded to evaluate the response of the cyanobacteria to a variety of medium parameters using high-resolution dose response screening. In 1D screening experiments, we used the standard growth medium for the respective strains (BG-11 for PCC 6803 and UTEX 2973, AD7 for UTEX 3154) and varied one parameter at a time. These included the nitrogen (N) source, phosphorus (P) source as well as medium salinity and sodium bicarbonate concentrations (Table 1). We then proceeded to look at combinatorial effects using 2D screening where both the N and P concentrations were varied simultaneously. An overview with the concentration range of all tested effectors for 1D and 2D-screening experiments is shown in Table 1.

Table 1 Range of concentration in single and two-dimensional screening for various medium components used in this study. Reference values of concentrations in BG-11 TES and AD7 medium are given.

Medium component	single effector dose-response screening (1D)	binary mixture screening (2D)	BG-11 TES medium	AD7 medium
$NaNO_3$	2 – 50 mM	0 – 30 mM	17.6 mM	12 mM
K_2HPO_4	0.05 – 5 mM	0 – 0.5 mM	0.175 mM	–
KH_2PO_4	0.05 – 5 mM	0 – 0.5 mM	–	0.37 mM
NaCl	0 – 1.3 M	–	–	308 mM
$NaHCO_3$	0 – 100 mM	–	–	–

We first started by testing different concentrations of $NaNO_3$ ranging from 2 to 50 mM. The data show that the freshwater PCC 6803 and UTEX 2973 achieved maximum biomass values

at approximately 10 and 20 mM NaNO$_3$, respectively (Fig. 4a, Supplementary Data Table S2). For the saltwater UTEX 3154, the maximum biomass value was achieved at approximately 30 mM NaNO$_3$ (Fig. 4a). The concentration of NaNO$_3$ present in the freshwater cyanobacterial growth medium BG-11 is 17.6 mM. Comparing this value with the limiting NaNO$_3$ concentrations for PCC 6803 and UTEX 2973 (10 and 20 mM, respectively), we can conclude that N is not typically the limiting nutrient in BG-11. Accordingly, an earlier study showed that during batch cultivation of PCC 6803 in BG-11 one of the major medium limitations may be sulfate ions[30]. Regarding the saltwater medium AD7, the concentration of NaNO$_3$ is 12 mM. Considering that the biomass accumulation of UTEX 3154 only peaked at around 30 mM NaNO$_3$, our data suggest that N may be a limiting nutrient in AD7. This is supported by the original PCC 11901 strain publication where the authors determined the ideal NaNO$_3$ concentration to be between 24 and 48 mM[20]. Overall, these data show that, given enough N, all three cyanobacteria are rapidly limited by other nutrients. Therefore, we proceeded to apply our microfluidic approach to test the effect of varying concentrations of phosphate (K$_2$HPO$_4$ for UTEX 2973 and PCC 6803 and KH$_2$PO$_4$ for UTEX 3154) up to a maximum concentration of 5 mM. The data show that the maximum biomass values were registered between 2.5 and 3.5 mM phosphate for PCC 6803 and UTEX 2973 and 0.75 mM phosphate for UTEX 3154 (Fig. 4b, Supplementary Data Table S3). Looking at the formulations of the base medium, phosphate is present at a concentration of 0.175 mM K$_2$HPO$_4$ in BG-11 and 0.37 mM KH$_2$PO$_4$ in AD7. Therefore, our microfluidics growth data suggest that both media are P deficient. This is particularly the case for BG-11 which has a K$_2$HPO$_4$ concentration 5 to 6 times lower than the levels at which we observed the highest biomass accumulation. It has been suggested that media designed for the growth of algae and cyanobacteria are often P limited due to a lack of compatibility with the Redfield ratio[31]. This ratio describes the amount of carbon (C), N and P typically present in both phytoplankton biomass and in dissolved nutrient pools and has been determined to be 106 C:16 N: 1 P. Based on the media formulation used in the study, AD7 presents a N:P ratio of 32:1 and BG-11 100:1. Thus, supporting our previous hypothesis that both media, and BG-11 in particular, may be P limited.

The autotrophic growth of cyanobacteria requires a source of inorganic C. This is typically provided as CO$_2$ which can be supplied as air (0.04% CO$_2$), CO$_2$ enriched air (typically 1-5%) or in the form of bicarbonate salts. Installing a gas supply to cyanobacterial cultures can be costly and presents a logistical challenge. Therefore, bicarbonate salts are a popular low-cost inorganic C source in cyanobacterial medium. Here, we tested the addition of bicarbonate to BG-11 and AD7 in the range of 0 to 100 mM (Fig. 4c, Supplementary Data Table S4). The addition of bicarbonate improved the growth of PCC 6803 from 35 mM and achieved a maximum biomass accumulation at approximately 50 mM. For UTEX 2973 and UTEX 3154 there was no significant difference in biomass accumulation in the tested range. In our previous experiments we have shown that BG-11 is P limited (Fig. 4b). This could explain the lack of response of UTEX 2973 to the varying bicarbonate concentrations. In regard to UTEX 3154, a previous study in *Synechococcus* sp. PCC 7002 showed that significant biomass accumulation was only visible with bicarbonate concentrations higher than 500 mM[32]. While this is an indication that the range tested here may not encompass the ideal bicarbonate values for this cyanobacterium, *Synechococcus* sp. PCC 7002 and UTEX 3154 present significant genetic differences therefore it is difficult to make definite conclusions. Finally, another factor could be light limitation. In our experiments we used 20±5 µmol photons m^{-2} s^{-1} while the maximum growth rates of UTEX 2973 were reported at 1500 µmol photons m^{-2} s^{-1}, 42°C and 5% CO$_2$[27]. However, this is not directly comparable as the light path in our microfluidic setup is 1.6 mm

as opposed to the 27 mm used to determine the maximum growth rates of UTEX 2973 in the literature. Further tests would be needed to establish a comparison.

Fig. 4 Highly resolved dose-response screenings of key macronutrients in UTEX 3154, UTEX 2973 and PCC 6803. a Normalized autofluorescence after 7 days in response to varying concentrations of $NaNO_3$. **b** Normalized autofluorescence after 7 days in response to varying concentrations of K_2HPO_4 (UTEX 2973, PCC 6803) or KH_2PO_4 (UTEX 3154). **c** Normalized autofluorescence after 7 days in response to varying concentrations of bicarbonate ($NaHCO_3$). Data points are averages of 10±3 droplets. Error bars represent standard deviation.

Salinity of the growth medium is a critical factor as high salinities can induce a variety of stresses and consequently pose a challenge to cell survival[33]. In addition, future large-scale cultivation of cyanobacteria must be done in seawater due to the limited freshwater resources present on Earth. Therefore, there has been an increased interest in prospecting for and developing salt tolerant cyanobacterial chassis. Here, we used our microfluidics platform to determine the salt tolerance of PCC 6803, UTEX 2973 and UTEX 3154 (Fig. 5, Supplementary Data Table S5). As expected, the two freshwater strains exhibit lower salt tolerances than UTEX 3154. UTEX 2973 exhibits the lowest salt tolerance with a decline in biomass accumulation starting at 0.3 M NaCl. PCC 6803 maintains similar levels of biomass accumulation until 0.65 M with a sharp decline observed thereafter. Total inhibition was observed of both PCC 6803 and UTEX 2973 at 0.7 M NaCl. UTEX 3154 accumulates similar biomass levels until approximately 0.8 M, whereafter a sharp decline is also observed. It is worth noting here that the base AD7 used in this study contains 308 mM NaCl and 8 mM KCl therefore the data show that UTEX 3154 can tolerate salt concentrations up to 1.1 M NaCl. These values are in accordance with the published literature on salt tolerance in cyanobacteria[34]. Our data show that this microfluidics setups can be used for high-resolution screening for optimum salinity cultivation conditions of single-celled cyanobacteria and could

serve as an effective high-throughput method to screen for strains with increased salt tolerance in future studies.

Fig. 5 1D screening of NaCl tolerance in cyanobacteria. Normalized autofluorescence after 7 days in response to varying concentrations of NaCl shown for three different cyanobacterial strains, UTEX 3154, UTEX 2973 and PCC 6803. Data points are averages of 10±3 droplets. Error bars represent standard deviation.

Combinatorial effect of phosphorus and nitrogen on the growth behavior of cyanobacteria

The above results demonstrate that our microfluidics platform can rapidly screen a wide range of single parameters (i.e. 1D screening). However, it is often of interest to quickly screen a combination of parameters. Therefore, we took advantage of the platform capabilities to simultaneously screen two independent parameters (i.e. 2D screening). The output of 2D screening experiments allows us to generate a response surface where we can estimate the outcome of specific response variables (e.g. biomass accumulation) under the effect of two parameters simultaneously. For our 2D proof of concept we chose to screen N (NaNO$_3$) and P (K$_2$HPO$_4$ or KH$_2$PO$_4$) sources in conjunction (Fig. 6, Supplementary Data Table S6, S7, S8). These two parameters were chosen because the N:P ratio is one of the key parameters that influences algal growth and rapidly optimizing N and P concentrations is fundamental for cost-efficient scale-up of microalgal cultures[35]. Our data show that final biomass values in PCC 6803 and UTEX 2973 peaked at the maximum N values tested (0.45 mM K$_2$HPO$_4$/30 mM NaNO$_3$ for PCC 6803 and 0.4 mM K$_2$HPO$_4$/30 mM NaNO$_3$ for UTEX 2973) (Fig. 6a, b). Interestingly, an increase in N at low P values or an increase of P at low N values was not sufficient to obtain high biomass values. It was only when both parameters were increased simultaneously that a significant increase in final biomass values was observed. This contrasts with the conclusions from the 1D screening data where P seemed to be limiting the culture. This suggests that first, it is more efficient to find a good balance between N and P instead of just increasing one parameter and second, 2D screening is fundamental to understanding nutrient dynamics in cyanobacterial cultures. Regarding the N:P ratio, both strains achieved their maximum biomass values at a ratio of approximately 100:1. This is the same ratio as BG-11 which suggests that the classic cyanobacterial medium has a good N:P ratio but would benefit from higher concentrations of both N and P. For UTEX 3154 no clear trend was observed within the tested N:P range (Fig. 6c). Together with the 1D screening data, this suggests that N may be the limiting nutrient in the AD7. However, the possibility that a nutrient other than N or P is limiting the culture remains open.

Fig. 6 2D effector screening of nitrogen and phosphorus source in cyanobacterial cultivation using standard growth media. a PCC6803 autofluorescence after 7 days in response to varying concentrations of $NaNO_3$ and K_2HPO_4 in BG-11 medium. **b** UTEX 2973 autofluorescence after 7 days in response to varying concentrations of $NaNO_3$ and K_2HPO_4 in BG-11 medium. **c** UTEX 3154 autofluorescence after 7 days in response to varying concentrations of $NaNO_3$ and KH_2PO_4 in AD7 medium. Data points are averages of approximately 5±3 droplets.

Improved N:P ratios from 2D screening increase biomass accumulation in high density cultivation

To assess whether the optimal N:P concentrations suggested by the microfluidic setup would translate to a more widely used cultivation setup, we carried out growth assays in a laboratory setting. To this end, PCC 6803 and UTEX 2973 were grown in high-density cultivators where gaseous CO_2 is supplied via integrated semi-permeable membranes. With this setup, growth was compared in standard BG-11 medium (0.175 mM K_2HPO_4, 17.6 mM $NaNO_3$) and BG-11 with the optimized N:P concentrations obtained from the 2D N:P microfluidic screening experiment. More specifically, 0.45 mM K_2HPO_4 with 30 mM $NaNO_3$ for PCC 6803 and 0.4 mM K_2HPO_4 with 30 mM $NaNO_3$ for UTEX 2973. For both PCC 6803 and UTEX 2973 significant increases ($p < 0.05$) of final biomass values of 7.4% (Fig. 7a) and 15.7% (Fig. 7b), respectively, could be observed. Overall, this confirmed that the findings from the microfluidic experiments are transferable to biotechnologically relevant high-density cultivation setups.

Fig. 7 High-density cultivation in BG-11 medium containing N:P ratios optimized through 2D microfluidic screening. Growth of **a** PCC 6803 and **b** UTEX 2973 in standard vs. optimized N/P ratio observed by measuring optical density (OD) at 750 nm. n=3 and error bars represent standard deviation.

Conclusions

To achieve cost-effective scale-up of cyanobacteria it is crucial to screen for the ideal cultivation conditions. In particular, medium optimization can significantly increase biomass

and product yields. However, the cost and time investment required to test different levels of key nutrients, and the possible interactions amongst them, is prohibitive with standard reactor setups. Recently, miniaturized multiplex screening has been suggested as a route to tackle the large parameter fields of media optimization. In this study we used a droplet-based microfluidic technique to improve the cultivation of three different biotechnologically relevant cyanobacterial strains. Our proof of concept demonstrated that the strains could be successfully cultivated, and growth data could be collected online with non-invasive, in-situ measurements. The 1D-screening data confirmed that our microfluidic platform is well-suited for the investigation of cyanobacterial response towards single nutrients. In addition, the 2D-screening allowed us to easily explore the two-dimensional space of nutrient interactions. In conclusion, this study shows that microfluidics can play a valuable role in improving the cost-effectiveness of cyanobacterial cultivation. We also expect that this microfluidics approach can be generalized to other applications such as expression level optimization of engineered cyanobacteria and bioprospecting.

Author Contributions: Conceptualization and study design: JC, DAR and JAZZ. Experimental Work and Data Analysis: JC, DAR, TX and JAZZ. Funding acquisition and project administration JC, DAR, GAG and JAZZ. Original manuscript draft preparation JC, DAR and JAZZ. All authors have read and approved the final manuscript.

Acknowledgments: We thank Prof. Michael Köhler for the fruitful discussion. We thank Frances Möller and Steffen Schneider for lab assistance. JC gratefully acknowledges financial support from the project "Screen | in drop lines" (2016FE9016) by Thüringer Aufbaubank and a habilitation scholarship from the TU Ilmenau, DAR was supported by the Alexander von Humboldt Foundation and by the IMPULSE^{project} (IP-2020-03, Friedrich Schiller University Jena). This work was funded by the Deutsche Forschungsgemeinschaft (DFG, German Research Foundation) under Germany's Excellence Strategy – EXC 2051 – Project-ID 390713860 (JAZZ) and the by the Deutsche Forschungsgemeinschaft (DFG, German Research Foundation) – CRC 1127/2 – 239748522 (JAZZ).

Conflicts of Interest: The authors declare no competing interests.

Data availability: All cyanobacterial strains used in this study are available for purchase from the Pasteur Culture Collection, Paris (France) or the UTEX Culture Collection of Algae, University of Texas, Austin (USA). The raw data of all experiments are provided in the Supplementary Data files.

References

1. Araújo, R. *et al.* Current Status of the Algae Production Industry in Europe: An Emerging

    Sector of the Blue Bioeconomy. *Front. Mar.Sci.* **7**, 626389 (2021).

2. Harrison, D. J. *et al.* Micromachining a Miniaturized Capillary Electrophoresis-Based

    Chemical Analysis System on a Chip. *Science* **261**, 895–897 (1993).

3. Kopp, M. U., Mello, A. J. de & Manz, A. Chemical Amplification: Continuous-Flow PCR on

    a Chip. *Science* **280**, 1046–1048 (1998).

4. Schneegaß, I. & Köhler, J. M. Flow-through polymerase chain reactions in chip thermocyclers. *Rev. Mol. Biotechnol.* **82**, 101–121 (2001).

5. Köhler, J. M. *et al.* Digital reaction technology by micro segmented flow—components, concepts and applications. *Chem. Eng. J.* **101**, 201–216 (2004).

6. Debs, B. E., Utharala, R., Balyasnikova, I. V., Griffiths, A. D. & Merten, C. A. Functional single-cell hybridoma screening using droplet-based microfluidics. *Proc. Natl Acad. Sci. USA* **109**, 11570–11575 (2012).

7. Boedicker, J. Q., Li, L., Kline, T. R. & Ismagilov, R. F. Detecting bacteria and determining their susceptibility to antibiotics by stochastic confinement in nanoliter droplets using plug-based microfluidics. *Lab Chip* **8**, 1265–1272 (2008).

8. Funfak, A., Cao, J., Knauer, A., Martin, K. & Köhler, J. M. Synergistic effects of metal nanoparticles and a phenolic uncoupler using microdroplet-based two-dimensional approach. *J. Environ. Monit.* **13**, 410–415 (2011).

9. Cao, J. *et al.* Uncovering toxicological complexity by multi-dimensional screenings in microsegmented flow: modulation of antibiotic interference by nanoparticles. *Lab Chip* **12**, 474–484 (2012).

10. Kaminski, T. S., Scheler, O. & Garstecki, P. Droplet microfluidics for microbiology: techniques, applications and challenges. *Lab Chip* **16**, 2168–2187 (2016).

11. Cao, J., Goldhan, J., Martin, K. & Köhler, J. M. Investigation of mixture toxicity of widely used drugs caffeine and ampicillin in the presence of an ACE inhibitor on bacterial growth using droplet-based microfluidic technique. *Green Process Synth.* **2**, 591–601 (2013).

12. Mahler, L. *et al.* Highly parallelized droplet cultivation and prioritization of antibiotic producers from natural microbial communities. *eLife* **10**, e64774 (2021).

13. Kürsten, D., Cao, J., Funfak, A., Müller, P. & Köhler, J. M. Cultivation of *Chlorella vulgaris* in microfluid segments and microtoxicological determination of their sensitivity against CuCl$_2$ in the nanoliter range. *Eng. Life Sci.* **11**, 580–587 (2011).

14. Funfak, A., Brösing, A., Brand, M. & Köhler, J. M. Micro fluid segment technique for screening and development studies on *Danio rerio* embryos. *Lab Chip* **7**, 1132–1138 (2007).

15. Cao, J., Chande, C., Kalensee, F., Schüler, T. & Köhler, M. Microfluidically supported characterization of responses of *Rhodococcus erythropolis* strains isolated from different soils on Cu-, Ni-, and Co-stress. *Braz. J. Microbiol.* **52**, 1405–1415 (2021).

16. Kürsten, D. *et al.* Identification of response classes from heavy metal-tolerant soil microbial communities by highly resolved concentration-dependent screenings in a microfluidic system. *Methods Ecol. Evol.* **6**, 600–609 (2015).

17. Wang, L. & Dandy, D. S. A microfluidic concentrator for cyanobacteria harvesting. *Algal Res.* **26**, 481–489 (2017).

18. Yao, L. *et al.* Pooled CRISPRi screening of the cyanobacterium *Synechocystis* sp PCC 6803 for enhanced industrial phenotypes. *Nat. Commun.* **11**, 1666 (2020).

19. Abalde-Cela, S. *et al.* High-throughput detection of ethanol-producing cyanobacteria in a microdroplet platform. *J. R. Soc. Interface* **12**, 20150216 (2015).

20. Włodarczyk, A., Selão, T. T., Norling, B. & Nixon, P. J. Newly discovered *Synechococcus* sp. PCC 11901 is a robust cyanobacterial strain for high biomass production. *Commun. Biol.* **3**, 1–14 (2020).

21. Stanier, R. Y., Kunisawa, R., Mandel, M. & Cohen-Bazire, G. Purification and Properties of Unicellular Blue-Green Algae (Order Chroococcales). *Bacteriol. Rev.* **35**, 171–205 (1971).

22. Stevens, S. E., Patterson, C. O. P. & Myers, J. The Production of Hydrogen Peroxide by Blue-Green Algae: A Survey[1]. *J. Phycol.* **9**, 427–430 (1973).

23. Arnon, D. I., McSwain, B. D., Tsujimoto, H. Y. & Wada, K. Photochemical activity and components of membrane preparations from blue-green algae. I. Coexistence of two photosystems in relation to chlorophyll *a* and removal of phycocyanin. *Biochim. Biophys. Acta Bioenerg.* **357**, 231–245 (1974).

24. Bähr, L., Wüstenberg, A. & Ehwald, R. Two-tier vessel for photoautotrophic high-density cultures. *J. Appl. Phycol.* **28**, 783–793 (2016).

25. Cao, J. *et al.* Droplet-Based Screening for the Investigation of Microbial Nonlinear Dose–Response Characteristics System, Background and Examples. *Micromachines* **11**, 577 (2020).

26. Yu, J. *et al. Synechococcus elongatus* UTEX 2973, a fast growing cyanobacterial chassis for biosynthesis using light and CO_2. *Sci. Rep.* **5**, 8132 (2015).

27. Ungerer, J., Lin, P.-C., Chen, H.-Y. & Pakrasi, H. B. Adjustments to Photosystem Stoichiometry and Electron Transfer Proteins Are Key to the Remarkably Fast Growth of the Cyanobacterium *Synechococcus elongatus* UTEX 2973. *mBio* **9**, e02327-17 (2018).

28. Vermass, W. F. J., Rutherford, A. W. & Hansson, Ö. Site-directed mutagenesis in photosystem II of the cyanobacterium *Synechocystis* sp. PCC 6803: Donor D is a tyrosine residue in the D2 protein. *Proc. Natl Acad. Sci. USA* **85**, 8477–8481 (1988).

29. Howitt, C. A., Udall, P. K. & Vermaas, W. F. J. Type 2 NADH Dehydrogenases in the Cyanobacterium *Synechocystis* sp. Strain PCC 6803 Are Involved in Regulation Rather Than Respiration. *J. Bacteriol.* **181**, 3994–4003 (1999).

30. van Alphen, P., Abedini Najafabadi, H., Branco dos Santos, F. & Hellingwerf Klaas, J. Increasing the Photoautotrophic Growth Rate of *Synechocystis* sp. PCC 6803 by Identifying the Limitations of Its Cultivation. *Biotechnol. J.* **13**, 1700764 (2018).

31. Kim, H. W., Vannela, R., Zhou, C. & Rittmann, B. E. Nutrient acquisition and limitation for the photoautotrophic growth of *Synechocystis* sp. PCC6803 as a renewable biomass source. *Biotechnol. Bioeng.* **108**, 277–285 (2011).

32. De Farias Silva, C. E., Gris, B., Sforza, E., La Rocca, N. & Bertucco, A. Effects of Sodium Bicarbonate on Biomass and Carbohydrate Production in *Synechococcus* PCC 7002. *Chem. Eng. Trans.* **49**, 241–246 (2016).

33. Pade, N. & Hagemann, M. Salt Acclimation of Cyanobacteria and Their Application in Biotechnology. *Life* **5**, 25–49 (2015).

34. Cui, J., Sun, T., Chen, L. & Zhang, W. Engineering salt tolerance of photosynthetic cyanobacteria for seawater utilization. *Biotechnol. Adv.* **43**, 107578 (2020).

35. Slade, R. & Bauen, A. Micro-algae cultivation for biofuels: Cost, energy balance, environmental impacts and future prospects. *Biomass Bioenerg.* **53**, 29–38 (2013).