# The Bioregistry: Unifying the Identification of Biomedical Entities through an Integrative, Open, Community-driven Metaregistry

**Charles Tapley Hoyt**[1], **Meghan Balk**[2], **Tiffany J. Callahan**[3], **Daniel Domingo-Fernández**[4,5], **Melissa A. Haendel**[3], **Harshad B. Hegde**[6], **Daniel S. Himmelstein**[7], **Klas Karis**[1], **John Kunze**[8], **Tiago Lubiana**[9], **Nicolas Matentzoglu**[10], **Julie McMurry**[11], **Sierra Moxon**[6], **Christopher J. Mungall**[6], **Adriano Rutz**[12,13], **Deepak R. Unni**[6,14], **Egon Willighagen**[15], **Donald Winston**[16], and **Benjamin M. Gyori**[1,*]

[1]Laboratory of Systems Pharmacology, Harvard Medical School
[2]University of Arizona
[3]University of Colorado Anschutz Medical Campus
[4]Department of Bioinformatics, Fraunhofer SCAI
[5]Enveda Biosciences
[6]Lawrence Berkeley National Laboratory
[7]Related Sciences
[8]California Digital Library, University of California
[9]School of Pharmaceutical Sciences, University of São Paulo
[10]Semanticly
[11]University of Colorado, Anschutz Medical Campus
[12]School of Pharmaceutical Sciences, University of Geneva
[13]Institute of Pharmaceutical Sciences of Western Switzerland, University of Geneva
[14]European Molecular Biology Laboratory
[15]Department of Bioinformatics - BiGCaT, NUTRIM, Maastricht University
[16]Polyneme LLC
[*]corresponding author(s): Benjamin M. Gyori (benjamin_gyori@hms.harvard.edu)

## ABSTRACT

The standardized identification of biomedical entities is a cornerstone of interoperability, reuse, and data integration in the life sciences. Several registries have been developed to catalog resources maintaining identifiers for biomedical entities such as small molecules, proteins, cell lines, and clinical trials. However, existing registries have struggled to provide sufficient coverage and metadata standards that meet the evolving needs of modern life sciences researchers. Here, we introduce the Bioregistry, an integrative, open, community-driven metaregistry that synthesizes and substantially expands upon 20 existing registries. The Bioregistry addresses the need for a sustainable registry by leveraging public infrastructure and automation, and employing a progressive governance model centered around open code and open data to foster community contribution. The Bioregistry can be used to support the standardized annotation of data, models, ontologies, and scientific literature, thereby promoting their interoperability and reuse. The Bioregistry can be accessed through https://bioregistry.io and its source code and data are available under the MIT and CC0 Licenses at https://github.com/biopragmatics/bioregistry.

## 1 Introduction

One of the key challenges in creating and maintaining Findable, Accessible, Interoperable, and Reusable (FAIR)[1–3] data in the life sciences is the standardized identification of entities ranging from chemicals, proteins, and diseases to patents and publications. These entities are typically curated in *identifier resources* (e.g., ontologies and databases) such as Chemical Entities of Biomedical Interest (ChEBI)[4], UniProt[5], and PubMed that assign to each entity a *local unique identifier* (i.e., accession number). Each resource defines an internally consistent pattern for its entities' local unique identifiers, such as the combination of numbers and letters found in UniProt identifiers (e.g., `P0DP23`) or the simple numbers found in PubMed identifiers (e.g., `29175850`). Uniform resource identifiers (URIs) (e.g., https://www.uniprot.org/uniprot/P0DP23) and

compact uniform resource identifiers (CURIEs) (e.g., `uniprot:P0DP23`) have become the predominant syntaxes used in the life sciences for identifying entities that encode both the resource from which the entity originates and its local unique identifier[6]. URIs encode the resource with a *URI prefix* (e.g., `https://www.uniprot.org/uniprot/`) while CURIEs encode it with a *prefix* (e.g., `uniprot`).

However, even when using URIs and CURIEs, a number of challenges remain in establishing consistency and interoperability. Namely, several different incompatible URIs and CURIEs can be used to refer to the same entity. For example, the local unique identifier `P0DP23` for the entry in UniProt[5] about the Calmodulin-1 protein can be represented by at least seven distinct URIs and three distinct CURIEs (see Supplementary Tables 1 and 2 for details). This problem is compounded when attempting to integrate multiple resources, a cornerstone of modern computational life sciences. For example, genomic data from HGNC[7] can not be readily integrated with biochemical reactions data from Rhea[8] because HGNC uses the prefix `ec-code` and Rhea uses the prefix `EC` when referring to entities in the Enzyme Commission identifier resource[9]. Similarly, many biomedical resources construct local unique identifiers for the same entity in the Enzyme Commission identifier resource differently, e.g., `1.4.-.-` in the Gene Ontology (GO)[10], `1.4.*` in ChEBI, and `1.4` in IntEnz[11] for *Oxidoreductases acting on the CH-NH2 group of donors*.

In order to standardize the usages of URIs and CURIEs and therefore enable their interoperability, a *registry* containing canonical, validatable definitions of identifier resources that, for each, includes a prefix, a URI prefix, a local unique identifier pattern, and other associated metadata is needed. Registries thus capture for each identifier resource how to construct, parse, and interchange canonical URI and CURIE. A registry can be used by external biomedical resources to standardize the way they reference entities (e.g., database cross-references appearing in ontologies) to promote integration with other resources, as well as by consumers to navigate prefixes and their associated metadata. Multiple registries[12–14] have been previously built for this purpose, but they each suffer from substantial gaps in their coverage of known resources, the metadata captured about these resources, and lack interoperability among each others' entries. For example, the National Center for Biotechnology Information Taxonomy Database (NCBITaxon)[15] is prefixed as `taxonomy` in Identifiers.org[12] and as `NCBITAXON` in BioPortal[16].

These issues are exacerbated by shortcomings in existing registries' governance and curation workflows, which impede their ability to stay current, trustworthy, and engage the community as the landscape of life science resources rapidly evolves. These issues include, that they 1) are built on private infrastructure within an institution; 2) are maintained by small, private groups that - due to under-funding - struggle to respond to requests; 3) lack adequate support for external contributions 4) are neither versioned nor archived. As an alternative to general-purpose registries, numerous projects (e.g., GO, Cellosaurus[17], GenBank[18]) have created their own registries, however, these each only cover identifier resources relevant for the given project, and use standards that are only internally consistent to the project. Finally, several services act as registries but are by design limited in scope to include a selected set of resources and provide incomplete metadata necessary to promote the standardization of references. These include the Open Biomedical Ontologies (OBO) Foundry[19], Ontology Lookup Service (OLS)[20], and BioPortal[16]. A detailed survey of the governance and maintenance models for existing registries can be found in Supplementary Table 3. Overall, the content of any one registry does not reflect the evolving landscape of biomedical resources and thus satisfy user needs.

To overcome the limitations of existing registries, a new approach for building a biomedical registry is necessary, which ideally fulfills the three requirements: 1) integrative, 2) open, and 3) community-driven. First, an *integrative* registry re-uses, improves, and extends on existing registries. Given that existing registries define conflicting standards (i.e., assign conflicting prefixes, URI prefixes, or other metadata for the same identifier resource) and therefore lack interoperability, this necessitates alignment and harmonization among resources in each registry. Second, an *open* registry makes its underlying data and associated code available under permissive licenses in a public, version-controlled repository, and relies on free, publicly available infrastructure for semi-automated quality control and deployment. Third, a *community-driven* registry solicits contributions from community members and provides an appropriate technical platform and governance structure to support this. This technical platform needs to support discussion and feedback as well as quality assurance workflows tightly coupled to the underlying open data, code, and infrastructure. Overall, these properties are expected to promote the sustainability and longevity of the registry.

To address these limitations, we introduce the Bioregistry: an integrative, open, and community-driven metaregistry. The Bioregistry integrates content from existing registries, semi-automatically identifies equivalences between records in existing registries, and resolves conflicts between them using a novel workflow. The result of this alignment makes the Bioregistry a *metaregistry* (i.e., a registry of registries) which, for each resource, maintains cross-registry mappings to serve as an interoperability layer between conflicting standards. The Bioregistry also includes substantial manual curation for resources not appearing in any pre-existing registry, and additional curation extends and improves on the metadata associated with resources in these registries. As a result of this process, the Bioregistry expands substantially on the content of each individual pre-existing registry (e.g., 81% over Identifiers.org) as well as all aligned registries combined (see Table 2 on alignment). The Bioregistry also provides a higher granularity data model compared to any existing registry thereby better supporting

integration. The Bioregistry is built using open source code, open data, and leverages public infrastructure and automation to support its maintenance and extension. Further, it has well-defined contribution guidelines and a multi-institutional governance model that enables contributions directly from the broader community to support the project's longevity.

The Bioregistry (0.5.36) integrates content from and aligns 20 external registries and contains 1,410 individual records. These records extend on each prior registry (as compared to e.g., 838 records in BioContext[21] and 796 in Identifiers.org[12]), as well as all aligned registries combined: 159 of the Bioregistry's 1,410 records are novel, i.e. they do not appear in any existing registry. The Bioregistry also adds novel curated metadata for 807 of the remaining 1,238 records (65% of all records). A summary of the content captured in Bioregistry is provided in Table 1. We provide detailed metrics and comparison to other resources in the Results section.

| Category | Count |
|---|---|
| External registries imported | 20 |
| Individual resources represented | 1,418 |
| Cross-registry resource mappings | 6,675 |
| Contributors | 15 |

**Table 1.** Overview statistics of the Bioregistry version 0.5.36 (2022-07-07).

The Bioregistry has already been integrated with several projects aimed at data integration, knowledge assembly, and semantically annotated publications, described in section 3 on use cases and integrations. Current integrations of Bioregistry include BridgeDb[22], PheKnowLator[23], Manubot[24], Biomappings[25], SSSOM[26], INDRA[27], and the OBO Foundry[19].

The Bioregistry is available through an interactive web portal (https://bioregistry.io), an OpenAPI-documented web service (https://bioregistry.io/apidocs), a Python software package (https://pypi.org/project/bioregistry), and a Docker image (https://hub.docker.com/r/biopragmatics/bioregistry). All underlying data, code, and governance documentation are accessible through GitHub (https://github.com/biopragmatics/bioregistry) under the MIT and CC0 licenses and archived on Zenodo[28].

## 2 Results

### Bioregistry Data Model

The Bioregistry uses a granular and extensible data model to represent records of identifier resources. Required fields for each record include a canonical prefix, a human-readable label, a homepage, and a description. The data model also allows for multiple optional fields including the license, version, prefix synonyms for the resource (a full list can be found in the Data Model section of the Supplement), and capturing whether the resource is deprecated or proprietary. Each record can further include an example local unique identifier, a regular expression pattern for validating local unique identifiers, and a URI format string for constructing URIs from local unique identifiers. Records describing ontologies can include optional download links for associated OBO, OWL, and OBO Graph JSON artifacts. To keep contributions traceable and provide attribution, each record captures the submitter and reviewer who contributed to the entry. Records can also be grouped into collections for better contextualization, such as prefixes useful for the Semantic Web (e.g., DC, FOAF, RDF, RDFS).

Importantly, the Bioregistry captures not only individual resource records but also semantic relationships between records (including e.g., *depends on*, which asserts that one resource reuses terms from another, such as GO depends on ChEBI, and mappings of each resource to external registries where it appears. These additional relations constitute the Bioregistry's *metaregistry*, a term meant to represent the fact that it creates links among previously incompatible resources through a set of cross-registry mappings.

The Bioregistry data model is described in detail in the *Data Model* section of the Supplement. A comparison between the data model and various properties of the Bioregistry and external registries in Table 2 demonstrates the heterogeneity of metadata standards in external registries and the flexibility of the Bioregistry to represent higher granular metadata. For example, this enables the Bioregistry to represent deprecated and obsolete records for posterity, such as hgnc.genefamily (the HGNC Gene Family resource[29]) which was replaced by hgnc.genegroup and casspc (Eschmeyer's Catalog of Fishes[30]) which is used by the Teleost Taxonomy Ontology[31] and Vertebrate Taxonomy Ontology[32] but was itself never published.

### Integration and harmonization of existing registries

The Bioregistry imports records from 20 external registries. We divided registries into distinct groups to which we applied different import policies ranging from registries imported entirely to ones from which metadata for only select records are imported (see section 5 on Methods). The Bioregistry uses a multi-stage process in which registries are sequentially imported

**Table 2.** An overview on registries covering biomedical ontologies, controlled vocabularies, and databases.

| Registry | Name | Homepage | Desc. | Example ID | ID Pattern | Provider | Alt. Providers | Alt. Prefixes | License | Version | Contact | FAIR Data | Search | Prefix Provider | Resolver | Lookup |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Bioregistry | Y | Y | Y | Y | o | o | o | o | o | o | o | Y | Y | Y | Y | |
| AberOWL[33] | Y | Y | Y | - | | - | - | | | o | | Y | Y | Y | | Y |
| AgroPortal[34] | Y | Y | Y | - | | - | - | | o | o | o | | | Y | | |
| BioContext[21] | | | | | | o | | | | | | Y | | Y | | |
| Biolink[35] | Y | | | | | Y | | | o | | | Y | | | | |
| BioPortal[16] | Y | Y | Y | - | | - | - | | | Y | o | | | Y | | |
| Cellosaurus[17] | Y | Y | | | | Y | | | | | | Y | | | | |
| CHEMINF[36] | Y | | | | | | | | | | | | | Y | | |
| CropOCT[37] | Y | -* | | - | | - | - | | | | | Y | Y | Y | | |
| EcoPortal[38] | Y | o | Y | - | | - | - | | o | o | o | | | Y | | |
| FAIRSharing[39] | Y | Y | Y | | | | | | | | Y | | Y | Y | | |
| GO[10] | Y | o | o | o | o | o | o | | | | | Y | | | | |
| Identifiers.org[12] | Y | Y | Y | Y | Y | Y | o | | | | | Y | Y | Y | Y | |
| N2T[13] | Y | Y | Y | Y | Y | Y | o | o | | | | Y | | Y | Y | |
| GenBank[18] | Y | Y | | Y | | | | | | | | | | | | |
| OBO Foundry[19] | Y | Y | Y | | | | | | Y | | Y | Y | | Y | Y | |
| OLS[20] | Y | o | Y | - | | - | - | | Y | o | o | Y | Y | Y | | |
| OntoBee[40] | Y | Y | Y | - | | - | - | | | | Y | | | Y | | Y |
| Prefix Commons[14] | Y | o | o | o | o | o | Y | o | | | | Y | Y | Y | | |
| UniProt[5] | Y | Y | | | | Y | | | | | | Y | Y | Y | | |
| Wikidata | Y | o | Y | o | o | o | o | | o* | o* | o* | Y | Y | Y | | |

A "Y" means the field is required. A "o" means it is part of the schema, but not required or incomplete on some entries. A blank cell means that it is not part of the metadata schema. A "-" means some fields (i.e., Example ID, Default Provider, Alternate Providers) are omitted because inclusion would be redundant, e.g., for lookup services like the OLS. The FAIR column denotes that a structured dump of the data is easily findable, accessible, and in a structured format in bulk. The search column means there is a URL into which a search query can be formatted to show a list of results. The prefix provider column means there is a URL into which a prefix can be formatted to show a dedicated page for its metadata. *Caveats: Several of Wikidata's fields can be accessed indirectly with alternative SPARQL queries. BioPortal's data is locked behind an API that requires a key and has rate limited access. The Crop Ontology Curation Tool does not list homepages because it is the homepage itself. Non-english language registries in the OntoPortal Alliance (https://ontoportal.org) were not included.

such that a record from a given registry is either 1) aligned with an existing Bioregistry record and a cross-registry mapping is created 2) added as a new record, or 3) set aside for manual curation (see section 5 on Methods). The key challenge in this import process is aligning (i.e., finding equivalences between) records since the external registries' records are partially overlapping and inconsistent. A novel contribution of the Bioregistry is that it explicitly represents equivalence mappings between its own records and records in external registries, creating a network of cross-registry mappings with Bioregistry as the hub constituting a metaregistry. We found that in many cases, cross-registry mappings are straightforward because the records' prefixes are exact string matches. However, we also found high heterogeneity among existing registries in the usage of capitalization (e.g., go vs. GO), punctuation (e.g. ec-code vs eccode), abbreviations (e.g., flybase vs. fb), and even different vocabulary (e.g., intenz vs. eccode) to represent the same resource, which results in fragmentation and lack of interoperability. The Bioregistry's alignment procedure recovers a total of 6,676 such cross-registry mappings thereby connecting resources across existing registries that were previously disconnected.

We additionally curated 388 synonyms used when referring to identifier resources outside registries such as in OBO Foundry ontology database cross-references. These synonyms support the registry alignment workflow and broaden the ability of Bioregistry to standardize references to identifier resources beyond just external registries.

We investigated how the content of the integrated Bioregistry compares to each individual external registry that it imports and aligns (Figure 1A). It covers several registries (BioContext[21], CHEMINF[36], Crop Ontology Curation Tool (CropOCT)[37],

OBO Foundry[19], OLS, Name-to-Thing (N2T)[13], Identifiers.org[12]) almost entirely (over 85% of the external registries' records are mapped to a Bioregistry record) while significantly expanding on the content of each of them from a minimum of +81% for Identifiers.org to a maximum of +6,980% for CHEMINF. The Bioregistry is able to align a smaller proportion of records in external registries such as FAIRSharing[39] (32.8%), BioPortal[16] (31.3%), Aber-OWL[33] (23.8%), and Wikidata (18.5%) due to several characteristics of each registry. For example, many records in FAIRSharing[39] do not refer to identifier resources, Wikidata contains many records lacking a biological scope, and Aber-OWL and BioPortal contain ontologies of heterogeneous quality which are queued for on-demand inclusion rather than automated ingestion into in the Bioregistry (see section 5 on Methods). Despite lower coverage of their entries, the Bioregistry still substantially expands on these external registries between a minimum of +81% for Aber-OWL to a maximum of +5,624% for EcoPortal[38].

**Figure 1. A)** Summarizes the pairwise overlap (in orange) between the prefixes in the Bioregistry and its integrated external registries. The blue sections show records that could not be aligned and the green sections represent additional prefixes available in the Bioregistry but not the external resource. The absolute number of records in the union of the external registry with the Bioregistry (accounting for known overlaps) are shown on the right as well as the percentage relative gain introduced by the Bioregistry in parentheses. **B)** A histogram that shows how many cross references each entry in the Bioregistry has to external registries. The green bar highlights the prefixes with no cross references that only appear in the Bioregistry. **C)** A schematic diagram depicting the Bioregistry as an interoperability layer between external registries. Using the NCBI Taxonomy identifier resource as an example, this subfigure shows the different resources' prefixes in purple boxes as well as additional synonyms used in various biomedical resources in orange boxes. The components of this figure are regenerated daily with GitHub Actions and stored in `https://github.com/bioregistry/bioregistry/tree/main/docs/img`.

We then investigated the frequency of appearance of each identifier resource in multiple registries (Figure 1B). We found

that only 7 resources appeared in more than 12 of the 20 external registries (including well-known resources such as GO, ChEBI, and NCBITaxon), and no resource appeared in more than 15, further illustrating the fragmented state of existing registries and the benefits of an integrative registry in having improved coverage. Further, the Bioregistry contains 159 novel prefixes not available in any other registry (Figure 1B, green bar). As an example, we examined NCBITaxon, one of the resources that appears in the largest number of existing registries. This identifier resource appears in 15 external registries under 7 different prefixes including taxon, taxonomy, and NCBITaxon (Figure 1C). In addition, the Bioregistry curates 9 prefix synonyms that appear in various non-registry biomedical resources (e.g., NCBI_Taxon_id, uniprot.taxonomy, NCBI_taxid), demonstrating the high heterogeneity observed across various identifier resources. Such cross-registry mappings and synonyms in the Bioregistry enable it to act as an interoperability layer to standardize across a large number of external registries and non-registry resources.

## Web portal for interactive and programmatic use

The contents of the Bioregistry can be browsed interactively through the web portal at https://bioregistry.io shown in Figure 2. The portal implements a powerful search feature to help users look up prefixes and CURIEs they encounter in various databases, ontologies, and other biomedical resources. The search feature extends to not only the prefix, synonyms, title, and description of each record, but also all of the corresponding fields in linked records from external registries (Figure 2A). The full prefix list can be browsed (Figure 2B) and each prefix page organizes and contextualizes all information available from novel curation in the Bioregistry as well as imported from external registries (Figure 2C, D). Notably, it links to external registry pages when mappings are available. For example, the page for NCBITaxon (https://bioregistry.io/ncbitaxon) links to a large number of external registry pages (Figure 2E). In addition to the data in the Bioregistry, this page constructs example URIs for first-party providers, third-party providers (e.g., OntoBee[40], OLS), and external resolvers (e.g., Identifiers.org, N2T) using a combination of information stored about external registries and programmatic logic in the underlying Bioregistry Python package (Figure 2F). The web portal provides several other features including generating pages for each of the external registries integrated into the Bioregistry that show their various properties and functionalities, facilitating curating and displaying user-generated collections of prefixes such as the list of Semantic Web prefixes at `https://bioregistry.io/collection/0000002`, and listing contributors. The portal also implements a resolver that allows for the uniform construction of URIs from CURIEs that are automatically redirected to the appropriate location based on the URI format string annotated to the CURIE's prefix. The Bioregistry's resolver uses the URI scheme `https://bioregistry.io/<prefix>:<local-unique-identifier>`, similar to the resolver schemes used by Identifiers.org and N2T. Bioregistry also makes available a programming language-agnostic RESTful interface that gives access to all functionality (e.g., search, autocompletion, record retrieval, URI generation) and is documented with OpenAPI/Swagger at `https://bioregistry.io/apidocs`. The underlying data used to generate each page can be downloaded in a variety of formats including JSON, YAML, TSV, RDF, and others (where applicable).

Finally, the portal serves as a hub for links to the code, data, documentation, and narrative surrounding the Bioregistry.

## Exported artifacts for data integration and reusability

The Bioregistry Github repository contains the root content of the database (i.e., the registry, metaregistry, and collections) as JSON files in a version controlled setting, serving as the single source of truth. In addition, it makes available several derived artifacts that are meant to facilitate integration with downstream systems and resources. These exported artifacts are regenerated daily, and made available via the web portal at `http://bioregistry.io/download` and are archived on Zenodo at doi:10.5281/zenodo.4390079.

In addition to the native JSON format, the Bioregistry data is made available as a set of YAML and TSV files to facilitate reuse. Further, equivalence mappings between resources in external registries are exported into the Simple Standard for Sharing Ontological Mappings (SSSOM)[26] format. SSSOM is a standard for sharing mappings between different namespaces that we use to represent mappings between resources appearing in different registries, such as the relations exemplified in Figure 1C.

The Bioregistry also provides a number of artifacts to facilitate integration with Semantic Web contexts and linked open data. First, we constructed an RDF schema for the Bioregistry that reuses elements from common Semantic Web vocabularies (e.g., DC, FOAF) and creates its own elements in the `bioregistry.schema` vocabulary described at `https://bioregistry.io/schema`. All components of the Bioregistry (i.e., the registry, metaregistry, collections) were jointly exported into RDF under this schema in several commonly used formats including N-Triples, Turtle and JSON-LD. This allows the Bioregistry to be loaded using triple stores (e.g., Virtuoso) or programming libraries (e.g. Python's RDFLib) and subsequently queried with SPARQL. We also assembled a network derived from the RDF export that can be browsed interactively on the Network Data Exchange (NDEx)[41] available at `https://bioregistry.io/ndex:860647c4-f7c1-11ec-ac45-0ac135e8bacf`.

Finally, the Bioregistry makes available several Semantic Web contexts that each map a set of prefixes (e.g., chebi) to a corresponding URI prefix (e.g., `http://purl.obolibrary.org/obo/CHEBI_`). These are derived from the root data using a set of policies for choosing a preferred prefix and URI format for resources in the registry. In addition to a general

**Figure 2.** Website Screenshots. **A)** The homepage of https://bioregistry.io prominently features a combine prefix search and CURIE resolution box along with links to all of the components of the site. **B)** The full registry of prefixes, resource names, and descriptions can be viewed and full text search performed. **C)** Each prefix page shows metadata about the corresponding resource, its identifiers, and serves as a hub for additional functionality in D, E, and F. **D)** The prefix page additionally includes the metaregistry's cross-registry mappings from the prefix to external registries' prefixes. **E)** Each external registry page shows metadata and the capability list of external resources. **F)** a sample identifier demonstrates all of the providers that can be resolved.

purpose context encompassing all of Bioregistry, we make available application-specific semantic contexts for integration with the OBO Foundry, and a context limited to prefixes useful for general Semantic Web resources.

## Maintenance model and governance

In contrast to the maintenance and governance structures employed by existing registries, the Bioregistry takes an alternative approach relying on open data, open code, open infrastructure, automated testing, and automated updating. Similar models have been adopted with great success in existing large collaborative projects such as the OBO Foundry. We accomplished this through several steps. First, the Bioregistry data is stored and versioned using GitHub (see section 5 on Methods). Second, anyone can propose additions or changes either directly by submitting a pull request to the Bioregistry repository or by filling out an appropriate issue template that triggers an automated generation of a pull request. Both create an open forum for discussion that invites a wide variety of stakeholders to engage (implementation details in Methods). Third, using GitHub allows for the technical implementation of quality control and quality assurance workflows that are coupled to pull requests in order to ensure that all changes meet a predefined set of standards, which are described explicitly and publicly in contribution guidelines as well as implicitly in the implementation of the quality assurance workflow. In addition to the open data, open code, open infrastructure philosophy, the Bioregistry project has sought out community guidance on how to establish a governance

model that is more robust to the fluctuation of funding and personnel who are actively working on and moderating the project. This has resulted in the establishment of a Review Team and a Development Team as well as a public minimal governance model that describes how to induct new members, how to remove members, who respectively has the technical authority and community responsibility to facilitate and ultimately judge changes to the underlying database and make changes to the code base, and how to improve the governance model over time. These teams have been initially seeded with members from diverse scientific backgrounds, locations, and institutions to further promote the durability of the project. These guidelines also include a liberal policy on authorship to further demonstrate the project's commitment to inclusivity.

## 3 Use cases and integrations

Here, we highlight several projects and standards that have already adopted various functionalities of the Bioregistry.

### Supporting Interoperable Data Annotation

Several projects use the Bioregistry to create *prefix maps*, or mappings between prefixes (e.g., `uniprot`) and their corresponding URI prefixes (e.g., `https://www.uniprot.org/uniprot/`). These support the the interoperability of data annotations and the conversion between URIs and CURIEs in Semantic Web applications. The Simple Standard for Sharing Ontological Mappings (SSSOM)[26] is a metadata standard for various mappings (e.g., equivalences) between ontology and database terms and an associated toolset (https://github.com/mapping-commons/sssom-py) based on LinkML (https://linkml.io) for loading, validating, and converting SSSOM content. The standard is meant to encourage higher quality curation in biomedical ontologies which often lack important metadata such as the mapping type, a standardized prefix and local unique identifier for the subject and object terms, provenance about how the mapping was generated, and provenance about who generated the mapping. The default prefix map used in validation is generated by the Bioregistry following the procedure described in the Supplementary.

Manubot[24] is a tool for open collaborative writing that aims to bring automation, customizability, and transparency to scholarly publishing. With Manubot, users write manuscripts using markdown with special support for citation by persistent identifiers represented as CURIEs such as `[@doi:10.1371/journal.pcbi.1007128]` (which can then be automatically turned into a full citation). Embedding CURIEs in manuscripts is especially valuable when referring to resources that are not citable manuscripts such as clinical trials (e.g., in a review of COVID-19[42]). Manubot initially added support for 700 CURIE prefixes by incorporating Identifiers.org but later switched to the Bioregistry which at the time added support for an additional 365 prefixes. Besides being more comprehensive, the Bioregistry's open contribution model allowed for addressing several longstanding issues with Identifiers.org including invalid regular expression patterns, missing prefixes, as well as inconsistencies due to some namespaces being redundantly embedded in identifiers.

We discuss the plans and considerations for adopting the Bioregistry for interoperable data annotation in software and projects including Biolink Model[35] and the Alliance of Genome Resources[43] in the Supplement.

### Validation and Quality Control of Entity References

Several projects use the Bioregistry to standardize or validate prefixes and local unique identifiers and promote interoperability and reusability. Biomappings[25] (`https://github.com/biopragmatics/biomappings`) is a repository for curated and predicted equivalence and related mappings between biomedical entities intended to fill the systematic gaps in availability of mappings between widely-used biomedical resources. It contains several workflows for generating new predicted mappings using Gilda[44] or custom scripts and provides a web-based curation interface for triaging predicted mappings and adding novel ones.

Biomappings uses open tools like git and GitHub combined with a permissive CC0 license to enable external contributions via pull requests. It ensures data integrity by validating all prefixes and local unique identifiers in the repository using the Bioregistry on each commit. The curation interface uses the Bioregistry to generate links to a high-quality web page describing each biomedical entity, making curation easier. Biomappings uses GitHub Pages and Jekyll to generate a web-based summary of its content that uses the Bioregistry to automatically generate links to the Bioregistry's prefix pages and to resolve CURIEs. Additionally, Biomappings provides an export in which the prefixes and local unique identifiers have been mapped to use redundant prefixes in identifiers for any systems that still rely on legacy Identifiers.org standards.

The Integrated Network and Dynamical Reasoning Assembler (INDRA)[27] assembles biomedical knowledge from natural language and databases in order to construct executable models. INDRA Statements contain references to biomedical entities that are grounded to one or more identifier resources. It uses the Bioregistry to first check that the prefixes used in the groundings are standardized, then it uses the Bioregistry to validate the associated unique local identifiers with each.

The Phenotype Knowledge Translator (PheKnowLator)[23] ecosystem constructs FAIR biomedical knowledge graphs using ontologies and reasoning with the addition of non-ontological data sources. PheKnowLator uses the Bioregistry to standardize references in CURIEs and URIs from both data types to provide semantically consistent results for downstream use cases. The

Bioregistry helps overcome significant challenges posed by ontologies (e.g., changing namespaces over time, data that is not from an ontology that does not provide valid namespaces or URIs), and their integration. The Bioregistry API has become a vital component of the build process and is used to standardize URIs for all entities and triples. It has also provided new opportunities to extend PheKnowLator's testing harness. Overall, the inclusion of this resource has improved the PheKnowLator Ecosystem and the knowledge graphs it produces.

### Contextualizing Entities with Website Links

Several projects use the Bioregistry to generate and resolve URIs within their APIs or user-facing websites in order to provide additional context to the entities they reference. BridgeDb is both an identifier mapping service and an interface for harmonizing disparate mapping services[22]. The Bioregistry has been integrated in BridgeDb's Java and R clients as well as Bacting[45] to enable looking up data sources by their Bioregistry prefixes and creation of identifier objects from CURIEs, and their full URIs that can be resolved by the Bioregistry's resolver, relying on the ability of the Bioregistry to standardize the given CURIE from its internal standard. This functionality and the BridgeDb identifier mappings databases allow CURIEs for Ensembl[46] to be translated to CURIEs for UniProt and Wikidata.

The Bioregistry has also been used in several websites to generate URLs for human genes, protein complexes, and other entities. For example, the DUB Portal[47], is a website summarizing experimental analyses of deubiquitinating enzymes and uses the Bioregistry to link to human genes in HGNC and protein families in the FamPlex vocabulary[48]. The website for FamPlex also uses the Bioregistry to standardize and link references for human genes; equivalence mappings to InterPro[49], Medical Subject Headings (MeSH)[50], GO, Complex Portal[51], NextProt[52] for protein families and complexes; and references for publications in PubMed and PubMed Central. Similarly, the interactive user interface for the BERN2[53] named entity recognition platform standardizes its biomedical entities and generates links using the Bioregistry.

### Unified Access to External Registries

Because of its integration of external registries, the Bioregistry is also useful for unified access to their respective data. The OBO Foundry[19] facilitates the coordinated development of biomedical ontologies through a set of guiding principles and community organization. Its associated repository (https://github.com/OBOFoundry/OBOFoundry.github.io) stores the structured metadata about each ontology, including their preferred prefix, title, homepage, description, and usages. Recently, the Bioregistry has been used to help support the standardization and maintenance of this metadata in several instances described in the *Use Case Details* section of the Supplement.

## 4  Discussion

### Limitations

The construction of the Bioregistry simultaneously balances three things: the legacy of previous registries, the need to provide a practical description of the way prefixes, CURIEs, and URIs are used in the wild, and the need for new perspectives. The construction of the Bioregistry as a descriptive resource leads to several limitations: First, it has limited ability to enforce itself as standard. Second, it does not have the ability to proactively prevent conflicts; non-trivial conflicts can still happen and have to be retroactively arbitrated. Third, it does not have the ability to advise and mentor creators of new identifier resources to make good choices in their identifier schemes, such as those suggested by McMurry *et al.* (2017).

While the Bioregistry provides a solution for standardizing the syntax of references to and between various biomedical resources, it is not itself sufficient for standardizing equivalent entities occurring in different semantic spaces (e.g., Monarch Disease Ontology (MONDO)[54], Medical Subject Headings (MeSH)[50], Human Phenotype Ontology (HPO)[55], and Human Disease Ontology (DO)[56] for phenotypes and diseases; Cell Ontology (CL)[57], Cell Line Ontology (CL)[58], Brenda Tissue Ontology (BTO)[59] for cell types; GO, Reactome[60], WikiPathways[61] for pathways) that often lead to redundancy when integrating disparate resources, such as when constructing knowledge graphs. However, the Bioregistry enables the standardization of the underlying CURIEs and URIs in these resources that makes existing solutions such as lexical mapping, graph-based entity alignment, and ontology merging more actionable.

A practical challenge in adopting the Bioregistry's standard for prefixes, CURIEs, and URIs in a given resource is the need to both update the data and associated code in the resource itself as well as in downstream consumers of the resource. This can manifest in several ways, including updating non-standard synonyms (e.g. many ontologies use `MSH` as a non-standard prefix for MeSH), updating non-standard construction of CURIEs (e.g., using redundant prefixes as prescribed by Identifiers.org like in `GO:GO:0006915`), or updating non-standard URIs (e.g., switching all ORCiD URIs to use the https protocol).

Many consumers of biomedical resources use exact string matching when handling CURIEs, meaning that any typographical or lexicographical variation between normalized Bioregistry CURIEs the expectations of the consumer (e.g., in their code) could slow adoption. While the Bioregistry has the facilities for converting between different context-dependent formulations of CURIEs, discussion remains ongoing between stakeholders on how to best adopt new external standards.

## Future Work on the Bioregistry

Following the initial development, deployment, publication, and early adoption of the Bioregistry, two grand ongoing challenges remain. The first is to be vigilant in the maintenance, enrichment, and extension of the content in the registry to best possible reflect the reality of the ever-changing landscape of biomedical identifier resources. While this has not been realized by previous registries, we believe that the combination of the technical infrastructure, philosophy, and governance model will support this endeavor. The second is to build and maintain a community of users. This entails both engaging developers, curators, and consumers of biomedical resources using prefixes, CURIEs, and IRIs to identify their challenges and improve the Bioregistry's data model, associated tooling, and content to help address them. Next, this entails facilitating communication and discussion between this diverse set of individuals and developers, curators, and consumers of other registries as well as offering training for usage of the Bioregistry and in its philosophy. Finally, this effort can extend to groups manually creating content such as databases and ontologies as well as automatically creating content with methods like named entity recognition and named entity normalization.

### Future Vision

We envision the Bioregistry could more broadly be used to promote and support the standardized annotation of data, models, ontologies, and scientific literature. First, the growing body of data being made available through publications and data repositories often lack standardized annotations to their records (e.g., columns in a table). If adopted, the Bioregistry could provide a consistent way of annotating these data to make them more FAIR, especially facilitating reuse.

Second, we envision the Bioregistry promoting and supporting the standardization of structured metadata associated with models and networks derived from data such as mechanistic models (e.g., in the BioModels database[62]), network-based models (e.g., in Network Data Exchange (NDEx)[41]), and machine learning models in order to promote their interoperability and reuse. This vision aligns well with the recommendations from a recent assessment of the reproduciblity of such models[63] that highlighted the more general importance of annotation using high-quality controlled vocabularies like GO and ChEBI.

Third, though biomedical ontologies have proven invaluable for data annotation, key ontologies still suffer from a lack of standardization of cross-references[19], making it difficult to merge and reason across ontologies and other structured data sources. Given that ontologies are often curated in public version-controlled repositories in standardized formats (e.g., OBO, OWL), the Bioregistry could be used to support their semi-automated standardization and maintenance in order to both reduce curation burden and potentiate their value in data integration scenarios.

Finally, we envision the potential adoption of the Bioregistry by academic publishers to support the standardized annotation of named entities in the text provided by authors (e.g., with BioFactoid[64]), and thereby decrease the need for doing expensive and error-prone post-processing like automated named entity recognition on publications to create structured representations.

## 5 Conclusion

We presented the Bioregistry, an integrative registry of biomedical identifier resources. The Bioregistry takes a novel approach to curation by importing and harmonizing data from external registries that can be further improved and extended with novel curation. It relies on an open data, open code, open infrastructure philosophy combined with a novel governance strategy to foster community contributions and engagement, and ensure its longevity and adoption. It uses public infrastructure for quality assurance, distribution, and deployment to promote transparency, reduce cost, and uncouple its long-term maintenance from a specific institution, funding source, or group of maintainers. While the Bioregistry demonstrates higher coverage and metadata granularity than other registries, it also explicitly encourages reuse and redistribution via its highly permissive CC0 license.

## Methods

The Bioregistry repository tightly couples the data to a Python package that facilitates loading, accessing, and modifying the root data files. It provides several high-level data structures and workflows for accessing and reasoning over the Bioregistry and external registries' integrated data, that support the quality assurance workflows (described above), the web application (described above), the alignment workflows (described below), the generation of derived artifacts (described above) and other user-facing functionality such as prefix standardization, CURIE standardization, and URI parsing. Full documentation for the Python software package can be found at `https://bioregistry.readthedocs.io`.

### Alignment

While manual curation of mappings to external registries is feasible when adding novel prefixes to the Bioregistry, the frequency of updates to external registries motivated the development and application of periodic automated and semi-automated alignment. We first stratify all external registries into three categories based on their available metadata, biomedical scope, focus on assigning global prefixes to resources, and governance. The first group with metadata availability, a biomedical scope, and focus

on assigning global prefixes contains the Identifiers.org, the OBO Foundry, OLS, N2T. The second group contains registries such as GO, NCBI, UniProt, Cellosaurus, and FAIRSharing that contain entries that do not correspond to identifier spaces which are excluded from the import. It additionally included registries like BioContext and BioPortal because of insufficient metadata that often made it impossible to determine what identifier resource the metadata refers to. The third group contains registries with minimal metadata or lack of biomedical focus such as Prefix.cc. The alignment algorithm first generates a lookup table based on the canonical prefix, preferred prefix, and all prefix synonyms (see the *Data Model* in the Supplement) for each resource in the Bioregistry. The prefix policies and automated quality assurance checks in the Bioregistry ensure that there are no collisions in this lookup table. For each external registry, the data are downloaded, normalized, and exactly one field is annotated as the external prefix. All Bioregistry prefixes that already have been mapped to an external prefix in the external registry are removed from the lookup table. Similarly, all external prefixes that already have mappings are not considered for new mappings. Each external prefix that matches an entry in the lookup table is assigned an automated mapping. A manually curated list of incorrect mappings and collisions are used to post-process the automated mappings and remove false negative mappings (see *Alignment Case Studies* in the Supplement). External prefixes that could not be mapped to a Bioregistry prefix are handled based on their stratification. For the first group of registries, the prefix is added as a new record to the Bioregistry. For the second group of registries, the prefix is added to a curation sheet along with its relevant metadata (e.g., title, homepage, example identifier) for later manual curation. For the third group of registries with minimal metadata, no report is made.

### Promoting sustainability and longevity through automation

The Bioregistry is hosted on GitHub (`https://github.com/biopragmatics/bioregistry`) to take advantage of its public, cloud-based version control, collaboration, and workflow management platforms. The single source of truth data (i.e., root data) for the Bioregistry is stored in version control. This implicitly versions all minor changes with git commit hashes and allows git tags to be used to mediate releases, which are automatically archived and re-distributed on both GitHub and Zenodo (`https://zenodo.org`).

The Bioregistry uses GitHub Actions as a continuous integration service to run code and data quality assurance to promote the maintainability and integrity of the resource (see *Testing Suite* in the Supplement). They further enable workflows for automatically generating pull requests and notifying reviewers to enable non-technical users to make submissions to the resource. The Bioregistry further uses GitHub Actions as a continuous delivery and continuous deployment system to run the aforementioned alignment workflows, generate derived artifacts, release code to the Python Package Index (PyPI), containerize code on Docker Hub (`https://hub.docker.com`), deploy the web application to Amazon Web Services (`https://aws.amazon.com`) on a daily basis (see *Automated Deployment* in the Supplement). Combined, the continuous integration, delivery, and deployment services allow contributors and consumers of the Bioregistry to more easily propose improvements, review them as a community, and see them reflected in the data and website without the need for manual intervention by the project team. Using an entirely free, public, and open public infrastructure to do so promotes longevity and sustainability by mitigating the monetary requirements. Further, the technical requirements of the deployment of the web service and hosting are also minimized such that hosting costs around 33$/year and compute costs around 27$/year (see *Hosting* in the Supplement).

## Code availability

The source code and data for the Bioregistry are available under the MIT and CC0 Licenses at `https://github.com/biopragmatics/bioregistry`.

## References

1. Wilkinson, M. D. *et al.* The FAIR Guiding Principles for scientific data management and stewardship. *Sci. Data* **3**, 160018, 10.1038/sdata.2016.18 (2016).

2. Jacobsen, A. *et al.* FAIR Principles: Interpretations and Implementation Considerations. *Data Intell.* **2**, 10–29, 10.1162/dint_r_00024 (2020).

3. Wilson, S. L. *et al.* Sharing biological data: why, when, and how. *FEBS Lett.* **595**, 847–863, https://doi.org/10.1002/1873-3468.14067 (2021). https://febs.onlinelibrary.wiley.com/doi/pdf/10.1002/1873-3468.14067.

4. Hastings, J. *et al.* ChEBI in 2016: Improved services and an expanding collection of metabolites. *Nucleic Acids Res.* **44**, D1214–D1219, 10.1093/nar/gkv1031 (2016).

5. Bateman, A. *et al.* UniProt: the universal protein knowledgebase in 2021. *Nucleic Acids Res.* **49**, D480–D489, 10.1093/nar/gkaa1100 (2021).

6. McMurry, J. A. *et al.* Identifiers for the 21st century: How to design, provision, and reuse persistent identifiers to maximize utility and impact of life science data. *PLoS Biol.* **15**, 1–18, 10.1371/journal.pbio.2001414 (2017).

7. Tweedie, S. *et al.* Genenames.org: the HGNC and VGNC resources in 2021. *Nucleic Acids Res.* **49**, D939–D946, 10.1093/nar/gkaa980 (2021).

8. Bansal, P. *et al.* Rhea, the reaction knowledgebase in 2022. *Nucleic Acids Res.* **50**, D693–D700, 10.1093/nar/gkab1016 (2022).

9. Barrett, A. J. Enzyme Nomenclature. Recommendations 1992. *Eur. J. Biochem.* **232**, 1, https://doi.org/10.1111/j.1432-1033.1995.tb20774.x (1995).

10. The Gene Ontology Consortium. The Gene Ontology Resource: 20 years and still GOing strong. *Nucleic Acids Res.* **47**, D330–D338, 10.1093/nar/gky1055 (2019).

11. Fleischmann, A. *et al.* IntEnz, the integrated relational enzyme database. *Nucleic Acids Res.* **32**, D434–D437, 10.1093/nar/gkh119 (2004).

12. Juty, N., Le Novere, N. & Laibe, C. Identifiers.org and MIRIAM Registry: Community resources to provide persistent identification. *Nucleic Acids Res.* **40**, 580–586, 10.1093/nar/gkr1097 (2012).

13. Wimalaratne, S. M. *et al.* Uniform resolution of compact identifiers for biomedical data. *Sci. Data* **5**, 1–8, 10.1038/sdata.2018.29 (2018).

14. McMurry, J. & Kunze, J. Prefix commons. https://github.com/prefixcommons/biocontext (2017).

15. Schoch, C. L. *et al.* NCBI Taxonomy: a comprehensive update on curation, resources and tools. *Database* **2020**, baaa062, 10.1093/database/baaa062 (2020).

16. Whetzel, P. L. *et al.* BioPortal: enhanced functionality via new Web services from the National Center for Biomedical Ontology to access and use ontologies in software applications. *Nucleic Acids Res.* **39**, W541–5, 10.1093/nar/gkr469 (2011).

17. Bairoch, A. The Cellosaurus, a Cell-Line Knowledge Resource. *J. Biomol. Tech.* **29**, 25–38, 10.7171/jbt.18-2902-002 (2018).

18. Clark, K., Karsch-Mizrachi, I., Lipman, D. J., Ostell, J. & Sayers, E. W. GenBank. *Nucleic Acids Res.* **44**, D67–72, 10.1093/nar/gkv1276 (2016).

19. Jackson, R. C. *et al.* OBO Foundry in 2021: Operationalizing Open Data Principles to Evaluate Ontologies. *Database (Oxford).* **2021**, 1–9, 10.1093/database/baab069 (2021).

20. Cote, R., Jones, P., Apweiler, R. & Hermjakob, H. The Ontology Lookup Service, a lightweight cross-platform tool for controlled vocabulary queries. *BMC Bioinforma.* **7**, 1–7, 10.1186/1471-2105-7-97 (2006).

21. Mungall, C. *et al.* prefixcommons/biocontext: v0.1.0, 10.5281/zenodo.6800248 (2022).

22. van Iersel, M. P. *et al.* The BridgeDb framework: Standardized access to gene, protein and metabolite identifier mapping services. *BMC Bioinforma.* **11**, 10.1186/1471-2105-11-5 (2010).

23. Callahan, T. J., Tripodi, I. J., Hunter, L. E. & Baumgartner, W. A. A framework for automated construction of heterogeneous large-scale biomedical knowledge graphs. *bioRxiv* 10.1101/2020.04.30.071407 (2020). https://www.biorxiv.org/content/early/2020/05/02/2020.04.30.071407.full.pdf.

24. Himmelstein, D. S. *et al.* Open collaborative writing with Manubot. *PLoS Comput. Biol.* **15**, e1007128, 10.1371/journal.pcbi.1007128 (2019).

25. Hoyt, C. T., Hoyt, A. & Gyori, B. M. Biomappings, 10.5281/zenodo.4323555 (2021).

26. Matentzoglu, N. *et al.* A Simple Standard for Sharing Ontological Mappings (SSSOM). *Database* **2022**, baac035, 10.1093/database/baac035 (2022).

27. Gyori, B. M. *et al.* From word models to executable models of signaling networks using automated assembly. *Mol. Syst. Biol.* **13**, 954, 10.15252/msb.20177651 (2017).

28. Hoyt, C. T. biopragmatics/bioregistry, 10.5281/zenodo.4390079.

29. Gray, K. A., Seal, R. L., Tweedie, S., Wright, M. W. & Bruford, E. A. A review of the new HGNC gene family resource. *Hum. Genomics* **10**, 6, 10.1186/s40246-016-0062-6 (2016).

30. Eschmeyer, W. & of Sciences, C. A. *Catalog of Fishes*. No. v. 4 in California Academy of Sciences. Center for Biodiversity Research and Information. 1 (California Academy of Sciences, 1998).

31. Midford, P. *et al.* The Teleost Taxonomy Ontology. *Nat. Preced.* 10.1038/npre.2010.4629.1 (2010).

32. Midford, P. E. *et al.* The vertebrate taxonomy ontology: a framework for reasoning across model organism and species phenotypes. *J. Biomed. Semant.* **4**, 34, 10.1186/2041-1480-4-34 (2013).

33. Hoehndorf, R., Slater, L., Schofield, P. N. & Gkoutos, G. V. Aber-OWL: a framework for ontology-based data access in biology. *BMC Bioinforma.* **16**, 26, 10.1186/s12859-015-0456-9 (2015).

34. Jonquet, C. *et al.* AgroPortal: A vocabulary and ontology repository for agronomy. *Comput. Electron. Agric.* **144**, 126–143, https://doi.org/10.1016/j.compag.2017.10.012 (2018).

35. Unni, D. R. *et al.* Biolink Model: A universal schema for knowledge graphs in clinical, biomedical, and translational science. *Clin. Transl. Sci.* https://doi.org/10.1111/cts.13302 (2022).

36. Hastings, J. *et al.* The chemical information ontology: Provenance and disambiguation for chemical data on the biological semantic web. *PLOS ONE* **6**, 1–13, 10.1371/journal.pone.0025513 (2011).

37. Arnaud, E. *et al.* The Ontologies Community of Practice: A CGIAR Initiative for Big Data in Agrifood Systems. *Patterns* **1**, 100105, https://doi.org/10.1016/j.patter.2020.100105 (2020).

38. Kechagioglou, X., Vaira, L., Tomassino, P., Fiore, N. & Basset, A. EcoPortal : An Environment for FAIR Semantic Resources in the Ecological Domain. In *JOWO* (Bolzano, Italy, 2021).

39. Sansone, S.-A. *et al.* FAIRsharing as a community approach to standards, repositories and policies. *Nat. Biotechnol.* **37**, 358–367, 10.1038/s41587-019-0080-8 (2019).

40. Ong, E. *et al.* Ontobee: A linked ontology data server to support ontology term dereferencing, linkage, query and integration. *Nucleic Acids Res.* **45**, D347–D352, 10.1093/nar/gkw918 (2017).

41. Pratt, D. *et al.* NDEx, the Network Data Exchange. *Cell Syst.* **1**, 302–305, 10.1016/j.cels.2015.10.001 (2015).

42. Rando, H. M. *et al.* An Open-Publishing Response to the COVID-19 Infodemic. (2021).

43. Kishore, R. *et al.* Automated generation of gene summaries at the Alliance of Genome Resources. *Database* **2020**, baaa037, 10.1093/database/baaa037 (2020).

44. Gyori, B. M., Hoyt, C. T. & Steppi, A. Gilda: biomedical entity text normalization with machine-learned disambiguation as a service. *Bioinforma. Adv.* **2**, 10.1093/bioadv/vbac034 (2022). Vbac034, https://academic.oup.com/bioinformaticsadvances/article-pdf/2/1/vbac034/43775895/vbac034.pdf.

45. Willighagen, E. Bacting : a next generation , command line version of Bioclipse Statement of Need. *J. Open Source Softw.* **6**, 1–5, 10.21105/joss.02558 (2021).

46. Cunningham, F. *et al.* Ensembl 2022. *Nucleic Acids Res.* **50**, D988–D995, 10.1093/nar/gkab1049 (2021). https://academic.oup.com/nar/article-pdf/50/D1/D988/42058123/gkab1049.pdf.

47. Doherty, L. M. *et al.* Integrating multi-omics data reveals function and therapeutic potential of deubiquitinating enzymes. *eLife* **11**, e72879, 10.7554/eLife.72879 (2022).

48. Bachman, J. A., Gyori, B. M. & Sorger, P. K. FamPlex: A resource for entity recognition and relationship resolution of human protein families and complexes in biomedical text mining. *BMC Bioinforma.* **19**, 1–14, 10.1186/s12859-018-2211-5 (2018).

49. Mulder, N. J. *et al.* InterPro, progress and status in 2005. *Nucleic Acids Res.* **33**, D201–D205, 10.1093/nar/gki106 (2005). https://academic.oup.com/nar/article-pdf/33/suppl_1/D201/7622281/gki106.pdf.

50. Rogers, F. B. Medical subject headings. *Bull. Med. Libr. Assoc.* **51**, 114–6 (1963).

51. Meldal, B. H. *et al.* The complex portal - An encyclopaedia of macromolecular complexes. *Nucleic Acids Res.* **43**, D479–D484, 10.1093/nar/gku975 (2015).

52. Zahn-Zabal, M. *et al.* The neXtProt knowledgebase in 2020: data, tools and usability improvements. *Nucleic Acids Res.* **48**, D328–D334, 10.1093/nar/gkz995 (2019). https://academic.oup.com/nar/article-pdf/48/D1/D328/31697996/gkz995.pdf.

53. Sung, M. *et al.* Bern2: an advanced neural biomedical namedentity recognition and normalization tool. *arXiv* (2022). 2201.02080.

54. Vasilevsky, N. A. *et al.* Mondo: Unifying diseases for the world, by the world. *medRxiv* 10.1101/2022.04.13.22273750 (2022).

55. Köhler, S. *et al.* The Human Phenotype Ontology in 2021. *Nucleic Acids Res.* **49**, D1207–D1217, 10.1093/nar/gkaa1043 (2020). https://academic.oup.com/nar/article-pdf/49/D1/D1207/35364524/gkaa1043.pdf.

56. Schriml, L. M. *et al.* The human disease ontology 2022 update. *Nucleic Acids Res.* **50**, D1255–D1261, 10.1093/nar/gkab1063 (2021). https://academic.oup.com/nar/article-pdf/50/D1/D1255/42058205/gkab1063.pdf.

57. Diehl, A. D. *et al.* The Cell Ontology 2016: enhanced content, modularization, and ontology interoperability. *J. Biomed. Semant.* **7**, 44, 10.1186/s13326-016-0088-7 (2016).

58. Sarntivijai, S. *et al.* CLO: The cell line ontology. *J. Biomed. Semant.* **5**, 37, 10.1186/2041-1480-5-37 (2014).

59. Gremse, M. *et al.* The BRENDA Tissue Ontology (BTO): the first all-integrating ontology of all organisms for enzyme sources. *Nucleic Acids Res.* **39**, D507–D513, 10.1093/nar/gkq968 (2011).

60. Gillespie, M. *et al.* The reactome pathway knowledgebase 2022. *Nucleic Acids Res.* **50**, D687–D692, 10.1093/nar/gkab1028 (2021). https://academic.oup.com/nar/article-pdf/50/D1/D687/42058295/gkab1028.pdf.

61. Martens, M. *et al.* WikiPathways: connecting communities. *Nucleic Acids Res.* **49**, D613–D621, 10.1093/nar/gkaa1024 (2021).

62. Malik-Sheriff, R. S. *et al.* BioModels — 15 years of sharing computational models in life science. *Nucleic Acids Res.* **48**, D407–D415, 10.1093/nar/gkz1055 (2020). Gkz1055, https://academic.oup.com/nar/article-pdf/48/D1/D407/31698010/gkz1055.pdff.

63. Tiwari, K. *et al.* Reproducibility in systems biology modelling. *Mol. Syst. Biol.* **17**, e9982, https://doi.org/10.15252/msb.20209982 (2021).

64. Wong, J. V. *et al.* Science Forum: Author-sourced capture of pathway knowledge in computable form using Biofactoid. *Elife* **10**, e68292, 10.7554/eLife.68292 (2021).

## Acknowledgements

CTH, KK, BMG were funded under the Defense Advanced Research Projects Agency (DARPA) Young Faculty Award [W911NF-20-1-0255]. EW received funding by NWO grant [203.001.121].

## Author contributions statement

CTH and BMG conceived and implemented the software and resource, analyzed the results, and wrote the manuscript. CJM, JK, JM, and MAH contributed to the conception and design of the resource and software. AR, BMG, CTH, CJM, DDF, DSH, DW, MB, NM, SM, TL, and TJC performed data curation for the resource, BMG, CTH, DRU, EW, HBH, KK, NM, and SM contributed to the software. CJM, DSH, DRU, EW, JM, NM, SM, TJC co-wrote the manuscript. All authors reviewed and edited the manuscript.

## Competing interests

DDF received salary from Enveda Biosciences.