Local minimization of prediction errors drives learning of invariant object representations in a generative network model of visual perception

Short title: Learning invariant representations in a generative predictive coding network

Matthias Brucklacher [1*], Sander M. Bohte [1,2] , Jorge F. Mejias [1], Cyriel M. A. Pennartz [1]

[1] Swammerdam Institute for Life Sciences, University of Amsterdam, Science Park 904, 1090GE Amsterdam, Netherlands

[2] Machine Learning Group, Centrum Wiskunde & Informatica, Science Park 123, 1098XG Amsterdam, Netherlands

* Corresponding author
 Email: m.m.brucklacher@uva.nl (MB)

Abstract

The ventral visual processing hierarchy of the cortex needs to fulfill at least two key functions: Perceived objects must be mapped to high-level representations invariantly of the precise viewing conditions, and a generative model must be learned that allows, for instance, to fill in occluded information guided by visual experience. Here, we show how a multilayered predictive coding network can learn to recognize objects from the bottom up and to generate specific representations via a top-down pathway through a single learning rule: the local minimization of prediction errors. Trained on sequences of continuously transformed objects, neurons in the highest network area become tuned to object identity invariant of precise position, comparable to inferotemporal neurons in macaques. Drawing on this, the dynamic properties of invariant object representations reproduce experimentally observed hierarchies of timescales from low to high levels of the ventral processing stream. The predicted faster decorrelation of error-neuron activity compared to representation neurons is of relevance for the experimental search for neural correlates of prediction errors. Lastly, the generative capacity of the network is confirmed by reconstructing specific object images, robust to partial occlusion of the inputs. By learning invariance from temporal continuity within a generative model, the network goes beyond purely input-reconstructing models of predictive coding and generalizes the framework to moving inputs in a more biologically plausible way than self-supervised networks with non-local error-backpropagation.

Author Summary

Neurons in the inferotemporal cortex of primates respond to images of complex objects independent of position, rotational angle, or size. While feedforward models of visual perception such as deep neural networks can explain this, they fail to account for the use of top-down information, for example when sensory evidence is scarce. Here, we address the question of how the neuronal networks in the brain learn both bottom-up and top-down processing without artificial supervision signals. Building on previous work that explains vision as a process of iteratively improving predictions, learning in the predictive coding network is driven by the local minimization of prediction errors. When trained on sequences of moving inputs, the network learns both invariant high-level representations comparable to those in the inferotemporal cortex of primates, and a generative model capable of reconstructing whole objects from partially occluded input images in agreement with experimental recordings from early visual areas. Advancing the search for experimental hallmarks of prediction errors, we find that error neurons in the network change their activity on a shorter timescale than representation neurons.

1. Introduction

How networks of neurons in the brain infer the identity of objects from limited sensory information is one of the preeminent questions of neurobiology. Strengthening theories of generative perception (1–5), evidence has accumulated to suggest that the mammalian perceptual system is relying on various forms of prediction to facilitate this process. Across time, repetition suppression that requires explicit expectations (6,7), encoding of deviation from temporal expectations in macaque's inferotemporal and prefrontal cortex (8,9) and encoding of expected movement outcomes in mouse V1 (10) show that the brain constantly tries to predict future inputs. V1 activity in illusory contours (11,12), encoding of information from occluded scene areas in early visual areas of humans (13) and modulation of neural responses by expectations based on the surrounding context (14) show that predictions are not only made forward in time, but also across space (in the present). According to predictive coding theory, these predictions are mediated by corticocortical top-down connections (3) and then corrected based on the received bottom-up input (5) in line with hierarchical Bayesian perception (15). Predictive coding models have successfully explained properties of the visual system such as learning of end-stopping neurons and wavelet-like receptive fields (5) and V1 activity in illusory contours (16,17). However, these studies are focused on low-level effects, while the learned higher-level representations have been investigated much less (although see (18) for learning of sparse representations).

Continuously generated by the awake brain, neural representations of the external world form a partial solution to the problem of inference, arguably constituting the basis of conscious experience (19), decision-making and adaptive planning (20). They can be loosely defined as activity patterns in response to a sensory stimulation elicited by an object. Especially important is the ability to represent multiple views of the same object in similar patterns of

activity. These invariant representations have two key advantages: First, information acquired about an object (such as a novel action associated with it) can be linked to only one representation, making learning more efficient. Secondly, as illustrated in Fig 1, the newly acquired invariant information about single objects generalizes automatically across all viewing conditions, facilitating learning from few examples. Evidence for invariant neural representations comes from the ventral temporal lobe (21), the hippocampus in humans (22), inferotemporal cortex of rhesus (23,24) and macaque monkeys (25) as well as rats' laterolateral extrastriate area (LL) (26,27). Current theories of how neurons come to acquire such a specialized tuning either fail to account for fundamental aspects of brain circuitry and physiology or rely on artificial learning paradigms. To construct useful representations, biological systems are limited to mostly unsupervised learning (from unlabeled data) and local learning rules, whereas machine vision algorithms based on neural networks typically rely on large amounts of labeled training data and use mechanisms like weight-sharing (28). These mechanisms facilitate generalization across viewing conditions but lack a biological foundation.

A biologically plausible approach to learn view-invariance from transformation sequences is so-called trace learning (29–31). It is based on the idea that temporal proximity between sensory patterns should be reflected in representational similarity, as the assumption can be made about the world that the causes (objects etc.) vary more slowly than the stimulation patterns they evoke on the retina. Indeed there is evidence for the importance of temporal stimulus continuity for learning of transformation-tolerance in early visual areas of chicks (32) and area IT of monkeys (33). Based on this principle of representing consecutive inputs similarly, Halvagal and Zenke (34) recently showed that a more intricate learning rule with additional variance maximization leads to disentangled high-level representations.

Fig 1. View-invariant representations for efficient cognition. a) Barely escaping an attack, the monkey learns to associate an action ("flee", encoded by the neural pattern in primary motor area M1) with the activity pattern in its retinal ganglion cells (RGCs, bottom) triggered by the image of an approaching eagle. Active cells are shown in grey. b-1) When the monkey later encounters a similar eagle from a different angle, an invariant higher-level representation (center) can still trigger the same action. b-2) Without invariant coding, the action does not generalize to this viewing condition. Red box: Scope of this paper: How do multiple low-level activity patterns become linked to one high-level, invariant representation?

However, all of these models process information in a strictly feedforward manner or limit the role of feedback connections to a modulatory function, in contrast to evidence on retinotopic, content-carrying feedback connections in the brain (35–37). Here, we propose a common underlying learning mechanism for both high-level representations and a generative model capable of reconstructing specific of sensory inputs: the minimization of local prediction errors.

Like the abovementioned feedforward models of invariance learning, predictive coding offers a mechanism for maintenance of higher-level representations: they are only updated when lower levels send up error signals. It can be implemented in a hierarchical neural network model of the visual processing stream using local, Hebbian learning. Furthermore, it is

intimately related to the abovementioned slowness principle, which states that the most meaningful features often change on a slow timescale (38), because extracted causes tend to be good predictors for future input (39). To sum up, predictive coding is a promising candidate to explain learning of invariant object representations within the framework of generative modelling.

To acquire transformation-tolerance from temporal continuity, input sequences are required. Most predictive coding models so far, however, either operate on static inputs (5,18,40) or use non-local learning rules such as backpropagation (41) and biologically implausible LSTM units (16,42). Here, we train multilayered predictive coding networks on transformation sequences with purely Hebbian learning (based on (5) and (18)). We confirm learning of a generative model, showing that top-down predictions made by the network approximate the original input. Importantly, these predictions are not forward in time, but across retinotopic space, representing the current input. Presented with partially occluded input sequences, the network pattern-completes the occluded areas through top-down feedback, mimicking functions of human V1 and V2. While reconstructions from lower areas are more faithful, predictive neurons in the network's higher areas develop view-invariant representations akin to responses of neurons in the inferotemporal area of primate cortex: Input stimuli shown in temporal proximity are represented similarly. A decoding analysis confirms that distinct objects are well separable. Lastly, the temporal dynamics of the neural subpopulations are analyzed and compared to recent electrophysiological data from rats. As in the experiment, temporal stability of representation neurons (measured by the decay of autocorrelation) increases as one moves up the hierarchy. In addition, the model makes the prediction that high-level error-coding neurons operate on a faster timescale than their representational counterparts.

2. Methods

We developed a neural network consisting of four hierarchically arranged areas. Applying the principles of predictive computation, we restricted ourselves to the minimally necessary components, but other connectivity patterns are conceivable (suggested e.g. by Heeger (43)). As in previous implementations of predictive coding (5,18), each area contains two subpopulations of neurons that are illustrated in Fig 2:

1. Representation neurons collectively hold the "inferred causes", in higher areas corresponding to perceptual content. Together with the synaptic connections towards lower areas, they generate top-down predictions to match the current representations in the area below.

2. Error neurons measure mismatch between representation neuron activity (in the lowest area: the sensory input) and top-down predictions.

Fig 2. Model architecture and inference on video sequences. a) Representational activity y_l in area l ($l \in \{1,2\}$) is influenced by both top-down predictions highlighted in red via the respective top-down errors $\boldsymbol{\beta_l}$, and by the bottom-up errors $\boldsymbol{\beta_{l-1}}$. Intra-area connections between representation neurons (circles) and respective error neurons (squares) are one-to-one, while inter-area connections are all-to-all. Synaptic connections between neurons are drawn as filled circles if inhibitory and as triangles if excitatory. b) A sequence of input images is fed into the lowest area of the network across subsequent moments in time($t - 2, ..., t$). The network maintains representational activity through time and thus uses it as a prior for the inference of subsequent representations.

Some models such as (44) suggest computation of errors in dendrites, but based on the evidence for neural encoding of errors (35), we assign dedicated neurons to encode them. Development of such error-tuned neurons has been modelled by (45) in cortical microcircuits and by (46) as a result of energy efficiency. The number of neurons in each area depends on the dimensions of the dataset and is given in section 6.1 of the Supplementary Material.

2.1 Inference: Updating neural activity

At the start of a sequence, all neural activity is set to a uniform, low value (unless stated differently in the Results section). While an image is presented to the network, the lowest area representation neurons linearly reflect the pixel-wise intensity of the input (at the bottom of Fig 2b). Error neurons in area l receive excitatory input from the activity $\boldsymbol{y}_l$ of associated representation neurons as shown in the one-to-one connections in Fig 2a, and are inhibited by the summed-up predictions $\hat{\boldsymbol{y}}_l$ from the higher area:

$$\boldsymbol{\beta}_l^{(t)} = \boldsymbol{y}_l^{(t-1)} - \hat{\boldsymbol{y}}_l^{(t)} \tag{1}$$
$$= \boldsymbol{y}_l^{(t)} - \boldsymbol{W}_l^{(t-1)}\boldsymbol{y}_{l+1}^{(t-1)}$$

where bold letters indicate vectors and matrices and $\boldsymbol{W}_l^{(t-1)}$ denotes the symmetric weight matrix between area l and area $l+1$ from the previous time step (the weights will change during learning). Each representation neuron receives inhibitory input from one error neuron in the same area and excitatory input from the weighted bottom-up errors:

$$\boldsymbol{x}_l^{(t)} = \boldsymbol{x}_l^{(t-1)} + \epsilon_{inf} \left(\boldsymbol{W}_{l-1}^{(t-1)^T}\boldsymbol{\beta}_{l-1}^{(t)} - \boldsymbol{\beta}_l^{(t)}\right) \tag{2}$$

This adjustment of neural activation state $\boldsymbol{x}_l$ (akin to membrane potential) of representation neurons can be interpreted as matching top-down predictions better than before (and thus

reducing activity of the associated error neuron) and sending down predictions that better match representation neuron activity in the area below (thus reducing errors there). The rate at which neuronal activation is changed is governed by the parameter ϵ_{inf} referred to in the following as the *inference rate*. The activation state $\boldsymbol{x}_l$ is now translated into an output firing rate $\boldsymbol{y}_l$:

$$\boldsymbol{y}_l^{(t)} = \phi(\boldsymbol{x}_l^{(t)} + \Delta_x) \tag{3}$$

where ϕ denotes the sigmoid activation function, and Δ_x a constant lateral offset of the firing threshold. The saturation of the sigmoid for large inputs corresponds to a maximal firing rate of the representation neurons, in contrast to the more artificial, (rectified) linear activation functions used in (5) and (18) that do not have an upper bound.

2.2 Unsupervised Learning: Updating synaptic strengths

After a fixed number of inference steps (Supplementary Material 6.1), long-term adaptation of synaptic weights is conducted in a Hebbian manner, strengthening synapses between active error neurons in area l and simultaneously active representation neurons in the area above $(l+1)$:

$$\boldsymbol{W}_{l-1}^{(t)} = \boldsymbol{W}_{l-1}^{(t-1)} + \epsilon_{learn} \cdot \boldsymbol{\beta}_{l-1}^{(t)} \boldsymbol{y}_l^{(t)^T} \tag{4}$$

with learning rate ϵ_{learn}. The sign of the prediction error controls the direction of the weight change. If the prediction is too large relative to the activity of the representation neurons in this area, the error is negative, and the weight mediating the prediction will be reduced. As a result, given the same prediction, the error in the consecutive time step will be smaller.

¹⁸⁵ To summarize, both the balanced, excitatory-inhibitory wiring of the network and the unsupervised adaptation of weights based on remaining prediction errors lead to an alignment of representations and predictions, and thus a reduction in error neuron activity.

2.3 Training procedure

We trained the network on temporally dynamic inputs, using short video sequences. After
¹⁹⁰ validating network performance on moving horizontal and vertical bars, we switched to using ten digits of the MNIST handwritten digits dataset (one per digit from 0-9). Each sequence contained six gradually transformed images, and separate datasets were created for translational motion, rotation, and scaling (Fig 3). For translational and rotational motion, two transformation speeds were used, differing in overlap between consecutive images. The
¹⁹⁵ examples shown in Fig 3 are from the dataset with larger step size ("fast" condition). To further examine robustness of the training paradigm under more realistic and less sparse inputs, random noise patterns were added to the image background during training. A last dataset consisted of five high-pass filtered images of toy objects (an airplane shown in the last row of Fig 3, a sports car, a truck, a lion and a tin man) from the smallNORB dataset (47),
²⁰⁰ undergoing a rotation.

Fig 3. Example sequences from the stimulus datasets. First row: digit translation without noise, second row: digit scaling with noise, third and fourth row: rotation of digit/toy plane without noise.

The network was trained on the ten (for the toy objects: five) sequences, each presenting a different digit, for multiple epochs. Each epoch consisted of iterations of the same sequence (e.g. of a moving digit '6') before switching to the next (of digit '7'). Hyperparameters such as the number of repetitions are listed in Supplementary Material 6.1. This repetition of individual sequences drastically improved network performance and could be achieved by the brain through a replay or reactivation mechanism (observed in visual cortex by (48,49), see also (50,51)). For laterally moving stimuli, repeated presentation can also be achieved by object-tracking saccades that lead to repeated motion across the same photoreceptors on the retina. As the most information-neutral state, the activity was reset to uniform low values at the beginning of each sequence. This assumption is justified for objects that are seen independently of each other; for instance, not every '6' is followed by a '7'. For each image, multiple inference-learning cycles (Eq 1-4) were conducted before switching to the next image in the sequence. A training epoch consisted of an iteration through all sequences from the dataset. Supplementary Material 6.2 contains the pseudocode for the nested training loops.

3. Results

We trained the network on sequences of moving objects as specified in the Methods section, and focused on the evolving high-level representations, resulting neural dynamics, and generative input-reconstructing capacities of the network, all in comparison to neurobiology.

3.1 Transformation-invariant stimulus representations

We found that neurons in network area 3 became tuned to samples in a position-invariant manner. To quantify invariance, we analyzed the neural representations in the highest area of trained networks (Fig 2) under changes of inputs. More specifically, inference was run on still images from the training datasets until convergence was reached (see Supplementary Material

6.3 for a description of convergence). Then, pairwise comparison of inferred area 3 representations measured in cosine distance quantified representational dissimilarity between representations of the same sample, e.g. a digit, (within-sequence) or different samples (across-sequence). All pairwise values were plotted in Representational Dissimilarity Matrices (RDMs, (52)) in Fig 4.

Indicating invariance, RDMs of trained networks showed high similarity within sequences; for instance, digit "1" was represented by highly similar activity patterns in area 3, irrespective of position. Representations of samples from different sequences, such as digit "1" and digit "2" at the same position were distinct, as indicated by a high dissimilarity in matrix elements off the block diagonal. The same held true for the rotating and scaling digits (Fig 4c and Fig 4d) as well as for the five rotating toy objects (Fig 4f). Noise (shown for the translational motion in Fig 4d versus the noiseless motion in Fig 4c) slightly degraded clarity of the RDM but preserved the overall structure well.

Invariance of representations was a consequence of learning from continuously transforming inputs as evidenced by the RDMs of the untrained network that showed very low structure (Fig 4a, note the different color scale, cosine distance below 0.001). Networks trained on the static frames of the sequences, in which activity was reset after each frame also lacked a block-diagonal structure (Fig S1).

Area 3-representations were informative about the identity of the sample moving in sequence as decodability improved with training (Fig 5). In addition to its behavioral relevance,

Fig 4. Representations invariant to viewing conditions are learned without supervision signals. The matrices depict cosine dissimilarity between representations in area 3. Each of the rows and columns in these plots corresponds to one input image, thus each matrix is symmetrical. Along each dimension, samples are ordered sequence-wise, i.e., rows and columns 0-5, 6-11 etc. are the same object in six different transformation states. Low values shown in purple correspond to similar activity patterns, i.e. a similar set of neurons represents the stimuli given by the combination of row and column, high values shown in yellow correspond to orthogonal activity vectors. a) Baseline, an untrained network tested on the translationally moving digits dataset. b)-e) Networks trained and tested on one of the three datasets of ten rotating, translating (with and without noise) and scaling digits show a clear block-diagonal structure with low values for comparisons within sequences. f) Network trained and tested on five rotation sequences of toy objects.

decodability of representations quantifies the learned within-sequence invariance. A biologically plausible way to make high-level object representations available to downstream processes (such as action selection, Fig 1) is a layer of weighted synaptic connections, i.e., a linear decoder, to infer object identity. We simulated this through a linear mapping of area 3-activity vectors to ten object identity-encoding neurons (digits "0", "1", ..., "9"). After fitting the decoding model to 2/3 of the representations, evaluation was conducted on the remaining 1/3 in a stratified k-fold manner (with $k = 3$). Compared to the information content in the input signal, as measured by accuracy of a linear decoder, as well as k-means clustering, area 3 representations achieved better decoding performance after around five training epochs (Fig 5a). This was confirmed across almost all used datasets (Tab 1) and even increased as the transformation step size was increased, resulting in smaller overlap between consecutive images ("fast" conditions in Tab 1, shown in the first and third row of Fig 3).

Fig 5. Area 3-representations encode object identity. Decoding accuracy of a linear decoder operating on area 3-representations of our predictive coding network trained in the continuous paradigm (PC-continuous) plotted across training epochs (iterations through the whole dataset). a) Accuracy quickly rises above performance of k-means clustering and linear decoding directly on the input data (LD inputs) for the rotating toy objects dataset. b) Influence of continuous training: Decoding accuracy in networks trained on continuous sequences (continuous lines) is increased compared to networks trained on isolated (static) frames of the sequences.

Dataset	PC-continuous, area 3	PC-static, area 3	k-means input	Linear decoding input
Toy objects rot.	**95.83**	16.67	53.33	83.33
Digits rotating	**86.25**	30.00	48.33	85.00
Digits rotating, noise	**78.75**	33.75	N/A	N/A
Digits scaling	76.67	55.00	68.33	**100.00**
Digits scaling, noise	**83.75**	56.25	N/A	N/A
Digits translation	**84.58**	38.33	60.00	75,00
Digits translation, noise	**79.17**	42.08	N/A	N/A
Digits fast rotation	**95.83**	20.00	31.67	40.00
Digits fast translation	**85.42**	19.17	38.33	25.00
Digits fast translation, noise	**72.92**	16.25	N/A	N/A

Tab 1. Decoding accuracy (in percent) across datasets and models. The best performing decoder per dataset is marked in bold. The left column is the predictive coding network trained in the continuous manner put forward in this paper.

The continuous training paradigm improved decoding performance in comparison to networks trained on static inputs. There, decoding performance was consistently more than twenty percentage points worse (Fig 5b and Tab 1). This can partially be explained by the more sample-specific representations when activity was not carried over from one image to the next (Fig S1).

3.2 Temporal stability of representations

Without explicitly integrated constraints, the network developed a hierarchy of timescales in which representations in higher network areas decorrelated more slowly than in lower areas. We quantified this by measuring the autocorrelation R during presentation of rotating digits. It is defined as

$$R(\mathbf{z}, \Delta) = \frac{1}{N(T - \Delta)} \sum_{t-1}^{T-\Delta} \mathbf{z}(t) \cdot \mathbf{z}(t + \Delta) \qquad (5)$$

where Δ is the time lag measured in inference steps between the points to be compared, T is the duration of each sequence, N the number of neurons in the subpopulation and $\mathbf{z}(t)$ the activity vector in the subpopulation (averaged across 10 inference steps, which are summarized to one time step in the following). High values indicate similar, non-zero activities and thus high temporal stability. The resulting autocorrelation curves for time lags between 0 and the length of an individual sequence are shown in Fig 6a-b, averaged across the ten rotation sequences. From these curves, decay constants were inferred by measuring the time until decay to 1/e. If that value was not reached until the sequence end, we extrapolated by using a linear continuation through the values at Δ=0 and Δ=600 time steps. The resulting decay times are shown in Fig 6c. A significant difference was found between representation neurons in area 3 and area 1 (mean difference: 715.09 time steps, p=1.58e-8, determined by ANOVA), as well as a smaller, but still significant difference between representation neurons in area 2 and area 1 (467.95 time steps, p=6.08e-6). In error-coding neurons, the hierarchy was less pronounced, but area 0 and area 2 nonetheless showed a significant difference (p=0.03). Comparison to a statically trained network with the same architecture which failed to develop a temporal hierarchy in representations (Supplementary Material 6.4) showed that the temporal hierarchy was not built into the model architecture,

but instead is an emergent property of the model under the continuous training paradigm. This is underlined by the fact that the same inference rate was used in all network areas. The hierarchy in representational dynamics is in agreement with experimental findings in rat visual cortex (53). There, the authors computed neuronal timescales from the decay of autocorrelation in a similar manner and found more stable activity patterns in higher areas of rat visual cortex (Fig 6d).

The decay speed of autocorrelation also allowed us to differentiate between quickly decorrelating error neurons and more persistent representation neurons in higher network areas. Error-coding neurons in area 2 showed a shorter activity timescale than representation neurons within the same area. The difference equaled 474.04 time steps (p=3.9e-11), compared to only 21.10 time steps (p=2.87e-11) in the statically trained network (Fig S2). In this context, Piasini et al. (53) discussed the following scenario: When perceiving a continuously moving object, its identity is predictable over time. Thus, one could expect a diminishing firing rate in neurons representing this object, in contrast to their evidence on larger timescales in higher visual areas. Our results reconcile these views by differentiating between quickly decorrelating error-signals and persistent representations. Remarkably, this prediction about the consequences of predictive coding circuitry for the activity timescales of error- and representation neurons has not been proposed before.

Fig 6. The network develops a hierarchy of timescales comparable to experimental data from rodent visual cortex. a) Temporal decay of activity autocorrelation for the representation neuron subpopulations (RNs). b) Decay of autocorrelation for the error-coding subpopulations (ENs). c) Inferred decay constants per subpopulation, p-values are given in the main text. d) Comparison to experimental evidence from rat visual cortex. Hierarchical ordering of intrinsic timescales as the decay constants of activity autocorrelation, from V1 across lateromedial (LM), laterointermediate (LI) to laterolateral (LL) extrastriate areas, adapted from (53). *** p=5e-7, 1e-13, 2e-14, respectively for LM, LI and LL.

3.3 Generative capacity

The network learned a generative model of the visual inputs as shown by successful input-reconstruction through the network's top-down pathway (Fig 7). Since areas further up in the ventral processing stream of the cerebral cortex are thought to encode object identity, it is interesting to ask, in how far they are to be able to encode fully detailed scene information, or whether they contain only reduced information (such as object identity). To examine the functioning of this reverse pathway under the continuous transformation training paradigm, we investigated the representational content in each area by reconstructing sensory inputs in

a top-down manner. After training, a static input image was presented until network activity converged (Supplementary Material 6.3). Then, the input was blanked out and the inferred activity pattern (representation) from a selected area was propagated back down to the input neurons via the top-down weights. Area by area, activity $\boldsymbol{y}_l$ of representation neurons was installed by the descending predictions $\hat{\boldsymbol{y}}_l$ (see Supplementary Material 6.5 for details).

Fig 7. Learning of a generative model. a) Illustration of top-down reconstructions. The first column depicts original input images from different datasets. Columns two to four show the activity pattern in the input area generated by propagating latent representations from different network areas to the input layer in a top-down manner. In early network areas, representations inferred from sensory inputs carried enough information to reconstruct the input image once it was removed. Reconstructions from higher areas lead were less accurate. b) Mean squared reconstruction errors (MSE), comparing the original input to the reconstructions on a pixel-level.

As shown in Fig 7a, the accuracy of reconstruction strongly depended on the area it was initiated from. While predictions from latent representations in area 1 gave rise to reconstructions that resembled the original inputs and achieved low reconstruction errors (Fig 7b), higher areas were less accurate. From there, reconstructions were either blurry or showed the stimulus in a different position, rotational angle, or scale than presented prior to construction (e.g. the "0" from area 3 in the second row of Fig 7). This logically follows from the invariance achieved in these higher areas, from where a single generalized representation cannot suffice to regenerate many specific images. Despite this limitation in obtaining precise reconstructions, which resulted from training on extended sequences instead of individual frames, area 1-representation neurons in all networks contained enough information to regenerate the inputs, thus confirming that the model had learned a generative model of the dataset.

3.4 Reconstructing objects from occluded scenes

The generative capacity of the network's top-down pathway was further confirmed by its ability to reconstruct whole objects from partially occluded sequences as shown in Fig 8. A behaviorally relevant use of a generative pathway is the ability to fill in for missing information, such as when guessing what the whole scene may look like and planning an action towards occluded parts of an object. To investigate filling-in in the model, we presented occluded test sequences to the network trained on laterally moving digits (the same as before). After inference on each frame of the test dataset, the predictions sent down to the lowest network area were normalized and plotted retinotopically in Fig 8. Details on the reconstruction process can be found in Supplementary Material 6.6. Indeed, predictions sent towards the lowest area carried information about the occluded parts (Fig 8a).

Fig 8. Reconstruction of partially occluded sequences. a) First and third row: the input sequences shown to the network with the occluder outlined in red. Rows two and four: images arising from top-down predictions sent to the area 0 carried information about occluded areas of the input. b) Comparison to a purely feedforward network (no reconstruction) and a network trained on static images. Shown is the mean squared reconstruction error in the occluded part, averaged across all ten sequences, rising as the occluded field becomes larger (plotted over the first to last image of the occlusion sequence).

As the input deteriorated, predictions also visibly degraded, resulting in a rising MSE (Fig 8b). Interestingly, reconstructive accuracy was not significantly different from a network trained on the static images. This may be explained by two opposing mechanisms: memorization of specific frames putatively aids reconstruction in the static network (Fig S1) and on the other side availability of invariant object identity from the temporal context, which can be expected to improve reconstruction in the continuously trained network. Overall, the availability of top-down information in occluded fields of network area 0 is comparable to the presence of concealed scene information observed in early visual areas of humans (13) that cannot be explained by feedforward models of perception.

4. Discussion

4.1 Summary of results

We have shown how networks that minimize local prediction errors learn object representations invariant to the precise viewing conditions in higher network areas (Fig 4), while acquiring a generative model in which especially lower areas are able to reconstruct specific inputs (Fig 7, Fig 8). The learned high-level representations distinguish between different objects, as linear decoding accuracy of object identity was high (Fig 5). Comparison to considerably worse decoding performance in networks trained on static images underlined the importance of continuous transformation for the learning process (Fig 5). Focusing on the implications for neural dynamics, learning from continuous motion led to a hierarchy of timescales in representation neurons that showed more slowly changing activity in higher areas, where they notably differed from the more quickly varying error neurons (Fig 6).

4.2 A generative model to learn invariant representations

Without the need for a supervision signal, the model developed meaningful, decodable representations purely by Hebbian learning. Linking slowly varying predictions in higher areas to more quickly changing inputs in lower areas lead to emergence of temporally stable representations without the need for an explicit constraint for slowness as used for example in (38). At the same time, the model acquired generative capacity that enables reconstruction of partially occluded stimuli, in line with retinotopic and content-carrying feedback connections to V1 ((13,36), see also (3) for a review of predictive feedback mechanisms). Other neuron-level models of invariance-learning (28,29,31,34) neither account for such feedback nor experimentally observed explicit encoding of mismatch between prediction and observation (10,35) and used considerably more complex learning rules requiring a larger set of assumptions (34). By solving the task of invariance learning in agreement with the

generativity of sensory cortical systems, the claim for predictive coding circuits as fundamental building blocks of the brain's perceptual pathways is strengthened. We argue that the model generalizes predictive coding to moving stimuli in a biologically more plausible way than other approaches (16,42,46) that rely on non-local error backpropagation (41) or backpropagation through time (46).

4.3 Limitations in performance

Decoding accuracy on novel samples from a given class such as differently written "1"'s was not tested, as generalization of invariance to out-of-sample stimuli was not the goal of this study (for generalization of reconstruction to novel images see Dora et al. (18)). Currently, there is no mechanism in the model to map unseen inputs to the same high-level activity, if the overlap to seen examples of the same class is small. Here, a weakly supervised paradigm could be used. It has been shown that under constraints which would be out of the scope of this paper to discuss, predictive coding can do exact backpropagation when clamping the highest layer activities in a supervised manner (54,55). Although sufficient for learning of invariant representations, the fully connected architecture we used can be expected to limit good performance on out-of-sample testing. Combination of receptive field-like local filters with a pooling mechanism (56) may be necessary to become tolerant to the varying configurations of individual features comprising the objects from the same class.

Input reconstructions from higher network areas degraded as representations became more invariant. This is a direct consequence of Eq 6: Each element from the set of area 3-representations casts a unique prediction to the area below. Consequently, multiple different (not invariant) area 3 patterns would be necessary to fully reconstruct a sequence of inputs. Thus, either the invariance in area 3 or the faithfulness of the reconstruction suffers. Nevertheless, the network as a whole appeared to strike a good balance in the trade-off of

memorizing information to reconstruct individual samples in lower areas (hence the better reconstruction accuracy from area 1 in Fig 7) and abstracting over the sequence, where area 3 represents object identity invariantly (Fig 5), fitting theoretical descriptions of multilevel perception (ch. 9 in (19)). The more detailed and sample-specific information may provide useful input to the action-oriented dorsal processing stream (57), whereas the hierarchy of the ventral visual cortex extracts object identity and relevant concepts (58).

4.4 Hypotheses on the neural circuitry of predictive coding

The model captures neural response properties in early and high-level areas of the visual cortical hierarchy. Retinotopic (36) and information carrying (13) feedback to early visual areas (cf. Fig 7; Fig 8) as well as invariant (24,25) and object-specific representations (cf. Fig 4) in the temporal lobe (21–23) are captured by the simulation results. While there is ample evidence for a hierarchy of timescales in the visual processing streams of humans (59), primates (60) and rodents (53), with larger temporal stability in higher areas, the compatibility with deep predictive coding is debated (53). Our simulation results of increasingly large timescales further up in the network hierarchy may help to reconcile predictive coding with the experimental evidence. Compared to emergence of temporal hierarchies purely as a result of dynamics in spiking neurons (61) or large-scale models (62,63), our model provides a complementary account, postulating development of the temporal hierarchy as a consequence of a functional computation: learning invariance by local error minimization.

What novel insights can be extracted about the brain's putative use of predictive algorithms? Theories of predictive coding range from limiting it to a few functions (such as subtraction of corollary discharges to compensate for self-motion (10)) and input reconstruction (5) to claiming extended versions of it as the most important organizational principle of the brain (4), namely the free energy principle. PC models provide a critical step to make theories of

perception and imagery quantitative and falsifiable as well as to guide experimental research. Based on the simulation results, error neurons in higher visual areas operate on a much shorter activity timescale than their representational counterparts. This comparison of distinct subpopulations may provide an additional angle to measuring neural correlates of prediction errors (for a review see (64)), as representation neuron responses have been barely considered in experimental work so far. In combination with work on encoding of errors in superficial, and representations in deep cortical layers (3,65–67), area- and layer-wise recordings of characteristic timescales could lead to a better understanding of cortical microcircuits underlying predictive coding. Layer-wise investigations also show distinct patterns of feedforward and feedback connectivity (68) and information processing (69). Only with knowledge about these microcircuits, models of finer granularity can be constructed.

4.5 Conclusion

Predictive coding is a theory with great explanatory power, but with unclear scope. Here, we go beyond the original scope of pure input-reconstruction and find that predictive coding networks can additionally solve an important computational problem of vision. Our results are in line with experimental data from multiple species, strengthening predictive coding as a fundamental theory of mammalian perception.

5. Acknowledgements

The authors would like to thank Shirin Dora and Kwangjun Lee for the constructive discussions.

This project has received funding from the European Union's Horizon 2020 Framework Programme for Research and Innovation under the Specific Grant Agreement No. 945539 (Human Brain Project SGA3; to C.P. and S.B.).

Bibliography

1. Gregory RL. Perceptions as hypotheses. Philos Trans R Soc Lond B Biol Sci. 1980;290(1038):181–97.

2. Mumford D. On the computational architecture of the neocortex. Biol Cybern. 1992;66(3):241–51.

3. Pennartz CM, Dora S, Muckli L, Lorteije JA. Towards a unified view on pathways and functions of neural recurrent processing. Trends Neurosci. 2019;42(9):589–603.

4. Friston K. The free-energy principle: a unified brain theory? Nat Rev Neurosci. 2010;11(2):127–38.

5. Rao RP, Ballard DH. Predictive coding in the visual cortex: a functional interpretation of some extra-classical receptive-field effects. Nat Neurosci. 1999;2(1):79–87.

6. Summerfield C, Trittschuh EH, Monti JM, Mesulam MM, Egner T. Neural repetition suppression reflects fulfilled perceptual expectations. Nat Neurosci. 2008;11(9):1004–6.

7. Todorovic A, van Ede F, Maris E, de Lange FP. Prior expectation mediates neural adaptation to repeated sounds in the auditory cortex: an MEG study. J Neurosci. 2011;31(25):9118–23.

8. Bellet ME, Gay M, Bellet J, Jarraya B, Dehaene S, van Kerkoerle T, et al. Prefrontal neural ensembles encode an internal model of visual sequences and their violations. bioRxiv. 2021;

9. Schwiedrzik CM, Freiwald WA. High-level prediction signals in a low-level area of the macaque face-processing hierarchy. Neuron. 2017;96(1):89–97.

10. Leinweber M, Ward DR, Sobczak JM, Attinger A, Keller GB. A sensorimotor circuit in mouse cortex for visual flow predictions. Neuron. 2017;95(6):1420–32.

11. Bartels A. Visual perception: Early visual cortex fills in the gaps. Curr Biol. 2014;24(13):R600–2.

12. Kok P, de Lange FP. Shape perception simultaneously up-and downregulates neural activity in the primary visual cortex. Curr Biol. 2014;24(13):1531–5.

13. Smith FW, Muckli L. Nonstimulated early visual areas carry information about surrounding context. Proc Natl Acad Sci. 2010;107(46):20099–103.

14. Knierim JJ, van Essen DC. Neuronal responses to static texture patterns in area V1 of the alert macaque monkey. J Neurophysiol. 1992 Apr;67(4):961–80.

15. Lee TS, Mumford D. Hierarchical Bayesian inference in the visual cortex. JOSA A. 2003;20(7):1434–48.

16. Lotter W, Kreiman G, Cox D. A neural network trained for prediction mimics diverse features of biological neurons and perception. Nat Mach Intell. 2020;2(4):210–9.

17. Pang Z, O'May CB, Choksi B, VanRullen R. Predictive coding feedback results in perceived illusory contours in a recurrent neural network. Neural Netw. 2021 Dec 1;144:164–75.

18. Dora S, Bohte SM, Pennartz C. Deep Gated Hebbian Predictive Coding Accounts for Emergence of Complex Neural Response Properties Along the Visual Cortical Hierarchy. Front Comput Neurosci. 2021;65.

19. Pennartz CM. The brain's representational power: on consciousness and the integration of modalities. MIT Press; 2015.

20. Butz MV, Kutter EF. How the mind comes into being: Introducing cognitive science from a functional and computational perspective. Oxford University Press; 2016.

21. Haxby JV, Gobbini MI, Furey ML, Ishai A, Schouten JL, Pietrini P. Distributed and overlapping representations of faces and objects in ventral temporal cortex. Science. 2001;293(5539):2425–30.

22. Quiroga RQ, Reddy L, Kreiman G, Koch C, Fried I. Invariant visual representation by single neurons in the human brain. Nature. 2005;435(7045):1102–7.

23. Desimone R, Albright TD, Gross CG, Bruce C. Stimulus-selective properties of inferior temporal neurons in the macaque. J Neurosci. 1984;4(8):2051–62.

24. Logothetis NK, Pauls J, Poggio T. Shape representation in the inferior temporal cortex of monkeys. Curr Biol. 1995;5(5):552–63.

25. Freiwald WA, Tsao DY. Functional compartmentalization and viewpoint generalization within the macaque face-processing system. Science. 2010;330(6005):845–51.

26. Tafazoli S, Di Filippo A, Zoccolan D. Transformation-tolerant object recognition in rats revealed by visual priming. J Neurosci. 2012;32(1):21–34.

27. Tafazoli S, Safaai H, De Franceschi G, Rosselli FB, Vanzella W, Riggi M, et al. Emergence of transformation-tolerant representations of visual objects in rat lateral extrastriate cortex. Elife. 2017;6:e22794.

28. LeCun Y, Boser B, Denker JS, Henderson D, Howard RE, Hubbard W, et al. Backpropagation applied to handwritten zip code recognition. Neural Comput. 1989;1(4):541–51.

29. Földiák P. Learning invariance from transformation sequences. Neural Comput. 1991;3(2):194–200.

30. Elliffe MC, Rolls ET, Parga N, Renart A. A recurrent model of transformation invariance by association. Neural Netw. 2000;13(2):225–37.

31. Rolls ET. Invariant visual object and face recognition: neural and computational bases, and a model, VisNet. Front Comput Neurosci. 2012;6:35.

32. Matteucci G, Zoccolan D. Unsupervised experience with temporal continuity of the visual environment is causally involved in the development of V1 complex cells. Sci Adv. 2020;6(22):eaba3742.

33. Li N, DiCarlo JJ. Unsupervised natural experience rapidly alters invariant object representation in visual cortex. science. 2008;321(5895):1502–7.

34. Halvagal MS, Zenke F. The combination of Hebbian and predictive plasticity learns invariant object representations in deep sensory networks. bioRxiv. 2022;

35. Zmarz P, Keller GB. Mismatch receptive fields in mouse visual cortex. Neuron. 2016;92(4):766–72.

36. Marques T, Nguyen J, Fioreze G, Petreanu L. The functional organization of cortical feedback inputs to primary visual cortex. Nat Neurosci. 2018;21(5):757–64.

37. Pak A, Ryu E, Li C, Chubykin AA. Top-Down Feedback Controls the Cortical Representation of Illusory Contours in Mouse Primary Visual Cortex. J Neurosci. 2020 Jan 15;40(3):648–60.

38. Wiskott L, Sejnowski TJ. Slow feature analysis: Unsupervised learning of invariances. Neural Comput. 2002;14(4):715–70.

39. Creutzig F, Sprekeler H. Predictive coding and the slowness principle: An information-theoretic approach. Neural Comput. 2008;20(4):1026–41.

40. Spratling MW. A Hierarchical Predictive Coding Model of Object Recognition in Natural Images. Cogn Comput. 2017 Apr 1;9(2):151–67.

41. Rumelhart DE, Hinton GE, Williams RJ. Learning internal representations by error propagation. California Univ San Diego La Jolla Inst for Cognitive Science; 1985.

42. Lotter W, Kreiman G, Cox D. Deep predictive coding networks for video prediction and unsupervised learning. ArXiv Prepr ArXiv160508104. 2016;

43. Heeger DJ. Theory of cortical function. Proc Natl Acad Sci. 2017;114(8):1773–82.

44. Sacramento J, Ponte Costa R, Bengio Y, Senn W. Dendritic cortical microcircuits approximate the backpropagation algorithm. In: Advances in Neural Information Processing Systems. Curran Associates, Inc.; 2018.

45. Hertäg L, Sprekeler H. Learning prediction error neurons in a canonical interneuron circuit. Elife. 2020;9:e57541.

46. Ali A, Ahmad N, de Groot E, van Gerven MAJ, Kietzmann TC. Predictive Coding is a Consequence of Energy Efficiency in Recurrent Neural Networks. Rochester, NY: Social Science Research Network; 2021 Dec. Report No.: 3976481.

47. LeCun Y, Huang FJ, Bottou L. Learning Methods for Generic Object Recognition with Invariance to Pose and Lighting. In IEEE Computer Society; 2004. p. 97–104.

48. Ji D, Wilson MA. Coordinated memory replay in the visual cortex and hippocampus during sleep. Nat Neurosci. 2007;10(1):100–7.

49. Xu S, Jiang W, Poo MM, Dan Y. Activity Recall in Visual Cortical Ensemble. Nat Neurosci. 2012 Jan 22;15(3):449-S2.

50. Lansink CS, Goltstein PM, Lankelma JV, McNaughton BL, Pennartz CMA. Hippocampus Leads Ventral Striatum in Replay of Place-Reward Information. PLOS Biol. 2009 Aug 18;7(8):e1000173.

51. Wilson MA, McNaughton BL. Reactivation of hippocampal ensemble memories during sleep. Science. 1994 Jul 29;265(5172):676–9.

52. Kriegeskorte N, Mur M, Bandettini PA. Representational similarity analysis-connecting the branches of systems neuroscience. Front Syst Neurosci. 2008;2:4.

53. Piasini E, Soltuzu L, Muratore P, Caramellino R, Vinken K, de Beeck HO, et al. Temporal stability of stimulus representation increases along rodent visual cortical hierarchies. Nat Commun. 2021;12(1):1–19.

54. Salvatori T, Song Y, Lukasiewicz T, Bogacz R, Xu Z. Predictive Coding Can Do Exact Backpropagation on Convolutional and Recurrent Neural Networks. ArXiv Prepr ArXiv210303725. 2021;

55. Whittington JC, Bogacz R. An approximation of the error backpropagation algorithm in a predictive coding network with local Hebbian synaptic plasticity. Neural Comput. 2017;29(5):1229–62.

56. Riesenhuber M, Poggio T. Hierarchical models of object recognition in cortex. Nat Neurosci. 1999;2(11):1019–25.

57. Goodale MA, Milner AD. Separate visual pathways for perception and action. Trends Neurosci. 1992 Jan 1;15(1):20–5.

58. Mishkin M, Ungerleider LG, Macko KA. Object vision and spatial vision: two cortical pathways. Trends Neurosci. 1983 Jan 1;6:414–7.

59. Hasson U, Yang E, Vallines I, Heeger DJ, Rubin N. A hierarchy of temporal receptive windows in human cortex. J Neurosci. 2008;28(10):2539–50.

60. Murray JD, Bernacchia A, Freedman DJ, Romo R, Wallis JD, Cai X, et al. A hierarchy of intrinsic timescales across primate cortex. Nat Neurosci. 2014;17(12):1661–3.

61. van Meegen A, van Albada SJ. Microscopic theory of intrinsic timescales in spiking neural networks. Phys Rev Res. 2021 Oct 28;3(4):043077.

62. Chaudhuri R, Knoblauch K, Gariel MA, Kennedy H, Wang XJ. A large-scale circuit mechanism for hierarchical dynamical processing in the primate cortex. Neuron. 2015;88(2):419–31.

63. Mejias JF, Wang XJ. Mechanisms of distributed working memory in a large-scale network of macaque neocortex. Elife. 2022;11:e72136.

64. Walsh KS, McGovern DP, Clark A, O'Connell RG. Evaluating the neurophysiological evidence for predictive processing as a model of perception. Ann N Y Acad Sci. 2020;1464(1):242.

65. Bastos AM, Usrey WM, Adams RA, Mangun GR, Fries P, Friston KJ. Canonical microcircuits for predictive coding. Neuron. 2012;76(4):695–711.

66. Keller GB, Mrsic-Flogel TD. Predictive processing: a canonical cortical computation. Neuron. 2018;100(2):424–35.

67. Jordan R, Keller GB. Opposing influence of top-down and bottom-up input on excitatory layer 2/3 neurons in mouse primary visual cortex. Neuron. 2020;108(6):1194–206.

68. Markov NT, Vezoli J, Chameau P, Falchier A, Quilodran R, Huissoud C, et al. Anatomy of hierarchy: feedforward and feedback pathways in macaque visual cortex. J Comp Neurol. 2014;522(1):225–59.

69. Oude Lohuis MN, Pie JL, Marchesi P, Montijn JS, de Kock CPJ, Pennartz CMA, et al. Multisensory task demands temporally extend the causal requirement for visual cortex in perception. Nat Commun. 2022 May 23;13(1):2864.

6. Supplementary Materials

6.1 Network architecture and hyperparameters

The networks consist of four fully connected areas of which the topmost (area 3) has no error units and the lowest (area 0) is driven by the input only, in a pixel-wise manner. Thus, the number of neurons in area 0 corresponds to the resolution of the inputs. Tab S1 shows the precise number of neurons per area and simulation. Tab S2 lists the used hyperparameters.

Dataset	Architecture
Translation MNIST	1156, 2000, 500, 30
Rotating MNIST, Scaling MNIST	784, 2000, 500, 30
Toy objects	1156, 1000, 250, 15

Tab S1. Network architecture used for the different datasets.

Parameter	Value	Meaning
ϵ_{inf}	0.05	uniform inference rate for areas 1-3
ϵ_{learn}	0.01	learning rate
n_{eps}	20-40	number of training epochs
n_{isteps}	10	inference steps before weight update
n_{freps}	5	inference-learn cycles on each frame
n_{sreps}	10	cycles on each sequence per epoch

Tab S2. Network hyperparameters.

6.2 Training

Network training was conducted in nested loops as described in section 2.3. Alg S1 depicts the pseudocode for both training paradigms. The main difference between the continuous and static training paradigms is the additional reset of activity in the beginning of the fifth for loop. To compensate for the shorter time between activity resets in the static training paradigm, the number of cycles per frame n_{freps} is increased by a factor of 6.

```
for i ← 1, n_eps do                              ▷ Epochs
    for j ← 1, n_seqs do                         ▷ Number of sequences
        Initialize activity
        for k ← 1, n_sreps do                    ▷ Iterations per sequence
            for l ← 1, n_fps do                  ▷ Frames per sequence
                for m ← 1, n_freps do            ▷ Iterations per frame
                    (Static training: Reset activity)
                    for n ← 1, n_isteps do       ▷ Inference steps
                        inference ((1(3)
                    end for
                    update weights ((4)
                end for
            end for
        end for
    end for
end for
```

Alg S1. Nested loops during network training as described in the Methods section. In the static training, activities are reset each time a new input is presented.

6.3 Inference of high-level representations

Convergence of high-level neural activity took considerably longer (2000 inference steps were used) than the duration that was necessary until the total prediction error in the network converged (one to two orders of magnitude less). I.e., after the predictions errors were minimized, further inference improved invariance, but not stimulus reconstruction.

6.4 Influence of temporal continuity

In how far is the learning of invariant representations attributable to the training paradigm? Fig S1 shows the RDM of a network trained in a static manner: the more position-dependent representations contrast the RDMs of the continuously trained networks (Fig 4b-f) with more uniform representations within sequences.

To analyze whether the different neural timescales are a result of the training paradigm or a result of the network architecture, we compared the decay speed of activity autocorrelation to the statically trained network (Fig S2).

Fig S1. Network trained in a static manner with resets of activity after each frame show less invariance in area-3 representations compared to the continuously trained networks (Fig 4b-f). The diagonal structure of the RDM shows that representations are specific to individual images and do not generalize across positions.

Fig S2. Decay of activity autocorrelation of neural subpopulations in a statically trained network in which activity is reset after each frame. a) Representation neurons, b) Error neurons, c) Inferred decay constants to quantify the timescale on which neural activity changed.

6.5 Reconstruction of complete inputs

To test which input patterns can be reconstructed from different network areas, an input image needs to be presented for an extended period. Here, 2000 inference steps are used. The image was then removed, and reconstructions were triggered from the chosen area, i.e., predictions are consecutively projected to the area below according to Fig 2a:

$$\hat{y}_l = W_l y_{1+1} \tag{6}$$

6.6 Reconstruction of occluded sequences

For reconstruction of whole objects from partially occluded sequences, the first frame of a sequence was presented for 2000 inference steps to give higher areas time to infer stimulus identity. Each consecutive frame of the sequence was then shown for 100 inference steps. Lastly, reconstructions were normalized, dividing all predictions by the value of the largest prediction.