Data and text mining

Deep Multimodal Graph-Based Network for Survival Prediction from Highly Multiplexed Images and Patient Variables

Xiaohang Fu[1,*], Ellis Patrick[2,3] and Jinman Kim[1,*]

[1]School of Computer Science, Faculty of Engineering, The University of Sydney, NSW 2006, Australia
[2]School of Mathematics and Statistics, The University of Sydney, NSW 2006, Australia
[3]Centre for Cancer Research, Westmead Institute of Medical Research, The University of Sydney, NSW 2145, Australia

*To whom correspondence should be addressed.

Abstract

Motivation: The spatial architecture of the tumour microenvironment and phenotypic heterogeneity of tumour cells have been shown to be associated with cancer prognosis and clinical outcomes, including survival prediction. Recent advances in highly multiplexed imaging, including imaging mass cytometry (IMC), capture spatially resolved, high-dimensional maps that quantify dozens of disease-relevant biomarkers at the single-cell level, that contain potential to inform patient-specific prognosis. However, existing methods for predicting survival either do not leverage IMC images as they only use patient variables (PVs), or require substantial pre-processing such as cell segmentation and handcrafting a selection of features. The value in combining the two modalities (IMC images and PVs) in a complementary manner has not been fully explored. There is no end-to-end method designed to use both modalities with minimal pre-processing to directly output survival predictions with enhanced accuracy.
Results: We introduce a deep multimodal graph-based network (DMGN) that integrates IMC images and multiple PVs for end-to-end survival prediction of breast cancer. We propose a graph-based module that aggregates deep image features from different spatial regions across the image with all PVs. We propose another module to automatically generate embeddings specialised for each PV to support multimodal aggregation. We show that our modules consistently enhance survival prediction performance using two public datasets, and that our DMGN outperforms state-of-the-art methods at survival prediction.
Availability: The source code is available at https://github.com/xhelenfu/DMGN_Survival_Prediction
Contact: xiaohang.fu@sydney.edu.au

1 Introduction

The spatial organisation and structure of the tumour microenvironment surrounding tumour cells, and cellular phenotypic heterogeneity are associated with clinical outcomes and prognosis in cancer (Ali et al. 2020; Bedard et al. 2013; Dagogo-Jack and Shaw 2018). This information may be valuable for improving the accuracy of survival prediction models, which aim to predict the time to death events given an array of information regarding the patient. Recent techniques in highly multiplexed imaging mass cytometry (IMC) use isotope-tagged antibodies to capture maps of the spatial expression of over 30 biomarkers at the single-cell level (Ali et al. 2020; Curtis et al. 2012; Jackson et al. 2020). These images contain detailed high-dimensional information and provide opportunities for further quantitative analysis, including survival prediction.

Traditional survival analysis typically relies on the Cox proportional hazards (CPH) model (Cox 1992). More recently, deep learning (DL) models have been successfully applied in a wide range of applications, including modelling the survival function. In contrast to conventional survival models, DL models do not require manual feature generation and selection, as they can automatically extract deep features from the inputs

Fig. 1. Proposed DMGN model for end-to-end survival prediction from PVs and IMC images. PVs are processed by the PVEM to produce embeddings. The IMC image is processed by a CNN backbone to create deep image features. Both modalities are combined in the RMRM and then used to predict survival.

that are relevant to survival. As an example, DeepSurv (Katzman et al. 2018) used a negative Cox partial likelihood loss to handle right-censored survival data. However, existing DL survival prediction methods typically focus on analysing patient variables (PVs), such as the patient's clinical information including age, or gene expression (Katzman et al. 2018; Lee et al. 2018; Sharma et al. 2021; Sun et al. 2021; G. Wu et al. 2021). This single modality approach ignores spatial phenotype information at the cellular level that is relevant to disease prognosis.

Multiplexed images have recently been leveraged to predict oestrogen receptor (ER) status (Martin-Gonzalez et al. 2021). This demonstrated the potential of a graph neural network (GNN) (Z. Wu et al. 2020), which models objects as nodes and capture the relationships between them as edges, to represent cellular communities and cell-cell interactions. However, this approach is unimodal and does not consider PVs. It also relies on considerable image pre-processing to segment cells and create neighbourhoods, which adds extra labour and potential errors that would propagate to the survival analysis downstream.

1.1 Our contributions

- We introduce a deep multimodal graph-based network (DMGN) that integrates highly multiplexed IMC images and multiple PVs for survival prediction of cancer. To our knowledge, our method is the first to combine these two modalities for end-to-end survival prediction.
- We leverage a convolutional neural network (CNN) to automatically extract deep image features across the entire input IMC image. Our method does not require cell segmentation, marker selection, or any other input processing external to the basic DL data pipeline.
- We propose a region-based multimodal relational module (RMRM) to combine features from both modalities. The RMRM graph considers relationships between image features in different spatial regions and all PVs. The relationship between each PV and spatial region is scaled based on its strength, which allows the RMRM to capture relationships in more detail and support explainability.

- We use a patient variable embedding module (PVEM) to automatically generate embedded representations that are meaningful to each PV through auxiliary reconstruction tasks. These representations support the relational learning with image features in the RMRM and improve survival prediction.

2 Materials and methods

2.1 Datasets

Table 1. Details of the two public datasets used in this study.

	METABRIC	Basel
Number of patient variables	9	9
Median censored time	2,908 days	74 months
Uncensored rate	45.2%	28.1%
Total number of patients	456	285
Total number of samples	518	376
Number of IMC channels	50	52

Two independent publicly available datasets were used. We used the Molecular Taxonomy of Breast Cancer International Consortium (METABRIC) dataset (Ali et al. 2020; Curtis et al. 2012) as the primary dataset. IMC images and PVs were available for 456 patients (518 samples). The uncensored rate (observed death) was 45.2%, and the median survival time was 2,908 days. We used 9 PVs as done by previous studies (Katzman et al. 2018; Sharma et al. 2021; Sun et al. 2021; G. Wu et al. 2021). The variables comprised 5 clinical features (age at diagnosis, ER status, chemotherapy indicator (CT), hormone treatment indicator (HT), and radiotherapy indicator (RT)), and 4 gene indicators (MKI67, EGFR,

PGR, and ERBB2). Invasive carcinoma cores of 0.6 mm were labelled with antibodies and quantified using a Hyperion Imaging Mass Cytometer (Fluidigm). The IMC images contained 50 channels with heights of 25–744 (average 464) pixels, and widths of 60–834 (average 478) pixels.

We used the Basel dataset (Jackson et al. 2020) for further validation and independent testing. IMC images and PVs were available for 285 patients (376 samples). The uncensored rate was 28.1%, and the median survival was 74 months. We used the same PVs as for the METABRIC dataset, except RT was unavailable and was substituted by immune therapy (IT). Cores of 0.8 mm were analysed using a Hyperion Imaging System (Fluidigm). The IMC images contained 52 channels with heights of 223–883 (average 711) pixels, and widths of 178–1032 (average 746) pixels.

We used all censored and uncensored samples, and marker channels for both datasets in the model inputs. All images were resized to 176×176 pixels with bilinear interpolation. Details of the datasets are in Table 1.

2.2 Deep multimodal graph-based network (DMGN)

In our method, information from each modality is first extracted by two separate branches. IMC images are processed by a CNN backbone to output a grid of feature vectors that describe spatial regions (fixed windows or patches of pixels) across the image. PVs are processed by the PVEM to generate variable-specific embedding vectors. The feature vectors for both modalities are then integrated in the RMRM and used to predict survival. We present an overview of our method in Fig. 1.

We use the versatile ResNet-50 model (Kaiming He et al. 2015b) as the CNN backbone for visual feature extraction. We do not select for certain IMC markers; all channels in the IMC image are used. We insert a 1×1 convolution layer immediately after the 'conv5_x' block of the backbone to reduce the number of feature channels from 2,048 to 128. This minimises the risk of overfitting by reducing the number of parameters in the model. The output of the CNN backbone is a feature volume $\mathbf{h}^{\mathbf{IMC}} \in \mathbb{R}^{6 \times 6 \times 128}$ for each input image.

2.2.1 Patient variable embedding module (PVEM)

Prior to multimodal relational learning, each PV is transformed into feature embeddings by the PVEM. There are 9 units in the module, each specialised for a PV. The units consist of fully connected (FC) layers arranged to perform autoencoding of the input variable, i.e., they learn to reconstruct the input variable.

We define the units to output PV embeddings and reconstructions as:

$$\mathbf{h}_j^{\mathbf{PVEM}}(\mathbf{x}_j) = \mathbf{W}_{0,j}\mathbf{x}_j + \mathbf{b}_{0,j} \tag{1}$$

$$\mathbf{p}_j^{\mathbf{PVEM}}(\mathbf{h}_j^{\mathbf{PVEM}}) = \mathbf{W}_{1,j}\mathbf{ReLU}(\mathbf{h}_j^{\mathbf{PVEM}}) + \mathbf{b}_{1,j} \tag{2}$$

where $\mathbf{p}_j^{\mathbf{PVEM}} \in \mathbb{R}^{1 \times k}$ denotes the prediction for variable j. $\mathbf{p}_j^{\mathbf{PVEM}}$ is a single scalar ($k = 1$) for continuous PVs (age, MKI67, EGFR, PGR, and ERBB2), or class probabilities ($k = 2$) for categorical variables (ER status, CT, HT, and RT/IT) with softmax activation. $\mathbf{h}_j^{\mathbf{PVEM}} \in \mathbb{R}^{128 \times 1}$ is the variable-specific feature vector embedding. The PVEM unit of a category is characterised by a set of trainable weights and biases of two FC layers, comprising of $\mathbf{W}_{0,j} \in \mathbb{R}^{k \times 128}$, $\mathbf{W}_{1,j} \in \mathbb{R}^{128 \times k}$, $\mathbf{b}_{0,j} \in \mathbb{R}^{1 \times 128}$, and $\mathbf{b}_{1,j} \in \mathbb{R}^{1 \times k}$.

During training, $\mathbf{p}^{\mathbf{PVEM}}$ is used to compute auxiliary reconstruction losses L^{PVEM} that contribute to the total loss. L^{PVEM} is the sum of the mean squared errors of the continuous variables and cross-entropy losses of the categorical variables.

By minimising the auxiliary losses, PVEM ensures that $\mathbf{h}^{\mathbf{PVEM}}$ is a meaningful representation of each PV. This assists with multimodal relational processing in the RMRM. The auxiliary predictions are only used during model training and have no role at inference time.

2.2.2 Region-based multimodal relational module (RMRM)

The RMRM integrates features between both modalities using two graph convolutional network (GCN) layers with the same graph topologies. Graph convolutions allow each node to receive the aggregated feature vectors of its neighbouring (connected) nodes. The input feature vector for the node of PV j is $\mathbf{h}_j^{\mathbf{PVEM}}$, and for IMC region i is $\mathbf{h}_i^{\mathbf{IMC}}$. The RMRM topology considers relationships between features of each IMC image region and all 9 PVs. Features are transformed and passed between the two modalities via bidirectional edges. Each node receives the aggregated feature vectors of its neighbouring nodes. Each IMC region receives the features of all PVs (through PV–IMC edges), and each PV receives the features of all IMC regions (through IMC–PV edges). Additionally, there is a self-edge for each node which preserves some features of each own node during a graph convolution. The adjacency matrix that describes the RMRM is presented in Fig. 2.

Fig. 2. RMRM adjacency matrix. Filled squares are edges between source and destination nodes. Blank squares represent the absence of an edge (zeros are omitted for simplicity). All 36 image regions are connected to the 9 PVs by bidirectional edges.

Each graph convolution in the RMRM linearly transforms the neighbouring feature vectors via learned weights, then sums the resulting vectors and applies an activation function to the output. In a standard GCN, the neighbouring nodes are weighted equally towards the central node. We used the graph attention network (GAT) (Veličković et al. 2017) approach to allow the contributions of each neighbour node towards the central node to be adaptive, rather than equal and fixed. This allows the most important information to be prioritised. GAT operates on the graph layers of the GRM with topologies and connections as described in Fig. 2. The graph attentional layer computes normalised attention coefficients via a self-attention mechanism:

$$\alpha_{uv} = \frac{\exp\big(\text{LeakyReLU}(\mathbf{a}^T[\mathbf{Wh}_u \parallel \mathbf{Wh}_v])\big)}{\sum_{k \in \mathcal{N}_u} \exp\big(\text{LeakyReLU}(\mathbf{a}^T[\mathbf{Wh}_u \parallel \mathbf{Wh}_k])\big)} \tag{3}$$

where $\mathbf{h} = \{\mathbf{h}_1, \mathbf{h}_2, \dots, \mathbf{h}_N\}$, $\mathbf{h}_n \in \mathbb{R}^F$ represents the input feature vectors to the GAT layer with $N = 45$, corresponding to the 9 PVs and 36 IMC regions (i.e., $\mathbf{h}^{\mathbf{PVEM}} \in \mathbb{R}^{128 \times 9}$ and $\mathbf{h}^{\mathbf{IMC}} \in \mathbb{R}^{128 \times 36}$), α_{uv} is the attention coefficient for node v to u, and $\mathcal{N}_u$ denotes the neighbourhood nodes of u. The feature vectors are linearly transformed via $\mathbf{W} \in \mathbb{R}^{F' \times F}$, the weight matrix shared for every node, then by $\mathbf{a} \in \mathbb{R}^{2F'}$, the weight vector of a single-layer feedforward neural network of the attention mechanism,

with ∥ representing concatenation. LeakyReLU nonlinearity (with a slope of 0.2 for inputs < 0) followed by softmax normalisation are then applied.

The updated feature vectors, $\mathbf{h}' = \{\mathbf{h}'_1, \mathbf{h}'_2, ..., \mathbf{h}'_N\}$, $\mathbf{h}'_n \in \mathbb{R}^{F'}$, can then be computed by proportionally aggregating over neighbouring nodes:

$$\mathbf{h}'_u = \sigma\left(\sum_{v \in \mathcal{N}_u} \alpha_{uv} \mathbf{W}\mathbf{h}_v\right) \tag{4}$$

where σ is the exponential linear unit (ELU) nonlinearity (Clevert et al. 2016).

Furthermore, we used the multi-head attention mechanism for better stability, computing multiple independent attention coefficients for each node that are aggregated via concatenation:

$$\mathbf{h}'_u = \|_{m=1}^{M} \sigma\left(\sum_{v \in \mathcal{N}_u} \alpha_{uv}^m \mathbf{W}^m \mathbf{h}_v\right) \tag{5}$$

where, for the m-th attention head, α_{uv}^m are the normalised attention coefficients and $\mathbf{W}^m$ are the weights of the input linear transformation. In the first layer, we use 8 attention heads per node and $F_0 = 8$, thereby computing a total of 64 features, as done in the original paper (Veličković et al. 2017). For the second layer, we compute $F_1 = 128$ features with a single attention head.

2.2.3 Survival prediction and training

The RMRM outputs of the IMC feature volumes $\mathbf{h}^{\mathbf{IMC}''} \in \mathbb{R}^{128 \times 36}$ are subsequently vectorised by a global average pooling (GAP) layer (M. Lin et al. 2014), producing a vector of $\mathbf{g}^{\mathbf{IMC}} \in \mathbb{R}^{128 \times 1}$ per image. This vector is then concatenated with all RMRM PV output vectors, resulting in one vector with dimensionality $1{,}280 \times 1$ per input sample. The last group of layers comprises an FC layer, ReLU activation, and a final output FC layer with linear activation.

The output of the model is a scalar $\hat{h}_\theta(x)$ that estimates the log-risk function in the Cox model (Katzman et al. 2018). The model is trained by minimising the sum of L^{PVEM} and mean negative Cox partial likelihood loss L^{Surv}, which is suitable for right-censored survival data:

$$L^{Surv} = -\frac{1}{N_{E=1}} \sum_{i:E_i=1} \left(\hat{h}_\theta(x_i) - \log \sum_{j \in \mathcal{R}(T_i)} e^{\hat{h}_\theta(x_j)}\right) \tag{6}$$

$$L^{total} = \lambda L^{PVEM} + L^{Surv} + \gamma \|\theta\|_2^2 \tag{7}$$

where x_i denotes the input IMC image and PVs of sample i, θ represents the model parameters, E indicates an observed event ($N_{E=1}$ is the number of patients with recorded death), T is the overall survival time (for $E = 1$) or censored time (for $E = 0$), and $\mathcal{R}(T_i)$ are the patients with $T \geq T_i$. λ is a hyperparameter to scale L^{PVEM}, and γ is the L_2 regularisation hyperparameter.

2.3 Implementation details

The following implementation and hyperparameter choices were kept consistent for all experiments to ensure a fair comparison. The networks were trained end-to-end from scratch for 300 epochs with a batch size of 8. We employed the Adam optimiser (Kingma and Ba 2014) to minimise the training loss (Eq. 7) at a fixed learning rate of 0.0001, with a first moment estimate of 0.9 and second moment estimate of 0.999. We set λ to 4, as determined empirically (evaluation in Supplementary Table S1), and γ to 0.0001. Weights of the convolutional layers were initialised using He et al.'s method (K. He et al. 2015a), while biases were initialised to zero. Glorot (Xavier) initialisation (Glorot and Bengio 2010) was used for FC layers. Dropout was not used in any experiment.

The channels of the images were mean-subtracted and normalised to unit variance using the training set means and standard deviations. We employed standard online (on-the-fly) image data augmentation by randomly applying a flip (horizontal or vertical), or rotation (of 90, 180 or 270 degrees) to the input images. The order of training examples was shuffled for every epoch. All networks were implemented using the PyTorch framework (Paszke et al. 2019). Both training and testing were performed with a 12GB NVIDIA GTX Titan V GPU. Training required about 1.5 hours for completion per cross-validation fold.

2.4 Evaluation metrics

Survival prediction performance of the methods was evaluated using the concordance index (C-index) (Harrell Jr et al. 1984), which is the standard evaluation metric in survival analysis. The C-index ranges from 0 to 1.0, where 1.0 indicates perfect ranking of predicted death times, and 0.5 indicates random predictions.

The log-rank test was used to assess the difference between two Kaplan-Meier survival curves. A log-rank p-value below 0.05 is considered statistically significant.

2.5 Ablation study and validation

We performed an ablation study to validate the survival prediction performance of our proposed modules and DMGN. We first determined the performance using only a single modality—either IMC images or PVs. The model for image-only inputs consisted of a ResNet-50 backbone with the same survival prediction output layers as in the DMGN. The model for the PVs consisted of the PVEM (but without auxiliary reconstruction losses) and the same survival prediction output layers.

We then benchmarked conventional approaches to combine multimodal information, including concatenation of multimodal feature vectors, and attention-weighted aggregation. Attention is a common approach in many multimodal applications that use weights to select and combine relevant features from both modalities (Arevalo et al. 2017; Jain and Wigington 2019; C. Zhang et al. 2020a).

We assessed the performance of our DMGN without auxiliary PVEM reconstruction losses. Furthermore, we investigated a modified RMRM that operates on $\mathbf{h}^{\mathbf{IMC}''} \in \mathbb{R}^{128 \times 1}$ instead of $\mathbf{h}^{\mathbf{IMC}''} \in \mathbb{R}^{128 \times 36}$, by moving GAP to just before the RMRM instead of just after. This effectively removes all spatial information in the RMRM by compressing the image features to a single feature vector.

For all methods, we performed 5-fold cross-validation on both datasets by randomly assigning 80% of the patients for training and the remaining 20% for testing in each fold. We also carried out independent validation where the model was trained using METABRIC data but validated using all available Basel data. We used markers common to both datasets and removed RT from METABRIC data and IT from Basel data. There was no additional input pre-processing or model finetuning for this independent validation.

2.6 Comparison to existing methods

We benchmarked our proposed DMGN to existing survival prediction methods for both datasets. State-of-the-art methods for the METABRIC dataset include DeepHit (Lee et al. 2018), DeepSurv (Katzman et al. 2018), BroadSurv (G. Wu et al. 2021), DAGSurv (Sharma et al. 2021), and AttentionSurv (Sun et al. 2021). We report the C-index for the 3-year predicted survival for DAGSurv as it is a discrete-time survival model, following previous survival analysis studies (Kim et al. 2020; Y. Zhang et al. 2020b). All these methods were designed for single modality inputs and use the same 9 PVs as our DMGN (age, ER status, CT, HT, RT, MKI67, EGFR, PGR, and ERBB2), except for DeepHit, which used 21

variables. We also report results for the CPH model (Cox 1992) and random survival forest (RSF) (Ishwaran et al. 2008).

We used the CPH model (Cox 1992) with various input modality combinations and regularisation as the benchmark for the Basel dataset, due to a lack of recent methods. We used either L_1, L_2, or L_1+L_2 regularisation strategies. The inputs were either cell type proportions, PVs, or both cell type proportions and PVs. Cell type proportions of each IMC image were computed using metacluster cell type counts (Jackson et al. 2020), divided by the total cell count for the image.

3 Results

3.1 Ablation study and validation

The prediction performance of the DMGN was consistently superior compared to the various DL baselines for the two datasets (Table 2). The single modality (image or PVs only) results indicate that PVs contain more useful information for survival prediction compared to images. The higher scores of all multimodal approaches compared to single modality approaches demonstrate the importance in using both modalities.

Table 2. Prediction performance (C-index) of the proposed DMGN compared to DL baselines with different inputs and fusion methods. Bold indicates the best performance for each dataset.

Method	METABRIC	Basel
IMC image only	0.6581	0.6769
PVs only	0.7147	0.7078
Multimodal, concatenation	0.7174	0.7131
Multimodal, attention	0.7327	0.7242
Multimodal, DMGN (no aux losses)	0.7398	0.7354
Multimodal, DMGN (no spatial)	0.7399	0.7359
Multimodal, DMGN (proposed)	**0.7484**	**0.7479**

In both datasets the concatenation approach improved performance slightly compared to using only PVs. Concatenation is a suboptimal approach to combine multimodal information as it does not extract any further useful relationships from the two modalities that would be more informative compared to single modality information. The improvements from attention-weighted aggregation were more substantial, as this

approach prioritises the multimodal features according to their importance for survival prediction.

All DMGN variants were superior to concatenation and attention-based aggregation. Performance of the DMGN was lower without auxiliary reconstruction losses. This finding supports the motivation and design of reconstruction losses, i.e., they allow the PVEM output features to be more descriptive of each PV, thereby allowing more meaningful relational learning with image features and ultimately aiding survival prediction.

DMGN performance was also inferior without spatial image information during relational processing in the RMRM. Our proposed topology considers different relationships between each PV to various regions of the image. This allows multimodal relationships to be extracted in more detail. The ablation study shows that the spatial simplification of IMC images has a deleterious effect in the present multimodal fusion task.

To further illustrate the utility of our model, the Kaplan-Meier survival curves for one testing fold from the METABRIC (left) and Basel (right) datasets are shown in Fig. 3. Our DMGN successfully stratified the patients into two significantly different high and low risk groups (log-rank $p = 3\times10^{-21}$ for METABRIC, $p = 2\times10^{-9}$ for Basel). The curves for the other folds displayed similarly significant separation between the two groups (all log-rank $p < 10^{-5}$).

The independent validation performance for our DMGN that was trained on METABRIC data and tested on Basel data was lower than our model that was both trained and tested on Basel data (Table 3). This finding is not surprising for DL since model weights adapt to the input characteristics of the training set and typically do not generalise to new data at the same level of accuracy (Geirhos et al. 2018). The reduction in independent validation performance would also be compounded by heterogeneous characteristics between the datasets, differences in the panel design, and differences in imaging protocols (Ali et al. 2020; Curtis et al. 2012; Jackson et al. 2020).

Table 3. Validation of the proposed DMGN on an independent test set.

Method	C-index
Test METABRIC (trained METABRIC)	0.7380
Test Basel (trained Basel)	0.7146
Independent test Basel (trained METABRIC)	0.6312

3.2 Comparison to existing methods

Our DMGN had superior survival prediction performance compared to all existing methods for both datasets (Table 4 and Table 5). Performance of

Fig. 3. Kaplan-Meier survival curves. DMGN predictions for high risk (higher than or equal to median) and low risk (lower than median) groups for a) METABRIC and b) Basel datasets for one testing fold. '×' indicates a censored patient. Predicted KM curves are significantly different for high and low risk groups (log-rank $p = 3\times10^{-21}$ for METABRIC, $p = 2\times10^{-9}$ for Basel).

CPH with different input modalities on the Basel dataset (Table 5) followed the same pattern as the DL ablations experiments (Table 2), where image-only inputs resulted in the lowest performance. Performance using PV-only inputs was higher but was surpassed by multimodal inputs.

Table 4. Comparison of the proposed DMGN to existing methods on the METABRIC dataset.

Method	C-index
CPH	0.632
RSF	0.620
DeepSurv (Katzman et al. 2018)	0.654
DeepHit (Lee et al. 2018)	0.691
BroadSurv (G. Wu et al. 2021)	0.643
DAGSurv (Sharma et al. 2021)	0.689
AttentionSurv (Sun et al. 2021)	0.708
DMGN (proposed)	**0.748**

Table 5. Comparison of the proposed DMGN to existing methods on the Basel dataset.

Method	C-index
CPH (cell type proportions, L_2)	0.584
CPH (PVs, L_2)	0.686
CPH (cell type proportions + PVs, L_1)	0.696
CPH (cell type proportions + PVs, L_2)	0.698
CPH (cell type proportions + PVs, $L_1 + L_2$)	0.697
DMGN (proposed)	**0.748**

3.3 Weights of patient variables

Table 6. Average RMRM weights of the PVs to image regions and their rank in descending order.

Patient Variable	METABRIC		Basel	
	Weight	Rank	Weight	Rank
Age	0.1374	1	0.0982	4
MKI67	0.1324	2	0.0967	6
EGFR	0.0935	7	0.0911	9
PGR	0.1000	4	0.0932	7
ERBB2	0.0906	8	0.1021	1
CT	0.1140	3	0.0986	3
RT (METABRIC) / IT (Basel)	0.0948	5	0.0971	5
HT	0.0894	9	0.1006	2
ER	0.0939	6	0.0925	8

We analysed the weights of the RMRM connections between PVs and image regions (PV–IMC intermodal edges, cyan in Fig. 2). The average weights of the test samples in all cross-validation folds and their rankings for both datasets are presented in Table 6. The weights revealed different patterns and characteristics of the two cohorts. The rankings for the two cohorts were different, e.g., the top two PVs were 'age' and 'MKI67' for

METABRIC but were 'ERBB2' and 'HT' for Basel. The differences in the weights of the PVs were smaller for Basel compared to METABRIC.

4 Discussion

In this manuscript we proposed a deep multimodal graph-based network that integrates IMC images and multiple PVs for end-to-end survival prediction. Our main findings are that: i) the ablation study showed that our PVEM and RMRM were effective at improving survival prediction performance and outperformed alternative multimodal approaches; ii) our DMGN had superior performance when compared to the state-of-the-art methods for both datasets; and iii) the RMRM weights revealed different characteristics of the two datasets and the relationships between PVs and IMC images.

4.1 Ablation study and validation

The ablation study (Table 1) validated the benefits of using both modalities (IMC images and PVs), and the effectiveness of our DMGN architecture with PVEM and RMRM for survival prediction. Our modules provide advantages that are not feasible in conventional multimodal fusion approaches such as with concatenation and attention. The RMRM captures multimodal relationships across different spatial regions of the image, and scales the contributions from each feature to prioritise the most important relationships. Multimodal aggregation is also carried out with meaningful representations of the PVs due to the PVEM.

Our DMGN has demonstrated competence in segregating high- and low-risk groups (Fig. 3), which is practically beneficial as this knowledge may be used to guide personalised patient management. However, the performance of DMGN may be limited when directly applied to an independent cohort with different data characteristics (Table 3). While it was encouraging that our DMGN was robust to a reordering and omission of markers when trained and tested on IMC experiments with similar but ultimately different panel designs, standardised imaging protocols or preprocessing would clearly help to ensure comparable image intensity distributions and alleviate performance reductions (Willemink et al. 2020).

4.2 Comparison to existing methods

The comparisons (Table 4 and Table 5) showed the consistent advantages of our DMGN over existing methods across the two datasets. In addition to the contributions provided by our PVEM and RMRM, our DMGN is distinct from existing methods in our use of IMC images in addition to PVs. These images spatially quantify multiple clinically established breast cancer biomarkers such as MKI67 and HER2, and characterise spatial cellular heterogeneity, composition, and organisation (Ali et al. 2020; Curtis et al. 2012; Jackson et al. 2020), which are potential indicators of cancer prognosis (Bedard et al. 2013; Dagogo-Jack and Shaw 2018). The use of a single modality in survival analysis (i.e., PVs) as done by previous studies is therefore limited, and our results show that the value in multiplexed images should be exploited. Our model can leverage both modalities, and aggregate PVs and spatial features across the image to outperform the state-of-the-art.

4.3 Weights of patient variables

The PVEM allows a level of explainability as the relative strengths between the PVs and image regions can be assessed according to the weights

of each connection in the graph. This ability of the PVEM may be used to understand the contributing factors towards survival predictions and signify samples for further analysis. For example, image regions with particularly high or low PVEM weights to certain PVs may be quantitatively analysed at the cellular level.

4.4 Future work

While our DMGN was specifically optimised and validated on IMC data, there is potential for it to be extended and applied to other multiplexed imaging assays (Lewis et al. 2021). This could include other proteomic assays such as co-detection by indexing (CODEX) (Black et al. 2021) and cyclic immunofluorescence (CycIF) (J.-R. Lin et al. 2015) which can measure a similar number of protein markers to IMC but can measure larger regions of tissue. It could also include transcriptomic assays such as sequential Fluorescence in situ Hybridization (seqFISH+) (Eng et al. 2019) and high-definition spatial transcriptomics (Vickovic et al. 2019) that can measure an order of magnitude more features.

PV embeddings may be integrated with image features at different stages in the CNN. Such a design may be more effective at leveraging image features at different scales. Future iterations of the DMGN can include components designed to increase the explainability and interpretability of the architecture. Cell segmentation masks, or cell segmentation as a secondary objective may be incorporated into the architecture to delineate relationships between IMC markers and PVs that are inside or outside cell areas. This may be beneficial for performance or explainability.

5   Conclusion

We introduced an end-to-end DL model for survival prediction that integrates information from multiple PVs and highly multiplexed images with minimal pre-processing. Our RMRM aggregates features from different spatial areas of the image and all PVs. Our PVEM can automatically produce embedded representations for each PV to support intermodal learning and survival prediction. Our method consistently surpassed existing methods for predicting the survival of breast cancer patients.

Funding

This work has been partly supported by Australian Research Council grants (DP200103748 and DE200100944), and AIR@innoHK programme of the Innovation and Technology Commission of Hong Kong.

Conflict of Interest: none declared.

Data availability

All data used in this study are publicly available. The METABRIC dataset (Ali et al. 2020; Curtis et al. 2012) may be obtained from https://idr.openmicroscopy.org/ (accession code idr0076). The Basel dataset (Jackson et al. 2020) may be obtained from https://doi.org/10.5281/zenodo.3518284.

References

Ali, H. Raza, et al. (2020), 'Imaging mass cytometry and multiplatform genomics define the phenogenomic landscape of breast cancer', *Nature Cancer,* 1 (2), 163-75.

Arevalo, John, et al. (2017), 'Gated Multimodal Units for Information Fusion'.

Bedard, Philippe L., et al. (2013), 'Tumour heterogeneity in the clinic', *Nature,* 501 (7467), 355-64.

Black, Sarah, et al. (2021), 'CODEX multiplexed tissue imaging with DNA-conjugated antibodies', *Nature Protocols,* 16 (8), 3802-35.

Clevert, Djork-Arné, Unterthiner, Thomas, and Hochreiter, Sepp (2016), 'Fast and Accurate Deep Network Learning by Exponential Linear Units (ELUs)'.

Cox, David R. (1992), 'Regression Models and Life-Tables', in Samuel Kotz and Norman L. Johnson (eds.), *Breakthroughs in Statistics: Methodology and Distribution* (New York, NY: Springer New York), 527-41.

Curtis, Christina, et al. (2012), 'The genomic and transcriptomic architecture of 2,000 breast tumours reveals novel subgroups', *Nature,* 486 (7403), 346-52.

Dagogo-Jack, Ibiayi and Shaw, Alice T. (2018), 'Tumour heterogeneity and resistance to cancer therapies', *Nature Reviews Clinical Oncology,* 15 (2), 81-94.

Eng, Chee-Huat Linus, et al. (2019), 'Transcriptome-scale super-resolved imaging in tissues by RNA seqFISH+', *Nature,* 568 (7751), 235-39.

Geirhos, Robert, et al. (2018), 'Generalisation in humans and deep neural networks', *Advances in neural information processing systems,* 31.

Glorot, Xavier and Bengio, Yoshua (2010), 'Understanding the difficulty of training deep feedforward neural networks', *Proceedings of the thirteenth international conference on artificial intelligence and statistics*, 249-56.

Harrell Jr, Frank E, et al. (1984), 'Regression modelling strategies for improved prognostic prediction', *Statistics in medicine,* 3 (2), 143-52.

He, K., et al. (2015a), 'Delving Deep into Rectifiers: Surpassing Human-Level Performance on ImageNet Classification', *2015 IEEE International Conference on Computer Vision (ICCV)*, 1026-34.

He, Kaiming, et al. (2015b), 'Deep Residual Learning for Image Recognition', *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 770-78.

Ishwaran, Hemant, et al. (2008), 'Random survival forests', *The annals of applied statistics,* 2 (3), 841-60.

Jackson, Hartland W., et al. (2020), 'The single-cell pathology landscape of breast cancer', *Nature,* 578 (7796), 615-20.

Jain, R. and Wigington, C. (2019), 'Multimodal Document Image Classification', *2019 International Conference on Document Analysis and Recognition (ICDAR)*, 71-77.

Katzman, Jared L., et al. (2018), 'DeepSurv: personalized treatment recommender system using a Cox proportional hazards deep neural network', *BMC Medical Research Methodology,* 18 (1), 24.

Kim, Hyungjin, et al. (2020), 'Preoperative CT-based deep learning model for predicting disease-free survival in patients with lung adenocarcinomas', *Radiology,* 296 (1), 216-24.

Kingma, Diederik P. and Ba, Jimmy (2014), 'Adam: A Method for Stochastic Optimization', *CoRR,* abs/1412.6980.

Lee, Changhee, et al. (2018), 'DeepHit: A Deep Learning Approach to Survival Analysis With Competing Risks', *Proceedings of the AAAI Conference on Artificial Intelligence,* 32 (1).

Lewis, Sabrina M., et al. (2021), 'Spatial omics and multiplexed imaging to explore cancer biology', *Nature Methods,* 18 (9), 997-1012.

Lin, Jia-Ren, Fallahi-Sichani, Mohammad, and Sorger, Peter K. (2015), 'Highly multiplexed imaging of single cells using a high-throughput cyclic immunofluorescence method', *Nature Communications,* 6 (1), 8390.

Lin, Min, Chen, Qiang, and Yan, Shuicheng (2014), 'Network in network', *International Conference on Learning Representations (ICLR)*.

Martin-Gonzalez, Paula, Crispin-Ortuzar, Mireia, and Markowetz, Florian (2021), 'Predictive modelling of highly multiplexed tumour tissue images by graph neural networks', *Interpretability of Machine Intelligence in Medical Image Computing, and Topological Data Analysis and Its Applications for Medical Data* (Springer), 98-107.

Paszke, Adam, et al. (2019), 'Pytorch: An imperative style, high-performance deep learning library', *Advances in neural information processing systems*, 8026-37.

Sharma, Ansh Kumar, et al. (2021), 'DAGSurv: Directed Ayclic Graph Based Survival Analysis Using Deep Neural Networks', in N. Balasubramanian Vineeth and Tsang Ivor (eds.), *Proceedings of The 13th Asian Conference on Machine Learning* (157; Proceedings of Machine Learning Research: PMLR), 1065--80.

Sun, Zhaohong, et al. (2021), 'Attention-Based Deep Recurrent Model for Survival Prediction', *ACM Trans. Comput. Healthcare,* 2 (4), Article 35.

Veličković, Petar, et al. (2017), 'Graph attention networks', *arXiv preprint arXiv:1710.10903*.

Vickovic, Sanja, et al. (2019), 'High-definition spatial transcriptomics for in situ tissue profiling', *Nature Methods,* 16 (10), 987-90.

Willemink, Martin J., et al. (2020), 'Preparing Medical Imaging Data for Machine Learning', *Radiology,* 295 (1), 4-15.

Wu, G., et al. (2021), 'BroadSurv: A Novel Broad Learning System-based Approach for Survival Analysis', *2021 8th International Conference on Information, Cybernetics, and Computational Social Systems (ICCSS)*, 26-31.

Wu, Zonghan, et al. (2020), 'A comprehensive survey on graph neural networks', *IEEE transactions on neural networks and learning systems,* 32 (1), 4-24.

Zhang, C., et al. (2020a), 'Multimodal Intelligence: Representation Learning, Information Fusion, and Applications', *IEEE Journal of Selected Topics in Signal Processing,* 14 (3), 478-93.

Zhang, Yucheng, et al. (2020b), 'CNN-based survival model for pancreatic ductal adenocarcinoma in medical imaging', *BMC medical imaging,* 20 (1), 1-8.