Measures of epitope binding degeneracy from T cell receptor repertoires

Andreas Mayer[1, 2] and Curtis G. Callan Jr[3, 4]

[1]*Division of Infection and Immunity, University College London*
[2]*Lewis-Sigler Institute for Integrative Genomics, Princeton University*
[3]*Department of Physics, Princeton University*
[4]*Institute for Advanced Study, Princeton, NJ*
(Dated: July 25, 2022)

Adaptive immunity is driven by specific binding of hyper-variable receptors to diverse molecular targets. The sequence diversity of receptors and targets are both individually known but, because multiple receptors can recognize the same target, a measure of the effective 'functional' diversity of the human immune system has remained elusive. Here, we show that sequence near-coincidences within T cell receptors that bind specific epitopes provide a new window into this problem, and allow the quantification of how binding probability co-varies with sequence. We find that near-coincidence statistics within epitope-specific repertoires imply a measure of binding degeneracy to amino acid changes in receptor sequence that is consistent across disparate experiments. Paired data on both chains of the heterodimeric receptor are particularly revealing since simultaneous near-coincidences are rare and we show how they can be exploited to estimate the number of epitope responses that created the memory compartment. In addition, we find that paired-chain coincidences are strongly suppressed across donors with different human leukocyte antigens, evidence for a central role of antigen-driven selection in making paired chain receptors public. These results demonstrate the power of coincidence analysis to reveal the sequence determinants of selection in receptor repertoires.

Which epitopes are recognized by a patient's T cells? The specificity of T cells is encoded genetically in the loci coding for the hypervariable loops of the T cell receptor (TCR) chains [1], and thus in principle reading out the immune repertoire by sequencing provides the information to answer this question [2–4]. Yet, deciphering the complex sequence 'code' for the many-to-many mapping between TCRs and peptide-major histocompability complexes (pMHCs) remains an open problem [5].

Aspects of this code are coming into view thanks to data from multiple experimental approaches. Structural studies have revealed the spatial arrangements in which TCRs bind pMHCs [6–11]. Mutagenesis experiments [12, 13] have provided early evidence that some amino acid substitutions in TCRs maintain or even increase binding affinity to a given epitope. Such local degeneracy of the binding code has been confirmed more recently by sequencing of epitope-specific groups of TCRs [14–21], and sequence patterns in these datasets are now used in machine learning approaches to predict further binders to the same epitope [22–26].

Direct experiment can, however, examine only a minute fraction of all the possible binding combinations, due to the enormous diversity of potential receptors and epitopes: more than 10^{12} different peptides [27] are presented on 1000s of human MHC alleles [28] to up to 10^{61} possible TCRs [29] generated by the recombination machinery. As a result, rules that generalize across epitopes would be of utmost utility, but TCR diversity has made it complicated to find common signatures of epitope-driven selection.

To address this problem, we here introduce a statistical framework that quantifies selection by comparing sequence coincidences in epitope-specific and background TCR repertoires. Our approach takes inspiration from population genetics, where selection is commonly detected by comparing the accumulation of non-synonymous and synonymous mutations [30]. Here, selection acts on the standing variation created by the TCR recombination process, but the coherence of selection on the amino-acid level similarly increases the probability with which T cell clonotypes defined by distinct nucleotide sequences share the same amino acid sequence. Generalizing the analysis to inexact coincidences (pairs of sequences with high sequence similarity), we find that they, too, are enhanced by epitope-driven selection. We demonstrate mathematically that the ratio of near-coincidence probabilities between data and background, as a function of sequence distance, is a direct measure for how selection is correlated across sequence space.

Applying this framework to epitope-specific T cell repertoires from multiple recent studies [14–17] reveals a common signature of selection across disparate experiments. We relate this signature to the existence of a typical average local binding degeneracy, defined as the fraction of the available sequence neighbors of a specific T cell that will also bind to the same pMHC. Interestingly, we find a weaker version of this signature in repertoires with paired sequencing of both TCR chains, which have not been subjected to *ex vivo* enrichment for epitope-specific T cells [31]. We exploit this observation in two ways: we provide clear evidence that this signature is associated with MHC presentation of antigen by demonstrating coincidences between different donors are strongly affected by their human leukocyte antigen (HLA) overlap; in addition, after some mathematical analysis, we use it to quantify the effective functional diversity of the memory repertoire, in the sense of an estimated number of epitope recognition events it records. Taken together, these results illustrate how coincidence analysis can help address questions that have so far remained elusive.

FIG. 1: **Patterns of sequence similarity within epitope-specific repertoires motivate using sequence (near-)coincidences as a diagnostic of selection.** (A) Sequence-similarity clustermap of TCRs binding to an Epstein-Barr Virus epitope as obtained by single cell TCR sequencing following tetramer sorting (Data: Dash et al. [14], antigen BMLF). Lower/upper triangle shows pairwise distances of CDR3α/CDR3β sequences. Sequences are ordered by average linkage hierarchical clustering based on summed $\alpha\beta$ distance. Columns on the left show subject of origin and cluster assignment; sequences not belonging to a cluster based on a cutoff distance of 6 are shown in black. (B) Sequence logos for two cluster of specific sequences. (C-E) Normalized coincidence frequency distributions of (C) CDR3β, (D) CDR3α, and (E) CDR3$\alpha\beta$ sequences specific to the epitope show vastly increased sequence similarity relative to background expectations.

I. OVERVIEW OF ANALYSIS STRATEGY

We illustrate our approach on a repertoire of CD8$^+$ T cells specific to an Epstein-Barr Virus peptide presented on HLA-A*02:01. The data is from Dash et al. [14] and was obtained using single cell receptor sequencing of tetramer-sorted T cells binding the specific pMHC.

Fig. 1A shows a clustering by pairwise sequence distance of all clones, a visualization we term a sequence-similarity clustermap. In this visualization, each position in the heatmap records the sequence distance Δ between the amino acid sequences of a pair of distinct T cell clones. TCRs are heterodimeric, and the heatmaps above(below) the diagonal record distances between the $\beta(\alpha)$ hypervariable complementary-determining region 3 (CDR3) loops of the sequence pair. Clustering is done on the sum of distances between α and β chains. Here, and throughout this work, we define sequence distances as the minimal

number of edits (insertions, deletion, or substitutions) that change one sequence into another, known as the Levenshtein distance. By clones we mean lineages of cells that go back to the same ancestral recombination event, which we define in practice based on nucleotide sequence identity. A zero distance pair arises when two distinct nucleotide sequences have the same amino acid translation, and so on. We chose to ignore the number of times a given nucleotide sequence is sampled, as clone sizes also reflect TCR-independent lineage differences [32, 33]. Instead, we analyze convergent selection imposed on distinct clones with the same or similar TCR as a stringent measure of epitope-driven functional selection.

Fig. 1A allows some direct conclusions about important features of TCR-pMHC binding code: First, it highlights the remarkable sequence similarity among specific TCRs and it shows that this similarity also holds for TCRs from different donors. Second, it shows that there are several clusters of sequences differing by a few substitutions, representing distinct broad "solutions" to this particular epitope recognition problem, plus a larger number of isolated solutions that differ from all other sequences by many substitutions. Fig. 1B shows the sequence logos of two prominent solutions, which interestingly are quite different from each other as sequences (and potentially also as structures). Third, it demonstrates that chain-pairing is biased even among specific binders as similarity on one chain is often associated with similarity on the other chain.

To compare statistics of sequence-similarity across epitope targets, we next compress the off-diagonal elements of the clustermap into a normalized pairwise distance histograms that we denote by $p_C(\Delta)$. Figs. 1C,D show the histograms for α and β chains, respectively. Fig 1E shows the histogram for the complete $\alpha\beta$-TCR, with paired chain sequence distance defined as the sum of distances of both chains. These normalized pairwise distance distributions are the basic element of our analysis framework. We also plot the $p_C(\Delta)$ distributions derived from bulk sequencing of a "background" sample as a proxy for the expected distribution prior to selection. We use sequencing data from Minervina et al. [16] of total peripheral blood mononuclear cells (PBMCs) from a healthy individual for these background curves for α and β chains. For the paired chain background curve we currently lack sufficiently deeply sequenced datasets. Fortunately, previous studies have concluded that α and β chain gene usages are largely uncorrelated [31, 34, 35], so we use the convolution of the α chain and β chain distributions as a plausible paired chain background prior to selection.

The central observation is that $p_C(\Delta)$ for the selected sequences is orders of magnitude larger than the corresponding background for small Δ. Exact coincidence frequencies are in excess by surprisingly large factors ($\sim 10^9$ and $\sim 10^4$ for paired and unpaired chains, respectively). This excess extends to near-coincidences, but interestingly, for large enough Δ, the selected and the background values of $p_C(\Delta)$ approach each other. The manner in which their ratio falls to unity will turn out to be roughly the same across different types of experiments, an intriguing fact that points to shared underlying biophysical rules of specific binding.

Given the diversity of TCRs it is surprising that we are able to find any coincidences in small epitope-specific repertoires. This is due to the stringent selection pressures as quantified by the increase of coincidences over background. Additionally, the occurrence of coincidences at sample sizes much smaller than the space of all sequences is connected to the "birthday problem" in probability theory [36, 37]: In a sample of N distinct sequences there are $N(N-1)/2$ distinct pairs, and the expected number of pairs at distance Δ is thus $p_C(\Delta)N(N-1)/2$. This means that we can estimate normalized pair probabilities $p_C(\Delta) \sim 10^{-3}$ using repertoires of only $N \sim 10^2$ sequences. This is fortunate since it is precisely this combination of orders of magnitude that we encounter when we estimate $p_C(\Delta)$ from epitope-specific repertoires at small values of Δ (Fig. 1C-E).

II. THEORY OF COINCIDENCE ANALYSIS

A. Definitions and statistical estimation

The T cell clones that enter the immune repertoire are drawn from a background distribution $P(\boldsymbol{\sigma})$ over all possible nucleotide sequences $\boldsymbol{\sigma}$ that code for the TCR hypervariable chains. This distribution summarizes the statistics of the recombination process by which the receptor coding genes are rearranged, and it is known that probabilities of individual sequences range over many orders of magnitude [38]. Experimentally, clones are identified by distinct nucleotide sequences, and coincidences (exact or near) are defined by the corresponding amino acid sequence (since that is what determines functional identity or similarity). Generation probabilities are such that it is unlikely that two separate T cell generation events will give the same nucleotide sequence, but it is less uncommon for them to give the same CDR3 amino acid sequence. Therefore the practical limitation of identifying clones by distinct nucleotide sequences instead of recombination events introduces only minimal bias. The normalized histogram of pairwise distances defined operationally in the previous section is then an empirical estimate of coincidence probabilities, more formally defined as

$$p_C[P](\Delta) = \sum_{\boldsymbol{\sigma},\boldsymbol{\sigma}'} P(\boldsymbol{\sigma})P(\boldsymbol{\sigma}')\boldsymbol{I}_{d(\boldsymbol{\sigma},\boldsymbol{\sigma}')=\Delta}, \qquad (1)$$

where $\boldsymbol{I}$ is the indicator function, the sum is over independent pairs of nucleotide sequences, and $d(\boldsymbol{\sigma},\boldsymbol{\sigma}')$ is the sequence distance between the amino acid translations of the sequences. We note that the $\Delta = 0$ value of the distribution defined in Eqn. 1 is a quantity known in the ecology literature as Simpson's diversity index [36]. As an example of its interpretation, if the population being observed

consists of S equally frequent species, the index equals $1/S$. It is a useful measure of diversity because it can be estimated simply and robustly by counting pairwise coincidences in draws from a population. In our application of this measure, amino acid receptor sequences take the role of species and since there is a natural measure of distance between sequences, it makes sense to also consider inexact coincidences up to varying sequence distances. A central point of this paper is that a great deal of information is contained in the generalization of Simpson's index to inexact coincidences.

B. Near coincidences increase under selection

We are interested in how coincidence probabilities change when an initial population of sequences is subsampled by a functional requirement, such as recognizing a particular peptide antigen. We analyze this as follows: let $Q(\boldsymbol{\sigma})$, normalized by $\langle Q(\boldsymbol{\sigma})\rangle_{P(\boldsymbol{\sigma})} = 1$, be the probability that a sequence $\boldsymbol{\sigma}$ will meet the chosen selection condition. The distribution of selected sequences is then $Q(\boldsymbol{\sigma})P(\boldsymbol{\sigma})$. As we derive in Appendix A the coincidence distributions of the two ensembles are related via the cross-moments of the selection factors,

$$\frac{p_C[QP](\Delta)}{p_C[P](\Delta)} = \langle Q(\boldsymbol{\sigma})Q(\boldsymbol{\sigma}')\rangle_{\boldsymbol{\sigma}\overset{\Delta}{\sim}\boldsymbol{\sigma}'}, \qquad (2)$$

where $\langle.\rangle_{\boldsymbol{\sigma}\overset{\Delta}{\sim}\boldsymbol{\sigma}'}$ indicates that the average is calculated over random pairs of sequences at distance Δ, i.e. over the distribution $P(\boldsymbol{\sigma},\boldsymbol{\sigma}'|d(\boldsymbol{\sigma},\boldsymbol{\sigma}') = \Delta)$.

To gain intuition we consider a simple class of selection functions of relevance to antigen-specific selection, where Q weights equally a specific subset $\mathcal{S}$ of sequences and gives zero weight to all others:

$$Q(\boldsymbol{\sigma}) = \boldsymbol{I}_{\mathcal{S}}(\boldsymbol{\sigma})/P(\mathcal{S}), \qquad (3)$$

where $P(\mathcal{S}) = \sum_{\boldsymbol{\sigma}\in\mathcal{S}} P(\boldsymbol{\sigma})$ is the fraction of all sequences that are selected. Given the statistical process that created the background repertoire, any given background sequence has an expected number of 'neighbors' at sequence distance Δ; if the sequence in question is selected, we can ask what fraction $f_{\boldsymbol{\sigma}}(\Delta)$ of its neighbors at distance Δ are also selected. Plugging Eqn. 3 into Eqn. 2 we find that the coincidence ratio is proportional to the average of that fraction over the selected sequences $\langle f_{\boldsymbol{\sigma}}(\Delta)\rangle_{\boldsymbol{\sigma}\in\mathcal{S}} = \langle \boldsymbol{I}_{\mathcal{S}}(\boldsymbol{\sigma}')\rangle_{\boldsymbol{\sigma}\overset{\Delta}{\sim}\boldsymbol{\sigma}',\boldsymbol{\sigma}\in\mathcal{S}}$:

$$\frac{p_C[QP](\Delta)}{p_C[P](\Delta)} = \frac{\langle f_{\boldsymbol{\sigma}}(\Delta)\rangle_{\boldsymbol{\sigma}\in\mathcal{S}}}{P(\mathcal{S})}. \qquad (4)$$

The meaning of this equation is explained graphically in Fig. 2A, where nodes represent distinct nucleotide rearrangements and links identify pairs that have the same amino acid translation. Two selection procedures from the background (Fig. 2A left) are shown: selecting 50% of nucleotide sequences (Fig. 2A middle) or selecting 50%

FIG. 2: **How selection increases coincidences.** (A) Illustration of how different selection procedures change the graph of sequence neighbors. Nucleotide sequences in a background graph (right) are connected by edges if the pair translates to the same amino acid sequence. Random sampling of nucleotide sequences (middle) does not change the coincidence probability. Random sampling of amino acid sequences (right) selects connected components of the graph and thus increases the coincidence probability. (B-D) Coincidence probabilities for synthetic data generated by selecting 1% of nucleotide sequences (B), 1% of amino acid sequences (C), and 1% of amino acid sequences and 10% of their neighbors (D) at random from a background CDR3β repertoire. The grey lines show estimates for 20 individual samples, and the blue line their average.

of amino acid sequences (Fig. 2A right). When selecting random nucleotide sequences neighbors of selected nodes are selected with the same probability as any other node, $\langle f_{\boldsymbol{\sigma}}(0)\rangle_{\boldsymbol{\sigma}\in\mathcal{S}} = P(\mathcal{S})$, and thus the coincidence probability remains unchanged according to Eqn. 4. Meanwhile when selecting amino acid sequences, linked clusters of clones are selected together, $\langle f_{\boldsymbol{\sigma}}(0)\rangle_{\boldsymbol{\sigma}\in\mathcal{S}} = 1$, and the coincidence probability increases (see [39] for a related

application of random amino acid selection to predict sharing numbers).

For antigen-specific selection the proportionality constant $1/P(\mathcal{S})$ is equal to the value of the coincidence ratio at $\Delta = 0$, as by assumption all nucleotide sequences coding for the same amino acid sequence are specific. If the selection fraction is small, the coincidence ratio is large, in line with the interpretation of this ratio as a measure of the strength of selection. What follows is a direct way to estimate the average number of specific neighbors:

$$\frac{p_C[QP](\Delta)}{p_C[P](\Delta)} = \frac{p_C[QP](0)}{p_C[P](0)} \, \langle f_{\boldsymbol{\sigma}}(\Delta) \rangle_{\boldsymbol{\sigma} \in S} \qquad (5)$$

How coincidence ratios decrease with distance Δ is thus a measure of the average sequence degeneracy of the selection process. Applying this equation to experimental data will allow us to estimate this fundamental quantity.

C. Numerical illustrations

We can illustrate the above-described effects of selection by taking random samples, according to several protocols, of an unselected dataset of approximately 10^5 CDR3β sequences taken from whole blood (data from [16]). We first compare selecting random nucleotide sequences (Fig. 2B) with selecting random amino acid sequences (Fig. 2C), in each instance selecting 1% of sequences. For random selection on nucleotide sequence, apart from statistical noise, $p_C(\Delta)$ is the same for the selected set and background. For random selection on amino acid sequence, we see that while the $\Delta \neq 0$ coincidence frequencies are still equivalent to background, the exact coincidence frequency increases hundredfold. This increase corresponds to the inverse of the selection fraction $P(\mathcal{S}) \sim 10^{-2}$, exactly as predicted by Eqn. 2.

Finally, we sought to incorporate sequence correlation in selection between similar amino acid sequences to model the local degeneracy in antigen recognition apparent in Fig. 1A. To this end, for each selected sequence $\boldsymbol{\sigma}$, we also select a fraction p_{corr} of sequences that are within sequence distance Δ_{corr} from $\boldsymbol{\sigma}$. The construction of such a sequence-correlated random selection model is somewhat subtle as a naive scheme oversamples sequences with many neighbors. We thus derived a corrected sampling scheme explained in Appendix D that overcomes this bias. The results of this selection procedure for $\Delta_{corr} = 1$ and $p_{corr} = 0.1$ are shown in Fig. 2D. As expected sequence correlations lead to an enhancement of $p_C(\Delta)$ over background that extends to near coincidences. Also, the selection enhancement ratio decreases by a factor of ~ 0.1 (the value of p_{corr}) between $\Delta = 0$ and $\Delta = 1$, in accord with Eqn. 5.

FIG. 3: **Excess coincidences follow a common functional form across experiments.** Sequence similarity of specific T cells for β-chain repertoires (top row), α-chain repertoires (middle row) and paired $\alpha\beta$-chain repertoires (lower row) compared with background expectations. In each panel the assay type and the antigen source are noted in the upper right. Panel H is special as analyzed TCRs are from unsorted blood and have not been explicitly selected for binding to a specific epitope. A common reference curve is plotted for visual guidance. Its parameter K is set equal to the empirical value at $\Delta = 0$. Z is determined by normalization. Datasets: A,D,F - Dash et al. [14]; B,E - Minervina et al. [16]; C - Nolan et al. [15]; G - Minervina et al. [17]; H - Tanno et al. [31].

III. COMMON FEATURES OF SELECTION ACROSS MULTIPLE DATASETS

We now use the lens of coincidence analysis to examine a broad set of experimental datasets that use different assays to select T cell repertoires specific to epitopes from different sources (details in Methods and Data) [14–17, 31]. Our analysis of these diverse datasets reveals striking similarities in the functional dependence of excess coincidences on sequence distance, along with large differences in overall selection strength (Fig. 3).

We first apply coincidence analysis to the single chain data from Nolan et al. [15] (Fig. 3B) and Minervina et al. [16] (Fig. 3C,E). Nolan et al. sequenced β-chain sequences of T cells selected (by passage through the MIRA pipeline [40]) for recognizing individual peptides in a broad panel of peptides from the SARS-Cov-2 genome, while Minervina et al. identified α and β chain sequences of T cells that responded dynamically during the SARS-Cov-2 infection of two human subjects using longitudinal sequencing. As a comparison we also analyze β (α) chain sequences from the Dash et al. [14] paired chain dataset across all three studied viral epitopes, ignoring the paired α (β) chain sequences (Fig. 3A,D). For each repertoire, we construct the normalized histogram $p_C(\Delta)$ of pairwise distances and take its ratio with $p_{C,back}(\Delta)$, the same statistic for background sequences. To smooth out variability, we then average over epitopes or subjects, respectively.

We next apply coincidence analysis to paired chain data from Dash et al. [14] (Fig. 3F), Minervina et al. [17] (Fig. 3G), and Tanno et al. [31] (Fig. 3H), taking the distance between two paired sequences to be the sum of distances between the two chains. Minervina et al. sequenced paired-chain $\alpha\beta$ TCRs that were determined by DNA-barcoded MHC dextramers to have specificity to chosen SARS-CoV-2 epitopes, while Tanno et al. provides a large dataset of paired-chain total T cell repertoires that have not been directly subjected to *ex vivo* selection. We compute the coincidence probability ratio $p_C(\Delta)/p_{C,back}(\Delta)$ against a synthetic background computationally constructed from single chain data under an independent pairing assumption, as described previously.

Together, these analyses show that across experiments and chains (Fig. 3 columns and rows respectively), the excess coincidence ratio $p_C(\Delta)/p_{C,back}(\Delta)$ declines with a similar exponential rate from its value at $\Delta = 0$ for small Δ. Additionally, across all datasets coincidences reduce to those of the background for distances substantially less than the mean sequence distance between background sequences. In other words, the statistical differences between selected repertoires and the background are limited to small sequence distances Δ. The orange curves plot a simple parametric function (specified in the legend) that captures the two key features: it interpolates between an initial exponential decrease by roughly one power of ten per unit increase in Δ and asymptotes to a constant. The parameter K is set to the value of excess coincidences at $\Delta = 0$, and the parameter Z is determined self-consistently by normalization. Without any additional fitting parameters the reference curve is in good agreement with the empirical data across all experiments, highlighting their similarity.

The exponential falloff for small Δ is a quantitative measure of binding degeneracy with respect to small sequence changes. According to Eqn. 5 the observed common falloff rate means that, on average, about one tenth of the $\Delta = 1$ sequence neighbors of a T cell that recognizes an epitope will also recognize the same epitope (and roughly one percent of the $\Delta = 2$ neighbors, etc).

FIG. 4: **Epitope binding restricts diversity of both chains individually, and also restricts their pairing.** Bar chart shows the decomposition of paired chain exact coincidence probability ratios (Fig. 3F) for individual epitopes in the Dash set into contributions from selection of β (Fig. 3A) and α chains (Fig. 3D) individually (blue,orange), plus a smaller contribution from restricting the pairing of the two chains (green).

This degree of sequence degeneracy is observed both for β-chains (Fig. 3A-C) and α-chains (Fig. 3D,E). The observation that this parameter agrees across experiments and chains is striking, and suggests it is a fundamental biophysical feature of TCR-pMHC binding interactions.

Epitope-specific repertoires sequenced at the paired-chain level can be used to quantify the relative contribution to binding specificity of the two chains. Figs. 3A,D show that there is, on average, a strong diversity restriction (as measured by excess coincidences) for both chains individually due to epitope selection. If the selected chains could be freely paired without affecting specificity, then the overall excess coincidence factor for paired chains would be the product of the factors for the individual chains (Appendix C). In fact, Fig. 3F shows that paired chain coincidences are more frequent than this expectation by perhaps as much as a factor 10 (out of an overall increase by a factor of $\sim 10^9$). For further insight, we repeated the analysis separately for each individual epitope (Fig. 4): the paired chain selection factor is in each instance the product of two large factors due to selection of the β and α chains individually times a smaller factor that arises from restricting pairing among the selected sets of chains, and there is only limited variation in the contributions of the three terms across epitopes. These results show why paired chain information is essential for accurately predicting the specificity of a TCR.

IV. A MIXTURE OF MOTIFS MODEL REPRODUCES THE SELECTION SIGNATURE

What does the dependence of coincidence probability ratios on distance tell us about the binding energy landscape for epitope recognition? As a first step towards

FIG. 5: **Coincidences in mixture of motifs model.** Coincidence probabilities (A) and coincidence probability ratios to background (B) for synthetic data generated from a mixture of motifs model with different numbers of motifs M and $c = 3$. These models show both an exponential falloff of $p_C/p_{C,back}$ for small Δ and that this quantity plateaus for large Δ for sufficiently large M (the key features of the empirical data in Fig. 3). Analytic expectations from Eqn. 9 (crosses in B) are in good agreement with the numerical simulation results.

answering this question we introduce a schematic binding energy model for TCR-pMHC interactions. Our goal at this stage is not to explain the phenomenon in detail, but rather to demonstrate general properties of the binding energy that can give rise to the observed signature of epitope-driven selection.

In our schematic model we describe the interaction of a TCR with its complementary pMHC as a string-matching problem [41, 42]. For simplicity we consider synthetic TCR sequences $\boldsymbol{\sigma}$ of a fixed length $k = 6$, corresponding to the number of hypervariable residues within a typical CDR3 loop. For a particular pMHC complex p, we assume that the binding energy depends on the residues within the TCR additively, and that each site makes a binary contribution to the energy:

$$E_p(\boldsymbol{\sigma}) = \sum_{i=1}^{k} \epsilon_p(i, \sigma_i), \quad \epsilon_p(i, \sigma_i) = \begin{cases} -1 & \text{for } \sigma_i \in \mathcal{S}_i^p \\ 0, & \text{otherwise.} \end{cases}$$
(6)

Here, for each site, $\mathcal{S}_i^p$ is a set of "good" amino acids that contribute to the binding of sequence $\boldsymbol{\sigma}$ to epitope p. A sequence is taken to bind only if $E_p(\boldsymbol{\sigma}) = -k$, that is to say that the amino acid at each site i is in the allowed set $\mathcal{S}_i^p$. This definition of binding energy describes a random motif model, where a motif is defined as any combination of allowed amino acids at the different sites. The motif of course will vary from one epitope to another.

As in our model TCRs have fixed length we consider the simpler Hamming distance instead of edit distance, and we make two further assumptions to simplify analytical calculations: First, at each site there are an equal number c of allowed amino acids, $\forall i : |\mathcal{S}_i| = c$. Second, background sequences are drawn from the flat distribution

over all k-mers: at each site we draw independently and uniformly at random one out of the $q = 20$ amino acids. Calculating the near-coincidence histograms within the background set and within the specific set for a particular epitope then reduces to purely combinatorial exercise with the analytical results

$$p_C(\Delta) = \frac{1}{c^k} \binom{k}{\Delta} (c-1)^{\Delta} \quad \text{for} \quad \Delta = 0 \ldots k$$
$$p_{C,back}(\Delta) = \frac{1}{q^k} \binom{k}{\Delta} (q-1)^{\Delta} \quad \text{for} \quad \Delta = 0 \ldots k.$$
(7)

The near-coincidence enhancement factor in this model is therefore

$$\frac{p_C(\Delta)}{p_{C,back}(\Delta)} = \left(\frac{c-1}{q-1} \right)^{\Delta} \left(\frac{q}{c} \right)^{k}.$$
(8)

This expression reproduces the exponential falloff with Δ that is seen in real data, with the falloff rate dependent on the number of allowed amino acids c. To make the rate compatible with the observed factors of ten, requires that at each site there are on average $c = 3$ possible amino acids, such that the fraction of specific neighboring sequences is equal to $(c-1)/(q-1) = 2/19 \approx 0.1$.

However, this model does not capture the second observation in the empirical data, namely, that beyond a certain sequence distance Δ, the enhancement ratio asymptotes to a constant, indicating that the near-coincidence statistics of the epitope-selected repertoire become similar to those of the background. To address this, we recall that Fig. 1 strongly suggests that there are multiple "solutions" to the problem of recognizing a given epitope, and we thus extend our binding model to incorporate this idea. For each epitope, we let there be M randomly chosen motifs, each defining a different binding energy function as per Eqn. 6 with independently drawn sets of allowed amino acids $\mathcal{S}_i^p$ for each of the M recognition "solutions". The binding energy of a TCR sequence is then taken to be the minimum over these motifs. The distribution of T cells selected by this binding energy can be approximated as a mixture of the distributions selected by the individual motifs. Applying results for coincidences in mixture distributions (derived in Appendix B), we obtain an analytical prediction for excess coincidences

$$\frac{p_C(\Delta)}{p_{C,back}(\Delta)} \approx \frac{1}{M} \left(\frac{c-1}{q-1} \right)^{\Delta} \left(\frac{q}{c} \right)^{k} + 1 - \frac{1}{M}.$$
(9)

We also performed a direct simulation to confirm this analytic result: we generated a large background repertoire of k-mers with a common, quasi-realistic, frequency of amino acid choices at each site; we also randomly generated M motifs, each one of which is a list of k-mers that are 'recognized' by the motif (generated according to the rules described above); the selected sequences are then defined to be the background sequences that appear in the full list of motif sequences. The results of the analytic calculation and the simulation, calculated using the

FIG. 6: **Comparison of near-coincidence probabilities across paired-chain datasets.** The highest values come from TCR repertoires specific to individual epitopes (solid orange curve: average over epitopes studied in Dash et al. [14] and Minervina et al. [17]). Paired-chain sequencing of whole blood (green), sorted CD4$^+$ memory (dashed red) and CD4$^+$ naive (purple) repertoires (data averaged over subjects from Tanno et al. [31]) give much smaller values. Background coincidence probabilities (calculated assuming independent chain pairing) are shown in blue. See text for discussion of the large difference in coincidence probabilities between repertoires.

same parameters, are perfectly consistent (Fig. 5). The key point is that, for multiple motifs, the ratio $p_C/p_{C,back}$ asymptotes to a constant (close to unity) as Δ approaches the maximum possible value in this setup, $\Delta = 6$. The mixture of motifs models thus reproduces both salient features of the selection signatures in the empirical data.

V. FUNCTIONAL DIVERSITY LINKS COINCIDENCES ACROSS SCALES

We now revisit the intriguing observation of a selection-like signature in paired chain sequencing data from whole blood (specifically, the coincidence enhancement displayed in Fig. 3H). In Fig. 6 we compare coincidence frequencies obtained from direct paired chain sequencing of blood samples with coincidence frequencies among multimer-sorted T cells that recognize individual epitopes. We note that coincidences within multimer-sorted repertoires exceed those in blood samples by four orders of magnitude. Also, the comparison with sorted memory and naive repertoires shows that coincidences in the total repertoire are primarily driven by memory cells. Bearing in mind that the whole blood coincidence analysis compares sequences within and between all the memory sub-compartments created by past infections, we hypothesize that the coincidences in whole blood reflect high-levels of sequence similarity among groups of memory cells selected in response

to specific epitopes encountered in the past. Intuitively, we then expect coincidences in whole blood to depend on the diversity of the memory repertoire, i.e. on how many different epitope exposures the immune system is remembering. To make this intuition quantitative we develop a mathematical formalism to predict coincidences in mixture distributions.

We propose to model TCRs in an individual's memory compartment as a mixture distribution over the set $\mathbf{\Pi}$ of peptide-MHC complexes (pMHCs) that have driven past immune responses in that individual. For each $\boldsymbol{\pi} \in \mathbf{\Pi}$, there is a distribution of T cell sequences $P(\boldsymbol{\sigma}|\boldsymbol{\pi})$ that target $\boldsymbol{\pi}$. The distribution of TCRs in the memory compartment will then be the mixture distribution

$$P(\boldsymbol{\sigma}) = \sum_{\boldsymbol{\pi} \in \mathbf{\Pi}} P(\boldsymbol{\sigma}|\boldsymbol{\pi})P(\boldsymbol{\pi}), \tag{10}$$

where $P(\boldsymbol{\pi})$ is the proportion of all TCRs selected for binding to pMHC $\boldsymbol{\pi}$. The coincidence probability for mixtures can be calculated using the following mixture decomposition theorem, which we derive in Appendix B:

$$\begin{aligned} p_C[P(\boldsymbol{\sigma})] = {} & p_C[P(\boldsymbol{\pi})] \langle p_C[P(\boldsymbol{\sigma}|\boldsymbol{\pi})] \rangle \\ & + (1 - p_C[P(\boldsymbol{\pi})]) \langle p_C[P(\boldsymbol{\sigma}|\boldsymbol{\pi}_1), P(\boldsymbol{\sigma}|\boldsymbol{\pi}_2)] \rangle, \end{aligned} \tag{11}$$

where the averages are over $P(\boldsymbol{\pi}|\boldsymbol{\pi}_1 = \boldsymbol{\pi}_2 = \boldsymbol{\pi})$ and $P(\boldsymbol{\pi}_1, \boldsymbol{\pi}_2|\boldsymbol{\pi}_1 \neq \boldsymbol{\pi}_2)$, respectively. It is noteworthy that we were able to derive this exact decomposition of coincidence probabilities in mixtures. For example, no equivalent formula exists for Shannon entropy, an alternative measure of diversity, which has led to long-lasting debates within ecology about the decomposition of diversity in pooled communities [43, 44].

Eqn. 11 is a sum of two non-negative terms, each of which can be given an intuitive interpretation. To develop this intuition we note that the probability of coincidence can be calculated as the average probability with which two randomly chosen sequences $\boldsymbol{\sigma}_1$ and $\boldsymbol{\sigma}_2$ coincide, $p_C[P(\boldsymbol{\sigma})] = \sum_{\boldsymbol{\sigma}_1, \boldsymbol{\sigma}_2} P(\boldsymbol{\sigma}_1)P(\boldsymbol{\sigma}_2)\delta_{\boldsymbol{\sigma}_1, \boldsymbol{\sigma}_2}$. This probability can be decomposed by conditioning on mixture identity for $\boldsymbol{\sigma}_1$ and $\boldsymbol{\sigma}_2$: The overall probability of coincidence is then a weighted mean of average within-group coincidence probabilities (first term) and of average between-group coincidence probabilities (second term). The relative weight given to within group comparisons is precisely given by the probability with which two randomly chosen elements come from the same group, i.e. the coincidence probability of the group assignments $p_C[P(\boldsymbol{\pi})]$.

Multimer sorting followed by sequencing gives draws from $P(\boldsymbol{\sigma}|\boldsymbol{\pi})$ for specific pMHCs $\boldsymbol{\pi}$ [14, 17], and this data can be used to estimate the average within-epitope-group exact coincidence probability $p_C[P(\boldsymbol{\sigma}|\boldsymbol{\pi})]$. Absent better information, we shall assume that the average value $p_C[P(\boldsymbol{\sigma}|\boldsymbol{\pi})] \sim 10^{-4}$ in these experiments is the typical order of magnitude for all epitopes. We further assume that the between-epitope-group term in Eqn. 11 is negligible. Then the only remaining quantity is $p_C[P(\boldsymbol{\pi})]$,

the Simpson diversity of the set of epitope-specific groups within the repertoire. Putting the numbers together we obtain an effective diversity $1/p_C[P(\pi)] \sim 10^4$, a not implausible value for the pMHC diversity of a memory compartment.

In other words, the large ratio between coincidence frequencies in a repertoire selected *ex vivo* by an individual pMHC complex and the coincidence frequencies in the memory compartment as a whole is informative about the number of epitope recognition events that created the memory compartment in the first place. While the precise numbers are likely to change as more comprehensive data becomes available, the calculation above gives a clear recipe to settle the question of how functionally diverse our immune repertoire is. More broadly, mixture averaging also likely explains why coincidence probabilities among longitudinally identified TCRs (presumably specific to multiple immunodominant epitopes) are lower than among TCRs specific to individual epitopes (Fig. 3 B,E vs. Fig. 3 A,C,D).

VI. HLA OVERLAP DETERMINES COINCIDENCES BETWEEN DONORS

How many TCRs are shared between donors? In previous studies of T cell repertoires, there has been much interest in such shared sequences, on the grounds that such 'public' sequences may point towards common pathogen exposures [39, 45]. Since in order to mount a common response to a pathogen epitope, two subjects must not only share (up to near-coincidence) T cells with the same TCR, but must also share an MHC molecule on which the epitope can be presented, we expect more T cell sharing between donors that share HLA alleles. In line with this expectation, Tanno et al. [31] observed an association between exact sharing of paired $\alpha\beta$ TCRs and the number of shared HLA alleles. By our logic, it makes sense to broaden the definition of public T cells to those that are nearly coincident across donors, and present at rates well above an appropriately estimated background. We will thus revisit the analysis by Tanno and co-workers by applying our coincidence analysis framework to their dataset. Specifically, we calculate the histogram of sequence distances between TCRs drawn from pairs of repertoires, and ask how the strength of any selection signal depends on the similarity of HLA type between the two repertoires.

We grouped subject pairs by HLA overlap defined as $J = |A \cap B| / \max(|A|, |B|)$, where A and B are the sets of HLA alleles in the two subjects. The overlap ranges between $J = 1$ for identical twins, to $J = 0$ if there is no common HLA allele. We also applied additional filtering steps to control for confounding factors (Appendix E). We eliminated exact nucleotide sequence coincidences on either chain in inter-sample comparisons to mimic the filtering we applied to intra-sample analyses, and as in twin pairs such coincidences can reflect long-lived clones of shared ancestry that result from shared blood

supply during fetal development [46, 47]. Additionally, we removed sequences whose VJα genes match those of two non-canonical T cell subsets that recognize non-peptide ligands not presented on classical MHC [48].

The results of the analysis are shown in Fig. 7: Near-coincidence probabilities between whole blood repertoires decrease systematically with decreasing HLA overlap (Fig. 7B), and the same trend holds in sorted CD4$^+$ memory (Fig. 7B) and CD4$^+$ naive cells (Fig. 7C). These HLA-dependent effects are large: exact coincidence probabilities range over two orders of magnitude as HLA overlap varies. This contrasts with prior studies that have found only a small influence of HLA type in single chain repertoires [49]. The interpretation suggested by our earlier analysis (Fig. 4) is that HLA binding requires specific pairs of α and β chains. To confirm that our observed large effect sizes are compatible with weak signals in single chain repertoires, we constructed synthetic distributions for randomized $\alpha\beta$ pairings by convolving the single chain distance distributions within HLA overlap groups. The results are shown as dashed lines in Fig. 7 (using the same color coding for the HLA overlap groups as for the real data). They reveal that single chain coincidences are almost independent of HLA overlap, even though this procedure retains the correlations between individual chains and HLA type.

The comparison of coincidence probabilities between these different ways of filtering and segregating the data is informative about how different mechanisms might contribute to chain pairing biases. First, Fig. 7C shows no significant deviations from pairing independence (dashed lines in the figure) across naive cells from non-twin donors. This limits the strength of chain pairing correlations that might arise through pMHC-independent processes, such as VDJ recombination, or from steric and biophysical constraints between chains for protein folding [34, 35]. We note that this finding validates the use of the independent chain pairing assumption for generating background distributions representative of repertoire statistics before selection has acted. Second, Fig. 7C also shows a clear signal of correlated chain pairing in naive cells both intra-sample (black line) and across twin pairs (blue line). This strongly suggests that thymic positive and negative selection substantially contribute to the pairing biases. Third, Fig. 7B shows that within the memory repertoire coincidences between twins occur at remarkably similar rates to the intra-sample coincidence rates, which suggests that memory selection is driven by prevalent pMHCs encountered by both donors (herpesviruses are one potential source of such pMHCs [50]). Alternatively, sequences binding a certain HLA might generally show substantially restricted pairing independently of which peptide is presented [51, 52] – something we will soon be able to test as more epitope-specific repertoires for different peptides presented on the same MHC are characterized. In summary, HLA-dependent selection leads to major biases in the pairing of TCR α and β chains at the repertoire level, the outcome of a combination of thymic and peripheral

FIG. 7: **Inter-subject coincidences depend on HLA overlap.** Pairwise inter-dataset coincidence frequency analysis for the 15 paired-seq datasets from Tanno et al. [31] grouped by pairwise HLA overlap. A: pairs of unsorted PBMC repertoires; B: pairs of CD4$^+$ memory repertoires; C: pairs of CD4$^+$ naive repertoires. Each plot shows means over pairs whose HLA overlap lies within the indicated ranges together with estimated standard errors assuming Poisson sampling. For comparison, the mean intra-dataset coincidence distribution is shown in black. Background distributions constructed by scrambling the α and β chain associations within individuals are shown as dashed curves (colored according to the same HLA overlap code). These curves show no near-coincidence enhancement signal and very weak dependence on HLA overlap class.

selection pressures. As dataset sizes continue to increase, the strategy we have described here provides a strategy for untangling these pressures in detail.

VII. DISCUSSION

In this work we have introduced a versatile statistical framework for measuring selection in T cell receptor repertoires. Simply put, we have evidence of selection if the number of exactly (and nearly exactly) coincident receptor sequence pairs in a repertoire is substantially larger than the number that one would find in a reference repertoire. Importantly, we showed that this intuitive notion can be developed into a mathematical theory relating the number of excess coincidences to quantities of direct immunological interest, such as the extent of sequence degeneracy of T cell binding to particular epitopes, or the functional diversity of an individual's memory repertoire.

We take a probabilistic approach to selection, where each target epitope defines a probability distribution on the unselected, or naive, T cells that make up the immune repertoire. Experiments that query blood samples for binding to a specific pMHC represent a draw from this probability distribution, and experiments that capture T cell responses to multiple targets sample a mixture of distributions over targets. Certain global quantities of immunological interest are averages over these distributions and, in our approach, the experimental data serve to give empirical estimates of these averages. We highlight two salient examples:

First, we quantify the fraction of sequence neighbors of a typical specific sequence that share the same specificity. Our analysis predicts that when varying single amino acids in the hypervariable regions in accord with the TCR generative statistics, roughly one out of ten such changes lead to a receptor that still binds the same target. Across disparate datasets this measure of local recognition degeneracy shows remarkable consistency. We envisage that it can be used to guide bioinformatic clustering methods for finding groups of T cells with common specificity [14, 19, 53], for instance to put data-driven constraints on threshold choices. Importantly, the predicted level of local degeneracy is in rough accord with measured distributions of binding affinity changes between point-mutated TCRs [54, 55], and can be systematically tested in future experiments generating libraries of point mutated TCRs and measuring their binding affinity after expression in cell lines. With the rapid increase in the number of assayed epitopes, another area for future work will be to characterize in detail variation around the average selection strength and binding degeneracy, including for example between TCRs binding MHC-I or MHC-II (most data analyzed in the current study relates to MHC-I binding).

Second, we provided a recipe to quantify the functional diversity of a T cell compartment, as measured by the number of different epitopes that have selected the T cells comprising the compartment. From paired-chain sequencing data on human blood samples [31] we derived a rough estimate of the functional diversity of a typical memory compartment. This coarse-grained functional diversity is orders of magnitude smaller than TCR sequence diversity, which is consistent with the relatively small number of immunodominant epitopes typically targeted in response to

individual pathogen infections [56] and theoretical predictions that adaptive immunity learns sparse features of the epitope distribution [57]. Additionally, cumulative coincidence probabilities at different sequence distances should provide a useful measure of repertoire diversity weighted by sequence similarity, a subject of recent interest in the field [55, 58, 59].

Beyond the quantification of functional diversity our analysis of deeply sequenced paired chain repertoires across individuals suggests additional research directions. We identify a substantial number of TCR specificity groups that the data suggest are in large parts driven by common epitopes across individuals. Guided by such TCR groups it would be interesting to generalize the recently proposed reverse epitope discovery approach [60, 61] to the repertoire scale: cross-referencing coincident TCRs with other data, such as TCR-epitope databases [20, 62] and computationally predicted HLA binding of putative peptides, might guide the identification of the targets of these groups of T cells. More broadly, as dataset sizes increase an analysis of the dependence of cross-donor coincidence probabilities on which HLAs the two donors share could allow an unbiased apportionment of the immune repertoire selected by different HLA types.

In summary, our results reveal both complexity and predictability in the immune receptor code. The emerging picture is captured schematically in the mixture of motifs model that we have introduced: Epitope-specific repertoires are characterized by globally diverse binding solutions that sometimes share surprisingly little sequence similarity, but also display remarkably consistent signatures of local degeneracy. This picture, if further confirmed in structural studies [8, 9], can help focus future machine learning efforts in this area. The consistent signal of local degeneracy suggests that a promising direction will be to use machine learning to refine metrics, such as TCRdist [14, 53], that can group TCRs specific to a common target within large mixtures. Our framework should be of use in such efforts, as it can readily turn any definition of TCR similarity, not just the simple edit distance we have considered here, into probabilities of shared specificity. The existence of multiple binding solutions, on the other hand, might explain why purely sequence-based models for computationally predicting binding partners of epitopes (i.e. in the absence of any experimentally determined binders) have had limited success [23], and why structural modeling might be needed to resolve the complex sequence determinants of the different binding solutions [63].

Methods and Data

In this paper, we analyze datasets that represent significantly different approaches, both conceptual and experimental, to creating functionally selected T cell repertoires. They are succinctly described as follows:

The Dash dataset [14] is based on tetramer sorting of CD8$^+$ T cells from blood, using three well-studied standard viral epitopes (HLA-A*02:01-BMLF1$_{280}$ (BMLF), HLA-B*07:02-pp65$_{495}$ (pp65), and HLA-A*02:01-M1$_{58}$ (M1)), followed by single-cell TCR sequencing to obtain paired TCRα and TCRβ reads of the captured cells. This protocol was repeated for 32 donors, resulting in a list of 415 paired $\alpha\beta$ TCRs associated with the three epitopes.

The Minervina 2022 dataset [17] uses DNA-barcoded MHC dextramers to identify T cells specific to 19 SARS-CoV-2 epitopes by sequencing. T cells were identified across a cohort of donors with a varied history of SARS-CoV-2 exposure and vaccination. We focused our analysis on the 8 epitopes for which there are at least 150 characterized $\alpha\beta$ TCRs each.

The Nolan dataset [15] is obtained by sorting about 3×10^7 T cells from a subject blood sample, then incubating the sorted cells with a cocktail of several hundred SARS-CoV-2 epitopes (chosen for their broad MHC presentability) to uniformly expand clones that recognize any of these epitopes. In a next step, aliquots of the expansion product are incubated with individual epitopes from the cocktail, followed by TCRβ sequencing to identify T cells that have expanded in this second step in response to individual epitopes. This yields a list of TCRβ clonotypes that recognize the epitope. This protocol is repeated for blood samples from about a hundred subjects, about a third of whom have had no known exposure to SARS-CoV-2 ("healthy" subjects). Summing over subject samples for each epitope, we get a list of a few tens to a few thousand clonotypes that recognize a given epitope. All told, the dataset is a list of some 10^5 TCRβ recombination events that respond to individual SARS-CoV-2 epitopes. We note that the α chains associated with each β chain are not known, and also that a given epitope may be presented on different MHC molecules in different individuals. To have adequate statistical power, we consider only epitopes from Nolan et al. [15] which are recognized by at least 150 distinct clones and we restrict our analysis to MHC-I epitopes.

The Minervina 2021 dataset [16] is based on a longitudinal study of TCRβ sequences in the blood of two unrelated subjects who contracted mild COVID-19. Analysis of time-separated samples allowed the identification of T cell clones, whose clone sizes changed significantly in response to infection. We focus on the several hundred CD8$^+$ clones, whose size decreased between the peak immune response at 15 days and a post-infection time point at 85 days. The specific epitopes to which these T cells respond are unknown, but they are presumably a subset of the SARS-CoV-2 viral epitopes that provoke the strongest immune response, and therefore constitute an interesting "selected" subset of the T cell repertoire.

The Tanno dataset [31] consists of paired-chain TCRs from a total of fifteen donors, including six pairs of twins. The mean number of reads is about 31,000 (minimum of 7400 and maximum of 69000). For three pairs of twins and three unrelated donors total PBMC samples were sequenced. Sorted CD4$^+$ naive (CD45RA$^+$, CCR7$^+$) and

memory (CD45RA$^-$) cells were sequenced for three additional twin pairs. All fifteen subjects were HLA typed on the allele level. We used processed data as described in the original study but applied additional filtering steps, the rationale for which is described in Appendix E. For the naive repertoire we also removed any overlap with clonotypes that were also found within the memory repertoire from the same individual. To compare coincidence frequencies across repertoires from different individuals (Fig. 7) we sum the number of coincidences across all comparisons within an HLA overlap bin. We add a pseudocount of 0.1 to the summed counts for visualization purposes, and we display Poisson errorbars as $\sqrt{c}/c_{tot}$ where c is the count at a specific distance and c_{tot} the sum of all counts across distances. These errorbars represent lower bounds, as in addition to counting error there is heterogeneity between individuals.

For all datasets, we filtered out clones whose CDR3 amino acid sequence did not start with the conserved cysteine (C), or end on phenylalanine (F), tryptophan (W), or cysteine (C).

Acknowledgements. We are grateful to Yuval Elhanati and Léo Régnier for previous collaboration on the sequence space structure of T cell repertoires, unpublished work that was essential to the development of the ideas underlying the current work. We thank Hidetaka Tanno for providing processed data files and Giulio Isacchini for helpful discussions. The work of AM was supported by a Lewis-Sigler felloship; the work of CC was supported in part by NSF grants PHY-1607612 and PHY-1734030. CC is grateful to the Institute for Advanced Study and the École normale supérieure, Paris, for hospitality during parts of the research reported here.

Author contributions and competing interests. CC and AM conceived research, performed analysis, and wrote the paper. CC and AM declare no competing interests.

[1] M. M. Davis and P. J. Bjorkman, Nature **334**, 395 (1988).

[2] H. S. Robins, P. V. Campregher, S. K. Srivastava, A. Wacher, C. J. Turtle, O. Kahsai, S. R. Riddell, E. H. Warren, and C. S. Carlson, Blood **114**, 4099 (2009).

[3] R. O. Emerson, W. S. DeWitt, M. Vignali, J. Gravley, J. K. Hu, E. J. Osborne, C. Desmarais, M. Klinger, C. S. Carlson, J. A. Hansen, et al., Nature Genetics **49**, 659 (2017).

[4] J. M. Heather, M. Ismail, T. Oakes, and B. Chain, Briefings in Bioinformatics **19**, 554 (2017).

[5] P. Bradley and P. G. Thomas, Annual Review of Immunology **37**, 547 (2019).

[6] K. C. Garcia, M. Degano, R. L. Stanfield, A. Brunmark, M. R. Jackson, P. A. Peterson, L. Teyton, and I. A. Wilson, Science **274**, 209 (1996).

[7] M. G. Rudolph, R. L. Stanfield, and I. A. Wilson, Annual Review Of Immunology **24**, 419 (2006).

[8] J. Rossjohn, S. Gras, J. J. Miles, S. J. Turner, D. I. Godfrey, and J. McCluskey, Annual Review of Immunology **33**, 169 (2015).

[9] I. Song, A. Gil, R. Mishra, D. Ghersi, L. K. Selin, and L. J. Stern, Nature Structural & Molecular Biology **24**, 395 (2017).

[10] C. H. Coles, R. M. Mulvaney, S. Malla, A. Walker, K. J. Smith, A. Lloyd, K. L. Lowe, M. L. McCully, R. Martinez Hague, M. Aleksic, et al., The Journal of Immunology **204**, 1943 (2020).

[11] P. Zareie, C. Szeto, C. Farenc, S. D. Gunasinghe, E. M. Kolawole, A. Nguyen, C. Blyth, X. Y. Sng, J. Li, C. M. Jones, et al., Science **372**, eabe9124 (2021).

[12] P. D. Holler, P. O. Holman, E. V. Shusta, S. O. Herrin, K. D. Wittrup, and D. M. Kranz, PNAS **97**, 5387 (2000).

[13] Y. Li, R. Moysey, P. E. Molloy, A.-l. Vuidepot, T. Mahon, E. Baston, S. Dunn, N. Liddy, J. Jacob, B. K. Jakobsen, et al., Nature Biotechnology **23**, 349 (2005).

[14] P. Dash, A. J. Fiore-Gartland, T. Hertz, G. C. Wang, S. Sharma, A. Souquette, J. C. Crawford, E. B. Clemens, T. H. Nguyen, K. Kedzierska, et al., Nature **547**, 89 (2017).

[15] S. Nolan, M. Vignali, M. Klinger, J. N. Dines, I. M. Kaplan, T. Craft, K. Boland, M. Mazza, and K. Dobbs, Research Square Preprint (2020).

[16] A. A. Minervina, E. A. Komech, A. Titov, M. B. Koraichi, E. Rosati, I. Z. Mamedov, A. Franke, G. A. Efimov, D. M. Chudakov, T. Mora, et al., eLife **10**, e63502 (2021).

[17] A. A. Minervina, M. V. Pogorelyy, A. M. Kirk, J. C. Crawford, E. K. Allen, C. H. Chou, R. C. Mettelman, K. J. Allison, C. Y. Lin, D. C. Brice, et al., Nature Immunology **23**, 781 (2022).

[18] P. Bacher, E. Rosati, D. Esser, P. Koehler, A. Franke, and A. Scheffold, Immunity **53**, 1258 (2020).

[19] J. Glanville, H. Huang, A. Nau, O. Hatton, L. E. Wagar, F. Rubelt, X. Ji, A. Han, S. M. Krams, C. Pettus, et al., Nature **547**, 94 (2017).

[20] M. Shugay, D. V. Bagaev, I. V. Zvyagin, R. M. Vroomans, J. C. Crawford, G. Dolton, E. A. Komech, A. L. Sycheva, A. E. Koneva, E. S. Egorov, et al., Nucleic Acids Research **46**, D419 (2017).

[21] H. Huang, C. Wang, F. Rubelt, T. J. Scriba, and M. M. Davis, Nature Biotechnology **38**, 1194 (2020).

[22] S. Gielis, P. Moris, W. Bittremieux, N. De Neuter, B. Ogunjimi, K. Laukens, and P. Meysman, Frontiers in Immunology **10**, 2820 (2019).

[23] D. S. Fischer, Y. Wu, B. Schubert, and F. J. Theis, Molecular Systems Biology **16**, e9416 (2020).

[24] W. Zhang, P. G. Hawkins, J. He, N. T. Gupta, J. Liu, G. Choonoo, S. W. Jeong, C. R. Chen, A. Dhanik, M. Dillon, et al., Science Advances **7**, eabf5835 (2021).

[25] A. Montemurro, V. Schuster, H. R. Povlsen, A. K. Bentzen, V. Jurtz, W. D. Chronister, A. Crinklaw, S. R. Hadrup, O. Winther, B. Peters, et al., Communications Biology **4**, 1060 (2021).

[26] B. Bravi, V. P. Balachandran, B. D. Greenbaum, A. M. Walczak, T. Mora, R. Monasson, and S. Cocco, PLoS Computational Biology **17**, e1009297 (2021).

[27] A. K. Sewell, Nature Reviews Immunology **12**, 669 (2012).

[28] J. Robinson, J. A. Halliwell, J. D. Hayhurst, P. Flicek, P. Parham, and S. G. Marsh, Nucleic Acids Research **43**,

D423 (2015).

[29] T. Mora and A. Walczak, in *Systems Immunology*, edited by J. Das and C. Jayaprakash (CRC Press, 2019), chap. 11.

[30] Z. Yang and J. R. Bielawski, Trends in Ecology and Evolution **15**, 496 (2000).

[31] H. Tanno, T. M. Gould, J. R. Mcdaniel, W. Cao, Y. Tanno, and R. E. Durrett, Proceedings of the National Academy of Sciences **117**, 532 (2020).

[32] V. R. Buchholz, M. Flossdorf, I. Hensel, L. Kretschmer, B. Weissbrich, P. Gräf, A. Verschoor, M. Schiemann, T. Höfer, and D. H. Busch, Science **340**, 630 (2013).

[33] C. Gerlach, J. C. Rohr, L. Perié, N. Van Rooij, J. W. Van Heijst, A. Velds, J. Urbanus, S. H. Naik, H. Jacobs, J. B. Beltman, et al., Science **340**, 635 (2013).

[34] T. Dupic, Q. Marcou, A. M. Walczak, and T. Mora, PLoS Computational Biology **15**, e1006874 (2019).

[35] D. S. Shcherbinin, V. A. Belousov, and M. Shugay, PLoS Computational Biology **16**, e1007714 (2020).

[36] E. H. Simpson, Nature **163**, 688 (1949).

[37] T. S. Nunnikhoven, American Statistician **46**, 270 (1992).

[38] A. Murugan, T. Mora, A. M. Walczak, and C. G. Callan, Proceedings of the National Academy of Sciences **109**, 16161 (2012).

[39] Y. Elhanati, Z. Sethna, C. G. Callan, T. Mora, and A. M. Walczak, Immunological Reviews **284**, 167 (2018).

[40] M. Klinger, F. Pepin, J. Wilkins, T. Asbury, T. Wittkop, J. Zheng, M. Moorhead, and M. Faham, Plos One **10**, e0141561 (2015).

[41] J. D. Farmer, N. H. Packard, and A. S. Perelson, Physica D: Nonlinear Phenomena **22**, 187 (1986).

[42] A. Kosmrlj, A. K. Jha, E. S. Huseby, M. Kardar, and A. K. Chakraborty, Proceedings of the National Academy of Sciences **105**, 16671 (2008).

[43] L. Jost, *Entropy and diversity* (2006).

[44] A. Chao, N. J. Gotelli, T. C. Hsieh, E. L. Sander, K. H. Ma, R. K. Colwell, and A. M. Ellison, Ecological Monographs **84**, 45 (2014).

[45] V. Venturi, D. a. Price, D. C. Douek, and M. P. Davenport, Nature Reviews Immunology **8**, 231 (2008).

[46] M. V. Pogorelyy, Y. Elhanati, Q. Marcou, A. L. Sycheva, E. A. Komech, V. I. Nazarov, O. V. Britanova, D. M. Chudakov, I. Z. Mamedov, Y. B. Lebedev, et al., PLoS Computational Biology **13**, e1005572 (2017).

[47] M. U. Gaimann, M. Nguyen, J. Desponds, and A. Mayer, eLife **9**, e61639 (2020).

[48] D. I. Godfrey, A. P. Uldrich, J. Mccluskey, J. Rossjohn, and D. B. Moody, Nature Immunology **16** (2015).

[49] S. A. Johnson, S. L. Seale, R. M. Gittelman, J. A. Rytlewski, H. S. Robins, and P. A. Fields, PLoS ONE **16**, 1 (2021).

[50] G. J. Xu, T. Kula, Q. Xu, M. Z. Li, S. D. Vernon, T. Ndung'u, K. Ruxrungtham, J. Sanchez, C. Brander, R. T. Chung, et al., Science **348**, aaa0698 (2015).

[51] N. L. L. Gruta, S. Gras, S. R. Daley, P. G. Thomas, and J. Rossjohn, Nature Reviews Immunology 2018 p. 1 (2018).

[52] J. A. Carter, J. B. Preall, K. Grigaityte, S. J. Goldfless, E. Jeffery, A. W. Briggs, F. Vigneault, and G. S. Atwal, Frontiers in Immunology **10**, 1 (2019).

[53] K. Mayer-Blackwell, S. Schattgen, L. Cohen, J. C. Crawford, A. Souquette, J. A. Gaevert, T. Hertz, P. G. Thomas, P. Bradley, and A. Fiore, eLife **10**, e68605 (2021).

[54] J. Jankauskaite, B. Jiménez-García, J. Dapkunas, J. Fernández-Recio, and I. H. Moal, Bioinformatics **35**, 462 (2019).

[55] R. Arora, H. M. Burke, and R. Arnaout, bioRxiv preprint 483131 (2018).

[56] A. Cassotta, P. Paparoditis, R. Geiger, R. R. Mettu, S. J. Landry, A. Donati, M. Benevento, M. Foglierini, D. J. Lewis, A. Lanzavecchia, et al., Journal of Experimental Medicine **217**, e20200206 (2020).

[57] A. Mayer, V. Balasubramanian, A. M. Walczak, and T. Mora, Proceedings of the National Academy of Sciences **116**, 8815 (2019).

[58] T. Leinster and C. A. Cobbold, Ecology **93**, 477 (2012).

[59] M. Vujović, P. Marcatili, B. Chain, J. Kaplinsky, and T. Andresen, bioRxiv Preprint 2021.01.11.417444v2 (2021).

[60] P. A. Mudd, A. A. Minervina, M. V. Pogorelyy, J. S. Turner, W. Kim, E. Kalaidina, J. Petersen, A. J. Schmitz, T. Lei, A. Haile, et al., Cell **185**, 603 (2022).

[61] M. V. Pogorelyy, E. Rosati, A. A. Minervina, R. C. Mettelman, A. Scheffold, A. Franke, P. Bacher, and P. G. Thomas, Cell Reports Medicine p. 100697 (2022).

[62] N. Tickotsky, T. Sagiv, J. Prilusky, E. Shifrut, and N. Friedman, Bioinformatics **33**, 2924 (2017).

[63] K. K. Jensen, V. Rantos, E. C. Jappe, T. H. Olsen, M. C. Jespersen, V. Jurtz, L. E. Jessen, E. Lanzarotti, S. Mahajan, B. Peters, et al., Scientific Reports **9**, 1 (2019).

[64] Z. Sethna, G. Isacchini, T. Dupic, T. Mora, M. Walczak, and Y. Elhanati, PLoS Computational Biology **16**, e1008394 (2020).

Appendix A: Formal treatment of effect of selection on coincidence statistics

1. Coincidence changes are related to the cross-moments of the selection factors

We are interested in how the probability of coincidences changes as we modify a base measure $P(\boldsymbol{\sigma})$ with a weighting function $Q(\boldsymbol{\sigma})$ that represents the effect of selection according to

$$\tilde{P}(\boldsymbol{\sigma}) = Q(\boldsymbol{\sigma})P(\boldsymbol{\sigma}), \tag{A1}$$

with $\langle Q(\boldsymbol{\sigma})\rangle_{P(\boldsymbol{\sigma})} = 1$ for normalization. Plugging in $\tilde{P}$ into the definition of the near-coincidence probability, we have

$$p_C[\tilde{P}](\Delta) = \sum_{\boldsymbol{\sigma},\boldsymbol{\sigma}'} P(\boldsymbol{\sigma})P(\boldsymbol{\sigma}')Q(\boldsymbol{\sigma})Q(\boldsymbol{\sigma}')I_{d(\boldsymbol{\sigma},\boldsymbol{\sigma}')=\Delta}. \tag{A2}$$

This expression can be rewritten formally as an average over randomly picked pairs of sequences,

$$p_C[\tilde{P}](\Delta) = \langle Q(\boldsymbol{\sigma})Q(\boldsymbol{\sigma}')\boldsymbol{I}_{d(\boldsymbol{\sigma},\boldsymbol{\sigma}')=\Delta}\rangle_{P(\boldsymbol{\sigma},\boldsymbol{\sigma}')}, \tag{A3}$$

where $P(\boldsymbol{\sigma},\boldsymbol{\sigma}') = P(\boldsymbol{\sigma})P(\boldsymbol{\sigma}')$. Only pairs that are at distance Δ contribute to the average, which suggests restricting the average to these pairs. When conditioning on pairs of sequences at distance Δ, the conditional probability of sequences $\boldsymbol{\sigma},\boldsymbol{\sigma}'$ reads

$$P(\boldsymbol{\sigma},\boldsymbol{\sigma}'|d(\boldsymbol{\sigma},\boldsymbol{\sigma}') = \Delta) = \frac{P(\boldsymbol{\sigma},\boldsymbol{\sigma}')I_{d(\boldsymbol{\sigma},\boldsymbol{\sigma}')=\Delta}}{P(d(\tilde{\boldsymbol{\sigma}},\tilde{\boldsymbol{\sigma}}') = \Delta)}, \tag{A4}$$

where $P(d(\tilde{\boldsymbol{\sigma}},\tilde{\boldsymbol{\sigma}}') = \Delta) = \langle \boldsymbol{I}_{d(\tilde{\boldsymbol{\sigma}},\tilde{\boldsymbol{\sigma}}')=\Delta}\rangle_{P(\tilde{\boldsymbol{\sigma}},\tilde{\boldsymbol{\sigma}}')} = p_C[P](\Delta)$ is the near-coincidence probability in the unselected set. The probability of coincidence thus changes upon selection according to

$$p_C[\tilde{P}](\Delta) = \langle Q(\boldsymbol{\sigma})Q(\boldsymbol{\sigma}')\rangle_{P(\boldsymbol{\sigma},\boldsymbol{\sigma}'|d(\boldsymbol{\sigma},\boldsymbol{\sigma}')=\Delta)}\, p_C[P](\Delta), \tag{A5}$$

which completes the derivation of Eqn. 2 in the main text.

2. Relation to the covariance of selection factors

To gain intuition into Eqn. 2 we can rewrite the first factor on the left hand side in terms of the covariance of selection factors. In general, $\mathrm{Cov}(X,Y) = \langle XY\rangle - \langle X\rangle\langle Y\rangle$. Thus

$$\langle Q(\boldsymbol{\sigma})Q(\boldsymbol{\sigma}')\rangle = \mathrm{Cov}(Q(\boldsymbol{\sigma}),Q(\boldsymbol{\sigma}')) + \langle Q(\boldsymbol{\sigma})\rangle^2, \tag{A6}$$

where the covariance is calculated across random pairs at distance Δ, $P(\boldsymbol{\sigma},\boldsymbol{\sigma}'|d(\boldsymbol{\sigma},\boldsymbol{\sigma}') = \Delta)$, and the average across the marginal distribution, $\sum_{\boldsymbol{\sigma}'} P(\boldsymbol{\sigma},\boldsymbol{\sigma}'|d(\boldsymbol{\sigma},\boldsymbol{\sigma}') = \Delta)$. The normalization of $\tilde{P}$ implies $\langle Q(\boldsymbol{\sigma})\rangle_{P(\boldsymbol{\sigma})} = 1$, hence

$$p_C[\tilde{P}](\Delta) = (\mathrm{Cov}(Q(\boldsymbol{\sigma}),Q(\boldsymbol{\sigma}')) + 1)\, p_C[P](\Delta) \tag{A7}$$

when the average of $Q(\boldsymbol{\sigma})$ over the marginal distribution can be approximated by its simple average over $P(\boldsymbol{\sigma})$.

To derive the condition for which Eqn. A7 is exact, we define the local neighbor density around a sequence $\boldsymbol{\sigma}$,

$$n_{\boldsymbol{\sigma}}(\Delta) = \sum_{\boldsymbol{\sigma}'} P(\boldsymbol{\sigma}')I_{d(\boldsymbol{\sigma},\boldsymbol{\sigma}')=\Delta}. \tag{A8}$$

Using this definition we can write

$$\langle Q(\boldsymbol{\sigma})\rangle_{P(\boldsymbol{\sigma},\boldsymbol{\sigma}'|d(\boldsymbol{\sigma},\boldsymbol{\sigma}')=\Delta)} = \left\langle Q(\sigma)\sum_{\boldsymbol{\sigma}'} P(\boldsymbol{\sigma}')I_{d(\boldsymbol{\sigma},\boldsymbol{\sigma}')=\Delta}/p_C[P](\Delta)\right\rangle_{P(\boldsymbol{\sigma})} = \langle Q(\sigma)n_{\boldsymbol{\sigma}}(\Delta)\rangle_{P(\boldsymbol{\sigma})}\,/\,p_c[P](\Delta). \tag{A9}$$

When the probability of selecting a sequence is uncorrelated with its neighbor density, we have

$$\langle Q(\sigma)n_{\boldsymbol{\sigma}}(\Delta)\rangle_{P(\boldsymbol{\sigma})} = \langle Q(\sigma)\rangle_{P(\boldsymbol{\sigma})}\langle n_{\boldsymbol{\sigma}}(\Delta)\rangle_{P(\boldsymbol{\sigma})} = \langle Q(\sigma)\rangle_{P(\boldsymbol{\sigma})}p_C[P](\Delta), \tag{A10}$$

and thus the averages are the same, $\langle Q(\boldsymbol{\sigma})\rangle_{P(\boldsymbol{\sigma},\boldsymbol{\sigma}'|d(\boldsymbol{\sigma},\boldsymbol{\sigma}')=\Delta)} = \langle Q(\sigma)\rangle_{P(\boldsymbol{\sigma})}$, and Eqn. A7 is exact.

Appendix B: Decomposing coincidences in mixtures

Here we give the formal derivation of Eqn. 11 in the text which describes a situation where the underlying distribution on sequences is a mixture of distributions, each one describing the sequences selected by a particular antigen (or peptide-MHC complex). As discussed in the text, this is a way to describe the memory compartment of the immune system, or the set of TCRs selected by a peptide pool. We define the mixture distribution as

$$P(\boldsymbol{\sigma}) = \sum_{\boldsymbol{\pi} \in \Pi} P(\boldsymbol{\sigma}|\boldsymbol{\pi})P(\boldsymbol{\pi}), \tag{B1}$$

where $P(\boldsymbol{\pi})$ are the mixtures weights with $\sum_{\boldsymbol{\pi}} P(\boldsymbol{\pi}) = 1$. The coincidence probability is given by

$$p_C[P(\boldsymbol{\sigma})] = \sum_{\boldsymbol{\sigma}} \left(\sum_{\boldsymbol{\pi}} P(\boldsymbol{\sigma}|\boldsymbol{\pi})P(\boldsymbol{\pi}) \right)^2, \tag{B2}$$

$$= \sum_{\boldsymbol{\pi}} P(\boldsymbol{\pi})^2 \sum_{\boldsymbol{\sigma}} P(\boldsymbol{\sigma}|\boldsymbol{\pi})^2 + \sum_{\boldsymbol{\pi}_1 \neq \boldsymbol{\pi}_2} P(\boldsymbol{\pi}_1)P(\boldsymbol{\pi}_2) \sum_{\boldsymbol{\sigma}} P(\boldsymbol{\sigma}|\boldsymbol{\pi}_1)P(\boldsymbol{\sigma}|\boldsymbol{\pi}_2). \tag{B3}$$

To proceed let us define the generalized coincidence probability for two probability distributions as

$$p_C[P_i(\boldsymbol{\sigma}), P_j(\boldsymbol{\sigma})] = \sum_{\boldsymbol{\sigma}} P_i(\boldsymbol{\sigma})P_j(\boldsymbol{\sigma}). \tag{B4}$$

We can then rewrite the coincidence probability in the following form

$$p_C[P(\boldsymbol{\sigma})] = \sum_{\boldsymbol{\pi}} P(\boldsymbol{\pi})^2 p_C[P(\boldsymbol{\sigma}|\boldsymbol{\pi})] + \sum_{\boldsymbol{\pi}_1 \neq \boldsymbol{\pi}_2} P(\boldsymbol{\pi}_1)P(\boldsymbol{\pi}_2)p_C[P(\boldsymbol{\sigma}|\boldsymbol{\pi}_1), P(\boldsymbol{\sigma}|\boldsymbol{\pi}_2)]. \tag{B5}$$

We further note

$$P(\boldsymbol{\pi}_1, \boldsymbol{\pi}_2|\boldsymbol{\pi}_1 \neq \boldsymbol{\pi}_2) = \frac{P(\boldsymbol{\pi}_1)P(\boldsymbol{\pi}_2)}{1 - p_C[P(\boldsymbol{\pi})]}, \tag{B6}$$

and

$$P(\boldsymbol{\pi}|\boldsymbol{\pi}_1 = \boldsymbol{\pi}_2 = \boldsymbol{\pi}) = \frac{P(\boldsymbol{\pi})^2}{p_C[P(\boldsymbol{\pi})]}. \tag{B7}$$

Putting it all together we obtain the following decomposition of the total coincidence probability:

$$p_C[P(\boldsymbol{\sigma})] = p_C[P(\boldsymbol{\pi})] \langle p_C[P(\boldsymbol{\sigma}|\boldsymbol{\pi})] \rangle_{P(\boldsymbol{\pi}|\boldsymbol{\pi}_1 = \boldsymbol{\pi}_2 = \boldsymbol{\pi})} + (1 - p_C[P(\boldsymbol{\pi})]) \langle p_C[P(\boldsymbol{\sigma}|\boldsymbol{\pi}_1), P(\boldsymbol{\sigma}|\boldsymbol{\pi}_2)] \rangle_{P(\boldsymbol{\pi}_1, \boldsymbol{\pi}_2|\boldsymbol{\pi}_1 \neq \boldsymbol{\pi}_2)} \tag{B8}$$

This equation has an intuitive interpretation. The overall probability of coincidence is a weighted average of average within group coincidence probabilities (first term) and average between group coincidence probabilities (second term). The relative weight given to within group comparisons is precisely given by the probability with which two randomly chosen elements come from the same group, i.e. the coincidence probability of the group assignments $p_C[P(\boldsymbol{\pi})]$.

Appendix C: Decomposing selection on paired chain data

How does selection on the heterodimeric TCR protein restrict diversity on the two constituent chains? To answer this question we start by introducing some notation. The complete clone $\boldsymbol{\sigma}$ is defined by both its α chain sequence, which we denote $\boldsymbol{\sigma}_\alpha$, and its β chain sequence, which we denote $\boldsymbol{\sigma}_\beta$. We define the set of all complete TCRs that bind a specific epitope $\mathcal{S}$, such that $\boldsymbol{\sigma} \in \mathcal{S}$ implies the specificity of the receptor encoded by the nucleotide sequence $\boldsymbol{\sigma}$. The overall selection factor is then equal to

$$Q(\boldsymbol{\sigma}) = \frac{1}{p(\mathcal{S})} \boldsymbol{I}_{\mathcal{S}}(\boldsymbol{\sigma}), \tag{C1}$$

and the exact coincidences in the paired chain data are enriched by a factor $\chi_{\alpha\beta}$,

$$\chi_{\alpha\beta} = \frac{p_C[Q(\boldsymbol{\sigma})P(\boldsymbol{\sigma})](0)}{p_{C,back}[P(\boldsymbol{\sigma})](0)} = \frac{1}{p(\mathcal{S})}. \tag{C2}$$

In the following we will ask how this ratio relates to the same ratios calculated for the individuals chains, this is to

$$\chi_\alpha = \frac{p_C[Q(\boldsymbol{\sigma}_\alpha)P(\boldsymbol{\sigma}_\alpha)](0)}{p_{C,back}[P(\boldsymbol{\sigma}_\alpha)](0)}, \quad \chi_\beta = \frac{p_C[Q(\boldsymbol{\sigma}_\beta)P(\boldsymbol{\sigma}_\beta)](0)}{p_{C,back}[P(\boldsymbol{\sigma}_\beta)](0)}, \tag{C3}$$

where we will assume independent chain pairing in the background $P(\boldsymbol{\sigma}) = P(\boldsymbol{\sigma}_\alpha)P(\boldsymbol{\sigma}_\beta)$.

Given the full model the selection coefficients for single chains are marginalized averages over all possible choices for the second chain. To calculate these we can rearrange terms in the definition of the marginal single chain post-selection distributions:

$$\tilde{P}(\boldsymbol{\sigma}_\alpha) = \sum_{\boldsymbol{\sigma}_\beta} Q(\boldsymbol{\sigma})P(\boldsymbol{\sigma}) \tag{C4}$$

$$= P(\boldsymbol{\sigma}_\alpha) \sum_{\boldsymbol{\sigma}_\beta} \frac{\boldsymbol{I}_{\mathcal{S}}(\boldsymbol{\sigma}_\alpha, \boldsymbol{\sigma}_\beta)}{P(\mathcal{S})} P(\boldsymbol{\sigma}_\beta), \tag{C5}$$

from which we read off

$$Q(\boldsymbol{\sigma}_\alpha) = \frac{\langle \boldsymbol{I}_{\mathcal{S}}(\boldsymbol{\sigma}_\alpha, \boldsymbol{\sigma}_\beta) \rangle_{P(\boldsymbol{\sigma}_\beta)}}{P(\mathcal{S})}. \tag{C6}$$

Importantly, we show in the following that $\chi_{\alpha\beta} = \chi_\alpha\chi_\beta$, when there are no chain pairing biases within the epitope-specific set of sequences. To start, note that the set of specific $\alpha\beta$ sequences is given by the cartesian product

$$\mathcal{S} = \mathcal{S}_\alpha \times \mathcal{S}_\beta, \tag{C7}$$

of the single chain sets

$$\mathcal{S}_\alpha = \{\boldsymbol{\sigma}_\alpha : \exists \boldsymbol{\sigma}_\beta : (\boldsymbol{\sigma}_\alpha, \boldsymbol{\sigma}_\beta) \in \mathcal{S}\}, \quad \mathcal{S}_\beta = \{\boldsymbol{\sigma}_\beta : \exists \boldsymbol{\sigma}_\alpha : (\boldsymbol{\sigma}_\alpha, \boldsymbol{\sigma}_\beta) \in \mathcal{S}\}, \tag{C8}$$

which are composed of all chains that when paired with any of the opposite chains are specific. From these definitions it follows that

$$P(\mathcal{S}) = P(\mathcal{S}_\alpha)P(\mathcal{S}_\beta). \tag{C9}$$

Furthermore some algebra shows

$$Q(\boldsymbol{\sigma}_\alpha) = \frac{\boldsymbol{I}_{\mathcal{S}_\alpha}(\boldsymbol{\sigma}_\alpha)}{P(\mathcal{S}_\alpha)}, \quad Q(\boldsymbol{\sigma}_\beta) = \frac{\boldsymbol{I}_{\mathcal{S}_\beta}(\boldsymbol{\sigma}_\beta)}{P(\mathcal{S}_\beta)}. \tag{C10}$$

and thus

$$\chi_\alpha = \frac{1}{P(\mathcal{S}_\alpha)}, \quad \chi_\beta = \frac{1}{P(\mathcal{S}_\beta)}. \tag{C11}$$

Combining this result with Eqn. C9 we complete the derivation of the equality

$$\chi_{\alpha\beta} = \chi_\alpha\chi_\beta \tag{C12}$$

In the general case, the set $\mathcal{S}$ of all specific sequences is a proper subset of the cartesian product $\mathcal{S}_\alpha \times \mathcal{S}_\beta$, and thus $P(\mathcal{S}) < P(\mathcal{S}_\alpha)P(\mathcal{S}_\beta)$. We thus expect the coincidence ratio for the paired chain receptors to increase. This motivates using the ratio

$$\frac{\chi_{\alpha\beta}}{\chi_\alpha\chi_\beta} \tag{C13}$$

as a measure of pairing biases among the specific receptor chains.

Appendix D: Random models of sequence-correlated selection

In the main text we defined a simple random model of sequence-correlated selection on a background repertoire of recombination events (or clones) by a notional epitope as follows: choose at random a fraction (1% in the examples studied) of the CDR3 amino acid sequences that appear in this background and declare that any recombination event with a CDR3 amino acid sequence included in this list is 'selected'; in addition, let a random fraction (10% in the examples that follow) of all background events with CDR3 amino acid sequence lying at Levenshtein distance one from an element of the selected list be declared to be selected as well. This procedure is motivated by the observation that systematic studies of T cell selection by individual epitopes show a) the existence of multiple unrelated 'solutions' in sequence space to the problem of binding a specific epitope, and b) the existence of some degree of sequence degeneracy within individual binding solutions.

This protocol will bias selection toward sequences that have more than the average number of near neighbors in sequence space. While there is nothing wrong in principle with this, systematic studies of selection by multiple epitopes (such as [15]) show little if any such bias. This motivates us to modify the basic random selection procedure to make the probability of selecting a given background sequence independent of the number of its neighbors in sequence space. In what follows, we approximately solve a simplified version of this problem using the language of random graphs, and use that solution to propose a modification of the sequence-correlated random selection algorithm. We then show by concrete example that this modification achieves the desired result in the more demanding context of selection from realistic T cell sequence ensembles.

1. Mathematical analysis of the two-step selection algorithm

Consider the following random graph problem: we have a set of N nodes, with links between the nodes defined by an adjacency matrix A_{ij} where $A_{ij} = 1$ if node i and j are connected by an edge, and $A_{ij} = 0$ otherwise. The nodes represent amino acid sequences in a background repertoire, and links connect sequence distance one sequence neighbors. We define a 'selected' subgraph by assigning Ising variables s_i to each node to indicate whether the node is selected ($s_i = 1$) or not ($s_i = 0$). Our goal is to find a way of choosing the s_i such that a specified fraction of the nodes have $s_i = 1$ and the probability that a particular node i is selected is independent of the number of links that node participates in. Thus the selected subgraph inherits a subset of the nodes i of the original graph and its adjacency matrix is the projection of A_{ij} on the surviving nodes (no new nodes are created).

We define a two step selection process: We first select a fraction $q_1 \ll 1$ of the nodes and we then select a fraction q_2 (typically $q_2 \gg q_1$) of the links that connect a selected node to one that was not selected; when such a link is selected, we add the originally unselected node to which it connects to the list of selected nodes (i.e. we capture some of the neighbors of a selected node). We take η_i (θ_{ij}) as independent binary random variables (0 or 1) that describe which nodes (links) are picked during the first (second) step of the selection procedure, respectively and have averages q_1 (q_2) respectively.

The variable s_i that indicates whether a given node was picked in either of the two steps can be written as

$$s_i = \eta_i + (1 - \eta_i) \min \left[\sum_{j \neq i} A_{ij} \theta_{ij} \eta_j, 1 \right],$$
(D1)

The min function in the second term accounts for the possibility of multiple selection of the unselected node i in the link selection step. In practice, this occurs very rarely for the values of the parameters $q_{1,2}$ that are of interest to us. We will thus ignore this non-linearity in what follows for tractability. We can calculate various marginals and correlations involving the s_i by averaging over the independent, uncorrelated, binary variables η_i and θ_{ij}. Doing so, we find

$$\langle s_i \rangle = \langle \eta_i \rangle + (1 - \langle \eta_i \rangle) \sum_{j \neq i} A_{ij} \langle \theta_{ij} \rangle \langle \eta_j \rangle,$$
(D2)

$$\langle s_i s_j \rangle = \langle \eta_i \rangle \langle \eta_j \rangle + (1 - \langle \eta_i \rangle) \sum_{k \neq i} A_{ik} \langle \theta_{ik} \rangle \langle \eta_k \eta_j \rangle + (1 - \langle \eta_j \rangle) \sum_{l \neq j} A_{jl} \langle \theta_{jl} \rangle \langle \eta_l \eta_i \rangle$$
$$+ (1 - \langle \eta_i \rangle)(1 - \langle \eta_j \rangle) \sum_{k,l \neq i,j} A_{ik} A_{jl} \langle \theta_{ik} \rangle \langle \theta_{jl} \rangle \langle \eta_k \eta_l \rangle.$$
(D3)

For $i \neq j$, η_i and η_j are statistically independent by assumption and, because η_i is binary, $\eta_i^2 = \eta_i$. This yields the identity

$$\langle \eta_i \eta_j \rangle = (1 - \delta_{ij})\langle \eta_i \rangle \langle \eta_j \rangle + \delta_{ij}\langle \eta_i \rangle, \tag{D4}$$

which we can use to simplify the equation for the joint selection probability of a pair of nodes as follows:

$$
\begin{aligned}
\langle s_i s_j \rangle = &\langle \eta_i \rangle \langle \eta_j \rangle \\
&+ (1 - \langle \eta_i \rangle)\langle \eta_j \rangle A_{ij}\langle \theta_{ij} \rangle \\
&+ (1 - \langle \eta_i \rangle)\langle \eta_j \rangle \sum_{k \neq i,j} A_{ik}\langle \theta_{ik} \rangle \langle \eta_k \rangle \\
&+ (1 - \langle \eta_j \rangle)\langle \eta_i \rangle A_{ji}\langle \theta_{ji} \rangle \\
&+ (1 - \langle \eta_j \rangle)\langle \eta_i \rangle \sum_{l \neq i,j} A_{jl}\langle \theta_{jl} \rangle \langle \eta_l \rangle \\
&+ (1 - \langle \eta_i \rangle)(1 - \langle \eta_j \rangle) \sum_{k \neq i,j} A_{ik}A_{jk}\langle \theta_{ik} \rangle \langle \theta_{jk} \rangle \langle \eta_k \rangle \\
&+ (1 - \langle \eta_i \rangle)(1 - \langle \eta_j \rangle) \sum_{k \neq l \neq i,j} A_{ik}A_{jl}\langle \theta_{ik} \rangle \langle \theta_{jl} \rangle \langle \eta_k \rangle \langle \eta_l \rangle.
\end{aligned}
\tag{D5}
$$

Let us use these expressions to analyze the naive algorithm for sequence-correlated random selection that was described at the beginning of this appendix. In this scheme $\forall i : \langle \eta_i \rangle = q_1 \ll 1$ and $\forall i,j : \langle \theta_{ij} \rangle = q_2 \ll 1$. Importantly, for nodes i, j connected by an edge (so that $A_{ij} = 1$), the leading order terms in the above expression for $\langle s_i s_j \rangle$ give, for $q_1 \ll q_2$ (the case of interest):

$$\langle s_i s_j \rangle \approx \langle \eta_j \rangle \langle \theta_{ij} \rangle + \langle \eta_i \rangle \langle \theta_{ji} \rangle = 2q_1 q_2. \tag{D6}$$

In other words, the procedure allows us to enhance the probability of picking adjacent vertices beyond the independent probability q_1^2 of picking two isolated vertices.

However, as mentioned above, this procedure introduces a bias towards sampling highly connected sequences. More precisely, according to Eqn. D2

$$\langle s_i \rangle = q_1 + (1 - q_1)q_1 q_2 N_i \quad \text{with } N_i = \sum_{j \neq i} A_{ij} \tag{D7}$$

where N_i is the number of edges connecting to the i-th vertex: the more connected nodes i will have higher probability of being selected. The idea of the corrected procedure is to make the selection probability in the first step dependent on the neighbor number: $\langle \eta_i \rangle = q_1(N_i)$ where $q_1(N)$ is a function to be determined. The probability with which node i is selected in this procedure can be expressed as

$$\langle s_i \rangle = q_1(N_i) + (1 - q_1(N_i))q_2 N_i \left(\frac{1}{N_i} \sum_{j \neq i} A_{ij} q_1(N_j) \right), \tag{D8}$$

where the term within brackets is the average first step selection probability of all neighboring sequences connected to i by a link. To derive an appropriate functional form for $q_1(N_i)$ we make the further assumption that neighboring nodes have the same number of edges on average, so that $\frac{1}{N_i} \sum_{j \neq i} A_{ij} q_1(N_j) \approx q_1(N_i)$. One can than show that the choice of

$$q_1(N_i) = \frac{q_1}{1 + q_2 N_i}, \tag{D9}$$

leads to an approximately constant probability of selection, $\langle s_i \rangle \approx q_1$, independent of i, if $q_1 \ll 1$.

2. Numerical tests of the corrected algorithm

How well does proposed neighbor-number corrected selection algorithm works on realistic T cell sequence data? We have applied the algorithm described in the previous paragraphs to background repertoires of approximately 10^5 sequences of naive CD8$^+$ T cells obtained from a human subject (part of the immuneCODE dataset [15]). We

FIG. 8: Assessment of the uniformity of random selection from background sequence repertoires across groups of sequences classified by different numbers of Levenshtein distance one neighbors. The plot shows the fraction of each class in the background repertoire that appears in the selected repertoire, averaged over 100 realizations of the selection algorithm.

generated 100 selected repertoires of $\sim 10^3$ sequences from this background using the neighbor number corrected algorithm. In this background repertoire, the average number of distance-one neighbors of a sequence is close to three and the variance is very large. This analysis is thus a good test for how well the corrected selection algorithm succeeds in equalizing selection probability for nodes with different numbers of neighbors.

In Fig. 8 we plot the probability of selection of a recombination event from the background repertoire, averaged over 100 realizations of the algorithm. We use a fixed selection parameter $q_1 = .01$ and neighbor selection parameters q_2 ranging from 0.0 to 0.1. We plot the selection fraction as a function of the number of distance one neighbors the selected node has in the background repertoire. The net selection probability except for fluctuations is nearly constant out to neighbor number of ~ 10, a value that captures 90% of the nodes in the background.

It is instructive to display the near-coincidence frequency distributions that result from the corrected selection algorithm for different values of q_2 (Fig. 9). As expected from Eqn. 5 the rate of falloff of the coincidence frequency enhancement over background at small sequence distance Δ depends on the parameter q_2 that governs the fraction of the neighbors of a selected sequence that will also be selected.

FIG. 9: Coincidence frequency distributions for different realizations of the neighbor-corrected random selection algorithm. The black lines give the results of individual random realizations of selection, while the blue curves give averages over the full set of 100 realizations. The key feature to note is the inverse correlation between q_2, the parameter governing the sequence neighbor selection probability, and the initial slope of the log ratio of near-coincidence frequencies to background.

FIG. 10: **Rationale for collapsing α chains paired with multiple β chains in the paired chain data from Tanno et al. [31].** (A) The ratio between nucleotide and amino acid coincidence probabilities for α chains is calulcated for each subject and for data generated from SONIA, a model of VDJ recombination and thymic selection. The ratio is at least two-fold higher in the data than expected suggesting substantial cross-contamination. (B) Collapsing redundant alpha chains reduces variation in amino acid coincidence probabilities across samples and makes them more comparable to those found in bulk single chain datasets (donors M and W at baseline from Minervina et al. [16]).

Appendix E: Analysis of paired chain sequencing data from Tanno et al.

In the following we describe some observations about the nature of sequence coincidences in the paired chain sequencing data from Tanno et al. [31], that have prompted us to perform further filtering steps beyond the analysis pipeline proposed in the previous work.

The experimental protocol uses overlap extension polymerase chain reaction to link both α and β hypervariable chains before sequencing. Linking predominantly occurs between mRNA from the same single cell as those are captured on the same bead. However, cross-contamination can lead to erroneous pairing of mRNA from different cells. To reduce cross-contamination the authors clustered CDR3β on 95% sequence identity (for typical sequence lengths this is ≤ 2 nts), and kept only the most frequent CDR3α sequence from each cluster. No such clustering had been performed for CDR3α, and we thus asked to what extent contamination accounts for CDR3α sequences associated with multiple CDR3β sequences. To assess this we calculated the ratio between CDR3α coincidence probabilities on the nucleotide and amino acid level (Fig. 10A). As a comparison we calculated the same ratio for sequences generated using a probabilistic model of VDJ recombination [64] and found that ratios greatly exceed expectations. This finding suggests substantial cross-contamination that might impact downstream analysis. We thus implemented a filtering step clustering CDR3α sequences with exact sequencing identity, and kept only the most frequent CDR3β sequence from each cluster. Such filtering substantially reduces coincidence probabilities bringing them closer in line with those observed in a bulk-sequenced α chain repertoire dataset (Fig. 10B). Additionally variability across subjects is also reduced, suggesting different levels of cross-contamination across samples.

We next asked whether there was anything special about coincidences observed among pairs of subjects with the lowest HLA overlap. On examining the specific sequences responsible for exact coincidences in these pairs, we found that certain VJ combinations were heavily overrepresented among their α chains. These VJ combinations map to known signatures of noncanonical T cells with semi-invariant receptors, so called MAIT and iNKT cells [48]. These T cells have semi-invariant α-chains and restricted β chain diversity, which explains why they contribute heavily to near-coincidences. Both T cell subsets bind to non-peptide ligands, which are not presented on MHC molecules. As we are interested in identifying signatures of selection driven by pMHC binding, we exclude the VJα combinations coding for these invariant T cells (TRAV1-2 paired with TRAJ12/TRAJ20/TRAJ33 for MAITs, and TRAV10 paired with TRAJ18 for iNKTs).

While these additional filtering steps have a numerically small effect on the total numbers of near-coincidences, we believe that this careful approach is warranted as some of the most interesting comparisons rest on the small numbers of exact or nearly exact coincidences.