Temporal Mapper: transition networks in simulated and real

neural dynamics

Mengsen Zhang[1,2][†][*], Samir Chowdhury[1][†], and Manish Saggar[1][*]

[1]Department of Psychiatry and Behavioral Sciences, Stanford University, Stanford, CA

94304

[2]Department of Psychiatry, University of North Carolina at Chapel Hill, NC 27514

†equal contribution

[*]Correspondence: mengsen_zhang@med.unc.edu, saggar@stanford.edu

Abstract

Characterizing large-scale dynamic organization of the brain relies on both data-driven

and mechanistic modeling, which demands a low vs. high level of prior knowledge and

assumptions about how constituents of the brain interact. However, the conceptual

translation between the two is not straightforward. The present work aims to provide a

bridge between data-driven and mechanistic modeling. We conceptualize brain

dynamics as a complex landscape that is continuously modulated by internal and

external changes. The modulation can induce transitions between one stable brain state

(attractor) to another. Here, we provide a novel method – Temporal Mapper – built upon

established tools from the field of Topological Data Analysis to retrieve the network of

attractor transitions from time-series data alone. For theoretical validation, we use a

biophysical network model to induce transitions in a controlled manner, which provides

simulated time series equipped with a ground-truth attractor transition network. Our

approach reconstructs the ground-truth transition network from simulated time-series

data better than existing time-varying approaches. For empirical relevance, we apply

our approach to fMRI data gathered during a continuous multitask experiment. We

found that occupancy of the high-degree nodes and cycles of the transition network was

significantly associated with subjects' behavioral performance. Taken together, we

provide an important first step towards integrating data-driven and mechanistic

modeling of brain dynamics.

Introduction

The brain exhibits complex dynamics (Buzsaki, 2006; Kelso, 1995).

Characterizing its overall dynamic organization is a fundamental step in assessing brain

functions and brain fingerprinting for healthy individuals and patients with psychiatric

disorders (Saggar and Uddin, 2019). One common approach is to infer dominant "brain

states" and the transitions between them from neuroimaging time series data (e.g.,

Cavanna et al., 2018; Li et al., 2017; Meer et al., 2020; Saggar et al., 2018; Taghia et

al., 2018; Tang et al., 2012; Zalesky et al., 2014)). Such "states" and transitions can be

defined by a diverse array of data-driven methods. Here we categorized a model as

data-driven if it does not require additional knowledge of the brain other than the time

series data recorded from it. On the other side of the spectrum, brain dynamics are

often modeled by large-scale nonlinear dynamical systems models with various levels of

biophysical details (Breakspear, 2017; Deco et al., 2011). Here we categorize this type

of model as mechanistic, as they aim to describe the dynamical mechanism of

interaction between constituents of the brain, which requires prior knowledge or

assumptions about the biophysical and anatomical features of the brain in addition to

the time series data measured. States and transitions discovered using data-driven

methods often share conceptual appeal to nonlinear dynamics concepts such as

attractors (stable states) and phase transitions. Yet, a direct link between data-driven

and mechanistic modeling of the brain remains *missing*. In this work, we develop a data

analysis method to represent time series data as a directed graph, whose nodes and

edges could reasonably map directly to the underlying attractors and phase transitions

in a nonlinear dynamic model of the brain. We first validate our method using simulated

transitions and then apply the method to human fMRI data to demonstrate its empirical

relevance in assessing transitions associated with cognitive task switching. This work

helps build the missing link between data-driven and mechanistic modeling of complex

brain dynamics. With a direct link to mechanistic models, data-driven models may better

inform experimenters and clinicians of the network effect of causal perturbation (e.g.,

transcranial magnetic stimulation) in basic neuroscience and in the treatment of

psychiatric disorders.

A signature of nonlinear brain dynamics is multistability, i.e., the coexistence of

multiple stable brain activity patterns (Kelso, 2012), which may be referred to as

attractors in technical terms or persistent brain states colloquially. Transitions between

these brain states may occur either driven by external influences or internal dynamics.

Intermittent visits to different brain states are often referred to as metastability (Tognoli

and Kelso, 2014). Multistability and metastability—the existence of and the transitions

between different brain states—are key elements in the mechanistic modeling of brain

dynamics and functional connectivity (FC) (van den Heuvel and Hulshoff Pol, 2010).

Typically, such modeling approaches use large-scale biophysical network models that

also incorporate biologically informed parameters and the human structural connectome

(Deco et al., 2014, 2013, 2011; Deco and Jirsa, 2012; Golos et al., 2015; Hansen et al.,

2015; Zhang et al., 2022).

The mechanistic modeling of state transitions in large-scale brain dynamics was

motivated by, among other things, the observations of how large-scale functional

connectivity patterns vary as a function of time, i.e., the dynamic functional connectivity

(dFC) (Hutchison et al., 2013; Preti et al., 2017). dFC patterns are primarily computed

as correlation coefficients between time series within a sliding window. More recently,

single time-frame methods (e.g., (Faskowitz et al., 2020; Zamani Esfahlani et al., 2020))

have been developed to tackle FC analysis at the finest temporal resolution and reduce

the amount of data needed for stably estimating dFC patterns (Laumann et al., 2017;

Leonardi and Van De Ville, 2015). Altogether, (d)FC analyses play a central role in the

empirical understanding of brain dynamic organization. Abnormal FC and abnormal

transitions between dFC patterns have been linked to a wide spectrum of psychiatric

and neurological disorders (Barber et al., 2018; Díez-Cirarda et al., 2018; Du et al.,

2021; Fox and Greicius, 2010; Garrity et al., 2007; Lui et al., 2011; Rabany et al., 2019;

Saggar and Uddin, 2019).

What remains unclear is to what extent dFC patterns can be mapped to

dynamical systems concepts such as attractors or stable states. With a data-driven

approach, dFC patterns that repeat in time can be assigned to a relatively small number

of "FC states" using, for example, clustering methods (Allen et al., 2014) or hidden

Markov models (Quinn et al., 2018; Rabiner, 1989; Vidaurre et al., 2017). However,

directly conceptualizing FC states as dynamical system states or attractors is not easy,

especially when one needs to write down the differential equations governing the state

evolution. Thus, mechanistic models of large-scale brain dynamics typically use mean-

field neural activity (Cabral et al., 2017) (e.g., population firing rate, the fraction of open

synaptic channels) or its derived BOLD signal (Friston et al., 2003), rather than

vectorized dFC patterns, as state variables. FC states can be derived post-hoc from

simulated neural dynamics (Golos et al., 2015; Hansen et al., 2015), but a *direct*

correspondence between such post-hoc FC states and dynamical system attractors is

yet to be demonstrated. Our recent modeling work suggests that FC patterns may be

signatures of phase transitions between stable states rather than the states themselves

(Zhang et al., 2022). All the above point to the need for a data-driven method to quantify

stable brain states and transitions directly from time-series data and allow mapping of

such states/transitions to underlying attractors and phase transitions derived from

mechanistic modeling.

In the present work, we leverage existing methods of computational

topology/geometry and large-scale biophysical network modeling to bridge this gap.

Topological and geometrical analysis of dynamical systems traces back to the time of

Poincaré (Poincaré, 1967). However, efficient computational infrastructure for

generalizing such methods to higher-dimensional dynamics was not in place until

recently. Morse decomposition has been used in the rigorous analysis of nonlinear

dynamical systems, e.g., to represent a dynamical system as a directed graph whose

nodes map to attractors (and repellers) and edges to transitions (connecting orbits)

(Cummins et al., 2016; Kalies et al., 2005). However, neuroimaging data live in a very

high dimensional space sparsely covered by samples, which renders many rigorous

methods inapplicable. With a data-driven approach, combinatorial representations (e.g.,

graphs or simplicial complexes) of neural time series or FC patterns can be generated

using existing topological data analysis (TDA) tools such as Mapper (Singh et al. 2007;

Carlsson 2009; Saggar et al. 2018; Geniesse et al. 2022; Geniesse et al. 2019; Saggar

et al. 2021) and persistent homology (Edelsbrunner and Morozov 2013; Carlsson 2009;

Chazal and Michel 2021; Petri et al. 2014; Giusti et al. 2015; Billings et al. 2021). In

between, there are emerging efforts to develop dynamical system-oriented TDA

methods (Garland et al., 2016; Kim and Mémoli, 2021; Munch, 2013; Myers et al., 2019;

Perea, 2019; Tymochko et al., 2020), some specifically supported by mechanistic

models of biological dynamics (Gameiro et al., 2004; Topaz et al., 2015; Ulmer et al.,

2019; Zhang et al., 2020). The present work falls under this in-between category,

building on our previous work on the TDA (Geniesse et al., 2022, 2019; Saggar et al.,

2018) and biophysical network modeling of large-scale brain dynamics (Zhang et al.,

2022).

In the current work, our contribution is threefold. First, we introduce a novel

method to extract features associated with dynamical systems (i.e., attractors and their

directed transitions) from the observed time-series data alone. Second, to validate our

approach, we develop a method to simulate a complex sequence of phase transitions in

a large-scale neural dynamic model in a controlled manner. This simulated data not only

provides a ground truth of the co-existing attractors in the model and their respective

transitions but also allows examination of intricate but relevant nonlinear dynamic

concepts such as hysteresis. Third, we apply our method to a real-world human fMRI

dataset to examine the efficacy of our method in capturing states and their transitions

associated with cognitive task switching from time-series data alone. Taken together,

we provide a critical methodological step towards bridging the mechanistic and data-

driven modeling of large-scale brain dynamics.

Results

In this section, for larger accessibility of our results, we first provide a brief

introduction to the key nonlinear dynamics concepts and intuitions. We then introduce

the framework to simulate a complex sequence of phase transitions using a large-scale

neural dynamic model. Finally, we present an introduction to our Temporal Mapper

approach and its application to simulated as well as real-world fMRI datasets.

2.1 Nonlinear dynamics and the brain

Brain activities can be thought of as dynamics unfolding on a nonlinear

landscape (Figure 1a). Each state in this landscape represents a pattern of activation

over the whole brain. Some states are stable, which are termed attractors (Figure 1a1-

3) since they attract nearby states to evolve towards them. The coexistence of multiple

attractors— multistability—is a signature of the brain's dynamic complexity (Kelso,

2012). The landscape can be shaped by a variety of intrinsic and extrinsic factors, such

as external input, synaptic conductance, and structural connectivity (Zhang et al., 2022).

Theoretically, these factors are often considered control parameters (Figure 1b).

As the control parameter changes, the landscape deforms with it. For illustration,

sliding the gray plane in Figure 1b up and down the control parameter axis changes the

landscape within the plane. With sufficient multistability, changing a control parameter

back and forth along the same path (Figure 1c, dashed lines below the horizontal axis)

can lead to distinct paths of transitions between attractors (Figure 1c, dashed lines in

the bifurcation diagram above the horizontal axis)—a feature known as *hysteresis*. Due

to the asymmetry in the path of transitions, directed graphs are better suited to

minimally represent the transition network (Figure 1d), where the nodes map to the

attractors visited (nodes 1-3) and edges map to the transitions between attractors.

The topological complexity of this attractor transition network reflects the brain's

intrinsic complexity through its interaction with the internal or external environment. In

the present work, we develop a method to retrieve such transition networks from

simulated neural dynamics and human fMRI data. In the following sections, we

demonstrate that the networks reconstructed from simulated data are reasonable

approximations of the theoretical ground truth, and those constructed from fMRI data

help predict human behavioral performance.

Figure 1. Deformation of the brain dynamic landscape induces transitions between

stable brain states. A toy example of a dynamic landscape is shown as a colored curve

in (a). The horizontal axis represents all possible brain states, i.e., the state space,

whereas the position of the red ball represents the current brain state. States at the

local minima of the landscape (a1-3) are attractors—slight perturbation of the current

state (e.g., red ball) leads to relaxation back to the same state. States at the local

maxima of the landscape are repellers (to the left and right of state 2, unlabeled)—slight

perturbation of the state pushes the system into the basin of one of the attractors. The

landscape may be deformed by continuous changes in the brain structure, physiology,

or the external environment, here represented abstractly as a control parameter (b). As

the landscape deforms (sliding the gray plane in b), the attractors and repellers shift

continuously with it, for the most part, marked by dashed lines in red and black

respectively. At critical points where an attractor and a repeller collide, there is a sudden

change in the repertoire of attractors, potentially leading to a transition between

attractors. The change of the landscape is commonly visualized as a bifurcation

diagram (c), which keeps track of the change of attractors (red lines, 1-3) and repellers

(black lines). Here "attractor" is used in a general sense, referring to both the points in

the state space (the intersections between red lines and the gray plane in the bottom

plane in b) and the connected components resulting from the continuous deformation of

these points in the product between the state space and the parameter space (red lines

in c). Due to multistability and hysteresis, the system may take different paths in the

bifurcation diagram as the control parameter moves back and forth along the same line

(dashed lines in c; green indicates forward paths, yellow indicates backward paths). In

an even simpler form, this path dependency can be represented as a directed graph (d),

denoting the sequence in which attractors are visited (color indicates forward and

backward paths in c).

2.2 Computational framework to simulate complex sequences of phase transitions and

represent them as an attractor transition network

In this subsection, we introduce the computational framework used to simulate

neural dynamics. Simulations convey several advantages: (1) we can parametrically

control and induce transitions between attractors, (2) we can compute the ground-truth

transition network given the exact equations, and (3) we can directly compare the

reconstructed network (from simulated time series alone without knowing the equations

or any parameters) to the ground truth to assess the quality of reconstruction.

For simulations and computing the ground-truth transition network, we choose a

biophysically informed model of human brain dynamics (Figure 2a; see Section 4.1 for

details). The model describes the dynamics of a network of 66 brain regions, shown to

capture functional connectivity patterns in human resting fMRI (Zhang et al., 2022) (the

cartoon in Figure 2a includes 6 regions only for illustrative purposes). The model is an

adaptation of the reduced Wong-Wang model (Wong and Wang, 2006; Deco et al,

2014) in the form of the Wilson-Cowan model (1972, 1973) with improved multistability

(Zhang et al., 2022). Each region i consists of an excitatory population (E) and an

inhibitory population (I), with associated state variables $(S_E^{(i)}, S_I^{(i)})$. Long-range

connections between regions (C_{ij} in Figure 2a) are defined by the human connectome

using data from the Human Connectome Project (Civier et al., 2019; Van Essen et al.,

2013) (see Methods for details). The overall strength of global interaction is modulated

by an additional global coupling parameter G. We define G as the control parameter,

whose dynamics (Figure 2b) modulate the shape of the underlying dynamic landscape

and induce transitions between attractors through bifurcation (see bifurcation diagram

Figure 2d). The simulated neural dynamics in this time-varying landscape are shown in

Figure 2c. It is important to note that here we assume the control parameter G, and

consequently the shape of the underlying landscape itself, is changing much slower

than the state dynamics occurring within the landscape (the ball in Figure 1a can roll

quickly into the valley when the landscape has barely deformed). In other words, the

present conceptual framework assumes a separation of time scale between the

dynamics of the control parameter (e.g. G) and intrinsic state dynamics (e.g., defined in

Eq.1-2 by the time constants τ_E and τ_I for the excitatory and inhibitory neuronal

population respectively). Physiologically, the changes in global coupling G can be

interpreted as changes in the arousal level due to, for example, task demands. Recent

work of Munn and colleagues (2021) suggests that cortical dynamic landscapes are

modulated by ascending subcortical arousal systems mediated by the locus coeruleus

(adrenergic) and the basal nucleus of Meynert (cholinergic). In particular, the locus

coeruleus-mediated system promotes global integration across the cortex and reduces

the energy barrier for state transitions.

Our methodological goal is to recover the cross-attractor transitions from the

simulated neural dynamics (the gating variables $S_E^{(i)}$) and the BOLD signals derived

from them (down-sampled to TR=720 ms as in the Human Connectome Project (Van

Essen et al., 2013)). The transitions can be encapsulated as a transition network

(Figure 2e) and unfolded in time as a recurrence plot (Figure 2f). The recurrence plot

depicts how far away the attractor occupied at each time point is from that of every

other time point. Here, "how far away" is measured by the shortest path length from one

node to another in the attractor transition network instead of the Euclidean distance

between states in the original state space. The path length takes into account the

underlying dynamics: two states can be far away in the state space but closely

connected by transitions in the dynamical system, and conversely, two states can be

close in the state space, but it could be costly to transition between each other against

the underlying dynamics. The theoretical ground truth (Figure 2e,f) is constructed by

assigning each time point to an attractor (Figure 2d,e) pre-computed from equations 4-5

(see methods in Section 4.2). Computation of the ground truth requires all model

parameters, including the state variables $S_E^{(i)}$, $S_I^{(i)}$, and the control parameter G for

example. As depicted, the transition network is directed to capture the "flow" of time.

Further, the size of the node in the transition network represents how many sequential

time points map onto that attractor, i.e., the dwell time.

We assess the efficacy of our and others' methods by comparing the

reconstructed networks (Figure 3c,d) and recurrence plots (Figure 3i,j) to the ground

truth (Figure 2e,f).

Figure 2. Attractor transition network for simulated neural dynamics. A biophysical

network model [20] is used to describe the dynamics of the brain (a). Each brain region

is modeled as a pair of excitatory (E) and inhibitory (I) populations, connected by local

excitatory (w_{EE}, w_{EI}) and inhibitory (w_{IE}, w_{II}) synapses. Each region is also connected to

others through long-range connections (red dashed lines). The overall strength of long-

range interaction is scaled by a parameter G, the global coupling. To simulate neural

dynamics in a changing landscape (c), G is varied in time (b), mimicking the rise and fall

of arousal during rest and tasks. The duration of the simulation is 20 minutes. To

construct a ground-truth transition network between attractors (f), fixed points of the

differential equations (eq. 4-5) are computed for different levels of G and classified by

local linear stability analysis. Fixed points classified as attractors are shown in a

bifurcation diagram (d). Each attractor traces out a continuous line in a high-dimensional

space—the direct product of the state space S and the parameter space G. These lines

or attractors can be identified as clusters in S × G. Each time point in (b,c) is classified

as the regime of one attractor in the high-dimensional space S × *G*. All visited attractors

constitute the nodes of the ground-truth transition network (e), colored accordingly. A

directed edge links one attractor to another if there is a transition from the former to the

latter in time. To examine how dynamics unfold in time in this attractor transition

network (e), we construct a recurrence plot (f) that indicates the shortest path length

between any two time points (the attractors visited) in the network.

2.3 Temporal Mapper to reconstruct attractor transition network from time series alone

To reconstruct the attractor transition network, using only time series data, our

Temporal Mapper approach first constructs a temporal version of the k-nearest neighbor

(kNN) graph from samples in the time series (Figure 3a.i→a.iv). The time series data

from multiple brain regions (Figure 3a.i) are first used to compute the pairwise distance

between time points in Euclidean space (Figure 3a.ii). This distance matrix is used to

determine the k-nearest neighbors for each time point. Time points that are reciprocal k-

nearest neighbors (excluding temporal neighbors) are connected by edges, forming the

spatial kNN graph (Figure 3a.iii). Reciprocal edges in the neighborhood graph (Figure

3a.iii) connect spatial neighbors, while directed edges connect temporal neighbors,

indicating the "arrow of time" (Figure 3a.iv). Nodes that are close to each other in the

neighborhood graph are contracted to a single node in its compressed version (Figure

3a.v). We consider the compressed graphs (Figure 3a.v) as reconstructed attractor

transition networks. Further details of this construction are provided in Section 4.4.

Visually, the reconstructions (Figure 3, b.i, c.i) are reasonable approximations of the

ground truth (Figure 2e,f). This result is confirmed by quantitative comparisons against

permuted time series (Figure 3d,e) and phase-randomized time series (Figure S1). The

reconstruction remains robust at lower sampling rates (e.g., TR = 2s; See

Supplementary Figure S11 and S12 for reconstruction accuracy drop-off rate under

down-sampling) and across different realizations and integration time steps (Figure

S14). See Section 4.5 for details of the graph dissimilarity measures used in these

comparisons.

Figure 3. Reconstructed transition network using the Temporal Mapper approach captures theoretical ground truth. (a) shows the basic procedures of the Temporal Mapper in reconstructing attractor transition networks from time-series data. Neural time series is treated as a point cloud of N points (N time points) in an M-dimensional space (M regions of interest, ROI). As the system moves between different attractors, the

activation level changes discretely. The mean activation level can be used to label each

discrete state or attractor, as in Figure 2d. Pairwise distance (a.ii) between data points

that are not temporally adjacent was used to construct the spatial k-nearest-neighbor

(kNN) graph (a.iii). The temporal connectivity, i.e., the "arrows of time", is then added to

the graph as directed edges (a.iv). To further compress the graph, nodes within a path

length δ to each other are contracted to a single node in the final attractor transition

network (a.v). Each node of the attractor transition network can be colored to reflect the

properties of the time points associated with it (e.g., ground truth attractor labels or,

when ground truth is unknown, the average brain activation level for time points

associated with the node). (b.i) shows the attractor transition network reconstructed

from simulated neural dynamics S_E (the fraction of open synaptic channels, c.f. Figure

2c) with $k = 16$ and $\delta = 10$. (b.ii) gives the attractor transition network reconstructed

from the S_E -derived BOLD signals with $k = 14$ and $\delta = 10$, and further parameter

perturbation analysis is provided in Figure S2. The node color in (b) reflects the rank of

the average brain activation level for sample points associated with each node. (c.i) and

(c.ii) are the recurrence plots defined for (b.i) and (b.ii) respectively. Comparing (b.i, b.ii)

to Figure 2e and (c.i, c.ii) to Figure 2f, we see that the reconstructions are reasonable

approximations of the ground truth. Quantitatively, we evaluate the error of

approximation as the dissimilarity between the reconstructed attractor transition

networks and the ground truth transition network (Gromov-Wasserstein distance, GW;

green lines in d.i and d.ii) and the dissimilarity between their respective recurrence plots

(L2 distance; green lines in e.i and e.ii). The reconstruction error from the original time

series is significantly lower than that of randomly permuted time series (gray bars---null

distribution, red area---its 95% confidence interval).

2.3.1 The transition network, BOLD signals, and dFC reveal different facets of brain

dynamics

Next, we use the simulated data to compare the dynamics in the reconstructed

transition networks to its associated BOLD dynamics (from which the network is

reconstructed) and dFC. Given the a priori knowledge of the ground truth, we are able

to examine how different representations of the simulated time series capture different

aspects of the model brain dynamics.

Dynamics in different spaces of representation (e.g., transition network, BOLD,

dFC) can be compared in terms of the recurrence plots—a distance matrix that

describes how far away the states at any two time points are from each other. The

recurrence plot of the ground truth transition network (Figure 4a, reproduced from

Figure 2g) and that of the control parameter G (Figure 4b) provide an a priori reference

for comparing the reconstructed network (Figure 4c), BOLD (d), and dFC (e). In the

networks (Figure 4a, c), the inter-state distance used to compute the recurrence plots is

the shortest path length from one node to another. For the control parameter G and

BOLD (Figure 4b, d), the distance is simply the Euclidean distance between states. For

dFC (Figure 4e), the distance is the Euclidean distance between vectorized dFC

matrices (Fisher-z transformed elements in the lower triangle) computed in a 30-TR

sliding window. fMRI data in 20-30 TR windows have been shown to generate stable

correlations (Allen et al., 2014; Hutchison et al., 2013).

Dynamics in the ground truth and the reconstructed transition networks can also

be represented as the state (attractor) dynamics shown in Figure 4g and h respectively.

In this representation, we can visualize which attractors are visited during the course of

time. Here, we sorted (and colored) the attractors based on their SE values (i.e., higher

values mean more excitation). As evident, the dynamics extracted using the

reconstructed transition network (from the Temporal Mapper approach) closely follow

the dynamics of the ground truth network, indicating the nodes of the Temporal Mapper

network map onto underlying dynamical attractors reasonably well. A similar

visualization for BOLD and dFC can be constructed using traditional community

detection approaches on the recurrence matrix (see Figure S3 for more details).

The recurrence plot for the ground truth transition network is more complex than

that of the control parameter G (Figure 4a vs b)—this added complexity reflects that of

the underlying dynamic landscape, which is what we aim to examine. In terms of the

state dynamics, the model brain passed through a sequence of attractors and

transitions in a path-dependent manner (gray areas, Figure 4g), while the control

parameter undergoes continuous and reversible changes (Figure 4f, color-coded by

attractor index to show the model brain can visit distinct attractors given the same level

of G). Such path dependency in the ground truth transition network is indicative of

multistability and hysteresis of the underlying dynamic landscape (c.f. Figure 1c). Thus,

the discrete sequence of attractor transitions (gray areas, Figure 4g) is the signature of

the model brain dynamics. The reconstructed transition network (Figure 4c) reasonably

approximates the ground truths (Figure 4a) both in terms of the recurrence plot (Figure

4c) and the state dynamics (Figure 4h). Though some detailed transitions in the ground

truth are not resolved by the reconstructed network, it is not surprising due to the low-

pass filtering effect of the hemodynamic response—faster neural activity may not be

recoverable from BOLD signals in principle. The recurrence plot of the simulated BOLD

(Figure 4d) to a large extent follows the control parameter G, though some transitions

are already visible without further state detection. Interestingly, the recurrence plot of

dFC (Figure 4e) approximates neither that of the ground truth transition network nor that

of the parameter G. dFC does not differentiate distinct attractors and exhibits a mixed

reaction to transitions and parameter changes (see Figure S3d for how dFC states differ

from attractors states in Figure S3b and BOLD states in Figure S3c).

A further comparison between the reconstructed transition network, BOLD, and

dFC is shown in Figure 4i as the row averages of the corresponding recurrence plots,

i.e., the average distance from the state/attractor at each time point to all other time

points. This simplified representation helps us visualize the difference between

dynamics in different spaces. This method was used by (Saggar et al., 2018) to

examine transitions between tasks in the aforementioned continuous multitask

experiment (Gonzalez-Castillo et al., 2015). To understand what information each

representation captures, we separate the dynamics into two different regimes: one with

a single highly persistent attractor (white areas in Figure 4g), and one with a sequence

of transitions between less persistent attractors (gray area). The average distance in the

reconstructed network (blue, purple curves in Figure 4i) and BOLD (red) change little in

the single-attractor regime (white areas). In the same single attractor regime, the

average distance of dFC (yellow curve in Figure 4i) appears to track the time derivative

of the control parameter G only when G is decreasing (2nd and 4th white areas).

Clearly, dFC states are not equivalent to persistent attractors. The distinction between

the single-attractor and the transition regimes (white versus gray areas in Figure 4i) is

best indicated by the average distance in the reconstructed network (blue, purple

curve). Specifically, the persistent attractors are more source like (high sink distance,

low source distance – purple above blue curve in the white areas of Figure 4i) while the

sequence of transitions between less persistent attractors are more sink like (high

source distance, low sink distance – purple below blue curve in the gray areas of Figure

4i). In contrast, the average distance of BOLD (Figure 4i, red) best mirrors the value of

G (Figure 4f; high G is associated with low average BOLD distance and vice versa). In

short, the dynamics in the reconstructed transition network most effectively separate the

regimes of attractor persistence and transitions in the model brain, compared to BOLD

and dFC.

Figure 4. Comparisons between reconstructed transition networks, BOLD, and

dFC. (a) and (b) show the recurrence plots of the ground truth transition network (a-left,

reproduced from Figure 2f) and the control parameter *G* (b)*, respectively. They provide

a basis for comparing the reconstructed transition network using the Temporal Mapper

(T-mapper) (c), the corresponding BOLD signal (d), and dFC (e). The difference

between the ground truth network (a) and the parameter *G* (b) reflects the organization

of the underlying dynamic landscape. The greatest distinction is that the recurrent plot

(a) is highly asymmetric compared to (b). The lack of symmetry in (a) reflects the path

dependency and hysteresis of the underlying dynamical system. From visual inspection,

the reconstructed transition network (c) is the best approximation of the ground truth

network (a), especially for the asymmetric features. In contrast, the raw BOLD (d)

clearly follows *G* (b) though some transitions are also visible. dFC (computed from

BOLD in 30-TR windows) is neither an obvious representation of the ground truth

network nor that of the parameter *G*. Quantitatively, we computed the L2- and GW

distance between each recurrent plot (c, d, e, b) to the ground truth (box in a). For both

measures, Temporal Mapper produces the most similar recurrence plot to ground truth,

while dFC produces the most dissimilar recurrence plot. (f)-(h) compare the

reconstructed network (h) more directly to the ground truth network (g) and the

parameter *G* (f) in terms of the attractors visited at each point in time (only attractors

that persisted greater than 5 TRs are shown). Colors in (f) and (g) reflect the attractor

indices of the ground truth (y-axis of g) ordered by the global average brain activity (i.e.,

mean *SE*) associated with each attractor, as shown in Figure 2d. Similarly, state

dynamics in the T-mapper reconstructed network (h) are ordered and colored by the

global average of the simulated BOLD (rank) associated with each node. Gray areas

highlight the sequence of state transitions that distinguishes nonlinear brain dynamics

(g, h) from the continuous change of the control parameter (f). (i) compares the T-

mapper reconstructed transition network, BOLD, and dFC by the row/column averages

of the corresponding recurrence plots (c-e). Since BOLD and dFC recurrence plots are

symmetrical, their row and column averages are identical (red trace for BOLD, yellow

trace for dFC in i). For T-mapper reconstructed transition network, the row average is

the source distance (average distance from the current state to all other states; blue

trace), and the column average is the sink distance (average distance from all other

states to the current state; purple trace). See text for details.

2.4 Application of Temporal Mapper to real human fMRI dataset

Following the above theoretical analysis, we now apply the method to real human

fMRI data to characterize the dynamic landscape of the human brain. We examine what

features of the reconstructed transition networks are relevant to cognitive performance

to demonstrate how the method developed above can be used in empirical settings.

Data from 18 subjects were acquired from a continuous multi-task experiment

(Gonzalez-Castillo et al., 2015). Each subject performed 8 blocks (color-coded in Figure

5g) of tasks (memory, video, math) or rest in a single 25.4-minute scan. The theoretical

model used in the previous sections was designed to reflect this type of block design

using the time-varying parameter G. During construction of the transition networks, we

set the parameters to $k = 5$ and $\delta = 2$. Justification for this choice as well as further

parameter perturbation analysis is reported in Figures S9, S10.

Figure 5a,d show the reconstructed transition network and the corresponding

recurrence plot for a subject with good behavioral performance (top 4 in accuracy and

reaction time), and Figure 5b,e for a subject with bad behavioral performance (bottom 4

in accuracy and reaction time). For both subjects, the central nodes are occupied mainly

during the memory and math tasks (yellow, red nodes in Figure 5a,b) and go on

excursions during the video task and rest (orange, green nodes). In aggregate across

all subjects (Figure 5c), the memory task clearly dominates the highest-degree nodes

(yellow bars on the left end). In contrast, rest and the video task dominate the long

excursions through the highest-degree nodes (green and orange bars on the right end

in Figure 5f). Later, we use this separation between the more cognitively demanding

tasks (memory and math) and the relatively less demanding tasks (video and rest) over

different types of nodes to predict subjects' behavior performance (Figure 6).

Similar to Figure 4i for the theoretical model, here we examine the dynamics in

the transition networks constructed from human fMRI data in Figure 5g as the row

average (source distance, blue) and column average (sink distance, red) of the

recurrence plots. Both the source and sink distance clearly track the transitions between

blocks. Interestingly, both math and memory are associated with a low average distance

in contrast to video and rest, which suggests brain states associated with math and

memory are in the more central part of the transition network. The observation is

consistent with our previous findings using related methods, Mapper (Saggar et al.,

2018) and NeuMapper (Geniesse et al., 2022), where the task-positive brain activation

patterns were found concentrated at the core of the graph with a clear core-periphery

structure. Figure 5h shows the difference between the source and sink distance. When

this sink-source difference deviates from zero (black dashed line), the brain occupies a

node that is either more of a source to other nodes (source-like, negative values) or

more of a sink to other nodes (sink-like, positive values; see Figure S6 for example

networks). The source-like or sink-like deviation is visibly more prominent near the

transitions between tasks, e.g., block 2 in Figure 5h. This observation is verified

statistically in Figure S7a. The source-like or sink-like deviation is also more prominent

during rest and the video task than during the memory and math tasks (c.f. Figure S7b).

A closer examination of the dynamics in Figure 5h reveals that the brain tends to enter

the memory and math tasks through source-like nodes (downward arrow in Figure 5h)

and exit the block through sink-like nodes (upward arrow in Figure 5h). This is not the

case for rest and the video task. The corresponding statistical verification is shown in

Figure S8. This may be due to the fact that math and memory tasks are more structured

such that the brain enters the task via specific source states, while the brain can enter

the resting state, for example, from any state. In short, the transition networks and

recurrence plots exhibit multiple features that keep track of the task and block structure.

Figure 5. Transition networks of human fMRI data differentiate tasks and reveal transitions. (a) and (b) show the transition networks constructed from two subjects' fMRI data in a continuous-multitask experiment as examples (Gonzalez-Castillo et al., 2015). (a) is for subject-17, among the best task performers, and (b) for subject-12, among the worst task performers. The color of each node denotes the dominant task

label of the associated time points. The corresponding recurrence plots are shown in (d)

and (e). (c) shows how tasks TR are distributed in the top x% highest-degree nodes of

the networks across all subjects (x-axis in log scale). Memory and math clearly

dominate the highest-degree nodes. In addition, (f) shows how task TRs are distributed

over cycles of various lengths that pass through the top 2% of highest-degree nodes,

excluding the TRs in the high-degree nodes themselves. Rest and video dominate

longer cycles. (g) shows the average path length from each TR as a source to all other

TRs (blue) or to each TR as a sink from all other TRs (red). The path length is

normalized by the maximal distance for each subject. Solid lines show the averages

across subjects; shaded areas show the corresponding standard errors. A smaller

average distance indicates that the node being occupied is a better source (sink) for

other nodes. The difference between the source distance and the sink distance is

shown in (h). A negative (positive) number indicates that the node occupied at the time

is more of a source (sink) to other nodes.

Figure 6 shows how features of the transition networks relate to subjects'

behavioral performance. Greater separation between cognitively demanding tasks

(memory and math) and less demanding tasks (video and rest) over the highest-degree

nodes predicts a higher percentage of correct responses (Figure 6a), a faster reaction

time (Figure 6b) and fewer missed trials (Figure 6c). The statistical significance of the

correlation coefficients is further validated against 1000 random permutations of the

subject-performance correspondence (95% confidence intervals: (-0.4697, 0.5163), (-

0.5123, 0.4302), (-0.5340, 0.4342) for Figure 6a,b,c respectively). The number of cycles

connecting each high-degree node back to itself also exhibits behavioral relevance

(Figure 6d-f). On average, a greater number of cycles is strongly associated with slower

reaction time (F(1,400)=46.63, $p < 10^{-10}$; Figure 6e). There is also a scale-specific

effect—cycles around length 10 are especially predictive of slower reactions. Here the

cycle length can be roughly interpreted as the number of TRs required to leave and

return to a high-degree node. To a lesser extent, a greater total number of cycles is also

associated with a greater percentage of correct responses (F(1,400)=4.17, p=0.014).

There is no statistically significant relation between the number of cycles and the

percentage of missed trials. In short, high-degree nodes and the excursions from them,

i.e., cycles, are key behavioral relevant features.

Figure 6. Features of transition networks predict behavioral performance. (a-c) shows

how the overall task performance is associated with separations between the high-

cognitive demand tasks (math and memory) and low-cognitive demand tasks (video and

rest) over the transition network. The node-task separation is measured by the fraction

of memory and math TRs in the top 2% highest-degree nodes of the transition

networks, which also measures the preference of video and rest for low-degree nodes

(c.f. Figure 5c). Subjects with a greater node-task separation have a greater percentage

of correct responses (a), a faster reaction time (b), and fewer missed trials (c) across all

tasks. (d-f) show the length distributions of the cycles passing through the high-degree

nodes. Solid lines indicate the number of cycles at each length averaged across

subjects, who are split into two groups (red vs. blue) by the median of the percentage of

correct responses (d), reaction time (e), or the percentage of missed trials (f). Shaded

590 areas indicate the corresponding standard errors. An abundance of intermediate-length

591 cycles is associated with slower reaction time (e). There are no length-specific effects

592 on the percentage of correct responses (d) or missed trials (f). See text for related main

593 effects. (* $p<0.05$, ** $p<0.01$, *** $p<0.001$, with Tukey-HSD for multiple comparisons)

Discussion

In the present work, we propose a computational method for reconstructing

attractor transition networks from neural time series, named the Temporal Mapper. The

method represents a time series as a directed graph whose nodes and edges map to

attractors and phase transitions in the underlying dynamical system. In particular, the

method addresses the scenario where the underlying system is non-stationary or non-

autonomous, as for example, when the brain is under continuously varying task

demand, environmental changes, arousal levels. Using simulated brain dynamics, we

demonstrate that the method provides a good approximation of the theoretical ground

truth of cross-attractor transitions. Applying the method to human fMRI data, we show

that the dynamics in the reconstructed networks clearly track the transitions between

tasks. High-degree nodes and cycles of the network are key features that help predict

human behavioral performance. Together, the theoretical and empirical analyses

provide a basic theoretical and computational framework for bridging the data-driven

and mechanistic modeling of brain states and transitions.

The present method builds on our previous works on characterizing neural

dynamic landscape using topological data analysis (TDA). In particular, it belongs to a

family of neural time series analysis tools (Geniesse et al., 2022, 2019; Saggar et al.,

2021, 2018) based on Mapper (Singh et al., 2007). NeuMapper (Geniesse et al., 2022)

is the closest methodological match to Temporal Mapper in that it uses a reciprocal kNN

graph construction without using local low-dimensional embeddings as an intermediate

step. In another variant of Mapper approach, used in (Saggar et al., 2021), an

embedding step is typically utilized to examine the latent space, with any chosen

dimension reduction techniques. Across the family of Mapper-based tools and related

topological methods (Carlsson, 2009; Munch, 2013), time series are commonly treated

as distributions of sample points in the state space. Constructing a topological

representation, e.g., a graph, from such a distribution often concerns only the spatial

distance between points in the state space or that of their lower-dimensional

projections. The fact that these sample points are part of a time series—that there is an

explicit sequential relation between sample points—is unutilized. Specifically, within the

realm of fMRI data, which has been traditionally studied using time series techniques,

previous applications of Mapper (Geniesse et al., 2022; Saggar et al., 2021, 2018) have

focused on the geometric distribution of sample points and discarded the temporal

information in the sequence of sample points. The present method is designed precisely

to take advantage of this sequential information, i.e., the arrow of time. Incorporating the

arrow of time better reflects the fact that the system that generates the time series, e.g.,

the brain, is a dynamical system. That is, the subsequent states of the system depend

on the current state, and the exact nature of this dependency is the nature of the

dynamical system. Restoring this temporal dependency in the construction has several

consequences that we describe next.

First, the arrow of time restores the connectivity between sample points that

could be far apart in the state space but tightly linked dynamically. The implication is

most significant during a phase transition (vertical dashed lines in Figure 1c). At a

transition, the dynamical system jumps suddenly from one attractor to another at a time

scale much faster than the state dynamics within the same attractor. The combination of

high velocity and even sampling in time makes consecutive sample points far apart in

the state space, despite the direct dynamic dependency between them. Without the

arrow of time, the increase of velocity during transitions is unaccounted for. The spatial

information alone cannot determine the dynamic linkage between states of the system

during the transitions, which happen to be key moments of interest.

Second, path lengths in the transition networks carry dynamical rather than

purely geometrical information. The arrow of time introduces directedness into the

networks. Thus, the shortest path lengths between two nodes are no longer symmetric

and thus cannot be interpreted as geometric distance. The arrow of time attaches

information about the underlying dynamic landscape to the state space. At an intuitive

level, the shortest path from node x to node y can be considered the path of least time,

or least action, within the landscape. In other words, paths in the transition networks

could putatively encode actions in the state space.

Lastly, incorporating the arrow of time distinguishes the present method from

common point cloud-based TDA techniques. Point-cloud data—sets of disconnected

points—are fundamental substrates of topological or geometrical analysis and learning.

Such analysis includes nonlinear dimension reduction techniques such as Isomap

(Tenenbaum et al., 2000) or Laplacian Eigenmaps (Belkin and Niyogi, 2003),

topological data analysis (TDA) methodologies such as persistent homology (Carlsson,

2009; Edelsbrunner and Morozov, 2013), and deep learning (Qi et al., 2017). With the

points first connected to their temporal neighbors, the present method operates on, in

essence, a discretized version of a curve with a direction defined on it—naturally

depicting a trajectory of an autonomous, deterministic dynamical system. Constructing a

spatiotemporal neighborhood graph (Figure 3b) is thus folding a directed curve rather

than "connecting dots". An exposition of the mathematical consequences of the

construction is beyond the scope of the present work but worthy of further study,

especially with regard to its behavior as the sampling rate of the time series approaches

infinity and when multiple trajectories are included in the construction.

One may find the transition networks in the present work reminiscent of hidden

Markov models (HMM) for detecting discrete states in brain dynamics and transition

probabilities between states (Baker et al., 2014; Meer et al., 2020; Ou et al., 2013;

Rezek and Roberts, 2005; Vidaurre et al., 2017). A key distinction is that the number of

discrete states in an HMM is set a priori, while its analog in the present method—the

number of attractors visited—is data-driven. The dynamic landscape of the human brain

can be highly complex and sensitive to the organization of the large-scale structural

connectome (Zhang et al., 2022). There is no a priori way to determine how many

attractors may be visited during tasks and rest. Moreover, the dynamic landscape of

each subject is shaped by the structural connectivity in each subject's own brain. It

cannot be assumed that the same number of attractors would be visited across

subjects. Thus, the present method presents a flexible framework that requires fewer

assumptions about the underlying dynamical system. For example, the Markov property

for HMM (dependency on present state only) may not be satisfied in non-autonomous

dynamical systems as conceptualized in the present work (see Figure S13 for an

application of HMM on the simulated data), while the Temporal Mapper does not require

the Markov property. Apart from statistical inference methods such as the HMM,

topological representations of attractor networks also figure in differential equation-

oriented state-space decomposition methods, e.g., based on the Conley Index Theory

(Ban and Kalies, 2006; Kalies et al., 2005). In comparison to such mathematically

rigorous approaches, the present method better accommodates empirical applications

where the state space is often sparsely covered by data and the underlying dynamical

system is changing with time. Conceptually, the attractor transition networks in the

present study should be thought of not as representing the structure of an autonomous

dynamical system, but rather the complex interaction between the environment and the

brain dynamic landscape.

Our flexible, individualized construction of transition networks comes with a

cost—there lacks a direct correspondence between different networks. An advantage of

an HMM constructed from data concatenated across subjects (c.f. Meer et al., 2020) is

that the model comes with a fixed number of states across all subjects, with direct one-

to-one correspondence. In contrast, the correspondence problem for the present

method is data-driven and needs to be solved separately. For example, attractor

transition networks for different subjects (Figure 5a,b) contain different numbers of

nodes (attractors) and edges (transitions). How nodes and edges in Figure 5a map to

those in Figure 5b is not obvious. Even when comparing attractor transition networks

with the same number of nodes, obtaining a correspondence is equivalent to solving an

instance of the Graph Matching problem, which is a hard, fundamental challenge in

graph processing (Umeyama, 1988; Zaslavskiy et al., 2009). In the present work, the

correspondence between networks is made using techniques from optimal transport

theory, specifically the use of Gromov-Wasserstein (GW) matchings between networks

(Figure 3e,g) which can provide approximate graph matching solutions even for graphs

with different numbers of nodes. GW matching does not require a temporal

correspondence or any a priori knowledge of how the networks are constructed, and

can thus be used in a broad context. For example, for resting-state fMRI, there is no a

priori way to map the transition network constructed from one recording session to that

of another. GW matchings provide a solution to compare a subject's resting transition

networks in different sessions to examine the stability of the brain dynamic landscape,

or to compare transition networks of healthy subjects to that of the psychiatric patients

to examine the dynamic basis of the disorder. We therefore introduce this tool to the

neuroimaging community with broader future applications in mind.

The present work also brings attention to the interpretation of dFC states. It is

shown in Figure 4e,i and Figure S3d that dFC states are not equivalent to attractors in

the brain dynamics: dFC is in part sensitive to the transitions (Figure 4i gray areas) and

in part to the change in the control parameter without inducing any phase transition

(Figure 4e white areas). It has been proposed that resting-state FC reflects cross-

attractor transitions (Zhang et al., 2022). While dFC-based clustering can differentiate

tasks very well (Gonzalez-Castillo et al., 2019), this differentiation may not be

interpreted as the brain occupying distinct attractors during different tasks, but rather,

these tasks involve different transitions and environment-driven correlations.

Complementing existing dFC-based approaches, the attractor transition networks

incorporate information of the underlying dynamical system and provide a channel to

connect data-driven representations to dynamical systems concepts. Future work may

further explore the relation between attractor transition networks and dFC by using

single-frame techniques for FC quantification (Esfahlani et al., 2020; Faskowitz et al.,

2020).

In application to the human fMRI data, we provide a series of analyses

comparable to those of an earlier work (Saggar et al., 2018), where undirected networks

were constructed using Mapper (Singh et al., 2007) from the same dataset (Gonzalez-

Castillo et al., 2015). Saggar et al (Saggar et al., 2018) observed that the core of the

networks was dominated by cognitively demanding tasks, such as memory, math, and

to a lesser extent, video tasks, while the peripheries were dominated by rest. In the

same vein, we observe that the highest-degree nodes are dominated by memory and

math (Figure 5c), and that the level of dominance predicts behavioral performance

(Figure 6a-c). Note that due to the compression step in the present construction (Figure

3b→c), tightly connected nodes in the neighborhood graph (Figure 3b) are contracted to

a single node in the final attractor transition network (Figure 3c). It is reasonable to

assume that tightly connected nodes that serve as the core for periphery nodes in the

neighborhood graph would become a high-degree node in the compressed graph. Thus,

the high-degree nodes in the present work may be thought of as a loose counterpart to

the core of the Mapper-based construction (Saggar et al., 2018).

The periphery structures of interest in the present construction are the cycles that

connect the high-degree nodes back to themselves. For the human fMRI data, long

cycles are dominated by rest and the video task (Figure 5f), analogous to the Mapper-

based result (Saggar et al., 2018) that periphery nodes are dominated by rest.

Importantly, the present cycle-based analysis of the periphery structure allows us to

examine recurrent dynamics of different duration (reflected as cycle length, Figure 5f)

and identify the behavioral relevant time scales (Figure 6d-f). Interestingly, slower

reaction time during tasks is associated with an excess of intermediate but not long

cycles (Figure 6e). This suggests that intermediate cycles putatively represent the stray

path that the brain took, resulting in slower reaction times. Interestingly, a greater

number of cycles predicts higher accuracy, which, combined with the reaction time

results, may reflect a speed-accuracy trade-off. It provides an example of process-

based analysis of brain dynamics afforded by the present, dynamics-minded,

construction. From a more technical viewpoint, the spectrum of cycle length (Figure 6d-

f) is tightly connected to the multiscale nature of the attractor transition network. The

Temporal Mapper naturally admits multiscale construction via the compression distance

δ (Figure 3a.iv). That is, one can consider the attractor transition network as a sequence

of networks at different scales δ (see Figure S9 for example) instead of a single graph.

At a specific scale, any smaller recurrent processes, i.e., smaller cycles formed by a few

recurring attractors, will be contracted into a single node. Thus, the spectrum of cycle

length indicates at which scales the graph can be further compressed. Further method

development and empirical testing are required to better take advantage of the

multiscale information in the Temporal Mapper. In addition, unfolding the dynamics in

time as the average distance in the transition network tracks the transition between

tasks (Figure 5g), comparable to Mapper-based results (Saggar et al., 2018). In the

present work, the directed nature of the attractor transition networks introduces

additional information—the direction of least action between states. Some nodes have a

characteristic direction as a sink or a source (positive or negative deviation in Figure

5h), serving as entry and exit for the cognitively demanding tasks (Figure S8). Note that

the sink-/source-ness of the associated brain activity patterns may not be absolute, as it

is possible for the sink-/source-ness to depend on the specific design of the experiment

(e.g., what types of tasks are included in the session and the time allocation for each

task). Further studies are necessary to elucidate the interpretation of sink/sourceness in

a more general context, which will require applying the Temporal Mapper to a wider

range of datasets. Nevertheless, the present study demonstrates that the directedness

introduced by the arrow time is task-specific. Future work may further explore the

cognitive correlates of different directed features of the graph, including the

sink/sourceness of the nodes. Moreover, this directedness may be useful for designing

neural stimulation protocols to more effectively perturb the brain into desirable states.

In conclusion, we propose a computational method for constructing attractor

transition networks from simulated and empirical time series of brain dynamics.

Complementing existing geometrical and statistical approaches to characterizing brain

dynamics, the present work aims to provide a channel of correspondence between

data-driven topological modeling and mechanistic modeling. Incorporating time in the

construction of spatiotemporal neighborhoods, paths in the attractor transition networks

encode the action of the underlying dynamical systems. The method is both validated

using a biophysical network model of the brain and shown to reveal behavioral and

cognitive relevant features in human fMRI data. The present work serves as a starting

point for dynamical theory-driven topological analysis of brain dynamics. Future work

will compare the present state and transition detection methods more extensively to

existing community detection methods and further validate the method using

consortium-sized data (Gordon et al., 2017; Saggar et al., 2021; Smith et al., 2013).

Materials and Methods

4.1 Biophysical network model of the human brain

The theoretical components of the present work are based on a biophysical network

model of large-scale brain dynamics (Zhang et al., 2022), which is an variant of the

reduced Wong-Wang model (Wong and Wang, 2006; Deco et al, 2013, 2014). The

model is a Wilson-Cowan type model (Wilson and Cowan, 1972, 1973). The whole brain

is modeled in terms of the mean-field activity of neuronal populations in each brain

region (Figure 2a). Each model region contains a pair of excitatory (E) and inhibitory (I)

populations, whose activity is described by the *local model* (Figure 2a, right box) in

terms of the state variables S_E and S_I:

$$\frac{dS_E}{dt} = -\frac{S_E}{\tau_E} + (1 - S_E)\gamma_E H_E(w_{EE}S_E - w_{IE}S_I + I_E) \tag{1}$$

$$\frac{dS_I}{dt} = -\frac{S_I}{\tau_I} + (1 - S_I)\gamma_I H_I(w_{EI}S_E - w_{II}S_I + I_I) \tag{2}$$

S_E and S_I indicate the fraction of open synaptic channels in their respective populations,

referred to as the gating variables. Through local connections (w's), the excitatory

population excites itself with strength w_{EE} and the inhibitory population with strength

w_{EI}, while the inhibitory population inhibits itself with strength w_{II} and the excitatory

population with strength w_{IE}. Each population can also receive input from outside of this

region, denoted as I_E and I_I. The activity of each population has a natural decay time of

τ_E and τ_I respectively. Each population's activity tends to increase with the fraction of

closed channels $(1 - S_p)$ and the population firing rate (H_p), scaled by a factor γ_p for $p \in$

$\{E, I\}$. H_E and H_I are transfer functions that map synaptic current input to population

firing rate of the excitatory and the inhibitory population respectively. In particular, they

are sigmoidal functions of the form

$$H_p(x) = \frac{r_{max} + \frac{a_p x - b_p - r_{max}}{1 - e^{d_p(a_p x - b_p - r_{max})}}}{1 - e^{-d_p(a_p x - b_p)}}$$ (3)

whose output increases with input monotonically and saturates at r_{max}---the maximal

firing rate limited by the absolute refractory period of neurons. The specific shape of

each transfer function is determined by three additional parameters a_p, b_p, and d_p (a_p

and b_p determine the location and slope of the near-linear segment in the middle; d_p

determines the smoothness of the corners bordering the said near-linear segment). This

transfer function is converted from Wong and Wang's original formulation (Abbott and

Chance, 2005; Wong and Wang, 2006) (a soft rectifier function, adopted into large-scale

biophysical network models of the brain by Deco et al, 2013, 2014) into a sigmoidal

form, while retaining the original value of parameters a_p, b_p, and d_p (shown in Table 1).

The parameters were chosen to approximate the average response of a population of

spiking pyramidal cells ($p = E$) and interneurons ($p = I$) respectively, incorporating

physiologically plausible parameters (Wang, 2002; Wong and Wang, 2006).

Connecting the local models into a global network (Figure 2a, left, dashed lines) gives

us the *global model*:

$$\frac{dS_E^{(i)}}{dt} = -\frac{S_E^{(i)}}{\tau_E} + (1 - S_E^{(i)})\gamma_E H_E(w_{EE}^{(i)}S_E^{(i)} - w_{IE}^{(i)}S_I^{(i)} + I_G^{(i)}(\overrightarrow{S_E})) + \sigma\xi_E^{(i)}(t)$$

861   (4)

$\frac{dS_I^{(i)}}{dt} = -\frac{S_I^{(i)}}{\tau_I} + (1 - S_I^{(i)})\gamma_I H_I(w_{EI}^{(i)}S_E^{(i)} - w_{II}^{(i)}S_I^{(i)} + I_I) + \sigma\xi_I^{(i)}(t),$ (5)

where $S_E^{(i)}$ and $S_I^{(i)}$ are the synaptic gating variable of the excitatory and the inhibitory

population of the i-th brain region respectively, and $\xi.^{(i)}$ is a noise term scaled to an

amplitude σ. For computing the fixed points, $\sigma = 0$; for numeric simulations, $\sigma = 0.01$

following Zhang et al (2022). The state of all excitatory populations is denoted as a

vector $\vec{S}_E$, the i-th element of which is $S_E^{(i)}$. The global input to the i-th brain region

depends on both its connectivity with, and the ongoing state of, other brain regions,

$I_G^{(i)}(\vec{S}_E) = G \sum_{j=1, j\neq i}^{N} C_{ij}S_E^{(j)}$ (6)

where N denotes the total number of brain areas, $C_{ij} \geq 0$ the long-range structural

connectivity from the j-th to the i-th brain region and G is a global coupling parameter

that controls the overall level of interaction across brain regions. Since C_{ij} is only

intended to represent long-range connectivity, we let $C_{ij} = 0$ for any $i = j$ to preclude

recurrent connections. For the effects of G and C_{ij} to be independently comparable, here

we impose a normalization condition on the matrix norm:

$||C||_\infty = \max_i(\sum_{j=1}^{N} |C_{ij}|) = 1$

(7)

In the present work, nodes of the global network correspond to anatomical regions in

the human brain based on a 66-region parcellation used in (Deco et al., 2013; Hagmann

et al., 2008) (Table S1); the weight of edges reflects the strength of long-range

structural connectivity between brain regions, estimated using structural data from the

Human Connectome Project (Civier et al., 2019; Van Essen et al., 2013). Specific

parameter values are given in Table 1.

Parameter	Interpretation	Value
τ_E	Decay time of NMDA receptor	0.1 (s)
τ_I	Decay time of GABA receptor	0.01 (s)
γ_E	Kinetic parameter of excitatory population	0.641
γ_E	Kinetic parameter of inhibitory population	1
a_E	Parameter of H_E	310 (nC^{-1})
b_E	Parameter of H_E	125 (Hz)
d_E	Parameter of H_E	0.16 (s)

a_I	Parameter of H_I	615 (nC^{-1})
b_I	Parameter of H_I	177 (Hz)
d_I	Parameter of H_I	0.087 (s)
r_{max}	Maximal firing rate	500 (Hz)
w_{EE}	Excitatory-to-excitatory coupling	2.8 (nA)
w_{EI}	Excitatory-to-inhibitory coupling	1 (nA)
w_{IE}	Inhibitory-to-excitatory coupling	2.8 (nA)
w_{II}	Inhibitory-to-inhibitory coupling	0.05 (nA)
I_I	External input to inhibitory population	0.1 (nA)
G	Global coupling	1.1-5 (nA)
C_{ij}	Structural connectivity between brain regions	Human structural connectome (Civier et al., 2019; Van Essen et al.,

		2013)
σ	Noise amplitude	0.01

Table 1. The interpretation and value of model parameters. Here we summarize the

parameters used in the global model (equation 4-5). Critical parameters are inherited

from (Wong and Wang, 2006) to maintain biological plausibility.

4.2 Computation of the attractor repertoire and ground-truth transition network

Fixed points of the global model (equations 4-6) are computed using *fsolve* in MATLAB

for each parameter G (in 0.01 increments). A subset of the fixed points is further

classified as attractors based on local stability analysis using the Jacobian matrix and

simulated perturbation. These attractors are visualized in Figure 2d as a bifurcation

diagram (see (Zhang et al., 2022) for further computational details). Attractors that

continuously map to each other under the variation of parameter G are considered

qualitatively equivalent. Thus, in the present work, the term "attractor" is used in a broad

sense, referring to the connected components of (narrow-sense) attractors in the

product of the state space and the parameter space. Computationally, single-linkage

clustering is used to obtain these connected components. The set of all connected

components or clusters constitutes the attractor repertoire, providing a compact

description of the model dynamic landscape (Zhang et al., 2022).

The attractor repertoire further provides a skeleton to convert any simulated times

series of the state variables (within the appropriate parameter range) into the

corresponding symbolic dynamics. Here symbolic dynamics refers to a sequence of

symbols, where each symbol represents an attractor, and the sequence represents the

order in which the attractors are visited in time. Computationally, each time point in the

simulated time series is assigned to an attractor using nearest-neighbor classification in

the product of the state space and the parameter space, given the pre-computed

attractor repertoire. The resulting symbolic dynamics is used to construct the ground-

truth attractor transition network (Figure 2f). Nodes of the network are unique symbols

appearing in the sequence. There is a link from node *i* to node *j* if the corresponding

symbol *i* appears immediately before symbol *j* in the sequence. Each node is equipped

with a probability measure proportional to the dwell time at the corresponding attractor

(i.e., node size in Figure 2f).

4.3 Simulated brain activities and BOLD signals

We simulate time series of brain activities and the derived BOLD signals as substrates

for data-driven construction of attractor transition networks (Section 4.4). The neural

activity of each model brain region *i* is represented by the local excitatory population

activity $S_E{}^{(i)}$ (equations 4-6), simulated using the Heun stochastic integration scheme

with a 0.001 s time step.

The derived BOLD (Blood-oxygen-level-dependent) activities are computed using the

Balloon-Windkessel model (Buxton et al., 1998; Friston et al., 2003, 2000; Mandeville et

al., 1999),

$\dot{s}_i = S_E{}^{(i)} - \kappa_i s_i - \gamma_i(f_i - 1)$ (8)

$\dot{f}_i = s_i$ (9)

$\tau_i \dot{v}_i = f_i - v_i{}^{1/\alpha}$ (10)

$\tau_i \dot{q}_i = \frac{f_i}{\rho_i}[1 - (1 - \rho_i)^{1/f_i}] - v_i{}^{1/\alpha-1} q_i$

(11)

$BOLD_i = V_0[k_1(1 - q_i) + k_2(1 - q_i/v_i) + k_3(1 - v_i)],$ (12)

where the interpretation and values of the parameters are given in Table 2. The initial

condition is:

$[s_i(0), f_i(0), v_i(0), q_i(0)] = [0,1,1,1],$

(13)

which is a hemodynamic equilibrium state without neural activity. The BOLD dynamics

are passively driven by neural activity $S_E{}^{(i)}$, simulated using the Euler method with an

integration time step of $0.001\ s$.

Parameter	Interpretation	Value
s_i	Vasodilatory signal	Variable

f_i	Blood inflow	Variable
v_i	Blood volume	Variable
q_i	Deoxyhemoglobin content	Variable
κ_i	Rate of signal decay	$0.65(s^{-1})$
γ_i	Rate of flow-dependent elimination	$0.41(s^{-1})$
τ_i	Hemodynamic transit time	$0.98\ (s)$
α	Grubb's exponent	0.32
ρ	Resting oxygen extraction fraction	0.34
V_0	Resting blood volume fraction	0.02
k_1	BOLD weight parameter	$7\rho_i$
k_2	BOLD weight parameter	2
k_3	BOLD weight parameter	$2\rho_i - 0.2$

Table 2. Parameters of the Balloon-Windkessel model of BOLD activity, obtained from (Friston et al., 2003).

4.4 Temporal Mapper – construction of transition networks

The fundamental backbones of our transition networks are the k-nearest-neighbor

graphs (kNNG) that often appear in dimension reduction techniques (Van Der Maaten et

al., 2009). Before introducing this construction, we first set up some preliminaries.

Given a d-dimensional vector v and $p \geq 1$, the p-norm of v is defined by writing $||v||_p :=$

$(\sum_{i=1}^{d} |v_i|^p)^{1/p}$. Unless specified otherwise, we will use $p = 2$ throughout this work, i.e.

the Euclidean norm. Next, given a dataset X as an $n \times d$ matrix, we will typically

interpret X as a collection of n points $\{x_1, x_2, \ldots x_n\}$ in d-dimensional space. Finally, for

any positive integer $k \geq 1$, the collection of *top-k* nearest neighbors for any point x_i,

denoted $top(k, x_i)$, is the collection of the k points closest to x_i in the sense of the

Euclidean norm. The standard kNNG on X is defined to be the graph with node set

$\{x_1, x_2, \ldots, x_n\}$ and edge set:

$\{(x_i, x_j) : x_i \in top(k, x_j) \text{ or } x_j \in top(k, x_i)\}$.

A related construction is the *reciprocal k-nearest neighbor graph* (rkNNG) construction.

Here the nodes are given as before, but a stricter convention is followed for the edge

set:

$\{(x_i, x_j) : x_i \in top(k, x_j) \text{ and } x_j \in top(k, x_i)\}.$

The reciprocal construction takes more information about local densities into account

than the standard kNNG, and is occasionally more useful in practice (Qin et al., 2011).

With this setup in place, we are ready to describe our construction. In our setting,

datapoints that are close in time also have a tendency to be close in space, as the

states change continuously (i.e. without sharp jumps) within an attractor. Keeping this

tendency in mind, we carry out the following procedure:

● Construct a standard kNNG

● Remove edges of the form (x_i, x_{i+1}) (these will be added back in)

● Remove all non-reciprocal connections, i.e. only retain edges (x_i, x_j) if $x_i \in$

$top(k, x_j)$ and $x_j \in top(k, x_i)$

● Add directed temporal links (x_i, x_{i+1}); existing undirected edges (x_i, x_j) are

viewed as double edges $(x_i, x_j), (x_j, x_i)$. This final digraph is denoted $\tilde{G}$.

The initial pruning of temporal neighbors is carried out to help recover directionality in

the data (see Figure S5). Other strategies may be possible, but the current method

worked sufficiently well for our purposes. The intermediate step of removing non-

reciprocal connections is a strategy for disambiguating between points that have

differing local densities (Qin et al., 2011). The final addition of the temporal links injects

the "arrow of time" back into the graphical representation. Note that this final step is not

typical, but is possible in our setting because we work with time series data and know

an explicit ordering of our data points. An important feature of the networks that we

constructed was that they tended to be *strongly connected* as digraphs, meaning that it

was possible to take a directed path between any two vertices. Our construction also

accommodates multiple time series or time series with missing frames (frame censoring

is common in fMRI time series to remove motion artifacts): the arrow of time is only

removed and reintroduced between consecutive time points in the *same* time series or

epoch in step 2 and 4 above. When the data constitute a single uninterrupted time

series, the digraph will always have one connected component by virtue of the arrows of

time that connect every pair of consecutive time points. When the data contain multiple

disjoint time series, it is possible for the digraph to have multiple connected components

for certain parameter k as the connectivity across time series depends solely on the

existence of reciprocal *spatial* neighbors. If it is desirable for the digraph to have a

single connected component, one can choose to (a) increase k until reciprocal kNN

exists between any pair of time series, or (b) pre-align the time series to increase the

spatial proximity between them.

1018

The final step in the construction of the transition network achieves *compression* and

follows the notion of *reciprocal clustering of digraphs* introduced by Carlsson et al.,

(2013). For a fixed parameter $\delta > 0$ (specifically $\delta = 2$ in this work), we construct an

auxiliary undirected graph U on X with edges $\{(x_i, x_j) : d_{\tilde{G}}(x_i, x_j) \leq \delta, d_{\tilde{G}}(x_j, x_i) \leq \delta\}$.

The connected components of U partition the vertex set of $\tilde{G}$ into blocks $B_1, B_2, \ldots, B_m$.

The final compressed transition network G is now constructed with vertex set $V(G) =$

$\{B_1, B_2, ..., B_m\}$ and edge set

1026

1027 $$E(G) := \{(B_i, B_j) : \text{there exists } (v, v') \in E(\tilde{G}) \text{ for some } v \in B_i, v' \in B_j\}.$$

1028

1029 Note that if v and v' belongs to the same connected component of the kNNG $\tilde{G}$, there

1030 exists some edge between the partitions of the said connected component. Thus, the

1031 number of connected components does not change due to compression.

1032 4.5 Gromov-Wasserstein distance between transition networks

1033

Temporal Mapper produces directed graphs where arrows display temporal structure. In

general, comparing such graphs directly requires solving a correspondence problem as

different graphs may have different numbers of nodes. To solve this correspondence

problem, we use the Gromov-Wasserstein (GW) distance (Mémoli, 2007). While

originally formulated for metric spaces, the GW formulation was shown to admit a bona

fide distance between directed graphs with arbitrary edge weights in (Chowdhury and

Mémoli, 2019), and has recently enjoyed significant attention from the machine learning

community (Flamary et al., 2021; Peyré et al., 2016; Peyré and Cuturi, 2019; Solomon

et al., 2016; Titouan et al., 2019; Xu et al., 2019). In the (di)graph setting, the GW

distance allows one to compare the full structure of two (di)graphs without reducing to

summary statistics such as degree distributions or centrality.

1045

The GW distance formulation for graphs proceeds as follows. Let $G = (V, E)$, $H = (W, F)$

be two graphs (possibly directed and/or weighted) on vertex sets V, W of possibly

different sizes. For Temporal Mapper, E and F are the (asymmetric) geodesic distance

matrices–note that these matrices are well-defined because the underlying digraphs are

strongly connected. Additionally, let p, q be two probability distributions on V, W

respectively, denoting the significance of each node. In the Temporal Mapper setting,

this is just the number of data points in each node, appropriately normalized, and thus

reflects the compression at each node. In matrix-vector notation, we have:

1054

1055   • E a $|V| \times |V|$ matrix, p a $|V| \times 1$ vector such that $p_i > 0$ for all $1 \leq i \leq |V|$ and

1056 $\sum_{i=1}^{|V|} p_i = 1$

1057   • F a $|W| \times |W|$ matrix, q a $|W| \times 1$ vector such that $q_i > 0$ for all $1 \leq i \leq |W|$ and

1058 $\sum_{i=1}^{|W|} q_i = 1$.

1059

The correspondence between nodes is represented as a joint probability distribution

matrix C of size $|V| \times |W|$ satisfying nonnegativity and summation constraints $C_{ij} \geq$

$0, \sum_{i,j} C_{ij} = 1$ as well as marginal constraints such that the rows and columns of C

correspond to p and q, respectively. Such a joint distribution is typically referred to as a

coupling matrix, and the collection of coupling matrices is denoted $C(p, q)$. Intuitively, a

coupling describes "how much each node in V corresponds to a given node in W".

1066

1067 Finally, the GW distance between the two graphs is a given as the result of the following

1068 optimization problem:

1069

1070
$$d_{GW}((E,p),(F,q))^2 = \min_{C \in C(p,q)} \sum_{ijkl} |E_{ik} - F_{jl}|^2 \, C_{kl} C_{ij}.$$

1071

This is a nonconvex quadratic optimization problem (nonconvex because symmetries in

the graphs may lead to different correspondences achieving the same minimum,

quadratic because the C appears twice) and is generally difficult to solve. Intuitively, this

distance measures the expected distortion that the edges of G would necessarily

undergo upon being transformed into the graph H. While significant progress has been

made in obtaining local minimizers of the underlying optimization through regularization

or gradient descent (Flamary et al., 2021; Peyré and Cuturi, 2019), it is in general

difficult to assess the quality of these local minimizers except in certain domain areas

such as computer vision where the output can be directly inspected in two or three

dimensions.

1082

1083   Instead, we opt to solve a lower bound for the GW problem that can be formulated as a

1084   linear program with an exact solution. This lower bound, which was referred to as the

1085   third lower bound (TLB) in (Mémoli, 2007), arises by decoupling the quadratic

1086   optimization problem and instead solving:

1087

1088 $\text{TLB}((E,p),(F,q))^2 = \min_{B,C \in C(p,q)} \sum_{ijkl} |E_{ik} - F_{jl}|^2 B_{kl} C_{ij} = \min_{B \in C(p,q)} (\min_{C \in C(p,q)} |E_{ik} - F_{jl}|^2 B_{kl}) C_{ij}.$

1089

1090

1091   It can be shown (Schmitzer and Schnörr, 2013) that the inner infimization problem has a

1092   closed form solution. In other words, the preceding problem amounts to solving the

1093   following *linear program*:

1094

1095 $\min_{C \in C(p,q)} \sum_{ij} J_{ij} C_{ij},$ where $J_{ij} = \min_{B \in C(p,q)} \sum_{kl} |E_{ik} - F_{jl}|^2 B_{kl}$,

1096   and each J_{ij} can be individually solved in closed form.

1097

Because there are $|V| \times |W|$ individual entries making up $|J|$, and the entries can all be

computed independently, this problem is perfectly suited for GPU computations. Our

GPU implementation of the TLB computes each coefficient J_{ij} in a separate thread block

so that all coefficients are computed in parallel. The final linear program can be solved

easily using standard linear solvers, e.g. using the network simplex algorithm (Bonneel

et al., 2011). For applications in the present work, the GPU-infused version accelerates

the original implementation (Chowdhury and Mémoli, 2019) by roughly 200 times.

1105

1106   4.6 Cycles of transition networks

1107

Enumerating all cycles in a graph can be computationally expensive (Giscard et al.,

2019). However, the transition networks that appear in our setting are small enough that

we can enumerate all cycles and carry out further postprocessing in reasonable time.

Given a transition network G with vertices indexed as $\{v_1, v_2, \dots, v_d\}$, we proceed via the

following heuristic approach. First we loop over all pairs of vertices (v_i, v_j) and use

Matlab's native shortest path algorithm (i.e. a breadth-first search of complexity $O(|V| + $

$|E|)$) to find the shortest paths from v_i to v_j and from v_j to v_i, respectively. These paths

are then concatenated (avoiding trivial repetition at endpoints) to obtain a cycle. If a

cycle has repeated nodes, i.e. is not a simple cycle, then it is discarded. Finally, after

the loop terminates, there may be multiple copies of the same cycle with different

starting points. For each of these cases, we retain the copy starting at the smallest

index and discard the others.

1120

1121   4.7 The continuous multitask experiment

1122

In this study, we utilized an fMRI dataset comprising 18 participants collected by

(Gonzalez-Castillo et al., 2015) using a continuous multitask paradigm (CMP). We

retrieved the data from the XNAT Central public repository (https://central.xnat.org;

Project ID: FCStateClassif). Informed consent was obtained from all participants, and

the local Institutional Review Board of the National Institute of Mental Health in

Bethesda, MD reviewed and approved the CMP data collection. We briefly describe the

experiment structure and preprocessing below.

1130

Participants were scanned continuously for 25 minutes and 24 seconds while

performing four different cognitive tasks. Each task was presented for two separate

180s blocks, and each task block was preceded by a 12s instruction period. These four

tasks were: (1) Rest (R), where participants were instructed to fixate on a crosshair in

the center of the screen and let their mind wander; (2) 2-back Working Memory (M),

where participants were presented with a continuous sequence of individual geometric

shapes and were instructed to press a button whenever the current shape was the

same as the shape that appeared two shapes before; (3) Math/arithmetic (A), where

participants were presented with simple arithmetic operations, involving three numbers

between 1 and 10 and two operands (either addition or subtraction); and (4) Video (V),

where participants watched a video of a fish tank from a single point of view with

different types of fish swimming into an out of the frame, and were instructed to press a

button when a red crosshair appeared on a clown fish and another when it appeared on

any other type of fish. For arithmetic, the operations remained on the screen for 4 s and

successive trials were separated by a blank screen that appeared for 1 s, yielding a

total of 36 operations per each 180s block. For video, the targets appeared for 200 ms

with a total of 16 targets during each of the 180s blocks. The order of task blocks was

randomized such that the same task did not appear in two consecutive blocks, and the

same ordering of tasks was used for all participants. The randomized task order was R-

M-V-A-M-R-A-V.

1151

1152   The fMRI data were acquired on a Siemens 7 Tesla MRI scanner equipped with a 32-

1153   channel head coil using a whole-brain echo planar imaging (EPI) sequence (repetition

1154   time [TR] = 1.5 s, echo time [TE] = 25 ms, and voxel size = 2 mm isotropic). A total of

1155   1017 volumes were acquired while participants performed the continuous multitask

1156   paradigm.

1157

Functional and anatomical MR images were preprocessed using the Configurable

Pipeline for the Analysis of Connectomes (C-PAC version 0.3.4; https://fcp-

indi.github.io/docs/user/index.html). We used the preprocessing utilized in a previous

study (Saggar et al., 2018). Briefly, the fMRI data preprocessing steps included ANTS

registration into MNI152 space, slice timing correction, motion correction, skull stripping,

grand mean scaling, spatial smoothing (FWHM of 4 mm), and temporal band-pass

filtering (0.009 Hz < f < 0.08Hz). For each ROI, nuisance signal correction was

performed by regressing out linear and quadratic trends, physiological noise (white

matter and cerebrospinal fluid), motion-related noise (three translational and three

rotational head-motion parameters) using the Volterra expansion (Friston et al., 1996)

(i.e., six parameters, their temporal derivatives, and each of these values squared), and

residual signal unrelated to neural activity extracted using the CompCor algorithm

(Behzadi et al., 2007) (i.e., five principal components derived from noise regions in

which the time-series data were unlikely to be modulated by neural activity). The

resulting data were brought to 3 mm MNI space, and the mean time series was

extracted from 375 pre-defined regions-of-interest (ROIs) using the Shine et al. (Shine

et al., 2016) atlas. The atlas includes 333 cortical regions from the Gordon et al.

(Gordon et al., 2016) atlas, 14 subcortical regions from the Harvard-Oxford subcortical

atlas, and 28 cerebellar regions from the SUIT atlas (Diedrichsen et al., 2009).

Individual ROIs with zero variance were excluded prior to computing attractor transition

networks.

1179

1180   The behavioral data included both responses and reaction times for Working Memory,

1181   Math, and Video tasks. Participants were instructed to respond as quickly and

1182   accurately as possible with only one response per question. Behavior scores including

1183   the percent correct, percent missed, and response times for Working Memory (M), Math

1184   (A), and Video (V) tasks were computed for each participant.

1185

References

Abbott, L.F., Chance, F.S., 2005. Drivers and modulators from push-pull and balanced

synaptic input. Prog. Brain Res. 149, 147–155.

Allen, E.A., Damaraju, E., Plis, S.M., Erhardt, E.B., Eichele, T., Calhoun, V.D., 2014.

Tracking whole-brain connectivity dynamics in the resting state. Cereb. Cortex 24,

663–676.

Baker, A.P., Brookes, M.J., Rezek, I.A., Smith, S.M., Behrens, T., Probert Smith, P.J.,

Woolrich, M., 2014. Fast transient networks in spontaneous human brain activity.

Elife 3, e01867.

Ban, H., Kalies, W.D., 2006. A Computational Approach to Conley's Decomposition

Theorem. Journal of Computational and Nonlinear Dynamics.

https://doi.org/10.1115/1.2338651

Barber, A.D., Lindquist, M.A., DeRosse, P., Karlsgodt, K.H., 2018. Dynamic Functional

Connectivity States Reflecting Psychotic-like Experiences. Biological Psychiatry:

Cognitive Neuroscience and Neuroimaging 3, 443–453.

Behzadi, Y., Restom, K., Liau, J., Liu, T.T., 2007. A component based noise correction

method (CompCor) for BOLD and perfusion based fMRI. Neuroimage 37, 90–101.

Belkin, M., Niyogi, P., 2003. Laplacian Eigenmaps for Dimensionality Reduction and

Data Representation. Neural Comput. 15, 1373–1396.

Bonneel, N., van de Panne, M., Paris, S., Heidrich, W., 2011. Displacement

interpolation using Lagrangian mass transport, in: Proceedings of the 2011

SIGGRAPH Asia Conference, SA '11. Association for Computing Machinery, New

York, NY, USA, pp. 1–12.

Breakspear, M., 2017. Dynamic models of large-scale brain activity. Nat. Neurosci. 20,

340–352.

Buxton, R.B., Wong, E.C., Frank, L.R., 1998. Dynamics of blood flow and oxygenation

changes during brain activation: the balloon model. Magn. Reson. Med. 39, 855–

864.

Buzsaki, G., 2006. Rhythms of the Brain. Oxford University Press.

Cabral, J., Kringelbach, M.L., Deco, G., 2017. Functional connectivity dynamically

evolves on multiple time-scales over a static structural connectome: Models and

mechanisms. Neuroimage 160, 84–96.

Carlsson, G., 2009. Topology and data. Bull. Am. Math. Soc. 46, 255–308.

Carlsson, G., Mémoli, F., Ribeiro, A., Segarra, S., 2013. Axiomatic construction of

hierarchical clustering in asymmetric networks, in: 2013 IEEE International

Conference on Acoustics, Speech and Signal Processing. pp. 5219–5223.

Cavanna, F., Vilas, M.G., Palmucci, M., Tagliazucchi, E., 2018. Dynamic functional

connectivity and brain metastability during altered states of consciousness.

Neuroimage 180, 383–395.

Chazal, F., Michel, B., 2021. An Introduction to Topological Data Analysis: Fundamental

and Practical Aspects for Data Scientists. Front Artif Intell 4, 667963.

Chowdhury, S., Mémoli, F., 2019. The Gromov–Wasserstein distance between

networks and stable network invariants. Inf Inference 8, 757–787.

Civier, O., Smith, R.E., Yeh, C.-H., Connelly, A., Calamante, F., 2019. Is removal of

weak connections necessary for graph-theoretical analysis of dense weighted

structural connectomes from diffusion MRI? Neuroimage 194, 68–81.

Cummins, B., Gedeon, T., Harker, S., Mischaikow, K., Mok, K., 2016. Combinatorial

Representation of Parameter Space for Switching Networks. SIAM J. Appl. Dyn.

Syst. 15, 2176–2212.

Deco, G., Jirsa, V.K., 2012. Ongoing Cortical Activity at Rest: Criticality, Multistability,

and Ghost Attractors. Journal of Neuroscience.

https://doi.org/10.1523/jneurosci.2523-11.2012

Deco, G., Jirsa, V.K., McIntosh, A.R., 2011. Emerging concepts for the dynamical

organization of resting-state activity in the brain. Nat. Rev. Neurosci. 12, 43–56.

Deco, G., Ponce-Alvarez, A., Hagmann, P., Romani, G.L., Mantini, D., Corbetta, M.,

2014. How Local Excitation–Inhibition Ratio Impacts the Whole Brain Dynamics. J.

Neurosci. 34, 7886–7898.

Deco, G., Ponce-Alvarez, A., Mantini, D., Romani, G.L., Hagmann, P., Corbetta, M.,

2013. Resting-state functional connectivity emerges from structurally and

dynamically shaped slow linear fluctuations. J. Neurosci. 33, 11239–11252.

Diedrichsen, J., Balsters, J.H., Flavell, J., Cussans, E., Ramnani, N., 2009. A

probabilistic MR atlas of the human cerebellum. Neuroimage 46, 39–46.

Díez-Cirarda, M., Strafella, A.P., Kim, J., Peña, J., Ojeda, N., Cabrera-Zubizarreta, A.,

Ibarretxe-Bilbao, N., 2018. Dynamic functional connectivity in Parkinson's disease

patients with mild cognitive impairment and normal cognition. Neuroimage Clin 17,

847–855.

Du, M., Zhang, L., Li, L., Ji, E., Han, X., Huang, G., Liang, Z., Shi, L., Yang, H., Zhang,

Z., 2021. Abnormal transitions of dynamic functional connectivity states in bipolar

disorder: A whole-brain resting-state fMRI study. J. Affect. Disord. 289, 7–15.

Edelsbrunner, H., Morozov, D., 2013. Persistent Homology: Theory and Practice.

European Congress of Mathematics Kraków, 2 – 7 July, 2012 31–50.

Esfahlani, F.Z., Jo, Y., Faskowitz, J., Byrge, L., Kennedy, D.P., Sporns, O., Betzel, R.F.,

2020. High-amplitude cofluctuations in cortical activity drive functional connectivity.

Proc. Natl. Acad. Sci. U. S. A. 117, 28393–28401.

Faskowitz, J., Esfahlani, F.Z., Jo, Y., Sporns, O., Betzel, R.F., 2020. Edge-centric

functional network representations of human cerebral cortex reveal overlapping

system-level architecture. Nat. Neurosci. 23, 1644–1654.

Flamary, R., Courty, N., Gramfort, A., Alaya, M., Laetitia, B.A.C.S., 2021. Pot: Python

optimal transport. Journal of Machine Learning Research 22, 1–8.

Fox, M.D., Greicius, M., 2010. Clinical applications of resting state functional

connectivity. Front. Syst. Neurosci. 4, 19.

Friston, K.J., Harrison, L., Penny, W., 2003. Dynamic causal modelling. Neuroimage 19,

1273–1302.

Friston, K.J., Mechelli, A., Turner, R., Price, C.J., 2000. Nonlinear responses in fMRI:

the Balloon model, Volterra kernels, and other hemodynamics. Neuroimage 12,

466–477.

Friston, K.J., Williams, S., Howard, R., Frackowiak, R.S., Turner, R., 1996. Movement-

related effects in fMRI time-series. Magn. Reson. Med. 35, 346–355.

Gameiro, M., Mischaikow, K., Kalies, W., 2004. Topological characterization of spatial-

temporal chaos. Phys. Rev. E Stat. Nonlin. Soft Matter Phys. 70, 035203.

Garland, J., Bradley, E., Meiss, J.D., 2016. Exploring the topology of dynamical

reconstructions. Physica D 334, 49–59.

Garrity, A.G., Pearlson, G.D., McKiernan, K., Lloyd, D., Kiehl, K.A., Calhoun, V.D.,

2007. Aberrant "Default Mode" Functional Connectivity in Schizophrenia. AJP 164,

450–457.

Geniesse, C., Chowdhury, S., Saggar, M., 2022. NeuMapper: A scalable computational

framework for multiscale exploration of the brain's dynamical organization. Network

Neuroscience. https://doi.org/10.1162/netn_a_00229

Geniesse, C., Sporns, O., Petri, G., Saggar, M., 2019. Generating dynamical

neuroimaging spatiotemporal representations (DyNeuSR) using topological data

analysis. Netw Neurosci 3, 763–778.

Giscard, P.-L., Kriege, N., Wilson, R.C., 2019. A General Purpose Algorithm for

Counting Simple Cycles and Simple Paths of Any Length. Algorithmica.

https://doi.org/10.1007/s00453-019-00552-1

Giusti, C., Pastalkova, E., Curto, C., Itskov, V., 2015. Clique topology reveals intrinsic

geometric structure in neural correlations. Proceedings of the National Academy of

Sciences. https://doi.org/10.1073/pnas.1506407112

Golos, M., Jirsa, V., Daucé, E., 2015. Multistability in Large Scale Models of Brain

Activity. PLoS Comput. Biol. 11, e1004644.

Gonzalez-Castillo, J., Caballero-Gaudes, C., Topolski, N., Handwerker, D.A., Pereira,

F., Bandettini, P.A., 2019. Imaging the spontaneous flow of thought: Distinct periods

of cognition contribute to dynamic functional connectivity during rest. Neuroimage

202, 116129.

Gonzalez-Castillo, J., Hoy, C.W., Handwerker, D.A., Robinson, M.E., Buchanan, L.C.,

Saad, Z.S., Bandettini, P.A., 2015. Tracking ongoing cognition in individuals using

brief, whole-brain functional connectivity patterns. Proc. Natl. Acad. Sci. U. S. A.

112, 8762–8767.

Gordon, E.M., Laumann, T.O., Adeyemo, B., Huckins, J.F., Kelley, W.M., Petersen,

S.E., 2016. Generation and Evaluation of a Cortical Area Parcellation from Resting-

State Correlations. Cereb. Cortex 26, 288–303.

Gordon, E.M., Laumann, T.O., Gilmore, A.W., Newbold, D.J., Greene, D.J., Berg, J.J.,

Ortega, M., Hoyt-Drazen, C., Gratton, C., Sun, H., Hampton, J.M., Coalson, R.S.,

Nguyen, A.L., McDermott, K.B., Shimony, J.S., Snyder, A.Z., Schlaggar, B.L.,

Petersen, S.E., Nelson, S.M., Dosenbach, N.U.F., 2017. Precision Functional

Mapping of Individual Human Brains. Neuron 95, 791–807.e7.

Hagmann, P., Cammoun, L., Gigandet, X., Meuli, R., Honey, C.J., Wedeen, V.J.,

Sporns, O., 2008. Mapping the Structural Core of Human Cerebral Cortex. PLoS

Biology. https://doi.org/10.1371/journal.pbio.0060159

Hansen, E.C.A., Battaglia, D., Spiegler, A., Deco, G., Jirsa, V.K., 2015. Functional

connectivity dynamics: Modeling the switching behavior of the resting state.

NeuroImage. https://doi.org/10.1016/j.neuroimage.2014.11.001

Hutchison, R.M., Womelsdorf, T., Allen, E.A., Bandettini, P.A., Calhoun, V.D., Corbetta,

M., Della Penna, S., Duyn, J.H., Glover, G.H., Gonzalez-Castillo, J., Handwerker,

D.A., Keilholz, S., Kiviniemi, V., Leopold, D.A., de Pasquale, F., Sporns, O., Walter,

M., Chang, C., 2013. Dynamic functional connectivity: promise, issues, and

interpretations. Neuroimage 80, 360–378.

Kalies, W.D., Mischaikow, K., VanderVorst, R.C.A.M., 2005. An Algorithmic Approach to

Chain Recurrence. Found. Comut. Math. 5, 409–449.

Kelso, J.A.S., 2012. Multistability and metastability: understanding dynamic coordination

in the brain. Philos. Trans. R. Soc. Lond. B Biol. Sci. 367, 906–918.

Kelso, J.A.S., 1995. Dynamic Patterns: The Self-organization of Brain and Behavior.

MIT Press.

Kim, W., Mémoli, F., 2021. Spatiotemporal Persistent Homology for Dynamic Metric

Spaces. Discrete Comput. Geom. 66, 831–875.

Laumann, T.O., Snyder, A.Z., Mitra, A., Gordon, E.M., Gratton, C., Adeyemo, B.,

Gilmore, A.W., Nelson, S.M., Berg, J.J., Greene, D.J., McCarthy, J.E., Tagliazucchi,

E., Laufs, H., Schlaggar, B.L., Dosenbach, N.U.F., Petersen, S.E., 2017. On the

Stability of BOLD fMRI Correlations. Cereb. Cortex 27, 4719–4732.

Leonardi, N., Van De Ville, D., 2015. On spurious and real fluctuations of dynamic

functional connectivity during rest. NeuroImage.

https://doi.org/10.1016/j.neuroimage.2014.09.007

Li, J., Zhang, D., Liang, A., Liang, B., Wang, Z., Cai, Y., Gao, M., Gao, Z., Chang, S.,

Jiao, B., Huang, R., Liu, M., 2017. High transition frequencies of dynamic functional

connectivity states in the creative brain. Sci. Rep. 7, 46072.

Lui, S., Wu, Q., Qiu, L., Yang, X., Kuang, W., Chan, R.C.K., Huang, X., Kemp, G.J.,

Mechelli, A., Gong, Q., 2011. Resting-state functional connectivity in treatment-

resistant depression. Am. J. Psychiatry 168, 642–648.

Mandeville, J.B., Marota, J.J., Ayata, C., Zaharchuk, G., Moskowitz, M.A., Rosen, B.R.,

Weisskoff, R.M., 1999. Evidence of a cerebrovascular postarteriole windkessel with

delayed compliance. J. Cereb. Blood Flow Metab. 19, 679–689.

Meer, J.N. van der, Breakspear, M., Chang, L.J., Sonkusare, S., Cocchi, L., 2020.

Movie viewing elicits rich and reliable brain state dynamics. Nat. Commun. 11,

5004.

Mémoli, F., 2007. On the use of Gromov-Hausdorff distances for shape comparison.

Munch, E., 2013. Applications of persistent homology to time varying systems.

Munn, B. R., Müller, E. J., Wainstein, G. & Shine, J. M., 2021. The ascending arousal

system shapes neural dynamics to mediate awareness of cognitive states. Nat

Commun 12, 6016.

Myers, A., Munch, E., Khasawneh, F.A., 2019. Persistent homology of complex

networks for dynamic state detection. Phys Rev E 100, 022314.

Ou, J., Xie, L., Wang, P., Li, X., Zhu, D., Jiang, R., Wang, Y., Chen, Y., Zhang, J., Liu,

T., 2013. Modeling brain functional dynamics via hidden Markov models, in: 2013

6th International IEEE/EMBS Conference on Neural Engineering (NER). pp. 569–

572.

Perea, J.A., 2019. Topological Time Series Analysis. Not. Am. Math. Soc. 66, 686–694.

Petri, G., Expert, P., Turkheimer, F., Carhart-Harris, R., Nutt, D., Hellyer, P.J.,

Vaccarino, F., 2014. Homological scaffolds of brain functional networks. J. R. Soc.

Interface 11, 20140873.

Peyré, G., Cuturi, M., 2019. Computational Optimal Transport: With Applications to Data

Science. Now Publishers.

Peyré, G., Cuturi, M., Solomon, J., 2016. Gromov-Wasserstein Averaging of Kernel and

Distance Matrices, in: Balcan, M.F., Weinberger, K.Q. (Eds.), Proceedings of The

33rd International Conference on Machine Learning, Proceedings of Machine

Learning Research. PMLR, New York, New York, USA, pp. 2664–2672.

Poincaré, H., 1967. New Methods of Celestial Mechanics. National Aeronautics and

Space Administration.

Preti, M.G., Bolton, T.A., Van De Ville, D., 2017. The dynamic functional connectome:

State-of-the-art and perspectives. Neuroimage 160, 41–54.

Qi, C.R., Su, H., Mo, K., Guibas, L.J., 2017. Pointnet: Deep learning on point sets for 3d

classification and segmentation, in: Proceedings of the IEEE Conference on

Computer Vision and Pattern Recognition. pp. 652–660.

Qin, D., Gammeter, S., Bossard, L., Quack, T., van Gool, L., 2011. Hello neighbor:

Accurate object retrieval with k-reciprocal nearest neighbors, in: CVPR 2011. pp.

777–784.

Quinn, A.J., Vidaurre, D., Abeysuriya, R., Becker, R., Nobre, A.C., Woolrich, M.W.,

2018. Task-Evoked Dynamic Network Analysis Through Hidden Markov Modeling.

Front. Neurosci. 12, 603.

Rabany, L., Brocke, S., Calhoun, V.D., Pittman, B., Corbera, S., Wexler, B.E., Bell,

M.D., Pelphrey, K., Pearlson, G.D., Assaf, M., 2019. Dynamic functional

connectivity in schizophrenia and autism spectrum disorder: Convergence,

1386   divergence and classification. Neuroimage Clin 24, 101966.

1387 Rabiner, L.R., 1989. A tutorial on hidden Markov models and selected applications in

1388   speech recognition. Proc. IEEE 77, 257–286.

1389 Rezek, I., Roberts, S., 2005. Ensemble Hidden Markov Models with Extended

1390   Observation Densities for Biosignal Analysis, in: Husmeier, D., Dybowski, R.,

1391   Roberts, S. (Eds.), Probabilistic Modeling in Bioinformatics and Medical Informatics.

1392   Springer London, London, pp. 419–450.

1393 Saggar, M., Shine, J.M., Liégeois, R., Dosenbach, N.U.F., Fair, D., 2021. Precision

1394   dynamical mapping using topological data analysis reveals a unique hub-like

1395   transition state at rest. bioRxiv. https://doi.org/10.1101/2021.08.05.455149

1396 Saggar, M., Sporns, O., Gonzalez-Castillo, J., Bandettini, P.A., Carlsson, G., Glover, G.,

1397   Reiss, A.L., 2018. Towards a new approach to reveal dynamical organization of the

1398   brain using topological data analysis. Nat. Commun. 9, 1399.

1399 Saggar, M., Uddin, L.Q., 2019. Pushing the boundaries of psychiatric neuroimaging to

1400   ground diagnosis in biology. eNeuro 6, ENEURO.0384–19.2019.

1401 Schmitzer, B., Schnörr, C., 2013. Modelling Convex Shape Priors and Matching Based

1402   on the Gromov-Wasserstein Distance. J. Math. Imaging Vis. 46, 143–159.

1403 Shine, J.M., Bissett, P.G., Bell, P.T., Koyejo, O., Balsters, J.H., Gorgolewski, K.J.,

1404   Moodie, C.A., Poldrack, R.A., 2016. The Dynamics of Functional Brain Networks:

1405   Integrated Network States during Cognitive Task Performance. Neuron 92, 544–

1406   554.

1407 Singh, G., Mémoli, F., Carlsson, G.E., Others, 2007. Topological methods for the

1408   analysis of high dimensional data sets and 3d object recognition. PBG@

Eurographics 2.

Smith, S.M., Beckmann, C.F., Andersson, J., Auerbach, E.J., Bijsterbosch, J., Douaud,

G., Duff, E., Feinberg, D.A., Griffanti, L., Harms, M.P., Kelly, M., Laumann, T.,

Miller, K.L., Moeller, S., Petersen, S., Power, J., Salimi-Khorshidi, G., Snyder, A.Z.,

Vu, A.T., Woolrich, M.W., Xu, J., Yacoub, E., Uğurbil, K., Van Essen, D.C., Glasser,

M.F., WU-Minn HCP Consortium, 2013. Resting-state fMRI in the Human

Connectome Project. Neuroimage 80, 144–168.

Solomon, J., Peyré, G., Kim, V.G., Sra, S., 2016. Entropic metric alignment for

correspondence problems. ACM Trans. Graph. 35, 1–13.

Taghia, J., Cai, W., Ryali, S., Kochalka, J., Nicholas, J., Chen, T., Menon, V., 2018.

Uncovering hidden brain state dynamics that regulate performance and decision-

making during cognition. Nat. Commun. 9, 2505.

Tang, Y.-Y., Rothbart, M.K., Posner, M.I., 2012. Neural correlates of establishing,

maintaining, and switching brain states. Trends Cogn. Sci. 16, 330–337.

Tenenbaum, J.B., de Silva, V., Langford, J.C., 2000. A Global Geometric Framework for

Nonlinear Dimensionality Reduction. Science.

https://doi.org/10.1126/science.290.5500.2319

Titouan, V., Courty, N., Tavenard, R., Laetitia, C., Flamary, R., 2019. Optimal Transport

for structured data with application on graphs, in: Chaudhuri, K., Salakhutdinov, R.

(Eds.), Proceedings of the 36th International Conference on Machine Learning,

Proceedings of Machine Learning Research. PMLR, pp. 6275–6284.

Tognoli, E., Kelso, J.A.S., 2014. The metastable brain. Neuron 81, 35–48.

Topaz, C.M., Ziegelmeier, L., Halverson, T., 2015. Topological data analysis of

biological aggregation models. PLoS One 10, e0126383.

Tymochko, S., Munch, E., Khasawneh, F.A., 2020. Using Zigzag Persistent Homology

to Detect Hopf Bifurcations in Dynamical Systems. Algorithms 13, 278.

Ulmer, M., Ziegelmeier, L., Topaz, C.M., 2019. A topological approach to selecting

models of biological experiments. PLoS One 14, e0213679.

Umeyama, S., 1988. An eigendecomposition approach to weighted graph matching

problems. IEEE Trans. Pattern Anal. Mach. Intell. 10, 695–703.

van den Heuvel, M.P., Hulshoff Pol, H.E., 2010. Exploring the brain network: A review

on resting-state fMRI functional connectivity. Eur. Neuropsychopharmacol. 20, 519–

534.

Van Der Maaten, L., Postma, E., Van den Herik, J., 2009. Dimensionality reduction: a

comparative. J. Mach. Learn. Res.

Van Essen, D.C., Smith, S.M., Barch, D.M., Behrens, T.E.J., Yacoub, E., Ugurbil, K.,

WU-Minn HCP Consortium, 2013. The WU-Minn Human Connectome Project: an

overview. Neuroimage 80, 62–79.

Vidaurre, D., Smith, S.M., Woolrich, M.W., 2017. Brain network dynamics are

hierarchically organized in time. Proc. Natl. Acad. Sci. U. S. A. 114, 12827–12832.

Wang, X.-J., 2002. Probabilistic decision making by slow reverberation in cortical

circuits. Neuron 36, 955–968.

Wilson, H. R. & Cowan, J. D., 1972. Excitatory and Inhibitory Interactions in Localized

Populations of Model Neurons. *Biophys J* **12**, 1–24.

Wilson, H. R. & Cowan, J. D., 1973. A mathematical theory of the functional dynamics

of cortical and thalamic nervous tissue. *Kybernetik* **13**, 55–80.

Wong, K.-F., Wang, X.-J., 2006. A recurrent network mechanism of time integration in

perceptual decisions. J. Neurosci. 26, 1314–1328.

Xu, H., Luo, D., Carin, L., 2019. Scalable Gromov-Wasserstein learning for graph

partitioning and matching. Adv. Neural Inf. Process. Syst.

Zalesky, A., Fornito, A., Cocchi, L., Gollo, L.L., Breakspear, M., 2014. Time-resolved

resting-state brain networks. Proc. Natl. Acad. Sci. U. S. A. 111, 10341–10346.

Zamani Esfahlani, F., Jo, Y., Faskowitz, J., Byrge, L., Kennedy, D.P., Sporns, O.,

Betzel, R.F., 2020. High-amplitude cofluctuations in cortical activity drive functional

connectivity. Proc. Natl. Acad. Sci. U. S. A. 117, 28393–28401.

Zaslavskiy, M., Bach, F., Vert, J.-P., 2009. A path following algorithm for the graph

matching problem. IEEE Trans. Pattern Anal. Mach. Intell. 31, 2227–2242.

Zhang, M., Kalies, W.D., Kelso, J.A.S., Tognoli, E., 2020. Topological portraits of

multiscale coordination dynamics. J. Neurosci. Methods 339, 108672.

Zhang, M., Sun, Y., Saggar, M., 2022. Cross-attractor repertoire provides new

perspective on structure-function relationship in the brain.

https://doi.org/10.1101/2020.05.14.097196

1471