Deep neural network automated segmentation of cellular structures in volume electron microscopy

Benjamin Gallusser[1,2,&], Giorgio Maltese[1,&], Giuseppe Di Caprio[1,3,&], Tegy John Vadakkan[1], Anwesha Sanyal[1,4], Elliott Somerville[1], Mihir Sahasrabudhe[1,5], Justin O'Connor[6], Martin Weigert[2,] Tom Kirchhausen[1,3,4,*]

[1]Program in Cellular and Molecular Medicine, Boston Children's Hospital, 200 Longwood Ave, Boston, MA 02115, USA

[2]Institute of Bioengineering, School of Life Sciences, École Polytechnique Fédérale de Lausanne, Switzerland

[3]Department of Pediatrics, Harvard Medical School, 200 Longwood Ave, Boston, MA 02115, USA

[4]Department of Cell Biology, Harvard Medical School, 200 Longwood Ave, Boston, MA 02115, USA

[5]Université Paris-Saclay, Centrale Supélec, Mathématiques et Informatique pour la Complexité et les Systèmes, 91190, Gif-sur-Yvette, France

[6]Department of Biological Chemistry & Molecular Pharmacology, Harvard Medical School, 200 Longwood Ave, Boston, MA 02115, USA

[&]Equal contribution

[*] Corresponding author:
Dr. Tom Kirchhausen
Harvard Medical School
200 Longwood Ave
Boston, MA 02115
kirchhausen@crystal.harvard.edu
ORCID 0000-0003-0559-893X
phone: +1 617 713 8888
fax: +1 617 713 8898

Running title: Computer-aided detection of cellular structures

35   *Keywords:* whole-cell FIB-SEM, deep learning, machine learning, *Automated Segmentation of*

36   *intracellular substructures in Electron Microscopy* (ASEM), nuclear pores, clathrin coated pits and

37   vesicles

Summary

Recent advances in automated segmentation using deep neural network models allow identification of subcellular structures. This study describes a new pipeline to train a convolutional network for rapid and efficient detection of structures of wide range in size and complexity.

Abstract

Three-dimensional electron-microscopy is an important imaging modality in contemporary cell biology. Identification of intracellular structures is laborious and time-consuming, however, and seriously impairs effective use of a potentially powerful tool. Resolving this bottleneck is therefore a critical next step in frontier biomedical imaging. We describe *Automated Segmentation of intracellular substructures in Electron Microscopy* (ASEM), a new pipeline to train a convolutional network to detect structures of wide range in size and complexity. We obtain for each structure a dedicated model based on a small number of sparsely annotated ground truth annotations from only one or two cells. To improve model generalization to different imaging conditions, we developed a rapid, computationally effective strategy to refine an already trained model by including a few additional annotations. We show the successful automated identification of mitochondria, Golgi apparatus, endoplasmic reticulum, nuclear pore complexes, clathrin coated pits and coated vesicles, and caveolae in cells imaged by focused ion beam scanning electron microscopy with quasi-isotropic resolution.

Introduction

Three-dimensional, high-resolution imaging provides a snapshot of the internal organization of a cell at a defined time point and in a defined physiological state. Focused ion beam scanning electron microscopy (FIB-SEM) yields nearly isotropic, nanometer-level resolution, three-dimensional images by sequential imaging of the surface layer of a sample, which is then etched away with an ion beam to reveal the layer beneath. FIB-SEM technology continues to develop, and it can be a particularly valuable contemporary tool for imaging the complete volume of a cell, but segmentation of the three-dimensional data sets and subsequent analysis of the results are substantial hurdles, as the images are far too large to interpret by inspection (Heinrich et al., 2021)

The widespread success of machine learning in bioimage informatics has recently inspired the application of deep-learning approaches to automated segmentation. Examples using deep convolutional networks for data with anisotropic resolution include DeepEM3D (Zeng et al., 2017) and CDeep-3M (Haberl et al., 2018), for segmentation of mitochondria and Golgi apparatus with extensive post-processing (Mekuč et al., 2020, 2022), as well as cell-organelle segmentation in quasi-isotropic FIB-SEM data of beta cells (Müller et al., 2020). A pipeline created by the COSEM project (Heinrich et al., 2021) enables automated whole-cell segmentation of 35 organelles from relatively sparse but very precise 3D ground truth annotations from FIB-SEM data of cells prepared by high pressure freezing and freeze substitution (HPFS), obtained at 3-5 nm voxel size with approximately isotropic resolution The most common strategy used by the COSEM project involved training with ground truth annotations from 2-3 different classes of objects at the same time, typically at a high computational cost (500,000 or more training iterations) (Heinrich et al., 2021).

The current approaches all suffer from a demand for substantial computational resources, and they generally require a large set of precise manual annotations. Both requirements limit their practical applicability. We describe here the development and use of a new deep learning pipeline called *Automated Segmentation of intracellular substructures in Electron Microscopy* (ASEM), which can detect structures of a wide range in size and complexity using deep neural networks trained on a limited number of loosely marked ground truth annotations. ASEM includes a semi-automated graph-cut procedure we developed to assist in the tedious task of ground truth preparation and a computationally efficient transfer-learning approach with a fine-tuning protocol that can be used without the need for high-end specialized CPU/GPU workstations.

We illustrate here the utility of ASEM by describing the results of its application to data from
several types of cells, including FIB-SEM images made publicly available by the COSEM Project
(Heinrich et al., 2021). We note that while cellular samples have traditionally been processed by
chemical fixation (CF) and staining at room temperature, HPFS at cryogenic temperatures (as
was the case for the COSEM Project data) yields a substantial increase in the preservation of
many complex cellular features. We applied ASEM to three-dimensional FIB-SEM images of cells
prepared by either CF or HPFS. We validated our approach by segmenting mitochondria,
endoplasmic reticulum (ER) and Golgi apparatus, as these organelles had been studied
previously in similar efforts (Mekuč et al., 2020, 2022)(Heinrich et al., 2021; Liu et al., 2020), and
then used ASEM to recognize much smaller structures, nuclear pores and clathrin coated pits
and vesicles. For nuclear pores in interphase, we can segment nearly all the pores in the nuclear
membrane. We can therefore directly analyze the range of membrane-pore diameters, even for
a single cell in a particular physiological state. For clathrin coated pits, we show that a relatively
restricted training set leads to accurate segmentation of coated pits at all stages of their
maturation as well as coated vesicles, the final step after fission from the originating membrane,
and we can derive morphological metrics consistent with the classical constant-growth assembly
model (Ehrlich et al., 2004; Kirchhausen, 1993, 2009; Willy et al., 2021).
108
109 All datasets, code and models are open-source (https://github.com/kirchhausenlab/incasem,
110 https://open.quiltdata.com/b/incasem), so that other users working with images acquired with the
111 same or somewhat different imaging conditions can generate their own predictive models and
112 benefit from our pre-trained models, either directly or by adapting them by fine-tuning, without the
113 need for specialized CPU/GPU workstations.

Results

FIB-SEM imaging of cells

We obtained three-dimensional focused ion beam scanning electron microscopy (FIB-SEM) data sets for different types of adherent mammalian cells grown in culture (Table S1). The samples we imaged were prepared either by conventional chemical fixation and staining with osmium and uranyl acetate at room temperature (CF) or by fixation and similar staining at very low temperature using high pressure freezing and freeze substitution (HPFS), a protocol that substantially increases sample preservation (Hoffman et al., 2020; Studer et al., 2008; Xu et al., 2021). To image a volume of a cell, we used a block-face crossbeam FIB-SEM with nominal isotropic resolution of 5 or 10 nm per voxel; each image stack, obtained during 1-2 days of continuous FIB-SEM operation, was about 15-20 GB in size and contained ~ 2000 registered sequential TIFF files and spanned a volume of roughly 2000^3 voxels corresponding to large parts of each cell. These volume datasets were used to train the deep learning pipeline for automated segmentation of subcellular structures and to explore the effects of different fixation and staining procedures on the outcome of the segmentation tasks.

We also tested the performance of our deep learning models with a small number of FIB-SEM images from HPFS preparations of complete cells, obtained from the publicly available OpenOrganelle initiative (Xu et al., 2021) (Table S1). They were acquired by the COSEM team at Janelia Research Campus at a nominal resolution of 4 x 4 x 3-5 nm per voxel with a custom-modified FIB-SEM as part of their concurrent efforts to develop methodology for automated organelle segmentation aided by deep learning.

As described below, using the specific models generated with our deep learning pipeline (Fig. 1), we could reliably identify subcellular structures ranging in size and complexity from mitochondria, endoplasmic reticulum, Golgi apparatus to nuclear pores, clathrin coated pits, coated vesicles, and caveolae.

Ground truth annotation

The first step in any common machine-learning procedure is to create pixelwise "ground truth" annotations -- to be used for training a specific segmentation model. In the present work, we used a modest number of relatively loosely annotated manual segmentations of the subcellular structure of interest (see Methods for details). These segmentations came from arbitrarily chosen, diverse, and not necessarily overlapping regions from one or more cells (Table S2). As the

contrast and textural appearance of raw FIB-SEM images can vary substantially due to sample
preparation and imaging conditions, we make heavy use of augmentations, a technique
commonly used to train deep neural networks (Shorten and Khoshgoftaar, 2019). We applied a
series of randomized transformations to each of the manual segmentations to generate a set of
the required size (see Methods and Table S3). The various applications described here validate
this approach, which greatly reduces the manual annotation effort and makes broad application
feasible.

We obtained ground truth annotations for mitochondria and Golgi apparatus, portions of
endoplasmic reticulum (ER), 19 endocytic clathrin coated pits at the plasma membrane, and 12
nuclear pores on the nuclear envelope (Table S4). We annotated mitochondria using the carving
module in Ilastik (Berg et al., 2019) and if required, edited the annotation manually using VAST
(Berger et al., 2018), a volume annotation and segmentation tool for manual and semi-automatic
labeling of large 3D image stacks (see example in Fig. S1 and Video 1). We annotated the more
complex Golgi apparatus and ER with a dedicated graph cut-assisted, semi-automated annotation
tool we developed and describe in Methods that accelerated the annotation time by 5-10-fold;
when needed, we corrected the annotation locally with VAST (see example in Fig. S2). We
generated manually, also with VAST, the ground truth annotations for clathrin coated structures
and nuclear pores. In all cases, we applied the data augmentation procedure to the curated
manual annotations.

Deep learning segmentation pipeline
Our general training strategy (schematically represented in Fig. 1A) relied on a 3D convolutional
neural network (CNN) architecture based on a 3D U-Net (Çiçek et al., 2016) (Fig. S3); this
approach has been used previously for segmenting intracellular structures in electron microscopy
data (Heinrich et al., 2021; Plaza and Funke, 2018). For each organelle class, we used a single,
dedicated deep neural network, trained on augmented ground truth annotations generated from
a small number of annotations contained within subvolumes (~ 2-80 μm^3) of the FIB-SEM data
(Table S4). We used binary cross entropy as a loss function and trained each model for roughly
100k iterations on a single GPU (~23h), after which the training/validation loss converged to a
stable value (Fig. S4). To avoid overfitting, we cross-validated the evolution of the model
periodically during the training session, by monitoring the loss between the model prediction and
the subset of ground truth annotations in validation blocks of the FIB-SEM image not used for
training. The final model yielded a predicted map that assigned to each voxel a probability of

belonging to the structure (Fig. 1B), from which we derived a final binary map by setting a
threshold value of 0.5. These models, unique for a given organelle or structure, were then used
to find the specific cellular structure of interest in the FIB-SEM images of regions excluded from
training or of fully naïve cells that had not been used for training at all.

As previously noted by others, we also observed that the image contrast and texture of FIB-SEM
data can vary substantially between different acquisitions, depending not only on cell type and
mode of sample preparation (CF, HPFS), but unexpectedly also between adjacent cells of the
same type in the same Epon block (Fig. S5). We found empirically that while the neural network
could be trained to segment organelles successfully from samples prepared by the same mode
of preparation, a model trained with ground truth annotations from HPFS cells failed when applied
to CF treated cells, and vice versa. Although routinely implemented in our pipeline, contrast
normalization by contrast-limited adaptive histogram equalization (CLAHE) (Pizer et al., 1987;
Zuiderveld, 1994) of FIB-SEM data sets from different cells failed to improve the predictions
(Table S5). Novel use of local shape descriptors as an auxiliary learning task (Sheridan et al.,
2021) calculated from the ground truth annotations and representing high-level morphological
notions such as object size and distance to object boundary also did not improve model prediction.
As described below in detail, we resolved this problem by combining ground truth annotations
from both data sets for training.

Automated segmentation of organelles

We first applied ASEM to perform automated segmentation of FIB-SEM images from cells
prepared by CF of nominal 5 nm isotropic resolution and relatively high contrast (Fig. 2 and Video
2); the summary shown in Table S6 illustrates the predictive performance obtained for models
specific for mitochondria, ER and Golgi apparatus. For mitochondria, we selected from Cell 1 a
training block of about 462×10^6 voxels and used semi-automated annotation to generate ground
truth annotations for the mitochondria contained within this volume, representing roughly 8% of
all voxels (Table S6); Model performance was assessed every 1,000 iterations during the training
phase by calculating the cross-entropy loss between the current prediction and the mitochondria
ground truth within a validation block (not used during training). Additional smaller validation
blocks (Table S4) containing mitochondria ground truth from naïve Cells 2, 3 and 6 were used to
avoid overfitting during the training phase and to validate the model performance by measuring
the validation losses. Validation losses rapidly converged within 20,000 - 40,000 training
iterations, resulting in a relatively high F1 score (0.91) for Cell 1 and lower values for the data

from naïve Cells 2, 3 and 6 (0.47, 0.66, 0.81, cf. Table S6). Similar results were obtained when

training with ground truth annotations from Cell 2 instead of Cell 1 (Table S6); the validation losses

also converged within 20,000-40,000 training iterations with good F1 scores for Cell 2 (0.87) and

naïve Cells 1 and 3 (0.89, 0.74) and a slightly lower score for Cell 6 (0.7) with no further

improvement with additional training iterations.

To find additional ways to enhance the generalization ability of the model, we modified the training

pipeline to combine the ground truth annotations from Cells 1 and 2. We first tested the

performance of the mitochondria model using the validation blocks in naïve Cells 3 and 6. In this

case, the new model had a significantly improved performance (Table S6), reflected by even

higher F1 scores for naïve Cells 3 and 6 (0.75, 0.88), but only after 95,000 - 115,000 iterations

(Fig. S4). A similar improvement in model performance was observed for ER predictions when

we first combined ground truth annotations of Cells 1 and 2. The new ER model, then used to

predict ER in Cells 1, 2 and naïve Cells 3 and 6, led to generally improved F1 scores of 0.95,

0.90, 0.92 and 0.77, respectively (Table S6). Consistent with F1 scores smaller than the optimal

value of 1, we observed by visual inspection a small number of false negative (yellow arrows) or

false positive (red arrows) assignments as highlighted in Fig. 2A (see also Movie 2). Combining

ground truth annotations from Cells 19 and 20 during training to predict the more complex Golgi

apparatus in naïve Cells 3 or 6 marginally outperformed the models trained with either Cell 1 or

Cell 2 (Table S6), also illustrated with one example of visual inspection of ground truth annotations

and predictions showing instances of false positive assignments (red arrows, Fig. 2B). Thus, the

predictive performance of a model could often be improved by using a model obtained by jointly

training with ground truth annotations from two cells instead of training with data from one cell or

the other.

We also tested the performance of ASEM using FIB-SEM images and ground truth annotations

acquired by the OpenOrganelle initiative (Xu et al., 2021) (Table S1). These cells were prepared

by HPFS and imaged with higher isotropic resolution (4 x 4 x 3-5 nm) but lower contrast). We

examined the ability of our training pipeline to segment these data sets and focused on

mitochondria and ER but not Golgi due to a lack of a sufficient number of ground truth annotations

for Golgi objects in the available OpenOrganelle datasets (Table S7). We generated independent

models for mitochondria and ER, by training with corresponding combined ground truth

annotations from Hela Cells 19 and 20, followed by model performance verification using unseen

ground truth annotations from the same Hela cells or from different types of naïve cells not used

for training (Cell 21 Jurkat-1 and Cell 22 Macrophage-2, Table S7). Our pipeline performed well

after ~ 100K training cycles and managed to segment mitochondria in unseen data from each of

the two Hela cells used for training (F1 scores of 0.99, Table S7) and from unseen data from each

of the naïve Cell 21 Jurkat-1 or Cell 22 Macrophage-2 (F1 scores of 0.94 and 0.93; Table S7).

Automated segmentation of the ER was less efficient, requiring ~ 200K training cycles to reach

the highest model performance (F1 scores of 0.91, 0.80, 0.48 and 0.81, respectively; Table S7).

These first results indicate that our training strategy can create predictive models for successful

identification of mitochondria, ER and Golgi apparatus in cells prepared by CF and of

mitochondria and Golgi in samples prepared by HPFS.

To test the strength of combining ground truth annotations from two cells to train and then predict

on a naïve cell, we explored the tolerance of the training pipeline to modest variations in image

resolution. The results are shown for the representative FIB-SEM images in Figs. 3 and 4 and

Video 3 and 4 obtained for a naïve Cell 15 SVG-A prepared by HPFS acquired at an isotropic 5

x 5 x 5 nm (Table S4); visual inspection of the images show successful predicted segmentations

for mitochondria, ER and Golgi apparatus using models obtained by combined training with

ground truth annotations from Hela cells 19 and 20 also prepared by HPFS and whose FIB-SEM

images were acquired with mixed resolutions of 4 x 4 x 5.2 and 4 x 4 x 3.2 nm, respectively.

Because models generated with mitochondria or ER ground truth annotations from cells prepared

by CF were unable to predict well on cells prepared by HPFS and vice versa, we explored the

possibility of combining training data from both sample preparation protocols, using the same

training datasets from HEK293A Cells 1 and 2, prepared by CF, and Cells 19 and 20 Hela

prepared by HPFS. The mitochondria and the ER models performed nearly as well as specialized

single-organelle models on almost all validation data sets regardless of sample preparation

protocol used (Fig. 5, panel A and Table S8).

Fine-tuning

To improve the predictive performance with images from naïve cells, we explored the effect of

fine-tuning a pre-existing model on its segmenting accuracy, a simple implementation of transfer

learning (Weiss et al., 2016). As described in Methods, we started with an already trained model

and resumed model training for a low number of iterations (15,000) using only the new ground

truth annotations from the naïve cell; the new ground truth annotations, although resembling those

used for the first training, would typically have slightly different characteristics.

The following examples illustrate the range of results obtained upon implementation of fine-tuning

using HPFS FIB-SEM data. The ER model, first obtained after ~ 180,000 training cycles using

ground truth annotations from Hela Cells 19 and 20, was then fine-tuned for additional 12,000 or

6,000 training cycles with small amounts of ground truth data from either naïve Cell 21 Jurkat-1

or Cell 22 Macrophage-2; both fine-tuning cases showed a significant improvement in the F1

precision scores, from 0.48 to 0.69 and from 0.81 to 0.90, without affecting recall (Fig. S6, Table

S9); in other words, the model learned to correctly classify ER while at the same time reducing

the number of false positives by rejecting structures that appeared similar but did not belong to

the same semantic class (Fig. 5B). The next two cases of fine tuning illustrate little or no

improvement in predictive model performance for mitochondria in cells prepared by HPFS or CF

(Fig. 5C, S6 and Table S9). The model obtained after 95,000 training cycles using HPFS FIB-

SEM data from Hela Cells 19 and 20 showed similar F1 scores (0.93) for naïve Cell 21 Jurkat-1

or Cell 22 Macrophage-2 before or after fine-tuning for 7,000 cycles. Similarly, a mitochondria

model obtained after 95,000 training iterations using CF FIB-SEM data from Cells 1 and 2 and

then fine-tuned for additional 6,000 fine-tuning training steps using ground truth annotations from

Cells 3 or 6 showed either a significant increase (from 0.75 to 0.88) or no increase at all (0.88) in

F1 scores, respectively (Fig 5D and Table S9). The fine-tuning strategy could not adjust

mitochondria, ER or Golgi apparatus models generated using cells prepared by HPFS to predict

in naïve CF treated cells, and vice versa. We conclude that fine-tuning can be beneficial for

segmenting relatively large membrane-bound organelles particularly in cases where the pre-

trained model behaved poorly in naïve cells, but it could not resolve situations in which the staining

characteristics of the samples were extremely different, even though they had been prepared by

the same staining procedures.

Automated segmentation of nuclear pores

To test whether our pipeline can automatically identify and segment small subcellular structures,

we trained the neural network with ground truth annotations from nuclear pores, structures

embedded in the double-membrane nuclear envelope with membrane pore openings of ~100-

120 nm in diameter. We used FIB-SEM data with nominal 5 nm isotropic resolution from

interphase SVG-A and Hela cells imaged using HPFS to ensure minimal perturbations in the

structural organization of the nuclear pores and their surrounding inner and outer nuclear

membranes.

We used VAST to generate ground truth annotations for ten nuclear pores from Cell 13a - SVG-
A (5 x 5 x 5 nm isotropic resolution) (Table S4). The segmentations, representing the inner and
outer nuclear membrane envelope contours immediately adjacent to nuclear pores, also included
5 additional pixels (~ 25 nm) of inner and outer nuclear membrane extending away from the
nuclear pore opening (Fig. 6A). Training was performed with the augmented data generated from
only eight nuclear pores (with two additional objects for validation), resulting in a nuclear pore
model that performed well after 100,000 training cycles (F1=0.52, Precision=0.35, Recall=0.99,
Table S8). In all cases, the high recall score was consistent with a perfect correspondence to all
the voxels that defined the ground truth annotations. The relatively low F1 and precision scores
reflected 'fatter' predictions due to voxels assigned to positions immediately adjacent to the 'single
row' of voxels overlapping the nuclear pores in the ground truth annotations. Visual inspection
confirmed accurate identification of all nuclear pores in naïve SVG-A cells 15 (Video 4) and 17 (5
x 5 x 5 nm isotropic resolution) and Cell 19 Hela (4 x 4 x 5.2 nm) not used for training (Fig. 6B).
Because of the high predictive accuracy attained with this simple nuclear pore model (Video 4), it
was not necessary to improve the model using our more extended training pipelines.

Based on ensemble cryo EM data from thousands of nuclear pores that provide a unique atomic
model per data set (Schuller et al., 2021), combined with more selective images of single nuclear
pores obtained using cryo tomography of yeast cells in different physiological states (Zimmerli et
al., 2021), it is now believed that the diameter of the nuclear pore varies in response to the
physiological state of the cell. It is not known, however, to what extent this size variability occurs
within a single cell in a unique physiological state. Taking advantage of our automated
segmentation pipeline that makes it practical to analyze hundreds of single nuclear pores, we
explored the extent by which their membrane pore diameters varied within a single cell. Inspection
of the nuclear membrane surrounding the pores viewed along the axis normal to the nuclear
envelope confirmed the radial symmetry of the pore (Fig. 6B) with a relatively broad and
continuous variation in membrane pore diameter, ranging from 60 to 130 nm (median 92 nm, with
75-108 nm 10-90 percentile range: n= 934; 305, 135, and 494 pores from SVG-A Cells 15 and
17, and Hela Cell 19, respectively) (Fig. 6C); these values were obtained by measuring in the raw
images the distances between the peak signals at opposite ends of the nuclear membrane pore
(see Methods and Fig. S7 A-D). The membrane pore sizes did not follow a normal distribution,
but instead had a slight asymmetry contributed by smaller species. They were also distinct from
the Gaussian fit (blue, Fig. 6C) corresponding to the expected size distribution if the data would
have originated from a single pore size centered on the most abundant species. We found no

evidence to suggest presence of spatial correlation between pore diameter and different regions
of the nuclear envelope within the cell, for example away from the cover slip or normal to this
surface, nor did we find evidence of local clustering of pores with a favored size (Fig. 6D and
S7E).
356
Automated segmentation of clathrin coated pits, coated vesicles and caveolae
As a further test of ASEM with relatively small structures, we chose clathrin coated pits, 30-100
nm membrane invaginations in the plasma membrane and the trans Golgi network (TGN) involved
in selective cargo traffic (Kirchhausen, 2000). We trained the model with ground truth annotations
from 15 endocytic plasma membrane coated pits of different sizes and shapes thus representing
different stages of clathrin coat assembly. While the resolution of the FIB-SEM was insufficient
to discern the familiar spikes or the hexagonal and pentagonal facets of a clathrin coat as seen
in samples imaged by TEM, the presence of strong membrane staining, which we attribute to
clathrin and associated proteins (Fig. 7A), made these invaginations recognizably distinct from
caveolae, which are smaller (50 – 100 nm) flask-shaped invaginations and lack enhanced
membrane staining (Fig. 7B). None of the cells had recognizable regions of strongly stained, flat
membrane, often found on the coverslip-attached surface of cells in culture and in other
specialized locations (Akisaka et al., 2008; Grove et al., 2014; Heuser, 1980; Maupin and Pollard,
1983; Saffarian et al., 2009; Signoret et al., 2005). We used VAST to generate the coated-pit
ground truth annotations, which were simply a collection of single traces loosely overlapping the
endocytic membrane invagination (Fig 7A, blue).
373
The coated pit model obtained after 80,000-100,000 training iterations combined 15 ground truth
annotations we made, six from Cell 12 Hela and nine from Cell 13 Hela imaged by the COSEM
project. Visual inspection of the predictions generated by this relatively simple training in parts of
Hela cells 12 and 13 cells that had not been used for training showed accurate recognition of all
endocytic coated pits (representative example in Fig. 7B); we obtained similar results from naïve
SVG-A cells 15 (Video 4) and 17, and Hela cell 19. The model also identified all coated pits in the
TGN (Fig. 7B). It incorrectly identified caveolae as coated pits (Fig 7B), but we could detect no
other incorrect predictions anywhere in the cell volume. Sharply invaginating curvature of the
stained membrane outline thus appears to be an important component of the pattern the model
learned to recognize.
384

We used our additional annotated ground truth annotations from Hela Cells 12 and 13 that had

not been included in the training set to calculate F1, recall and precision scores (Table S8). In all

cases, the high recall score (0.99) demonstrated the almost perfect reconstruction of all voxels

belonging to the ground truth annotations. The relatively low F1 and precision scores (~ 0.65 and

0.51) were due to incorrect voxel predictions immediately adjacent to the 'single row' of true voxel

assignments overlapping the invaginated membrane in the ground truth annotations (Fig. 7A, B).

The model also recognized vesicles near the plasma membrane and the TGN that an expert

human observer would have interpreted from their staining to be clathrin coated vesicles, even

though training of the model did not include ground truth annotations representing them (Fig. 7B).

We confirmed that the model recognized *all* the presumptive coated vesicles in a cell, by visual

inspection across the full volumes of Hela cells 12 and 13, as well as of three cells that did not

contribute at all to the training set, SVG-A cells 15 and 17 and Hela cell 19. Training on endocytic

coated pits thus also allowed recognition of endocytic coated vesicles and TGN coated pits.

We took advantage of the large, combined set of three-dimensional image data from coated pits

and vesicles to analyze assembly stages using the metrics depicted in Fig. S8). We determined

the depths and widths at ½ depth for each of the membrane invaginations in SVG-A cell 17 (Fig.

7C). Caveolae, recognized by the absence of an enhanced membrane signal, were relatively

small, with narrow distributions of depths and widths centered on 61 and 81 nm (Fig. 7C).

Endocytic coated pits, identified by their enhanced membrane signals, were generally larger than

caveolae and had wider distributions of depths and widths, which clustered into two groups.

Coated pits with open necks (>40 nm) had shallow, ~ 50 nm invaginations; those with narrower

necks (~ 10 to 40 nm) had deep, ~ 100-130 nm invaginations (Fig. 7D, left and central panel, and

7E, right panel). Endocytic coated pits and vesicles were also larger than the corresponding

structures emanating from internal membranes associated with the TGN (Fig. 7D, left panel).

The eccentricity of the assembling pit, defined as the ratio of major and minor axes of the ellipsoid

that fit best to a given membrane profile, showed a relatively narrow and overlapping distribution

(Fig. 7D, right panel), ranging from 1 (symmetric) and 1.6 (less symmetric) for endocytic pits and

vesicles. Most of the pits and vesicles associated with internal membranes in SVG-A Cell 17 (Fig.

7D, right panel) had eccentricities close to 1; in those cases, the major axis of most pits was

orthogonal to the plane from which the pits invaginated. Similar results were obtained for SVG-A

cell 15 and Hela cells 12 and 13 (Fig. S19, A-C).   These results are consistent with a budding

mechanism in which stepwise growth of the clathrin coat drives invagination of the membrane,

ultimately creating a constriction, as the curved clathrin lattice approaches closure, that is narrow

enough for dynamin to pinch off the nascent vesicle (Kirchhausen et al., 2014).

Discussion

The automated 3-D image segmentation pipeline embodied in ASEM overcomes three critical hurdles for making FIB-SEM more practical and more broadly useful than currently available procedures. (1) Our graph-cut based annotation approach facilitates and simplifies the manual stages of the analysis, especially when combined with data augmentation that minimizes the number of hand-curated annotations. Between 8 and 16 annotated ground truth annotations encompassing the complete volumes of smaller objects or partial volumes of larger ones were generally enough when augmented as described. We used rough rather than voxel-precise labeling to delineate the outline of the subcellular structures for which we were training. While this strategy was effective for our training pipeline, it was much less time-consuming than the precise delineation efforts used by COSEM. We could then readily correct any erroneous voxel detections, either by manual intervention or by automatic post-processing. (2) For the applications described here, ASEM requires far less computational effort than does COSEM or other approaches, largely because we restrict the training to a single type of structure and thus create a separate model for each type. Consequently, we found that about ~100,000-150,000 training iterations were sufficient for accurate prediction, whereas COSEM required five times as many. (3) We can substantially improve the success rate in a completely naïve cell by using a model trained on ground truth annotations from another cell and re-training by a simplified transfer-learning approach with a very small number of ground truth annotations from the new cell, thereby adapting the model to a cell with slightly different imaging characteristics at the cost of modest additional segmentation and computational effort. In the examples here, just 5,000-10,000 training iterations were enough to increase prediction accuracy throughout the rest of that cell.

To test the robustness and flexibility of ASEM, we used the model trained with ER ground truth annotations from cells in interphase for identifying and segmenting ER in an early anaphase mitotic cell. The model, which had correctly identified and segmented the complete ER in a naïve interphase cell, also accurately identified and segmented the ER in the mitotic cell. The result is non-trivial, because relatively extended, fenestrated, double-membrane sheets, with small interconnecting tubules, dominate the morphology of the mitotic ER, while tubules of varying lengths, connecting much smaller sheets, are the principal structures in the interphase ER. Segmenting the mitotic ER required less than an hour; it would have taken a human annotator several weeks. Previous analyses were limited to small cell volumes precisely because of this constraint. We further showed that automatic segmentation of the Golgi apparatus with ASEM confirmed the results described by the COSEM Project team (Heinrich et al., 2021). The Golgi is

not a stack of closely packed, uniform cisternae, as often diagrammed in textbooks. Rather, each
member of the stack is a complex, perforated structure of variable shape, surrounded by many
small vesicles.

We used automatic segmentation of mitochondria, ER and Golgi apparatus primarily for
comparison with published results from other methods, to validate the features of ASEM designed
to accelerate and simplify the entire pipeline. We turned to smaller subcellular structures as tests
of new and potentially more challenging applications. Nuclear pores are more homogenous than
larger organelles, and thus in principle easier to recognize, but any one pore has much less spatial
information than does a Golgi stack or a mitochondrion, and as we have found, the diameter of
the membrane pore varies even across the nucleus of single cells at a fixed time point, despite
the likely invariance of much of the nuclear pore complex protein assembly. Clathrin coated pits
are both small (on the scale of the ER and Golgi apparatus) and variable, in size and as well as
in assembly stage. In both cases, by training ASEM with a large set of ground truth annotations
generated by data augmentation from a very small number of hand-annotated objects, we could
automatically identify essentially all the objects in the cell, despite the variable diameter of the
nuclear membrane pore and the variable size and stage of completion of a clathrin coated pit.
Moreover, a model trained on plasma-membrane coated pits identified coated pits in the Golgi
and free clathrin coated vesicles in the cytosol.

The osmium-uranyl staining in current FIB-SEM sample preparation, for both CF and HPFS,
preferentially marks lipid headgroups, proteins and nucleic acids. Although with the training set
used here, the model did not distinguish between clathrin coated pits and caveolae, the eye clearly
picks up the much heavier staining of the former (Fig. 7). The model correctly retrieved clathrin
coated vesicles, as well as coated pits in the TGN, and distinguished them from COPI and COPII
vesicles which carry cargo between the Golgi apparatus and the ER, perhaps because they are
smaller structures, of substantially sharper curvature than the clathrin coated structures the model
had learned to recognize. How well the model will find protein-dominated structures -- e.g., virus
assembly intermediates -- remains to be determined.

Imaging the entire volume of a single cell at ~5 nm resolution can answer questions that are much
harder to tackle by methods such as cryo-tomography that access at somewhat higher resolution
only a small slice of a cell. One example is our finding, that nuclear pores vary in size across the
nuclear membrane and hence that the variability identified by cryo-tomography is present at an

arbitrary time point in a single cell. The deep-learning protocols we have developed, and the

readily implemented and freely accessible analysis tools we provide, form an experimental

pipeline that will run entirely on commercially available workstations. We suggest that EM volume

imaging will prove to be a powerful complement to the live-cell fluorescence volume imaging

afforded by lattice light-sheet microscopy.

Material and methods

Chemical Fixation, dehydration and embedding

Cells plated on glass coverslips were processed for chemical fixation (CF) by incubation for 30 minutes at room temperature with 0.2% glutaraldehyde (Electron Microscopy Science, Cat.16220) and 2.5% paraformaldehyde (PFA, Electron Microscopy Science, Cat. 15700) dissolved in 0.1M PIPES buffer (pH 7.4, Sigma-Aldrich, Cat. P6757), followed by a rinse with 0.1M PIPES buffer. A 2% OsO4 aqueous solution (Electron Microscopy Sciences) dissolved in 0.1M PIPES, pH 7.4 was used to stain the cells for 1 hour at RT, followed by incubation for another 1 hour at RT in a solution containing 2.5% potassium ferrocyanide (Sigma-Aldrich) in 0.1 M PIPES, pH 7.4. The cells were rinsed three times at five-minute intervals with deionized ultrapure water followed by a 30-minute incubation at RT with a filtered (Whatman, 0.2 µm) freshly prepared solution of 1% thiocarbohydrazide (Electron Microscopy Sciences) made by dissolving it at 60°C for 15 minutes. The cells were again rinsed three times at 5-minute intervals, followed by another incubation with 2% OsO4 aqueous solution for 1 hour at RT. The cells were again rinsed three times at five-minute intervals with ultrapure water, followed by two rinses with 0.05 M maleate buffer, pH 5.15 (Sigma-Aldrich), and finally incubated with 1% uranyl acetate (Electron Microscopy Sciences) dissolved in 0.05 M maleate buffer pH 5.15 for 12 hours at 4°C.

A resin mixture containing methylhexahydrophthalic anhydride (J&K Scientific) and cycloaliphatic epoxide (ERL 4221, Electron Microscopy Sciences) at a weight ratio of 1.27:1, mixed with the catalyzing agent (Hishicolin PX-4ET, Nippon Chemical Industrial) at a 1:100 ratio by volume, was prepared in a water bath sonicator at RT for 15 minutes.

During the same period, the glass coverslips with the attached CF samples were placed face up on wet ice and then rinsed twice for five minutes with ultrapure water, followed by dehydration using a graded series of ethanol solutions (30, 50, 70, 90%) each step lasting three minutes, then three washes in 100% absolute ethanol for 10 minutes ending with three washes with anhydrous acetone (Sigma-Aldrich) for 10 minutes at RT.

The glass cover slips with the attached, dehydrated CF samples immersed in anhydrous acetone were placed in a wide-mouth glass jar, mixed with the resin at a 1:1 volumetric ratio, and gently rocked on a plate rocker for 12 hours at room temperature. The resin mixture was then removed by aspiration and replaced with 10 ml of freshly prepared resin mixture and further incubated with gentle rocking for another two hours; this step was repeated thrice, each time with freshly

prepared resin. Finally, the glass cover slips with the attached cells were placed on top of cut off
caps from 1.5 mL Eppendorf tubes containing freshly prepared resin was oriented with the cells
towards the cap, and the resin allowed to polymerize for 12 hours at 100°C. Upon resin hardening,
the caps were immersed in boiling water for 5 minutes and then quickly transferred into liquid
nitrogen leading to separation of the glass cover slip from the resin and retention of the cells in
the polymerized resin.
536

High pressure freezing, freeze-substitution and embedding

Cells were plated on 6 x 0.1 mm sapphire disks in MEM (Corning™ 10009CV) supplemented with
10% Fetal Bovine Serum (Atlanta Biologicals S11150). Two sapphire discs (Technotrade
international 616-100), one or both containing attached cells facing inwards, were separated by
a 100 µm stainless steel spacer (Technotrade international 1257-100) and processed for high
pressure freezing on a Leica EM ICE high pressure freezer (Leica microsystems). Following high
pressure freezing, the sapphire discs were placed under liquid nitrogen and transferred into the
top of cryotubes placed in liquid nitrogen and containing frozen 2% OsO4, 0.1% uranyl acetate
and 3% water in acetone; freeze substitution (FS) was carried using an EM AFS2 automatic freeze
substitution device (Leica Microsystems) according to a pre-programmed FS schedule (-140°C to
-90°C for 2h, -90°C to -90°C for 24h, -90°C to 0°C for 12h and 0°C to 22°C for 1h). Samples were
then removed from the AFS2 device, rinsed 3 times in anhydrous acetone, 3 times in propylene
oxide (Electron Microscopy Sciences), 3 times in 50% resin (24g Embed 812, 9g DDSA, 15g
NMA, 1.2g BDMA; Electron Microscopy Sciences 14121) dissolved in propylene oxide, and finally
transferred into embedding molds (EMS 70900) containing 100% resin; the resin was then
allowed to polymerize for 48 hours at 65°C. The sapphire disc was then separated from the resin
block by sequential immersion in liquid nitrogen and boiling water.
554

FIB-SEM imaging

The polymerized resin blocks were cut from the molds and glued, with the free face facing away,
onto the top of aluminum pin mount stubs (Ted Pella), using conductive silver epoxy adhesive
(EPO-TEK H20S, Electron Microscopy Sciences). The free face was then coated with carbon (20
nm thickness) generated from a high purity carbon cord source (Electron Microscopy Sciences)
using a Quorum Q150R ES sputter coater (Quorum Technologies) and the resin block loaded on
the microscope specimen stage of a Zeiss Crossbeam 540 microscope for FIB-SEM imaging.
After eucentric correction, the stage was titled to 54° with a working distance of 5 mm for
coincidence of ion and electron beams. A cell of interest was located on the free face of the resin

block by SEM, after which a thin layer of platinum was deposited using the gas injection system.

A coarse trench was then milled adjacent to the cell using the 30 kV/30 nA gallium ion beam. This

block face was polished with a 30 kV/7 nA gallium beam before starting the interlaced sequence

of FIB milling with a 30 kV/3 nA gallium beam and SEM imaging with a 1.5 kV/400 pA electron

beam advanced in 5 nm steps. The X/Y pixel size was 5 nm to create isotropic voxels. For

samples prepared by HPFS, we added registration marks on top of the platinum layer generated

with a 1.5 kV/50 pA gallium beam, followed by contrast enhancement of the marks by irradiation

with a 1.5 kV/5 nA electron beam and final deposition of second platinum layer. FIB-SEM images

were collected using the Inlens detector with a pixel dwell time of 10-15 us. The FIB-SEM images

were aligned post-acquisition with the Fiji plugin Register Virtual Stack Slices, using the

translation (Feature extraction model and Registration model) and shrinkage constraint options

(Schroeder et al., 2021).

FIB-SEM data at 10 nm were acquired using a backscatter electron detector (EsB) with a grid

voltage set to 808 V to filter out scattered secondary electrons, with a dwell time of 3 µs, line

averaging of 8, and pixel size of 10 x 10 nm (X/Y). FIB milling was performed with the 30 kV/30

nA gallium ion beam in 10 nm steps to create isotropic 10 x 10 x 10 nm (XYZ) voxels. The

sequential FIB-SEM images were registered using the Fiji plugin *StackReg* with Rigid Body

transformation.

Ground truth annotation

All our ground truth annotations were binary masks located at least 47 voxels away from the

boundaries of the 3D FIB-SEM image. This ensured that training of the neural network was done

with sufficient semantic context within the image resulting in improved model predictions.

Ground truth annotations for mitochondria, Golgi apparatus and endoplasmic reticulum were

generated by using the carving module of Ilastik (Berg et al., 2019) or our graph cuts-based semi-

automated annotation tool, and when needed, by further manual editing using VAST (Berger et

al., 2018) to remove voxels that did not belong to the structure of interest or to add voxels for

regions that had not been included in the original binary mask.

Ground truth annotations for the relatively complex three-dimensional substructure of the Golgi

apparatus included membrane boundaries and the lumen for the characteristic 3-6 closely

stacked fully enclosed membrane lamellae, the fenestrated and somewhat swollen trans-Golgi

network stack, and the variable number of small vesicles clustered next to the Golgi
apparatus. They were created with our semi-automated graph-cut annotation tool.
600
601 Ground truth annotations for endocytic clathrin coated pits and for caveolae were manually
602 generated in consecutive planes using VAST, by drawing along the contours following the plasma
603 membrane invaginations characteristic of these structures.
604
605 Ground truth annotations for nuclear pores were manually generated plane by plane using VAST,
606 by drawing along the contours of the nuclear outer and inner membrane adjacent to the nuclear
607 pore.
608
609 **Graph-cut annotation tool**
610 We developed a new tool to aid an expert annotator in marking *sparse* and *coarse* labels one
611 plane at a time in a sub-volume to generate the segmentation required to generate ground truth
612 annotations for a chosen organelle and separate it from the background (see Figure S2).
613
This tool was written in Python and adopted to suit the annotation needs associated with 3D FIB-
SEM data. It is publicly available at https://github.com/kirchhausenlab/gc_segment, accompanied
by detailed usage instructions and best practices. A graph-cut segmentation strategy was
subsequently adopted to generate segmentations from these annotations. In effect, the annotator
generated sparse and coarse annotations for organelles and the background (sparse over *z*-
planes, coarse in terms of adhering to organelle boundaries) inside sub-volumes extracted
manually from the 3D volume. Even though the annotations were coarse, the annotator took care
not to mis-label any voxel. The maxflow algorithm (Boykov et al., 2001)was then employed to
segment organelles based on these annotations.
623
The objective energy function for our problem was formulated based on early work on graph-cut
segmentation in computer vision (Boykov and Kolmogorov, 2004). As the sub-volumes are
characteristically large, they were first divided into supervoxels using the SLIC algorithm (Achanta
et al., 2012). In simple terms, supervoxels were formed by grouping adjacent voxels together
based on a similarity criterion, which for our problem setting was chosen as agreement in
grayscale values.
630

To describe our energy function, we introduce the following notation. The subscripts u and v

denote supervoxels; the subscripts p and q denote voxels. Let $G = (G_1, G_2, \dots, G_p, \dots, G_N)$ be the

annotation vector for a sub-volume consisting of N voxels and let $A = (A_1, A_2, \dots, A_u, \dots, A_V)$ be the

vector corresponding to the unknown labelling of the V supervoxels in the volume. The labelling

represents the distinction between organelle and background and is thus binary. For $G_p \in \{0,1\}$

and $A_u \in \{0,1\}$, the labels 0 and 1 represent background and organelle, respectively. The vector

A represents the *deduced labelling* (or *segmentation*) for each supervoxel. We define an objective

energy function over A; the vector A that results in the *least* energy is the deduced labelling. The

energy function is

$$E(A) = R(A) + \lambda B(A) ,$$

where

$$R(A) = \sum_u \beta D_u(A_u) + \gamma P_u(A_u) , \text{ and}$$

$$B(A) = \sum_{u,v \in L} B_{u,v} \delta(A_u, A_v)$$

Here, $\delta(A_u, A_v)$ is set equal to 1 if $A_u \neq A_v$ and 0 otherwise. L signifies the set of voxels adjacent

to each other and hence deemed *neighbors*. Adjacency means that two supervoxels share a

boundary with each other. β, γ, and λ are weights given to the individual terms.

P_u and D_u represent *unary* terms of the energy function, as they depend only on one supervoxel,

while $B_{\{u,v\}}$ represents *pair-wise* terms. The terms P_p, and D_p, can similarly be defined for voxels,

and then used to define the aggregated terms P_u, D_u, and $B_{\{u,v\}}$.

The unary terms are defined by two factors, (a) the grayscale values of voxels and their agreement

with the annotated foreground and background voxels, as in earlier work (Boykov and

Kolmogorov, 2004; Boykov et al., 2001), and (b) the distance of the voxels from the nearest

annotation of foreground and background. The pair-wise terms are also defined according to

earlier work, based on the distance between two supervoxels, defined as the distance between

the arithmetic center of two supervoxels.

The variables A_u represent a segmentation of the organelle in the 3D sub-volume. The objective

of the semi-automatic segmentation is to find the vector A that minimizes the energy function

$E(A)$. As the defined energy function is sub-modular, it can be optimized using graph cuts

(Kolmogorov and Zabin, 2004). An efficient algorithm to optimize such functions, called *maxflow*

(Boykov and Kolmogorov, 2004), was used to find the optimum vector A.

There are hyper-parameters in our formulation, namely β, γ, and λ. These were empirically

defined as $\beta = 1$, $\gamma = 1$, and $\lambda = 10$.

Data preprocessing for deep learning

Cell image stacks underwent the following steps before they were ready for training:

1. Conversion from TIFF format to the block-wise storage format ZARR.

673   The size of a FIB-SEM dataset corresponding to a stack of registered TIFF files

674   (approximately 2000 planes) was about 20GB. These TIFF stacks were converted into a

675   ZARR 3-D compressed array (Alistair et al., 2021) to increase the efficiency for

676   further pre-processing steps and, most importantly, for the neural network training.

677   2. Cropping of the dataset to exclude empty regions outside the cell and to speed up all

678   further preprocessing steps.

679   3. Block-wise adjustment of brightness and contrast with 3D contrast-limited adaptive

680   histogram equalization (CLAHE, (Zuiderveld, 1994)) using `scikit-`

681   `image.exposure.equalize_adapthist` with kernel size 128 and clip limit 0.02 (see

682   figure S3).

683   4. Application of morphological operations to automatically clean up ground truth annotations

684   based on biological assumptions, implemented with the python libraries `scikit-`

685   `image.morphology` (Walt et al., 2014) and `scipy.ndimage` (Virtanen et al., 2020). For

686   mitochondria and Golgi apparatus, small objects were removed (less than 27 voxels); for

687   endoplasmic reticulum, holes were removed (less than 20,000 voxels, corresponding to

688   0.0025 μm^3.); no clean-up was required for nuclear pores or clathrin coated pits.

689   5. Automatic creation of a coarse voxel-wise mask to mark voxels outside of the cell, using

690   a combination of operations from the python libraries `scikit-image.morphology` and

691   `scipy.ndimage`. The parameters and combination of operations were adapted visually to

692   each dataset. Operations included intensity thresholding, binary opening and closing,

693   filling small holes, and removing small objects.

694   6. Optional: Correction for systematic biases in annotations. We observed that our semi-

695   automatic annotations carry biases that can be corrected automatically. For mitochondria

696   and Golgi apparatus, most of the annotations did not include the membrane, which we

697	wanted to consider as part of the organelle. Note that this correction depended on the
698	characteristics of a specific dataset (e.g., contrast of membranes): mitochondria
699	annotations were dilated by one voxel (5 nm), Golgi apparatus annotations were dilated
700	by three voxels (15 nm); ER, nuclear pores and clathrin coated pits annotations were not
701	dilated.
702	7. Defining a metric exclusion zone. Although step (6) allowed us to add most of the
703	organelles' membrane to the annotation, the ground truth was often not voxel accurate at
704	the organelle boundaries. A neural network model trained with such data cannot produce
705	voxel-accurate predictions at the organelle boundaries, leading to misleading evaluation
706	scores (e. g., F1, see Fig. S10). Following previous works (Haberl et al., 2020; Lucchi et
707	al., 2012), we avoided this issue by defining an exclusion zone around our semi-automatic
708	imprecise annotations, created by dilating and eroding the annotations and taking the
709	logical difference between the two outcomes. The size of both dilation and erosion
710	depends on the specific structure, as follows — four voxels for mitochondria, two voxels
711	for Golgi apparatuses, one voxel each for endoplasmic reticulum, and three voxels dilation
712	plus one voxel erosion for clathrin coated pits and nuclear pores.

All operations required only local context, meaning that they could be applied block-wise, and the

computation could be parallelized to multiple CPU cores. To avoid artefacts at the block boundary,

we provided sufficient spatial context to each block with the python library DAISY

[https://github.com/funkelab/daisy], which was used for multi-process computation on all cores of

a CPU. These computations were performed on Intel Xeon workstation processors with 20-40

physical cores. Detailed instructions on the use of the preprocessing pipeline are provided at

https://github.com/kirchhausenlab/incasem#Prepare-your-own-ground-truth-annotations-for-fine-

tuning-or-training.

Deep learning

Model architecture

A 3D U-Net (Çiçek et al., 2016) based on the architecture used in Funke et al. (2018) was defined,

with three downsampling layers with a factor of two, and two convolutional layers on each

downsampling level. Refer to Figure S3 for details. In total, the network had ~6 million parameters.

It was implemented in PyTorch (Paszke et al., 2019)

Training: Overview of pipeline

The pipeline to feed blocks to the neural network was based on (Buhmann et al., 2021) and

implemented using GUNPOWDER [https://github.com/funkey/gunpowder], a library that

facilitates machine learning on large multi-dimensional arrays.

We trained one model per organelle; that is, for model training data, *foreground* refers to voxels

corresponding to only one type of organelle. For each iteration during the training phase, a block

of 204 x 204 x 204 voxels was randomly sampled from the electron microscopy dataset, together

with the corresponding block of ground truth. The blocks were augmented by voxel-wise

transformations, e.g., random intensity shifts, and geometric transformations, e.g., random

rotations and deformations. The blocks were processed through the network, which returned as

an output block a 3D probability map of 110 x 110 x 110 voxels, centered with respect to the

larger input block. The input blocks contained an additional 47 voxels per side to provide the

context required by our convolutional neural network architecture. The output probability map was

compared with the ground truth using cross-entropy loss, which was minimized by iteratively

updating the model parameters by stochastic gradient descent.

Training: Data sampling

Our dataset annotations were highly imbalanced. Because our structures of interest were small,

only a few voxels formed the so-called foreground (FG), with a large portion of the dataset

consisting of arbitrary background (BG=1-FG) (e.g., cytosol, nucleus, other organelles).

Imbalanced datasets are known to be problematic for convergence of neural network training,

and we confirmed this empirically while working with our datasets. As a rule of thumb, it is

desirable to sample blocks having a foreground to background ratio roughly equivalent to the

global ratio of the two. To make use of all available training data, while keeping the number of

unbalanced training blocks as low as possible, we implemented the following scheme (using

operations available in GUNPOWDER):

1. Reject blocks that contain more than 25% out-of-sample voxels.

2. Calculate the FG/BG ratio for each incoming block.

3. Reject a block with probability 0.9 if fewer than 5% of the voxels in it (ratio in step (2)) are

labeled as foreground.

Training: Data augmentation

It was impractical to process and store tens of thousands of augmented FIB-SEM blocks, required to train the 3D neural network model. Instead, during each training cycle, we augmented the number of ground truth annotations by randomly applying the transformations listed in Table S8 to the training block.

Training: Pipeline details

After data augmentation, we shifted the scale of the data in the input block (204 x 204 x 204 voxels), such that the input intensities were in [-1, 1]. Each block accepted by the neural network was then propagated through the network leading to outputs of spatial dimensions 110 x 110 x 110 voxels, centered with respect to the larger input block. The neural network assigned complementary FG and BG probability to each voxel. The probability map was then compared to the ground truth annotations with the binary cross-entropy loss. We balanced the loss contribution of foreground and background voxels inversely proportional to their occurrence, clipped at a value of 1:100. The training loss was backpropagated, and the network parameters were updated using the Adam optimizer (Kingma et al., 2014) with 0.00003 learning rate and 0.00003 weight decay. The network parameters were saved at the end of every 1000 training iterations.

Training: Computational requirements

Eight CPU cores were used in parallel for data fetching and augmentation, while a single GPU (Nvidia A100 on a DGX-A100 system) was used for training. Typically, a training iteration lasted 1-1.3 sec, and 100,000 iterations (28 h, including periodic validation tests) were sufficient to train our 3D neural network model.

Validation: Procedure

To avoid overfitting, we assessed the model's performances during the training phase on both training dataset and validation dataset, where the latter dataset was not used to update the model parameters. Every 1,000 iterations we saved the training model, froze its weights, and calculated the loss on a small set of ground truth blocks. These were hold-out blocks from the cells that contained the training data, or blocks originating from naïve cells not represented in the training data. By comparing training and validation losses (see plot in Figure S5) we usually identified three different regimes: under-fit, fit and over-fit. When the model under-fitted, both training and validation loss decreased with the training iteration. In the fit regime (Figure S5, in grey), typically

from more than 20,000 training iterations, the validation loss was approximately constant, while
the training loss slightly reduced. In the over-fit regime, the training loss continued to drop, but
the validation loss started to rise. We considered the model saved at the training iteration in the
middle of the fit regime to be the one that could best generalize better, i.e., make optimal
predictions on previously un-seen data. This is a standard procedure in Machine Learning, known
as "early stopping".
801
Validation: Performance metrics
The performance of the models obtained by the 3D U-net neural networks was determined by
comparing the predicted binary segmentation with respect to ground-truth using the following
three metrics: (1) precision (percentage of voxels predicted as subcellular structure that is the
substructure), (2) recall (percentage of substructure voxels correctly predicted as substructure)
and (3) F1 index score (harmonic mean of precision and recall, see Figure S10). These metrics
were also used by other state-of-the-art supervised learning methods, such as COSEM, allowing
for a quantitative comparison.
810
811   Using the true positives TP, false positives FP and false negatives FN, we define precision, recall
812   and F1 as:

813    $$precision = \frac{TP}{TP+FP} \qquad recall = \frac{TP}{TP+FN} \qquad F1 = 2\frac{precision \times recall}{precision+recall} = \frac{TP}{TP+(FP+FN)/2}$$

814
Prediction: Data preprocessing
As for training, the segmentation of new FIB-SEM datasets required certain preprocessing steps
(refer to *Data preprocessing for deep learning* for details):
1. Conversion from TIFF format to block-wise storage format ZARR.
2. Crop the dataset to exclude empty regions outside the cell.
3. Create an approximate voxel-wise mask to mark voxels outside of the cell.
4. Image data normalization with CLAHE (see Figure S3).
822
Prediction: Pipeline
As first step, the trained model at the iteration determined by early stopping (see *Validation:*
Procedure, above) was loaded with frozen weights. The dataset to segment was scanned block
by block and fed into the model, without performing data augmentation. Since the architecture of
the 3D U-Net neural network is fully convolutionaland since each predicted voxel has access to
sufficient context, we could produce the predictions block-wise independently and in parallel.

The model performed a forward pass, producing as output a 3D voxel-wise probability map, saved

to disk in ZARR format. A threshold of 0.5 was applied to the predicted probability map to extract

a binary segmentation map (organelle/background). Although our pipeline allowed the user to set

this threshold to an arbitrary value from zero to one, we set it to the default value of 0.5 in every

experiment to avoid introducing any post-processing bias. The segmentation map was later

visualized in neuroglancer [https://github.com/google/neuroglancer], superimposed on the

electron microscopy image. Finally, we converted the predicted segmentations back to TIFF

format and reverted the initial dataset cropping to obtain a segmentation that was globally aligned

with the originally acquired image stack from the microscope.

Prediction: Computational requirements

A prediction was performed on a single GPU (Nvidia A100 on a DGX-A100 system), backed by

multiple CPU cores, employed to parallelly load and pre-process the data. When using five CPU

cores, our hardware processed 350 blocks (204 x 204 x 204 voxels) in slightly less than five

minutes. Typically, the prediction of one cell image stack, acquired at 5 nm isotropic resolution,

took between 40 minutes and 90 minutes, depending on its volume.

Fine-tuning

To fine-tune a trained model on a naïve cell, we performed the following steps:

1. One block of ground-truth block (minimum 204 x 204 x204 voxels) within the cell to fine-
tune was annotated.

2. A model previously trained on the same organelle, whose weights were frozen at the first
train iteration of the fit region, was loaded for continued training.

3. A training of 15'000 iterations was launched, using as training data only the new prepared
ground-truth block. All fine-tuning training hyperparameters were set identical to the
original training.

4. The model was saved every 1'000 iterations. The best model iteration was picked based
on the original validation dataset from the fine-tuning target cell.

Details to perform fine-tuning training using our pipeline are provided at
https://github.com/kirchhausenlab/incasem#Fine-tuning.

Brief example of fine-tuning

We started by preparing a small ground-truth block of the cell to fine-tune. Because the volume

of the additional ground truth was much smaller than the volume of the ground truth fed to the

pre-trained model (from ~1/69 to ~1/3, Table S9), the additional annotation effort was not very

demanding. In the case of CF datasets, for the fine-tuning of mitochondria in Cell 3 BSC-1 and

Cell 6 SUM 159, we loaded the segmentation map performed by the pre-trained model (model

1847) and refined it by manual editing in VAST. Conversely, to fine-tune HPF OpenOrganelle

datasets in the prediction of mitochondria and ER, we picked one additional COSEM ground-truth

crop, previously excluded from the training and validation data. We loaded the pre-trained model

at the first training iteration within the fit regime (i.e., the iteration after which the validation loss

was fairly stable, Fig. S4); for example, in Fig. S4, CF Mitochondria model, we loaded the model

at the training iteration 95,000. We resumed training of the model using only the additional ground

truth block and data augmentation. Typically, after a few thousand training iterations (about ~1/15

of the training iterations needed to produce the pre-trained models), the fine-tuned model learned

to segment the fine-tune dataset more precisely, with an increased overall F1 score (Table S9).

We noticed that fine-tuning was beneficial mainly when the initially trained model behaved poorly,

such as in the case of HPFS ER, Cell 21 Jurkat-1, for which F1 increased by 0.21.

To understand how fine-tune training helped to improve segmentation, we compared the

segmentation performed by the pre-trained model versus the one produced by the fine-tuned

model (Figure 5-D). In the case of CF, mitochondria, only a few portions of mitochondria were

occasionally missed by the pre-trained model, but they were eventually retrieved by the fine-tuned

models. In HPF ER, fine-tuning reduced the number of false positives, resulting in a neater

segmentation map, suitable for further biological studies.

To quantify the impact of fine-tune training, we calculated precision and recall in addition to F1

(Figure S6). Typically, fine-tuning enhanced precision, without affecting recall: the fine-tuned

model learned to classify cell components that looked like the organelle under study, but did not

actually belong to the same semantic class, reducing the number of false positives.

As baseline, we compared the fine-tuned model with one having randomly initialized weights and

trained using the same (small) ground truth volume. We found that for most datasets and

organelles (ER Cell 21 Jurkat-1, ER Cell 22 Macrophage-2, mitochondria Cell 21 Jurkat-1,

mitochondria Cell 3 BSC-1, mitochondria Cell 6 SUM 159), the models trained using randomly

initialized weight reached substantially lower F1 scores, even when trained much longer, with up

to 200,000 training iterations. Only in one case (mitochondria Macrophage-2), did the model

achieved approximately the same F1 score, but only after training for 160,000 iterations, 20 times

more than the number required by the corresponding fine-tuned model.

We concluded that fine-tune training is a useful tool to apply whenever the segmentation of a

naïve cell falls short. By taking advantage of pre-trained models and preparing a small ground

truth volume, one can train more accurate models, at a small fraction of the ground truth

annotation and computational costs usually required.

Analysis of nuclear pores

Automated orientation of nuclear pores on the nuclear envelope

We determined the nuclear pore membrane diameters from top-down FIB-SEM views towards

the nuclear envelope of each of the nuclear pores. This orientation process was automated with

the following steps. First, we generated a 3D binary mask corresponding to the predicted

probability with a threshold of 0.5 for each one of the nuclear pores identified by the 3D U-net

nuclear pore model (Fig. S7A). Second, we determined for each mask its volume, principal axis,

and centroid coordinates. A filtering step was included to eliminate masks with small volume or

short axis due to incompleteness of the predicted mask. Third, we used median filtering of the 3D

point cloud data to remove outliers, thus creating a virtual 'low resolution' 3D surface of the nuclear

envelope by alpha-shape triangulation of the centroids (Akkiraju et al.) (Fig. S7B, top). Fourth, we

obtained a vector normal to each triangle within the triangulation (Fig. S8B, bottom). Finally, we

used the angular information of this vector to reorient the coordinates of the raw image of the

nuclear pore closest to the triangulation to position the nuclear membrane on a view normal to

the observer (Fig. S7C).

Determination of nuclear pore membrane diameter

The diameter of the membrane pore, defined by the contact between the nuclear membrane and

the pore opening, was determined from the distance separating the two peak signals measured

along a line transecting the middle of the nuclear envelope immediately surrounding the nuclear

pore (d1 and d2 in Fig. S7D). The nuclear pore membrane diameter was expressed as the median

of eighteen radial measurements 10° apart. This calculation increased the precision of the

measurement by taking advantage of the known radial symmetry of the nuclear pore and the

surrounding nuclear envelope on the axis normal to the nuclear envelope; the standard deviation

for each pore diameter measurement (e.g., experimentally determined uncertainty) was 6 nm.

Analysis of clathrin coated pits and coated vesicles

The model trained on endocytic clathrin coated pits in cell 12 and cell 13 was used to predict clathrin coated structures in cells 12, 13, 15, and 17. The predictions were gated at a probability of 0.5 and the corresponding masks then used to locate the clathrin coated structures. These structures were classified as endocytic clathrin coated pits and coated vesicles if located at the plasma membrane or within 400 nm, respectively; 'secretory' coated pits and coated vesicles denote the remaining similar structures located in the cell interior. Each prediction was confirmed by visually inspection of the corresponding image along the three orthogonal directions.

Measurements of neck, height, and width from the pits (Fig. S8A) and major and minor axis of the ellipses best fitting the pits and coated vesicles (Fig. S8A,B) were determined by the following sequential steps: (1) select the view displaying the largest outline by inspection of 9 consecutive planes along each of the three orthogonal views centered on the centroid of the pit or vesicles; (2) manually measure the neck height and widths of the pits; (3) establish the outline of the pit or vesicle in the section chosen in the first step; the darker pixels where the pit or vesicle was present were selected manually (Fig. S9C, red square in the left panel), segmented into a binary mask with an Otsu intensity threshold (Otsu, 1979), and skeletonized (Fig. S8C, middle panel); (4) establish the ellipse best fitting the skeletonized outline of the pit or vesicle (Fig. S8C, right panel); (5) obtain major and minor axis of the ellipse.

Statistical analysis

The normality of the nuclear pore size distribution was examined using the Shapiro-Wilk test (Fig. 6C). The comparison of size distributions between nuclear pore diameters from values determined experimentally and simulated from the median value with an uncertainty of 6 nm using the nonparametric Kolmogorov-Smirnov test showed they were statistically different ($p < 0.0001$).

Data availability

The datasets of raw and normalized FIBSEM cells images, ground truth annotations, probability maps predicted by the models and corresponding segmentation masks are publicly available at the AWS INCASeM bucket [https://open.quiltdata.com/b/incasem].

Code availability

964   The software and step-by-step instructions to use it are publicly available at

965   https://github.com/kirchhausenlab/gc_segment (Graph-cut annotation tool) and

966   https://github.com/kirchhausenlab/incasem (Deep-learning pipeline).

968   Trained neural network models are available at https://open.quiltdata.com/b/incasem/tree/ with

969   usage instructions at https://github.com/kirchhausenlab/incasem.

Supplemental material

Supplemental material consists of Figs. S1-S10 and Tables S1-S9.

Acknowledgments

We thank Jan Funke for initial guidance on the use of deep learning and for maintaining together with members of his laboratory the gunpowder and funlib libraries; Jose Inacio Da Costa Filho for testing our public available codes; Arlo Sheridan for helpful discussions; Teresa Rodriguez and Henrique Girão for providing cells 1 and 2; Giovanni de Nola and Teresa Rodriguez for preparing Cells 1-4 for FIB-SEM imaging; Rasmus Herlo and Max Page for preparing Cell 5 for FIB-SEM imaging; Justin Houser for preparing Cell 6a-9 for FIB-SEM imaging; Gleb Shtengel and and C. Shan Xu for preparing Cells10-13 for FIB-SEM imaging; and S.C. Harrison for extensive editorial help; and members of the Kirchhausen laboratory for help and encouragement.

The research was supported a National Institute of General Medical Sciences Maximizing Investigators' Research Award GM130386 and a generous grant from SANA to T.K. Acquisition of the FIB-SEM microscope was supported by a generous grant from Biogen to T. Kirchhausen. Acquisition of the computing hardware including the DGX's GPU-based computers, CPU clusters, fast access memory, archival servers and workstations that made possible this study were supported by generous grants from the Massachusetts Life Sciences Center to T.K. and an equipment supplement to the National Institute of General Medical Sciences Maximizing Investigators' Research Award GM130386. Construction of the server room housing the computing hardware was made possible with generous support from the PCMM Program at Boston Children's Hospital.

The authors declare no competing financial interests.

Author contributions

B. Gallusser, Mihir Sahasrabudhe and T. Kirchhausen conceptualized the computational aspects of the project; B. Gallusser, G. Maltese, G. Di Caprio, and M. Sahasrabudhe created, implemented, and used the computational pipeline to train the neural network, obtain models and make predictions; J. O'Connor helped set up and maintaing the computing infrastructure; T. J. Vadakkan, B. Gallusser, G. Maltese and G. Di Caprio generated and curated the ground truth annotations used for training. G. Di Caprio analyzed the data on nuclear pores and coated

References

Achanta, R., Shaji, A., Smith, K., Lucchi, A., Fua, P., and Süsstrunk, S. (2012). SLIC Superpixels Compared to State-of-the-Art Superpixel Methods. Ieee T Pattern Anal *34*, 2274–2282.

Akisaka, T., Yoshida, H., Suzuki, R., and Takama, K. (2008). Adhesion structures and their cytoskeleton-membrane interactions at podosomes of osteoclasts in culture. Cell Tissue Res *331*, 625–641.

Akkiraju, N., Edelsbrunner, H., Facello, M., Fu, F., Mucke, E., and Varella, C. Alpha shapes: definition and software. Proc. Internat. Comput. Geom. Software Workshop.

Berg, S., Kutra, D., Kroeger, T., Straehle, C.N., Kausler, B.X., Haubold, C., Schiegg, M., Ales, J., Beier, T., Rudy, M., et al. (2019). ilastik: interactive machine learning for (bio)image analysis. Nature Methods *16*, 1226–1232.

Berger, D.R., Seung, H.S., and Lichtman, J.W. (2018). VAST (Volume Annotation and Segmentation Tool): Efficient Manual and Semi-Automatic Labeling of Large 3D Image Stacks. Front Neural Circuit *12*, 88.

Boykov, Y., and Kolmogorov, V. (2004). An Experimental Comparison of Min-Cut/Max-Flow Algorithms for Energy Minimization in Vision. Ieee T Pattern Anal *26*, 1124–1137.

Boykov, Y., Veksler, O., and Zabih, R. (2001). Fast approximate energy minimization via graph cuts. Ieee T Pattern Anal *23*, 1222–1239.

Buhmann, J., Sheridan, A., Malin-Mayor, C., Schlegel, P., Gerhard, S., Kazimiers, T., Krause, R., Nguyen, T.M., Heinrich, L., Lee, W.-C.A., et al. (2021). Automatic detection of synaptic partners in a whole-brain Drosophila electron microscopy data set. Nat Methods *18*, 771–774.

Çiçek, Ö., Abdulkadir, A., Lienkamp, S.S., Brox, T., and Ronneberger, O. (2016). Medical Image Computing and Computer-Assisted Intervention – MICCAI 2016, 19th International Conference, Athens, Greece, October 17-21, 2016, Proceedings, Part II. Lect Notes Comput Sc 424–432.

Ehrlich, M., Boll, W., Oijen, A. van, Hariharan, R., Chandran, K., Nibert, M.L., and Kirchhausen, T. (2004). Endocytosis by random initiation and stabilization of clathrin-coated pits. Cell *118*, 591–605.

Grove, J., Metcalf, D.J., Knight, A.E., Wavre-Shapton, S.T., Sun, T., Protonotarios, E.D., Griffin, L.D., Lippincott-Schwartz, J., and Marsh, M. (2014). Flat clathrin lattices: stable features of the plasma membrane. Molecular Biology of the Cell *25*, 3581–3594.

Haberl, M.G., Churas, C., Tindall, L., Boassa, D., Phan, S., Bushong, E.A., Madany, M., Akay, R., Deerinck, T.J., Peltier, S.T., et al. (2018). CDeep3M-Plug-and-Play cloud-based deep learning for image segmentation. Nature Methods *15*, 677–680.

Haberl, M.G., Wong, W., Penticoff, S., Je, J., Madany, M., Borchardt, A., Boassa, D., Peltier,
S.T., and Ellisman, M.H. (2020). CDeep3M-Preview: Online segmentation using the deep neural
network model zoo. BioRxiv *16*, 1233.

Heinrich, L., Bennett, D., Ackerman, D., Park, W., Bogovic, J., Eckstein, N., Petruncio, A.,
Clements, J., Pang, S., Xu, C.S., et al. (2021). Whole-cell organelle segmentation in volume
electron microscopy. Nature 1–6.

Heuser, J. (1980). Three-dimensional visualization of coated vesicle formation in fibroblasts. J
Cell Biol *84*, 560–583.

Hoffman, D.P., Shtengel, G., Xu, C.S., Campbell, K.R., Freeman, M., Wang, L., Milkie, D.E.,
Pasolli, H.A., Iyer, N., Bogovic, J.A., et al. (2020). Correlative three-dimensional super-
resolution and block-face electron microscopy of whole vitreously frozen cells. Science (New
York, N.Y.) *367*, eaaz5357.

Kirchhausen, T. (1993). Coated pits and coated vesicles - sorting it all out. Current Opinion in
Structural Biology *3*, 182–188.

Kirchhausen, T. (2000). Clathrin. Annual Review of Biochemistry *69*, 699–727.

Kirchhausen, T. (2009). Imaging endocytic clathrin structures in living cells. Trends in Cell
Biology *19*, 596–605.

Kirchhausen, T., Owen, D., and Harrison, S.C. (2014). Molecular structure, function, and
dynamics of clathrin-mediated membrane traffic. Cold Spring Harbor Perspectives in Biology *6*,
a016725.

Kolmogorov, V., and Zabin, R. (2004). What energy functions can be minimized via graph cuts?
Ieee T Pattern Anal *26*, 147–159.

Liu, J., Li, L., Yang, Y., Hong, B., Chen, X., Xie, Q., and Han, H. (2020). Automatic
Reconstruction of Mitochondria and Endoplasmic Reticulum in Electron Microscopy Volumes
by Deep Learning. Front Neurosci-Switz *14*, 599.

Lucchi, A., Smith, K., Achanta, R., Knott, G., and Fua, P. (2012). Supervoxel-Based
Segmentation of Mitochondria in EM Image Stacks with Learned Shape Features. Ieee T Med
Imaging *31*, 474–486.

Maupin, P., and Pollard, T.D. (1983). Improved preservation and staining of HeLa cell actin
filaments, clathrin-coated membranes, and other cytoplasmic structures by tannic acid-
glutaraldehyde-saponin fixation. The Journal of Cell Biology *96*, 51–62.

Mekuč, M.Ž., Bohak, C., Hudoklin, S., Kim, B.H., Romih, R., Kim, M.Y., and Marolt, M.
(2020). Automatic segmentation of mitochondria and endolysosomes in volumetric electron
microscopy data. Comput Biol Med *119*, 103693.

Mekuč, M.Ž., Bohak, C., Boneš, E., Hudoklin, S., Romih, R., and Marolt, M. (2022). Automatic
segmentation and reconstruction of intracellular compartments in volumetric electron
microscopy data. Comput Meth Prog Bio *223*, 106959.

Müller, A., Schmidt, D., Xu, C.S., Pang, S., D'Costa, J.V., Kretschmar, S., Münster, C., Kurth,
T., Jug, F., Weigert, M., et al. (2020). 3D FIB-SEM reconstruction of microtubule–organelle
interaction in whole primary mouse β cells. J Cell Biology *220*, e202010039.

Otsu, N. (1979). A Threshold Selection Method from Gray-Level Histograms. Ieee Transactions
Syst Man Cybern *9*, 62–66.

Paszke, A., Gross, S., Massa, F., Lerer, A., Bradbury, J., Chanan, G., Killeen, T., Lin, Z.,
Gimelshein, N., Antiga, L., et al. (2019). PyTorch: An Imperative Style, High-Performance Deep
Learning Library. Arxiv.

Pizer, S.M., Amburn, E.P., Austin, J.D., Cromartie, R., Geselowitz, A., Greer, T., Romeny, B. ter
H., Zimmerman, J.B., and Zuiderveld, K. (1987). Adaptive histogram equalization and its
variations. Comput Vis Graph Image Process *39*, 355–368.

Plaza, S.M., and Funke, J. (2018). Analyzing Image Segmentation for Connectomics. Front
Neural Circuit *12*, 102.

Saffarian, S., Cocucci, E., and Kirchhausen, T. (2009). Distinct dynamics of endocytic clathrin-
coated pits and coated plaques. PLoS Biology *7*, e1000191.

Schroeder, A.B., Dobson, E.T.A., Rueden, C.T., Tomancak, P., Jug, F., and Eliceiri, K.W.
(2021). The ImageJ ecosystem: Open-source software for image visualization, processing, and
analysis. Protein Sci *30*, 234–249.

Schuller, A.P., Wojtynek, M., Mankus, D., Tatli, M., Kronenberg-Tenga, R., Regmi, S.G., Dip,
P.V., Lytton-Jean, A.K.R., Brignole, E.J., Dasso, M., et al. (2021). The cellular environment
shapes the nuclear pore complex architecture. Nature 1–5.

Shorten, C., and Khoshgoftaar, T.M. (2019). A survey on Image Data Augmentation for Deep
Learning. J Big Data *6*, 60.

Signoret, N., Hewlett, L., Wavre, S., Pelchen-Matthews, A., Oppermann, M., and Marsh, M.
(2005). Agonist-induced Endocytosis of CC Chemokine Receptor 5 Is Clathrin Dependent. Mol
Biol Cell *16*, 902–917.

Studer, D., Humbel, B.M., and Chiquet, M. (2008). Electron microscopy of high pressure frozen
samples: bridging the gap between cellular ultrastructure and atomic resolution. Histochem Cell
Biol *130*, 877–889.

Virtanen, P., Gommers, R., Oliphant, T.E., Haberland, M., Reddy, T., Cournapeau, D., Burovski,
E., Peterson, P., Weckesser, W., Bright, J., et al. (2020). SciPy 1.0: fundamental algorithms for
scientific computing in Python. Nat Methods *17*, 261–272.

Walt, S. van der, Schönberger, J.L., Nunez-Iglesias, J., Boulogne, F., Warner, J.D., Yager, N.,
Gouillart, E., Yu, T., and contributors, scikit-image (2014). scikit-image: image processing in
Python. Peerj *2*, e453.

Weiss, K., Khoshgoftaar, T.M., and Wang, D. (2016). A survey of transfer learning. J Big Data
3, 9.

Willy, N.M., Ferguson, J.P., Akatay, A., Huber, S., Djakbarova, U., Silahli, S., Cakez, C., Hasan,
F., Chang, H.C., Travesset, A., et al. (2021). De novo endocytic clathrin coats develop curvature
at early stages of their formation. Dev Cell *56*, 3146-3159.e5.

Xu, C.S., Pang, S., Shtengel, G., Müller, A., Ritter, A.T., Hoffman, H.K., Takemura, S., Lu, Z.,
Pasolli, H.A., Iyer, N., et al. (2021). An open-access volume electron microscopy atlas of whole
cells and tissues. Nature *599*, 147–151.

Zeng, T., Murphy, R., Wu, B., and Ji, S. (2017). DeepEM3D: approaching human-level
performance on 3D anisotropic EM image segmentation. Bioinformatics (Oxford, England) *33*,
2555–2562.

Zimmerli, C.E., Allegretti, M., Rantos, V., Goetz, S.K., Obarska-Kosinska, A., Zagoriy, I.,
Halavatyi, A., Hummer, G., Mahamid, J., Kosinski, J., et al. (2021). Nuclear pores dilate and
constrict in cellulo. Sci New York N Y *374*, eabd9776.

Zuiderveld, K. (1994). Graphics Gems. Viii Image Process 474–485.

Figure and Video legends

Figure 1. Pipelines used for training and deep-learning neural network prediction

Schematic representation of the deep-learning approach for recognizing subcellular structures in FIB-SEM volume images using a 3D U-net encoder-decoder neural network.

(A) For training, three-dimensional stacks containing FIB-SEM data, augmented as described in Methods, are provided as input images to the 3D U-Net; in this example, the stack includes a limited number of three-dimensional ground truth annotations for the ER in the form of binary masks (yellow). The ER predicted by the 3D U-net model is a probability 3D map, whose accuracy is evaluated as a prediction error by measuring the cross-entropy loss. The model parameters are iteratively updated during training until convergence of the probability error is achieved.

(B) For prediction, small three-dimensional stacks with data not used for training covering the complete FIB-SEM volume image of a naïve cell (or from the remaining regions of the cell used for training) are provided as input to the 3D U-net model trained in **(A)**. In this example, the predicted ER is a three-dimensional probability map centered on the three-dimensional stack. This arrangement standardizes the three-dimensional context for all predicted voxels within the FIB-SEM image.

Figure 2. Performance of the deep-learning network to predict in naïve cells

Visual comparisons between predictions (crimson) by 3D U-net models trained using combined data from two HEK293A cells to recognize **(A)** ER or **(B)** Golgi apparatus and corresponding ground truth annotations (purple) in the naïve BSC-1 and SUM 159 cells not used for training (Table S1). The representative images from single plane views from FIB-SEM volume data are from cells prepared by CF isotropically acquired at 5 nm resolution; red and yellow arrows highlight small regions containing voxels of false positive and false negative assignments. Scale bar, 500 nm (See Videos 1 and 2).

Figure 3. Network predictions of mitochondria, ER and Golgi apparatus

Single plane view from a FIB-SEM volume image from naïve cell 15 (SVG-A) not used for training prepared by HPFS and visualized during interphase at 5 nm isotropic resolution. The small region contains representative model predictions for mitochondria (cyan), ER (yellow) and Golgi apparatus (magenta) obtained from three 3D U-net models, each trained with organelle-specific ground truth annotations, without fine-tuning, from interphase cells 19 (Hela-2) and 20 (Hela-3) prepared by HPFS. Scale bar, 2 um.

Figure 4. Predictive ER model resolves the structural complexity of the ER network during

different stages of the cell cycle

(**A**) Representative examples of ER predictions in naïve cell 15 (SVG-A) processed during

interphase as described in Fig. 3 showing the characteristic network of ER sheets connected at

branch points to ER tubules. ER tubules were more abundant towards the periphery of this cell,

ER sheets were more abundant closer to the nucleus. For clarity, manual VAST editing was used

to eliminate pixels due to false positive predictions associated with the nuclear envelope. Scale

bar, 1 um.

(B) Representative examples of ER predictions from a mitotic naïve cell 8 (SUM 159) prepared

by CF and imaged isotropically at 10 nm; the ER model was trained with ER ground truth

annotations from interphase cells 1 and 2 (HEK293A) prepared by CF visualized isotropically at

5 nm resolution. It shows successful recognition of an extensive network of fenestrated ER sheets

(red arrow heads) connected to ER tubules, characteristic of mitotic cells. Ground truth

annotations used to train the interphase ER model did not contain ER fenestrations, as they are

barely present during stage of the cell cycle. Darker regions corresponding to chromosomes are

outlined with yellow dotted lines. Scale bar, 3 um (see Video 3).

1020

Figure 5. Effects of extensive combination of data sets and fine-tuning during training

(A-D) Examples to highlight the effect on the predictive performance of **(A, C, D)** mitochondria

and **(A, B)** ER and models trained with data from cells prepared by CF or HPFS, with substantial

differences in general appearance and contrast. The images show several comparisons between

ground truth annotations and predictions from models trained as described in the insets with data

obtained from cells prepared by different sample preparation protocols. Details of the cell and

training protocols are in Tables S1, S2 and S8. Voxels corresponding to false positive (cyan

arrows) and false negative (red arrows) predictions are indicated. Scale bar, 500 nm.

(A) Predictions from *cross-domain* models, for which the training data and predictions were done

using cells prepared with different sample preparation protocols, were less accurate than those

obtained from the *specialized* models, for which training, and predictions were done using cells

prepared with the same sample preparation protocol. Predictions from the *generalist* models,

obtained by training using ground truth annotations from cells prepared by CF and HPFS,

performed as well as the predictions from the specialized models.

(B-D) Effect on the predictive performance of the models by fine tuning during training.

1036

Figure 6. Identification of nuclear pores and variations in their membrane pore diameter

A nuclear pore model was generated by training without fine tuning used ground truth annotations

of nuclear pores from cell 13a SVG-A prepared by HPFS and imaged at 5 nm isotropic resolution.

(A) Orthogonal views of a representative nuclear pore not used for training show ground truth

annotations and model prediction. Scale bar, 50 nm.

(B) Nuclear pore predictions for all the pores on the nuclear envelope of naïve cell 19 (Hela-2)

prepared by HPFS and visualized during interphase at 4 x 4 x 5.3 nm isotropic resolution (left

panel); the inset highlights the characteristic doughnut shape of the nuclear pore. Scale bar, 2

um. Representative orthogonal views (right panels) of a nuclear pore and model prediction. Scale

bar, 50 nm.

(C) Histogram of nuclear membrane pore diameters of nuclear pores measured in naïve cells 15,

17 and 19 (N=934) identified by the nuclear pore model. Each membrane pore diameter

determined in the raw image represents the average value from 18 measurements spaced 18°

apart (see inset and Methods). The Gaussian fit (blue) shows the expected size distribution if the

data had come from membrane pores of a single diameter centered on the experimentally

determined median (most abundant species); the bar width (6 nm) corresponds to the expected

error of the measurements (see Methods).

(D) Three-dimensional distribution of nuclear pores on the nuclear envelope of cell 19, color coded

as a function of membrane pore diameter.

1056

Figure 7. Identification of clathrin coated pits, coated vesicles and caveolae.

A coated pit model was generated by training with ground truth annotations from Cell 12 (Hela-2)

prepared by HPFS and imaged at ~ 5 nm isotropic resolution.

(A) Orthogonal views of a representative endocytic clathrin coated pit (CCP) not used for training

showing ground truth annotations and model prediction. Scale bar, 50 nm.

(B) Orthogonal views of a caveola, an endocytic clathrin coated pit (CCP) and a clathrin coated

vesicle (CCV) at the plasma membrane, and a coated pit (CCP) and vesicle (CCV) associated

with membranes from the secretory pathway. Each panel shows the ground truth annotation and

the model prediction. An example of a COPI vesicle not predicted by the coated pit model is also

shown. Views are from naïve cell 17 SVGA prepared by HPFS and imaged with ~ 5 nm isotropic

resolution.

(C) Violin plots of width and height for caveolae (CAV) and endocytic clathrin coated pits (CCP)

in the raw images of the structures identified by the coated pit model in cell 17 (see also Figure

S8, and Clathrin coated pits and vesicles, Methods).

(**D**) Violin plots of major and minor axis and eccentricity of the fitted ellipse of all pits and vesicles
in the raw images of the structures identified by the coated pit model in cell 17 (see also Figure
S8, and Clathrin coated pits and vesicles, Methods).
(E) The left-hand panel shows the distribution of height versus neck width for endocytic clathrin
coated pits in cell 17, identified by the coated pit model. The plot shows two clusters, which
correspond to early and late coated pits, respectively, as illustrated by the schematics (see also
Figure S8, and "Clathrin coated pits and vesicles" in Methods). The right-hand panel shows
histograms for height and major axis of the fitted ellipse for late endocytic coated pits and coated
vesicles, respectively.
1080
Video 1. Ground truth annotations for mitochondria, ER and Golgi apparatus
Passing through a FIB-SEM volume with contrast equalized using CLAHE. Image is from Cell 1
HEK293A prepared by CF and imaged at ~ 5 nm isotropic resolution. The video shows ground
truth annotations for mitochondria (cyan), ER (red) and Golgi apparatus (green). The annotations
were generated for all mitochondria and Golgi apparatus within the FIB-SEM volume, and all ER
within the highlighted 8 µm x 3 µm x 3 µm block (orange box).
1087
Video 2. Predictions of mitochondria
Passing through the FIB-SEM volume with contrast was equalized using CLAHE. Image is from
naïve Cell 1 HEK293A (not used for training). The video shows predictions by the mitochondria
model trained with ground truth annotations for mitochondria from Cell 2 HEK293A. Both cells
were prepared by CF and imaged at ~ 5 nm isotropic resolution. The model identified all
mitochondria; comparison of the ground truth annotations and predictions shows correct voxel
assignments (true positives, yellow), missing assignments (false negatives, cyan), incorrect
assignments (false positives, magenta). The small fraction of false positive assignments predicted
by the model are associated with unidentified tubular and spherical structures of small size.
1097
Video 3. Prediction of mitotic ER
Passing through the FIB-SEM volume with contrast equalized. Image is from naïve prometaphase
Cell 8 SUM 159 imaged at ~ 10 nm isotropic resolution. The video shows ER predictions (yellow)
generated with ground truth annotations from interphase Cell 1 HEK293A and Cell 2 HEK293A
imaged at ~ 5 nm isotropic resolution. All cells were prepared by CF. Visual inspection confirmed
that the model correctly predicted all the ER, including the fenestrations characteristic of the

mitotic ER sheets; fenestrations were not included in the ground truths used for training, as they
are mostly absent in the ER of interphase cells (Chou et al., 2021).

1106

Video 4. Prediction of mitochondria, ER, Golgi apparatus, nuclear pores, and clathrin
coated pits and vesicles
Passing through the raw FIB-SEM volume from naïve Cell 15 SVG-A prepared by HPFS and
imaged at ~ 5 nm isotropic resolution. The video shows predictions as surface renderings for
mitochondria (cyan), ER (yellow), Golgi apparatus (magenta) in a block of 3 µm x 3 µm x 3 µm
(block size: 664 x 586 x 572 voxels). A small number of false positive pixels generated by the
Golgi model and located within a 323 x 271 x 230 voxel block were removed using VAST. One
identified Golgi apparatus is highlighted (light pink) . Predictions for all nuclear pores (yellow) and
clathrin coated pits and vesicles within the imaged volume are also shown. Visual inspection
confirmed that the models trained with ground truth annotations from Cell 19 HeLa and Cell 20
HeLa prepared by HPFS and imaged at ~ 5 nm isotropic resolution correctly predicted all the
subcellular structures.

A Training

Ground truth annotation

ER

In → 3D U-Net → **Out**

update repeatedly

Cross-entropy loss

Freeze model after training

Probability map

FIB-SEM image stack with
3D ground-truth annotations

B Prediction on naive cell

Trained model

ER

not ER

In → 3D U-Net → **Out**

Predicted probability map

thresholding

Full cell prediction

Figure 1

A

ER

Ground-truth | Prediction

trained with HEK2293A + HEK293A'

BSC-1

SUM 159

500 nm

trained with HEK2293A + HEK293A'

B

Golgi

Ground-truth | Prediction

trained with HEK2293A + HEK293A'

BSC-1

SUM 159

500 nm

trained with HEK2293A + HEK293A'

Samples:
Cell 1   CF HEK293A
Cell 2   CF HEK293A'
Cell 3   CF BSC-1
Cell 6   CF SUM 159

Figure 2

3D predictions

Cell 15 HPFS SVG-A

2 um

Mitochondria **ER** **Golgi**

Figure 3

A

3D predictions   Cell 15 HPFS SVG-A

ER

1 µm

45° 45° 45° 45° 45° 45° 45°

B

Cell 8 CF SUM 159

ER

3 µm

Figure 4

Figure 5

A

Cell 13a HPFS SVG-A

Raw · Ground-truth · Prediction · Composite

50 nm

90°

B

Cell 19 HPFS Hela

Raw data · Prediction

2 µm

50 nm

90°

C

cells 15 & 17 HPFS SVG-A
19 HPFS Hela

N=934

simulation
d = 100 nm

events

NP diameter (nm)

D

Cell 19 HPFS Hela, N=494

y (µm)

x (µm)

z (µm)

z
x
y

NP diameter (nm)

2 µm

Figure 6

A training Cell 12 HPFS Hela

Raw   Ground-truth   Prediction   Composite

Endocytic

CCP

50 nm

90°

B prediction naive cell 17 HPFS SVG-A

Raw   Prediction

Caveolae

Golgi

ccv 5

ccp 4

nucleus

cav   ccp   ccv

1   2   3   6   cell membrane

Endocytic

CCP

Raw   Prediction

CCV

Secretory

50 nm

COP I

Figure 7

Figure 7