Clarifying the role of an unavailable distractor alternative in human multiattribute choice

Yinan Cao[1] and Konstantinos Tsetsos[1,2]

[1] Department of Neurophysiology and Pathophysiology, University Medical Center Hamburg-Eppendorf, Hamburg, Germany
[2] School of Psychological Science, University of Bristol, Bristol, United Kingdom

Correspondence: ycaoneuro@gmail.com, k.tsetsos@bristol.ac.uk

Abstract

Decisions between two alternatives can be influenced by a third irrelevant decoy alternative. Although decoy effects typically depend on the decoy's relative position in a multiattribute choice space, recent studies using risky prospects (i.e., varying in reward and probability) reported a novel 'positive' decoy effect operating on a single value dimension: The higher the expected value of an *unavailable* (distractor) prospect was, the easier the discrimination between two available target prospects became, especially when their expected value difference was small. Here we ask whether this previously reported distractor effect affords alternative interpretations. Indeed, we find that it occurred because the distractor's expected value covaried positively with the subjective utility difference between the two targets. Looking beyond this covariation, we report a modest negative distractor effect, which in turn could conceivably be attributed to classic multiattribute decoy effects. Our findings clarify the modulatory role of an unavailable distracting option in multiattribute decisions.

Highlights:

- Previously reported distractor effects hinged on the assumption that people make risky choices using expected value, but this assumption is at odds with the empirical reality.
- Instead, in the datasets of over 140 participants, people rely on subjective utilities, and namely *additive utility*, which calls for a revisit of previously reported distractor effects.
- Previously reported positive and interacting distractor effects occurred due to an unintended covariation between the distractor variable and the utilities of the targets.
- Classic multiattribute decoy effects are robustly present in speeded risky choice.

Introduction

Humans strive to make good decisions but are rarely veridical judges of the world. Instead, our judgments are swayed by seemingly irrelevant factors[1] and our preferences are improvised as we go along[2]. For instance, echoing well-documented optical illusions, we may perceive the same doughnut as larger on a tiny plate than on a bigger one (**Fig. 1a**). Analogous distortions are encountered when we choose among alternatives that vary in more than one dimension or *attribute*. To illustrate, in the attraction effect[3], adding a similar but less advantageous 'decoy' option (a disk drive with a good storage capacity but at a high price) can make a target alternative (a lower-priced disk with more storage) appear more appealing than a competing alternative (an affordable disk with lower storage) (**Fig. 1b**).

Figure 1. Context effects in decision-making. (**a**) Judgment about object size can be influenced by the surround. (**b**) A paradigmatic choice scenario in which a multiattribute decoy effect can occur[3,29]. (**c**) Relative preference changes for alternatives A and B can be driven by an *attraction* bias that depends on the position of the decoy D with respect to each alternative, i.e., the relational (similarity) 'structure' among options in a multiattribute space. (**d**) The similarity structure among alternatives (D_1 is more similar/closer to B than to A, and vice versa in the case of D_2) determines the direction (sign) of the decoy effect. The decoy effect is defined as the change in choice rate of A over B when D is introduced to the original binary choice set of A and B only. The binary (baseline) choice rate is represented by the horizontal line. (**e**) According to 'value-first' theories[6], attributes are integrated and projected to a single value dimension. (**f**) Documented positive[16] or negative[13] distractor effects occur at the level of unidimensional value. In this value-first hypothesis, the similarity structure in the multidimensional space has no impact. The horizontal line represents a reference choice rate when D value is lower (e.g., the black dot in panel e).

The attraction effect together with related contextual *preference-reversal* phenomena violate the very notion of rational-choice explanation according to which preferences should be menu-invariant[4,5]. Instead, these phenomena suggest that preferences are menu-variant or *context-sensitive*, with the subjective utility of an economic alternative being malleable to the properties of other available alternatives. Preference reversals have been typically reported in multiattribute choice settings, instigating a departure from 'value-first' utility theories[6]—in which attributes are integrated within each option independently—and the development of novel theories of multiattribute choice[7–11].

In contrast to multiattribute decisions, decisions over alternatives varying along a single
attribute have been typically regarded as complying with the principles of rational choice
theory[12]. A plausible account for this dichotomy could be that multiattribute decisions are
more complex (**Fig. 1b—d**). Recently however, a new type of context effect has been reported
in unidimensional multialternative decisions. In the so-called *negative distractor* effect,
humans become more indifferent between two unequal alternatives of high value when a third
distracting option has a high, as opposed to a low, reward value[13] (although see a recent
replication failure of this effect[14]). This negative distractor effect is theoretically important
because it shows that violations of rationality may not be restricted to complex multiattribute
decisions[15] (**Fig. 1e**, **f**). In turn, this motivates the development of a cross-domain, unified
theory of decision irrationality.

Interestingly, in a series of more recent experiments involving risky prospects (alternatives
offering reward outcomes with some probabilities), the opposite pattern was predominantly
documented[16,17] (**Fig. 1f**): the decision accuracy of choosing the best of two target prospects is
particularly compromised by a low-value, 'unavailable' prospect (distractor) that should have
never been in contention. This disruption effect fades away as the distractor's expected value
increases, leading to a *positive* distractor effect. However, Gluth and colleagues (2018) casted
doubts on this effect, claiming that it arises due to statistical artefacts[18]. Later, in return, Chau
et al. (2020) defended the positive distractor effect by emphasising its robust presence in
difficult trials only (it tends to reverse into a negative distractor effect in easy trials, i.e.,
distractor effects *interact* across different parts of the decision space[17]).

Overall, the abovementioned risky-choice studies paint a rather complex empirical picture on
the ways the value of a distractor impacts decision quality. Notably, in these studies, key design
aspects and analyses rested on the assumption that participants' decisions were fully guided
by the expected value of the prospects (**Fig. 1e**). However, since Bernoulli's seminal work, it
has been well established that expected value is a theoretical construct that often fails to
adequately describe human decisions under uncertainty[19,20]. Instead, human decisions under
uncertainty are guided by subjective utilities that are shaped by a plethora of non-normative
factors[21]. Such factors—including the absolute reward magnitude of a prospect[22], the riskiness
of a prospect[23], or even the sum of the normalised reward and probability[24–26]—can perturb
people's valuations of risky prospects in ways that the expected-value framework does not
capture[27]. We reasoned that if such factors covaried with the expected value of the distractor,
then the distractor effects reported previously could, partially or fully, afford alternative
interpretations.

It could be argued that if the experimental choice-sets are generated randomly and afresh for
each participant, such covariations between the distractor's expected value and other factors
are likely to average out. However, we note that all previous studies reporting positive and
interacting distractor effects used the exact same set of trials for all participants. This set of
trials was generated pseudo-randomly, by resampling choice-sets until the expected value of
the distractor was sufficiently decorrelated from the expected value difference (*difficulty*)
between the two targets. On the positive side, presenting the same set of trials to all
participants eliminates the impact of stimulus variability on the group-level behaviour[28]. On
the negative side, using a single set of trials in conjunction with this decorrelation approach,

increases the risk of introducing unintended confounding covariations in the elected set of
trials, which in turn will have consistent impact on the group-level behaviour.
128
Here we outline two classes of unintended covariations that could potentially explain away
distractor effects. First, the expected value of the distractor could potentially covary with
specific (and influential to behaviour) reward/probability regularities in the two target
prospects (we call them *target-related* covariations). For instance, if people derive utilities
using additive integration of rewards and probabilities, target prospects 0.9 x £1 vs. 0.8 x £1
(EV difference: 0.1, additive utility difference: 0.1) will be less easily discriminable than target
prospects 0.5 x £0.5 vs. 0.3 x £0.5 (EV difference: 0.1, additive utility difference: 0.2). If the first
choice-set is more frequently associated with low distractor values than the second one, then
a positive distractor effect could be attributable to additive integration rather than distractor
value. Second, the expected value of the distractor alternative could covary with its relative
position in the reward-probability space (we call these *distractor-related* covariations). This
would influence decision accuracy because, as outlined earlier, the relative position of a decoy
alternative in the multiattribute choice space can induce strong choice biases[9,10]. For
illustration purposes only, we assume that the distractor boosts the tendency of choosing a
nearby target akin to the attraction effect[3,29] (**Fig. 1b, d**). Under this assumption, if high-value
distractors happen to be closer to the higher-value target, a positive distractor effect could be
entirely attributable to the attraction effect.
146
The aim of this paper is to re-assess distractor effects in the relevant, previously published
datasets[16–18] while looking beyond these two classes of potentially confounding covariations
(target-related and distractor-related). We began with establishing that the first class of target-
related covariations is indeed present in the examined datasets, with positive and interacting
'distractor' effects being evident even in 'matched' binary trials, in which the distractor
alternative was not present. Using a novel baselining approach, we asked if there are residual
distractor effects when the influence of these unintended covariations is controlled for,
reporting that distractor effects are eradicated. We then pinpointed these target-related
confounding covariations to people's strong tendency to integrate reward and probability
additively, and not multiplicatively. Moving forward, defining the key target and distractor
utility variables, not using expected value, but subjective (additive) utility, revealed a modest
negative distractor effect. Moving on to the second class of distractor-related covariations, we
established that choice accuracy was lawfully influenced by the position of the distractor in the
multiattribute space (**Fig. 1c, d**), consistent with a large body of empirical work in multiattribute
choice[9,29]. This 'decoy' influence was most pronounced when the distractor alternative was
close to the higher-value target in the multiattribute space, yielding an attraction effect (i.e., a
boost in accuracy) when the distractor was inferior, and a repulsion effect (i.e., a reduction in
accuracy) when the distractor was superior, in subjective utility, to the target. Of note, this
decoy influence peaking around the higher-value target, essentially re-describes a negative
distractor effect without evoking ad-hoc 'unidimensional distractor' mechanisms other than
those that are needed to produce classic multiattribute context effects[9,30].
168
169 Overall, our analyses update the state-of-the-art by suggesting that, when confounding
170 covariations are controlled for, only a modest negative distractor effect survives. Further, it is
171 conceivable that this distractor effect mirrors asymmetric classic multiattribute context
172 effects, which occurred robustly in the examined datasets.

173   Results
174
We re-analysed 5 datasets from published studies (Chau et al.[16]; Gluth et al.[18]; *N* = 144 human
participants) of a speeded multiattribute decision-making task. Participants were shown choice
alternatives that varied along two distinct reward attributes: reward magnitude (X) and reward
probability (P), which mapped to visual features (colourful slanted bars as options in **Fig. 2a**).
After learning the feature-to-attribute mapping, participants were instructed to choose the
most valuable one among multiple options placed in this multiattribute space (**Fig. 2a**) on each
trial and to maximise the total reward across trials. In the ternary-choice condition, one option
(the 'distractor', or *D*) was flagged *unavailable* for selection early in the trial. The expected
value (or *EV*, i.e., X multiplied by P) of the higher- and lower-value *available* alternatives
('targets'), and of the *unavailable* distractor were denoted by *HV*, *LV*, and *DV*, respectively.
185
Rational choice theory posits that an unavailable D should not in any way alter the relative
choice between two available H and L targets. However, the behavioural data in this task[16]
challenged this view. By examining the probability of H being chosen over L in ternary trials,
i.e., the *relative* choice accuracy, Chau et al.[6,18] reported that a *relative* distractor variable 'DV
− HV' (the EV difference between the distractor and the best available target) altered relative
accuracy. Other recent studies, using different stimuli, quantified the distractor influence using
an *absolute* distractor variable DV[13,14]). Wherever possible, we quantify distractor effects using
both the relative (DV − HV) and absolute (DV) distractor variables.
194
To begin with, we note that, in addition to ternary trials in which D was present (but
unavailable), participants encountered 'matched' binary trials in which only the H and L target
alternatives were shown. These binary trials are ideally suited for assessing the extent to which
previously reported distractor affects can be attributed to covariations between the distractor
variable and target-related properties. This is because for each ternary trial we can derive a
respective binary-choice baseline from binary trials that had the exact same targets but no
distractor (**Extended Data Fig. 1c**). Given that participants never saw D in binary trials, the
distractor variable is notional and should have no effect on the binary baseline accuracies.
However, if D does paradoxically 'influence' binary accuracies, then this would signal that the
distractor variable covaries with other unspecified modulators of choice accuracy.

Figure 2. Re-assessing distractor effects beyond target-related covariations in ternary- and binary-
choice trials. (**a**) Multiattribute stimuli in a previous study[16]. Participants made a speeded choice among
two available options (HV: high expected value; LV: low expected value) in the presence (ternary) or
absence (binary) of a 3[rd] distractor option ('*D*'). Three example stimuli are labelled for illustration
purposes only. In the experiment, D was surrounded by a purple square to show that it should not be
chosen. (**b**, **c**) Relative choice accuracy (probability of H choice among all H and L choices) in ternary
trials (panel b) and in binary-choice baselines (panel c) plotted as a function of both the expected value
(EV) difference between the two available options (HV − LV) and the EV difference between D and H.
Relative choice accuracy increases when HV − LV increases (bottom to top) as well as when DV − HV
increases (left to right, i.e., *positive* D effect). (**d**, **e**, **f**) Predicting relative accuracy in human data using
regression model (Methods). Asterisks: significant effects ($p < .05$; 2-sided 1-sample t-tests of GLM
coefficients against 0) following Holm's sequential Bonferroni correction for multiple comparisons. (**g**)
Rival hypotheses underlying the positive 'distractor' effect on binary-choice accuracy. Left: EV
indifference contour map; Right: additive-utility (AU) indifference contour map. Utility remains
constant across all points on the same indifference curve and increases across different curves in evenly
spaced steps along the direction of the dashed grey line. Decision accuracy scales with Δ(utility)
between H and L in binary choices. Left (hypothesis 1): $\Delta(EV) = (HV - LV)/(HV + LV)$ by virtue of divisive
normalisation; because $HV_2 - LV_2 = HV_1 - LV_1$, and $HV_2 + LV_2 > HV_1 + LV_1$, $\Delta(EV_2) < \Delta(EV_1)$. Right (hypothesis
2): $\Delta(AU) = AU_H - AU_L$; $\Delta(AU_2) < \Delta(AU_1)$. (**h**, **i**) Regression analysis of model-predicted accuracy in binary
choice. EV + DN model corresponds to hypothesis 1 whilst AU model corresponds to hypothesis 2 in
panel g. Error bars = ± s.e.m. (N = 144 participants).

Re-assessing distractor effects beyond target-related covariations

We used logistic regression (generalised linear model, or GLM) to quantify the effect of distractor variable on relative choice accuracy (the probability of H choice among all H and L choices). Differently from previous studies, which focused primarily on ternary-choice trials, here we analysed two different dependent variables (**Fig. 2d—f**): ternary-choice relative accuracies ('T') and their *respective* baseline accuracies ('B') (see Methods and **Extended Data Fig. 1c**). For the ternary-choice condition, our GLM reveals a significant main effect of the relative distractor variable 'DV − HV' ($t(143) = 3.89$, $p < .001$), and a significant interaction between this distractor variable and the index of decision difficulty 'HV − LV' on relative choice accuracy, $t(143) = -3.67$, $p < .001$ (**Fig. 2d**). These results agree with previous reports when analysing ternary choice alone[16,17]. Turning into the matched binary baseline accuracies, the GLM coefficients bear a striking resemblance to those of the ternary-choice GLM (see **Fig. 2e**; also compare **Fig. 2b** with **2c** for a stark resemblance between T and B accuracy patterns). Crucially, neither the main distractor effect nor the (HV − LV) x (DV − HV) interaction on relative accuracy is modulated by 'Condition' in a GLM combining T and B together, $|t(143)| < .92$, $p > .72$ (**Fig. 2f**). We see similar results when the relative distractor variable DV − HV is replaced by the absolute distractor variable 'DV' or when a covariate HV + LV is additionally included: the distractor's EV had no differential effect on relative accuracy across binary vs. ternary condition (**Extended Data Figs. 2, 3**). The 'distractor' effects (**Fig. 2e**) in binary trials (with only H and L stimuli present) indicate that the value of D covaries with target-related properties (other than HV − LV, which was already a regressor) that modulate choice accuracy. Next, we use computational modelling to unveil these confounding target-related properties.

Additive and not multiplicative information integration in risky choice

The original study reported a surprising phenomenon[16]: decisions seem to be particularly vulnerable to disruption by a 3rd low-value, as opposed to high-value, distracting alternative, i.e., a positive distractor effect. The very definition of this effect hinges upon the *a priori* assumption that decisions rely on calculating and subsequently comparing the expected values (EVs) across alternatives. An alternative prominent idea is that participants eschew EV calculations[31]; instead, they compute the difference between alternatives *within* each attribute and simply sum up these differences across attributes. Indeed, past studies in binary risky choice have ubiquitously reported decision strategies in humans and other animals[24,26,32] based on a weighted sum of the attribute differences, i.e., a decision variable equivalent to the additive utility (AU) difference between alternatives, $\Delta(AU) = \lambda(HX − LX) + (1 − \lambda)(HP − LP)$, where $0 \leq \lambda \leq 1$. Of note, we came to notice that the key distractor variable DV − HV positively covaries with the $\Delta(AU)$ between H and L in the stimuli (e.g., Pearson's $r(148) = .314$, $p < .0001$, in the case of equal weighting between X and P, $\lambda = .5$). This unintended covariation arose in the original study possibly due to a deliberate attempt to decorrelate two EV-based quantities (DV − HV and HV − LV) in the stimuli[16]. The correlation between DV − HV and $\Delta(AU)$ is stronger in more difficult trials ($r(71) = .52$, $p < .0001$, shared variance = 27%; splitting 150 trials into difficult vs. easy by the median of HV − LV[17]) than in easier trials ($r(59) = .43$, $p < .001$, shared variance = 19%), mirroring both the positive (overall positive correlation) and the interacting (change of correlation strength as a function of difficulty) 'distractor effects' on binary choice.

Additive integration explains 'distractor effect' in binary-choice trials

Notably, DV − HV also negatively covaries with HV + LV (Pearson's r(148) = -.78, p < .001), which potentially leads to another explanation of why binary choice accuracy seems lower as the matched DV − HV variable decreases. This explanation appeals to the divisive normalisation (DN) model based on EV[13,33]. Imagine choosing between two prospects, H and L, in two different choice-sets, H_1 vs. L_1, and H_2 vs. L_2, with the EV difference between H and L being the same across the two choice-sets (**Fig. 2g** left panel). DN applied to EVs ('EV + DN', hereafter) will shrink the EV difference between H and L more aggressively for set 2 than for set 1 because of the larger denominator in set 2, rendering set 2 a harder choice (lower accuracy). It is important to note that, in line with previous analyses[16,18], adding the HV + LV covariate to the GLMs does not explain away the interacting 'distractor' effect in binary trials (**Extended Data Fig. 3**). Qualitatively, the above 2 hypotheses ('AU' vs. 'EV + DN') both predict a positive main 'distractor' effect on binary choice accuracy, but their predictions for the (HV − LV) x (DV − HV) interaction could differ. For instance, DN might even predict a slightly positive, rather than negative, interacting distractor effect on binary accuracy—in this stimulus set, the divisively normalised Δ(EV) happens to be more positively correlated with DV − HV in easier trials (shared variance = 39.8%) than in harder trials (shared variance = 36.7%).

It is also important to note that, AU, on its own, can approximate this EV sum effect by nearly tripling the utility difference between H and L in set 1 compared with that in set 2, which also renders set 2 a harder choice (**Fig. 2g** right panel). These two models can thus mimic each other. To better distinguish between these candidate hypotheses, we fit a model with a softmax decision rule to each participant's binary choice probabilities (Methods). As expected, both the EV + DN model and the AU model (with a free λ parameter; mean λ estimate: .46, SE: .017) predict a positive 'distractor' main effect on binary accuracy (**Fig. 2h, i**). However, the AU model, but not the EV + DN model, reproduces a negative (HV − LV) x (DV − HV) interaction effect on accuracy (**Fig. 2i**), mirroring the human data (**Fig. 2e**). The AU model thus qualitatively provides a parsimonious account of the why 'distractor' effects occurred in binary trials.

Next, we used formal Bayesian model comparison to quantitatively identify the simplest possible model that can reproduce the binary-choice behaviour. For completeness, we added in the comparison a naïve expected-value (EV) model, and a recently proposed dual-route model, which relies on EV utility and flexibly arbitrates between DN and mutual-inhibition processes[17]. A vanilla DN model can be thought as a nested model within the dual-route model. All models were fitted to each participant's binary choices and reaction times (RTs) by optimising a joint likelihood function (Methods). Qualitatively, **Fig. 3a** shows that the naïve EV model fundamentally deviates from the human choice data: The model predicts a vertical gradient of choice accuracy constrained by HV − LV. When comparing these models head-to-head using a cross-validation scheme, we find that the AU model wins over any other model (**Fig. 3b**; protected exceedance probability $P_{pexc} > .99$; Methods). This result still holds robustly when including, in all models, subjective non-linear distortions of attributes[34] ('NL' in **Fig. 3b, c** right panels). Moreover, the RTs predicted by the divisive normalisation (DN) model mismatch the human RTs (**Fig. 3a**: 'EV + DN'). But this is not the sole reason why DN fails in the model

332   comparisons. DN still fails to win over the AU model even when we consider static versions of
333   the models fitted to the choice probabilities alone while ignoring the RTs (**Fig. 3c** 'Static
334   models'; Methods). These systematic model comparisons thus quantitatively support the AU
335   model as a remarkably simple account of the 'distractor' effects in binary trials (**Fig. 2i**).
336
The success of the AU model suggests that the reward attributes were not multiplicatively
conglomerated into a single EV dimension. To better illustrate the differences between AU-
and EV-based models, we plotted model predictions separately for different condition
categories in which H dominates L in one attribute only (single dom.) or in both attributes
simultaneously (double dom.; only 19% of all trials) (**Fig. 3d—f**). The EV model, being only
sensitive to the difference in the product of probability and reward, fails to capture any
performance variations across these distinct categories (because these categories are
orthogonal to the EV difference; **Fig. 3d**). By contrast, the AU model can capture these across-
category performance changes (**Fig. 3e**). Qualitatively, the dual-route model seems to be able
to capture some patterns of the human data on the binned maps (**Fig. 3a**: 'Dual-route'), but its
deviation from human behaviour becomes more salient when inspecting the model predictions
at each fixed level of EV difference (**Fig. 3f**). Taken together, we show that the AU model
reproduces the patterns of both accuracy and RT in binary-choice trials decisively better than
the models relying on EV or divisively normalised EV (also see **Supplementary Tables 1** and **2**
for model parameter estimates).
352
353   **A modest negative distractor effect operating on additive utility**
354
Because 'additive integration' is a decisively better model of binary-choice behaviour than
expected value (EV) based models are, here we re-assessed distractor effects after defining
the key variables using AU. To better define these variables, we fit the dynamic AU model (with
free λ weight; Methods: *Context-independent model*) to binary and ternary choices, separately,
and constructed subjective utility as AU = λ(X) + (1 − λ)(P). We then analysed relative choice
accuracy using a GLM with AU-based regressors: $AU_H − AU_L$ (AU difference between targets),
$AU_H + AU_L$ (AU sum), distractor variable (absolute: AU_D, or relative: $AU_D − AU_H$), distractor
variable x ($AU_H − AU_L$) interaction, and the interaction between each of these effects and 'C'
(Condition: T vs. B). The key regressors are the main distractor effect, 'distractor variable x C',
and the interacting distractor effect dependent on choice difficulty, 'distractor variable x (AU_H
$− AU_L$) x C', because these regressors assess the distractor effects in ternary choices over and
above the matched baseline performance (captured by the 'x C' interaction). First, we verified
that including the AU-sum regressors decisively improved the GLM's goodness-of-it, $\chi^2(2) >$
1.005×10^3, *p* < .0001; and the GLM with AU regressors had better goodness-of-it than the
GLM with EV regressors, $\chi^2(0) > 1.03 \times 10^4$, *p* < .0001 (for either absolute or relative distractor
variable). We found a significant *negative* main distractor effect, AU_D x C, on the choice
accuracy, *t*(143) = -2.27, *p* = .024 (uncorrected); however, this main effect was marginally
significant when using the relative distractor variable $AU_D − AU_H$, *t*(143) = -1.86, *p* = .065
(uncorrected). The interacting distractor effect was not significant *t*(143) < -.54, *p* > .1 (see
Supplementary Table 3 for a full report). We here reiterate that, by contrast, neither the main
nor the interacting distractor effects were significant in the GLM with EV-based regressors (*p*
> .3, uncorrected, **Fig. 2f** and **Extended Data Figs. 2**, **3**). These results based on subjective AU
fit more closely with recent reports showing a *negative* main distractor effect[13].
378

Distractor-related covariations and multiattribute context effects

Having revisited distractor effect while controlling for target-related confounding covariations, we now move into examining distractor-related covariations, i.e., whether multiattribute context effects were present in these datasets, and if so, whether they were related to the modest AU-based negative distractor effect we reported above.

Classic multiattribute context effects typically occur when a decoy alternative is added to a choice-set consisting of the two non-decoy alternatives (**Fig. 4a**). Two classic context effects are particularly relevant in this task because 84% of the ternary trials satisfy specific H, L, and D geometric (in the two-dimensional choice space) configurations that could give rise to these context effects (**Fig. 4a**). First, an attraction effect[3], whereby the probability of choosing a target over a competitor increases due to the presence of an 'inferior' *dominated* D near the target (also see **Fig. 1b—d** for an illustrative example); and second, a repulsion effect[29], whereby this pattern is reversed in the presence of a nearby 'superior' *dominating* D. We note in passing that other popular context effects, such as the similarity and the compromise effects, could not be examined here due to the absence or the very low frequency of occurrence of appropriate choice-sets (i.e., in these effects the decoys are required to be roughly iso-preferrable to the target or the competitor alternatives[35]).

404
Figure 4. Multiattribute context effects. (**a**) Attraction effect[3] can happen when D is dominated by H or
L. Repulsion effect[29] can happen when D dominates H or L. (**b**) T − B p(H over L) plotted as a function of
D's relative Euclidean distance to H vs. L in the attribute space and D's AU dominance – 'superior'
('inferior') D lies on a higher (lower) AU indifference line than both H and L. Error bars: ± s.e.m. across
participants (N = 144). (**c**) Condition-unspecific bias of p(H over L) in ternary conditions relative to binary
conditions. (**d**) Bias-corrected T − B p(H over L). Black asterisks: significant context effects (Bonferroni-
Holm corrected $p < .05$; two-tailed 1-sample t-tests against 0). (**e**) Bias-corrected T − B p(H over L)
predicted by different models. Grey asterisks: significant difference between model predictions and
human data (uncorrected $p < .05$; two-tailed paired-sample t-tests). (**f**) Main effect of D's AU dominance
(superior vs. inferior) on T − B relative accuracy change in human data and model predictions. (**g**)
Bayesian model comparison of context-dependent models (also see Extended Data Figs. 4, 5). (**h**) Model
recovery (Methods). Text in each cell: posterior model frequency; Heatmap: protected exceedance
probability (P_{pexc}) that a fitted model (each column) has the highest log-likelihood given input ternary-
trial data (choice probabilities and RTs) simulated by a certain model (each row).

Before characterising decoy effects, we considered the possibility that the change of relative
accuracy between binary (B) and ternary (T) choice reflects a condition-unspecific change in
behaviour, i.e., an accuracy reduction potentially induced by higher cognitive demands in the
ternary trials. We estimated this 'generic' bias by shuffling the mappings between ternary
conditions and their matched binary conditions (**Fig. 4c**; see Methods). After this bias was
corrected for each participant, the relative accuracy change from B to T was compared against
zero (i.e., a null hypothesis: T and B had no difference over and above the condition-unspecific
bias). The bias-corrected T − B relative accuracy change shows a strong attraction effect: The
relative choice accuracy dynamically decreases and increases as an inferior D gets closer to L
(n = 32 relevant trials in this category) and H (n = 33), respectively, $|t(143)| > 4.88$, $p < .0001$
(**Fig. 4d**). Meanwhile, a significant repulsion effect occurs when a superior D dominates H or L
in the attribute space, $t(143) = -2.53$, $p = .025$, particularly when D is closer to H (n = 41 relevant
trials in this category), but not when D is closer L (fewer trials n = 20 in this category; $t(143) = -$
1.09, $p = .28$, Bonferroni-Holm corrected). A repeated-measures ANOVA reveals a significant
interaction between the similarity structure (D closer to H vs. D closer to L) and the dominance
of D (inferior vs. superior), $F(1, 143) = 30.6$, $p < .0001$, partial $\eta^2 = .18$, on the T − B relative
accuracy change.

Of note, in line with the AU-based negative distractor effect we reported in the previous
section, the current analysis on multiattribute decoy effects also reveals a significant main
effect of D's AU dominance on relative accuracy change (repeated-measures ANOVA on T − B
relative accuracy change in all trials), $F(1, 143) = 6.51$, $p = .012$, partial $\eta^2 = .044$ (**Fig. 4f**:
'Human'). This overall dominance effect seems to be induced by a noticeable asymmetry in the
decoy effects: targeting H is more effective and the attraction effect is stronger than the
repulsion effect. Crucially, across participants there is a significant positive correlation between
the negative main distractor effect 'AU_D x C' (GLM in the previous section) and the negative
main effect of D's AU dominance here (Spearman's $\rho = .28$, $p = .00074$). This indicates that if a
participant had a stronger *asymmetry* in the decoy effects (D's AU dominance) then they would
also have a stronger AU-based negative distractor effect. We further interpret this
correspondence using computational modelling in the next section.

Selective gating explains multiattribute context effects and adapts to decision noise

Although the AU model successfully described behavioural responses in binary trials (**Fig. 3**), it
is essentially a context-independent model complying with the *independence from irrelevant*
alternatives (IIA) principle. That is, according to the AU model, the characteristics of D in
ternary trials should not lead to any preference change between the two available targets H
and L. In this section, we resort to computational modelling to understand why multiattribute
context effects occur in ternary trials. First, as shown in **Fig. 4e** leftmost panel, the T − B effects
in human data could not be explained by a context-independent AU model ('blind' to D, i.e.,
only taking H and L as inputs) with freely varying parameters across B and T conditions (the
free parameters could capture any global changes in behaviour due to, e.g., different noise
levels and/or attribute weighting, potentially induced by higher cognitive demands in the
ternary trials; Methods).

Next, we considered two models that can predict context effects in multiattribute choice:
selective integration (SI) and adaptive gain[29,36] (Methods). In the SI model, the gain of
processing on each attribute value relies on its rank within that attribute, with a selective gating
parameter w controlling the suppression strength for the low-rank attribute value. In the
adaptive gain model, each alternative is evaluated relative to the context statistics via a non-
linear function. We compared these models to the context-dependent dual-route model by
Chau et al., which had not been previously examined in relation to classic context effects[17]. As
shown in **Fig. 4e**, the SI model can reproduce all types of attraction and repulsion effects in the
data, but a dual-route model cannot. A systematic Bayesian random-effects model comparison
shows that SI prevails over all other models ($P_{pexc} > .99$; **Fig. 4g**), including the dual-route, DN,
or any context-independent model with either EV or AU as the utility function (**Extended Data**
Fig. 4). The adaptive gain model captures some key context effects, although not as closely as
the SI model does (fixed-effects: SI vs. adaptive gain, cross-validated log-likelihood ratio =
219.8, ΔBIC = -1194, pooled over participants; random-effects: SI's $P_{pexc} > .99$; **Fig. 4e**), and
explains the human data decisively better than the dual-route model (adaptive gain vs. dual-
route: cross-validated log-likelihood ratio = 48.58, ΔBIC = -806, pooled over participants;
adaptive gain's P_{pexc} = .78; see **Supplementary Table 4** for model parameters). A model recovery
procedure (Methods) also confirmed that our Bayesian model comparison was capable of
properly discriminating among these context-dependent models (SI, adaptive gain, and dual-
route; **Fig. 4h**).

Crucially, the SI model could lawfully reproduce the overall negative D's AU dominance effect
without relying on any additional mechanism such as divisive normalisation (DN), $F(1, 143)$ =
78.4, $p < .00001$, partial η^2 = .35, post-hoc t-test: $t(143)$ = -8.85, $p < .0001$ (**Fig. 4f**). By contrast,
the models that predict lawfully unidimensional distractor effect (dual-route and DN) could not
describe the multiattribute decoy effects (**Fig. 4e, f**; also see **Extended Data Fig. 5**). This
suggests that the negative D dominance effect is not the by-product of a unidimensional
distractor mechanism but instead falls out naturally from the presence of asymmetrical decoy
effects (i.e., stronger attraction effect, when H is targeted). The correlation between the D
dominance and AU distractor effects discussed above, corroborates the possibility that, to
some extent, the negative distractor effect is driven by asymmetrical decoy effects (**Fig. 4f**: SI
model mimics the negative D dominance effect).

How does the winning selective integration (SI) model capture the attraction and repulsion
effects? The way the model works in these two effects is shown in a schematic form in **Fig. 5a**
and **b**. Because SI selectively allocates reduced gain to 'locally losing' attribute values, it exerts
a stronger gating on the utility of option B when the decoy D dominates B (**Fig. 5b**) than when
D is dominated by B (**Fig. 5a**). Thus, the relative preference between A and B can be dynamically
reversed according to the dominance of D, giving rise to the opposing context effects of
attraction and repulsion.

507
Figure 5. Selective gating, context effects, and decision noise. (**a**, **b**) By virtue of SI, alternatives A, B, and
D are ranked within each attribute dimension; SI weights are then assigned to the sorted alternatives
accordingly (for illustration, $w_1 = 0$, $w_2 = .5$, and $w_3 = .9$). Attribute values are selectively suppressed in
proportion to the SI weights, i.e., lower ranked values are suppressed more strongly. As a result of SI
(assuming any $w_1 < w_2 <= w_3$), the additive utility (AU) of B is higher in the case of panel a than that of
B' in the case of panel b due to the distinct locations of decoy D. (**c**) Relationship between SI w and
decision noise. Red lines: robust linear regression fits (using Matlab's robustfit). β: softmax inverse
temperature. Top: binary trials ('B'); bottom: ternary trials ('T') (ternary SI w: mean across w_2 and w_3);
SI $w = 0$: lossless integration, i.e., attributes maintain their original values; SI $w > 0$: selective integration;
SI $w = 1$: attribute value shrinks to 0. ρ: Spearman's rank correlation coefficient. ***$p < .0001$. (**d**)
Relationship between SI w and drift sensitivity k (filled black) or decision bound (open grey).

519
520
Lastly, selective integration has been shown to maximise decision accuracy and economic
outcomes in the face of decision noise that arises when multiple attributes or pieces of
information need to be combined towards a decision[30,37]. Here, we examined whether SI
confers robustness on decisions by adapting to the individual decision noise levels. And if so, it
could provide a normative justification of these decoy biases as emergent properties of a
decision policy that maximises robustness against decision noise. After fitting a static version
of the SI model to choice probabilities (Methods), we found a positive correlation across
participants between the SI gating w and the temperature of a softmax choice function
(Spearman's $\rho(142) > .43$, $p < .0001$, for both binary and ternary choices; **Fig. 5c**). Additional
parameter-recovery simulations corroborated that these findings are not due to any trade-off
between model parameters (**Extended Data Fig. 6**). After fitting the dynamic SI model to
choices and RTs together, we found that the SI w negatively correlates with the utility drift
sensitivity (how effective a participant is in using the information about utility; Methods), but
not the height of the decision bound (**Fig. 5d**). These findings suggest that SI has an adaptive
role, as it selectively exaggerates the attribute difference between winning and losing
alternatives by just the right amount in proportion to decision noise.

Discussion

Context effects violate the axioms of rational choice theory and can shape our understanding of the computational mechanisms that underlie decision-making. Recent reports suggested that such effects do not occur only in multiattribute space, but also at the level of a single value dimension[13,16,17,38]. However, these reports diverge in their conclusions[14,18,39], with some studies showing a negative distractor effect while others, using risky-choice tasks, positive and interacting distractor effects. Here we focused on these risky-choice datasets and examined whether the positive and interacting distractor effects could afford alternative interpretations. We found that the previously reported positive and interacting effects can be explained away by confounding covariations among distractor variables and subjective utility, which in these datasets was shaped by additive and not multiplicative reward/probability integration. When we redefined distractor effects using the descriptively more adequate 'additive utility', we instead reported a modest negative distractor effect. Asides from this modest negative distractor effect, classic context (decoy) effects — determined by the multiattribute similarity and dominance relationship between the distractor and the available alternatives — occurred robustly. These context effects were asymmetric in magnitude, on average yielding an accuracy increase for inferior targets and an accuracy decrease for superior ones, mirroring thus the negative distractor effect.

These results clarify the role that an unavailable distractor alternative plays in decisions between two uncertain prospects. Notably, the negative distractor effect we reported is of rather small size. A plausible explanation of this negative distractor effect is that it could be driven, to some extent, by asymmetric multiattribute context effects. We make this conjecture for two reasons. First, from an empirical perspective, the 'dominance' effect arising from multiattribute decoy effects correlates with the negative distractor effect. Second, from a theoretical perspective, model comparison favours by large a model that can only produce multiattribute decoy effects and has no dedicated mechanism to generate unidimensional distractor effects. This alludes to a parsimonious account that precludes genuine unidimensional distractor effects. However, we interpret the link between the distractor and decoy effects with caution given that there are differences in the way the two effects were quantified. In the distractor effect, the key variable is defined continuously (i.e., the distractor's utility) while in decoy effects, 'dominance' is defined categorically (superior or inferior to the target). Similarly, a less parsimonious model in which both unidimensional distractor mechanism (i.e., divisive normalisation) and multiattribute context-sensitivities (i.e., selective integration) coexist has not been ruled out. Definitive conclusions on the link between distractor and decoy effects await new experimental designs in which the two types of effects can be quantified independently.

Of note, the multiattribute context effects occurring here are technically 'phantom' effects[40] due to the fact that the distractor could not be chosen; and contrary to most previous demonstrations, where the target and competitor alternatives are almost equally valuable, the effects we reported here arise even under a noticeable value difference between the target and the competitor[41].

In light of the stronger robust presence of decoy effects in these datasets, the hypothesis that multiattribute complexity is a key moderator of context dependencies, remains viable[8,42,43].

Encoding absolute information along several attributes is inefficient[2] and suffers from the *curse*
of dimensionality[44,45]. A plausible solution to circumvent these issues is to discard information
that is less important[46]. In a similar spirit, our selective integration model preferentially focuses
on larger values at the expense of smaller values, and because of this policy, context-effects
ensue. This selective policy potentially maximises robustness to decision noise[30,47], providing
thus a normative justification of contextual preference reversal. And although the selective
integration model had thus far been applied to dynamic (sequential) value accumulation
tasks[48], we here show that it can also account for behaviour in a static multiattribute task.
Nevertheless, we do not claim that SI, despite its simplicity and computational tractability, is
the only computational model that could explain the multiattribute context effects in this
task[49–52].
595
Notably, and contrary to the normative rule, participants in the datasets we analysed
integrated probability and payoff information additively and not multiplicatively. This additive
integration, or more generally, the processing of information in a 'within dimensions' fashion,
is probably what spurs contextual preference reversal in risky choice. However, unlike what we
observed here, a large and influential body of research in risky decision-making supports the
idea that non-linear transformations of probabilities and rewards are multiplicatively
combined (e.g., prospect theory[53]). This discrepancy can be potentially attributed to
differences in the stimuli employed in different experiments, with multiplicative integration
observed in numerically explicit gambles and additive integration when rewards and
probabilities are mapped onto and inferred from abstract non-numerical (perceptual)
dimensions[24–26,32].
607
To conclude, harnessing the power of open science, we scrutinised large datasets from
published studies (over 140 human participants) and re-assessed the role of the distractor
alternative in decisions under uncertainty. More broadly, we adopted an integrative approach
attempting to characterise the interplay between two types of context effects (unidimensional
and multiattribute), which had thus far been examined in isolation. Our findings contribute to
a large body of research[31,49,54,55] that challenges the standard tenet of neuroeconomics that
value representation is menu-invariant[56–58].
615
616

617 Methods
618
619 Multiattribute decision-making task and datasets
620
In the multiattribute decision-making task of Chau et al.[16], participants made a speeded choice
within 1.5 s between two available options (HV: high value; LV: low value) in the presence
('ternary') or absence ('binary') of a 3rd unavailable distractor option (D). On each trial, the 2
or 3 options appeared in different quadrants of a computer screen. Each option was a small
rectangle and its colour/orientation represented some level of reward magnitude/probability
(the feature-to-attribute mapping was counterbalanced across participants). There were equal
number of ternary (n = 150) and binary trials (n = 150). However, the ternary and binary trials
did not have 'one-to-one' mapping, i.e., some ternary trials had only 1 matched binary trial
with the same H and L options while others had several (also see **Extended Data Fig. 1**). The
available targets and the unavailable distractor were flagged by orange and pink surround
boxes, respectively, 0.1 s post stimulus onset. Participants received feedback about whether
the chosen option yielded a reward at the end of each trial. We re-analysed 5 published
datasets of this speeded-decision task (N = 144 human participants in total). These 5 datasets
all include ternary and binary trials: the original fMRI dataset (N = 21[6]), a *direct* replication
study (using exact trial sequence provided by Chau et al.) performed by Gluth et al. (Gluth
Experiment 4: N = 44), and additional replication experiments performed by Gluth et al. (Gluth
Experiments 1, 2, and 3; N = 79 in total[19]).
638
639 Computational modelling of behaviour
640
General architecture of dynamic models
We used the framework of feedforward inhibition (FFI) model to jointly fit choice probability
and RT. The FFI model conceptually 'interpolates' between a race model and a drift-diffusion
model[59]. Each accumulator is excited by the evidence for one alternative and inhibited by the
evidence for the other alternatives via feed-forward inhibition. Evidence units are ideal
integrators with no leak, and they receive crossed inhibition from different alternatives. The
activation of each integrator is x_i (for the ith alternative), which takes I_i as evidence input:
648

$$dx_i = (kI_i + I_0)dt + \xi\sqrt{dt} \tag{1}$$

Where k is a sensitivity parameter (drift rate coefficient, i.e., how effective the nervous system
is in using utility information), and I_0 a baseline drift, independent of I_i. ξ denotes Gaussian
noise of a zero mean and a variance of σ^2. The noise term is in proportion to the square-root
of dt because the noise variance itself is a linear function of dt. Evidence I_i is computed as the
utility of alternative i inhibited by the average utility across all other alternatives in a choice
set (assuming n alternatives in total including i):
655

$$I_i = U_i - c\left(\frac{\sum_{j \neq i} U_j}{n-1}\right) \tag{2}$$

656
657 Where c ($0 \leq c \leq 1$) is the FFI strength. When c = 0, the model becomes a classic race model;
658 when c = 1, it corresponds to a drift-diffusion model. The drift rate μ of FFI diffusion thus can
659 be rewritten as:

$$\mu_i = kU_i - ck\left(\frac{\sum_{j \neq i} U_j}{n-1}\right) + I_0 \tag{3}$$

660   The utility function U_i can take different forms of interest, such as expected value (EV), additive
661   utility (AU), or being adaptive to contexts (SI and adaptive gain models, see next).

663   We next derive the analytical solutions for the FFI dynamic system (equation 1). First, the
664   distribution of first-passage times t (i.e., decision-bound hitting times) is known to follow an
665   inverse Gaussian distribution[60]:

$$p(t; \theta, x_0, \mu) = \frac{\theta - x_0}{\sqrt{2\pi\sigma^2 t^3}} e^{\frac{-(\theta-x_0-\mu t)^2}{2\sigma^2 t}} \tag{4}$$

667   In which, x_0 is a starting point of the integrator, and θ, the height of decision bound. Then, we
668   can derive the probability of observing a response time RT on a given trial as:

$$p(t = T) = \frac{\theta - x_0}{\sqrt{2\pi\sigma^2 T^3}} e^{\frac{-(\theta-x_0-\mu T)^2}{2\sigma^2 T}} \tag{5}$$

671   Where $T = RT - t_{nd}$, and t_{nd} is a non-decision response delay. Now, we can obtain the
672   probability of observing a choice i but not choice j at time T as:

$$p(\text{choice} = i, t = T) = p(t_i = T)p(t_j > T) = p(t_i = T)[1 - p(t_j < T)] \tag{6}$$

674   That is, we can multiply the PDF for response i (e.g., H choice) with the cumulative probability
675   that the alternative response j (e.g., L choice) hits the decision bound if and only if at a time
676   later than T. Given that a CDF of an inverse Gaussian is expressible in terms of the CDF of the
677   standard Gaussian $\Phi(\cdot)$, i.e.,

$$p(t_j < T) = \Phi\left(\frac{\mu_j T - \theta + x_0}{\sigma\sqrt{T}}\right) + e^{\frac{2(\theta-x_0)\mu_j}{\sigma^2}} \Phi\left(\frac{-\mu_j T - \theta + x_0}{\sigma\sqrt{T}}\right) \tag{7}$$

680   and by substituting equation (7) into equation (6), we obtain the likelihood function of
681   observing choice i at time T as:

$$L(i, T) = \left[1 - \Phi\left(\frac{\mu_j T - \theta}{\sigma\sqrt{T}}\right) + e^{\frac{2\theta\mu_j}{\sigma^2}} \Phi\left(\frac{-\mu_j T - \theta}{\sigma\sqrt{T}}\right)\right] \frac{\theta}{\sigma\sqrt{2\pi T^3}} e^{\frac{-(\theta-\mu_i T)^2}{2\sigma^2 T}} \tag{8}$$

Further, we assume no bias in the starting point of accumulation, i.e., $x_0 = 0$, and a unit
variance of the noise term, i.e., $\sigma = 1$. This is equivalent to measuring the diffusion properties
such as sensitivity k and bound θ in units of σ, a convention in standard diffusion models that
prevents parameter trade-offs via a re-scaling of the diffusion space[61,62]. When fitting the
models to data, we maximised the sum of Log(L) (*LL*, hereafter) across trials given empirical
trial-by-trial choices and RTs. From this, and after getting the best-fitting model parameters,
we can get the model prediction of choice probability (equation 9) and mean RT (equation 10)
using the following integrals, respectively:

$$p(\text{choice} = i) = \int_0^{+\infty} L(i, t)dt \tag{9}$$

$$\mathbf{E}(t_i) = \int_0^{+\infty} \left(tL(i,t) \right) dt \bigg/ \int_0^{+\infty} L(i,t) dt \tag{10}$$

In practice, we used the trapezoidal numerical integration with a small enough dt = .001 s and
large enough T_{max} = 100 s. Empirically no negative drift rates were observed in any of the model
parameter estimates in any participant.

Context-independent model
The utility function U_i in the context-independent model is 'blind' to the distractor (D). When
being fitted to ternary trials, the context-independent model only takes H and L as inputs. For
instance, the context-independent AU model assumes additive utility, AU_H = (λ)HX + (1 - λ)HP,
and AU_L = (λ)LX + (1 - λ)LP, with λ being the attribute weight of reward magnitude ($0 \leq λ \leq 1$).

Selective integration (SI) model
We adopted the simplest form of SI model. The SI model discards information about choice
alternatives with relatively lower value in each attribute separately. Alternatives are compared
and then selectively gated based on their ranks within each attribute. The highest attribute
value remains unchanged ($w_1 = 0$), intermediate value gets suppressed by a multiplicative
weight w_2, whilst the lowest value gets more strongly suppressed by w_3 ($0 \leq w_2 \leq w_3 \leq 1$).
That is, the SI w represents the percent reduction in information processing gain in an
attribute. In case of a tie for the highest value, the two high values are unchanged, and the
lowest value is suppressed by w_3. By contrast, in case of a tie for the lowest value, the two low
values both get suppressed by w_3. After the selective gating within each attribute, which
transforms attribute values to X' and P', respectively, an additive utility is constructed for each
alternative via a weighted averaging, i.e., AU = (λ)X' + (1 - λ)P', with λ being the attribute weight
of reward magnitude ($0 \leq λ \leq 1$). This additive utility (after SI) is then fed into the FFI model as
the component U for each alternative (equation 3).

Adaptive gain model
The attribute value of a certain alternative, i, e.g., the reward magnitude, X_i, is inhibited by a
context mean across all alternatives in a choice set (e.g., n alternatives), which yields $\overline{X_i}$. $\overline{X_i}$
then passes through a sigmoidal transduction function with slope s and bias term b. This gain
control is adaptive in that it accommodates the contextual information. Importantly, the gain
control operates independently on each attribute, and it produces the final subjective attribute
value (X_i^{AG}) for the construction of additive utility for each alternative:

$$X_i^{AG} = 1 \bigg/ \left(1 + e^{\frac{b_x - \overline{X_i}}{s_x}} \right) \tag{11}$$

$$\overline{X_i} = X_i - \left(\frac{\sum_i X_i}{n} \right) \tag{12}$$

725   The adaptive gain modulation of P can be obtained by replacing X with P in the above two
726   equations. Ultimately, the utility of each alternative is computed as a weighted sum across
727   attribute values:

$$U_i = \lambda X_i^{AG} + (1 - \lambda) P_i^{AG} \tag{13}$$

Dual-route model

The dual-route model arbitrates between a vanilla mutual inhibition (MI) process and a MI process with additional divisive normalisation (DN). In the vanilla MI 'route', this model assumes that the evidence input to the accumulator is:

$$I_i = U_i - f_{MI}\left(\frac{\sum_i U_i}{n}\right) \tag{14}$$

Where U is expected value (EV), i.e., EV = XP, and f_{MI} is the inhibition strength of MI. In another rival route, the utility of each choice alternative is additionally divisively normalised by the sum of utilities across all alternatives (H + L in a binary trial; H + L + D in a ternary trial):

$$I_i^{DN} = U_i^{DN} - f_{MI}\left(\frac{\sum_i U_i^{DN}}{n}\right) \tag{15}$$

$$U_i^{DN} = U_i\Big/\sum_i U_i \tag{16}$$

The drift rate takes the same form as that in FFI: $\mu_i = kI_i + I_0$. Based on equation (8) and for clarity, we rewrite the two components in (8) as **g** and **G**:

$$\mathbf{G}(\mu, T, \theta, \sigma) = 1 - \Phi\left(\frac{\mu T - \theta}{\sigma\sqrt{T}}\right) + e^{\frac{2\theta\mu}{\sigma^2}}\Phi\left(\frac{-\mu T - \theta}{\sigma\sqrt{T}}\right) \tag{17}$$

$$\mathbf{g}(\mu, T, \theta, \sigma) = \frac{\theta}{\sigma\sqrt{2\pi T^3}}e^{\frac{-(\theta - \mu T)^2}{2\sigma^2 T}} \tag{18}$$

The likelihood of the DN route and the vanilla route arriving at the decision bound first to yield a choice i is, respectively:

$$L^{DN}(i, T) = \mathbf{g}(\mu_i^{DN}, T, \theta, \sigma)\mathbf{G}(\mu_j^{DN}, T, \theta, \sigma)\mathbf{G}(\mu_i, T, \theta, \sigma)\mathbf{G}(\mu_j, T, \theta, \sigma) \tag{19}$$

$$L(i, T) = \mathbf{g}(\mu_i, T, \theta, \sigma)\mathbf{G}(\mu_j, T, \theta, \sigma)\mathbf{G}(\mu_i^{DN}, T, \theta, \sigma)\mathbf{G}(\mu_j^{DN}, T, \theta, \sigma) \tag{20}$$

The final likelihood function of choice i at time T is thus: $L^{DN}(i, T) + L(i, T)$. These closed-form analytical solutions of choice probability and mean RT, as given by equations (9) and (10), match well with the model simulations performed in Chau et al. (2020)[17]. Empirically the trial-by-trial model predictions of a model with free σ (one for each route) vs. a model with $\sigma = 1$ are highly similar (across-participants mean Pearson's correlation coefficient $r(148) = .96$ for ternary choice probabilities, $r(148) = .98$ for binary choice probabilities, $r(148) = .97$ for ternary RTs, $r(148) = .88$ for binary RTs). Here we chose the simpler model with unit σ (lower BIC compared to the free σ model: -169 for ternary trials, -790 for binary trials, summed across participants).

Static models

The static models were fit to trial-by-trial human choice probability (while ignoring RT). These models assume a softmax function that takes as inputs the options' utilities (AU, EV, or

759   divisively normalised EV, see **Fig. 3**) and controls the level of decision noise via an inverse
760   temperature parameter β:

$$p(\text{choice} = i) = \frac{e^{\beta U_i}}{\sum_i e^{\beta U_i}} \tag{21}$$

761
The model-predicted and the empirical choice probabilities were then used to calculate the
binomial log-likelihood: $LL \propto p_e \log(p_m) + (1 - p_e) \log(1 - p_m)$, in which p_m and p_e
denotes the model-predicted and empirical p(H over L), respectively.

Model fitting, comparison, and recovery
Models were fit to data via maximising the log-likelihood summed over trials. Because the LL
functions all have analytical solutions, Matlab's fmincon was used for parameter optimisation.
To avoid local optima, we refit each model to each participant's behavioural data at least 10
times using a grid of randomly generated starting values for the free parameters. Conversative
criteria were used during the optimisation search: MaxFunEvals = MaxIter = 5,000; TolFun =
TolX = 10^{-10}. We then calculated each model's posterior frequency and protected exceedance
probability (i.e., the probability corrected for chance level that a model is more likely than any
others in describing the data) using the variational Bayesian analysis (VBA) toolbox[63,64]. To be
consistent with the methods in Chau et al.[17], we fit models to those trials with either H or L
responses whilst ignoring a very small portion of trials in which D was accidentally chosen
(median proportion of D choices: 4%, IQR: [2%, 8%], across participants).

Model comparison relied on cross-validation. That is, for each participant, we split the 150
trials into 5 folds and then fit each model to a 'training' set comprising 4 random folds of trials,
obtained the best-fitting parameters, and finally calculated the LL summed across trials in the
left-out 'test' fold. This process was repeated over test folds and the final cross-validated LL
was computed as the mean LL across cross-validation folds. Model recovery was carried out by
first simulating each model's behaviour (choice probability and RT) with its own best-fitting
parameters obtained from fitting the model to each participant's raw data; then cross-fitting
all models of interest to the simulated behaviour and calculating the LLs summed over trials;
and finally comparing models' goodness-of-fit using Bayesian model comparison.

Subjective distortion of reward attributes
When modelling binary-choice behaviour, in addition to assuming linear subjective
representations of reward attributes for simplicity, we also considered non-linear subjective
functions[34]. The probability distortion undergoes a log-odds function that converts a
probability value P to P_d, in a flexible manner (S-shape, inverted S-shape, concave, or convex,
depending on parameterisation), whereas the magnitude distortion follows a power function
that converts X to X_d:

$$\log\left(\frac{P_d}{1 - P_d}\right) = \eta \log\left(\frac{P}{1 - P}\right) + (1 - \eta) \log\left(\frac{P_0}{1 - P_0}\right) \tag{22}$$

$$X_d = X^\gamma \tag{23}$$

796   Where $\eta > 0$, P_0 ($0 < P_0 < 1$), and $\gamma > 0$ are the 3 parameters controlling the extent of non-
797   linearity of the distortion functions.

798
799

Condition-nonspecific response bias correction

Choice behaviour can differ between a binary condition and a ternary condition, simply due to the increased number of options (higher cognitive demands). To estimate these condition-nonspecific biases, we used a permutation approach to shuffling the mappings between the ternary conditions and their matched binary conditions (5,000 permutations). This yielded a mean bias term for the 'T minus matched B' data, and was eventually removed from the re-referenced ternary performance ('T − B'), for relative accuracy and for RT, respectively.

Generalised linear model (GLM) analysis of relative choice accuracy

We used GLM approach to analysing choice behaviour. For ternary conditions, we focused on the *relative* accuracy, i.e., the proportion of H choices among trials with H or L choices (while ignoring a small number of D-choice trials), which has been commonly used as a measure of the violation of the Independence from Irrelevant Alternatives (IIA) principle. Matched binary trials were identified for each ternary trial (see **Extended Data Fig. 1**). Among the 150 ternary trials there are 149 unique ternary conditions with a unique combination of probability (P) and magnitude (X) attributes across the 3 alternatives (H, L, and D), whereas among the 150 binary trials there are only 95 unique conditions with a specific combination of P and X across the 2 available options (H and L). The ternary and binary trials do not have 'one-to-one' mapping. Some ternary trials have more than 1 matched binary trial. The different counts of matched binary trials were explicitly considered as 'observation weights' in the GLM. We used logit binomial GLM to analyse trial-by-trial relative choice accuracy (MATLAB's glmfit with 'binomial' distribution and 'logit' link function). The GLMs in **Fig. 2** (**d** and **e**; using relative distractor variable 'DV − HV') and **Extended Data Fig. 2** (using absolute distractor variable 'DV') were specified as follows:

$$\text{Logit}(p(\text{H over L})) \sim \beta_0 + \beta_1\, z(\text{HV} - \text{LV}) + \beta_2\, z(\text{DV} - \text{HV}) + \beta_3\, z(\text{HV} - \text{LV}) \times z(\text{DV} - \text{HV})$$
$$\text{Logit}(p(\text{H over L})) \sim \beta_0 + \beta_1\, z(\text{HV} - \text{LV}) + \beta_2\, z(\text{DV}) + \beta_3\, z(\text{HV} - \text{LV}) \times z(\text{DV})$$

$z()$: z-score normalisation of the regressor vector. The interaction terms were constructed *after* individual component terms were z-scored[18]. The analysis shown in **Fig. 2f** combined ternary (T) and binary (B) relative accuracies in a single GLM and assessed how distractor-related effects interacted with 'Condition' (i.e., 'C', a dummy variable: 0 for B, 1 for T). The code for reproducing Fig. 2 and Extended Data Fig. 2 GLMs can be found here:
https://github.com/YinanCao/multiattribute-distractor/

Construction of binned maps

The choice-accuracy and RT maps (**Fig. 2b**, **c**; **Fig. 3a**) were constructed using the exact binning approach of Chau et al. (2020)[17]. Data were averaged using a sliding square window inside the space defined by the 2 expected-value differences, (DV − HV) and (HV − LV). The edge length of the window is 30% quantile difference along each dimension, with step-size being equal to 1% quantile difference. This binning approach smooths the data and results in a map of size 71-by-71.

Acknowledgements
We thank the authors of the original studies for sharing their data publicly (Chau et al., 2014, 2020: https://doi.org/10.5061/dryad.040h9t7; Gluth et al. (2018): https://osf.io/8r4fh/). This work was supported by the EU Horizon 2020 Research and Innovation Program (ERC starting grant no. 802905) to K.T. The funders had no role in study design, data collection and analysis, decision to publish or preparation of the manuscript.

Contributions
Y.C. performed the modelling and analyses. K.T. supervised all stages of the work. Y.C. and K.T. wrote the paper.

Code availability
https://github.com/YinanCao/multiattribute-distractor/

Competing interests
The authors declare no competing interests.

References

1. Stone, L. S. & Thompson, P. Human speed perception is contrast dependent. *Vision Res.* **32**, 1535–1549 (1992).
2. Summerfield, C. & Tsetsos, K. Do humans make good decisions? *Trends Cogn. Sci.* **19**, 27–34 (2015).
3. Huber, J., Payne, J. W. & Puto, C. Adding asymmetrically dominated alternatives: Violations of regularity and the similarity hypothesis. *J. Consum. Res.* **9**, 90–98 (1982).
4. Dumbalska, T., Li, V., Tsetsos, K. & Summerfield, C. A map of decoy influence in human multialternative choice. *Proc. Natl. Acad. Sci. U. S. A.* **117**, 25169–25178 (2020).
5. Vlaev, I., Chater, N., Stewart, N. & Brown, G. D. A. Does the brain calculate value? *Trends Cogn. Sci.* **15**, 546–554 (2011).
6. Chau, B. K. H., Kolling, N., Hunt, L. T., Walton, M. E. & Rushworth, M. F. S. A neural mechanism underlying failure of optimal choice with multiple alternatives. *Nat. Neurosci.* **17**, 463–470 (2014).
7. Louie, K., Khaw, M. W. & Glimcher, P. W. Normalization is a general neural mechanism for context-dependent decision making. *Proc. Natl. Acad. Sci. U. S. A.* **110**, 6139–6144 (2013).
8. Luce, R. D. The choice axiom after twenty years. *J. Math. Psychol.* **15**, 215–233 (1977).
9. Rieskamp, J., Busemeyer, J. R. & Mellers, B. A. Extending the bounds of rationality: Evidence and theories of preferential choice. *J. Econ. Lit.* **44**, 631–661 (2006).
10. Busemeyer, J. R., Gluth, S., Rieskamp, J. & Turner, B. M. Cognitive and neural bases of multi-attribute, multi-alternative, value-based decisions. *Trends Cogn. Sci.* **23**, 251–263 (2019).
11. Hunt, L. T., Dolan, R. J. & Behrens, T. E. J. Hierarchical competitions subserving multi-attribute choice. *Nat. Neurosci.* **17**, 1613–1622 (2014).
12. Tsetsos, K., Usher, M. & Chater, N. Preference reversal in multiattribute choice. *Psychol. Rev.* **117**, 1275–1293 (2010).
13. Turner, B. M., Schley, D. R., Muller, C. & Tsetsos, K. Competing theories of multialternative, multiattribute preferential choice. *Psychol. Rev.* **125**, 329–362 (2018).
14. Usher, M. & McClelland, J. L. Loss aversion and inhibition in dynamical models of multialternative choice. *Psychol. Rev.* **111**, 757–769 (2004).
15. Bogacz, R., Brown, E., Moehlis, J., Holmes, P. & Cohen, J. D. The physics of optimal decision making: a formal analysis of models of performance in two-alternative forced-choice tasks. *Psychol. Rev.* **113**, 700–765 (2006).

16.   Gluth, S., Kern, N., Kortmann, M. & Vitali, C. L. Value-based attention but not divisive normalization
influences decisions with multiple alternatives. *Nat Hum Behav* **4**, 634–645 (2020).
17.   Carandini, M. & Heeger, D. J. Normalization as a canonical neural computation. *Nat. Rev. Neurosci.*
13, 51–62 (2011).
18.   Chau, B. K., Law, C.-K., Lopez-Persem, A., Klein-Flügge, M. C. & Rushworth, M. F. Consistent
patterns of distractor effects during decision making. *Elife* **9**, (2020).
19.   Gluth, S., Spektor, M. S. & Rieskamp, J. Value-based attentional capture affects multi-alternative
decision making. *Elife* **7**, (2018).
20.   von Neumann, J. & Morgenstern, O. *Theory of Games and Economic Behavior*. (Princeton
University Press, 2007).
21.   Bernoulli, D. Exposition of a New Theory on the Measurement of Risk. *Econometrica* **22**, 23–36
(1954).
22.   Tversky, A. & Kahneman, D. Advances in prospect theory: Cumulative representation of
uncertainty. *J. Risk Uncertain.* **5**, 297–323 (1992).
23.   Pratt. Risk aversion in the small and in the large. *Uncertainty in economics* (1978).
24.   Weber, E. U., Shafir, S. & Blais, A.-R. Predicting risk sensitivity in humans and lower animals: risk as
variance or coefficient of variation. *Psychol. Rev.* **111**, 430–445 (2004).
25.   Rouault, M., Drugowitsch, J. & Koechlin, E. Prefrontal mechanisms combining rewards and beliefs
in human decision-making. *Nat. Commun.* **10**, 301 (2019).
26.   Stewart, N. Information integration in risky choice: identification and stability. *Front. Psychol.* **2**,
301 (2011).
27.   Farashahi, S., Donahue, C. H., Hayden, B. Y., Lee, D. & Soltani, A. Flexible combination of reward
information across primates. *Nat Hum Behav* **3**, 1215–1224 (2019).
28.   Peterson, J. C., Bourgin, D. D., Agrawal, M., Reichman, D. & Griffiths, T. L. Using large-scale
experiments and machine learning to discover theories of human decision-making. *Science* **372**,
1209–1214 (2021).
29.   Lu, Z.-L. & Dosher, B. A. Characterizing observers using external noise and observer models:
assessing internal representations with external noise. *Psychol. Rev.* **115**, 44–82 (2008).
30.   Tsetsos, K. *et al.* Economic irrationality is optimal during noisy decision making. *Proc. Natl. Acad.*
Sci. U. S. A. **113**, 3102–3107 (2016).
31.   Hayden, B. Y. & Niv, Y. The case against economic values in the orbitofrontal cortex (or anywhere
else in the brain). *Behav. Neurosci.* **135**, 192–201 (2021).
32.   Bongioanni, A. *et al.* Activation and disruption of a neural mechanism for novel choice in monkeys.
Nature **591**, 270–274 (2021).
33.   Pirrone, A., Reina, A., Stafford, T., Marshall, J. A. R. & Gobet, F. Magnitude-sensitivity: rethinking
decision-making. *Trends Cogn. Sci.* **26**, 66–80 (2022).
34.   Zhang, H. & Maloney, L. T. Ubiquitous log odds: a common representation of probability and
frequency distortion in perception, action, and cognition. *Front. Neurosci.* **6**, 1 (2012).
35.   Spektor, M. S., Bhatia, S. & Gluth, S. The elusiveness of context effects in decision making. *Trends*
Cogn. Sci. **25**, 843–854 (2021).
36.   Li, V., Michael, E., Balaguer, J., Castañón, S. H. & Summerfield, C. Gain control explains the effect
of distraction in human perceptual, cognitive, and economic decision making. *Proceedings of the*
National Academy of Sciences **115**, E8825–E8834 (2018).
37.   Wyart, V. & Koechlin, E. Choice variability and suboptimality in uncertain environments. *Current*
Opinion in Behavioral Sciences **11**, 109–115 (2016).
38.   Webb, R., Glimcher, P. W. & Louie, K. Divisive normalization does influence decisions with multiple
alternatives. *Nat Hum Behav* (2020) doi:10.1038/s41562-020-00941-5.
39.   Gluth, S., Kern, N. & Vitali, C. L. Reply to: Divisive normalization does influence decisions with
multiple alternatives. *Nat Hum Behav* (2020) doi:10.1038/s41562-020-00942-4.
40.   Pettibone, J. C. & Wedell, D. H. Testing alternative explanations of phantom decoy effects. *J. Behav.*
Decis. Mak. **20**, 323–341 (2007).

41. Farmer, G. D., Warren, P. A., El-Deredy, W. & Howes, A. The effect of expected value on attraction
effect preference reversals. *J. Behav. Decis. Mak.* **30**, 785–793 (2017).
42. Juechems, K. & Summerfield, C. Where Does Value Come From? *Trends Cogn. Sci.* **23**, 836–850
(2019).
43. Fellows, L. K. Deciding how to decide: ventromedial frontal lobe damage affects information
acquisition in multi-attribute decision making. *Brain* **129**, 944–952 (2006).
44. Sutton, R. S. Learning to predict by the methods of temporal differences. *Mach. Learn.* **3**, 9–44
(1988).
45. Bellman, R. E. *Dynamic programming*. (Princeton University Press, 1957).
46. Niv, Y. Learning task-state representations. *Nat. Neurosci.* **22**, 1544–1553 (2019).
47. Luyckx, F., Spitzer, B., Blangero, A., Tsetsos, K. & Summerfield, C. Selective integration during
sequential sampling in posterior neural signals. *Cereb. Cortex* **30**, 4454–4464 (2020).
48. Usher, M., Tsetsos, K., Glickman, M. & Chater, N. Selective integration: An attentional theory of
choice biases and adaptive choice. *Curr. Dir. Psychol. Sci.* **28**, 552–559 (2019).
49. Noguchi, T. & Stewart, N. Multialternative decision by sampling: A model of decision making
constrained by process data. *Psychol. Rev.* **125**, 512–544 (2018).
50. Trueblood, J. S., Brown, S. D. & Heathcote, A. The multiattribute linear ballistic accumulator model
of context effects in multialternative choice. *Psychol. Rev.* **121**, 179–205 (2014).
51. Bhatia, S. Associations and the accumulation of preference. *Psychol. Rev.* **120**, 522–543 (2013).
52. Roe, R. M., Busemeyer, J. R. & Townsend, J. T. Multialternative decision field theory: A dynamic
connectionst model of decision making. *Psychol. Rev.* **108**, 370–392 (2001).
53. Kahneman, D. & Tversky, A. Prospect Theory: An analysis of decisions under risk. *Econometrica* **47**,
278 (1979).
54. Roesch, M. R., Taylor, A. R. & Schoenbaum, G. Encoding of time-discounted rewards in
orbitofrontal cortex is independent of value representation. *Neuron* **51**, 509–520 (2006).
55. Soltani, A., De Martino, B. & Camerer, C. A range-normalization model of context-dependent
choice: a new model and evidence. *PLoS Comput. Biol.* **8**, e1002607 (2012).
56. Kable, J. W. & Glimcher, P. W. The neurobiology of decision: consensus and controversy. *Neuron*
63, 733–745 (2009).
57. Levy, D. J. & Glimcher, P. W. The root of all value: a neural common currency for choice. *Curr. Opin.*
Neurobiol. **22**, 1027–1038 (2012).
58. Padoa-Schioppa, C. & Assad, J. A. The representation of economic value in the orbitofrontal cortex
is invariant for changes of menu. *Nat. Neurosci.* **11**, 95–102 (2008).
59. Mazurek, M. E., Roitman, J. D., Ditterich, J. & Shadlen, M. N. A role for neural integrators in
perceptual decision making. *Cereb. Cortex* **13**, 1257–1269 (2003).
60. Usher, M., Olami, Z. & McClelland, J. L. Hick's law in a stochastic race model with speed–accuracy
tradeoff. *J. Math. Psychol.* **46**, 704–715 (2002).
61. Drugowitsch, J., DeAngelis, G. C., Klier, E. M., Angelaki, D. E. & Pouget, A. Optimal multisensory
decision-making in a reaction-time task. *Elife* **3**, (2014).
62. Palmer, J., Huk, A. C. & Shadlen, M. N. The effect of stimulus strength on the speed and accuracy
of a perceptual decision. *J. Vis.* **5**, 376–404 (2005).
63. Rigoux, L., Stephan, K. E., Friston, K. J. & Daunizeau, J. Bayesian model selection for group studies—
revisited. *Neuroimage* **84**, 971–985 (2014).
64. Daunizeau, J., Adam, V. & Rigoux, L. VBA: a probabilistic treatment of nonlinear models for
neurobiological and behavioural data. *PLoS Comput. Biol.* **10**, e1003441 (2014).

Extended Data

Extended Data Figure 1 (related to Fig. 2). Distinctions between our baselining approach and
the method in the original study[16]. (**a**) Method in the original study[16]: A schematic showing that
the mean DV across relevant ternary trials ('T') is taken as a notional DV for each individual
binary trial ('B'). For each participant, among the 150 T trials there are 149 unique T conditions
with a specific combination of P and X attributes across the 3 alternatives, while among the
150 B trials there are only 95 unique B conditions with a specific combination of P and X across
the 2 options. The T and B trials do not have one-to-one mapping even if the unique stimulus
positions (among 4 quadrants of the screen) are taken into consideration. (**b**) A successful
reproduction of an invalid control analysis in the *Supplementary Fig. 3b* of the original study[16]:
"The effect of HV-D on human behavior was specific to distractor trials" using the notional DV
depicted in panel a. (**c**) Our baselining approach uses a new dependent variable, the trial-by-
trial baseline accuracy, via identifying all matched B trials (number of trials 1<= nB <=6) of every
T trial. Of note, when analysing choice accuracies in B trials using logistic regression (e.g., Fig.
2), Matlab's glmfit takes a 2-column response matrix whose first column indicates the number
of correct responses (H choices) for each observation and second column indicates nB for each
observation.

1010

1011

1018 **Extended Data Figure 2** (related to Fig. 2). Re-assessing distractor effects beyond target-related
1019 covariations. The only difference between this figure and Fig. 2 in the main text is that the
1020 regressor DV − HV in Fig. 2 is replaced by DV here. Error bars = ± s.e.m. (N = 144 participants).
1021

Extended Data Figure 3 (related to Fig. 2). Re-assessing distractor effects beyond target-related covariations. The GLMs here included an additional regressor HV + LV. Error bars = ± s.e.m. (*N* = 144 participants). Asterisks: significant effects (*p* < .05; 2-sided 1-sample *t*-tests of GLM beta coefficients against 0) following Holm's sequential Bonferroni correction for multiple comparisons.

Extended Data Figure 4 (related to Fig. 4). Bayesian random-effects model comparison based on cross-validated log-likelihood (5 folds). SI: Selective integration model; Adap. Gain: adaptive gain model; CI: context independent; EV: expected value; AU: additive utility.

1076 **Extended Data Figure 5** (related to Fig. 4). Dual-route and divisive normalisation (DN) model
1077 predictions for the relative accuracy change (Ternary minus Binary, T − B) as a function of (**a**)
1078 both D's AU dominance (colour of the bars) and D's position similarity to H and L in the 2D
1079 attribute space, or (**b**) D's AU dominance only (main effect).
1080

1081

Extended Data Figure 6 (related to Fig. 5). Parameter recovery. (a, b) Recovery of SI model parameters by simulating choice probabilities (1,000 trials) based on a grid of uniformly distributed parameters' values (n = 800 each) and then estimating the best-fitting parameters. (c, d) Each row shows a case of simulating choice probabilities by varying 1 model parameter while fixing all other parameters (λ = 0.5, β = 10, SI w = 0.5) and then estimating the best-fitting parameter values via model fitting. On-diagonal panels show the recovery of each parameter as a function of itself (all |Pearson's r| > .99), whilst off-diagonal panels suggest that variation in irrelevant parameters do not bias the recovery of any given parameter of interest (all |Pearson's r| < .056, p > .1).

Supplementary Information

1101

Supplementary Table 1 (related to Fig. 3). Optimal parameter estimates of dynamic models: Mean (SE) and cross-validated log-likelihood (CV LL).

1104

AU FFI linear (n = 6 free parameters)

λ	k	θ	I_0	t_{nd}	c	CV LL
.475 (.017)	3.89 (.11)	3.21 (.097)	2.81 (.06)	.141 (.012)	.76 (.011)	-958.5

EV FFI linear (n = 5)

k	θ	I_0	t_{nd}	c	CV LL
3.38 (.097)	3.076 (.09)	3.14 (.061)	.152 (.012)	.85 (.01)	-1191.3

EV (+ DN) FFI linear (n = 5)

k	θ	I_0	t_{nd}	c	CV LL
1.96 (.061)	2.92 (.097)	2.59 (.07)	.167 (.012)	.38 (.009)	-1286.1

Dual-route EV linear (n = 6)

k	k^{DN}	θ	I_0	t_{nd}	f_{MI}	CV LL
5.62 (.21)	2.53 (.11)	2.77 (.08)	1.99 (.064)	.169 (.011)	.75 (.021)	-1150

1109

AU FFI non-linear (n = 9)

λ	k	θ	I_0	t_{nd}	c	η	P_0	γ	CV LL
.337 (.023)	11.7 (.61)	3.26 (.099)	1.29 (.17)	.144 (.012)	.77 (.011)	5.6 (1.04)	.69 (.032)	4.8 (.88)	-822

EV FFI non-linear (n = 8)

k	θ	I_0	t_{nd}	c	η	P_0	γ	CV LL
6.25 (.41)	3.22 (.09)	2.48 (.16)	.15 (.012)	.81 (.012)	2.39 (.57)	.56 (.032)	1.04 (.14)	-897

EV (+ DN) FFI non-linear (n = 8)

k	θ	I_0	t_{nd}	c	η	P_0	γ	CV LL
3.52 (.44)	3.07 (.096)	2.67 (.083)	.16 (.012)	.45 (.015)	17.98 (1.7)	.61 (.03)	13.8 (1.4)	-1052

Dual-route EV non-linear (n = 9)

k	k^{DN}	θ	I_0	t_{nd}	f_{MI}	η	P_0	γ	CV LL
6.58 (.38)	4.29 (.40)	2.95 (.09)	1.69 (.12)	.16 (.011)	.67 (.027)	9.23 (1.28)	.56 (.03)	5.74 (.96)	-927

 Supplementary Table 2 (related to Fig. 2, 3). Optimal parameter estimates of static models:
1127 Mean (SE), and cross-validated log-likelihood (CV LL).
1128

1129

AU softmax linear (n = 2 free parameters)

λ	β	CV LL
.457 (.017)	9.15 (.302)	-2330.1

1130

EV softmax linear (n = 1)

β	CV LL
6.79 (.198)	-2645.5

1131

EV (+ DN) softmax linear (n = 1)

β	CV LL
3.35 (.11)	-2656.4

1132

1133

AU softmax non-linear (n = 5)

λ	β	η	P_0	γ	CV LL
.327 (.019)	16.4 (.47)	4.72 (.938)	.669 (.031)	4.43 (.792)	-2193.3

1134

EV softmax non-linear (n = 4)

β	η	P_0	γ	CV LL
33.9 (8.81)	3.69 (.74)	.524 (.036)	.82 (.13)	-2388.8

1135

EV (+ DN) softmax non-linear (n = 4)

β	η	P_0	γ	CV LL
31.3 (6.53)	13.5 (1.62)	.607 (.031)	9.44 (1.24)	-2481.2

1161 **Supplementary Table 3** (related to Fig. 2). GLMs using subjective additive-utility (AU)
1162 regressors. * Significant effects ($p < .05$; 2-sided 1-sample t-tests of GLM coefficients against
1163 0) following Holm's sequential Bonferroni correction for multiple comparisons. C: 'Condition'
1164 (binary vs. ternary).

1165

1166 *AU_D as (absolute) distractor variable (with 'AU sum' covariate):*

	T value	p-value (uncorrected)
$AU_H - AU_L$	12.3	< .0001*
$AU_H + AU_L$	11.9	< .0001*
AU_D	2.37	.0193
$(AU_H - AU_L) \times AU_D$	-.099	.92
$(AU_H - AU_L) \times C$	-6.09	< .0001*
$(AU_H + AU_L) \times C$	-5.24	< .0001*
$AU_D \times C$	-2.27	.024
$(AU_H - AU_L) \times AU_D \times C$	-1.64	.102
C	-5.04	< .0001*

1167 *AU_D as (absolute) distractor variable (without 'AU sum' covariate):*

	T value	p-value (uncorrected)
$AU_H - AU_L$	13.9	< .0001*
AU_D	3.93	< .001*
$(AU_H - AU_L) \times AU_D$	-.44	.66
$(AU_H - AU_L) \times C$	-6.56	< .0001*
$AU_D \times C$	-2.87	.0047*
$(AU_H - AU_L) \times AU_D \times C$	-1.74	.083
C	-8.06	< .0001*

1168 *$AU_D - AU_H$ as (relative) distractor variable (with 'AU sum' covariate):*

	T value	p-value (uncorrected)
$AU_H - AU_L$	13.1	< .0001*
$AU_H + AU_L$	11.7	< .0001*
$AU_D - AU_H$	-.35	.73
$(AU_H - AU_L) \times (AU_D - AU_H)$	-4.25	< .0001*
$(AU_H - AU_L) \times C$	-6.24	< .0001*
$(AU_H + AU_L) \times C$	-5.63	< .0001*
$(AU_D - AU_H) \times C$	-1.86	.065
$(AU_H - AU_L) \times (AU_D - AU_H) \times C$	-.54	.59
C	-5.39	< .0001*

1169 *$AU_D - AU_H$ as (relative) distractor variable (without 'AU sum' covariate):*

	T value	p-value (uncorrected)
$AU_H - AU_L$	13.7	< .0001*
$AU_D - AU_H$	-10.2	< .0001*
$(AU_H - AU_L) \times (AU_D - AU_H)$	-5.65	< .0001*
$(AU_H - AU_L) \times C$	-6.41	< .0001*
$(AU_D - AU_H) \times C$	1.95	.054
$(AU_H - AU_L) \times (AU_D - AU_H) \times C$	.22	.83
C	-7.18	< .0001*

1170

1171 **Supplementary Table 4** (related to Fig. 4). Optimal parameter estimates of context-dependent
1172 dynamic models: Mean (SE), and cross-validated log-likelihood (CV LL).
1173

1174

SI AU FFI (n = 8 free parameters) [Ternary]								
λ	SI w_2	SI w_3	k	θ	I_0	t_{nd}	c	CV LL
.534	.25	.43	2.44	4.73	3.82	.024	.786	-1310.5
(.019)	(.029)	(.034)	(.078)	(.108)	(.074)	(.006)	(.02)	

1175

SI AU FFI (n = 7) [Binary]							
λ	SI w_2	k	θ	I_0	t_{nd}	c	CV LL
.487	.31	3.54	3.21	2.91	.145	.74	-915
(.016)	(.02)	(.11)	(.097)	(.061)	(.012)	(.015)	

1176

1177

Adaptive Gain AU FFI (n = 10) [Ternary]										
λ	b_p	s_p	b_x	s_x	k	θ	I_0	t_{nd}	c	CV LL
.43	-.24	.23	.033	.24	44.2	4.7	.54	.023	.56	-1530
(.027)	(.12)	(.04)	(.12)	(.056)	(5.84)	(.11)	(.44)	(.006)	(.034)	

1178

Adaptive Gain AU FFI (n = 10) [Binary]										
λ	b_p	s_p	b_x	s_x	k	θ	I_0	t_{nd}	c	CV LL
.42	-.16	.15	-.092	.18	16.3	3.16	-2.68	.15	.19	-1012
(.023)	(.039)	(.02)	(.074)	(.051)	(2.4)	(.09)	(.43)	(.012)	(.02)	

1179

1180

Dual-route EV (n = 6) [Ternary]						
k	k^{DN}	θ	I_0	t_{nd}	f_{MI}	CV LL
3.21 (.15)	1.68 (.09)	4.16 (.097)	2.85 (.065)	.035 (.008)	.72 (.028)	-1579

1181

Dual-route EV (n = 6) [Binary]						
k	k^{DN}	θ	I_0	t_{nd}	f_{MI}	CV LL
5.62 (.21)	2.53 (.11)	2.77 (.08)	1.99 (.064)	.169 (.011)	.75 (.021)	-1150

1182
1183
1184
1185