Distinct encoding and post-encoding representational formats contribute to episodic sequence memory formation

Xiongbo Wu* and Lluís Fuentemilla

Department of Cognition, Development and Educational Psychology, Institute of Neurosciences, University of Barcelona, Barcelona 08035 Spain; Cognition and Brain Plasticity Unit, Bellvitge Institute for Biomedical Research, Hospitalet de Llobregat 08907, Spain

____

Abstract

In episodic encoding, an unfolding experience is rapidly transformed into a memory representation that binds separate episodic elements into a memory form to be later recollected. Here, we sought to investigate the representational format that accounts for successful memory formation of episodic sequences. We combined RSA and multivariate decoding analysis on EEG recordings while healthy female (N = 17) and male (N = 13) human participants encoded trial-unique combinations of face-object-scene picture triplets that were subsequently recalled in a test. Our findings revealed an ongoing process of image category integration throughout sequence encoding, that this process accumulated as a function of picture order in the sequence and that the degree of picture category integration throughout sequence encoding was not associated with episodic retrieval. We also found that episodic sequences that were later remembered were associated with an increased trial-specific neural similarity between EEG patterns elicited during picture sequence encoding and in the offset period, thereby indicating that a rapid memory reinstatement at the episodic offset supported the rapid transformation of an episodic sequence into a bound memory representation. The present findings demonstrate the time course and the functional relevance of the different representational formats that take place during online encoding and immediate offline periods that support the formation of memories for episodic sequences.

____

*For correspondence: xbwuni@gmail.com

Introduction

An important challenge in neuroscience is to understand how learning systems operate to rapidly transform an ongoing experience into bound episodic memory traces that can be recollected long term.

Traditionally, human episodic memory research answered this question by focusing on experiments using single items as studied material and analysing the neural underpinnings that predicted their successful retrieval during the online encoding (i.e., when stimuli to be remembered were present) (Paller and Wagner, 2002). This research showed that the same brain regions and patterns of activity that are engaged during memory "encoding" of an item tend to be reinstated during subsequent memory "retrieval" (Danker et al., 2017; Gordon et al., 2014; Ritchey et al., 2013; Staresina et al., 2012 and 2016), suggesting that remembering relies on reactivating the initial neural representations elicited online during encoding. Alternatively, another set of studies using single pictures as a studied material has emphasized that successful memory encoding involves a substantial transformation of early representations elicited during perception (Liu et al., 2021). Indeed, it has been shown that within the first few hundred milliseconds, brain activities gradually and progressively change from representing low-level visual information to higher-order categorical and semantic information (Clarke et al., 2018) and that these transformed, semantic representational formats contributed to stable short-term memory maintenance (Liu et al., 2020). While these two lines of research evidence highlight the dynamic representational nature that accounts for how the brain encodes single items in memory, it is also relevant to understand how these representational dynamics operate in the context of a sequential episodic encoding, akin to a more realistic scenario whereby the retrieval of an event involves remembering the elements that were encoded in the unfolding experience.

In the current study, we sought to investigate the representational format that accounts for successful encoding of episodic sequences in memory. Specifically, we aimed to examine whether successful encoding is supported by the preservation of the representational acuity or idiosyncrasy of each of the elements within a sequence or, alternatively, if it better requires an undergoing representational transformation of each of the elements so that they become integrated into a bound but semantic representational structure. In addition, we also aimed to investigate whether the immediate offline period after the completion of a sequential episode contributes to successful encoding. This is motivated by recent research that showed that brain mechanisms that followed online encoding of a continuous stream of stimuli offer an "optimal" window to register in memory a bound representation of an episode (e.g., Lu et al., 2022). Here, we hypothesize that one such offline neural mechanism promoting the binding of the elements of a sequence episode in memory is the rapid reactivation of them in a temporally compressed manner. Rodent studies showed that neural replay at quiescent periods immediately after single-trial spatial experiences supports

the formation of high-fidelity representation of the encoded trajectory in memory (Foster and Wilson, 2006). More recently, research in rodents pointed to a semantic aspect to replay, since it has been shown that novel information is added to the replay memory of a track upon subsequent re-exposures to it (Berners-Lee et al., 2022). In line with the animal literature, human literature has recently shown that representations of just-ended events are reactivated upon the completion of an event (Wu et al., 2021) or at event boundaries (Sols et al., 2017; Silva et al., 2019). However, these studies did not discern whether memory reinstatement of the just-encoded episode and its impact on retrieval relies on reactivating the initial neural representations elicited online during encoding or, alternatively, whether it strengthens the transformation of early encoded episodic material into a more semantic, abstract representation. Thus, an important question that remains unresolved relates to the representational format of this offset-locked neural activity supporting later recollection of the just-encoded experience.

We recorded scalp electrophysiological (EEG) signals while participants encoded trial-unique combinations of face-object-scene picture triplet sequences to be subsequently recalled in a test. Leveraged by the high temporal resolution of the EEG recording and the analytical power of representational similarity analysis (RSA) and multivariate decoding, we examined the dynamics of the representational format that contributed to successful episodic memory formation. The combination of these two analytical approaches allowed us to discern whether different types of memory representations, namely, "category-level" and "item-level", supported memory during the online encoding of the triplet sequence and offline, in the period that immediately followed encoding. Our results demonstrate the time course, and the functional relevance of the different representational formats that have an impact on memory formation and help advance our understanding of how the brain rapidly transforms the unfolding experience into bound episodic memory traces.

Materials and Methods

Participants

Thirty-two native Spanish speakers were recruited for the current experiment and compensated €10 per hour for their participation. All participants had normal or corrected-to-normal vision and reported no history of medical, neurological or psychiatric disorders. Two participants were excluded from the study due to technical problems during the EEG recordings. Data from 30 participants (17 females; age range 18–32 years, M = 23.77, SD = 4.38) were analysed. Informed consent was obtained from all participants in accordance with procedures approved by the Ethics Committee of the University of Barcelona.

Stimuli

The experimental design included 312 images (350×350 pixels each): 104 images of famous faces (52 male and 52 female), 104 images of famous places, and 104 object images. Famous face and scene images were selected from a larger sample of the image database consisting of 284 and 184 pictures of each category, respectively. The selection was carried out by a separate sample of 10 Spanish university students (5 females; age range 21-39 years) who rated their familiarity with each image on a scale from 1 to 4 (1: Not recognised; 2: Familiar; 3: Recognised but don't know the name; 4: Know the name). The final set of 104 face and place images were those that received the highest mean score by 10 external raters (mean score equal to or higher than 3.44 for male, 2.89 for female and 2 for places). The 104 objects were selected from available object-picture databases and covered 6 categories (clothing, food, tools, transport, work and leisure). For each participant, 60 images (20 object images, 20 face images of famous people and 20 images of famous places) were randomly selected for the localiser phase. Among the 312 images, 60 (20 object images, 20 face images of famous people and 20 images of famous places) were randomly selected for the localisation block. For the main task, 36 images (12 object images, 12 face images and 12 place images) were used for example trials and the rest 216 images (72 object images, 72 face images and 72 place images) were used for the encoding trials; this separation was kept the same across participants.

Experimental design

The experiment consisted of the localiser phase and the task phase. In the localiser phase, 60 images (20 faces, 20 scenes and 20 objects) were presented in random order to participants. Each trial started with a 1000 ms fixation cross, followed by a 2500 ms image presentation. A text displayed on the screen then indicated the need for the participants to state the category of the just-presented image (**Figure 1**). Participants had a maximum of 10 seconds to respond. The next trial started immediately once a response was given or the maximum time limit was passed. There was a brief break between every 20 trials when participants could briefly rest and decide to continue whenever they felt ready.

Figure 1. Experimental design. For the localisation task, 60 different images from 3 categories (face, place, and object) were presented. Participants were asked to indicate the image category. The encoding phase consisted of an image of an object, a famous face, and a famous place. Participants were asked to construct stories using the three elements for a later memory test. A blue asterisk appeared at the end of each triplet and participants rated their subjective sense of difficulty for story construction. For the Psychomotor vigilance task, participants were instructed to pay attention to the centre of the screen, waiting to react at the onset of a text timer by pressing the 'Space' button. In the recall phase there were 12 recall trials, each of which used the first image of the previously presented triplets to cue the free recall of the other two images. One block was completed after the retrieval phase and the next block started following a brief break. The experiment consisted of 6 blocks in total. An avatar image is displayed due to bioRxiv policy on not displaying pictures of real people.

113  The task phase started after the localiser phase. The task phase included 6 blocks,
each of them including an encoding task, a Psychomotor vigilance task (PVT) and a
retrieval test. Each block was independent of the other, so that picture images
presented in one block were never shown in any other of the blocks, but the task
instructions and their order of alternation were the same in each block. In the encoding
task, participants were instructed to encode 12 series of three images, namely an
object (O), a famous face (F), and a famous place (P). Participants were encouraged
to construct stories using triplet elements in the form of a narrative (e.g., Iniesta went
to Paris and purchased an expensive belt), and they were informed that the triplet
information would be tested later. In total, 72 triplets were randomly generated for each
participant from 216 images (72 object images, 72 face images and 72 place images),
and each image was used only once in the experiment. In each block, the presentation
order of the image categories in a series was fixed (e.g., always ordered as Face-
Place-Object in one block). There are in total 6 possible presentation orders, each of
which was used in one of the 6 blocks with no repetition and randomly generated for
each participant. At the beginning of each block, two example trials were presented,
indicating the order of presentation of the image categories. Participants were
instructed to use the two example trials to rehearse the upcoming series encoding in

the block and told that the example trials would not be tested later. Each encoding trial
began with the presentation of the text 'New Story' for 3000 ms, which marked the
start of a new triplet series. Triplet images were then presented sequentially on a white
screen for 2500 ms each after a 1000 ms black fixation cross. Immediately after the
presentation of the last image in each triplet, a blue asterisk appeared on the screen,
indicating a post-episode offset period of 3500 ms, during which participants were
instructed to avoid rehearsing the just-encoded triplet series. The asterisk remained
visible on the screen during the offset period. Participants were then asked to provide
a degree of subjective feeling of the difficulty of constructing a coherent episode with
the just-presented triplet of images by a button press on a scale from 1 ('very easy') to
4 ('very difficult'). The next trial began immediately after a response was given, or no
response was given after a time limit of 10 seconds. A small break of ~10 sec was
provided after completing 6 trials.

A block of the PVT task followed the encoding phase. In each PVT block,
participants were instructed to pay attention to the screen's centre and press the space
button as quickly as possible once the timer started counting. The task commenced
with the text presentation 'New Task' for 3000 ms. Then an empty red square was
displayed at the centre of the screen following a 1000 ms fixation cross. After a random
interval of between 5 sec to 15 sec, the timer started counting in the middle of the
square indicating the real passing time in milliseconds. The timer counted to a
maximum of 3500 ms if no response was given. Once the participants pressed the
button during the counting period, the timer stopped with the presentation of the final
reaction time in the centre of the screen for 2000 ms. In cases where no response to
the timer was given within the time limit, the presentation would be the final counting
time of the timer (i.e., 3500 ms). The new PVT trial started immediately after the
reaction time presentation. In total, 12 repetitions of response were required with no
interruption in the middle. A block of a PVT task lasted around 3 minutes.

The PVT task was followed by a cued-recall task. During this task, participants
were presented with the first image of all the encoded triplets in the current block in
random order. They were required to verbally recall the story episode containing the
other two images associated with the cue image. Each trial began with the text 'New
Recall' for 3000 ms, followed by the cue image on the screen for 2500 ms and a 1000
ms fixation cross. The text 'Explain the story' was then displayed on the screen, which
indicated to the participants they could start the verbal recall. The verbal recall had a
maximum duration of 30 s, during which the text instruction remained visible on the
screen all the time. Participants could skip to the next trial when finished with their
recall or if they were unable to recall any associated image by pressing the space bar.
A brief break of ~20 s separated the start of the next block.

EEG recording and pre-processing

During the experiment, EEG was recorded with a 64-channel system at a sampling rate of 512 Hz, using a eego™ amplifier and Ag/AgCl electrodes mounted in an electrocap (ANT neuro) located at 59 standard positions (FP1/2, AF3/4, Fz, F7/8, F5/6, F3/4, F1/2, FCz, FT7/8, FC5/6, FC3/4, FC1/2, Cz, T7/8, C5/C6, C3/4, C1/2, CPz, TP7/8, CP5/6, CP3/4, CP1/2, Pz, P7/8, P5/6, P3/4, P2/1, POz, PO7/8, PO5/6, PO3/4, Oz, O1/2) and at the left and right mastoids. Horizontal and vertical eye movements were monitored with electrodes placed at the right temple and the infraorbital ridge of the right eye. Electrode impedances were kept below 10 kΩ. EEG was re-referenced offline to the linked mastoids. Bad channels were interpolated, and a band-pass filter (0.5 Hz -30 Hz) was implemented offline. Blinks and eye movement artifacts were removed with independent component analysis (ICA) before the analysis.

Behavioural data analysis

During the retrieval phase of the experiment, participants were instructed to verbally recall the constructed story episode associated with the picture cue. Verbal recall of each trial was recorded through an audio recorder, and the audio files were later analysed. A successful recall of the image was considered as either correctly mentioning the name or describing it in precise detail. Memory for each triplet was quantified by the number of images (excluding the cue) correctly recalled.

EEG data analysis

For each participant, we extracted epochs of EEG activity surrounding pictures presented in the localiser and the encoding tasks. These EEG trial epochs had a duration of 2500 ms (1280 data points given the 512 Hz EEG recording sampling rate), and they were baseline corrected to the pre-stimulus interval (-100 to 0 ms). We also extracted EEG epochs of 2100 ms (1024 data points) from the offset period following the encoding of each triplet series. EEG signal to the offset period was baseline corrected to the -100 to 0 ms averaged EEG activity. EEG trial epochs that exceeded ± 100 μV were discarded for further analysis. EEG trials were then Gaussian smoothed by averaging data via a moving window of 100 ms (excluding the baseline period) and then downsampled by a factor of 5.

Representational Similarity Analysis (RSA)

RSA was performed timepoint-to-timepoint and included spatial features (i.e., scalp voltages from all the 28 electrodes) (Sols et al., 2018; Silva et al., 2019; Wu et al.,

2021). The similarity analysis was calculated using Pearson correlation coefficients,
which are insensitive to the absolute amplitude and variance of the EEG response.

We conducted a trial-based RSA between the EEG signal elicited by each
encoding item (1st, 2nd, and 3rd, regardless of the image category) and the EEG
signal elicited at the offset period following the encoding of the triplet series. After
smoothing and down-sampling, EEG epoch data elicited by each picture in the triplet
included 205 sample points (given the 512 Hz EEG recording sampling rate) covering
the 2000 ms of picture presentation and EEG data from post-triplet offset contained
359 time points, equivalent to 3500 ms. Point-to-point correlation values were then
calculated, resulting in a 2D similarity matrix with the size of 205×359, where the x-
axis represented the episodic offset time points and the y-axis represented the picture
encoding time points. The output 2D matrix depicted the overall degree of similarity
between EEG patterns elicited by each encoding image and the subsequent post-
episodic offset interval.

To account for RSA differences between conditions, we employed a nonparametric
statistical method (Maris and Oostenveld, 2007), which identifies clusters of significant
points on the resulting 2D similarity matrix and corrects for multiple comparisons based
on cluster-level randomisation testing. Statistics were computed on values between
conditions for each time point, and adjacent points in the 2D matrix that passed the
significance threshold ($p < 0.05$, two-tailed) were selected and grouped together as a
cluster. The cluster-level statistics took the sum of the statistics of all time points within
each identified cluster. This procedure was then repeated 1000 times with randomly
shuffled labels across conditions. Cluster-level statistics with the highest absolute
value for each permutation were registered to construct a distribution under the null
hypothesis. The nonparametric statistical test was calculated by the proportion of
permuted test statistics that exceeded the true observed cluster-level statistics.

We also examined whether possible RSA effects (i.e., at cluster level) that could
be seen when comparing successful and unsuccessful conditions in the previous
analysis were trial-specific or whether they reflect task-specific patterns of correlation
between online and offline encoding time periods. In other words, we aimed to assess
whether RSA in the same trial between image encoding and offset period from the
same trial was higher than RSA between image encoding and offset periods from
different trials. To assess these issues statistically, we ran the RSA individually and
separately for successful and unsuccessful memory conditions by randomly shuffling
the paring of EEG data from a given triplet and an offset period. This procedure was
repeated 200 times, each with a randomly generated shuffling order. The results were
then averaged across permutated trials for each of the identified clusters and
compared to the real cluster value using a repeated-measure ANOVA.

Linear Discriminant Analysis (LDA)

To identify the multivariate pattern of brain activity for image processing of different categories, a Linear Discriminant Analysis (LDA) was trained and tested on the EEG sensor patterns of localiser trials (pre-processed signal amplitude from 59 channels). The classifier was trained independently per participant and at each time point during localiser image presentation, then tested with a leave-one-out cross-validation procedure. Given that three categories were included in the current experiment (face, place, and object), at the training stage, the classifier was trained repetitively three times, including each possible pair out of the three classes. For each of the two classes, the classifier found the decision boundary that best separated the pattern activity. We then asked the classifier to estimate the unlabelled pattern of brain activity for each of the three decision boundaries (one for each pair of classes). The output of the classifier for each two trained classes at a given time point was the distance value to the decision boundary, which represents how probable the pattern of brain activity belonged to one of the two included classes, with the sign indicating the class and the magnitude reflecting the confidence of the classifier. The distance value for each pair of classes was then sigmoid transformed to get the probability of either class that unlabelled pattern activity belonged to (e.g., a distance value of 0 will return 50% for either class). After normalising and averaging values across the three possible pairings, the class with the highest probability was marked as the final label for the testing data. To access the general separability between the three classes in a compound measure, we defined a separability index as the sum of the absolute of the three distance values to each of the decision boundaries, with the assumption being that the greater the separability index, the higher the probability that the given activity pattern belonged to a specific class rather than assimilating to all three classes with equal distinctiveness (i.e., closer to zero).

This training-test procedure was repeated until every single localiser trial had been classified. The predicted labels for all trials at every given time point were then compared to the true classes to assess the accuracy of the classifier across all localiser times.

To evaluate how face, object and scene category representations accounted for EEG patterns elicited during picture encoding and at the offset period, we first identified the time point where the cross-validation of the classifier reached the peak accuracy. Using patterns of activity surrounding 10 time points around the peak (- 50 ms to 50 ms with the peak time point in the middle), we then trained the classifier per participant with all localiser trials and predicted all sample points separately for encoding and offset trials. The results were then averaged across localiser time points, resulting in a 1D separability index line for each trial where each sample point represented the encoding/offset time points.

Linear-mixed effect model

To further explore how the separability of pattern activity between picture categories changed along the encoding sequence and whether it is predictive for behavioural memory on a trial basis, we implemented a Linear Mixed Effect Model (LMM) on the resulting general distance value of each encoding image classified by patterns trained on trials from the localiser task. We further smoothed the resulting 1D distance value for each predicting encoding trial by averaging over a moving window of 200 ms, then introduced our LMM value on each time point as the independent variable and both the image order in triplet series (1st, 2nd, and 3rd) and recall memory (successfully recalled 0, 1, or 2 images following the cue), as well as the interaction of the two as fixed effect variables. Subject was introduced in the model as the grouping variable, with random intercept and a fixed slope for each fixed effect variable. The statistical significance was then evaluated using Bonferroni correction for each fixed effect variable at each timepoint thresholded with an adjusted alpha level of $\alpha = 2.44 \times 10^{-4}$ (0.05/205). The procedure was repeated to compare high and low memory conditions during offset. The output 1D distance line across offset was averaged for each condition across subjects. The t-statistics were then computed at each time point, and the significance was evaluated at the cluster level after cluster-based permutation.

Results

Localisation task

For the localisation task, 26 out of 30 participants reached 100% accuracy in identifying the image category, and the mean accuracy across the 30 participants was 99.72% (SD = 0.77%).

Recall of picture triplets

Participants were able to recall on average 1.12 pictures (SD = 0.37) following the cue, with the mean percentage of trials recalling 0, 1, and 2 items being respectively 35.61% (SD = 16.41%), 16.30% (SD = 6.52%) and 48.09% (SD = 20.68%) (**Figure 2a**). We also found that the average number of images recalled upon the picture cue did not vary between blocks, indicating that encoding and retrieval accuracy did not vary throughout the task (repeated-measures ANOVA with block number as the main factor: $F_{(5,140)} = 0.415$, $p = 0.838$). However, there was a significant difference in recall performance depending on the category order of the triplet series. More concretely, we found that encoding blocks that included triplets with face as the first picture (i.e., Face-Place-Object or Face-Object-Place) were less accurately recalled (Face-Place-Object: mean = 0.914, SD = 0.098; Face-Object-Place: mean = 0.905, SD = 0.082)

325 than triplets from blocks where place (Pace-Face-Object: mean = 1.253, SD = 0.081;
326 Pace-Object-Face: mean = 1.224, SD = 0.081) or object (Object-Face-Place: mean =
327 1.213, SD = 0.081; Object-Place-Face: mean = 1.230, SD = 0.084) was presented first
328 (repeated measures ANOVA: $F_{(5,140)}$ = 9.798, p < 0.001).

Figure 2. Behavioural results. (a) Percentage of trials as a function of numbers of images correctly retrieved during free recall. **(b)** Subjective rating of the difficulty of triplet encoding separated by whether or not the triplet was later successfully recalled (with both images associated with the cue being correctly recalled). Each dot on both plots represents the value for an individual in the corresponding condition. Each grey line on the boxplot connects the value of an individual in two conditions.

For RSA analysis, we adopted a median-split approach to separate the trials based
on whether the entire triplet images were correctly retrieved. Triplets with 2 images
recalled after the cue were labelled as successful recall, and triplets with either 1 image
or no image recalled were labelled as unsuccessful recall. The average percentage of
trials were respectively 48.09% (SD = 20.68%) for successful recall condition and
51.91% (SD = 20.68%) for unsuccessful recall condition (Wilcoxon signed-rank test: z
= -0.43, p = 0.67). RSA results for successful and unsuccessful recall trials were then
compared using a point-to-point paired t-test. The statistical difference between the
two conditions was then assessed with a cluster-based permutation approach.

Participants' ratings of encoding difficulty

On average, triplets were rated as 2.24 (SD = 0.47) (on a scale that ranged from
1: no difficulty to 4: very difficult), and the mean percentage of triplets rated as 1, 2, 3,
and 4 were respectively 27.91% (SD = 21.73%), 33.79% (SD = 13.80%), 24.65% (SD
= 13.13%) and 13.65% (SD = 12.03%). Based on the median-split criteria, difficulty
ratings for trials with successful recall (mean = 2.26 and SD = 0.48), and for trials with
unsuccessful recall (mean = 2.22 and SD = 0.51) did not differ statistically between
each other (paired Student t-test: $t_{(29)}$ = 1.01, p = 0.32, two-tailed) (**Figure 2b**).

RSA between item sequence and episodic offset at encoding

We first examined the existence of encoding-offset neural similarity differences between trials that were successfully or unsuccessfully recalled. This analysis revealed that EEG patterns elicited during the encoding of picture triplets that were later recalled showed, compared to unsuccessfully recalled trials, a higher degree of neural similarity during the episodic offset period (**Figures 3a and b**). This result was

Figure 3. RSA for image at encoding and at post-encoding. (a) Time-resolved degree of neural similarity between image encoding and post-triplet offset for trials with successful subsequent recall (left) and unsuccessful recall (right). **(b)** Difference between similarity values for the two conditions. Statistically significant (p < 0.05, cluster-based permutation test) higher similarity value was found for trials successful recall centred in two areas (indicated by black contour lines. $P_{cluster1}$ < 0.001; $P_{cluster2}$ = 0.002). **(c)** Within Cluster 1 and Cluster 2, averaged true RSA values vs. shuffled RSA separated for trials with successful and unsuccessful subsequent recall. Each dot on the plots represents the value for an individual in the corresponding condition.

corroborated statistically with the cluster-based permutation test, which showed two clusters of increased neural similarity starting at ~400 ms at offset period (Cluster 1: p < 0.001, mean t-value = 2.98, peak t-value = 4.74; Cluster 2: p = 0.002, mean t-value = 3.10, peak t-value = 4.92) (**Figure 3b**).

We next tested whether the RSA effects seen when comparing successful and
unsuccessful conditions were trial-specific. To address this issue, we ran RSA by
shuffling the encoding-offset pairing 200 times and obtained for each individual a
similarity value that represented task- rather than trial-specific RSA effects. To
evaluate whether real and shuffled RSA effects differed from each other statistically,
we conducted a repeated-measure ANOVA with four main factors, namely Memory
(Successful vs. Unsuccessful recall), Cluster number (Cluster 1 vs. 2), RSA condition
(True value vs. Permutated value) and also Image order in the sequence (S1, S2 or
S3). We found a significant main effect of Memory ($F_{(1,27)}$ = 20.08, p < 0.001) as well
as Cluster number ($F_{(1,27)}$ = 5.67, p = 0.025). Importantly, there was a significant
interaction between Memory and RSA condition ($F_{(1,27)}$ = 14.62, p < 0.001) (**Figure
3c**). There was also a significant interaction between Cluster and RSA condition ($F_{(1,27)}$
= 4.95, p = 0.035). None of the other main effects (or interaction between main effects)
reached significance threshold (all p > 0.05). These results indicated that the RSA
showed a trial-specific property only for successfully remembered trials.

Classification accuracy and separability of picture category

We adopted the LDA approach to classify and predict the image category being
processed based on the elicited EEG pattern in the localiser task. The classifier was
trained independently per participant and at each time point during picture encoding,
then tested with a leave-one-out cross-validation procedure. Two output values were
extracted for each time of training/testing, namely the category of tested data predicted
by the model with the highest probability among three alternatives (i.e., accuracy) and
a general distance value (D value) of tested data to the classification plane among
categories (i.e., separability) (**Figure 4a**).

The results of this analysis showed that picture category could be reliably
predicted rapidly at picture onset (i.e., ~130 ms), showing a peak classification
accuracy at ~180 ms (t_{29} = 8.41, p_{corr} < 0.001) (**Figure 4b**).

As expected, the pattern separability analysis showed similar temporal dynamics
to the accuracy ones. More specifically, pattern separability became significant as the
distance value increased compared to surrogate trials, with the difference emerging
from ~170ms. D value reached the local maximum at respectively ~180 ms (D = 6.57,
t_{29} = 5.032, p_{corr} = 0.005) and at ~380 ms (D = 6.60, t_{29} = 7.25, p_{corr} < 0.001) (**Figure
4c**).

395
396

Gradual integration of picture category information during sequence encoding

We examined whether the sequential encoding of pictures from different categories in the encoding task would involve a gradual integration of the just-encoded images from the sequence and whether this process predicted memory recall. To address this issue, we extracted the -50 to 50 ms EEG pattern surrounding the peak (i.e., at 180 ms from picture onset; **Figure 4b**) LDA accuracy during the encoding of images in the localiser task. We then used these EEG patterns as the training data in a new LDA and tested on EEG patterns elicited at each time point from each picture from the sequence on the encoding task.

We then averaged across all training time points at trial level and included the resulting distance value at each time point of encoding into LMM as the dependent

variable. For each trial, the number of items recalled, the encoding order of the image
in the triplets (i.e., 1st, 2nd and 3rd), and the interaction of the two were included in the
model as fixed-effect variables. Subject was introduced into the model as the grouping
variable, with random intercept and a fixed slope for each fixed-effect variable.

This analysis showed that the D value correlated negatively with the order of
picture in the sequence (**Figure 5a**) and that such effect emerged ~ 460 ms after
picture onset and persisted until ~860 ms. However, we found that D value did not
correlate with later picture recollection at the test nor the interaction of picture order
and memory. This suggested that the picture category integrative process takes place
during sequence encoding and that this had no impact on the later ability of the
participants to retrieve the sequence episode. To control for the possibility that the
observed effect was not merely due to a decrease in the specific category
classification accuracy as a function of the order of the picture in the sequence, we
extracted the mean accuracy across image order within the time window where the
significant decrease in pattern separability was identified (**Figure 5b**). A repeated-
measure ANOVA showed significantly above-chance accuracy value ($F_{(1,29)}$ = 111.57,
$p < 0.001$) with no main effect for image order ($F_{(2,58)}$ = 0.43, p = 0.65).

Figure 5. Pattern separability during image encoding predicted by LDA classifier trained on localisation trials. (a) D value (i.e., degree of category separability) during picture encoding from the triplets averaged across participants (upper, shaded area indicated SEM across participants) with statistical significance Bonferroni-corrected for the main effect of image order, subsequent memory and their interaction (lower). Shaded grey area and light grey dashed line marked the significance threshold boundaries (two-tailed) adjusted by Bonferroni correction. Time window where the main effect passed the threshold was marked in dark grey line below. **(b)** LDA accuracy averaged across the time window where a significant effect for image order was found. Category of image was classified equally accurate across image order (p = 0.65) yet significantly above chance (grey dashed line) (p < 0.001). Each black dot represents values for an individual participant. The central mark is the median, and the edges of the box are the 25th and 75th percentiles. **(c)** Abstract illustration of the speculated integration process. While the classifier continued to predict the image category accurately, there was a trend for an 'integrated' pattern indicated by a gradually decreased pattern separability.

Picture sequence integration and memory at episodic offset period

451   We next examined whether an integrated form of the just encoded sequence could
452   predict memory for the episode right after its online encoding, that is, once the
453   encoding ended, at the offset period. If this was the case, we should observe that D
454   value was reduced at the offset period for successful compared to unsuccessful
455   recalled picture sequences.

456
457

Figure 6. Pattern separability during post-triplet offset period predicted by LDA classifier trained on localisation trials. Lower distance value for trials that were later successfully emerged from ~320ms at triplet offset. Shaded area indicated SEM across participants. Dark grey line marked statistical significance adjusted by cluster-based permutation. An abstract illustration of separability pattern for successfully and unsuccessfully remembered trials were included on the right. Successfully remembered trials showed a more reduced *D* value as a sign of successful integration among the three categorical representations.

To address this issue, we again extracted the EEG pattern elicited during ~140
ms - 230 ms by picture presentation in the localiser task. We applied it to each time
point of the offset period from the encoding task. The resulting D value from the model
was then averaged across all training timepoints. We further smoothed the resulting
1D distance value trial by averaging over a moving window of 200 ms, then separated
D values for successful and unsuccessful memory trial conditions and averaged them
for each participant. Statistical comparisons between conditions were assessed and
then reassessed with a cluster-based permutation approach.

Confirming our hypothesis, the results of this analysis showed significant lower D
value for successful compared to unsuccessful recalled trials from ~320 ms to ~1680
ms (p = 0.01, mean t-value = -2.44, peak t-value = -2.78) at offset period (**Figure 6**).
Importantly, this time window coincided with the increased neural reactivation for
successfully recalled triplets identified previously in the RSA, suggesting an
overlapping functional role between post-encoding reactivation and integration.

Discussion

The current study examined the dynamics of the representational format that
contributed to successful episodic memory formation. The combination of RSA and
multivariate decoding approaches on EEG data allowed us to systematically compare
whether "category-level" or "item-level" supported memory formation during the online
encoding of a picture triplet sequence and offline, in the period that immediately
followed encoding. Our findings revealed an ongoing process of image category
integration throughout sequence encoding, that this process accumulated as a
function of picture order in the sequence and that the degree of picture category
integration throughout sequence encoding was not associated with episodic retrieval.
We also found that episodic sequences that were later remembered were associated
with an increased trial-specific neural similarity between EEG patterns elicited during
picture sequence encoding and at the at the offset period, thereby indicating that a
rapid memory reinstatement at the episodic offset supported the rapid transformation
of an episodic sequence into a bound memory representation.

Consistent with previous findings (Cichy et al., 2014; Wimmer et al., 2020;
Jafarpour et al., 2014), we successfully identified the neural patterns associated with
the encoding of picture categories in an early time window from image presentation
onset). However, instead of registering only the output from the classifier, generally
defined as the predicted class with maximal likelihood among possible alternatives,
we used it to develop an index that quantified the classifier's ability to distinguish
among all the possible classes at a given time point, the degree of separability or the
D index. In other words, the D index expresses the degree to which a tested neural
pattern assimilated or deviated from all the possible trained categories. By extracting

the *D* index during each of the pictures from the encoding triplet, we found a gradual decrease of pattern separability from neural patterns elicited at early temporal stages from the pictures sequence, being higher in the first picture and lower in the 3rd picture of the sequence. It is important to note that during this identified time window, the accuracy of the classifier to the correct category remained above chance and similar throughout each of the pictures from the triplet sequence. Thus, the observed gradual decrease in pattern separability cannot simply be attributed to a weak classification performance but instead indicates a gradual reduction in the specificity of activity patterns to a particular picture category (scene, object or face). One possible explanation of this finding may be attributed to an attenuated neural activity by prior expectation, given that participants could anticipate the category of the upcoming image since the order of presentation was fixed within each block. Though prior studies revealed that anticipation might reduce response in neurons tuned for expected stimulus (Kok et al., 2013; Kumar et al., 2017), multivariate approaches have instead shown a 'sharpening' effect for perceptual representations in cortical regions due to a more selective population response (De Lange et al., 2017), resulting in a more accurate pattern classification (Kok et al., 2013). Our findings that the decrease in picture category pattern separability is taking place at around 500 ms from picture onset, however, may not be explained by 'sharpening' effects because they are thought to occur earlier in the temporal course of processing (i.e., < 400 ms from stimuli onset). Instead, we argue that the gradual reduction in pattern separability following the sequential presentation of images reflected a continuously additive category-specific processing, which promoted the encoding of multiple categorical information in parallel, supported by various overlapping cortical regions. In fact, different yet overlapping cortical regions (e.g., various regions on the lateral surface of occipitotemporal cortex) are selectively sensitive to stimuli from different categories when presented in isolation, including face, objects and scenes (Silson et al. 2016). In naturalistic scenarios, the processing of multiple categories of information embedded in the encoding experience takes place simultaneously, and the neural signature of such processes can be decoded in different cortical regions (Cooper and Ritchey, 2020). In the context of our study, the ongoing need to associate each appearing picture with the previously encoded pictures from the sequence may have promoted integrative processes online during the encoding of the picture.

An interesting finding from our study is that a decrease in the degree of picture category pattern separability at the episodic offset, when the episode was completed, but not during online encoding, was in fact predictive of later episodic recollection at test. In addition, we found that later successfully recollected episodes showed greater trial-based neural similarity at an overlapping temporal window at the offset period. All in all, these findings suggest that successfully encoded episodic events triggered a rapid neural reactivation that promoted a strengthening of a unique representation of the encoded elements within the events into a bound memory trace. Previous fMRI literature using different input types such as picture sequences (DuBrow and Davachi, 2014), short video clips (Zacks et al., 2001; Ben-Yakov et al., 2011; Ben-Yakov et al.,

2013), and movies (Baldassano et al., 2017; Ben-Yakov et al., 2018) highlighted the sensitivity of the hippocampal-neocortical system to detect episodic offsets, suggesting that the end of a long-timescale event triggers memory encoding processes that occur after the event has ended. Our findings also align well with a recent study that combined direct electrophysiological recordings from human hippocampus and deep neural network analysis that showed that early representation of visual picture information in the first second after stimulus offset was associated with better long-term memory (Liu et al., 2021). However, our results extend previous ones by showing that a high-fidelity memory of the representation elicited at each image during encoding is reactivated at the offset period and the degree of this "sequenced high-fidelity representation" contributes to the possibility of accessing a bound representation of the episode.

In conclusion, we found a gradual integration process of perceptual representations as encoding experience unfolded and the neural mechanisms elicited in the episode offset period to promote the memory formation of episodic sequences. These findings contribute to an emerging understanding of the mechanism by which episodic information is encoded and subsequently retrieved. Current models emphasized the dynamic representational formats through which the brain transforms our experience into a memory trace. Our findings contribute to this important issue by showing that different representational formats are flexibly used during online and offline periods by the brain to support memory formation for episodic sequences.

Acknowledgements

We thank Bernhard Staresina for his helpful discussions in the initial stages of this project and on early versions of the manuscript. This work was supported by the Spanish Ministerio de Ciencia, Innovación y Universidades, which is part of Agencia Estatal de Investigación (AEI), through the project PID2019-111199GB-I00 (Co-funded by European Regional Development Fund. ERDF, a way to build Europe), to L.F. We thank CERCA Programme/Generalitat de Catalunya for institutional support.

References

Baldassano, C., Chen, J., Zadbood, A., Pillow, J. W., Hasson, U., & Norman, K. A. (2017). Discovering event structure in continuous narrative perception and memory. Neuron, 95(3), 709- 721.

Ben-Yakov, A., & Dudai, Y. (2011). Constructing realistic engrams: poststimulus activity of hippocampus and dorsal striatum predicts subsequent episodic memory. Journal of Neuroscience, 31(24), 9032-9042.

Ben-Yakov, A., Eshel, N., & Dudai, Y. (2013). Hippocampal immediate poststimulus activity in the encoding of consecutive naturalistic episodes. Journal of Experimental Psychology: General, 142(4), 1255.

Ben-Yakov, A., & Henson, R. N. (2018). The hippocampal film editor: sensitivity and specificity to event boundaries in continuous experience. Journal of Neuroscience, 38(47), 10057-10068.

Berners-Lee, A., Feng, T., Silva, D., Wu, X. (2022). Ambrose ER, Pfeiffer BE, Foster DJ. Hippocampal replays appear after a single experience and incorporate greater detail with more experience. Neuron, 110(11):1829-1842.e5

Cichy, R. M., Pantazis, D., Oliva, A. (2014). Resolving human object recognition in space and time. Nature neuroscience, 17(3), 455-462.

Clarke, A., Devereux, B.J., Tyler, L.K. (2018). Oscillatory dynamics of perceptual to conceptual transformations in the ventral visual pathway. J. Cogn. Neurosci. 30, 1590– 1605.

Cooper, R.A., Ritchey M (2020). Progression from feature-specific brain activity to hippocampal binding during episodic encoding. Journal of Neuroscience 40.8: 1701- 1709.

Danker, J. F., Tompary, A., & Davachi, L. (2017). Trial-by-trial hippocampal encoding activation predicts the fidelity of cortical reinstatement during subsequent retrieval. Cerebral Cortex, 27(7), 3515-3524.

De Lange, F. P., Heilbron, M., Kok, P. (2018). How do expectations shape perception? Trends in cognitive sciences, 22(9), 764-779.

DuBrow, S., Davachi, L. (2014). Temporal memory is shaped by encoding stability and intervening item reactivation. Journal of Neuroscience, 34(42), 13998-14005.

617 Foster, D.J., Wilson, M.A. (2006). Reverse replay of behavioural sequences in
618 hippocampal place cells during the awake state. Nature, 440(7084), 680-683.
619
620 Gordon, A.M., Rissman, J., Kiani, R., Wagner, A.D. (2014). Cortical reinstatement
621 mediates the relationship between content-specific encoding activity and subsequent
622 recollection decisions. Cereb. Cortex 24, 3350–3364.
623
624 Jafarpour, A., Fuentemilla, L., Horner, A. J., Penny, W., Duzel, E. (2014). Replay of
625 very early encoding representations during recollection. Journal of Neuroscience,
626 34(1), 242-248.
627
628 Kok, P., Jehee, J. F., & De Lange, F. P. (2012). Less is more: expectation sharpens
629 representations in the primary visual cortex. Neuron, 75(2), 265-270.
630
631 Kok, P., Brouwer, G.J., van Gerven, M.A., de Lange, F.P. (2013). Prior expectations
632 bias sensory representations in visual cortex. Journal of Neuroscience
633 9;33(41):16275-84.
634
635 Kumar, S., Kaposvari, P., Vogels, R. (2017). Encoding of Predictable and
636 Unpredictable Stimuli by Inferior Temporal Cortical Neurons. J Cogn Neurosci.
637 29(8):1445-1454.
638
639 Liu J, Zhang, H., Yu, T., Ni, D., Ren, L., Yang, Q., Lu, B., Wang, D., Heinen, R.,
640 Axmacher, N., Xue, X. (2020). Stable maintenance of multiple representational
641 formats in human visual short-term memory. Proc. Natl. Acad. Sci. U.S.A. 117, 32329–
642 32339.
643
644 Liu, J., Zhang, H., Yu, T., Ren, L., Ni, D., Yang, Q., Lu, B., Zhang, L., Axmacher, N.,
645 Xue, G. (2021). Transformative neural representations support long-term episodic
646 memory. Sci Adv. 7(41):eabg9715.
647
648 Lu, Q., Hasson, U., Norman, K.A. (2022). A neural network model of when to retrieve
649 and encode episodic memories. Elife 10;11:e74445.
650
651 Maris, E., Oostenveld, R. (2007). Nonparametric statistical testing of EEG- and MEG-
652 data. Journal of Neuroscience Methods 164, 177-190.
653
654 Paller, K. A., Wagner, A. D. (2002). Observing the transformation of experience into
655 memory. Trends in cognitive sciences, 6(2), 93-102.
656
657 Ritchey, M., Wing, E. A., LaBar, K. S., Cabeza, R. (2013). Neural similarity between
658 encoding and retrieval is related to memory via hippocampal interactions. Cerebral
659 cortex, 23(12), 2818-2828.
660

661 Silson, E. H., Groen, I. I., Kravitz, D. J., Baker, C. I. (2016). Evaluating the
662 correspondence between face-, scene-, and object-selectivity and retinotopic
663 organisation within lateral occipitotemporal cortex. Journal of vision, 16(6), 14-14.
664

665 Silva, M., Baldassano, C., Fuentemilla, L. (2019). Rapid memory reactivation at movie
666 event boundaries promotes episodic encoding. Journal of Neuroscience, 39(43),
667 8538-8548.
668

669 Sols, I., DuBrow, S., Davachi, L., Fuentemilla, L. (2017). Event boundaries trigger
670 rapid memory reinstatement of the prior events to promote their representation in long-
671 term memory. Current Biology, 27(22), 3499-3504.
672

673 Staresina, B. P., Henson, R. N., Kriegeskorte, N., Alink, A. (2012). Episodic
674 reinstatement in the medial temporal lobe. Journal of Neuroscience, 32(50), 18150-
675 18156.
676

677 Staresina, B.P., Michelmann, S., Bonnefond, M., Jensen, O., Axmacher, N., Fell, J.
678 (2016). Hippocampal pattern completion is linked to gamma power increases and
679 alpha power decreases during recollection. eLife 5, e17397.
680

681 Wimmer, G. E., Liu, Y., Vehar, N., Behrens, T. E., Dolan, R. J. (2020). Episodic
682 memory retrieval success is associated with rapid replay of episode content. Nature
683 Neuroscience, 23(8), 1025-1033.
684

685 Wu, X., Viñals, X., Ben-Yakov, A., Staresina, B. P., & Fuentemilla, L. (2021). Post-
686 encoding reactivation promotes one-shot learning of episodes in humans. bioRxiv.
687

688 Zacks, J.M., Braver, T.S., Sheridan, M.A., Donaldson, D.I., Snyder, A.Z., Ollinger,
689 J.M., Buckner, R.L., Raichle, M.E. (2001). Human brain activity time-locked to
690 perceptual event boundaries. Nat Neurosci. 4(6):651-5.