LRTK: A platform agnostic toolkit for linked-read analysis of both human genomes and metagenomes

Chao Yang[1†], Zhenmiao Zhang[1†], Yufen Huang[2,3], Xuefeng Xie[4], Herui Liao[5], Jin Xiao[1], Werner Pieter Veldsman[1], Kejing Yin[1], Xiaodong Fang[2,3*], Lu Zhang[1,6*]

[1]Department of Computer Science, Hong Kong Baptist University, Hong Kong SAR, Hong Kong

[2]BGI Research, Shenzhen 518083, China

[3]BGI Genomics, Shenzhen 518083, China

[4]BGI Research, Sanya 572025, China

[5]Department of Electrical Engineering, City University of Hong Kong, Hong Kong SAR, Hong Kong

[6]Institute for Research and Continuing Education, Hong Kong Baptist University, China

[†]These authors contributed equally to this work.

*To whom correspondence should be addressed: E-mail:

fangxd@genomics.cn ,

ericluzhang@hkbu.edu.hk.

Abstract

Linked-read sequencing technologies generate high base quality reads that contain extrapolative information on long-range DNA connectedness. These advantages of linked-read technologies are well known and has been demonstrated in many human genomic and metagenomic studies. However, existing linked-read analysis pipelines (e.g., Long Ranger) were primarily developed to process sequencing data from the human genome and are not suited for analyzing metagenomic sequencing data. Moreover, linked-read analysis pipelines are typically limited to one specific sequencing platform. To address these limitations, we present the Linked-Read ToolKit (LRTK), a unified and versatile toolkit for platform agnostic processing of linked-read sequencing data from both human genomes and metagenomes. LRTK provides functions to perform linked-read simulation, barcode error correction, read cloud assembly, barcode-aware read alignment, reconstruction of long DNA fragments, taxonomic classification and quantification, as well as barcode-assisted genomic variant calling and phasing. LRTK has the ability to process multiple samples automatically, and provides the user with the option to generate reproducible reports during processing of raw sequencing data and at multiple checkpoints throughout downstream analysis. We applied LRTK on two benchmarking and three real linked-read data sets from both the human genome and metagenome. We showcase LRTK's ability to generate comparative performance results from the preceding benchmark study and to report these results in publication-ready HTML document plots. LRTK provides comprehensive and flexible modules along with an easy-to-use

43 Python-based workflow for processing linked-read sequencing datasets, thereby filling

44 the current gap in the field caused by platform-centric genome-specific linked-read data

45 analysis tools.

47 **Key words:** linked-read sequencing, 10x Genomics, TELL-Seq, stLFR, metagenome,

48 human genome

Introduction

Linked-read sequencing generates reads with high base quality and extrapolative information on long-range DNA connectedness, which has led to significant advancements in human genome and metagenome research[1–3]. It circumvents the typical lack of long-range DNA information in short-read sequencing, and the high error rates and large initial DNA load requirements of long-read sequencing (e.g., Oxford Nanopore and Pacific Bioscience). These advantages of linked-read sequencing are invaluable when dealing with challenging cases of low-input clinical samples, such as cancer tissues or infectious disease samples. Linked-read technology furthermore promotes haplotype construction and the detection of complex structural variations[4], and its relatively low cost enables the application in large cohort studies.

Linked-read sequencing platforms, such as 10x Genomics linked-read (10x Genomics; now discontinued) and the newly developed single-tube long fragment read (stLFR)[2] and transposase enzyme linked long-read sequencing (TELL-Seq)[3], hold much promise in the metagenomics area. The hidden long-range information they provide enables local assembly of co-barcoded reads and thus significantly increases the number of high quality MAGs[5]. In longitudinal sequencing data sets[6–8], the barcodes associated with linked-read promote the phasing of variants and refine the identification of intra-host evolution of gut microbiota. In some complex environments, such as soil, linked-read sequencing has been shown to aid in

the investigation of soil microbe genomes[9]. However, existing linked-read pipelines

are mainly designed for use with the human genome, which points to an urgent need

for appropriate metagenome analysis toolkits **(Table S1)**.

Despite the limitations that genome specificity places on research scope,

linked-read sequencing has already been successfully applied to a myriad of genomic

studies. For example, Long Ranger[10] performs barcode-aware read alignment and

implements modules for variant calling and phasing using 10x Genomics linked-read.

Tell-Sort[3] is a Docker-based pipeline to process raw TELL-Seq reads, and detect

and phase genomic variants. stLFR[2] has found application in a customized pipeline

that has been developed to first convert its raw reads into a 10x-compatible format,

after which Long Ranger is applied for downstream analysis. The former pipeline

however typically requires a lot of random-access memory and its data format

conversion process is time consuming. Beyond the preceding examples that validate

the inherent usefulness of linked-read technology, our search of the literature

furthermore revealed a lack of unified and open-source toolkits that are compatible

with the different linked-read platforms.

To this end, we present Linked-Read ToolKit (LRTK), a unified and versatile

toolkit to analyze both metagenome and human genome linked-read sequencing data

derived from any of the three major linked-read sequencing platforms. LRTK delivers

a suite of utilities to simulate linked-read sequencing data, barcode correction, read

cloud assembly, barcode-aware alignment, reconstruction of long fragments, and

variant detection and phasing. LRTK is open-source, automatically produces HTML

reports to summarize quality statistics as part of its pipeline, and generates

publication-ready visualizations. We applied LRTK on benchmarking metagenome

and human genome sequencing data (ATCC-MSA-1003 and NA12878) to evaluate

the performance of 10x Genomics, stLFR and TELL-Seq linked-read sequencing

technologies. We also applied LRTK on three real data sets to demonstrate its

potential applications. Our results show that LRTK performs favorably on human

genomic sequencing data when compared to single platform technologies, and that it

adequately allows for data analysis of metagenomic sequencing data.

Results

Overview of LRTK

We developed a comprehensive workflow (which we refer to as LRTK) that takes

raw linked reads from 10x Genomics, stLFR, or TELL-Seq technologies, and

processes these inputs in a multi-step checkpointed pipeline that ends with the

generation of user-friendly reports. LRTK consists of two main sections for

metagenomic and human genome sequencing data **(Figure 1)**. For metagenomic

sequencing, LRTK includes the representative genomes from the UHGG[11] project

as its default microbial reference genomes. LRTK uses a modified

barcode-aware aligner based on EMA[12] to map reads to the reference genomes. To

reduce mapping errors, LRTK employs a tiered alignment approach to align the

sequencing reads. First, it identifies candidate genomes from the alignment files, and

extracts the related genomes from the reference genome database. Second, the reads

are aligned to the selected reference genomes to provide correct metagenomic read

assignments. If the single nucleotide variant (SNV) calling function is enabled, LRTK

also performs variation calling and phasing for the identified species.

In the human genome section, LRTK directly maps reads to the human genome

using the modified EMA[12] approach and marks the duplicates for each barcode.

LRTK reconstructs long DNA fragments through greedy extension based on the read

alignment coordinates if the co-barcoded reads are within a specified distance[13].

After mapping, LRTK provides user a choice of several well-known tools for variant

detection, including FreeBayes[14], SAMtools[15], GATK[16] for calling small

variants; and Aquila[17], LinkedSV[18] and VALOR2[19] for calling large variants.

For variant phasing, LRTK utilizes HapCUT2[20] and WhatsHap[21] to call phasing

blocks **(Table S2)**. Further details are available in the **Method** section.

LRTK support multiple linked-read sequencing technologies

LRTK can handle linked-read data from various sequencing technologies,

including but not limited to 10x Genomics, stLFR, or TELL-Seq. Initially, LRTK

converts the raw linked-read from 10x Genomics, stLFR and TELL-Seq into a unified

FASTQ format, which contains a new field "BX:Z:" to store 16 bp (10x Genomics

linked-read), 18 bp (TELL-Seq) and 30 bp (stLFR) barcode sequences **(Figure S1)**.

Because barcode sequences are typically located at the beginning or end of

linked-reads, LRTK includes functions to correct potential sequencing errors. For 10x

Genomics linked-read, after correction, there are approximately 94.8% of barcode

sequences on whitelist for NA12878 and 94.1% for ATCC-MSA-1003, respectively.

The performance is comparable to the results obtained from Long Ranger, which

retains 94.4% of barcode sequences for NA12878 and 93.6% for ATCC-MSA-1003.

The retention rates were slightly lower for stLFR linked-read, with 85.4% for

NA12878 and 90.7% for ATCC-MSA-1003. A known concern with stLFR

linked-read sequencing is the loss of barcode specificity during analysis. This occurs

when the data is typically converted into a 10x-compatible format to run Long Ranger

or directly aligned using BWA[22] without considering the barcode information[3].

We made modifications to EMA[12] **(Methods)** to accommodate barcodes with

varying lengths, including but not limited to stLFR. Our adapted approach proved to

be more effective at preserving barcode specificity than the 10x-compatible format

conversion approach.

LRTK supports reconstruction of long DNA fragments

The quality of DNA library may significantly affect assembly performance and

variant calling[23]. To evaluate the quality of linked-read sequencing libraries, we

reconstructed the long DNA fragments for both human genome and metagenome

sequencing data. We also calculated several key statistics to comprehensively

compare the fragment properties across different linked-read sequencing technologies.

The statistics include average coverage of short reads per fragment (C_R), average

physical coverage of the genome by long DNA fragments (C_F), number of fragments

per partition ($N_{F/P}$), fragment length (μ_{FL}), and unweighted and length-weighted DNA

fragment length (μ_{FL} and Wμ_{FL}) **(Figure S2)**. On human genome sequencing data (B2,

NA12878), LRTK detected approximately 7.36, 1.22 and 3.09 fragments per barcode

and achieved average fragment lengths of 50.19, 62.28 and 80.04 kb for 10x

Genomics linked-read, stLFR and TELL-Seq, respectively **(Figure 2B)**. On the

metagenome sequencing data (ATCC-MSA-1003), stLFR linked-read yielded the

lowest $N_{F/P}$ ($N_{F/P}$ =1.54), while TELL-Seq linked-read yielded a slightly higher

number ($N_{F/P}$ =4.26). Both numbers were much lower than that obtained from 10x

Genomics linked-read ($N_{F/P}$ =16.61) **(Figure 2A)**, indicating that stLFR and

TELL-Seq have superior performance in terms of the barcode specificity.

LRTK supports metagenome variant detection and phasing using barcode-aware alignment

Previous studies have amply demonstrated the huge potential of linked-reads in

metagenomics[5–9]. Here, we also evaluated the performance of linked-reads in

detecting taxonomic abundance and metagenomic variants. Based on

standardized microbial genome databases such as GTDB[24] and UHGG[11], we

developed a reference genome based computational framework to identify species and

SNVs from metagenomic sequencing data. Using the ATCC-MSA-1003

benchmarking data[23], we observed that LRTK had a comparable performance with

k-mer based tools such as KMCP[25] and marker-gene based tools, MIDAS2[26]

(Figure 3A). For high abundance species, LRTK could accurately identify SNVs from

the alignment files and use barcode information to estimate genetic linkages and infer

potential haplotypes. Comparison of metagenome SNV calling tools in the LRTK

pipeline showed high consistency among FreeBayes[14], inStrain[27] and

SAMtools[15] **(Figure 3B)**. We applied LRTK on a real longitudinal linked-read

metagenomic data set (D1)[6] to evaluate LRTK's performance in practice. LRTK

revealed the taxonomical composition and genomic variations for each sample. Using

multiple related samples, LRTK also identified a genome-wide mirrored allele

imbalance (MAI) for species *Alistipes finegoldii*, which may suggest intra-host strain

evolution over time **(Figure 3C and D)**.

LRTK promotes metagenome assembly using barcode specificity

De novo assembly approaches have reconstructed numerous novel

microorganisms from metagenomic sequencing data. Linked-read sequencing

enhances metagenome assembly performance, especially for low abundance

species[28]. Using benchmarking metagenomic sequencing data (ATCC-MSA-1003),

we compared the performance of three linked-read based assemblers: Athena[28],

Supernova[29] and Pangaea[30]. Among them, Pangaea achieved the best

reconstructed genome fractions, NGA50, and NA50, for both stLFR and TELL-Seq

sequencing data **(Figure 4A)**. With Pangaea, LRTK achieves NA50 values of 1.8 Mb

and 1.2 Mb for stLFR and TELL-Seq sequencing data, respectively. On 10x

Genomics sequencing data, Athena exhibited superior assembly performance, with a

NGA50 of 245 Kb. We applied LRTK on a dataset of human gut microbiomes

(D2)[30] for illustrative purposes. Two of the assembled contigs were circularized

genomes that showed near perfect collinearity with the closest reference genomes

(Figure 4B). LRTK could also automatically clusters the contigs into bins after

assembly. LRTK recovered 24 near-complete, 7 high quality and 52 medium quality

bins, respectively **(Figure 4C-E)**. The superior assembly performance we have

observed affirms the effectiveness of linked-read sequencing technologies in

metagenome assembly. Interestingly, the assembled metagenomes, due to their high

quality, have the potential to serve as reference genomes. This characteristic makes

LRTK valuable to longitudinal studies relying on linked-read metagenomic

sequencing data.

221 LRTK improves human genome variant phasing using
222   long-range information

Previous studies have shown that the high base accuracy and long DNA

fragments arising from linked-read sequencing benefits phasing of human genomic

variants[31]. Here, we benchmarked the computational tools for variant detection and

phasing tasks, and constructed a best practice to apply linked-reads on human genome

studies. To ensure fair comparisons, LRTK used the modified version of the

barcode-aware alignment tool, EMA[12], to map linked reads from different

sequencing technologies to the human genome (GRCH38). We first benchmarked the

commonly used tools FreeBayes[14], GATK[16] and SAMtools[15] to detect SNV

and small insertions and deletions (INDEL). Among them, GATK achieved the best

F1 score in detecting SNVs, followed by SAMtools and FreeBayes **(Figure 5A)**. For

INDEL calling, all three tools showed similar precision levels of around 0.5 while

GATK had a better recall rate **(Figure 5B)**. We compared the linked-read phasing

tools, Whatshap[21] and HapCUT2[20], in combination with the aforementioned

variant detection tools. We observed that HapCUT2 **(Figure 5C and D)** achieves

longer phasing blocks and higher phased heterozygous SNV rate compared to

WhatsHap[21]. Since most structural variation (SV) detection tools were developed to

be used with 10x Genomics sequencing data and may therefore have uncertain

performance loss when used with other sequencing technologies, we only

benchmarked the performance of SV calling tools using 10x Genomics sequencing

data. As illustrated in **Figure 5F and G**, Aquila had higher recall rates for 50 bp – 1

Kb deletions and insertions, while LinkedSV[18] performed better in detecting

deletions longer than 1 Kb. We also applied LRTK on a family trio's genomic

sequencing dataset (D3: NA24143, NA24149 and NA24385) to evaluate its actual

performance. LRTK demonstrated excellent phasing performance and improved

identity-by-descent (IBD) segments detection for pairwise samples **(Figure 5E)**.

248   LRTK provides flexible commands to process sequencing
249   data

A primary advantage of LRTK is its flexible, user-defined settings for different

tasks. Users have a choice to run each LRTK module independently and generate

separate results for each module. For instance, the MKFQ function could be

independently used to simulate sequencing reads from the stLFR platform. For some

functions, LRTK provides multiple tools for users to choose from. For metagenome

SNVs detection, LRTK offers the user a choice between SAMtools[15],

FreeBayes[14], and inStrain[27]. To accommodate user-specific requirements on

LRTK command, LRTK also allows users to set different parameters and save the

results for further comparison.

259   LRTK provides automated analysis and user-friendly reports

LRTK provides an automated analysis pipeline, starting from raw sequencing

reads to performing diverse data analysis and generating publication-ready

visualizations. Specifically, LRTK produces different types of data features, calculates

their corresponding statistical indicators, and presents them together in a HTML

report. Taking the aforementioned longitudinal linked-read sequencing dataset D1 as

an example, LRTK generates a systematic summary for the input data and analysis

results of each step. Firstly, LRTK produces summary statistics for the FASTQ files

obtained from the read quality control (QC) tools **(Figure S3A-B)**. After aligning

reads to reference genomes, LRTK calculates the key parameters for library

preparation and reconstructed long fragments **(Figure S3C-D)**. For detected species

and variants, LRTK generates basic statistics and presents them using concise

distribution plots **(Figure S3E-F).** For downstream analysis, LRTK conducts

principal components analysis (PCA) analysis on the relative abundance profiles and

clustering analysis on allele frequency to make comparisons across multiple samples

(Figure S3G-H). Similar reports could be produced for users employing LRTK to

study the human genome **(Figure S4)**.

Discussion

Seeing that multiple linked-read sequencing technologies are extensively utilized

in scientific studies, a platform agnostic linked-read processing tool would be an

intuitive solution to ensure reproducibility and robustness. Unfortunately, a

cross-platform software solution is currently unavailable to the research community.

Accordingly, we introduce LRTK, a unified and versatile computational framework to

efficiently process sequencing data from 10x Genomics, stLFR and TELL-Seq

technologies. LRTK includes separately invokable commands to perform linked-read

simulation, barcode correction, barcode-aware alignment, read cloud based assembly

reconstruction of long fragments and other barcode-assisted genomic variant calling

and phasing. LRTK also provides automated and complete analysis, from raw data

QC through advanced downstream analysis to generation of publication-ready

visualization. LRTK is also open source, allows easy integration with other scientific

pipelines.

One of the core advantages of LRTK is that it provides solutions for both

metagenomic analysis and human genome analysis. Linked-read sequencing

technologies offer highly accurate reads and inferable long-range information, which

confers distinct advantages in genome research, such as superior phasing ability[31].

Phasing is valuable in exploring intra-host evolution of microbiota where strains

under the same species may have some variants. LRTK follows a reference genome

based approach to detect species' abundance and to identify metagenome variants. It

also infers the mirrored allele imbalance from multiple related samples. In addition,

we establish a best practice to perform variation calling, phasing, and detection of

IBD segments for human genome.

Finally, it is worth mentioning that LRTK has the potential to be extended to

handle other types of linked-read sequencing technologies. For example, in 2017,

Illumina introduced the bead-based barcode partitioning in a single tube to phase

human genomes. It further proposed the complete long-read technology for complex

genomes in 2022[32]. Additionally, Meier J I, *et al.* developed Haplotype tagging to

investigate the butterfly species[33]. Redin D, *et al.* recently introduced a novel

library preparation method for high throughput barcoding of short reads[34]. The new

single cell metagenomic sequencing technologies employs highly accurate barcoded

reads and provides inferable long-range information, which could potentially be used

in combination with current linked-read technology in future studies[35]. We are

actively developing LRTK to incorporate these technologies.

Methods

Data collection

313 We curated one benchmarking dataset and two real datasets to demonstrate the

314 performance of LRTK in processing metagenomic sequencing data **(Table S3)**. The

315 benchmarking datasets (B1: ATCC-MSA-1003) were obtained from the NCBI with

316 the following accession numbers: SRR12283286 for 10x Genomics, and

317 PRJNA875547 for stLFR and TELL-Seq sequencing technologies. The first real

318 metagenomic dataset (D1), consisting of longitudinal 10x Genomics linked-read

319 sequencing data, was downloaded from the NCBI under accession number

320 SRP323279. We used only a subset of samples containing the barcode information in

321 the read ID **(Table S3)**. Another real metagenomic dataset (D2) containing deep

322 stLFR sequencing data, was downloaded from the China National GeneBank (CNGB)

323 under project CNP0003432.

324 For the human genome section, we obtained the linked-read of NA12878 for 10x

325 Genomics, stLFR and TELL-Seq and used them as the benchmarking dataset B2. We

326 also downloaded the 10x Genomics linked-read sequencing data for a family trio

327 (NA24143, NA24149 and NA24385) and used them as the real data set D3 **(Table**

328 **S3)**.

Data preprocessing

330  We utilized LRTK to convert the raw linked-read from 10x Genomics, stLFR and

331 TELL-Seq into a unified FASTQ format **(Figure S1)** and correct potential sequencing

332 errors in barcodes. For the 10x Genomics and stLFR linked-read, the barcodes are

333 aligned to their respective barcode whitelists using the BWA aln command. Aligned

334 barcodes containing fewer than 2 mismatches are then corrected as the corresponding

335 barcodes in the whitelist. Due to the lack of a barcode whitelist for TELL-Seq, LRTK

336 adopts the approach described by Chen *et al.*[3] to correct barcode errors. LRTK

counts the supporting read for each barcode, compares barcodes with one supporting

read to those with multiple supporting reads, and corrects potential sequencing errors

for barcodes with one mismatch to those with multiple supporting reads. The

linked-read in the unified FASTQ file are then subjected to fastp[36] to remove

adapter sequences and low-quality reads. For metagenomic sequencing data, the

sequencing reads are additionally aligned to the human genome and only unmapped

microbial reads are retained. LRTK also provides support for simulating linked-read

from 10x Genomics and stLFR platforms through modification of LRTK-SIM[23].

345 Metagenome assembly and binning

We evaluated the performance of three different metagenome assemblers:

Athena[28], Pangaea[30] and Supernova[29], and observed superior performance of

Pangaea on stLFR and TELL-Seq sequencing data. Therefore, for LRTK, we chose

Pangaea as the default assembler to assemble linked metagenomic sequencing data.

After the initial assembly, we extracted the contigs that were at least 1Mb in length

and checked their circularization. The uncircularized contigs were grouped using

MetaBAT2[37].

353 Barcode-aware read alignment

For human genome sequencing data, we utilized EMA, a barcode-aware

alignment approach, to map high-quality reads to the human reference genome[38].

We modified EMA to be compatible with the barcodes from stLFR (30 bp) and

TELL-Seq (18 bp). LRTK marks PCR duplicates for each barcode using the

"BARCODE_TAG" parameter in Picard (https://broadinstitute.github.io/picard/). The

alignment files are then sorted according to the genomic coordinates for further

analysis.

For metagenomic sequencing data, we developed a tiered alignment approach to

align the linked read to microbial genome using modified EMA. The default reference

genomes for the human gut metagenome were downloaded from UHGG[11]. After

the first alignment, we partitioned the reference genomes into 1-kb windows and

calculated the number of mapped reads for each window. The mapped reads are

categorized into two types: unique mapped reads (U) and reads with multiple

alignments (M). Thus, we can use the following formulas to determine the total read

count of the window (RC(W)), unique mapped read count ($RC(U)$) and multiply

mapped read count ($RC(M)$), where l is the window size.

$$RC(W) = RC(U) + RC(M)$$
$$RC(U) = \frac{U}{l}$$
$$RC(M) = \sum_{i=1}^{M} \omega_i * \{M\}/l$$

372 In the case of read with multiple alignments, a coefficient ω is introduced. When a

373 read in M has alignments with N different windows, ω is calculated using the

374 following formula:

$$\omega = U / \sum_{i=1}^{N} RC(U)$$

To ensure accurate estimation of genome abundance, we calculate it as the mean of

the n% most closely covered windows. After initial classifying of microbial genomes,

we extract their respective genome sequences and realign the reads to the new subset

reference genome sequence Finally, we recalculate the relative abundance by using

the most closely covered windows again.

Reconstruction of long DNA fragments

We developed a computational strategy to reconstruct long DNA fragments from

linked-read sequencing data. Initially LRTK extracts paired reads that share the same

barcode in the alignment file. The uniquely aligned paired-end reads are collected to

evaluate the distribution of insert sizes (with a mean of μ_{PE} and a standard deviation

of σ_{PE}). Alignments are removed if the distance between two reads in a pair (R1 and

R2) exceeds a certain threshold, that is,

$$Dis(\text{R1}, \text{R2}) > \mu_{PE} + 3 * \sigma_{PE}.$$

The remaining paired reads are used as seeds and extended to both directions to

connect with other seeds sharing the same barcode until no more eligible seeds can be

found within a specified distance. All of these co-barcoded reads are considered to be

derived from the same long DNA fragment and are collected as a read cloud.

Identify and phase genomic variants
397

LRTK supports multiple popular variant detection tools and adheres to best

practices for linked-read sequencing. For human genomic sequencing data, LRTK

provides FreeBayes[14], SAMtools[15] and GATK[16] to call SNVs and INDELs.

The available phasing tools include HapCUT2[20] and WhatsHap[21]. Having

obtained the phased SNVs, we then use hap-ibd[39] to detect pairwise

identity-by-descent segments across multiple samples. By default, large structural

variations (SVs) are identified and phased using Aquila[17]. However, Users have the

flexibility to select other tools such as LinkedSV[18] and VALOR2[19] for SV

analysis.

For metagenome sequencing data, LRTK offers three metagenome SNV callers:

FreeBayes[14], inStrain[27] and SAMtools[15]. The SNV phasing is performed on

high abundance species using WhatsHap[21] with the inferred ploidy. LRTK also

selects SNVs located on certain high abundance species and compares the SNV

profiles across multiple samples. Based on the allele frequency of SNVs, we used an

unsupervised clustering method to detect potential minor allele imbalance (MAI)

events for pairwise samples. In brief, one sample is chosen as the reference for all the

contigs. The minor allele frequency of heterozygous SNVs present in others samples

are then compared to the reference sample. We used the k-means clustering method to

separate the SNVs into distinct groups using the minor allele frequency matrix. The

number of clusters were determined by using the Calinski-Harabasz index. The

number of clusters may be used to determine the number of strains under the same

species.

Downstream analysis and HTML-based visualization

The human genome analysis report begins with generating the FASTQ quality

control statistics during the preprocessing step. For the barcode aware alignment step,

it presents the distribution of several key statistics about DNA library, including the

number of fragments per barcode, fragment length and read coverage per fragment. It

also includes information about the sequencing coverage and insert size. The variant

calling step summarizes the number of SNVs, small INDELs and large SVs and

illustrates their distributions.

Similarly, the metagenome analysis report firstly illustrates the QC results for

preprocessing, alignment and variant calling steps. Additionally, it includes an

optional report about the automatic analysis of multiple related samples. The report

shows the distribution of high abundant species across multiple samples, and uses a

principal component analysis (PCA) plot to visualize the divergence across them. The

report also depicts the distribution of SNVs of these high abundant species, and the

minor allele frequency distribution in pairwise samples.

Code Availability and Requirements

Source code is available at https://github.com/ericcombiolab/LRTK. LRTK can be

downloaded as a packaged conda environment (https://anaconda.org/bioconda/lrtk).

Project name: Linked Read ToolKits project

Project home page: https://github.com/ericcombiolab/LRTK

Operating system(s): Linux and macOS

Programming language: C and python

Other requirements: Conda, Python 3.6 or higher

License: MIT

RRID: SCR_023945

Data Availability

We curated two benchmarking datasets and three real datasets to evaluate the

performance of LRTK in processing linked-read sequencing data.

B1: The benchmarking dataset B1 contains the 10x Genomics, stLFR and TELL-Seq

sequencing data for ATCC MSA-1003 mock community. These datasets were

obtained from the NCBI with the following accession numbers: SRR12283286 for

10x Genomics, and PRJNA875547 for stLFR and TELL-Seq sequencing

technologies.

B2: The benchmarking dataset B2 contains the 10x Genomics, stLFR and TELL-Seq

sequencing data for human sample NA12878. The linked-read of for 10x Genomics

and stLFR were downloaded from GIAB while the raw TELL-Seq data was

downloaded with the accession number SRR10584152 (PRJNA591637).

D1: The first real metagenomic dataset (D1), consisting of longitudinal 10x Genomics

linked-read sequencing data, was downloaded from the NCBI under accession

number SRP323279. We used only a subset of samples containing the barcode

information in the read ID.

D2: The second real metagenomic dataset (D2), containing deep stLFR sequencing

data, was downloaded from the China National GeneBank (CNGB) under project

CNP0003432.

D3: We also downloaded the linked-read sequencing data for a family trio (NA24143,

NA24149 and NA24385) and used them as the real data set D3 (Table S3). The 10x

Genomics and stLFR sequencing data was downloaded from GIAB. For TELL-Seq

sequencing data, we only obtained the raw TELL-Seq data from NA24385 from SRA

database (PRJNA591637: including SRR10689414, SRR10689415, SRR10689416,

SRR10689417).

Abbreviations

475   stLFR: single-tube long fragment read

476   TELL-Seq: transposase enzyme linked long-read sequencing

477 SNV: single nucleotide variant

478 INDEL: small insertion and deletion

479 SV: structural variation

CRediT authorship contribution statement:

Chao Yang: Writing - original draft, and preparing figures and tables, preparing

source codes; **Zhenmiao Zhang:** preparing source codes; **Xuefeng Xie:**

Consolidating resources; **Yufen Huang:** Consolidating resources; **Herui Liao:**

preparing source codes; **Werner P Veldsman:** Revising - original draft, and

visualizations; **Jin Xiao:** Revising - original draft, and visualizations; **Kejing Yin:**

Supervision; **Xiaodong Fang:** Supervision; **Lu Zhang:** Project administer, Writing –

review & editing, Supervision, and funding acquisition.

Declaration of Competing Interest:

491 The authors declare that they have no known competing financial interests

Acknowledgments:

This research was partially supported by the open project of BGI-Shenzhen, Shenzhen

518000, China (BGIRSZ20220012), the Hong Kong Research Grant Council Early

Career Scheme (HKBU 22201419), HKBU Start-up Grant Tier 2

(RC-SGT2/19-20/SCI/007), HKBU IRCMS (No. IRCMS/19-20/D02), the

Guangdong Basic and Applied Basic Research Foundation (No. 2021A1515012226),

the Science Technology and Innovation Committee of Shenzhen Municipality, China

(SGDX20190919142801722) and Shenzhen Science and Technology Innovation

Commission (SZSTI) - Shenzhen Virtual University Park (SZVUP) Special Fund

Project (No. 2021Szvup135).

Additional Files

Figure S1. LRTK text file specification.

Figure S2. Ideogrammatic definitions of C_R, C_F, $N_{F/P}$, μ_{FL}, and $W\mu_{FL}$ metrics.

Figure S3. Demo reports for metagenomics sequencing.

Figure S4. Demo reports for human genome sequencing.

Table S1. Comparison of LRTK with other published linked-read pipelines.

Table S2. Bioinformatics tools included in LRTK.

Table S3. Linked-read sequencing data sources

References

1. Eisenstein M. Startups use short-read data to expand long-read sequencing market.

Nat Biotechnol. Nat Biotechnol; 2015; doi: 10.1038/NBT0515-433.

2. Wang O, Chin R, Cheng X, Yan Wu MK, Mao Q, Tang J, et al.. Efficient and

unique co-barcoding of second-generation sequencing reads from long DNA

molecules enabling cost effective and accurate sequencing, haplotyping, and de novo

assembly. *Genome Res*. Cold Spring Harbor Laboratory Press; 2019; doi:

10.1101/GR.245126.118.

3. Chen Z, Pham L, Wu TC, Mo G, Xia Y, Chan PL, et al.. Ultralow-input single-tube

linked-read library method enables short-read second-generation sequencing systems

to routinely generate highly accurate and economical long-range sequencing

information. *Genome Res*. Cold Spring Harbor Laboratory Press; 2020; doi:

10.1101/gr.260380.119.

4. Spies N, Weng Z, Bishara A, McDaniel J, Catoe D, Zook JM, et al.. Genome-wide

reconstruction of complex structural variants using read clouds. *Nat Methods 2017*

149. Nature Publishing Group; 2017; doi: 10.1038/nmeth.4366.

5. Siranosian BA, Brooks EF, Andermann T, Rezvani AR, Banaei N, Tang H, et al..

Rare transmission of commensal and pathogenic bacteria in the gut microbiome of

hospitalized adults. *Nat Commun 2022 131*. Nature Publishing Group; 2022; doi:

10.1038/s41467-022-28048-7.

6. Roodgar M, Good BH, Garud NR, Martis S, Avula M, Zhou W, et al.. Longitudinal

linked-read sequencing reveals ecological and evolutionary responses of a human gut

microbiome during antibiotic treatment. *Genome Res*. Cold Spring Harbor Laboratory

Press; 2021; doi: 10.1101/GR.265058.120/-/DC1.

7. Huang Y, Jiang P, Liang Z, Chen R, Yue Z, Xie X, et al.. Assembly and analytical

validation of a metagenomic reference catalog of human gut microbiota based on

co-barcoding sequencing. *Front Microbiol*. Frontiers; 2023; doi:

10.3389/FMICB.2023.1145315.

8. Davila Aleman FD. Microbiome and aging: A study of microbial evolution and

community structure across model organisms. Abtract and Metadata. 2022;

9. Tracanna V, Ossowicki A, Petrus MLC, Overduin S, Terlouw BR, Lund G, et al..

Dissecting Disease-Suppressive Rhizosphere Microbiomes by Functional Amplicon

Sequencing and 10× Metagenomics. *mSystems*. American Society for Microbiology;

2021; doi:

10.1128/MSYSTEMS.01116-20/SUPPL_FILE/MSYSTEMS.0116-20-S0001.PDF.

10. Zheng GXY, Lau BT, Schnall-Levin M, Jarosz M, Bell JM, Hindson CM, et al..

Haplotyping germline and cancer genomes with high-throughput linked-read

sequencing. *Nat Biotechnol 2016 343*. Nature Publishing Group; 2016; doi:

10.1038/nbt.3432.

11. A A, S N, M B, F S, M B, ZJ S, et al.. A unified catalog of 204,938 reference

genomes from the human gut microbiome. *Nat Biotechnol*. Nat Biotechnol; 2021; doi:

10.1038/S41587-020-0603-3.

12. Shajii A, Numanagić I, Whelan C, Berger B. Statistical Binning for Barcoded

Reads Improves Downstream Analyses. *Cell Syst*. Cell Press; 2018; doi:

10.1016/J.CELS.2018.07.005/ATTACHMENT/8C829484-1F22-47F4-A513-B90845

BD41D7/MMC1.PDF.

13. Zhang L, Zhou X, Weng Z, Sidow A. Assessment of human diploid genome

assembly with 10x Linked-Reads data. *Gigascience*. Gigascience; 2019; doi:

10.1093/GIGASCIENCE/GIZ141.

14. Garrison E, Marth G. Haplotype-based variant detection from short-read

sequencing. 2012; doi: 10.48550/arxiv.1207.3907.

15. Li H, Handsaker B, Wysoker A, Fennell T, Ruan J, Homer N, et al.. The Sequence

Alignment/Map format and SAMtools. *Bioinformatics*. Oxford Academic; 2009; doi:

10.1093/BIOINFORMATICS/BTP352.

16. McKenna A, Hanna M, Banks E, Sivachenko A, Cibulskis K, Kernytsky A, et al..

The Genome Analysis Toolkit: A MapReduce framework for analyzing

next-generation DNA sequencing data. *Genome Res*. Cold Spring Harbor Laboratory

Press; 2010; doi: 10.1101/GR.107524.110.

17. Zhou X, Zhang L, Weng Z, Dill DL, Sidow A. Aquila enables reference-assisted

diploid personal genome assembly and comprehensive variant detection based on

linked reads. *Nat Commun 2021 121*. Nature Publishing Group; 2021; doi:

10.1038/s41467-021-21395-x.

18. Fang L, Kao C, Gonzalez M V., Mafra FA, Pellegrino da Silva R, Li M, et al..

LinkedSV for detection of mosaic structural variants from linked-read exome and

genome sequencing data. *Nat Commun 2019 101*. Nature Publishing Group; 2019; doi:

10.1038/s41467-019-13397-7.

19. Karao□lano□lu F, Ricketts C, Ebren E, Rasekh ME, Hajirasouliha I, Alkan C.

VALOR2: characterization of large-scale structural variants using linked-reads.

Genome Biol. BioMed Central Ltd.; 2020; doi:

10.1186/S13059-020-01975-8/TABLES/2.

20. Edge P, Bafna V, Bansal V. HapCUT2: robust and accurate haplotype assembly

for diverse sequencing technologies. *Genome Res*. Genome Res; 2017; doi:

10.1101/GR.213462.116.

21. Patterson MD, Marschall T, Pisanti N, Van Iersel L, Stougie L, Klau GW, et al..

WhatsHap: Weighted Haplotype Assembly for Future-Generation Sequencing Reads.

https://home.liebertpub.com/cmb.   Mary Ann Liebert, Inc.   140 Huguenot Street,

3rd Floor New Rochelle, NY 10801 USA   ; 2015; doi: 10.1089/CMB.2014.0157.

22. Li H, Durbin R. Fast and accurate short read alignment with Burrows–Wheeler

transform. *Bioinformatics*. Oxford Academic; 2009; doi:

10.1093/BIOINFORMATICS/BTP324.

23. Zhang L, Fang X, Liao H, Zhang Z, Zhou X, Han L, et al.. A comprehensive

investigation of metagenome assembly by linked-read sequencing. *Microbiome*.

BioMed Central Ltd; 2020; doi: 10.1186/S40168-020-00929-3/FIGURES/4.

24. DH P, M C, C R, AJ M, PA C, P H. GTDB: an ongoing census of bacterial and

archaeal diversity through a phylogenetically consistent, rank normalized and

complete genome-based taxonomy. *Nucleic Acids Res*. Nucleic Acids Res; 2021; doi:

10.1093/NAR/GKAB776.

25. Shen W, Xiang H, Huang T, Tang H, Peng M, Cai D, et al.. KMCP: accurate

metagenomic profiling of both prokaryotic and viral populations by pseudo-mapping.

Bioinformatics. Oxford Academic; 2023; doi:

10.1093/BIOINFORMATICS/BTAC845.

26. Zhao C, Dimitrov B, Goldman M, Nayfach S, Pollard KS. MIDAS2:

Metagenomic Intra-species Diversity Analysis System. *Bioinformatics*. Oxford

Academic; 2023; doi: 10.1093/BIOINFORMATICS/BTAC713.

27. Olm MR, Crits-Christoph A, Bouma-Gregson K, Firek BA, Morowitz MJ,

Banfield JF. inStrain profiles population microdiversity from metagenomic data and

sensitively detects shared microbial strains. *Nat Biotechnol 2021 396*. Nature

Publishing Group; 2021; doi: 10.1038/s41587-020-00797-0.

28. A B, EL M, M K, AE P, Z W, A S, et al.. High-quality genome sequences of

uncultured microbes by assembly of read clouds. *Nat Biotechnol*. Nat Biotechnol;

2018; doi: 10.1038/NBT.4266.

29. Visendi P. De Novo Assembly of Linked Reads Using Supernova 2.0. *Methods*

Mol Biol. Humana Press Inc.; 2022; doi: 10.1007/978-1-0716-2067-0_12/COVER.

30. Zhang Z, Wang H, Yang C, Huang Y, Yue Z, Chen Y, et al.. Exploring

high-quality microbial genomes by assembly of linked-reads with high barcode

specificity using deep learning. *bioRxiv*. Cold Spring Harbor Laboratory; 2022; doi:

10.1101/2022.09.07.506963.

31. Chaisson MJP, Sanders AD, Zhao X, Malhotra A, Porubsky D, Rausch T, et al..

Multi-platform discovery of haplotype-resolved structural variation in human

genomes. *Nat Commun 2019 101*. Nature Publishing Group; 2019; doi:

10.1038/s41467-018-08148-z.

32. Zhang F, Christiansen L, Thomas J, Pokholok D, Jackson R, Morrell N, et al..

Haplotype phasing of whole human genomes using bead-based barcode partitioning in

a single tube. *Nat Biotechnol 2017 359*. Nature Publishing Group; 2017; doi:

10.1038/nbt.3897.

33. Meier JI, Salazar PA, Kučka M, Davies RW, Dréau A, Aldás I, et al.. Haplotype

tagging reveals parallel formation of hybrid races in two butterfly species. *Proc Natl*

Acad Sci U S A. National Academy of Sciences; 2021; doi:

10.1073/PNAS.2015005118/SUPPL_FILE/PNAS.2015005118.SD06.XLSX.

34. Redin D, Frick T, Aghelpasand H, Käller M, Borgström E, Olsen RA, et al.. High

throughput barcoding method for genome-scale phasing. *Sci Reports 2019 91*. Nature

Publishing Group; 2019; doi: 10.1038/s41598-019-54446-x.

35. Zheng W, Zhao S, Yin Y, Zhang H, Needham DM, Evans ED, et al..

High-throughput, single-microbe genomics with strain resolution, applied to a human

gut microbiome. *Science (80-)*. American Association for the Advancement of

Science; 2022; doi:

10.1126/SCIENCE.ABM1483/SUPPL_FILE/SCIENCE.ABM1483_MOVIES_S1_T

O_S10.ZIP.

36. Chen S, Zhou Y, Chen Y, Gu J. fastp: an ultra-fast all-in-one FASTQ

preprocessor. *Bioinformatics*. Oxford Academic; 2018; doi:

10.1093/BIOINFORMATICS/BTY560.

37. DD K, F L, E K, A T, R E, H A, et al.. MetaBAT 2: an adaptive binning algorithm

for robust and efficient genome reconstruction from metagenome assemblies. *PeerJ*.

PeerJ; 2019; doi: 10.7717/PEERJ.7359.

38. Schneider VA, Graves-Lindsay T, Howe K, Bouk N, Chen HC, Kitts PA, et al..

Evaluation of GRCh38 and de novo haploid genome assemblies demonstrates the

enduring quality of the reference assembly. *Genome Res*. Cold Spring Harbor

Laboratory Press; 2017; doi: 10.1101/GR.213611.116.

39. Zhou Y, Browning SR, Browning BL. A Fast and Simple Method for Detecting

Identity-by-Descent Segments in Large-Scale Data. *Am J Hum Genet*. Cell Press;

2020; doi: 10.1016/J.AJHG.2020.02.010.

Figures and Tables

Figure 1. Overview of LRTK. The LRTK workflow includes a metagenomic section

(left panel) and human genomic section (right panel). The metagenomic section

implements barcode correction, read cloud assembly, barcode-aware alignment, long

DNA fragment reconstruction, taxonomic classification and quantification, as well as

SNV detection and phasing. The human genomic section implements barcode

correction, barcode-aware alignment, long DNA fragment reconstruction, and

detection and phasing of SNVs, INDELs and SVs.

Figure 2. Quality metrics for different linked-read sequencing platforms. (A)

Quality metrics under metagenome sequencing. The left panel displays the number of

fragments per barcode for 10x Genomics, stLFR and INDEL in metagenomic

sequencing data, respectively. The middle panel shows the DNA length of

reconstructed fragments. The right panel shows the average read coverage per

fragment. **(B)** Quality metrics under human genome sequencing. The left panel shows

the number of fragments per barcode, while the middle panel shows the DNA length

of reconstructed fragments. The right panel shows the average read coverage per

fragment.

Figure 3. Comparison of linked-read based metagenomic quantification, SNV

identification and phasing. (A) Evaluation of tools to quantify taxonomic abundance

based on the linked-read metagenomic sequencing data. **(B)** Comparison of tools to

detect SNVs. **(C)** Dynamic changes of taxonomic abundance and allele frequency. **(D)**

SNV based strain phasing in pairwise samples.

Figure 4. Evaluation of linked-read based metagenomic assembly. (A) Evaluation

of assembly performance for Athena, Supernova and Pangaea using 10x Genomics,

stLFR and TELL-Seq sequencing. **(B)** Illustration of the two assembled circular

contigs. **(C)** The distribution of completeness and contamination for reconstructed

bins. **(D)** The number of contigs in each contig group. **(E)** The number of detected

tRNAs in each contig group.

Figure 5. Evaluation of linked-read based detection of variation in the human

genome. (A, B) Performance metrics on the detection of SNVs and INDELs using

FreeBayes, GATK and SAMtools for 10x Genomics, stLFR and TELL-Seq. **(C, D)**

The performance on phasing of small variants using HapCUT2 and WhatsHap for 10x

Genomics, stLFR and TELL-Seq. **(E)** Illustration of the improved performance on

IBD detection. **(F, G)** The performance on detection of large deletions **(F)** and

insertions **(G)** using Aquila, LinkedSV and LongRanger.

Supplementary Figure 1: LRTK text file specification. (A) An example of the

unified FASTQ format. Each read contains a barcode field "BX:Z:barcode" after the

read names. The lengths of barcodes are 16 bp, 30 bp and 18 bp for 10x Genomics

linked-read, stLFR and TELL-Seq, respectively. (**B**) An example of the BAM file

generated by LRTK. The barcode information is stored in the "BX:Z:barcode" field.

Supplementary Figure 2. Ideogrammatic definitions of C_R, C_F, $N_{F/P}$, μ_{FL}, and

Wμ_{FL} metrics. (**A**) C_R: Average depth of short reads per fragment. (**B**) C_F: Average

physical depth of the genome by long DNA fragments. (**C**) $N_{F/P}$: Number of fragments

per barcode. (**D**) Length-weighted average (μ_{FL}) and unweighted average (Wμ_{FL}) of

DNA fragment lengths.

Supplementary Figure 3. Demo reports for metagenomics sequencing. (**A**) Per

base sequencing quality scores along the reads. (**B**) Per Base GC content along the

reads. (**C**) The number of fragments per barcode. (**D**) Fragment length distribution.

(**E**). The abundance of the top 10 most abundant species. (**F**) The number of SNVs per

species. (**G**) A principal component analysis using sample data from different groups.

Supplementary Figure 4: Demo reports for human genome sequencing. (**A**) Per

base sequencing quality scores along the reads. (**B**) Per Base GC content along the

reads. (**C**) The number of fragments per barcode. (**D**) Fragment length distribution. (**E**)

Sequencing depth frequency. (**F**) The distribution of sequencing depth along a whole

genome. (**G**) The distribution of inferred insert sizes. (**H**) The distribution of detected

deletions. (**I**) The distribution of detected insertions.

Table S1: Comparison of LRTK with other published linked-read pipelines.

	Items	Long Ranger	LRTK

Input	10x Genomics	Y	Y
	stLFR	N	Y
	TELL-Seq	N	Y
Modules	Linked-read preprocessing	Y	Y
	metagenome quantification	N	Y
	metagenome SNV detection	N	Y
	metagenome phasing	N	Y
	metagenome assembly	N	Y
	metagenome downstream analysis	N	Y
	human genome alignment	Y	Y
	human genome SNV detection	Y	Y
	human genome SV detection	Y	Y
	human genome phasing	Y	Y
	human genome downstream analysis	N	Y

Table S2. Bioinformatics tools included in LRTK.

Categories	Tools
Linked read simulation	LRTK-SIM[23]
Read preprocessing	fastp[36]
Barcode mapping and correction	BWA[22]

Read-cloud metagenome assembly	Pangaea[30]
Barcode-aware read alignment	Modified EMA[12]
SNV detection	FreeBayes[14], GATK[16], inStrain[27], SAMtools[15]
Linked-read based SV detection	Aquila[17], LinkedSV[18], VALOR2[19],
Linked-read based phasing	HapCUT2[20], WhatsHap[21]

716 **Table S3. Linked-read sequencing data sources.**

Cohort	Sample	Sequencing Technologies	Data sources
B1	ATCC-MSA-1003	10x Genomics	SRR12283286
		stLFR	PRJNA875547
		TELL-Seq	PRJNA875547
D1	MPS_stool_lyme_10	10x Genomics	SRR14763277
	MPS_stool_lyme_8		SRR14763279
	MPS_stool_lyme_6		SRR14763281
	MPS_stool_lyme_5		SRR14763282
	MPS_stool_lyme_4		SRR14763283
	MPS_stool_lyme_3		SRR14763284
	MPS_stool_lyme_18		SRR14763286

	MPS_stool_lyme_17		SRR14763287
	MPS_stool_lyme_16		SRR14763288
	MPS_stool_lyme_15		SRR14763289
	MPS_stool_lyme_14		SRR14763290
	MPS_stool_lyme_13		SRR14763291
	MPS_stool_lyme_12		SRR14763292
	MPS_stool_lyme_11		SRR14763293
	MPS_stool_lyme_2		SRR14763294
	MPS_stool_lyme_1		SRR14763295
D2	S1	stLFR	CNP0003432
B2	NA12878	10x Genomics	https://ftp-trace.ncbi.nlm.nih.gov/giab/ftp/data/NA12878/10Xgenomics_ChromiumGenome_LongRanger2.0_06202016/NA12878.fastqs/
		stLFR	https://ftp-trace.ncbi.nlm.nih.gov/giab/ftp/data/NA12878/stLFR/
		TELL-Seq	https://www.ncbi.nlm.nih.gov/sra/SRX7264479
D3	NA24385	10x Genomics	https://ftp-trace.ncbi.nlm.nih.gov/giab/ftp/data/AshkenazimTrio/HG002_NA24385_son/10Xgenomics_ChromiumGenome/NA2

			4385.fastqs/
		stLFR	https://ftp-trace.ncbi.nlm.nih.gov/giab/ftp/ data/AshkenazimTrio/HG002_NA24385_s on/stLFR/
		TELL-Seq	https://www.ncbi.nlm.nih.gov/sra/SRX726 4481
	NA24143	10x Genomics	https://ftp-trace.ncbi.nlm.nih.gov/giab/ftp/ data/AshkenazimTrio/HG004_NA24143_ mother/10Xgenomics_ChromiumGenome/ NA24143.fastqs/
		stLFR	https://ftp-trace.ncbi.nlm.nih.gov/giab/ftp/ data/AshkenazimTrio/HG004_NA24143_ mother/stLFR/
		TELL-Seq	
	NA24149	10x Genomics	https://ftp-trace.ncbi.nlm.nih.gov/giab/ftp/ data/AshkenazimTrio/HG003_NA24149_f ather/10Xgenomics_ChromiumGenome/N A24149.fastqs/
		stLFR	https://ftp-trace.ncbi.nlm.nih.gov/giab/ftp/ data/AshkenazimTrio/HG003_NA24149_f ather/stLFR/

		TELL-Seq	