A comprehensive model of Drosophila epithelium reveals the role of embryo geometry and cell topology in mechanical responses

Mohamad Ibrahim Cheikh[1], Joel Tchoufag[2], Miriam Osterfield[1], Kevin Dean[3], Swayamdipta Bhaduri[1], Zhang Chuzhong[4], Kranthi Kiran Mandadapu[2], and Konstantin Doubrovinski[1]*

Abstract

In order to understand morphogenesis, it is necessary to know the material properties or forces shaping the living tissue. In spite of this need, very few *in vivo* measurements are currently available. Here, using the early Drosophila embryo as a model, we describe a novel cantilever-based technique which allows for the simultaneous quantification of applied force and tissue displacement in a living embryo. By analyzing data from a series of experiments in which embryonic epithelium is subjected to developmentally relevant perturbations, we conclude that the response to applied force is adiabatic and is dominated by elastic forces and geometric constraints, or system size effects. Crucially, computational modeling of the experimental data indicated that the apical surface of the epithelium must be softer than the basal surface, a result which we confirmed experimentally. Further, we used the combination of experimental data and comprehensive computational model to estimate the elastic modulus of the apical surface and set a lower bound on the elastic modulus of the basal surface. More generally, our investigations revealed important general features that we believe should be more widely addressed when quantitatively modeling tissue mechanics in any system. Specifically, different compartments of the same cell can have very different mechanical properties; when they do, they can contribute differently to different mechanical stimuli and cannot be merely averaged together. Additionally, tissue geometry can play a substantial role in mechanical response, and cannot be neglected.

Introduction

During development, many organs are shaped through epithelial morphogenesis, a process in which epithelial cell sheets actively deform to give rise to complex structures. The early *Drosophila* embryo has been an important system for studying epithelial morphogenesis (Blankenship et al., 2006, Kiehart et al., 2017, Martin et al., 2009), as it is readily amenable to genetic techniques, high-resolution imaging, and physical perturbations. Ventral furrow formation, an early morphogenetic event in which the mesoderm moves from the exterior to the interior of the fly embryo, has been particularly widely studied process which is understood in great genetic and molecular detail (Ko and Martin, 2020, Stathopoulos and Newcomb, 2020). The physical mechanisms by which the ventral furrow forms have also been widely examined,

[1] Department of Biophysics, University of Texas Southwestern Medical Center, Dallas, TX 75390-9050.

[2] Department of Chemical and Biomolecular Engineering, University of California, Berkeley, CA 94720, USA., Chemical Sciences Division, Lawrence Berkeley National Laboratory, Berkeley, CA 94720, USA.

[3] Department of Bioinformatics, University of Texas Southwestern Medical Center, Dallas, TX 75390-9050.

[4] Department of Material Science and Engineering, University of Texas at Arlington, Arlington, TX 76019-0031

* correspondence to: Konstantin.Doubrovinski@UTSouthwestern.edu

but these studies have failed to reach a consensus regarding what spatiotemporal patterns of
mechanical forces and material properties drive this physical transformation (Fierling et al.,
2022, Heer et al., 2017, Perez-Mockus et al., 2017, Polyakov et al., 2014, Rauzi et al., 2013). A
truly predictive mechanical model of ventral furrow formation would require an accurate
representation of the patterns of forces and the patterns of material properties in the embryo,
since these two factors combined determine the dynamics of tissue movement.

To constrain models of tissue morphogenesis enough to accurately describe the underlying
physics, it should suffice to know any two of these: the dynamics of tissue movement, the
pattern of forces, and the pattern of material properties. The dynamics of tissue movement can
often be easily ascertained from microscopy. Techniques for the measurement of forces in vivo
are still quite limited (Cost et al., 2015, Eder et al., 2017, Polacheck and Chen, 2016, Roca-
Cusachs et al., 2017), so an increasingly productive approach has been to develop techniques
for probing material properties of cells (Wu et al., 2018). However, these methods have several
shortcomings. Optical and magnetic tweezers (Bambardekar et al., 2015, Tanase et al., 2007)
typically generate forces in the piconewton range, such that the resulting displacements do not
exceed a few microns. Additionally, those forces are usually applied on a time-scale of seconds.
Hence, the force- and time-scales in these measurements tend to be well below the scales
characteristic of morphogenesis, which typically unfolds on a time-scale of tens of minutes or
hours and results in deformations on the order of tens to hundreds of microns. Since material
properties are in general expected to vary depending on the time- and force-scales involved,
such measurements may not be relevant for understanding the physical mechanisms underlying
morphogenesis. Bendable cantilevers and biological atomic force microscopes (AFM) allow for
applying much larger forces over larger times (Fernandez and Ott, 2008, Fischer-Friedrich et al.,
2014). However, these techniques are hard to use in living embryos since introducing a probe
into an embryo without significantly disrupting the tissue proves challenging. Recently, we and
one other lab introduced a measurement technique based on the use of ferrofluid droplets
(Doubrovinski et al., 2017, Serwane et al., 2017). This method allows probing tissue with forces
on the order of tens of nanonewtons, but requires a probe that is fairly large (10-20 microns;
several-fold larger than a typical cell), thus possibly locally damaging the tissue that is being
probed.

Previously, we and others used ferrofluid droplets to measure the viscosity of cytoplasm in the
Drosophila embryo, which we found to be approximately 1000 cP (Doubrovinski et al., 2017,
Selvaggi et al., 2018). We also demonstrated that the cell cortex is elastic, and we quantified the
timescale of elastic stress relaxation (Doubrovinski et al., 2017). However, we were not able to
measure the Young's (or elastic) modulus of the cortex. To accomplish this, and to address the
shortcomings of the currently available methods, we introduce here a novel measurement
technique based on soft bendable polymer-based cantilevers that may be introduced into an
embryo to probe tissue mechanics with high spatial precision. These measurements, combined
with computational modeling, reveal that response to applied force is dominated by elastic
forces and geometric constraints, and that viscous friction between the tissue and its
environment is largely irrelevant. Importantly, these combined approaches also allowed us to
estimate the elastic modulus of the apical surface of the epithelial cells, and to set a lower
bound on the elastic modulus of the apical surface.

Results

Flexible cantilevers as a probe for tissue properties

Progress towards establishing the mechanical properties of animal tissue is limited by both the
availability of measurements as well the development of quantitative models that can
realistically account for both the material properties and the geometry of cells. To tackle the first
challenge, we developed a novel technique which is inspired by previous measurements on
tissue culture cells where a bendable cantilever of glass was used as a force probe (Desprat et
al., 2005). In these experiments, the deflection of the cantilever is used to quantify the force
applied by the tip; in combination with the resulting tissue deformation, a force-displacement
relationship for the tissue can be established.

To probe the mechanics of individual embryonic cell edges, we needed to create a novel tool
that 1) can be inserted into a single embryonic cell, 2) is sufficiently compliant to appreciably
bend under the relevant nanonewton-range forces, and 3) is capable of being visualized within
the rather opaque embryonic interior. To meet these needs, we developed a technique for
manufacturing a probe consisting of a long stiff glass pipette with a soft, fluorescent polymer tip
that acts as a short flexible cantilever (Figure 1a). Briefly, a standard injection glass pipette is
used as a mold for making a PDMS (polydimethylsiloxane) cantilever. The tip of a glass pipette
is filled with an uncured mixture of polymer, crosslinker, and a green variant of BODIPY (boron-
dipyrromethene) dye, which enters by capillary action through an opening at the tip. After the
polymer is cured, the tip of the glass scaffold is etched away in a solution of hydrofluoric acid to
expose the soft PDMS core. This technique is described in further detail in the Methods section
and in Figure 1-figure supplement 1.

With this probe in hand, we began to study the mechanical properties of cellularization stage
Drosophila embryos. From fertilization through the earliest several cycles of mitosis, the
Drosophila embryo is a syncytium, i.e. a very large cell with multiple nuclei sharing common
cytoplasm. Subsequently, in the process of cellularization, membranes extend from the surface
of the embryo and protrude between the nuclei, such that the cytoplasm is for the first time
partitioned into individual cells (Campos-Ortega and Hartenstein, 1985). During cellularization,
every newly forming cell is in effect open on its basal side, such that the interior of that cell is
connected to the yolk compartment residing in the center of the embryo (see Figure 1b for a
schematic illustration). Drosophila embryos at this stage have become a key model for studying
epithelial mechanical properties (Bambardekar et al., 2015, D'Angelo et al., 2019, Doubrovinski
et al., 2017), as it forms a basis for understanding the molecular and physical changes that must
occur to drive the large-scale tissue morphogenesis that begins shortly afterward (Blankenship
et al., 2006, Kiehart et al., 2017, Martin et al., 2009).

To introduce our probe into a cellularization-stage embryo, we use a pulled glass pipette to cut a
slit in the embryo on the opposite surface from which we plan to take measurements (Figure
1b). Importantly, we found that when a fly embryo is cut along one side, the side that is not cut
continues to develop completely normally showing no noticeable defects. We insert the probe
through this cut, then through the basal hole of a cell on the far side of the embryo, so that the
flexible tip of the cantilever is positioned within a single cell. For consistency, we always make
the initial incision on the ventral side of the embryo and probe material properties of cells of the
dorsal side. Once the probe is inserted, we use a piezo-actuator mounted on the microscope
stage to control cantilever movement. As the cantilever is translated parallel to the cellular layer,
it pushes against the adjacent cell edge, thus exerting a pulling force on that cell (Video 1,
Figure 1b).

Each pulling experiment consists of three phases. First, during the loading phase, the base of
the cantilever is translated at a constant velocity of 0.5 microns/second for approximately 60
seconds. Next, during the holding phase, the cantilever is held in place for approximately 60
seconds. Finally, in the unloading (or relaxation) phase, the cantilever is rapidly retracted from
the interior of the cell, and the cellular layer is then allowed to freely relax. Through this
experiment, the bending of the cantilever and the deformation of the cellular layer are imaged
for subsequent quantification. For time frames from a typical pulling experiment, see (Figure 1c).

Cantilevers allow simultaneous quantification of applied force and tissue deformation

To quantitatively examine displacement information from this type of experiment, we plotted the
data in two distinct ways. First, we represented the imaging data from each experiment as a
kymograph, with the x axis indicating time, and the y axis displaying the position of the cell
membranes (as measured from the fluorescent signal intersecting a curve drawn through the
middle of the cellular layer). The kymograph for a representative pulling experiment is shown in
Figure 2a.

Additionally, we represent the imaging data from each experiment as a deformation profile. For
a given time point, we generate a curve showing the displacement of each membrane from its
initial position as a function of its initial position (Figure 2b). Plotting several such curves, each
representing a different time point of the experiment, together on one graph allows easy
visualization of how tissue displacement spreads over time as the tissue is pulled. The
deformation profiles for the loading and holding phases of a representative pulling experiment
are shown in Figures 2c and 2c'', respectively. For some analyses, it is also useful to generate
normalized deformation profiles, in which the displacement (or y) axis is linearly scaled so that
the maximal displacement for each time point equals 1 (Figure 2c'). Importantly, measurements
performed on different specimens are highly consistent (Figure 2-figure supplement 1).

One key advantage of the cantilever technique is that applied force can be calculated from
cantilever deflection, which itself can be measured directly from the imaging data. This can be
done because cantilever deflection is linearly proportional to the force being applied to it for the
range of deflections observed. By Newton's third law, this force is equal in magnitude to the
force the cantilever is exerting on the tissue.

To calculate the force, it is necessary to calibrate the probe. The force-deflection relation of
each cantilever can be readily calculated using two pieces of information: the geometry of the
individual cantilever, and the Young's (elastic) modulus of the PDMS material from which it is
made. To calculate the Young's modulus of PDMS, we used three complementary techniques:
(1) fabricating a macroscopic rod of PDMS to measure its deformation under its own weight
(Figure 3-figure supplement 1 a-b), (2) pulling the cantilever through a fluid of known viscosity to
measure the resulting deflection (Figure 3a-b), and (3) probing the cantilever with an AFM probe
(Figure 3-figure supplement 1 c-d). The three methods estimate the Young's modulus of the
PDMS comprising the cantilever to be 1.6 MPa, 1.2 MPa and 2 MPa respectively. The details of
these measurements, along with the procedure we used to combine this information with
individual cantilever geometry to calibrate each probe, are described in the Methods section.
Using this information, we calculated the force applied over the time course for five
representative experiments (Figure 3c). The average force measured at maximal tissue
displacement (at the end of the loading phase) was 11.1 +/- 1.2 nN, and fell to 5.0 +/- 0.45 nN
by the end of the holding phase.

Epithelial deformation during loading is nearly adiabatic

In order to correctly infer the various force contributions in a mechanical system, it is important
to know whether the dynamics are adiabatic or not. An adiabatic process is defined as one in
which no heat transfer takes place. Claiming that a process is adiabatic is equivalent to stating
that friction is negligible, or alternatively, that the system is at equilibrium at every time point.

During the holding phase, most of the cell edges remain in a constant position, although the
green cantilever trace and a few nearby cell edges move slightly upwards (Figures 2a, 2c'').
Since most motion ceases as soon as the cantilever stops moving, the tissue must have been
largely in mechanical equilibrium at the time the cantilever stopped moving; in other words, most
of the tissue was deforming adiabatically during the loading phase.

Further support for this conclusion comes from examining the loading phase more
quantitatively. In previous work, we analytically and computationally explored the behavior of
thin material sheets with a variety of mechanical properties (Doubrovinski et al., 2017). When
these sheets were pulled at a single point, similarly generated deformation profiles from different
time-points of the same experiment were invariant up to re-scaling the y- and the x-axis by the
factors t^{α} and t^{β} respectively (see Figure S4 of (Doubrovinski et al., 2017)), where the values
α and β are determined by the mechanical properties of the system. In particular β, should
exceed 0.5 if friction contributes significantly to the dynamics. In the pulling experiments
presented here, we find that the deformation profiles obtained from the loading phase (Figure
2c) can be collapsed on almost the same master curve by re-scaling or normalizing the y-axis
only; that is, $t^{\beta} = 1$, or equivalently $\beta = 0$ (Figure 2c'). This indicates that the tissue is deforming
without significant input from external friction, which is consistent with the tissue deforming
adiabatically (Figure 2d).

So far, we have demonstrated that the tissue is deforming largely adiabatically during the
loading phase. During ventral furrow formation, the leading edge of the ectoderm travels
towards the midline at a rate of approximately 0.1 microns per second (He et al., 2014). Since
this is slower than the deformation rate in our experiments, dissipative forces such as friction
must also be lower during ventral furrow formation. Therefore, we can conclude that tissue
deformation is also largely adiabatic during this morphogenetic process.

Epithelial deformation is dominated by elastic forces and boundary constraints

The time course of deformations and forces observed in our pulling experiments also reveal
additional key mechanical features of the cellularizing epithelium.

One important feature is that the tissue is significantly elastic. During the loading phase (in
which constant displacement is imposed), the applied force increases linearly with
displacement, rather than with the rate of displacement (Figure 3c). If viscous forces were
dominant then the force should be proportional to the rate of displacement, which is not the
case. During the unloading phase, after the cantilever has been withdrawn, the tissue relaxes
largely, though not entirely, back to its initial configuration (Figure 2a). These observations are
both clearly consistent with the tissue itself being either an elastic or viscoelastic material.

The arguments given in the previous section for adiabatic deformation also mean that elastic
forces dominate over friction and viscous shear forces in this system during the loading phase.

If friction and viscous shear forces contribute only in a minor way during loading, what is
primarily limiting tissue deformation in response to applied force? The observation that force on
the cantilever drops by only about half (not to zero) during the holding phase suggests that
boundary constraints may be important. To see why, consider a linear elastic spring which is
immersed in a highly viscous fluid, and which is free at both ends. In response to force applied
at one end, the trailing end will also move, though more slowly due to drag, and the spring will
stretch. If the leading end is then held in a constant position, the trailing end will eventually catch
up, the spring will eventually reach its resting length, and thus the spring will eventually cease
applying a backward force on the leading end. If, however, this spring is fixed in place at its
trailing end, a similar sequence of pulling then holding the free end will yield a different force
profile. The spring will stretch while the free end is being pulled, but when the free end is then
held fixed, the trailing end is unable to catch up. The spring should eventually reach a state of
uniform deformation, but it cannot reach its resting length, and so it will continue to exert a force
on whatever is holding the leading end in place. This analogy suggested to us that the reason
the force on the cantilever never approaches zero during the holding phase of our pulling
experiments is due to some type of boundary constraint. The nature of this "boundary
constraint" was not obvious to us at first, but will be explored in the computational studies below.

Computation model of the Drosophila embryo

With these mechanistic insights in mind, we wanted to build a computational model both to test
our preliminary conclusions, and to estimate the elastic modulus of the cellular layer. To
represent our experimental system computationally, we developed a 3-dimensional model
representing the entire embryo (Figure 4), in which geometries of all the relevant structures
were taken from literature (Mavrakis et al., 2008) and measurements (Figure 4b). The cells are
represented as open prisms with lateral and apical surfaces modeled as networks of elastic
springs (each with spring constant k); the basal surfaces are left open (Figure 4a''). The
cytoplasm filling the cell interiors and the yolk are modeled as a Newtonian fluid, with viscosity
set to the experimentally measured value of 1000 cP (Doubrovinski et al., 2017, Selvaggi et al.,
2018). The surface of the embryo is a rigid shell, with a no-slip condition imposed, representing
the vitelline membrane, and the perivitelline fluid between the vitelline membrane and the
cellular layer is approximated by a Newtonian fluid with the viscosity of water (~ 1cP) (Figure
4b). External force is applied to a single cell edge, representing the effect of the cantilever.

Although the elastic components as described above are the springs, there is no obvious
correspondence between individual springs and any particular cellular structure. In other words,
a spring constant derived from this model would not reflect the mechanical properties of any
particular cellular component. However, there is biological significance to the triangular network
of springs which comprise a single cell surface; it behaves like an elastic shell or sheet, and is a
good model for the biological cell surface (comprised of plasma membrane and its associated
cytoskeletal network). Previous work (Seung and Nelson, 1988) has shown that in an elastic
sheet modeled as a triangular network of springs, the elastic (or Young's) modulus of the sheet
(E) and the spring constant (k) obey the following relationship: $E = 2k/\sqrt{3}$. Therefore, elasticity
will be represented by either E or k in the following discussion, depending on the context. Note
that for this type of approximation, the Poisson's ratio is 1/3.

Assuming uniform mechanical properties fails to explain experimental data

During the unloading or relaxation phase, the computational model described above has only
one free parameter: the spring constant, k, of the individual springs (or equivalently, the Young's
modulus, E, of the cell surfaces). We could thus run the model with a range of values for k and
test which values, if any, fit the experimental data (Figure 5). To do this, we fixed a value for k
and imposed a rate of tissue deformation at a single edge which matched that imposed
experimentally during the loading and holding phases. We then removed the applied force and
allowed the model tissue to relax (Figure 5a). To quantify the relaxation rate, we calculated an
exponential decay rate τ from these data. Carrying out this parameter sweep, we found that a
value of k = 0.001 nN/μm (or equivalently E = 0.0012) resulted in a curve that matched the data
extremely well (Figures 5a,c Simulation 1).

Having found that a spring constant of 0.001 nN/μm allowed us to realistically model
experimental data from the unloading (or relaxation) phase of our experiments, we next wanted
to test whether our model could also accurately capture the loading (or pulling) phase. During
the loading phase, we had imposed a predetermined rate of displacement for a single edge, so
by design the displacement matches that seen in vivo. However, in the loading phase we have
an additional quantity that comes into play: the applied force needed to drive the tissue
deformation. The approach we used to determine the instantaneous force needed in our model
to generate the pre-determined displacement is described in the Appendix. For each value of k
examined in our parameter sweep, we determined the force required for the tissue deformation
and plotted this predicted force as function of time (Figure 5b). The predicted force increases
linearly during the loading phase, which agrees well with the experimentally observed linear
increase in force during loading (Figure 3c). However, for the value of k which best matched the
decay dynamics (k = 0.001 nN/μm, Simulation 1), the predicted maximal force at the end of the
loading phase was less than 0.2 nN (Figure 5b,c Simulation 1). This value is an order of
magnitude lower than the forces measured directly from the deflection of our calibrated
cantilevers at the end of either the loading (~11 nN) or holding (~5 nN) phase. Conversely, for
the value of k (0.050 nN/μm, Figure 5 Simulation 3) for which the predicted maximal force (3.4
nN) most closely resembled the experimental data, the decay dynamics were far too rapid, with
τ = 8.9 sec, compared to τ = 60 sec in the experimental data.

What is the reason for this discrepancy? Our predicted loading force was based on the
assumption that the dominant effects on tissue mechanics (as captured in our model) are the
same in the loading and unloading phase. Therefore, we began to consider ways in which this
assumption might not be true. We thus began a series of computational experiments using
simplified models to explore how specific features of the model affect loading and unloading.

Floppy and stiff networks contribute differently to loading and unloading dynamics

One feature we examined was the effect of network topology on the dynamics. Recent work has
explored the physical consequences of so-called "floppy" networks, in which the number of
degrees of freedom exceeds the number of constraints, versus "stiff" networks, in which
constraints exceed degrees of freedom (Broedersz and MacKintosh, 2014, Wyart et al., 2008).
For simplicity (and to reduce simulation time), we used a model tissue in which the epithelial
layer was replaced by a simple network of elastic springs, and viscous forces from the
cytoplasm and yolk were replaced by a constant drag force (see methods). We then explored
the different effects of stiff versus floppy networks by using either a triangular (stiff) or hexagonal
(floppy) network of springs.

During the initial loading phase, we imposed a fixed deformation rate at a chosen point, and
determined the instantaneous external force required to achieve this deformation. We
performed this simulation for models incorporating either triangular or hexagonal networks, and
also varied the spring constant k assigned to the springs or edges. For a given spring constant,
the force required to deform the triangular network was greater than the force required to
deform the hexagonal network by the same amount (Figure 6a). In spite of this quantitative
difference, these networks responded to pulling in a similar way qualitatively: in both cases, the
force needed for a given deformation increased as the elastic modulus increased (Figure 6a).

In the subsequent unloading phase, we removed the externally applied force and observed how
the tissue relaxed over time (Figure 6b). In the triangular cases, the tissue relaxed back to its
initial configuration more rapidly as k increased (Figure 6b,c). This agrees with the intuition that
tissue with higher elasticity should spring back more rapidly. In the hexagonal-mesh case,
however, the tissue relaxed back to its initial position *more slowly* as k increased (Figure 6b).
Furthermore, the extent of tissue relaxation was also lower (Figure 6b,d). These results indicate
that the response of hexagonal and floppy networks during unloading is qualitatively different.

A difference in apical and basal elasticity determines tissue dynamics

There is an obvious parallel between these types of networks and different compartments of the
cellularization-stage epithelia in our experiments. The apical surface appears most similar to a
stiff elastic sheet, while the lateral surfaces and basal edges form a semi-hexagonal, and
therefore floppy, network. Since the apical and basal-lateral compartments would therefore be
expected to contribute differently to the loading versus unloading phases of our experiments, we
hypothesized that our earlier mismatch of maximal forces calculated from the loading versus
unloading phase may be due to a difference in the elastic modulus of the apical and basal-
lateral compartments.

To test whether different compartments of the cellularization-stage epithelia exhibit different
elastic properties, we modified an experimental set-up we had used previously (Doubrovinski et
al., 2017). In those previous experiments, we injected a 20-30 micron diameter ferrofluid droplet
into the embryo, positioned it in the cellular layer, and used a magnet to apply force across the
basal-apical extent of the cell. In these previous experiments (reproduced in Figure 7a-a'), the
speed of deformation decreased as the droplet approached the magnet, which we attributed to
a build-up of elastic stress in the epithelium. In our new experiments, we used a smaller
(approximately 10 micron diameter) ferrofluid droplet, which we could then position entirely
inside the cell, allowing us to specifically apply force to a small region at the intersection of the
apical and lateral surfaces of the cell, without directly contacting the basal edges (Figure 7b). In
these experiments, the speed of deformation was constant or even increasing as the droplet
approached the magnet, demonstrating that elastic stresses in this case were very small
compared to the pulling force (Figure 7b'). This difference in dynamics demonstrates that the
apical and lateral portions of the cell are softer, i.e. have a lower elastic modulus, than the basal
edges.

We then returned to our full computational model of the embryo (Figure 4), this time assigning
different values of the spring constant k in different cellular compartments. To test the effect of
varying elasticity in the floppy cellular components, we did a series of simulations in which we
held k_{apical} fixed and assigned increasing values to $k_{lateral}$ and k_{basal} (Figure 7c-c''). Increasing
$k_{lateral}$ and k_{basal} 20-30 fold resulted in much higher values for maximal force F_{max} (going from 0.2

nN to nearly 7 nN), but resulted in very similar values for the decay constant τ (~ 50 sec). This

validated our hypothesis that increased elasticity within floppy structural components should

primarily affect mechanics during loading (characterized by F_{max}), with only minor effects on

unloading (characterized by τ). In contrast, when k_{basal} and $k_{lateral}$ were kept approximately

constant, but k_{apical} was increased about 6-fold, this resulted in a dramatic change of decay

constant τ, from 39 sec to 9 sec (Figure 7-figure supplement 1).

Notably, one of the parameter sets used in our simulations (K_{apical} = 0.007, $K_{lateral}$ = 0.126, K_{basal}

=6.825) resulted in a maximal force (7 nN) that fell within the 5 nN to 11 nN range of maximal

force measured directly from cantilever deflection in experiments. Furthermore, despite the

large values for basal/lateral elasticity (compared to k = 0.05 in Figure 5), the fit to relaxation

dynamics remained relatively good.

It is important to note that we expect that different distributions of elasticity among the floppy

portions of the cell would yield similar results. Since we currently do not have experimental tools

to measure, and thus computationally constrain, the ratio of lateral-to-basal elasticity, we cannot

at this point precisely determine those numbers independently. However, our computational and

experimental results combined do lead us to two firm conclusions. 1) The elastic modulus we

estimated from relaxation dynamics (E approximately = 0.001 to 0.01) provides a good estimate

specifically of apical elasticity. 2) Basal elasticity in this tissue is substantially higher than apical

elasticity.

Tissue geometry imposes effective boundary constraints on in vivo *dynamics*

By examining our computational model, which closely reproduces the dynamics seen in vivo, we

found ourselves able to answer a question that had puzzled us earlier. Why do tissue dynamics

appear to be subject to boundary effects if the embryo is an ellipsoid and, thus, the cell layer

appears not to have boundaries? One possibility is that some feature of the epithelium (for

example, the topology of the cell network) stabilizes the tissue structure in a way that cells some

distance from the cantilever would be immobile, forming a sort of pseudo-boundary. Plotting the

displacement of cells in our model reveals that this explanation is not true. Even at short pulling

times, cells throughout the model embryo move from their initial positions, even on the opposite

side of the embryo from the force application, and even at the distant anterior and posterior

poles (Figure 8a-a', Video 2). We next examined previously acquired experimental data

(Doubrovinski et al., 2017) to see if the same might be true in vivo. Indeed, when concentrated

force was applied to one side of the embryo using a ferrofluid droplet, cells on the opposite side

of the embryo clearly moved as well (Figure 8b-b', Video 3). Although cells appear to be moving

in a coherent direction (for example, counterclockwise clockwise in Figure 8b-b') along the

sagittal plane, the tissue is clearly not freely rotating, since the displacement drops off away

from the applied force. A consideration of embryo shape suggests two obvious reasons why it

does not rotate freely under applied force. Cells moving between the highly curved poles and

the flatter lateral regions would need to change shape and/or neighbor relationships, and there

may energetic barriers to this transition. In fact, our simulations reveal an upregulation of stress

near the poles (Figure 8c). Additionally, if cells cannot rearrange completely freely, an imaginary

ring composed of cells encircling the embryo crosswise must deform into a somewhat larger

ellipse under the described tissue motion (Figure 8d), which would be expected to result in

increased elastic tension among these cells. In summary, geometrical constraints preventing

free rotation of the tissue allow for the build-up of elastic stress throughout the tissue when force

is applied locally.

Discussion

In this work, we have introduced a novel measurement technique that enables the application of concentrated force to a single epithelial cell in a living developing embryo. Crucially, this technique allows for the simultaneous quantification of the force being applied and the resulting tissue deformation. We envisage that our method, being simple and cost effective, will find applications in other systems.

Here, we used this technique to induce tissue deformations of a comparable rate and magnitude to the deformations that occur during *Drosophila* ventral furrow formation. This allowed us to directly assess the tissue material properties relevant for that morphogenetic process. During the loading phase of our pulling experiments, we found that epithelial deformation is adiabatic and that mechanics are dominated by elastic forces and geometric constraints. Since deformations in our experiments were comparable to (and even slightly faster than) the endogenous tissue deformation during ventral furrow formation, these conclusions should apply to that process as well.

To extract a quantitative measurement of tissue elasticity from our experiments, we developed a computational model. Surprisingly, our data could not be reconciled to a model in which the tissue was uniformly elastic along the apical-basal axis. In contrast, our data could be fit well by a model in which apical surfaces are significantly softer than basal surfaces. Strikingly, experiments using small ferrofluid droplets also showed that apical surfaces are significantly softer than basal surfaces.

Using a simplified computational model, we demonstrated that the reason apical and basal structures contribute differently to force loading and unloading is because the apical structures are topologically stiff, while the basal (and lateral) structures are topologically floppy. It is important to emphasize that, although the basal-open structure of the *Drosophila* embryo is unusual, the general principles described here should be universal. Specifically, relaxation dynamics in general should be expected to primarily reveal elasticities of stiff (non-floppy) components. This would apply even in systems in which cells are closed. For example, material properties of the apical and basal surface of a more typical epithelial monolayer would be expected to be reflected in in-plane relaxation dynamics, since they are topologically stiff. Material properties of the lateral surfaces, in contrast, would comprise a minor contribution.

Another unexpected result from this work is that geometrical constraints (which could alternatively be called system-size effects because they depend on the system being "small enough") generate a significant force opposing tissue movement when force is applied locally within the *Drosophila* embryo. As a result, any deformation, however small, propagates through the tissue on a timescale of seconds. This effect was apparent in both our model and experimental data. Any model used to estimate the mechanical properties of the tissue must take this significant contribution to force balance into account. This was not realized in the previous related work on *Drosophila* embryo mechanics (Bambardekar et al., 2015, D'Angelo et al., 2019, Doubrovinski et al., 2017). Additionally, we envisage that similar physical effects may be equally relevant to experiments in other model systems such as zebrafish (Behrndt et al., 2012) and *C. elegans* (Mayer et al., 2010) and should thus be investigated.

It is of particular interest to compare our results with previous work on the system. In an important recent publication (D'Angelo et al., 2019), the authors performed magneto-rheology

on cellularization-stage *Drosophila* embryos using 5 µm magnetic beads that were placed
adjacent to the apical membrane. The authors carefully measured the response to a
consistently applied magnetic force and found an abrupt developmental change in mechanical
response, with tissue deformation becoming much greater beginning about 16 minutes before
the onset of gastrulation. Based on fitting these data to a computational model in which a 2D
viscoelastic sheet moving over a substrate represented the epithelium and vitelline membrane,
the authors proposed that a sudden softening of the epithelium and an abrupt increase in friction
with the vitelline membrane could account for their observations. Based on our work here, we
propose an alternative interpretation. We note that during the early stage of cellularization, cells
are short and the 5 µm apically-localized beads would also be expected to be in mechanical
contact with the very rigid basal side. At a later stage in cellularization, cells become taller and
the bead should only contact the apical and/or the lateral cellular domains, which we have
demonstrated are much softer. Furthermore, previous studies of cellularization dynamics are
consistent with the basal edge of the cells moving past the 5 µm magnetic beads at
approximately 16 minutes before gastrulation (Figard et al., 2013). We therefore propose that
differences in the apparent material properties reported in (D'Angelo et al., 2019) reflect
differences in the material properties of the cellular domains being probed, and not time-
dependent mechanical changes of the entire epithelial layer due to developmental progression.
Importantly, our proposal also explains the observation that colcemid treatment blocks the
apparent tissue softening (D'Angelo et al., 2019); microtubule depolymerization stops
cellularization, so treated cells would remain short (Royou et al., 2004).

In addition to qualitatively describing the relative mechanical contributions of different cell
biological structures to the early *Drosophila* embryo, this work also resulted in a quantitative
estimate for elasticity of the apical surface and a lower bound for elasticity of the basal domain.
Combined with previous measurements of cytoplasmic viscosity, these measurements provide
an essential set of physical parameters which are required for a truly predictive and quantitative
model of morphogenesis in this system.

For a more complete model, future work should address two issues. One is the time scale on
which elastic energy in the system is stored; in other words, how quickly the tissue completely
or partially "forgets" its initial shape, for example due to actin turnover. (Note that the data in
Figure 3c, where the force drops but then levels off during the holding phase, suggests that
some elastic stress persists on very long time scales.) We previously established a lower bound
for this rate (based on a combination of experiments and a highly simplified model)
(Doubrovinski et al., 2017), but we did not establish a narrow range or even an upper bound.
The other issue to address is the relative elasticity of lateral versus basal domains. Our
physically realistic model is too computationally intensive to expect to address this through
parameter sweeps (see the "Simplified model" section of Appendix for further discussion), so
this issue should be addressed experimentally.

Materials and Methods

Embryo collection and fly strains

All experiments used the membrane-Cherry fly line described in (Martin et al., 2010). The
fluorescent signal proved too faint for our purposes, so a membrane dye was used to visualize
membrane outlines instead (see below).

Embryos were collected using on grape juice agar (Genesee Scientific) plates with a smear of
yeast paste. To select embryos of a suitable stage, plates were covered in light halocarbon oil
(Halocarbon Oil 27, Sigma). Embryos with a distinctive faint halo in the periphery, indicative of
early cellularization, were transferred to small square mats of lab paper towel for further
manipulations. The embryos were dechorionated in bleach, then quickly rinsed 10-12 times in
distilled water. To attach the embryos to a slide, a thin streak of embryo glue (a saturated
solution of adhesive from double-sided Scotch tape dissolved in heptane) was placed across
the length of a coverslip and allowed to dry for 5-10 minutes. Dechorionated embryos were
picked up and placed on top of the glue streak using an eyelash. A total of 8-12 embryos were
chosen for each round of imaging. The embryos were then desiccated in a closed container with
Drierite (Fisher Scientific) for 22 minutes before further manipulations.

Microinjection of fluorescent dye

Needles used for dye microinjections were fabricated from borosilicate capillaries (B100-75-10,
Sutter Instruments) using a pipette puller (P-2000, Sutter Instruments). Pipettes were backfilled
with 25-fold diluted CellMask Deep Red Plasma Membrane stain (Thermo Fisher Scientific)
using a gel loading tip (Eppendorf). Pipettes were broken at the tip by gently nudging the
pointed end against an edge of a coverslip, under a drop of oil.

To inject dye, the tip of a pipette was carefully pushed against the vitelline membrane so as to
insert it into the perivitelline space without piercing the cellular layer. An Eppendorf injector
(FemtoJet 5247, Eppendorf) was used with the following settings: compensation pressure: 10
hPa, injection pressure: 220 hPa. Typically, the injection was performed using the "clean"
command such that maximal pressure was applied.

After injection, the embryos were cut along the side opposite to the site of injection for
subsequent cantilever insertion.

Fabrication of cantilevers

A glass pipette was pulled the same way as done when making micro-injection needles. The
pipette was then similarly fractured at the tip by gentle contact with a glass cover slip, but in air
with no added oil. To make the polymer filling for the glass needle, PDMS (Sylgard 184, Dow
Corning) was mixed with a stock solution of BODIPY (BODIPY 493/503, Thermo Fisher
Scientific; 1 mg per ml stock solution in anhydrous DMSO) in proportions 3:2 (by volume). The
mixture was placed in a dish of aluminium foil and left overnight at 80 °C to evaporate off
DMSO. Next, the PDMS-BODIPY mixture was mixed with PDMS crosslinker in proportions 10:1
by weight. This mixture cures within 48 hours if left at room temperature, but may be stored for
months at -20 °C without curing. A small droplet of PDMS-BODIPY-crosslinker mixture was
placed in the center of a weighting boat. A glass pipette is placed into the weighting boat so as
to immerse its (open) tip in the droplet, simultaneously leaning the other end of the pipette
against the edge of the weighting boat. The weighting boat is left at 80 °C for five hours allowing
PDMS to cure. Finally, the pipette is carefully lifted out from a (now cured) PDMS droplet. In this
way, the inner part of the pipette tip is filled with crosslinked fluorescent PDMS.

The PDMS-filled pipette was bevelled using a micropipette grinder (E-45, Narishige) for 20
seconds with the speed dial set to 7. This is needed to remove the very end of the tip since
otherwise the very tip of the cantilever will be too thin and will tend to curl on itself.

Finally, to expose the inner PDMS core, the outer layer of glass was etched away used Armour
Etch (Armour Glass Etching Cream, 2.8 Oz), a paste comprising a mixture of hydrofluoric acid
and fluorites. A spectrophotometer cuvette was filled with Armour Etch cream halfway, and a
layer of light silicone oil (Silicone oil for oil baths, Sigma) was added on top to prevent solvent
evaporation. The tip of the pipette was immersed into the etching paste and was left to etch for
3-5 minutes. To observe the pipette tip through a vertically mounted microscope, a retrofitted
MicroForge (MF-900) with a custom mount for the cuvette was used (Figure 1-figure
supplement 1d). This completely dissolved the exposed glass layer to expose the core of cured
PDMS. The pipette was then lifted out from the cuvette and gently washed with a solution of
Triton X-100 and saline (0.4% NaCl and 0.03% TX-100 in distilled water). Finally, the pipette is
bent 90 degrees in flame of a cigarette lighter to simplify its mounting in a pipette holder.

It is important to note that filling capillaries from the front, by capillary action, is absolutely critical
for generating cantilevers of reproducible properties. When microfabricating cantilevers using
pulled glass pipettes as a mold, one may try introducing PDMS into the pipette by backfilling (as
we in fact did initially). When microcantilevers are fabricated in this way, their Young's modulus
(measured by subjecting the probe to viscous drag) varied widely. To track the origin of this
undesired variability, we performed Focused Ion Beam (FIB) milling on our microfabricated
probes. In the course of milling, half of the cantilever beam was milled away along its length so
as to expose and examine the mid-cross-section of a sample using Scanning Electron
Microscopy. It was found that portions of the cantilever were in effect hollow, due to sub-micron-
sized bubbles trapped in the polymer (Figure 1-figure supplement 1a). We believe that bubbles
were formed due to the air trapped inside the capillary tip when it is being back-filled. In
contrast, when capillaries are filled from the front using capillary action, FIB milling reveals no
bubbles trapped within the polymer (Figure 1-figure supplement 1b), and measurements of the
Young's modulus are consistent.

Micromanipulation protocol and microscopy

The glass pipette with its PDMS cantilever tip was translated using a piezo actuator (PXY200SG
two-axis piezo actuator, Newport). The piezo was controlled with an amplifier (NPC3SG 3-
channel piezo amplifier, strain-gauge position control, Newport) interfaced with MATLAB. The
MATLAB code used to control the piezo is available for downloaded from
https://github.com/doubrovinskilab/cantilever_embryo_rheology. To mount the piezo-actuator on
a microscope stage, an optical breadboard was screwed to the stage using two custom
threaded holes. A three-axis stage (PT3 - 1" XYZ Translation Stage with Standard Micrometers,
Thorlabs) was mounted on the breadboard. The piezo actuator was attached to the three-axis
manual stage using two 45 degree angle brackets and a custom adopter mount.

Confocal laser-scanning microscopy was done using a Zeiss LSM 700 with excitation
wavelengths of 488 nm (green) and 639 nm (far red).

Computational Methods

The computational methods used in this paper (including cantilever calibration, models, and
numerical implementation) are described in detail in the Appendix.

559
560 **Acknowledgements**
561

We thank Jeffrey Woodruff for helpful discussions. We also thank Salena Fessehaye for
discussion of the manuscript.

We gratefully acknowledge the help of the Characterization Center for Materials and Biology at
UT Arlington, in particular Dr. Jiechao Jiang and Prof. Efstathios I. Meletis, for their help with
AFM characterization of the probe.

We thank the Nano3 facility at UCSD for their help with the cryo-EM aspects of the project.

We thank Saiana Khandarkhaeva, Natalia Dubrovinskaia and Leonid Dubrovinsky for their help
with the FIB modification of the commercial AFM probes.

The work was supported by the Robert A. Welch Foundation (grant I-1950-20180324) and the
NIH (grants 1R01GM134207 and 1R21HD105189).

577
References

BAMBARDEKAR, K., CLEMENT, R., BLANC, O., CHARDES, C. & LENNE, P. F. 2015. Direct laser manipulation
reveals the mechanics of cell contacts in vivo. *Proceedings of the National Academy of Sciences*
of the United States of America, 112**,** 1416-1421.
BEHRNDT, M., SALBREUX, G., CAMPINHO, P., HAUSCHILD, R., OSWALD, F., ROENSCH, J., GRILL, S. W. &
HEISENBERG, C. P. 2012. Forces Driving Epithelial Spreading in Zebrafish Gastrulation. *Science,*
338**,** 257-260.
BLANKENSHIP, J. T., BACKOVIC, S. T., SANNY, J. S., WEITZ, O. & ZALLEN, J. A. 2006. Multicellular rosette
formation links planar cell polarity to tissue morphogenesis. *Dev Cell,* 11**,** 459-70.
BROEDERSZ, C. P. & MACKINTOSH, F. C. 2014. Modeling semiflexible polymer networks. *Reviews of*
Modern Physics, 86**,** 995-1036.
CAMPOS-ORTEGA, J. A. & HARTENSTEIN, V. 1985. *The Embryonic Development of Drosophila*
melanogaster, Berlin, Springer.
COST, A. L., RINGER, P., CHROSTEK-GRASHOFF, A. & GRASHOFF, C. 2015. How to Measure Molecular
Forces in Cells: A Guide to Evaluating Genetically-Encoded FRET-Based Tension Sensors. *Cellular*
and Molecular Bioengineering, 8**,** 96-105.
D'ANGELO, A., DIERKES, K., CAROLIS, C., SALBREUX, G. & SOLON, J. 2019. In Vivo Force Application
Reveals a Fast Tissue Softening and External Friction Increase during Early Embryogenesis.
Current Biology, 29**,** 1564-+.
DESPRAT, N., RICHERT, A., SIMEON, J. & ASNACIOS, A. 2005. Creep function of a single living cell. *Biophys*
J, 88**,** 2224-33.
DOUBROVINSKI, K., SWAN, M., POLYAKOV, O. & WIESCHAUS, E. F. 2017. Measurement of cortical
elasticity in Drosophila melanogaster embryos using ferrofluids. *Proc Natl Acad Sci U S A,* 114**,**
1051-1056.
EDER, D., BASLER, K. & AEGERTER, C. M. 2017. Challenging FRET-based E-Cadherin force measurements
in Drosophila. *Scientific Reports,* 7.
FERNANDEZ, P. & OTT, A. 2008. Single cell mechanics: Stress stiffening and kinematic hardening. *Physical*
Review Letters, 100.
FIERLING, J., JOHN, A., DELORME, B., TORZYNSKI, A., BLANCHARD, G., LYE, C., MALANDAIN, G., SANSON,
B., ETIENNE, J., MARMOTTANT, P., QUILLIET, C., RAUZI, M. & POPKOVA, A. 2022. Embryo-scale
epithelial buckling forms a propagating furrow that initiates gastrulation. *Nature*
Communications, 13.
FIGARD, L., XU, H., GARCIA, H. G., GOLDING, I. & SOKAC, A. M. 2013. The plasma membrane flattens out
to fuel cell-surface growth during Drosophila cellularization. *Dev Cell,* 27**,** 648-55.
FISCHER-FRIEDRICH, E., HYMAN, A. A., JULICHER, F., MULLER, D. J. & HELENIUS, J. 2014. Quantification of
surface tension and internal pressure generated by single mitotic cells. *Sci Rep,* 4**,** 6213.
HE, B., DOUBROVINSKI, K., POLYAKOV, O. & WIESCHAUS, E. 2014. Apical constriction drives tissue-scale
hydrodynamic flow to mediate cell elongation. *Nature,* 508**,** 392-6.
HEER, N. C., MILLER, P. W., CHANET, S., STOOP, N., DUNKEL, J. & MARTIN, A. C. 2017. Actomyosin-based
tissue folding requires a multicellular myosin gradient. *Development,* 144**,** 1876-1886.
KIEHART, D. P., CRAWFORD, J. M., ARISTOTELOUS, A., VENAKIDES, S. & EDWARDS, G. S. 2017. Cell Sheet
Morphogenesis: Dorsal Closure in Drosophila melanogaster as a Model System. *Annu Rev Cell*
Dev Biol, 33**,** 169-202.
KO, C. S. & MARTIN, A. C. 2020. The cellular and molecular mechanisms that establish the mechanics of
Drosophila gastrulation. *Gastrulation: From Embryonic Pattern to Form,* 136**,** 141-165.

MARTIN, A. C., GELBART, M., FERNANDEZ-GONZALEZ, R., KASCHUBE, M. & WIESCHAUS, E. F. 2010.
Integration of contractile forces during tissue invagination. *J Cell Biol,* 188**,** 735-49.
MARTIN, A. C., KASCHUBE, M. & WIESCHAUS, E. F. 2009. Pulsed contractions of an actin-myosin network
drive apical constriction. *Nature,* 457**,** 495-9.
MAVRAKIS, M., RIKHY, R., LILLY, M. & LIPPINCOTT-SCHWARTZ, J. 2008. Fluorescence imaging techniques
for studying Drosophila embryo development. *Curr Protoc Cell Biol,* Chapter 4**,** Unit 4 18.
MAYER, M., DEPKEN, M., BOIS, J. S., JULICHER, F. & GRILL, S. W. 2010. Anisotropies in cortical tension
reveal the physical basis of polarizing cortical flows. *Nature,* 467**,** 617-U150.
PEREZ-MOCKUS, G., MAZOUNI, K., ROCA, V., CORRADI, G., CONTE, V. & SCHWEISGUTH, F. 2017. Spatial
regulation of contractility by Neuralized and Bearded during furrow invagination in Drosophila.
Nature Communications, 8.
POLACHECK, W. J. & CHEN, C. S. 2016. Measuring cell-generated forces: a guide to the available tools.
Nature Methods, 13**,** 415-423.
POLYAKOV, O., HE, B., SWAN, M., SHAEVITZ, J. W., KASCHUBE, M. & WIESCHAUS, E. 2014. Passive
Mechanical Forces Control Cell-Shape Change during Drosophila Ventral Furrow Formation.
Biophysical Journal, 107**,** 998-1010.
RAUZI, M., BREZAVSCEK, A. H., ZIHERL, P. & LEPTIN, M. 2013. Physical Models of Mesoderm Invagination
in Drosophila Embryo. *Biophysical Journal,* 105**,** 3-10.
ROCA-CUSACHS, P., CONTE, V. & TREPAT, X. 2017. Quantifying forces in cell biology. *Nature Cell Biology,*
19**,** 742-751.
ROYOU, A., FIELD, C., SISSON, J. C., SULLIVAN, W. & KARESS, R. 2004. Reassessing the role and dynamics
of nonmuscle myosin II during furrow formation in early Drosophila embryos. *Mol Biol Cell,* 15**,**
838-50.
SELVAGGI, L., PASAKARNIS, L., BRUNNER, D. & AEGERTER, C. M. 2018. Magnetic tweezers optimized to
exert high forces over extended distances from the magnet in multicellular systems. *Review of*
Scientific Instruments, 89.
SERWANE, F., MONGERA, A., ROWGHANIAN, P., KEALHOFER, D. A., LUCIO, A. A., HOCKENBERY, Z. M. &
CAMPAS, O. 2017. In vivo quantification of spatially varying mechanical properties in developing
tissues. *Nature Methods,* 14**,** 181-186.
SEUNG, H. S. & NELSON, D. R. 1988. Defects in Flexible Membranes with Crystalline Order. *Physical*
Review A, 38**,** 1005-1018.
STATHOPOULOS, A. & NEWCOMB, S. 2020. Setting up for gastrulation: D. melanogaster. *Gastrulation:*
From Embryonic Pattern to Form, 136**,** 3-32.
TANASE, M., BIAIS, N. & SHEETZ, M. 2007. Magnetic tweezers in cell biology. *Methods Cell Biol,* 83**,** 473-
93.
WU, P. H., AROUSH, D. R. B., ASNACIOS, A., CHEN, W. C., DOKUKIN, M. E., DOSS, B. L., DURAND-SMET, P.,
EKPENYONG, A., GUCK, J., GUZ, N. V., JANMEY, P. A., LEE, J. S. H., MOORE, N. M., OTT, A., POH,
Y. C., ROS, R., SANDER, M., SOKOLOV, I., STAUNTON, J. R., WANG, N., WHYTE, G. & WIRTZ, D.
2018. A comparison of methods to assess cell mechanical properties. *Nature Methods,* 15**,** 491-
+.
WYART, M., LIANG, H., KABLA, A. & MAHADEVAN, L. 2008. Elasticity of Floppy and Stiff Random
Networks. *Physical Review Letters,* 101.

 Appendix

Computational analysis of cantilever calibration

In order to obtain the Young's modulus of a cantilever, the cantilever was dragged at a constant
speed of 53 μm/s through Tween 20, a fluid whose density is density $\rho = 10^3 kg/m^3$ and
viscosity $\mu_f = 460$ cP (information provided by Sigma Aldrich). Using these data and the
measured dimensions of the cantilevers calibrated, the characteristic Reynolds number can be
estimated to $Re \sim 10^{-5}$, implying that inertial effects are negligible. The dynamics of the
cantilever is thus governed by the balance between viscous and elastic forces. Viscous drag
was calculated based on the slender body theory following (Cox, 1970), which is justified by the
small diameter-to-length ratio of the cantilever. In particular, the drag force per unit length reads:

$$F_v(x,t) = 2\pi\mu_f \frac{\partial h}{\partial t}\left(-\frac{2}{\ln(2R_a)/L)} - \frac{1}{\ln(2R_a/L)^2}\left[1 + 2\ln 2 + \ln\left(1 - \left(\frac{2x}{L}\right)^2\right) - \ln\left(\frac{R(x)}{R_a}\right)^2\right]\right) \quad ,$$

where $R(x) = R_{min} + x(R_{max} - R_{min})/L$ and $R_a = (R_{max} + R_{min})/2$ are the local and average
radii of the tapered cantilever, respectively, h is vertical deflection at a given position (x) and
time (t), and L is the length of the cantilever. On the other hand, since the cantilever length
remains constant, we use inextensible beam theory to obtain the expression for the force
density due to bending (Semler et al., 1994):

$$F_e(x,t) = -\frac{\partial^2}{\partial x^2}\left(EI(x)\frac{\partial^2 h}{\partial x^2}\frac{1}{[1+(\partial_x h)^2]^{3/2}}\right) \quad ,$$

where $I(x)$ is the area moment of inertia (at position x). To determine the value of the Young's
modulus E, we performed a parameter sweep varying the value of E. To do this, we solve the
equations following from the force balance (along the direction perpendicular to the axis of the
cantilever and assuming small displacement): $F_v + F_e = 0$. This was done using the open solver
FreeFEM (Hecht, 2012).

Numerical Model

Here we describe the numerical method used to simulate tissue deformation. Our approach is a
combination of the Immersed Boundary Method (IBM) (Cuvelier et al., 1986, Peskin, 1972,
Peskin and Printz, 1993) and the Finite Element Method (FEM) (Boffi et al., 2007). The chosen
methodology is motivated by the requirement to describe fluid-structure interactions when
treating the dynamics of embryonic cells that are elastic on the surface and filled with viscous
fluid in the interior (Doubrovinski et al., 2017).

The IBM approach involves considering an elastic solid immersed in a fluid as shown in Figure
4-figure supplement 1. In what follows, Ω_f denotes the region occupied by the fluid with
boundary Γ_f, while Γ_s is the interface of the fluid-immersed elastic solid. Initially, the fluid domain
Ω_f is discretized into finite elements (Figure 4-figure supplement 1 b-d). Within the IBM
approach, the geometry of this (Eulerian) grid remains fixed throughout a simulation. The
interface of the solid is meshed into triangles (whose edges will be modelled as linear springs,
see Figure 4-figure supplement 1 b). The nodes of the corresponding discretized (Lagrangian)
solid will be translated according to the relevant equations of motion which we turn to next.

Governing Equations

706
707   Describing the evolution of the solid interface (the cell surfaces) requires simulating the ambient
708   fluid, whose dynamics are given by the Stokes equations:

$$\nabla \cdot u_f = 0, \tag{1}$$

$$\mu \nabla^2 u_f - \nabla p_f = f_f. \tag{2}$$

Here μ is dynamic viscosity, while $u_f(x,t)$ and $p_f(x,t)$ are the velocity and the pressure fields,
respectively. Force density acting on the fluid is f_f. In our case, f_f derives entirely from forces
originating from the immersed structure Γ_s. We are justified in neglecting inertia since a typical
Reynolds number in our problem may be estimated to be on the order of Re = 10^{-8}. More
specifically, in a typical experiment, embryonic tissue is subjected to concentrated force as the
tissue is pulled by a cantilever. The typical speed U with which the cantilever is translated was
$0.005\ \mu m/ms$. The typical size (length) of an embryo L is $500\ \mu m$. The viscosity of the embryonic
cytoplasm was previously measured to be on the order of $1.0\ nN \cdot ms/\mu m^2$ (Doubrovinski et al.,
2017, Selvaggi et al., 2018). The density of the cytoplasm is on the order of that of water $\rho =$
$10^{-6}\ \mu g/\mu m^3$. Hence, we obtain Re $= \frac{\rho UL}{\mu} = 2.5 \times 10^{-8}$ as above.

To describe the surfaces of model cells, we assume that the cortex may be described as a thin
linearly elastic shell characterized by a (two-dimensional) Young's modulus and a Poisson's
ratio.

Finally, the dynamics of the solid are coupled to that of the fluid by imposing a no-slip boundary
condition, such that the velocity of the fluid matches that of the solid at the solid interface. The
net force density on the solid (f_s, which is defined below) is equated with the force on the fluid
(through the f_f term). Note that these are the key standard assumptions exploited in a typical
IBM implementation (Peskin, 1972, Peskin and Printz, 1993).

Numerical Implementation
728
729   For the fluid, we start by casting the governing equations for the fluid into their weak form:

$$\int_{\Omega_f} (\nabla \cdot u_f)\psi\, d\Omega_f = 0, \tag{3}$$

$$\mu\left(\int_{\Omega_f} \nabla u_f \cdot \nabla \phi\, d\Omega_f - \int_{\Gamma_f} \partial_n u_f \phi\, d\Gamma_f\right) - \left(\int_{\Omega_f} p_f \nabla \phi\, d\Omega_f - \int_{\Gamma_f} p_f \phi n\, d\Gamma_f\right) = \int_{\Omega_f} f_f \phi\, d\Omega_f. \tag{4}$$

where ψ and ϕ are test functions for the pressure and the velocity field, respectively (Boffi et. al.
2007, Boffi and Gastaldi 2003, Cuvelier 1986). The spatial domain is discretized into P1b-P1
finite elements which satisfy the inf-sup condition (Boffi and Gastaldi, 2003, Boffi et al., 2007,
Cuvelier et al., 1986). More specifically, we choose the cubic P1b element for the velocity test
function ϕ and the linear P1 element for the pressure test function ψ. Note that there are N
discrete nodes for the velocity field and M nodes for the pressure field in what follows.

Using the above discretization, the relevant fields are approximated as:

$$u_f = \sum_{j=1}^{N} \tilde{u}_{fj}\phi_j(x), \qquad p_k = \sum_{k=1}^{M} \tilde{p}_{fk}\psi_k(x). \tag{5}$$

737   In terms of the discretized variables the Stokes equations yield the Galerkin form:

$$\sum_{j}^{N} \tilde{u}_{fj} \int_{\Omega_f} (\nabla \cdot \phi_j)\psi_i \, d\Omega_f = 0, \qquad \forall i = 1, \dots, M \tag{6}$$

$$\mu \sum_{j}^{N} \tilde{u}_{fj} \left(\int_{\Omega_f} \nabla\phi_j \cdot \nabla\phi_i \, d\Omega_f - \int_{\Gamma_f} \partial_n\phi_j\phi_i d\Gamma_f \right) - \sum_{k}^{M} \tilde{p}_{fk} \left(\int_{\Omega_f} \psi_k \nabla\phi_i \, d\Omega_f - \int_{\Gamma_f} \psi_k\phi_i n d\Gamma_f \right) \tag{7}$$

$$= \int_{\Omega_f} f_f \phi_i \, d\Omega_f, \qquad \forall i = 1, \dots, N.$$

738   Equations (6) and (7) define a Finite Element (FE) system of 3N+M equations and 3N+M
739   unknowns (in the three-dimensional case). Assuming that the fluid boundary is Dirichlet, the
740   linear system will take the standard form

$$\begin{bmatrix} \mathbb{A} & \mathbb{B} \\ \mathbb{B}^{\mathrm{T}} & 0 \end{bmatrix} \begin{bmatrix} \tilde{u}_f \\ \tilde{p}_f \end{bmatrix} = \begin{bmatrix} \boldsymbol{F} \\ 0 \end{bmatrix} \tag{8}$$

741   where

$$\mathbb{A} = \mu \int_{\Omega_f} \nabla\phi_j \cdot \nabla\phi_i \, d\Omega_f, \tag{9}$$

$$\mathbb{B} = \int_{\Omega_f} \psi_k \nabla\phi_i \, d\Omega_f, \tag{10}$$

$$\boldsymbol{F} = \int_{\Omega_f} f_f \phi_i \, d\Omega_f. \tag{11}$$

The plasma membrane surfaces of the embryo can be thought of as a set of interconnected
linearly elastic two-dimensional plates. A particularly time-efficient implementation for
representing elastic plates involves discretizing each plate as a set of interconnected triangles
whose edges are linear springs (Seung and Nelson, 1988). More specifically, it may be shown
that in the limit of small deformation, the discrete triangulated mesh approximates a three-
dimensional linearly elastic material whose Youngs modulus is given by $E = 2k/\sqrt{3}$ (with k
being the spring constant of the mesh) and Poisson's ratio $\sigma = 1/3$ (Seung and Nelson, 1988).
Therefore, our immersed solid Γ_s, is modelled as a triangular mesh of springs. The no-slip
boundary condition at the fluid-solid interface amounts to moving the solid nodes with the local
velocity of the fluid:

$$\frac{dX_s}{dt} = u(X_s, t).$$

752 where X_s is a given point on the surface of the solid. Every spring comprising the discretized
753 solid contributes a force dipole at its two adjacent nodes:

$$F_s = k\Delta L \hat{s},$$

where F_s is the magnitude of the elastic force at a solid node, k is the spring constant, ΔL is the
difference of the corresponding instantaneous spring length and its rest length, while $\hat{s}$ is a unit
vector along the respective spring.

The coupling of solid and fluid dynamics is implemented within the IBM framework in a standard
way (Peskin, 1972, Peskin and Printz, 1993). In brief, force density of the solid is transferred to
the adjacent fluid nodes (the "spreading" step), contributing the f_f-term in the Equation (2).
Next, the velocity and pressure fields of the fluid are obtained from the system of linear
equations (Equation 8). Finally, in the "interpolation" step, the velocity of the fluid is interpolated
to the solid nodes and those nodes are then advanced through a time-step using a Euler-
forward scheme.

Validation of the numerical scheme
765
766 In this section, we validate our numerical solver by comparing simulation results to the solution
767 of an analytically tractable fluid-structure interaction problem. The problem, illustrated in Figure
768 4-figure supplement 2, involves stretching an elastic plate submerged in the middle of a viscous
769 fluid. The plate is fixed on the left, with the right end subjected to a constant force.

770 Neglecting inertia, we can write the equations governing the stretching of the plate as:

$$-2\mu \frac{\partial}{\partial y} u(x, y, t)|_{y=H} = E \frac{\partial^2 \delta(x, t)}{\partial x^2} \qquad \forall x \epsilon [0, L] \, \& \, t > 0, \qquad (12)$$

$$\delta(0, t) = 0 \qquad \forall t > 0, \qquad (13)$$

$$E \frac{\partial \delta(x, t)}{\partial x}\bigg|_{x=L} = F \qquad \forall t > 0, \qquad (14)$$

$$\frac{\partial \delta(x, t)}{\partial x}\bigg|_{t=0} = 0 \qquad \forall x \epsilon [0, L] \qquad (15)$$

$$\delta(x, 0) = 0 \qquad \forall x \epsilon [0, L] \qquad (16)$$

where $\delta(x, t)$ is the displacement of the plate, E the 2D-Youngs Modules of elasticity, μ the
viscosity of the fluid, and $\frac{\partial \delta(x,t)}{\partial t} = u(x, H, t)$ is the x-velocity component of the fluid. Equations
(13) and (14) are the boundary conditions for the problem, Equation (15) and (16) are the initial
conditions, and Equation (12) represents the balance of forces acting on the plate (equating
stress in the fluid to force density on the solid). The factor of 2 in Equation (12) comes from the
fact that viscous drag is present on both sides of the elastic plate.

To solve this system analytically, we assume the distance between the plate and fluid
boundaries is small in comparison to the length of the plate (i.e. $H \ll L$). In this case, the flow is

well approximated by the Poiseuille solution such that the y-velocity is identically zero, whereas
x-velocity $u(x, H, t)$ is linear in between the elastic plate and the horizontal walls of the fluid
domain. With these assumptions, Equation (12) may be recast as a diffusion problem

$$\eta \frac{\partial \delta(x,t)}{\partial t} = E \frac{\partial^2 \delta(x,t)}{\partial x^2} \qquad\qquad \forall x \epsilon [0, L] \ \& \ t > 0, \qquad (17)$$

782   where $\eta = 2\mu/H$ and $D = E/\eta$ is the diffusion coefficient. The solution of this problem is given
783   by the Fourier expansion

$$\delta(x,t) = \frac{f}{E}x + \frac{2f}{LE}\sum_{n=1}^{\infty}\frac{(-1)^n}{\beta_n^2}\exp\left(\frac{-\beta_n^2 E}{\eta}t\right)sin(\beta_n^2 x), \qquad \text{where } \beta_n = \frac{2n-1}{2L}\pi, \ n \epsilon \mathbb{N}_{>0} \qquad (18)$$

which may be considered a sum of the steady state solution and a transient. This expression,
which is the analytical solution to the problem, is shown as the red line in Figure 4-figure
supplement 2 b-c.

We also simulated the problem using our numerical scheme to obtain an approximate solution.
This simulated solution is shown as the blue line in Figure 4-figure supplement 2 b-c.

The analytical expression and numerical simulation are in very close agreement. Moreover, as
expected, the agreement systematically improves with decreasing thickness of the fluid layer
(data not shown). Taken together, simulation results in Figure 4-figure supplement 2 provide a
rigorous validation of the chosen numerical scheme.

Numerical simulations of experimental data
794

In this section we detail simulations used to interpret the pulling experiments probing the
rheology of embryonic epithelium. The geometry of a model *Drosophila* embryo is illustrated in
Figure 4. The computational domain is an ellipsoid whose dimensions approximately match the
well-documented dimensions of an embryo (Mavrakis et al., 2008). The outer solid boundary
represents the rigid vitelline membrane. Beneath the vitelline membrane is a thin (3 μm) gap of
perivitelline fluid. The rest of embryonic interior is described as a uniform Newtonian fluid with a
viscosity of 1000 cP, as previously measured (Doubrovinski et al., 2017, Selvaggi et al., 2018).
Cells are hexagonal prisms whose faces are elastic plates modelled by a set of inter-connected
springs (Figure 4a-a"). Dimensions of cells are based on experimental data.

A P1b-P1 FEM mesh was generated so as to discretize the whole computational domain
(including the model perivitelline space, cytoplasm and yolk). The mesh was further refined in
the region corresponding to the perivitelline fluid. Dirichelet (no-slip) condition was prescribed at
the outer domain boundary corresponding to the vitelline membrane.

To capture the cantilever pulling experiments, simulation is divided into three phases:

1. In the **loading phase**, one cell edge is subjected to force a pulling force for 60 seconds.
In our experiments, the imposed speed of the cell edge that was being pulled remained
approximately constant during the course of loading. To match the measurements, in our
simulations, the external pulling force was applied through a proportional control system
(P-controller) such that the externally applied force is given by

$$\vec{F}_{external}(t) = K_p \vec{e}(t) - \vec{F}_{internal}(t). \tag{20}$$

K_p was set to be 0.2 nN/μm; $\vec{F}_{internal}$ represents the sum of the internal forces on the
cell edge being pulled; the error value $\vec{e}(t)$ is the difference between the measured and
the simulated displacement of the cell edge that is being pulled. The external force (for
example Figure 7c') in our simulations was obtained from equation (20).

2. In the **holding phase**, the cell edge was held fixed for an additional time of 60 seconds.
3. In the **unloading phase**, the external pulling force was removed.

All simulation code is publicly available under
https://github.com/doubrovinskilab/cantilever_embryo_rheology.

Simplified model

To better understand simulation results obtained from the model in the previous section, we
considered the behaviour of floppy and stiff networks in the experimentally relevant geometry
(Figure 6). The full model is extremely computationally intensive; for example, simulation 4 in
Figure 7c' required 3 weeks of simulation time using 200 processor cores. Therefore, we used a
simplified model to allow us to more quickly explore parameter space. One simplification was
including 2D spring networks confined exclusively to the surface of the ellipsoid representing the
surface of the embryo (using a soft force of constraint). The more significant simplification in
terms of computational time was that we replaced explicitly modelled Stokes fluid with effective
drag.

As discussed below, the results from the simplified treatment cannot be quantitatively compared
to the results from the full treatment including hydrodynamic interactions. However, to only gain
qualitative insights into the behaviour of our system, it is admissible to replace Stokes fluid
dynamics with viscous drag, especially considering that we are mainly interested in the
behaviour of the solid and not the fluid. In our simulations (Figure 6), the networks were
confined exclusively to the surface of the ellipsoid representing the surface of the embryo using
a soft force of constraint. We checked that increasing the magnitude of the force of constraint by
an order of magnitude did not affect the dynamics. All other aspects of these simulations were
the same as in the case of the full hydrodynamic model.

For an example of how viscous drag can provide an inaccurate approximate for the physics
modelled by Stokes fluid dynamics, consider the following example. A thin two-dimensional disc
moving through a three-dimensional ambient Stokes fluid experiences force that is proportional
to the radius; in contrast, using standard assumptions for drag, the force would be proportional
to the area of the disc (Happel and Brenner, 1973). The use of drag in this example only
approximates the results obtained from explicitly modelling the fluid in the limit where the fluid
on either side of the disc is thin and bounded by another solid surface nearby (Happel and
Brenner, 1973). Since the embryo is filled with a fully 3D fluid, we therefore chose the more
physically correct model for our main simulations in spite of the limits this placed on our ability to
efficiently explore large regions of parameter space.

Appendix references:

BOFFI, D. & GASTALDI, L. 2003. A finite element approach for the immersed boundary method. *Computers & Structures,* 81**,** 491-501.

BOFFI, D., GASTALDI, L. & HELTAI, L. 2007. Numerical stability of the finite element immersed boundary method. *Mathematical Models & Methods in Applied Sciences,* 17**,** 1479-1505.

COX, R. J. 1970. The motion of long slender bodies in a viscous fluid Part 1. General theory. *Journal of Fluid Mechanics,* 44**,** 791-810.

CUVELIER, C., SEGAL, A. & STEENHOVEN, A. A. V. 1986. *Finite element methods and Navier-Stokes equations,* Dordrecht ; Lancaster, D. Reidel.

DOUBROVINSKI, K., SWAN, M., POLYAKOV, O. & WIESCHAUS, E. F. 2017. Measurement of cortical elasticity in Drosophila melanogaster embryos using ferrofluids. *Proc Natl Acad Sci U S A,* 114**,** 1051-1056.

HAPPEL, J. & BRENNER, H. 1973. *Low Reynolds number hydrodynamics. With special applications to particulate media,* Leiden,, Noordhoff International Publishing.

HECHT, F. 2012. New development in freefem++. *Journal of Numerical Mathematics,* 20**,** 251-265.

MAVRAKIS, M., RIKHY, R., LILLY, M. & LIPPINCOTT-SCHWARTZ, J. 2008. Fluorescence imaging techniques for studying Drosophila embryo development. *Curr Protoc Cell Biol,* Chapter 4**,** Unit 4 18.

PESKIN, C. S. 1972. Flow Patterns around Heart Valves - Numerical Method. *Journal of Computational Physics,* 10**,** 252-&.

PESKIN, C. S. & PRINTZ, B. F. 1993. Improved Volume Conservation in the Computation of Flows with Immersed Elastic Boundaries. *Journal of Computational Physics,* 105**,** 33-46.

SELVAGGI, L., PASAKARNIS, L., BRUNNER, D. & AEGERTER, C. M. 2018. Magnetic tweezers optimized to exert high forces over extended distances from the magnet in multicellular systems. *Review of Scientific Instruments,* 89.

SEMLER, C., LI, G. X. & PAIDOUSSIS, M. P. 1994. The Nonlinear Equations of Motion of Pipes Conveying Fluid. *Journal of Sound and Vibration,* 169**,** 577-599.

SEUNG, H. S. & NELSON, D. R. 1988. Defects in Flexible Membranes with Crystalline Order. *Physical Review A,* 38**,** 1005-1018.

(a)

(b)

Cantilever

Tissue cut here

(c)

t=0 s

t=33 s

t=50.2 s

t=175.8 s

Figure 1. Flexible cantilevers can be used as a probe for tissue properties.

a) SEM image of a typical cantilever. Scale bars are 5, 30 and 10 μm respectively from left to right. Left and right panels are zoomed-in views of boxed regions in the central panel. The junction where the glass pipette ends and the flexible, polymer-only portion begins is indicated with a red arrowhead. Technical details of cantilever microfabrication are shown in Figure 1-figure supplement 1.

b) Schematic of the pulling experiment. The embryo is cut along the ventral side and the cantilever is inserted through the cut. At the relevant developmental stage, cells have a "hole" on their basal side such that they are open to the interior. The flexible tip of the cantilever is inserted into a cell through the basal hole and translated so as to deform the cellular layer.

c) A sample measurement. To visualize cellular deformations arising from the applied force, cellular membranes are stained with a bright fluorescent dye (CellMask Deep Red) injected into the perivitelline space prior to measurement. The cantilever (green) is inserted into one of the cells (magenta) and is pulled upwards. The resulting deflection of the cantilever as well as the deformation of the cellular layer is readily visible and quantifiable.

Figure 2. Quantifying tissue deformation during cantilever-based experiments.

a) Left kymograph corresponds to a complete loading-unloading cycle. Right panel is a zoomed in portion of the same kymograph showing the loading phase only. Green streak reflects signal from the cantilever; magenta streaks reflect signal from the cell membranes. During the loading phase, when the cantilever base is being translated 0.5 microns per second, the green cantilever trace appears as a straight line, since the deflection of the soft cantilever tip is small relative to the translation of the base.

b) Schematic illustrating how a tissue deformation profile is constructed based on the data in a kymograph.

c) Tissue deformation profiles at several time points during the loading phase, extracted from the kymograph in a). Deformation profiles were highly reproducible between individual experiment, shown in Figure 2-figure supplement 1. c'). Same as c), with the curves linearly re-scaled along the y-axis so as to have the same maximum at zero. c''). Tissue deformation profile at several time points during the holding phase, also extracted from the kymograph in a).

d) Cartoon showing the expected outcomes of linearly re-scaling tissue deformation profiles for force loading under two mechanical regimes. In adiabatic regimes, curves from different time points should appear roughly the same when linearly re-scaled along the y axis only. In non-adiabatic regimes, linearly re-scaling along the y axis only is insufficient to generate similar curves.

Figure 3. Quantifying applied force during cantilever-based experiments.

a) Images from force calibration experiment. A cantilever was dragged through a fluid of known viscosity (Tween-20). Different snapshots show the profile of the cantilever at different times. Scalebar: 20 μm.

b) Quantification from force calibration experiment. Cantilever tip deflection as a function of time for five different cantilevers being dragged through Tween-20. The flexible tip quickly reaches a steady-state degree of deflection when dragged at a fixed velocity, and thus is under the influence of a constant force. The approach used to calculate the elastic modulus of the BODIPY-infused PDMS from these data is given in the Methods section. Additional approaches are described in Figure 3-figure supplement 1. The differences in magnitude of force deflection seen here are due to the different dimensions of each cantilever. Cantilevers used for in vivo experiments were individually calibrated taking the dimensions of the particular cantilever into account.

c) Force on cantilever as a function of time in five different *in vivo* pulling experiments. Force was calculated from cantilever deflection as described in methods. Only the loading (gray background) and holding (white background) phases of the experiments are shown, since the cantilever is no longer exerting force during the unloading phase. Maximal force at the end of loading was 11.1 +/- 1.2 nN; force at the end of the holding phase was 5.0 +/- 0.45 nN.

Figure 4

(a)

(a')

(a'')

(b)

511μm

184 μm

Force

Cytoplasm

y
x

cell height
20μm

cell height
10μm

(b')

(b'')

vitelline membrane

perivitelline space:
η=1cP, thickness: 3μm

cell membranes

cytoplasm:
η=1000cP

Figure 4. Three-dimensional computational model of the Drosophila embryo.

a-a") Illustrations of the cellular structures represented in the computational model.

a) An ellipsoid was tiled with a disordered hexagonal network to represent the cell boundaries on the surface of the embryo.

a') The cells themselves are three-dimensional prisms; a small portion of the surface, comprised of several cells, is shown here.

a") Cells are represented as open prisms with lateral (yellow) and apical (red) surfaces modeled as networks of elastic springs, each with spring constant k; the basal (blue) surface of each cell is left open.

b-b") Geometry of components of the simulated model embryo, not drawn to scale.

b) The long and short axis of the model embryo are 511 μm and 184 μm respectively. Cell height is assigned in a gradient, with 20 μm heights in the middle diminishing to 10 μm heights at the poles.

b') Cartoon cross-section of model embryo, and b") a portion of the cross-section. The vitelline membrane is 3 μm thick and filled with a fluid of 1 cP viscosity. The fluid in the interior of the embryo is assigned a viscosity of 1000 cP, agreeing with published measurements (Doubrovinski et al., 2017, Selvaggi et al., 2018). Details of numerical implementation and validation of the numerical method are described in the Methods, Figure 4-figure supplement 1, and Figure 4-figure supplement 2.

Figure 5. Results from parameter sweep with uniform elasticity explain relaxation dynamics or loading force but not both.

a) Parameter fitting for the spring constant k. The computational model was run with a range of values for the single free parameter k; see text. The externally applied force was removed to assess relaxation of the pulled edge during unloading. A constant value equal to the asympototic value was subtracted from each curve; when plotted on a log plot, the slope of resulting line gives the exponential decay rate, τ. b) Force versus time for the model in a) during the loading (gray background) and holding (light blue background) phases. Compare with Figure 3c, which shows the equivalent experimentally measured forces. c) Table of decay rates and maximal force for experiment and model parameter sweep. The value of k which best fits decay dynamics (0.001 nN/μm) drastically underestimates the loading force required.

Figure 6. Floppy and stiff networks contribute differently to loading and unloading dynamics.

a) Time evolution of force during the loading phase in simplified model tissues with triangular or hexagonal networks of springs. For both triangular (blue) and hexagonal (red) networks, the force required to impose a fixed displacement increases with increasing spring constant k.

b) Time evolution of force during the unloading phase in the same model tissues. Tissue relaxation is faster with increasing k in the triangular (blue) case, but slower with increasing k in the hexagonal (red) case.

c-d) Timepoints from the same model, showing the part of the network surrounding the node where force is applied (indicated by pale green circle). Images shown are from simulations where k = 0.035 nN/μm. The triangular network largely returns to its original configuration by the end of unloading (c"), but the hexagonal network remains significantly deformed at the same time point (d").

Figure 7. A difference in apical and basal elasticity determines tissue dynamics.

a-a') Ferrofluid pulling experiment with droplets that contact the basal edge. The data in this panel has been previously reported (Doubrovinski et al., 2017)
a) Time frames from a typical experiment. The droplet was pulled towards the magnet and then released after approximately 50 s. The red arrow indicates the position of the cellularization front (i.e. the basal side of the newly forming cells). The droplet is clearly in contact with the basal side at all time points.

a') Displacement of the ferrofluid droplet is plotted as a function of time for several experiments. For easiest comparison, the experiments chosen for this plot most closely match the total displacements in Figure 7b'. The speed of these droplets decreased as they approached the magnet, indicating a build-up of elastic stress in the epithelium.

b-b') Ferrofluid pulling experiment with smaller droplets that do not contact the basal edge.

b) Time frames from a typical experiment. The red arrow indicates the basal surface. In this sample, the droplet remains in the apical-lateral domain and does not contact the basal side at any time.

b') Ferrofluid droplet displacement measured in four different pulling experiments. In the gray/black curves, the droplet is never in contact with the basal side. These droplets do not slow down as they approach the magnet, indicating that elastic stress is not building up. The pink curve corresponds to a droplet that made mechanical contact with the basal side at the beginning of the experiment, but moved apically and lost contact with the basal surface at the time point indicate by the arrowhead. The acceleration that occurs at this time point is further evidence that the basal domain is more strongly elastic than the apical-lateral domain.

c-c'') Parameter fitting to assess mechanical contributions of lateral and basal structures. The computational model was run with a range of values for the parameters $k_{lateral}$ and k_{basal} while holding k_{apical} fixed. Compare with Figure 5 for fitting with a single spring constant k. Also see Figure 7-figure supplement 1 for an additional simulation varying k_{apical}. c) The externally applied force was removed to assess relaxation of the pulled edge during unloading. This data was used to calculate τ. c') Force versus time for the model in c) during the loading (gray background) and holding (light blue background) phases. c'') Table of decay rates and maximal force for experiment and model parameter sweep. Increased elasticity within lateral and basal structures affects mechanics during loading (characterized by F_{max}), with only minor effects on unloading (characterized by τ). Simulation 4 (blue curve) is our "best fit", approximately matching both the rate of unloading and the maximal force seen in experiments.

Figure 8

Figure 8. Tissue geometry constrains mechanical responses.

a) A thin section through the sagittal plane of the model from Figure 7c (simulation 4), shown at a single time point. The red, black, and green arrows indicate the curves used to generate the kymograph in a').

a') Kymograph corresponding to model data in a). Traces at the top of the kymograph are not strictly horizontal, showing that motion is detected even on the opposite side of the model embryo from the force application.

b) A time point from a ferrofluid droplet pulling experiment. Ferrofluid droplet indicated by red arrowhead. The red, black, and green arrows indicate the curves used to generate the kymograph in b').

b') Kymograph corresponding to experimental data in b). Traces at the top of the kymograph are not strictly horizontal, showing that motion is detected even on the opposite side of the embryo from the droplet-applied force.

c) Color plot indicating the distribution of stress across the model embryo from Figure 7c (simulation 4), averaged over the last 5 seconds of the pulling phase. Note that stress spreads across the whole tissue and is upregulated at the poles.

d) A schematic explaining how tissue geometry can affect the dynamics. An imaginary ellipsoid encircling the embryo is shown at two points: at the initial time point (green) and during force loading (red). Applying force at one point causes the imaginary ellipse to stretch, leading to an increase in elastic stress.

Figure 1 – figure supplement 1. Details of cantilever microfabrication.

a-b) Longitudinal sections through the tip of a polymer-filled glass pipette made using cryo Focused Ion Beam milling. The sample in a) was microfabricated by back-filling a glass pipette with PDMS-BODIPY mixture, whereas the sample in b) was filled through the front by capillary action. The sample in a) contains sub-micron-sized bubbles trapped in the polymer (red arrowheads). Feeding in the polymer through the tip eliminates bubbles, so this was the final protocol we adopted. c). Schematic of the setup used to microfabricate cantilevers. BODIPY-infused PDMS is loaded into a pulled glass pipette. The pipette is then immersed into a dilute solution of hydrofluoric acid (Armour etch, armourproducts.com) to etch away the glass from the 60-micron-long portion of the tip. d). A cuvette with the etching solution mounted on a retrofitted Microforge instrument. The pipette can be immersed into the etching solution using a micromanipulator and is simultaneously observed through a horizontally mounted microscope.

Figure 2 – figure supplement 1. Tissue deformation profiles are highly reproducible between measurements.

Tissue deformation curves from four independent experiments, shown at three different time-points in the loading phase. Analogous to the measurements in Figure 2c.

Figure 3 – figure supplement 1. Complementary measurements used to determine the Young's modulus of the microfabricated cantilevers.

a). A rod of fluorescent BODIPY-infused PDMS is suspended under its own weight. The Young's modulus is readily extracted from the shape of the deformed beam, its dimensions, and the density of PDMS (see Methods). b-b'). The rod from (a) was placed on a gel imager to illustrate its intense fluorescence under UV. c-d). AFM-measurements on microfabricated cantilevers. c) A custom AFM probe made from a commercially available AFM-cantilever using ion beam milling. The narrow 2 mm-wide tip at the end of the probe provides a defined point of force application, at the same time ensuring firm grip between the AFM probe and the sample. Scale bar = 10 μm. c'). AFM tip in contact with a micro-fabricated cantilever as seen through the optics of the AFM. Violet glare is the laser from the position sensitive detector of the AFM. d). Three representative AFM measurements from a single cantilever. Schematics at the top illustrate the location where the micro-fabricated cantilever contacted the custom AFM tip. The three measurements are the corresponding force-displacement curves with the loading part shown in red, and the unloading portion shown in blue. The curves are shifted along the x-axis for better visibility (since the reference point on the x-axis is inessential). The two rightmost curves are repetitions with the AFM tip contacting the cantilever at the same location. The Young's modulus for each cantilever examined (n= 6) was calculated as described in the Methods from the following information: the width of the cantilever; the distance from the AFM contact point to the junction with the glass scaffold, and the slope from the force-displacement curve.

Figure 4 – figure supplement 1. Schematic explaining terms used in the numerical model.

Our numerical approach combines the Immersed Boundary Method and the Finite Element Method, as described in the "Numerical Model" section of the Methods. a). Outer boundary of the computational domain Γ_f (dark blue line) encloses fluid domain Ω_f (light blue area); in our model, the computational domain is equivalent to the entire embryo. Boundary of the solid is denoted by Γ_s (red line); in our model, the solid boundaries correspond to the cellular surfaces. b). Same as a), illustrating discretization of the solid and the fluid domains. c,d) Two- and three- dimensional finite elements used in the simulations. Velocity (u) is defined on the nodes and on the center of mass, pressure (p) is defined only at the nodes.

Figure 4 – figure supplement 2. Test case to benchmark numerical method.

a). A schematic of the fluid-structure interaction test-problem showing a plate submerged in a fluid. The left end is fixed, the right end is subjected to a constant pulling force. The initial length of the plate is 5. The plate was placed in the center of a fluid domain having a length L of 8 and a height H of 0.05; the diagram shown is not to scale. The plate was discretized into a triangular mesh of linear springs whose spring constant was k= 0.13, fluid viscosity was set to μ =1. The top and bottom boundaries of the fluid domain are Dirichlet (no-slip), while the left and the right boundaries are Neumann zero gradient boundaries (i.e. open boundaries). The fluid domain was discretized using a structured finite element mesh of right triangles with sides Δx×Δy=0.005×0.0025. A constant pulling force of F=0.05 was applied to the right end of the plate. b),c) Time-evolution of a plate from a) shown on logarithmic (b) and linear (c) scales, plotting normalized displacement of the right-most point from initial position (with maximal displacement δ_{ss} set to 1). The numerical solution (blue) agrees well with the analytical solution (red), which is described in the Appendix. d) Iso-surfaces depicting the velocity magnitude profile around the plate, obtained from the numerical solution.

Figure 7 – figure supplement 1. The effects of apical elasticity on recoil.

The data here was generated in the same way as in Figure 7c-c''. Simulation 1 in this supplemental figure is the same as simulation 3 in the main Figure 7c-c''. Increasing k_{apical} about 6-fold (while holding k_{basal} and $k_{lateral}$ approximately constant), resulted in a substantial (approximately 4-fold) decrease in decay constant τ.